DeepPSC (protein structure camera): computer vision-based reconstruction of proteins backbone structure from alpha carbon trace as a case study

Xing Zhang[1], Junwen Luo[1], Yi Cai[1], Wei Zhu[1], Xiaofeng Yang[1]*, Hongmin Cai[2]*, and Zhanglin Lin[1]*

[1]School of Biology and Biological Engineering, [2]School of Computer Science and Engineering, South China University of Technology, 382 East Outer Loop Road, University Park, Guangzhou 510006, China;

* To whom correspondence should be addressed:

[1]School of Biology and Biological Engineering, South China University of Technology, 382 East Outer Loop Road, University Park, Guangzhou 510006, China; Tel: +86 (20) 3938-0680; Fax: +86 (20) 3938-0601; Email: zhanglinlin@scut.edu.cn (Z.L.); biyangxf@scut.edu.cn (X.Y.).

[2]School of Computer Science and Engineering, South China University of Technology, 382 East Outer Loop Road, University Park, Guangzhou 510006, China; Tel: +86 (20) 3938-2850; Fax: +86 (20) 3938-2850; Email: hmcai@scut.edu.cn (H.C.).

Abstract

Deep learning has been increasingly used in protein tertiary structure prediction, a major goal in life science. However, all the algorithms developed so far mostly use protein sequences as input, whereas the vast amount of protein tertiary structure information available in the Protein Data Bank (PDB) database remains largely unused, because of the inherent complexity of 3D data computation. In this study, we propose Protein Structure Camera (PSC) as an approach to convert protein structures into images. As a case study, we developed a deep learning method incorporating PSC (DeepPSC) to reconstruct protein backbone structures from alpha carbon traces. DeepPSC outperformed all the methods currently available for this task. This PSC approach provides a useful tool for protein structure representation, and for the application of deep learning in protein structure prediction and protein engineering.

1. Introduction

Protein structure determination is an ongoing issue and a major goal in life science that have captivated the attention of scientists for decades. Experimentally, protein structures have been mostly determined by X-ray diffraction crystallography (*1*), and to a less extent by nuclear magnetic resonance spectroscopy (*2*). In recent years, cryo-electron microscopy (EM) has also been increasingly used for structure determination (*3*). As an alternative to experimental methods, computational methods have also been developed for predicting protein structures from protein sequences (*4-8*), and deep learning has recently been applied to this prediction problem (*5-8*). In particular, DeepMind proposed a method called AlphaFold (*4*), which significantly outperformed all previous prediction methods. A number of algorithms that extract features from protein primary sequences for the purpose of protein function prediction and protein engineering, *e.g.*, UniREP (*9*) and TAPE (*10*), represent a further advancement in the field. Other applications of deep learning include protein fold recognition (*11-13*), and the predictions of protein secondary structures (*14*), protein functions (*15, 16*), and drug protein interactions (*17, 18*).

However, all the deep learning methods developed so far utilize only protein sequences as input, whereas the vast amount of protein tertiary structure information available in the rapidly expanding PDB database has not been sufficiently exploited in the calculations, due to its complexity. There are presently three common coarse approximation approaches for protein structure representation, namely, *k* nearest residues (*19*), distance or contact maps (*20*), and 3D grids (*21*), but all with limited

utility. Thus, we are interested in the following question: how to utilize protein structure information in deep learning?

It is well known that images can be efficiently processed by deep learning, and particularly in recent years, convolutional neural networks (CNN) have been successfully used in an array of computer vision tasks such as image classification (*22*), object detection (*23*) and face recognition (*23*). CNN can understand an object in the Euclidean space by extracting visual features from the corresponding image (*24, 25*). Fig. 1A shows a typical workflow of computer vision-based image classification. Here we propose a "Protein Structure Camera" (PSC) approach for converting protein tertiary structures into images for computer vision processing. In PSC, we used a 16 Å × 16 Å × 16 Å sliding cubic window centered on the alpha carbons of the amino acid residues (Cα) to dissect a protein structure (Fig. 1B). This was then turned into a group of compressed two dimensional 16 Å× 16 Å images with a -8 Å to 8 Å depth range, which were then fed to a CNN and implemented into a deep learning-based network architecture, or DeepPSC (Fig. 1C).

As a case study, we applied this DeepPSC for reconstructing protein backbone structures (containing atoms C, N, O, Cβ in addition to Cα) based on Cα traces, which is an important task for protein structure determination by experimental means and for protein structure prediction by computational approaches. Several protein structure refinement methods have been developed for the analysis of EM images to generate high-quality structure models, such as PHENIX (*26*) and Coot (*27*). Within these algorithms, the positions of the Cα, which are the atoms that can be located with the

highest accuracy, are determined first. Subsequently the backbone structure and then the full atom model are generated. Similarly, many computational algorithms predict the Cα trace as a preliminary reduced model. PHENIX ensembles PULCHRA (*28*) for backbone reconstruction, which uses a simple force field and steepest descent minimization. Coot ensembles CALPHA (*29, 30*), which is based on a library of backbone fragments compiled from experimentally determined structures. The widely used computational protein structure prediction platform I-TASSER (*31*) ensembles REMO (*32*), which directly reconstructs full-atom models (including the backbones) from a backbone isomer library. Similar library-based methods include BBQ (*33*), SABBAC (*34*), and PD2 (*35*), which often achieve better performance than PULCHRA or REMO. These three backbone structure reconstruction methods have also been applied for experimental structure determination (*36*), although they have not been incorporated in PHENIX or Coot. A significant limitation of the library-based methods, however, is that the wide range of conformations of protein backbones cannot be sufficiently represented by the limited number of fragments in the libraries.

In this work, we found that our DeepPSC approach outperformed all the previously reported methods for backbone reconstruction, including the benchmark PD2, and the ablation tests showed that the visual feature extracted from the protein structure images provided the main contribution for the improved performance.

2. Methods

2.1 Protein structure camera

The PSC concept is shown in Fig. 1B. Any given structural segment having $C\alpha_n$ as the center requires a preset orientation and scale. We defined the orientation from $C\alpha_n$ to $C\alpha_{n+1}$ as the X-axis. The Y-axis was then determined by the orientation from the X-axis to $C\alpha_{n+2}$, and the Z-axis was defined such as to build a left-hand Cartesian coordinate on the given local structural segment. We set the orientation directed from the positive to the negative regions of the Z-axis as the PSC view so that the orientations of different local structural segments could be normalized. For the penultimate $C\alpha$, the position on the Y-axis was determined by the orientation from the X-axis to $C\alpha_{n-1}$. Similarly, for the last $C\alpha$, we defined the orientation from the center to $C\alpha_{n-1}$ as the X-axis and the orientation from the X-axis to $C\alpha_{n-2}$ as the Y-axis. An enlarged view of Fig. 1B is given as supplementary Fig. S1.

Since 8 Å is generally regarded as the interaction distance cutoff between two residues (*8*), we used a sliding cubic window with a side length of 16 Å centered on the $C\alpha$, and a depth ranging from -8 Å to 8 Å was applied to the PSC view. Each PSC view was then encoded as an image with five channels, representing the Z-axis depth, the relative protein position, and three key amino acid properties including hydrophobicity (*37*), bulkiness (*38*) and flexibility (*39*), respectively. The resolution of the image is 128 × 128 pixels. In the image, each $C\alpha$ was first encoded as a pixel, and a straight line was used to connect adjacent $C\alpha$ pixels. The values of the properties along the straight line

were interpolated from the two Cα pixel values. A given protein Cα trace was thus converted into a group of local structural images.

2.2 Protein backbone structure representation

In this study, we represented the structure of the protein backbone as peptide plane torsions, as reported in a previous study (*40*). In other words, we applied a constraint that assumed $C\alpha_n$, C_n, O_n, N_n, $C\alpha_{n+1}$ forming a standard peptide plane (*trans* or *cis*). Within a given n^{th} trans peptide plane, as shown in Fig. 2A, the locations of the atoms C_n, O_n, N_n on the plane can be determined with a group of fixed lengths. For example, since the lengths of $C\alpha_n$-PC_n and PC_n-C_n are fixed, we could locate C_n on the plane. Next, as shown in Fig. 2B, we used the $C\alpha_{n+1}$-$C\alpha_{n+2}$ axis as a reference orientation to determine the torsion angles for each n^{th} peptide plane, *i.e.*, the torsion from $C\alpha_n$-$C\alpha_{n+2}$ to C_n (TC_n), and that from $C\alpha_n$-$C\alpha_{n+2}$ to N_n (TN_n), where TN_n is approximately 180 degrees larger than TC_n. The locations of $C\alpha_n$, C_n, O_n, N_n, $C\alpha_{n+1}$ were determined from the combination of all this information. In the case of cis peptides, the fixed lengths PC_n, PN_n, and PO_n are different from those of trans peptides, and TN_n and TC_n have similar values. In all cases, the value of TO_n is very close to that of TC_n, therefore TC_n was used as an approximation of TO_n in all calculations. TC_n and TN_n were encoded in the form of sine and cosine in the final representations. Note that in this study we denoted the atom N in the n^{th} peptide as N_n, while it is actually the $(n+1)^{th}$ atom N of the protein backbone.

Since the residues in proteins are L-amino acids, the coordinates of Cβ can be

determined when the locations of N, Cα, and C of a residue are known. Fig. 2C shows the rebuilding process used in this work. We first set the position of the projection of Cβ (Cβ') along the direction of the bisector of the angle C-Cα-N, with a fixed bond length between Cα and Cβ'. By rotating Cβ' with the fixed angle TCβ, the location of Cβ could be determined. Without constraints from the peptide plane, the first N atom and the last C and O atoms of a protein backbone are usually highly flexible, therefore our method could not predict the positions of these atoms.

2.3 Performance criteria

In this study the performance of various methods was evaluated on the basis of three criteria, *e.g.*, root mean square deviation (RMSD) (*41*), global distance test (GDT) (*42*), and Ramachandran (RAMA) outliers (*43*). RMSD is one of the most used criteria to measure the similarity between two structures (*41*), and is calculated as follows:

$$RMSD = \sqrt{\frac{\sum_{i=1}^{N} d_i}{N}} \tag{1}$$

where d_i is the coordinate deviation between atom i in two structures, and N is the total number of atoms. Considering that RMSD usually increases as the number of atoms of a protein increases (*44*), this value is usually normalized as $RMSD_{100}$, which describes the same deviation in 100 atoms (*45*), and is calculated as follows:

$$RMSD_{100} = \frac{RMSD}{1 + \ln\sqrt{\frac{N}{100}}} \tag{2}$$

where N is the number of atoms.

RMSD is, however, strongly affected by the parts in the structures that deviate the

most, therefore it often fails to represent the deviations of most of the atoms. Aimed at alleviating this problem, a community-wide experiment called CASP (critical assessment of techniques for Protein Structure Prediction) (*42*) have been using a different indicator, the Global Distance Test (GDT), as their main assessment method for ranking protein structure prediction methods. GDT scores are calculated as the percentage of atoms that have distance deviations smaller than the preset distance cutoffs. Cutoffs for GDT in CASP is usually set to 1, 2, 4, and 8 Å. In this study, the cutoff was set to 0.2 Å, and the GDT was labeled as GDT_P0.2.

The Ramachandran Plot is a statistical reference distribution of the combination of the backbone dihedral angles in proteins (*43*). In a Ramachandran Plot, one can classify residues in a given protein backbone structure as 'core', 'allowed', and 'outliers'. The percentage of outliers (RAMA outliers) is used to assess protein backbone structure uncertainty.

3. Results and Discussion

3.1 Deep neural network architecture

As shown in Fig. 3, the deep neural network implemented in DeepPSC takes local structure images as the input, and calculate the peptide plane torsions as the output. We first adopted ResNet50 (*46*), the most used convolutional neural network for computer vision processing, to extract visual features from the images, which are labelled as "local structural features". Then, we used a bidirectional long short-term memory

module (Bi-LSTM) (*47, 48*), the most used recurrent neural network module for sequence modelling, to sequentially pass information between the extracted local structural features. The outputs of this module were expected to mainly represent the local structures but they also contain sequential context information, and are labeled as "globalized local structural features". Afterward, considering that a single peptide plane is constructed by two adjacent residues, we paired every globalized local structural feature with the next one in the amino acid sequence as the "peptide plane feature". Finally, we used a multilayer perceptron (MLP) (*49*), a typical neural network module, to predict peptide plane torsions from the peptide plane features.

To compare our DeepPSC method with previously reported protein structure representation methods, we additionally built two baseline methods. In the first baseline, we used the k nearest residues method (*19*) to represent the Cα trace, and to encode the network input. To maintain the input information as close to that of our method as possible, we enriched the representation by adding relative protein positions and residue properties. For this baseline, an MLP module was used instead of ResNet 50, to extract local structural features for the input format, since the latter cannot process this baseline input (*19*). For the second baseline, protein structures were represented as distance maps and processed with a CNN, as previously reported, without any modifications (*20*).

3.2 Training and validation

We selected a subgroup from the protein structures reported in the PDB, to build a

tertiary structure dataset. A PDB entry was not included in this subgroup if: (i) the structure was not determined by X-ray crystallography; (ii) the entry has a number of residues fewer than 15 or higher than 800; (iii) the entry has missing atoms in the backbone or unnatural residues; (iv) the entry has sequence identity higher than 40% with another entry included in the subgroup (*35*). This resulted in the construction of a non-redundant dataset containing 10,302 protein structures.

We used 10-fold cross validation in training our models. The whole dataset was randomly and equally separated into ten sub-datasets. We routinely used one sub-dataset as the validation set and all the other nine sub-datasets as the model training sets. All the models were trained for 30 epochs using mean square error (MSE) as the loss function and the Adam optimizer (*50*). The learning rate was set to 0.0003 for the first 3 epochs, and then was adjusted according to the cosine-annealing schedule (*51*) in the following epochs. The trained models were validated with the corresponding validation set after every epoch. The curves of validation loss showed that all the models of DeepPSC and baseline 1 steadily converged at the 30^{th} epoch, while the models of baseline 2 showed poor fitting (supplementary Fig. S2).

The performance of our method was then evaluated with the test set of structures provided by PD2 (Table 1). The original PD2 set contained 28 high-quality and experimentally determined structures. Seven of them were excluded in our test set, because they contained either unnatural residues or missing atoms in the backbones, and thus our final test set contained 21 structures. We performed the 10-fold cross validation process on the three network architectures (DeepPSC, and the two baselines),

and obtained 10 models for each architecture, for a total of 30 models. Next, we applied each of these models to the test set and obtained the predicted torsion angles as outputs. Subsequently, for each architecture, we took the average of the outputs of the 10 cross validation models as the "ensemble model". Then the outputs of the ten models and that of the ensemble model were used to rebuild the backbone structures together with the corresponding Cα traces, and these rebuilt models were evaluated with the three performance criteria, $RMSD_{100}$, GDT_P0.2, and RAMA outliers. The average performance of the ten models for each architecture was calculated and shown as the "single model" performance, with the standard deviation of the single model performance indicating the robustness of the network architecture. Finally, we compared the performance of these architectures to that of PD2, BBQ, SABBAC and PULCHRA (Table 1).

3.3 Performance results

Generally, protein structures with resolution smaller than 2.0 Å are regarded as high-quality structures (*35*). According to the official statistics of PDB, up to July 27, 2020, the median resolution of X-ray crystallography structures in the database is 2.03 Å. The average error on atomic coordinates is resolution-dependent: a typical 2.0 Å crystallographic model has a coordinate error lower than 0.2 Å (*52*). Therefore, we considered 0.2 Å as the benchmark in our performance evaluation. Accordingly, we set the GDT cutoff at 0.2 Å to calculate the percentage of atoms that can be regarded as acceptable in a high-quality structure.

Based on the mean $RMSD_{100}$, and the GDT and RAMA outliers percentages as shown in Table 1, the backbone structures predicted by the ensemble model obtained with DeepPSC clearly outperformed those predicted by the baseline methods as well as the various traditional methods (PD2, BBQ, SABBAC and PULCHRA), in all three criteria. In particular, the performance of baseline 1, which was devoid of the image features of DeepPSC, suggested that the visual features extracted in DeepPSC were the main factor for its improved performance. By comparing the results for the Rebuilt model (directly from the PDB) and the ensemble model of DeepPSC, it could be deduced that the deviations observed in DeepPSC consisted of two elements: (i) the first was represented by the deviations introduced during the rebuilding process per se, which were the deviations between the ideal peptide plane conformations and the experimentally determined peptide plane conformations; (ii) the second is represented by the deviations induced by the model fitting in DeepPSC. Therefore, future developments should focus on devising an alternative strategy in lieu of the peptide plane assumption.

The distributions of the atomic coordinate deviations were also used to calculate the GDT_P0.2 scores of DeepPSC, PD2, PULCHRA and the two baselines (Fig. 4), which clearly show that the backbones reconstructed by DeepPSC were more accurate than those obtained with PD2, PULCHRA and the two baselines. Lastly, the Ramachandran plots of the reconstructions obtained with different methods clearly showed that the backbone structures reconstructed by DeepPSC were the most reasonable among all methods (Fig. 5). In particular, none of the glycine and proline residues in the backbones

obtained from DeepPSC were classified as outliers, consistent with the experimentally

determined PDB structures, whereas many of these residues resulted as outliers in the

backbones obtained by PD2 and PULCHRA, as well as by baseline 2. It is noteworthy

that for baseline 2, the dihedral angles share a "S-shape" distribution pattern for all the

four types of residues (general, glycine, pre-proline, and proline), which is consistent

with the poor network fitting of this type of protein structure representation, as shown

in supplementary Fig. S2.

3.4 Conclusion

We consider protein structure representation as a critical problem in applying deep

learning for reliable protein structure prediction, and for related endeavors such as

protein design. Our protein structure camera (PSC) approach provides a step forward

in protein structure representations, and toward enabling more sophisticated

applications of deep learning in biology.

Reference

1. M. S. Smyth, J. H. Martin, X-ray crystallography. *Molecular Pathology* **53**, 8-14 (2000).

2. J. D. F.-K. Voula Kanelis, and Lewis E. Kay, Multidimensional NMR methods for protein structure determination. *IUBMB Life* **52**, 291-302 (2001).

3. Y. Cheng, Single-particle cryo-EM - How did it get here and where will it go.

Science **361**, 876-880 (2018).

4. A. W. Senior *et al.*, Improved protein structure prediction using potentials from deep learning. *Nature* **577**, 706-710 (2020).

5. M. AlQuraishi, End-to-end differentiable learning of protein structure. *Cell Systems* **8**, 292-301 e293 (2019).

6. J. Eickholt, J. Cheng, Predicting protein residue-residue contacts using deep networks and boosting. *Bioinformatics* **28**, 3066-3072 (2012).

7. S. Wang, S. Sun, Z. Li, R. Zhang, J. Xu, Accurate de novo prediction of protein contact map by ultra-deep learning model. *PLoS Computational Biology* **13**, e1005324 (2017).

8. D. Xiong, J. Zeng, H. Gong, A deep learning framework for improving long-range residue-residue contact prediction using a hierarchical strategy. *Bioinformatics* **33**, 2675-2683 (2017).

9. E. C. Alley, G. Khimulya, S. Biswas, M. AlQuraishi, G. M. Church, Unified rational protein engineering with sequence-based deep representation learning. *Nature Methods* **16**, 1315-1322 (2019).

10. B. N. Rao R, Thomas N, et al., Evaluating protein transfer learning with TAPE. *arXiv*, 1906.08230 (2019).

11. J. Hou, B. Adhikari, J. Cheng, DeepSF: Deep convolutional neural network for mapping protein sequences to folds. *Bioinformatics* **34**, 1295-1303 (2018).

12. T. Jo, J. Hou, J. Eickholt, J. Cheng, Improving protein fold recognition by deep learning networks. *Scientific Reports* **5**, 17573 (2015).

13. K. Yan, X. Fang, Y. Xu, B. Liu, Protein fold recognition based on multi-view modeling. *Bioinformatics* **35**, 2982-2990 (2019).

14. S. Wang, J. Peng, J. Ma, J. Xu, Protein secondary structure prediction using deep convolutional neural fields. *Scientific Reports* **6**, 18962 (2016).

15. V. Gligorijevic, M. Barot, R. Bonneau, DeepNF: Deep network fusion for protein function prediction. *Bioinformatics* **34**, 3873-3881 (2018).

16. M. Kulmanov, M. A. Khan, R. Hoehndorf, J. Wren, DeepGO: Predicting protein functions from sequence and interactions using a deep ontology-aware classifier. *Bioinformatics* **34**, 660-668 (2018).

17. Y. Luo *et al.*, A network integration approach for drug-target interaction prediction and computational drug repositioning from heterogeneous information. *Nature Communications* **8**, 573 (2017).

18. M. Tsubaki, K. Tomii, J. Sese, Compound-protein interaction prediction with end-to-end learning of neural networks for graphs and sequences. *Bioinformatics* **35**, 309-318 (2019).

19. J. Wang, H. Cao, J. Z. H. Zhang, Y. Qi, Computational protein design with deep learning neural networks. *Scientific Reports* **8**, 6349 (2018).

20. S. Zheng, Y. Li, S. Chen, J. Xu, Y. Yang, Predicting drug–protein interaction using quasi-visual question answering system. *Nature Machine Intelligence* **2**, 134-140 (2020).

21. M. M. Stepniewska-Dziubinska, P. Zielenkiewicz, P. Siedlecki, Development and evaluation of a deep learning model for protein-ligand binding affinity prediction.

Bioinformatics **34**, 3666-3674 (2018).

22. A. Krizhevsky, I. Sutskever, G. E. Hinton, in *Advances in neural information processing systems*. (2012), pp. 1097-1105.

23. Z.-Q. Zhao, P. Zheng, S.-t. Xu, X. Wu, Object detection with deep learning: A review. *IEEE Transactions on Neural Networks and Learning Systems* **30**, 3212-3232 (2019).

24. S. Mallat, Understanding deep convolutional networks. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences* **374**, 20150203 (2016).

25. M. D. Zeiler, R. Fergus, in *European Conference on Computer Vision*. (Springer, 2014), pp. 818-833.

26. P. D. Adams *et al.*, PHENIX: A comprehensive Python-based system for macromolecular structure solution. *Acta Crystallographica. Section D, Biological Crystallography* **66**, 213-221 (2010).

27. P. Emsley, K. Cowtan, Coot: model-building tools for molecular graphics. *Acta Crystallographica. Section D, Biological Crystallography* **60**, 2126-2132 (2004).

28. P. Rotkiewicz, J. Skolnick, Fast procedure for reconstruction of full-atom protein models from reduced representations. *Journal of Computational Chemistry* **29**, 1460-1465 (2008).

29. R. M. Esnouf, Polyalanine reconstruction from Ca positions using the program CALPHA can aid initial phasing of data by molecular replacement procedures. *Acta crystallographica. Section D, Biological Crystallography* **D53**, 665-672

(1997).

30. P. Emsley, B. Lohkamp, W. G. Scott, K. Cowtan, Features and development of Coot. *Acta Crystallographica. Section D, Biological Crystallography* **66**, 486-501 (2010).

31. A. Roy, A. Kucukural, Y. Zhang, I-TASSER: A unified platform for automated protein structure and function prediction. *Nature Protocols* **5**, 725-738 (2010).

32. Y. Li, Y. Zhang, REMO: A new protocol to refine full atomic protein models from C-alpha traces by optimizing hydrogen-bonding networks. *Proteins* **76**, 665-676 (2009).

33. D. Gront, S. Kmiecik, A. Kolinski, Backbone building from quadrilaterals: a fast and accurate algorithm for protein backbone reconstruction from alpha carbon coordinates. *Journal of Computational Chemistry* **28**, 1593-1597 (2007).

34. J. Maupetit, R. Gautier, P. Tuffery, SABBAC: Online structural alphabet-based protein backbone reconstruction from alpha-carbon trace. *Nucleic Acids Research* **34**, W147-151 (2006).

35. B. L. Moore, L. A. Kelley, J. Barber, J. W. Murray, J. T. MacDonald, High-quality protein backbone reconstruction from alpha carbons using Gaussian mixture models. *Journal of Computational Chemistry* **34**, 1881-1889 (2013).

36. R. Zhang *et al.*, 4.4 A cryo-EM structure of an enveloped alphavirus Venezuelan equine encephalitis virus. *EMBO Journal* **30**, 3854-3863 (2011).

37. J. Kyte, and Russell F. Doolittle., A simple method for displaying the hydropathic character of a protein. *Journal of Molecular Biology* **157**, 105-132 (1982).

38. J. M. Zimmerman, Naomi Eliezer, and R. Simha., The characterization of amino acid sequences in proteins by statistical methods. *Journal of Theoretical Biology* **21**, 170-201 (1968).

39. F. Huang, W. M. Nau, A conformational flexibility scale for amino acids in peptides. *Angewandte Chemie International Edition* **42**, 2269-2272 (2003).

40. P. W. Payne, Reconstruction of protein conformations from estimated positions of the Cα coordinates. *Protein Science* **2**, 315-324 (1993).

41. I. Kufareva, R. Abagyan, Methods of protein structure comparison. *Methods in Molecular Biology* **857**, 231-257 (2012).

42. J. Moult, K. Fidelis, A. Kryshtafovych, T. Schwede, A. Tramontano, Critical assessment of methods of protein structure prediction (CASP) - round x. *Proteins* **82 Suppl 2**, 1-6 (2014).

43. S. C. Lovell *et al.*, Structure validation by Cα geometry: φ,ψ and Cβ deviation. *Proteins: Structure, Function, and Bioinformatics* **50**, 437-450 (2003).

44. K. Sargsyan, C. Grauffel, C. Lim, How molecular size impacts RMSD applications in molecular dynamics simulations. *Journal of Chemical Theory and Computation* **13**, 1518-1524 (2017).

45. O. Carugo, S. Pongor, A normalized root-mean-square distance for comparing protein three-dimensional structures. *Protein Science* **10**, 1470-1473 (2001).

46. K. He, X. Zhang, S. Ren, J. Sun, in *Proceedings of the IEEE conference on computer vision and pattern recognition*. (2016), pp. 770-778.

47. A. Graves, J. Schmidhuber, Framewise phoneme classification with bidirectional

LSTM and other neural network architectures. *Neural Networks* **18**, 602-610 (2005).

48. S. Hochreiter, J. Schmidhuber, Long short-term memory. *Neural Computation* **9**, 1735-1780 (1997).

49. D. E. Rumelhart, G. E. Hinton, R. J. Williams, in *Parallel distributed processing: explorations in the microstructure of cognition,* E. R. David, L. M. James, C. P. R. Group, Eds. (MIT Press, 1986), vol. 1, pp. 318-362.

50. D. P. Kingma, and Jimmy Ba, Adam: A method for stochastic optimization. *arXiv*, 1412.6980 (2014).

51. I. Loshchilov, and Frank Hutter, SGDR: Stochastic Gradient Descent with warm Restarts. *arXiv*, 1608.03983 (2016).

52. G. Scapin, C. S. Potter, B. Carragher, Cryo-EM for small molecules discovery, design, understanding, and application. *Cell Chemical Biology* **25**, 1318-1325 (2018).

53. E. F. Pettersen *et al.*, UCSF Chimera - A visualization system for exploratory research and analysis. *Journal of Computational Chemistry* **25**, 1605-1612 (2004).

Figure legends

Figure 1. Schematic for the deep learning algorithm used in this work, or DeepPSC. A) The workflow of a typical computer vision task. B) Visualization of Protein Structure Camera (PSC) workflow. This figure is generated with the Chimera software (*53*). C) The workflow of the deep learning-based algorithm DeepPSC used in this work for reconstructing backbone structures from alpha-carbon traces.

Figure 2. Diagrams of the backbone structure representation and rebuilding (only the case of a trans peptide plane is shown). A) Typical peptide plane conformation. $C\alpha_n$, C_n, O_n, N_n, $C\alpha_{n+1}$ located on the n^{th} peptide plane of the protein structure. PC_n, PN_n, and PO_n are the projections of C_n, N_n, and O_n on the $C\alpha_n$-$C\alpha_{n+1}$ axis, respectively. B) Side view from $C\alpha_n$ to $C\alpha_{n+1}$, in which TC_n and TN_n are the torsion angles from $C\alpha_{n+1}C\alpha_{n+2}$ to C_n, and from $C\alpha_{n+1}$-$C\alpha_{n+2}$ to N_n, respectively, with $C\alpha_n$-$C\alpha_{n+1}$ as the axis. C) rebuilding process for $C\beta$, using the constraint $\theta_N = \theta_C$.

Figure 3. Network Architecture of DeepPSC. ResNet50 was used to extract visual features from images as local structure features. All local structure features were then fed into a Bi-LSTM module for information globalization among residues, yielding globalized local structure features. Finally, an MLP module was used to predict peptide plane torsions for pairs of the above adjacent globalized local structure features.

Figure 4. Distributions of the atomic coordinate deviations (rows) of the various reconstruction methods (columns). The GDT scores for 0.2 Å cutoff are indicated in the plots.

Figure 5. Ramachandran plots of the reconstructions obtained with different methods compared to the original structures (PDB). Rows represent the different methods and columns represent all residues (General), glycines (Gly), the residues preceding prolines (Pre-Pro), and prolines (Pro). By taking the reference distributions in the backgrounds, residues are classified as normal residues (blue) or outliers (red).

Tables

Table 1. Overview of the results for various backbone reconstruction methods.

Methods	Models	Mean $RMSD_{100}$ (Å)	Mean GDT_P0.2 (%)	Mean RAMA outliers (%)
Rebuilt from PDB	——	0.040	95.76	0.22
DeepPSC	Ensemble model	**0.076**	**88.18**	**0.23**
	Single model	0.079±0.001	87.87±0.08	0.22±0.03
Baseline 1 (k nearest residues)	Ensemble model	0.101	83.44	0.50
	Single model	0.108±0.001	82.16±0.25	0.71±0.07
Baseline 2 (distance map)	Ensemble model	0.289	54.58	5.23
	Single model	0.289±0.001	54.42±0.48	5.30±0.17
PD2	——	0.149	73.26	0.90
BBQ	——	0.156	71.82	3.03
SABBAC*	——	0.201	58.30	1.94
PULCHRA	——	0.221	52.15	2.20

*SABBAC failed to process one of the 21 structures in the test set. The results shown here were obtained with the other 20 test structures.

A

An Object in Euclidean Space → Camera → Image → Convolutional Neural Network → Visual Feature → Downstream Network → Probability for Classes (0.21, 0.16, 0.07, 0.03, 0.01) → Ranking → Recognized Class 'Dog'

B

Protein Structure Camera

16 Å

8 Å
Depth Limitation
-8 Å

16 Å

128 pixel

128 pixel

Local Structure → View Orientation → Local Structure in Protein Structure Camera View → Array Encoding → Local Structure Image

→ X-axis for Cα_n   → Y-axis for Cα_n   → Z-axis for Cα_n   -- → Orientation from X-axis to Cα_{n+2}

C

Protein Cα Trace → Cα Sliding Window / Protein Structure Camera → Image → Convolutional Neural Network → Visual Feature → Downstream Network → Peptide Plane Torsion (0.37, -2.76 / -0.16, 3.08 / 1.49, -1.43 / 2.26, -0.92) → Geometrical Backbone Rebuild → Protein Backbone Structure