ResistoXplorer: a web-based tool for visual, statistical and exploratory data analysis of resistome data

Achal Dhariwal[1], Roger Junges[1], Tsute Chen[2,3] & Fernanda Cristina Petersen[1*]

[1] Institute of Oral Biology, Faculty of Dentistry, University of Oslo, Oslo, Norway

[2] Department of Microbiology, The Forsyth Institute, Cambridge, MA, USA

[3] Department of Oral Medicine, Infection, and Immunology, Harvard School of Dental Medicine, Boston, MA, USA

*To whom correspondence should be addressed: Tel: +47-22840312, Email: f.c.petersen@odont.uio.no

ABSTRACT

The study of resistomes using whole metagenomic sequencing enables high throughput

identification of resistance genes in complex microbial communities, such as the human

microbiome. Over recent years, sophisticated and diverse pipelines have been established to

facilitate raw data processing and annotation. Despite the progress, there are no easy-to-use tools

for comprehensive visual, statistical, and functional analysis of resistome data. Thus, exploration

of the resulting large complex datasets remains a key bottleneck requiring robust computational

resources and technical expertise, which creates a significant hurdle for advancements in the

field. Here, we introduce ResistoXplorer, a user-friendly tool that integrates recent advancements

in statistics and visualization, coupled with extensive functional annotations and phenotype

collection, to enable high-throughput analysis of common outputs generated from metagenomic

resistome studies. ResistoXplorer contains three modules- the 'Antimicrobial Resistance Gene

Table' module offers various options for composition profiling, functional profiling and

comparative analysis of resistome data; the 'Integration' module supports integrative exploratory

analysis of resistome and microbiome abundance profiles derived from metagenomic samples;

finally, the 'Antimicrobial Resistance Gene List' module enables users to intuitively explore the

associations between antimicrobial resistance genes and the microbial hosts using network visual

analytics to gain biological insights. ResistoXplorer is publicly available at

http://www.resistoxplorer.no.

1 INTRODUCTION

Antimicrobial resistance (AMR) represents a major threat to global public health and the

economy [1]. Consequently, examining the emergence and dissemination of AMR genetic

determinants is one of the priorities in global research [2-4]. Until recently, genetic determinants

were mostly understood in the context of specific pathogens. However, to fully understand how

antimicrobial resistance genes (ARGs) emerge and disseminate a more holistic approach is

required. In this respect, advancements in short-read based high-throughput DNA sequencing

(HTS) technologies and computation methods have facilitated rapid identification and

characterization of ARGs across all the microbial genomes present in a sample (metagenome) [5,

6]. They have been shown to provide unprecedented knowledge into the large reservoir of ARGs

and contributed to elucidate the ARG composition and the spread of AMR between human,

animal, and environmental microbial communities [7-12]. Currently, resistome profiles

describing ARGs in complex and diverse microbial metagenomes are primarily generated using

whole metagenome shotgun sequencing in which the total DNA extracted from a microbial

community is sequenced. The resulting DNA fragments can be analyzed using read or assembly-

based approaches to characterize their resistome composition [5, 6]. These derived sequencing

datasets are both large and complex, causing considerable 'big data' challenges in downstream

data analysis.

The main computational effort in resistome analysis of metagenomic datasets so far has focused

on processing, classification, assembly, and annotation of sequenced reads. This has led to the

development of a number of excellent bioinformatic tools and databases for detecting and

quantifying ARGs in metagenomes [5, 6, 13, 14]. However, there is still no clear consensus with

regards to standard analysis pipelines and workflows for high-throughput analysis of AMR

metagenomic resistome data [14, 15]. Nonetheless, the outputs from most of these pipelines can be summarized as a data table consisting of feature (ARGs) abundance information across samples, *i.e.* resistome profiles, along with their functional annotations and sample metadata. For most researchers, the fundamental challenge in data analysis can often be centered on how to understand and interpret the information in the abundance tables especially within the context of different experimental factors and annotations.

Downstream analysis of resistome data can be separated into four main categories: (i) composition profiling- to visualize and characterize the resistome based on approaches developed in community ecology such as alpha diversity, rarefaction curves or ordination analysis; (ii) functional profiling- to analyze resistome profiles at different functional categories (*e.g.* Drug class, Mechanism), thus gaining better insights on their collective functional capabilities; (iii) comparative analysis- to identify features having a significant differential abundance between studied conditions, and (iv) integrative analysis- to integrate the resistome and taxonomic data to understand the complex interplay and potential associations between microbial ecology and AMR. The computational methods and approaches to perform such analysis are fairly diverse and require deep understanding and programming skills, representing significant barriers for their broader and exploratory applications [16]. The first category of analysis can be more straightforward to perform, but the last three are challenging.

Fundamental challenges within the different categories relate to the fact that metagenomic data is often characterized by differences in library sizes, sparsity, over-dispersion, and compositionality [17, 18]. Hence, it is critical to normalize the data to achieve comparable and meaningful results [18-20]. To deal with uneven library sizes, researchers often employ two common normalization approaches prior to analysis: subsampling the reads in each sample to the same number

(rarefying) or rescaling the total number of reads in each sample to a uniform sum (using

proportions). The former may entail loss of valuable information, while the latter could lead to

issues related to data compositionality [21]. To overcome such challenges, sophisticated scaling

methods based on log-ratio transformations have been proposed [22, 23]. To identify

differentially abundant genes, the development of statistical models that account for features of

metagenomic data or the use of methods to transform data to have distributions that fit standard

test assumptions is generally recommended [19]. For instance, the metagenomeSeq algorithm

incorporates cumulative sum scaling normalization and a zero-inflated Gaussian (ZIG) mixture

model to reduce false positives and improve statistical power for differential abundance analysis

[24, 25]. It has also been demonstrated that algorithms developed for RNA-seq data such as

edgeR and DESeq2, along with their respective normalization methods, outperform other

approaches used for metagenomic abundance data [20, 25, 26]. These standard strategies are

widely employed, but do not explicitly account for the compositional nature of whole

metagenomic sequencing data [27, 28]. To address this issue, promising Compositional Data

Analysis (CoDA) approaches have been proposed [29, 30].

Nonetheless, there is no one statistical method suitable for all types of metagenomic datasets [20,

26]. The best results are achieved from a trade-off between data characteristics (sample or group

size, sequencing depth, effect sizes, genes abundances, etc.) and the normalization method,

incorporated with the coupled exploratory and comparative analysis [31]. Therefore, various

statistical and normalization methods are required for different metagenomic datasets, analyses

and research questions addressed [6, 19, 25, 26, 31]. However, most of the approaches have been

implemented as R packages. Although flexible, learning R in order to use these methods can be

challenging for most clinicians and researchers.

In the second category, functional profiling, the characterized resistome abundance profiles are analyzed by mapping ARGs either to their respective class of drugs to which they confer resistance (Class-level) or to their underlying molecular mechanism of resistance (Mechanism-level). Analyzing resistomes at such high level categories enables researchers to gain more biological, actionable, and functional insights together with a better understanding of their data. However, these functional levels and categories, along with their classification scheme, vary considerably between AMR reference databases [15]. Additionally, depending upon the database used for annotation, users need to manually collect and curate such information and then generate separate abundance tables for each functional level. Hence, collecting appropriate functional annotation information for hundreds of ARGs in resistomes for functional profiling and further downstream analysis can be confusing, arduous, time-consuming, and error-prone. On the contrary, some of these databases may also provide information regarding the microbial hosts that harbor or carry these reference ARGs. Information about such relationships can be complex as one microbe can carry multiple ARGs and single ARGs can in turn be present across multiple microbes. To explore such intricate 'multiple-to-multiple' relations, one option is to use a network-based visualization method. However, such visual exploration support is not present in current resistome analysis tools.

To address these gaps as well as to meet recent advances in resistome data analysis, we have developed ResistoXplorer, a user-friendly, web-based, visual analytics tool to assist clinicians, bench researchers, and interdisciplinary groups working in the AMR field to perform exploratory data analysis on abundance profiles and resistome signatures generated from AMR metagenomics studies. The key features of ResistoXplorer include:

- Support of a wide array of common as well as advanced methods for composition profiling, visualization and exploratory data analysis;

- Comprehensive support for various data normalization methods coupled with standard as well as more recent statistical and machine learning algorithms;

- Support of a variety of methods for performing vertical data integrative analysis on paired datasets (*i.e.* taxonomic and resistome abundance profiles)

- Comprehensive support for ARG functional annotations along with their microbe and phenotype associations based on data collected from >10 reference databases;

- A powerful and fully featured network visualization for intuitive exploration of ARG-microbe associations, including functional annotation enrichment analysis support.

Collectively, these features consist of a comprehensive tool suite for exploratory downstream analysis of data generated from AMR metagenomics studies. ResistoXplorer is freely available at http://www.resistoxplorer.no.

MATERIAL & METHODS

Design & Implementation

ResistoXplorer is implemented based on Java, R and JavaScript programing languages. The framework is developed based on the Java Server Faces technology using the PrimeFaces (https://www.primefaces.org/) and BootsFaces (https://www.bootsfaces.net) component library. The network visualization uses the sigma.js (http://sigmajs.org/) JavaScript library. Additionally, D3.js (https://d3js.org/) and CanvasXpress (https://canvasxpress.org/) JavaScript libraries are utilized for other interactive visualization. All the R packages for performing back-end analysis and visualization are mentioned in the 'About' section of the tool. At the start of the analysis, a

temporary account is created with an associated home folder to store the uploaded data and

analysis results. All the analysis results will be returned in real-time. Upon completing their

analysis session, users should download all their results. The system is deployed on a dedicated

server with 4 physical CPU cores (Intel Core i5 3.4GHz), 8GB RAM and Ubuntu 18.04 LTS was

used as the operation system. ResistoXplorer has been tested with major modern browsers such

as Google Chrome, Mozilla Firefox, Safari, and Microsoft Internet Explorer.

Program description and methods

ResistoXplorer consists of three main analysis modules. The first is the **ARG List** module that is

designed to explore the functional and microbial hosts associations for a given list of

antimicrobial resistance genes (ARGs) of interest. The second is the **ARG Table** module, which

contains functions for analyzing resistome abundance profiles generated from AMR

metagenomics studies. Lastly, the **Integration** module enables users to perform integrative

analysis on the paired taxonomic and resistome abundance profiles to further explore potential

associations coupled with novel biological insights and hypotheses. Figure 1 represents the

overall design and workflow of ResistoXplorer. We recommend users to try out our example

datasets to get familiar with the basic steps and key features of the tool before proceeding with

analysis of their own data. ResistoXplorer also contains manuals and a comprehensive list of

frequently asked questions (FAQs) to assist users to easily navigate through different analysis

tasks.

RESULTS & DISCUSSION

Data upload and processing

Overview of data inputs. The three analysis modules (ARG List, ARG Table and Integration) are

represented as three interactive buttons in ResistoXplorer. Users must choose an analysis path

based on their input. The input can be uploaded in two different ways – by entering a list of

antimicrobial resistance genes (ARGs) or by uploading an ARG abundance table along with a

sample metadata file containing group information. In the latter case, the files can be uploaded as

a tab-delimited text (.txt) or in comma-separated values (.csv). Further, users must also provide

the annotation information of ARGs either by uploading a file (.txt or .csv) or by just selecting

the same database used for their annotation during upstream analysis. Additionally, the

Integration module requires users to also upload a taxa abundance table in the same formats. The

taxonomic and functional annotation files are optional in case of integrative analysis. Users can

go to the corresponding 'Manuals' and 'Data Format' section, or download the example datasets

for more details.

ARG-functional annotations collection. The annotation information and the classification scheme

for reference ARGs (or sequences) are collected from 9 widely used generalized AMR

databases: CARD [32], ResFinder [33], MEGARes [15, 34], AMRFinder [35], SARG [36],

DeepARG-DB [37], ARGminer [38], ARDB [39] and ARG-ANNOT [40]. Further, this

annotation information is organized into tables containing the reference ARGs in rows and their

functional annotation levels across columns for each of the databases. The headers (names) for

reference ARGs are annotated as in the chosen database. Some of the annotation levels having

multiple functional category assignments for ARGs were removed from the tables to avoid false

counts inflation during downstream analysis. Additional manual curation for functional category

naming and data redundancies were performed in some of the databases. Further, we also

structured functional annotation information from the BacMet [41] database and antimicrobial

peptide (AMP) resistance gene dataset [42] to enable users to perform functional profiling and downstream analysis of antibacterial biocides/metals and AMP resistance genes abundance profiles. It should be noted that ResistoXplorer does not perform any functional annotation of sequencing data. The tables are stored in RDS file format for less storage space and fast retrieval of data. Users can use these tables to analyze their resistome profile directly at different functional levels rather than manually collecting the annotation information from their corresponding database. The 'Data Format' and 'About' pages provide a detailed description on the format, structure of annotation table and database statistics, together with the links to allow users to download the annotation structure ('Downloads' section) available for the individual database.

Data filtration and normalization. By default, features with zero read count across all the samples or only present in one sample with extremely low count (*e.g.,* 2) are removed from downstream analysis based upon some statistical and biological approximations. Also, features present in only a small percentage of samples (*e.g.*, 20%) with very few counts (*e.g.*, 2) cannot be discriminated from sequencing errors or low-level contamination, and also considered difficult to interpret their significance with respect to the whole community. By default, such low-quality features are filtered based on sample prevalence and their abundance levels to improve the comparative analysis. The default values are those used by the other tools and mostly found in the literature [43, 44]. Users can also choose to remove low abundant features by setting a minimum count cutoff based on their mean or median value. Conversely, some features remain constant in their abundances throughout the experimental conditions or across all the samples. These features are implausible to be informative in the comparative analysis. Users can exclude such low variant features based on their inter-quantile ranges, standard deviations or

coefficient of variations [43]. Removing those uninformative features can increase the statistical

power by reducing multiple testing issues during differential analysis [45]. The filtered data is

used for most of the downstream analysis except alpha diversity and rarefaction analysis. In case

of integrative analysis, users can also choose to apply different data filtration criteria for both

taxonomic and resistome abundance data.

After data filtering, users must perform data normalization to remove the systematic variability

between samples. Currently, ResistoXplorer offers three categories of data normalization-

rarefying, scaling and transformation, based on various widely used methods for metagenomic

abundance data [25]. In addition, ResistoXplorer supports other normalization methods like

centered log-ratio (clr) and additive log-ratio (alr) transformation to facilitate compositional data

analysis. The choice of method is dependent upon the type of analyses to be performed [20, 31].

The normalized data is used for exploratory data analysis including ordination, clustering and

integrative analysis. Users can explore different approaches and visually investigate the

clustering patterns (*i.e.*, ordination plots, dendrogram and heatmap) to determine the effects of

different normalization methods with regard to the experimental factor of interest. The total sum

scaling (TSS) normalization is recommended for such type of analysis and has been set as the

default option in ResistoXplorer [20, 46, 47]. Also, comparative analysis using different

approaches is performed on normalized data. However, each of these approaches will use its own

specific normalization procedure due to the lack of benchmark study evaluating which

normalization methods should be combined with the different statistical approaches to achieve

best performance for identifying differentially abundant genes [26]. For example, the relative log

expression (RLE) normalization is used for DESeq2, and the centered log-ratio transformation is

applied for ALDEx2. In the integrative analysis module, taxonomic and resistome datasets are

normalized using the same approach.

Composition profiling

Visual exploration. ResistoXplorer allows users to visually explore the resistome based on

various intuitive visualization approaches used for metagenomic data. For instance, users can

visualize resistome abundance data while simultaneously showing the functional hierarchical

relationships and connectivity between features using an interactive sankey diagram, zoomable

sunburst or treemap graphics (Figure 2C). In case of treemap, users can click a particular

rectangular block of interest to further inspect its compositions at a lower functional level. The

abundances can be represented as either absolute counts or relative proportions. However, such

visualizations are more suitable for resistome profiles having an acyclic and hierarchical

functional annotation structure. Abundance profiles can also be viewed at different functional

levels using other common visualizations such as stacked area or stacked bar plot (Figure 2A).

The plot is organized by experimental factors to help visualize the differences in resistome

composition across different conditions.

Diversity profiling. The resistome diversity profiling is implemented mainly based on the R

vegan and phyloseq packages [48, 49]. Currently, users can perform alpha diversity (within-

sample) analysis using eight common richness and/or evenness-based diversity measures. Since

the Chao1 measure performed well and is recommended for estimating ARG diversity [50], it

has been set as a default one in ResistoXplorer. The results are represented in the form of a dot

plot for individual samples and box plots for each sample group (Figure 2B). The corresponding

statistical significance is calculated automatically using either parametric or non-parametric tests.

The analysis can be performed at different functional levels based on the available annotations.

Additionally, the reliability of estimated diversity in samples can be assessed through rarefaction

curves in which the number of unique features (ARGs) identified is plotted against the sequence

sample size (Figure 2D).

Ordination analysis. The ordination analysis function allows users to explore and visualize the

similarities or dissimilarities between samples based on their composition at different functional

levels. The dissimilarity can be calculated using five non-phylogenetic-based quantitative or

qualitative distance measures. Since the different types of distance measures have specific niches

and can affect the outcomes and the interpretation of the analysis, it is recommended by several

authors to apply different measures to better understand the factors underlying composition

differences [6, 51, 52]. Currently, three widely accepted ordination methods are supported,

including principal coordinate analysis (PCoA), non-metric multidimensional scaling (NMDS)

and principal component analysis (PCA). In particular, users can follow a CoDA ordination

approach by performing PCA on the centered log-ratio transformed data. The corresponding

statistical significance is calculated using one of the three common multivariate statistical testing

methods with generally the more powerful method i.e., Permutational multivariate analysis of

variance (PERMANOVA) set as the default option [53]. By default, ordination analysis is

performed using PCoA on a most widely used Bray–Curtis dissimilarity metric and assessed

using PERMANOVA. The results are represented as both 2D and 3D sample plots. The samples

visualized in these ordination plots are colored based on metadata or their alpha diversity

measures to help users identify any underlying patterns in the datasets (Figure 3B).

Comparative analysis

Differential abundance testing. This section enables users to perform statistical testing to identify

features that are significantly different in abundance across sample groups. ResistoXplorer

supports standard tests, such as DESeq2 [22], edgeR [23], metagenomeSeq [24], LEfSe [54], as

well as more recent CoDA univariate analysis approaches such as ALDEx2 [55] and ANCOM

[56]. DESeq2 and edgeR are broadly used and generally considered as robust and powerful

parametric statistical approaches for datasets with small group and equally distributed library

sizes [18, 20, 25, 26]. They fit a generalized linear model and assume that read counts follow a

negative binomial distribution to account for the features of count data. In contrast, the

metagenomeSeq with its recommended CSS normalization has substantially higher performance

with larger group sizes [26, 48]. LEfSe uses the standard non-parametric tests for statistical

significance coupled with linear discriminant analysis to assess the effect size of those

differentially abundant features. The CoDA methods perform statistical testing on the log ratios

of features rather than their actual count abundances to deal with the compositional nature of

sequencing data. ALDEx2, for instance, performs parametric or nonparametric statistical tests on

log-ratio values from a modeled probability distribution of the data and returns the expected

values of statistical tests along with effect size estimates. ANCOM tests the log-ratio abundance

of all pairs of features for differences in means using nonparametric statistical tests. By default,

the Benjamini–Hochberg correction is used for all approaches to control the false discovery rate

(FDR) across significant genes. The differential analysis can also be performed at different

functional levels.

The results from the differential analysis are displayed as a table. By default, the result table will

show a maximum of 500 top features ordered according to their adjusted P-values. The

significant features (if present) are automatically highlighted in orange color. Further, users can

also see a boxplot summary for any feature of interest by just clicking the 'Details' icon. Since

different statistical approaches may generate divergent P-values, it is often recommended to

compare and visualize results using more than one statistical approach, as to increase confidence

in the interpretation of results.

Machine learning-based classification. Prediction of microbiome signatures using machine

learning algorithms has been gaining more recognition and shown to perform well in recent

resistome data analyses and classifications [7, 57, 58]. ResistoXplorer provides two such

powerful supervised classification methods - Random Forest [59] and Support Vector Machine

(SVM). Both can be applied to resistome data for identification of potential biomarkers. In

particular, the Random Forest algorithm uses an ensemble of classification trees (forest), with

final class prediction based on the majority vote of the ensemble. As the forest is constructed, it

can provide an unbiased estimate of prediction errors by aggregating cross-validation results

using bootstrapped samples. Random forest also measures the importance of each feature based

on the increase of the prediction errors when it is randomly shuffled. Alternatively, the SVM

algorithm uses a training set of samples separated into classes to identify a hyperplane in higher

dimensional feature space that generates the largest minimum distance (margin) between the

samples that belongs to different classes [60]. ResistoXplorer's SVM analysis is performed using

recursive feature selection and sample classification via linear kernel [61]. The features used by

the best model are considered to be important and ranked based on their frequencies of being

selected in the model. Figure 4D shows the classification performance of SVM with regards to

decreasing number of features (variables).

Other features. There are several other valuable functions implemented in ResistoXplorer for

exploratory analysis of resistome data. Users can perform core resistome analysis to detect core

sets of features present in samples or sample groups based on their abundance and prevalence

level (Figure 3A). ResistoXplorer also supports commonly used correlation analysis and

hierarchical clustering. The results from hierarchical clustering can be visualized using heatmaps

(Figure 4A) and dendrograms (Figure 4B). For publication purposes, all visualizations can be

downloaded as either Scalable Vector Graphics (SVG) or Portable Document Format (PDF)

files.

Integrative analysis

The main goal of this module is to explore and unveil potential hidden correlations between the

microbiome and resistome using a variety of integrative data analysis approaches. Such analyses

have been increasingly used to explore the associations between the bacteria and ARGs in

different environments [11, 62, 63]. Currently, ResistoXplorer offers several advanced and

commonly used univariate and multivariate statistical methods for data integration and

correlation analysis. All these analyses are performed on filtered and normalized datasets.

Global Similarity analysis. This section allows users to determine the overall similarity between

the microbiome and resistome dataset using two multivariate correlation-based approaches -

Procrustes analysis (PA) and Coinertia analysis (CIA). The datasets used for such analysis can be

normalized using scaling and/or transformation approaches to account for uneven library sizes

and compositional data. The analysis can be performed at various functional and taxonomic

levels based on available annotations. These functions currently support five common distance

measures. The ordinations from the distance matrices can be calculated using either PCoA, PCA

or NMDS. By default, both these analyses are being assessed employing widely used PCoA on a

Bray–Curtis distance metric. In case of PA, the microbiome ordination is scaled and rotated onto

the resistome ordination to minimize the sum of squared differences between the two

ordinations. For the CIA, the microbiome and resistome ordination are constrained so that the

squared covariances between them are maximized to measures the congruence between datasets.

The results are represented using both 2D and 3D ordination plots, where samples are colored

and shaped based on the datasets (Figure 5A). Users can also color the samples based on

different experimental factors to identify some patterns or gain biological insights. The

corresponding similarity coefficient and P-value from both these analyses are estimated

automatically to assess the strength and significance of the association between the two datasets.

The similarity coefficient ranges from 0 and 1, with 0 suggesting total similarity and 1 total

dissimilarity between the two datasets. Users can perform both Procrustes and Coinertia analysis

to gain more confidence by evaluating the congruency of the results.

Omics data integration approaches. ResistoXplorer offers other multivariate projection-based

exploratory approaches such as regularized canonical correlation analysis (rCCA) and sparse

partial least square (sPLS) for the integration of microbiome and resistome data. These

approaches aim at highlighting the correlations between high dimensional 'omics' datasets. They

are implemented primarily based on the R mixOmics package [64]. By default, both the datasets

are normalized during such analyses using their recommended normalization technique (*i.e.*, clr

transformation). Users can choose or tune the number of components and regularization

parameters for rCCA. In the case of sPLS, all variables are selected in both datasets by default.

In addition to sample plots, other variable plots like clustered image maps (Figure 5C) and

correlation circle plots (Figure 5D) are displayed to facilitate the interpretation of the complex

correlation structure between datasets.

Pairwise microbe-ARG correlation analysis. This section enables users to determine if there are

strong relationships (co-occurrence patterns) between individual microbial taxa (microbiome)

and ARGs (resistome) using univariate correlation analysis. Users can perform such analysis

using four different types of classical and more recent approaches, including Spearman, Pearson,

CCLasso and Maximal Information Coefficient. Since the Spearman correlation analysis is most

commonly used in resistome studies [65] and seems to perform overall better than other

approaches in identifying pairwise associations between omics data, it has been present as a first

choice in ResistoXplorer [66]. In particular, features (ARGs or taxa) that are not present in half

of the samples across all the groups are removed to eliminate an artificial association bias before

performing Spearman correlation analysis [65, 67]. By default, these approaches (except

CCLasso) use the microbiome and resistome relative abundances (proportions) for correlation

inference. While the CCLasso is based on log-ratio normalization of microbiome and resistome

compositional data. Due to the lack of consensus on each approach in different conditions, it is

recommended to compare results from multiple methods [66, 44]. The analysis can be conducted

on taxa at their different taxonomic annotations (*i.e.*, phylum, genus and species) and on

resistome at different functional levels (e.g., class, mechanisms, ARG, etc.) based on available

annotations. Users can select strong and significant pairwise correlations using a combination of

absolute correlation coefficients and adjusted P-value. The results are represented as a co-

occurrence network (Figure 6A) with each node indicating either a microbial taxon or a

resistance determinant (ARG). The nodes can be sized based on their network topological

measures (degree and betweenness). Users can double click on a node to highlight its

corresponding correlated nodes in a network. The width and color of an edge indicate the

strength and direction of the correlation between two nodes. The nodes are colored as well as

shaped according to the dataset. The underlying correlation matrices and network centrality-

based measures are also available to download.

ARGs-microbial host network exploration

The module offers users the possibility to understand the complex 'multiple-to-multiple'

relations between ARGs and microbial hosts, using an advanced network-based visual analytics

system. It is straightforward to identify key players from a network perspective, for instance, by

looking for those ARGs that are found in multiple microbes or by identifying those microbes that

simultaneously contain multiple ARGs of interest.

ARG-microbial host association data collection. ResistoXplorer currently supports four

reference databases (ResFinder [33], CARD [32], ARDB [39] and BacMet [41]) and a recently

published AMP dataset [42] for network-based microbial host associations exploration of ARGs.

These primary databases contain direct or indirect information regarding the microbial host for

the reference ARGs. In the latter case, the information on microbial host associated with each of

the reference ARGs has been collected from their corresponding GenBank Accession number

using a combination of text mining and manual curation, like in ResFinder and ARDB. Further,

this information has been manually annotated to improve name readability and remove

redundancy. Moreover, the available functional annotation information of ARGs was also

collected and organized into sets to facilitate enrichment analysis.

ARG–microbial host association table and network creation. The uploaded list of ARGs are

searched against the selected target database. This list can comprise significant ARGs detected in

differential abundance testing or ARGs identified through high-throughput qPCR. The results

will be represented as an association table with each row corresponding to a particular reference

ARG (sequence) and its potential microbial host. When available, the table also provides other

association information along with hyperlinks to the corresponding GenBank Accession number

and PubMed literature. Users can directly remove each row by clicking the delete icon in the last

column to keep only high-quality associations supported by literature or experimental evidence.

The resulting ARG-host associations are used to build the default networks. Since not all the

nodes will be connected, this approach may lead to the generation of multiple networks. The

statistics of nodes and edges are provided for users to have an overview of the size and

complexity of the generated networks. Further, users can also filter the nodes based on their

topological measures (degree and betweenness) in case of large networks for better

interpretation.

Network visualization and functional analysis. The resulting networks are visualized using

HTML5 canvas and JavaScript-based powerful and fully-featured visualization system. This

system is implemented based on a previously published visual analytics tool [68]. It is comprised

of three main components - the central network visualization area, the network customization

and functional analysis panel on the left, and the right panel containing a node table (Figure 7).

Users can intuitively visualize and manipulate the network in the central area using a mouse with

a scroll wheel. For example, users can scroll the wheel to zoom in and out the network, hover the

mouse over any node to view its name, click a node to display its details on the bottom-right

corner or double click a node to select it. The horizontal toolbar to the top exhibits basic

functions to manipulate the network. The first is the color picker to enable users to choose a

highlight color for the next selection. Users can also select and drag multiple nodes by using the

dashed square icon in the toolbar.

The network customization panel provides various options to configure the general visualization

features of the default network or to specify the range of mouse operation. The 'Layout' option

enables users to perform automatic network layout using different algorithms; the 'Background'

option enables users to select between a white and black background. The range of mouse

operations during highlighting and dragging-and-dropping can be varied using the 'Scope'

option. For instance, in 'single node' mode, only the node which has been clicked or dragged

will be highlighted or affected, whereas all the nodes that are being selected by the users will be

affected in the 'all highlights' mode. Additionally, the 'Download' option allows users to either

save the current network in different formats or to download the network file in GraphML format

for visualization in other software. The node table on the right panel displays the ARGs and their

microbial hosts along with corresponding network topological measures. The corresponding

abundance values, if available, will also be presented in the last column. Users can directly click

on any row of interest to select, and the network view will automatically zoom to the related

node. The bottom right panel provides more detailed info related to the node(s) being highlighted

or currently selected on the network.

ResistoXplorer also supports functional enrichment analysis of the ARGs present within the

current network using hypergeometric tests. This approach coupled with the network

visualization system has the potential to provide better interpretation of AMR resistance

mechanisms and inform on possible dissemination routes of ARGs. The categories or levels at

which enrichment analysis can be performed will be based on the initially selected database. The

enrichment analysis results are shown as a table on the left panel. By clicking on a row of the

result table, users can highlight all nodes related to an enriched function within the network.

There are also several other options and functionalities present, which allow users to intuitively

explore, manipulate and customize the ARG-microbial host association networks.

Use Case

To illustrate the functionality of the tool, we have selected two recent resistome studies with

publicly available metagenomic datasets [69, 70]. These datasets have been mounted as an

example sets in the 'ARG Table' module of our tool. In Doster et al., 2018 [70], the authors have

examined the effects of tulathromycin (antimicrobial drug) on gut microbiome and resistome

using commercial feedlot cattle, which we describe here in more detail. Two groups of cattle

were used, with one untreated group, and the other treated with metaphylaxis. Fecal samples

were collected from 15 cattle within each group at two time points- baseline (Day 1) and after 11

days (Day 11). Shotgun sequencing was performed on the extracted metagenomic DNA, and

reads were aligned to MEGARes and custom Kraken database for resistome and microbiome

characterization by the authors. The resulting resistome abundance profile is uploaded to the

ARG Table module of ResistoXplorer for further downstream analysis and exploration. Since the

reads were annotated using the MEGARes database, we have directly selected the precompiled

functional annotation information of the corresponding database to annotate and classify ARGs

(gene accessions) at higher functional levels. All the ARGs are mapped and classified at three

functional hierarchical levels - class, mechanism and group as per the MEGARes classification

scheme. We first compared the resistome alpha diversity at the mechanism level; the Shannon

diversity indices of the treatment group decrease over time, but the diversity changes are not

prominent in the untreated group (Figure 2B). The composition profiling is carried out to explore

and represent the gut resistome of cattle. As shown in Figure 2A, the resistome composition at

the class level is dominated mainly by the ARGs that confer resistance to tetracycline and the

macrolide-lincosamide-streptogramin (MLS) class of antibiotics in all the samples. The

hierarchical composition profiling using the Sankey diagram showed that almost all of the ARGs

that belongs to tetracycline-class confer resistance through ribosomal protection proteins. In

contrast, most of the ARGs that belong to the MLS-class confer resistance through macrolide

efflux pumps. Moreover, the resistome composition at different functional levels was quite

similar between treated and untreated cattle (Figure 2C). The ordination analysis at AMR

mechanism level using PCA (CoDA-based) and PCoA indicated that the resistome composition

of treated and untreated groups were significantly different between time points (ANOSIM: R =

0.49, P-value < 0.05; Figure 3B and 3C). We also performed differential abundance testing on

fecal resistome profile using metagenomeSeq and ALDEx2 (CoDA-based) at class, mechanism,

and group level. No significant features were found to be differentially abundant between

treatment groups using both these methods at all levels. All these analyses confirm and replicate

the previous findings and results of the original publication. We also performed additional

analyses of the data to highlight the utility and exploratory capabilities of ResistoXplorer. The

rarefaction curve analysis indicated that enough sequencing depth was achieved to describe the

ARG richness in all the metagenomic samples (Figure 2D). The heatmap showed that most of the

features (except TETQ, MEFA, TETW and TETO) at group level have a very low abundance

and sparse representation across all the 60 samples. The distinct abundance pattern of TET40

group is observed when comparing the Day1 with Day11 for both the treatment groups (Figure

4A). The hierarchical clustering analysis showed that samples belonging to both treated and

untreated groups are clustered effectively based on time points (Figure 4B). The ARGs

belonging to tetracyclines and MLS classes comprise the core resistome in cattle, based on their

abundance and prevalence level (Figure 3A). Additionally, both Random Forest and SVM

algorithms suggested that the treatment groups could not be predicted with high accuracies based

on the resistome profiles of fecal samples, confirming the findings that tulathromycin does not

seem to influence the gut resistome in cattle (Figure 4C and 4D).

Furthermore, the bacterial and ARG abundance profiles are uploaded to the Integration module

of ResistoXplorer to explore the relationship between the fecal microbiome and resistome in

cattle. The application of Procrustes analysis suggested that there were no significant overall

similarities between the resistome and bacterial abundance profile (M2 = 0.23, P-value > 0.05;

Figure 5A). However, the results from Coinertia analysis indicated that resistome and bacterial

composition are moderately correlated with statistical significance (RV coefficient = 0.47, P-

value < 0.05; Figure 5B). To deal with the result discrepancies between approaches, we also

investigated the pairwise associations between individual taxa (microbiome) and ARGs

(resistome) using Spearman and Pearson correlation analysis. The results showed that no

significant and strong pairwise correlations (criteria: absolute correlation coefficient > 0.7;

adjusted P-value < 0.05) were identified between any taxa (phylum level) and ARG (group level)

(Figure 6A and 6B), suggesting that the gut resistome was not correlated and structured by

bacterial composition.

Comparison with Other Tools

A variety of tools or pipelines have been developed in recent years to support resistome analysis

of metagenomic data [15, 33, 36, 37, 71, 72]. Most of these tools have been designed primarily

for raw reads processing and annotation, with limited or no support for interactive visual

exploration and downstream analysis. ResistoXplorer complements these tools and resources by

providing real-time visual analytics experience along with comprehensive support for statistical,

visual and exploratory analysis on the metagenomic resistome data. AMR++ Shiny [15] is a

web-based R/shiny application dedicated for basic exploratory and statistical analysis of

metagenomic resistome and microbiome data. More recently, resistomeAnalysis [67] R package

also supports visualization, comparative and integrative analysis of resistome abundance profile.

Based on the detailed comparisons among those tools (Table 1), it is clear that ResistoXplorer

offers a unique set of features and functions with regards to comprehensive statistical and

exploratory data analysis, visualization, integrative data analysis and ARG-microbial network

visual analysis.

Limitations and Future Directions

The ARG table module can be used for visualization and analysis of resistome profiles

characterizing different genetic determinants present within an AMR reference database.

However, ResistoXplorer does not allow users to choose multiple precompiled functional

annotation databases to analyze the entire ecologies (antimicrobial drugs, biocide, metal and

other resistance drivers) of resistance determinants. More importantly, the functional annotations

collected in ResistoXplorer mainly depend on the information and classification scheme present

in the original databases. Hence, there might still be some acyclic and hierarchical functional

annotation structure in databases, which users need to curate for accurate count-based analyses.

The biocuration of ARGs and their functional annotation structure for the supported databases is

beyond the scope of the study. Although some of the supported databases are no longer updated,

such as ARDB and ARG-ANNOT [5, 6], excluding them would have limited the possibility of

exploring and analyzing previous datasets, as well as a variety of present studies that still use

them. In regard to the ARG-microbial host associations module, these are limited by the type and

quality of information available in the databases. Currently, ResistoXplorer offers limited

functionalities and features for vertical data integration and pairwise correlation analysis. As

most of the advanced approaches for performing this type of analysis on multidimensional

datasets are based on computationally intensive re-sampling (cross-validation) and permutation-

based approaches to calculate statistical significance, which adds layers of complexity and

computational power demands, that is often challenging for a real-time interactive web

application. In future versions, we plan to continuously update and expand our database and

analysis support for exploration of mobilome, virulome and other resistance determinants of

relevance in AMR metagenomic studies.

CONCLUSION

Whole metagenomic sequencing studies are providing unparalleled knowledge on the diversity

of resistomes in the environment, animals and humans, and on the impact of interventions, such

as antibiotic use [7-12, 67, 69]. Currently, such studies and data analyses are mainly exploratory

in nature. In spite of the continuous development of many new statistical approaches, there is no

exclusive method that unfailingly performs well, as demonstrated by several benchmarking

studies [20, 25, 26, 46]. Indeed, it has been recently suggested that metagenomic analysis should

be explored comparatively using different available approaches [31]. However, this is a time

consuming task and requires knowledge and bioinformatics training on the implementation of

each statistical method employed. Therefore, it is critical to assist researchers and clinical

scientists in the field to easily explore their own datasets using a variety of approaches, in real-

time and through interactive visualization, to facilitate data understanding and hypothesis

generation. ResistoXplorer meets these requirements by offering comprehensive support for

composition profiling, statistical analysis, integrative analysis and visual exploration of resistome

data. Conversely, such analysis is entirely dependent on the comprehensiveness and quality of

the AMR reference databases [5, 6]. Hence, the use of continuously updated and curated

databases with a simple, acyclic and hierarchical functional annotation scheme is desired for

accurate downstream analysis. Lastly, ResistoXplorer will continuously be updated to follow the

advancements in approaches for resistome analysis. We believe ResistoXplorer will have the

potential to find large applicability as a useful resource for researchers in the field of AMR.

FUNDING

This work has been financed by the INDNOR and INTPART programs funded by The Research

Council of Norway, grant numbers 273833 and 274867, and the Olav Thon foundation.

ACKNOWLEDGEMENTS

REFERENCES

1. United IACG: **No Time to Wait–Securing the Future from Drug-resistant Infections.** *Report to the Secretary General of the Nations* 2019.
2. Simonsen GS, Tapsall JW, Allegranzi B, Talbot EA, Lazzari S: **The antimicrobial resistance containment and surveillance approach-a public health tool.** *Bulletin of the World Health Organization* 2004, **82:**928-934.
3. Cecchini M, Langer J, Slawomirski L: **Antimicrobial resistance in G7 countries and beyond: economic issues, policies and options for action.** *Paris: Organization for Economic Co-operation Development* 2015**:**1-75.
4. Metcalfe S, Baker MG, Freeman J, Wilson N, Murray P: **Combating antimicrobial resistance demands nation-wide action and global governance.** *NZ Med J* 2016, **129:**8-14.
5. Boolchandani M, D'Souza AW, Dantas G: **Sequencing-based methods and resources to study antimicrobial resistance.** *Nature Reviews Genetics* 2019**:**1.

6. Gupta CL, Tiwari RK, Cytryn E: **Platforms for elucidating antibiotic resistance in single genomes and complex metagenomes.** *Environment International* 2020, **138:**105667.

7. Xia Y, Zhu Y, Li Q, Lu J: **Human gut resistome can be country-specific.** *PeerJ* 2019, **7:**e6389.

8. Forslund K, Sunagawa S, Kultima JR, Mende DR, Arumugam M, Typas A, Bork P: **Country-specific antibiotic use practices impact the human gut resistome.** *Genome research* 2013, **23:**1163-1169.

9. Munk P, Andersen VD, de Knegt L, Jensen MS, Knudsen BE, Lukjancenko O, Mordhorst H, Clasen J, Agersø Y, Folkesson A: **A sampling and metagenomic sequencing-based methodology for monitoring antimicrobial resistance in swine herds.** *Journal of Antimicrobial Chemotherapy* 2016, **72:**385-392.

10. Pal C, Bengtsson-Palme J, Kristiansson E, Larsson DJ: **The structure and diversity of human, animal and environmental resistomes.** *Microbiome* 2016, **4:**54.

11. Forsberg KJ, Patel S, Gibson MK, Lauber CL, Knight R, Fierer N, Dantas G: **Bacterial phylogeny structures soil resistomes across habitats.** *Nature* 2014, **509:**612-616.

12. Hendriksen RS, Munk P, Njage P, Van Bunnik B, McNally L, Lukjancenko O, Röder T, Nieuwenhuijse D, Pedersen SK, Kjeldgaard J: **Global monitoring of antimicrobial resistance based on metagenomics analyses of urban sewage.** *Nature communications* 2019, **10:**1124.

13. McArthur AG, Wright GD: **Bioinformatics of antimicrobial resistance in the age of molecular epidemiology.** *Current opinion in microbiology* 2015, **27:**45-50.

14. Hendriksen RS, Bortolaia V, Tate H, Tyson G, Aarestrup FM, McDermott P: **Using Genomics to Track Global Antimicrobial Resistance.** *Frontiers in public health* 2019, **7:**242.

15. Lakin SM, Dean C, Noyes NR, Dettenwanger A, Ross AS, Doster E, Rovira P, Abdo Z, Jones KL, Ruiz J: **MEGARes: an antimicrobial resistance database for high throughput sequencing.** *Nucleic acids research* 2016, **45:**D574-D580.

16. Chong J, Xia J: **Computational approaches for integrative analysis of the metabolome and microbiome.** *Metabolites* 2017, **7:**62.

17. Li H: **Microbiome, metagenomics, and high-dimensional compositional data analysis.** *Annual Review of Statistics Its Application* 2015, **2:**73-94.

18. Calle ML: **Statistical analysis of metagenomics data.** *Genomics informatics* 2019, **17**.

19. Bengtsson-Palme J, Larsson DJ, Kristiansson E: **Using metagenomics to investigate human and environmental resistomes.** *Journal of Antimicrobial Chemotherapy* 2017, **72:**2690-2703.

20. Weiss S, Xu ZZ, Peddada S, Amir A, Bittinger K, Gonzalez A, Lozupone C, Zaneveld JR, Vázquez-Baeza Y, Birmingham A: **Normalization and microbial differential abundance strategies depend upon data characteristics.** *Microbiome* 2017, **5:**27.

21. Filzmoser P, Hron K, Reimann C: **Univariate statistical analysis of environmental (compositional) data: problems and possibilities.** *Science of the Total Environment* 2009, **407:**6100-6108.

22. Love MI, Huber W, Anders S: **Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2.** *Genome biology* 2014, **15:**550.

23. Robinson MD, McCarthy DJ, Smyth GK: **edgeR: a Bioconductor package for differential expression analysis of digital gene expression data.** *Bioinformatics* 2010, **26:**139-140.

24. Paulson JN, Pop M, Bravo HC: **metagenomeSeq: Statistical analysis for sparse high-throughput sequencing.** *Bioconductor package* 2013, **1:**63.

25. Pereira MB, Wallroth M, Jonsson V, Kristiansson E: **Comparison of normalization methods for the analysis of metagenomic gene abundance data.** *BMC genomics* 2018, **19:**274.

26. Jonsson V, Österlund T, Nerman O, Kristiansson E: **Statistical evaluation of methods for identification of differentially abundant genes in comparative metagenomics.** *BMC genomics* 2016, **17:**78.

27. Quinn TP, Erb I, Richardson MF, Crowley TM: **Understanding sequencing data as compositions: an outlook and review.** *Bioinformatics* 2018, **34:**2870-2878.

28. Gloor GB, Reid G: **Compositional analysis: a valid approach to analyze microbiome high-throughput sequencing data.** *Canadian journal of microbiology* 2016, **62:**692-703.

29. Gloor GB, Macklaim JM, Pawlowsky-Glahn V, Egozcue JJ: **Microbiome datasets are compositional: and this is not optional.** *Frontiers in microbiology* 2017, **8:**2224.

30. Quinn TP, Erb I, Gloor G, Notredame C, Richardson MF, Crowley TM: **A field guide for the compositional analysis of any-omics data.** *GigaScience* 2019, **8:**giz107.

31. Pérez-Cobas AE, Gomez-Valero L, Buchrieser C: **Metagenomic approaches in microbial ecology: an update on whole-genome and marker gene sequencing analyses.** *Microbial Genomics* 2020, **6**.

32. Alcock BP, Raphenya AR, Lau TT, Tsang KK, Bouchard M, Edalatmand A, Huynh W, Nguyen A-LV, Cheng AA, Liu S: **CARD 2020: antibiotic resistome surveillance with the comprehensive antibiotic resistance database.** *Nucleic acids research* 2020.

33. Zankari E, Hasman H, Cosentino S, Vestergaard M, Rasmussen S, Lund O, Aarestrup FM, Larsen MV: **Identification of acquired antimicrobial resistance genes.** *Journal of antimicrobial chemotherapy* 2012, **67:**2640-2644.

34. Doster E, Lakin SM, Dean CJ, Wolfe C, Young JG, Boucher C, Belk KE, Noyes NR, Morley PS: **MEGARes 2.0: a database for classification of antimicrobial drug, biocide and metal resistance determinants in metagenomic sequence data.** *Nucleic acids research* 2019.

35. Feldgarden M, Brover V, Haft DH, Prasad AB, Slotta DJ, Tolstoy I, Tyson GH, Zhao S, Hsu C-H, McDermott PF: **Validating the AMRFinder tool and resistance gene database by using antimicrobial resistance genotype-phenotype correlations in a collection of isolates.** *Antimicrobial agents chemotherapy* 2019, **63:**e00483-00419.

36. Yin X, Jiang X-T, Chai B, Li L, Yang Y, Cole JR, Tiedje JM, Zhang T: **ARGs-OAP v2. 0 with an expanded SARG database and Hidden Markov Models for enhancement characterization and quantification of antibiotic resistance genes in environmental metagenomes.** *Bioinformatics* 2018, **34:**2263-2270.

37. Arango-Argoty G, Garner E, Pruden A, Heath LS, Vikesland P, Zhang L: **DeepARG: a deep learning approach for predicting antibiotic resistance genes from metagenomic data.** *Microbiome* 2018, **6:**23.

38. Argoty GAA, Guron GK, Garner E, Riquelme MV, Heath L, Pruden A, Vikesland P, Zhang L: **ARG-miner: A web platform for crowdsourcing-based curation of antibiotic resistance genes.** *bioRxiv* 2019**:**274282.

39. Liu B, Pop M: **ARDB—antibiotic resistance genes database.** *Nucleic acids research* 2008, **37:**D443-D447.

40. Gupta SK, Padmanabhan BR, Diene SM, Lopez-Rojas R, Kempf M, Landraud L, Rolain J-M: **ARG-ANNOT, a new bioinformatic tool to discover antibiotic resistance genes in bacterial genomes.** *Antimicrobial agents chemotherapy* 2014, **58:**212-220.

41. Pal C, Bengtsson-Palme J, Rensing C, Kristiansson E, Larsson DJ: **BacMet: antibacterial biocide and metal resistance genes database.** *Nucleic acids research* 2013, **42:**D737-D743.

42. Kintses B, Méhi O, Ari E, Számel M, Györkei Á, Jangir PK, Nagy I, Pál F, Fekete G, Tengölics R: **Phylogenetic barriers to horizontal transfer of antimicrobial peptide resistance genes in the human gut microbiota.** *Nature microbiology* 2019, **4:**447.

43. Dhariwal A, Chong J, Habib S, King IL, Agellon LB, Xia J: **MicrobiomeAnalyst: a web-based tool for comprehensive statistical, visual and meta-analysis of microbiome data.** *Nucleic acids research* 2017, **45:**W180-W188.

44. Ni Y, Yu G, Chen H, Deng Y, Wells PM, Steves CJ, Ju F, Fu J: **M2IA: a web server for microbiome and metabolome integrative analysis.** *Bioinformatics* 2020, **36:**3493-3498.

45. Bourgon R, Gentleman R, Huber W: **Independent filtering increases detection power for high-throughput experiments.** *Proceedings of the National Academy of Sciences* 2010, **107:**9546-9551.

46. McMurdie PJ, Holmes S: **Waste not, want not: why rarefying microbiome data is inadmissible.** *PLoS computational biology* 2014, **10:**e1003531.

47. McKnight DT, Huerlimann R, Bower DS, Schwarzkopf L, Alford RA, Zenger KR: **Methods for normalizing microbiome data: an ecological perspective.** *Methods in Ecology Evolution* 2019, **10:**389-400.

48. McMurdie PJ, Holmes S: **phyloseq: an R package for reproducible interactive analysis and graphics of microbiome census data.** *PloS one* 2013, **8**.

49. Dixon P: **VEGAN, a package of R functions for community ecology.** *Journal of Vegetation Science* 2003, **14:**927-930.

50. Bengtsson-Palme J: **The diversity of uncharacterized antibiotic resistance genes can be predicted from known gene variants—but not always.** *Microbiome* 2018, **6:**125.

51. Goodrich JK, Di Rienzi SC, Poole AC, Koren O, Walters WA, Caporaso JG, Knight R, Ley RE: **Conducting a microbiome study.** *Cell* 2014, **158:**250-262.

52. Kuczynski J, Liu Z, Lozupone C, McDonald D, Fierer N, Knight R: **Microbial community resemblance methods differ in their ability to detect biologically relevant patterns.** *Nature methods* 2010, **7:**813-819.

53. Anderson MJ, Walsh DC: **PERMANOVA, ANOSIM, and the Mantel test in the face of heterogeneous dispersions: what null hypothesis are you testing?** *Ecological monographs* 2013, **83:**557-574.

54. Segata N, Izard J, Waldron L, Gevers D, Miropolsky L, Garrett WS, Huttenhower C: **Metagenomic biomarker discovery and explanation.** *Genome biology* 2011, **12:**R60.

55. Fernandes AD, Reid JN, Macklaim JM, McMurrough TA, Edgell DR, Gloor GB: **Unifying the analysis of high-throughput sequencing datasets: characterizing RNA-**

seq, 16S rRNA gene sequencing and selective growth experiments by compositional data analysis. *Microbiome* 2014, **2:**15.

56. Mandal S, Van Treuren W, White RA, Eggesbø M, Knight R, Peddada SD, disease: **Analysis of composition of microbiomes: a novel method for studying microbial composition.** *Microbial ecology in health* 2015, **26:**27663.

57. Gasparrini AJ, Wang B, Sun X, Kennedy EA, Hernandez-Leyva A, Ndao IM, Tarr PI, Warner BB, Dantas G: **Persistent metagenomic signatures of early-life hospitalization and antibiotic treatment in the infant gut microbiota and resistome.** *Nature microbiology* 2019**:**1-13.

58. Rahman SF, Olm MR, Morowitz MJ, Banfield JF: **Machine learning leveraging genomes from metagenomes identifies influential antibiotic resistance genes in the infant gut microbiome.** *MSystems* 2018, **3:**e00123-00117.

59. Breiman L: **Random forests.** *Machine learning* 2001, **45:**5-32.

60. Burges CJ: **A tutorial on support vector machines for pattern recognition.** *Data mining knowledge discovery* 1998, **2:**121-167.

61. Zhang X, Lu X, Shi Q, Xu X-q, Hon-chiu EL, Harris LN, Iglehart JD, Miron A, Liu JS, Wong WH: **Recursive SVM feature selection and sample classification for mass-spectrometry and microarray data.** *BMC bioinformatics* 2006, **7:**197.

62. Ruppé E, Ghozlane A, Tap J, Pons N, Alvarez A-S, Maziers N, Cuesta T, Hernando-Amado S, Clares I, Martínez JL: **Prediction of the intestinal resistome by a three-dimensional structure-based method.** *Nature microbiology* 2019, **4:**112-123.

63. Liu J, Taft DH, Maldonado-Gomez MX, Johnson D, Treiber ML, Lemay DG, DePeters EJ, Mills DA: **The fecal resistome of dairy cattle is associated with diet during nursing.** *Nature communications* 2019, **10:**1-15.

64. Rohart F, Gautier B, Singh A, Lê Cao K-A: **mixOmics: An R package for 'omics feature selection and multiple data integration.** *PLoS computational biology* 2017, **13:**e1005752.

65. Li B, Yang Y, Ma L, Ju F, Guo F, Tiedje JM, Zhang T: **Metagenomic and network analysis reveal wide distribution and co-occurrence of environmental antibiotic resistance genes.** *The ISME journal* 2015, **9:**2490.

66. You Y, Liang D, Wei R, Li M, Li Y, Wang J, Wang X, Zheng X, Jia W, Chen T: **Evaluation of metabolite-microbe correlation detection methods.** *Analytical biochemistry* 2019, **567:**106-111.

67. Carr VR, Witherden EA, Lee S, Shoaie S, Mullany P, Proctor GB, Gomez-Cabrero D, Moyes DL: **Abundance and diversity of resistomes differ between healthy human oral cavities and gut.** *Nature communications* 2020, **11:**1-10.

68. Fan Y, Siklenka K, Arora SK, Ribeiro P, Kimmins S, Xia J: **miRNet-dissecting miRNA-target interactions and functional associations through network-based visual analysis.** *Nucleic acids research* 2016, **44:**W135-W141.

69. Munk P, Knudsen BE, Lukjancenko O, Duarte ASR, Van Gompel L, Luiken RE, Smit LA, Schmitt H, Garcia AD, Hansen RB: **Abundance and diversity of the faecal resistome in slaughter pigs and broilers in nine European countries.** *Nature microbiology* 2018, **3:**898-908.

70. Doster E, Rovira P, Noyes NR, Burgess BA, Yang X, Weinroth MD, Lakin SM, Dean CJ, Linke L, Magnuson R: **Investigating effects of tulathromycin metaphylaxis on the**

fecal resistome and microbiome of commercial feedlot cattle early in the feeding period. *Frontiers in microbiology* 2018, **9:**1715.

71. Kaminski J, Gibson MK, Franzosa EA, Segata N, Dantas G, Huttenhower C: **High-specificity targeted functional profiling in microbial communities with ShortBRED.** *PLoS computational biology* 2015, **11:**e1004557.

72. Inouye M, Dashnow H, Raven L-A, Schultz MB, Pope BJ, Tomita T, Zobel J, Holt KE: **SRST2: rapid genomic surveillance for public health and hospital microbiology labs.** *Genome medicine* 2014, **6:**90.

Tables

Table 1: Comparison of ResistoXplorer with other web-based tools (except resistomeAnalysis R package) supporting downstream analysis of metagenomic resistome data. Tools exclusively dedicated for sequence annotations are not included. The URL of each tool is provided under the table.

Tools	ResistoXplorer	AMR++ Shiny	resistomeAnalysis	WHAM!
Platform	Web-based	Web-based + locally installable	R package	Web-based
Registration	No	No	-	No
Data Processing				
Data Input	Abundance tables	Abundance tables	Abundance tables	Abundance tables (Biobakery + EBI)
Functional annotation	User-defined + collected from >10 AMR databases	MEGARes	CARD	User-defined
Filtering	Abundance, variance	Abundance (Quantile)	-	Variance
Normalization	Scaling, transformation, rarefying	Cumulative Sum Scaling (CSS), rarefying	Total Sum Scaling (TSS), proportion	Proportion, clr
Composition Profiling				
Visual profiling	Stacked bar plot, stacked area, sankey diagram, zoomable sunburst, treemap	Stacked bar plot	Stacked bar plot	Interactive Stacked bar plot
Alpha diversity	Multiple	-	Richness	-
Ordination analysis	PCoA, NMDS & PCA (2D & 3D)	PCA & NMDS (Bray-Curtis) (2D)	PCoA (2D)	-
Comparative analysis				
Differential analysis	DESeq2, metagenomeSeq, EdgeR, LEfSe, ALDEx2, ANCOM	metagenomeSeq	DESeq2	ALDEx2
Classification	Random Forests, SVM	-	-	-
Other functions	Heatmaps, dendrogram, correlation, core resistome, alpha rarefaction curves	Heatmaps, Alpha rarefaction bar plots	Heatmaps, dendrogram, correlation, core resistome	Interactive Heatmaps, correlation

Integrative analysis	Procrustes, Coinertia, rCCA, sPLS, Spearman, Pearson, CCLasso, MIC	-	Spearman	Visual comparisons
Gene (ARG) List exploration	ARG-microbial host network visual analytics & functional analysis	-	-	-

ResistoXplorer: http://www.resistoxplorer.no

AMR ++ Shiny: https://github.com/lakinsm/amrplusplus-shiny

resistomeAnalysis (R package): https://github.com/blue-moon22/resistomeAnalysis

WHAM!: https://ruggleslab.shinyapps.io/wham_v1/

Figure Legends

Figure 1: ResistoXplorer flow chart. ResistoXplorer accepts resistance gene list and ARG/taxa

abundance tables as input data. Three successive steps are performed - data processing, data

analysis, and result exploration. The accompanying web interface proffers a varied suite of

options, and generates several tables and graphics to enable users to intuitively go over the data

analysis tasks.

Figure 2: Example outputs from composition profiling panel of ARG Table module in

ResistoXplorer. (A) A stacked bar chart showing class level resistance abundance profiles across

samples. (B) A box plot summary of the Shannon diversity index at mechanism level in different

treatment groups across sampling time points. (C) A Sankey diagram showing the resistome

abundance profile of treated (left) and untreated (right) cattle group at hierarchical functional

levels including class, mechanism and group. (D) A rarefaction curve showing the number of

unique ARGs identified in each sample as a function of sequence sample size.

Figure 3: Illustration of core resistome and ordination analysis results in ResistoXplorer. (A) A

heatmap showing the core resistome of cattle analyzed at class level. (B) A 3D PCA plot with

sample colors based on time points. (C) A 3D PCoA plot with sample colors with regards to

different treatment groups and time points.

Figure 4: Example outputs from clustering analysis and machine learning-based classifications

in ARG Table module of ResistoXplorer. (A) A clustered heatmap showing the variation of

resistome abundance at group level in samples organized based on time point. (B) A dendrogram

showing the clustering of samples with colors based on treatment and time point. (C) and (D) A

graphical summary of the classification performance on different treatment groups using the

Random Forests and SVM algorithm, respectively.

Figure 5: Example outputs from Integration module of ResistoXplorer. (A) A 3D NMDS plot

from Procrustes analysis with samples shape and color with regards to datasets. (B) A 3D PCoA

plot from Coinertia analysis, with the length of lines connecting two points indicates the

similarity of samples between two datasets. (C) A clustered image heatmap showing the

correlations between and among taxa (phylum level) and ARGs (group level). (D) A correlation

circle plot showing the correlation structure of features (taxa/ARGs) present in two datasets.

Figure 6: Illustration of pairwise correlation analysis results. (A) and (B) A co-occurrence

network showing the strong and significant pairwise correlations between taxa (phylum level)

and ARGs (class level) identified using Spearman and Pearson correlation analysis, respectively.

Figure 7: A screenshot of ResistoXplorer network visual analytics system. The view is divided

into three main compartments with the network visualization (toolbar on top) at the center, the

node table on the right and the network customization panel together with functional annotation

table on the left. Users can easily highlight and manually organize different groups of nodes

based on either their annotations or connectivity patterns. It is straightforward to identify those

ARGs that are found in multiple microbes, or those microbes that simultaneously contain

multiple ARGs of interest.