MethylSPWNet and MethylCapsNet: Biologically Motivated Organization of DNAm Neural Network, Inspired by Capsule Networks

Joshua J. Levy*,[1,2,3], Youdinghuan Chen[1,2], Nasim Azizgolshani[2], Curtis L. Petersen[2,4], Alexander J. Titus[5], Erika L. Moen[4,6], Louis J. Vaickus[3], Lucas A. Salas[2,7], Brock C. Christensen[2,7,8]

Author Affiliations:
1. Program in Quantitative Biomedical Sciences, Geisel School of Medicine at Dartmouth, Lebanon, NH 03756
2. Department of Epidemiology, Geisel School of Medicine at Dartmouth, Lebanon, NH 03756
3. Emerging Diagnostic and Investigative Technologies, Department of Pathology, Dartmouth Hitchcock Medical Center, Lebanon, NH 03756
4. The Dartmouth Institute for Health Policy and Clinical Practice, Lebanon, NH, 03756
5. Department of Life Sciences, University of New Hampshire, Manchester, NH 03101
6. Department of Biomedical Data Science, Geisel School of Medicine at Dartmouth, Lebanon, NH 03756
7. Department of Molecular and Systems Biology, Geisel School of Medicine at Dartmouth, Lebanon, NH 03756
8. Department of Community and Family Medicine, Geisel School of Medicine at Dartmouth, Lebanon, NH 03756

* To whom correspondence should be addressed. Contact: joshua.j.levy.gr@dartmouth.edu

Key Words: Deep Learning, DNA Methylation, Central Nervous System Tumors, Capsules, Prior Biological Knowledge, Neural Networks, WGCNA

Abstract

DNA methylation (DNAm) alterations have been heavily implicated in carcinogenesis and the pathophysiology of diseases through upstream regulation of gene expression. DNAm deep-learning approaches are able to capture features associated with aging, cell type, and disease progression, but lack incorporation of prior biological knowledge. Here, we present modular, user-friendly deep learning methodology and software, *MethylCapsNet* and *MethylSPWNet*, that group CpGs into biologically relevant capsules – such as gene promoter context, CpG island relationship, or user-defined groupings – and relate them to diagnostic and prognostic outcomes. We demonstrate these models' utility on 3,897 individuals in the classification of central nervous system (CNS) tumors. *MethylCapsNet* and *MethylSPWNet* provide an opportunity to increase DNAm deep learning analyses' interpretability by enabling a flexible organization of DNAm data into biologically relevant capsules.

Introduction

DNA methylation (DNAm) is a key epigenetic regulator of gene expression in health and disease states, processes of aging and cellular differentiation/stemness, and response to environmental exposures [1–3]. DNAm of cytosine in the context of cytosine-guanine dinucleotides (CpG) sites can be measured with standardized genome-scale oligonucleotide bead-arrays at hundreds of thousands of sites [4,5]. Though a CpG is either unmethylated or methylated, fluorescence signal intensities from array measures of bulk biospecimen DNA are used to derive a beta value measure that approximates the proportion of methylated DNA copies. Gene promoter CpG island methylation is associated with repression of transcription, whereas unmethylated CpG islands are permissive to gene transcription. Alterations to DNAm have a well-established role in

carcinogenesis and tumor progression, including inactivation of tumor suppressor genes, aberrant

oncogene expression, and loss of repression of repetitive element sequences that contribute to

genomic instability [6,7].

The World Health Organization Central Nervous System (CNS) tumor classification includes

over 38 tumor types defined by histopathological features [8]. Most of the 38 can be grouped

into the broader glioma, ependymoma, and embryonal tumor types. Within those three

categorizations, over 80 further delineations are specified by molecular subtyping. DNAm

alterations have been heavily implicated in the development and prognosis of CNS tumors. For

instance, epigenetic silencing of *MGMT* is associated with an improved response to

chemotherapy in glioblastoma patients through the deactivation of crucial DNA repair

mechanisms [9]. *IDH* mutations are associated with improved survival in glioma patients

through subsequent global hypermethylation of CpG island promoters, known as induction of the

CpG Island Methylator Phenotype (CIMP) [10–13]. Other examples include hypermethylation of

Wnt and Shh pathways in medulloblastoma patients [14]. The success of differential methylation

analyses in characterizing CNS tumors has recently led to the development of DNAm classifiers

of brain tumors as companion diagnostic tools to understand and correctly diagnose challenging

histologic cases and for the selection of targeted therapies [8].

While the development of this methylation-based brain-tumor machine learning classifier has

been heralded as an improvement, existing diagnostic framework clinically applicable classifiers

use only a small subset of measured CpGs (e.g., 10,000) [15]. Incorporating additional CpG

predictors may allow for the resolution of tumor classes otherwise not identified and help

understand relationships with outcomes [16]. This problem may be better approached using

machine learning analyses by merit of their prohibitive dimensionality. Deep learning algorithms

are a subclass of machine learning approaches that are based on the use of artificial neural

networks (ANN) [17–19]. Multi-layer perceptrons (MLP) represent a subclass of neural

networks that treat the input data as a one-dimensional vector and then pass the information from

one set of nodes to a subsequent set of nodes through fully connected layers of

weights/parameters. The information at the subsequent layer of nodes is transformed using non-

linear transforms/activations/link functions. These types of analyses are common for deep

learning analyses of DNAm data, where the input data is a list of beta values for each subject

[20].

DNAm deep learning frameworks, e.g., MethylNet, can accurately characterize tissue, disease

states and infer subject age and cell type proportions through unsupervised embedding,

generation, classification, and regression tasks [20–24]. They also attempt to ascribe important

methylated loci using model interpretability frameworks such as SHAP [25] or LIME [26].

While the inclusion of more CpGs presents an opportunity to expand the space of biologically

testable hypotheses [20], statistical challenges (e.g., multicollinearity) with interpretations and

generation of associations with pathways remain understudied [27].

Multicollinearity, the unusually high correlation between features, can be addressed with careful

feature-selection or grouping [1,28]. Feature selection methods and statistical learning methods

such as sparse Group LASSO and network regularization have identified important CpGs in

highly complex data [29–33]. More recent work has called for a greater understanding of

DNAm-DNAm interactions' implications through the incorporation of Gaussian Graphical

Models, Canonical Correlation Analysis, and module discovery through weighted gene co-

methylation networks [34–50]. There is growing support for the use of novel deep learning

methods to aggregate, group, and select CpGs by their local context (e.g., genes) to connect and

interpret the data with clinical outcomes [51–53]. Incorporation of prior biological knowledge

improves the transparency and interpretability of the modeling approach and reduces noise while

increasing signal by meaningfully pruning redundant relationships between predictors [54].

Capsule networks have served as inspiration for methods that group CpGs to harness their

statistical interactions and relate predictors' groupings to clinical and biological outcomes [27].

Capsule networks explicitly model the relationships between constituent parts/groups of

predictors, or capsules, through parameterizing pose matrices (unitary transformations) and then

hierarchically associate each of these parts independently to higher-order targets of interest.

While capsule networks are primarily featured in the computer vision domain, evolving methods

within different biomedical specialties often utilize grouped organization of predictors in the

neural network design [55].

Here we provide a deep learning framework for methylation data that draws inspiration from

capsule networks. We investigated the organization of CpG features into DNAm capsules, which

represent local contexts that can be related to one another. *MethylSPWNet* and *MethylCapsNet*

organize sets of CpGs into a series of capsules defined by higher-order genomic contexts and

performs classification tasks (Figure 1A, B). To bring additional interpretability to existing deep

learning approaches while capturing hierarchical association networks, we propose and explore

MethylSPWNet (Sparse Pathway Network) and *MethylCapsNet* as deep learning analogs of these

enrichment tests. We provide recommendations for developing these capsule and network-

deriving models and provide open-source software for training these models. The

MethylCapsNet framework proposes to expand the broad utility of these tools by allowing end-

users to construct their unique capsules that represent an array of biologically plausible contexts

that further explain their target of interest.

134
Figure 1: Description of Modeling Approaches: A) *MethylCapsNet* separate MLPs are utilized to form
capsule level embeddings from beta values of CpG groupings, which are then associated with outcome
targets of interest through dynamic routing of information; these embeddings may be studied to propose
networks based on co-methylation on the individual level; B) *MethylSPWNet* aggregates the beta values
of groups of CpGs through one locally connected layer; nodes of the resulting layer represent biologically
meaningful units that are passed through an MLP for final prediction; group L1 penalties are applied to
prune genes/capsules potentially unrelated to the outcome; red colors indicate beta values for CpGs,
which serve as input to the algorithm

Results

To illustrate the potential utility of capsule-inspired neural network approaches, we revisited the

Capper et al. [8] dataset used to train a model that differentiates CNS tumors [56]. CNS tumor

histology is largely characterized by the presence or absence of morphologically distinct cells of

origin, including neuronal, astrocytic, microglial, oligodendrocytic, and Schwann cells. We

aimed to predict the 38 histological subtypes of CNS tumors (39 classes, including controls) as a

test case for the capsule-inspired neural network approaches. While distinct cell types may

characterize these histological subtypes, it was not our aim to classify these cell types through

this modeling approach, as methods for brain cell type estimation using DNAm data are still

under development. We compare the *MethylCapsNet* and *MethylSPWNet* frameworks for capsule

organization with the existing *MethylNet* framework (which does not account for Capsule

organized information [20]) and a Random Forest model fit on 10k important CpGs derived

using a previously established method (*Random Forest 10k*). Additionally, we provide a Random

Forest model on the capsule-organized information extracted from *MethylSPWNet* (*Random*

Forest Capsules). Additional details of modeling approaches, fitting procedures, and capsule

selection are in the Methods section.

Capsule Generation for CNS Tumor Prediction

Capsules may be supplied to the neural network approaches in the form of annotations and/or

gene sets from MSigDB and GSEA: 1) genes, 2) sites upstream/downstream of the gene, 3) the

following Illumina methylation array annotations – UCSC_RefGene_Name,

UCSC_RefGene_Accession, UCSC_RefGene_Group, UCSC_CpG_Islands_Name,

Relation_to_UCSC_CpG_Island, Phantom, DMR, Enhancer, HMM_Island,

Regulatory_Feature_Name, Regulatory_Feature_Group, and DHS – and 4) the following GSEA

gene sets: C5.BP, C6, C1, H, C3.MIR, C2.CGP, C4.CM, C5.CC, C3.TFT, C5.MF, C7, C2.CP,

C4.CGN. Importantly, users can also input custom capsules into the pipeline through a dictionary

that maps CpG to a context name of choice. Finally, capsule generation has been integrated with

BedTools [57] (*genomic_binned* selection), which can break up the entire hg19 genome into

overlapping windows of fixed width. CpGs in these windows will belong to these capsules. We

utilized gene capsules for the primary classification study, though alternative methods for

capsule formation are explored in section "Exploration of Alternative Capsule Formations and

Cancer Subtypes."

Classification Study

178   **Table 1:** Classification Results for Random Forest Approaches, MethylNet, MethylSPWNet, and
179   MethylCapsNet*

Approach	Accuracy±SE	Recall±SE	Precision±SE	F1-Score±SE
Random Forest 10k	0.96±0.007	0.98±0.012	0.93±0.013	0.95±0.012
Random Forest Capsules	0.94±0.0087	0.97±0.016	0.91±0.017	0.93±0.016
MethylNet	0.97±0.0061	0.99±0.0099	0.96±0.011	0.97±0.011
MethylSPWNet	0.98±0.0049	0.96±0.0088	0.96±0.0085	0.96±0.0089
MethylCapsNet	0.98±0.0044	0.98±0.012	0.98±0.01	0.98±0.011

180   *All scores are reported as macro-measures across all subtypes; 95% confidence intervals estimated using 1000-sample non-parametric bootstrap
181

We trained each of the modeling approaches to differentiate 38 histological subtypes of CNS

tumors and compared their classification performance via a 1000-iteration non-parametric

bootstrap of F1-scores over the test set, which balances sensitivity and specificity and reduces

the bias in output. Our results indicate that *MethylNet*, *MethylSPWNet*, and *MethylCapsNet* can

achieve very similar high performance on a common data set (Table 1). The neural network

approaches achieved marginally better performance than the Random Forest approaches. A

breakdown of classification scores for the capsule-inspired models has been included in the

supplementary material (Supplementary Table 1). Since all three neural network approaches

offer similar performance on classifying brain tumors, we next sought to uncover overlap or

complementary insights provided by each modeling approach based on their data organization.

The high predictive accuracy of both capsule approaches provided grounds for exploring the

factors related to its decision-making process for increased transparency and validation of our

approach.

Clustering Gene-Level Brain Cancer Embeddings

Until this point, our unit of analysis has been individual CpGs. Summarizing gene-level

methylation using median or mean methylation is generally not appropriate. The relationship

between methylation state and gene expression can vary depending on the genomic context (e.g.,

promoter and gene body). However, while training *MethylSPWNet* to predict tumor histological

subtype, the model learns to generate gene-level summaries of methylation by updating the

weight of each CpG when aggregating beta values of CpGs on the gene-level (See Methods

"Description of MethylSPWNet"). This gene-level aggregation can transform a design matrix of

samples by CpGs into samples by genes. Gene-level embeddings correlated with outcome (here

tumor histological subtype), can then be interrogated for their relationship with known pathways

and gene networks. To visualize gene-level embeddings, we generated cluster heatmaps, where

rows constitute observations and columns comprise genes, showing plots of the top 2000

variable genes from neural network gene-level embeddings (Supplementary Figures 1-2).

To assess the representation capacity of MethylNet, MethylCapsNet, and MethylSPWNet

embeddings, we clustered embeddings with histologic tumor subtype, cell of origin, and

histological subtype with the molecular subclass (Supplementary Table 2). Preliminary

clustering of the observations demonstrates, for instance, the inability to differentiate *IDH*

mutant subtypes of glioma when defined by median methylation versus the neural network

parameterization. There is observed concordance between hierarchical clustering in this

embedding space and the brain cancer subtypes. This concordance is defined by their molecular

subtypes, the original histological subtypes that the model was trained on, or higher-order cells

of origin (e.g., mesenchymal, ependymal, neuro-glial origin). *MethylSPWNet* had the highest

degree of concordance with histological and molecular subtypes within the gene-level

embedding space [58] (V-Measure 0.72±0.0059; Supplementary Table 2). The ability to

recapitulate relevant histological subtypes of CNS tumors through the embeddings alone is

further corroborated by embedding plots [58]. In these, MethylCapsNet appears to generate the

best separation and differentiation of subtypes (Silhouette Score: 0.52±0.0048), followed by

MethylNet (Silhouette Score: 0.25±0.01), and MethylSPWNet (Silhouette Score: 0.1±0.0087),

estimated using a 1000-sample non-parametric bootstrap. Since these three approaches were

trained to recognize histological subtypes, the signal of the cell of cancer origin and molecular

subtypes were less well captured.

Gene-Level and Modularity Enrichment Analyses

Next, we aimed to evaluate the utility of the group-regularized deep learning approach for

capsule-organized summaries of DNAm on the gene-level for pathways and gene network

analyses. We performed a preliminary analysis of pathway and module detection based on the

extraction of hypervariable genes across the neural network embeddings and Louvain clustering

of networks of genes based on the pairwise correlation between the genes. Further description of

the methods and results is provided in the supplementary material (Supplementary Table 3;

Supplementary Figures 3-4).

A description and flow-chart showing an overview of methods for pathways and gene network

analysis downstream from *MethylSPWNet* can be found in the Methods section "Description of

Potential Downstream Analyses." We focused our presentation of results on three specific CNS

tumor subtypes: glioblastoma (GBM), low-grade glioma (LGG), and medulloblastoma (MB).

Gene-level embeddings (gene by sample) and pathways and gene network analysis results

(derived from those embeddings) are shown in Figures 2, 3, and 4, respectively. Results on

pathways and gene network analyses for these three CNS tumor subtypes (GBM, LGG, and MB)

are provided in additional files 1-3. A description of the additional files may be found in the

supplementary materials (section "Description of Additional Files").

248
249 **Figure 2: Clustermap of gene-level embeddings for 2000 most variable genes in:** A) GBM; B) LGG;
250 C) MB. The left color track indicates the presence of the subtype; yellow indicates the presence of

controls; green, purple, and pink indicates the presence of the GBM, LGG, and MB subtypes,
respectively; columns have been standardized to highlight trends; in the heatmap, red indicates high
MethylSPWNet embedding values, while blue indicates low embedding values

Subtype-Specific Pathways Discovery

Using the gene-level *MethylSPWNet* embedding values, we sought to calculate differentially

embedded genes between disease and controls (empirical Bayes) and determine the associations

of these genes with some of their correspondent pathways (see Methods "Description of

Potential Downstream Analyses"). A visualization of pathway networks and output of gene-

subtype associations and pathway enrichment statistics are provided in Figure 3. The empirical

Bayes results of the differential embedding analyses for each subtype are provided as Additional

Files.

Our analysis of the selected three CNS tumor subtypes (GBM, LGG, and MB) found many top

differential genes have been implicated for these subtypes in prior literature. For instance, *TACC*

and *FGFBP2* (Figure 3B) are differentially embedded between GBM and controls and have been

implicated with a tumorigenic gene fusion event (*TACC-FGFR3* [59–61]). *RASGRF2* (Figure

3B) has been linked to congenital GBM [62]. *LGI2* and *NPY5R* (Figure 3B) have both been

related to changes in Sox2 expression [63], which promotes cellular plasticity in GBM. An

interesting associated pathway for GBM was type 1 diabetes mellitus (Figure 3A-B), an

autoimmune disease, of which its spurious association could be related to found associations

with several immune evading markers. For LGG, *TLK1* (Figure 3D), a serine-threonine kinase

associated with replication, focal adhesion, and cell cycle, has previously been implicated in

gliomas [64]. Similarly, low *ELL2* expression (Figure 3D), regulated by microRNA (miRNA)-

mediated gene silencing, was reported to be a marker for poorer survival in GBM patients [65].

GNL1 (Figure 3D) was found in our analysis to be associated with LGG and has been identified

as being related to cell proliferation, given its role in the phosphorylation of Rb [66]. We also

found associations with the Opioid-signaling pathway and G alpha (i) signaling events [67], and

the tyrosine kinase receptor pathway VEGFR (Vascular Endothelial Growth Factor Receptor)

and downstream signaling pathway ERK (Figure 3C-D), largely involved with proliferation and

angiogenesis [68]. Regarding MB, as examples, we uncovered *NRBP2* (Nuclear Receptor

Binding Protein 2; Figure 3F), which had been shown to be downregulated in MB[69], and

SOX14 (Figure 3F), part of the *SOX* family which largely determines cell fate and thus heavily

implicated across many CNS tumors[70]. Additionally, pathways such as Muscle Contraction

(Figure 3E-F) have been associated with specific molecular subtypes of MB [14,71].

Grouped-Subtype Pathways Discovery

Additionally, we investigated associations uncovered by grouping together a few select disease

subtypes. We would expect, at minimum, differences between these subtypes and healthy

controls to be related to pathways that are specialized to those larger histological groupings.

First, we compared melanoma-related CNS tumors (MELAN/MELCYT) to controls by

performing enrichment analyses of the top 40 differentially embedded genes, as defined by the

ranked p-values. As a few examples of potentially enriched gene sets across multiple databases

after Bonferroni adjustment, we found potential enrichment for MITF transcription factor targets

(*TRRUST*; p=0.06) and neural crest differentiation (*Wikipathways*; p=0.07), BMP signaling (*GO

Biological Processes*; p=0.03) and IL23-mediated signaling (*NCI-Cancer*; p=0.05). Of interest

from the ependymal tumors (EPN/SUBEPN) was that the top 40 genes had demonstrated overlap

with genes related to the spinal cord (*Human Gene Atlas*; p=0.03).

300
Figure 3: Example Output from Pathway Enrichment Analyses for: A-B) GBM-Control embeddings;
C-D) LGG-Control embeddings; E-F) MB-Control embeddings; left-side plots: corresponds to summaries
of GO/KEGG/Reactome enrichments using EnrichmentMap in Cytoscape, plotted via RCy3; each small
node corresponds to a pathway; node and text size proportional to the number of overlapping genes after
differential gene-level embedding analysis; edge between nodes corresponds to shared genes; large
ellipses correspond to found clusters using Markov Chain clustering, three words extracted to annotate

cluster using a word cloud algorithm; right-side plots: example output of differential embedding (*limma*)
and pathway enrichment analyses (g:Profiler) on embeddings; top 5 genes and select pathways listed of
the many uncovered in each analysis.
310

Derivation of Weighted Gene Co-Embedding Networks

To investigate the gene-level embeddings for each of the 38 brain cancer subtypes (paired to

normal controls), we derived disease-specific modules of genes using the Weighted Gene

Correlation Network Analysis (WGCNA) R package (see Methods "Description of Potential

Downstream Analyses") [48].

We derived 606 modules of genes across the 38 subtypes (37 networks were derived, one

subtype was omitted for low sample count), 297 of which were significantly associated with

subtype (all P-values < 0.05). We have included as Additional Files the module membership of

each of the genes, module expression across the samples for the three example subtypes (GBM,

LGG, MB), hub genes for each module (genes located most centrally in each subnetwork), and

statistics that relate each module to the subtype. The connectivity of individual genes from the

generated WGCNA modules for GBM, LGG, and MB subtypes are shown in Figure 4. Tables of

top hub genes from selected modules strongly associated with each subtype are shown.

Some of the WGCNA modules' hub genes were found to be correspondent with prior knowledge

about their respective subtypes. In GBM, *RASGRF4* (blue module; Figure 4A-B) was previously

featured in Figure 3B. The silencing of *MGMT* (green module; Figure 4A-B) plays a significant

role in the progression of GBM through inactivation of its DNA repair mechanisms [9]. *MIR33B*

(brown module; Figure 4A-B) is also related to GBM progression by regulating cell

proliferation, invasion, migration, and MYC signaling [72,73]. Finally, the role of platelet factors

(*PF4*; blue module) and CpG island hypermethylation (homeobox gene *BARHL2*; turquoise

module) has previously been implicated with GBM [74,75]. Examples of hub genes in LGG

include *NRP1* (black module; Figure 4D) [76], *PTPRZ1* (pink module; Figure 4D) [77], and

COL6A3 (green module; Figure 4D). *NRP1* has been shown to be related to poor prognosis in

gliomas and signals through microglia/macrophages. *PTPRZ1* has previously been related to

malignant growth in GBM. Finally, *COL6A3* is a member of genes serving to form the tumor

vasculature. Finally, of interest in MB were *SOX 14* and *SOX17* (green module; Figure 4F) [70],

*CD4 (*green-yellow module; Figure 4F*), SLIT3* and *GFPT2* (black module, Figure 4F) and

SYNPO (blue module, Figure 4F). *CD4* is a gene that codes for the membrane glycoprotein of the

CD4 T-cell, where its characterization could be corroborated by the immune infiltration patterns

of the stroma for MB. *SOX14* and *SOX17* are pertinent for cell fate lineage. *SLIT3* is a gene

characterized by axon guidance and consequently tumor growth, migration, and angiogenesis.

Interestingly, *GFPT2* (amino acid metabolism), implicated with higher expression and lower

GBM survival [78]). *SYNPO*, central to the black module of MB, were also central to the blue

module of GBM.

B — GBM Significant Module Hub Genes

Description	blue	green	brown	turquoise
p-value	9.5e-37	6.5e-18	2.3e-11	3.5e-12
Correlation with GBM	0.81	0.62	-0.5	-0.52
Hub Gene 1	GFPT2	TNFRSF6B	MIR33B	LYRM4
Hub Gene 2	SYNPO	C3orf20	TSR3	PABPC3
Hub Gene 3	ENPEP	TSLP	LOC285796	LOC402778
Hub Gene 4	PF4	MYOM2	SERF2	BARHL2
Hub Gene 5	LOC285501	LOC220930	ADPRHL1	FAM71F1
Hub Gene 6	LRRC14B	PLA2G2D	ADCK2	DNAH1
Hub Gene 7	TRAM1L1	CDH23	NCS1	GALR2
Hub Gene 8	RASGRF2	MGMT	IL31	KLK6

D — LGG Significant Module Hub Genes

Description	pink	green	blue	black
p-value	1.7e-09	1.4e-06	4.8e-08	9.7e-12
Correlation with LGG	0.55	0.45	-0.51	-0.61
Hub Gene 1	PTPRZ1	COL6A3	PABPC3	NRP1
Hub Gene 2	MLST8	FLJ36000	PC	TMPRSS4
Hub Gene 3	MAP10	ATP6V0A4	PALMD	IGDCC4
Hub Gene 4	FCGR2A	METTL9	CTBP1	WFIKKN2
Hub Gene 5	C17orf99	C10orf71	SLC25A18	COL17A1
Hub Gene 6	FOXI2	GABBR2	GFRA4	ADPRHL1
Hub Gene 7	DNAJB8	CTSF	MIR486-1	MELTF
Hub Gene 8	SULT1A2	ERBB4	ASXL2	MIR134

F — MB Significant Module Hub Genes

Description	black	midnightblue	greenyellow	green
p-value	7.5e-47	1.9e-23	6.1e-29	2.9e-48
Correlation with MB	0.9	0.75	-0.8	-0.91
Hub Gene 1	GFPT2	GGACT	CD4	SOX17
Hub Gene 2	SLIT3	FOLR1	ST6GALNAC5	R3HDM2
Hub Gene 3	PDCD6	SCGB1D4	HSPB8	LHX1
Hub Gene 4	PCDHGA9	ADGRF2	RASSF9	AIFM2
Hub Gene 5	ENPEP	HEATR4	LIMS2	PPP4R3C
Hub Gene 6	ZAR1	COL7A1	MYPN	MIR196A2
Hub Gene 7	SYNPO	CPED1	LOC399815	SOX14
Hub Gene 8	C5orf52	CHD8	PANX2	ABCA2

Figure 4: Example Output from WGCNA Analyses for: A-B) GBM-Control embeddings; lack of connectivity between the blue/black modules and the other models suggests lack of functional relationship; C-D) LGG-Control embeddings; E-F) MB-Control embeddings; left-side plots: summarized gene-gene networks using the MAPPER algorithm; nodes indicate genes or dense grouping of genes; colored by discovered module via WGCNA; edges indicate co-methylation; right-side plots: example output from WGCNA analysis; the subset of gene-gene modules; p-value indicates whether significantly associated with tumor subtype; correlation value indicates directionality and strength of this relationship; select hub genes indicate genes with the highest centrality in each subnetwork/module.

Enrichment of Neural Network CpGs for Gene and Island Contexts

As Weighted Gene Correlation Network Analysis (WGCNA) identifies significant associations with known pathways and novel gene-gene co-methylation networks, we sought to investigate the CpG-specific parameters that corresponded to producing the embeddings to understand better why the neural network decided to upweight some CpGs, but not others. To elucidate the genomic contexts that *MethylSPWNet* found to be important, we explored the CpG island context and spatial relationship to the transcriptional start site (TSS) (Methods section "CpG Island/Gene Context Analysis"). CpG islands (CGI) are CpG dense regions. Approximately 60% of gene promoters contain CpG islands[79]. CpG shores immediately flank the CGIs by up to 2kb, shelves flank the shores by an additional 2kb, as regional CpG density decreases. Variables for the spatial relationship to the TSS include TSS1500 and TSS200, within 1500 bp and 200 bp of the TSS, respectively. Additional TSS variables are the 5'UTR immediately downstream of the TSS, the first exon, gene body, and 3'UTR.

Of note, we found that CpGs with positive weights (rank-ordered) were depleted for promoter island regions (defined as having TSS1500/TSS200 annotation and not open sea) (OR=0.69; p=0.04) as compared to sites not included in promoter-island regions (OR=1.45; p=0.04). However, when limiting the set of CpGs to only promoter regions (i.e., TSS1500/TSS200), we noted that positive weight CpGs were enriched for island context (i.e., not in an open sea region) (OR=1.21; p=0.03), while negative weight CpGs were depleted for the CGI context (OR=0.89; p=0.02). Furthermore, both the positive and negative weights of intragenic CpGs were depleted for association with the correspondent methylated promoters (as compared to unmethylated promoters) for their respective genes (positive weight OR=0.54, p<0.01; negative weight

OR=0.44, p<0.01). We have included tables for the relationship between CpG weight and

independently considered contexts in the Supplementary Materials (Supplementary Table 4;

Supplementary Figure 4).

MethylCapsNet Module Enrichment

From the embedding module discovery analysis and further contextualization of the neural

network CpG-weights, we observed that information encoded in *MethylSPWNet* corresponds to

key pathways associated with various CNS tumors and important genomic contexts.

MethylCapsNet offers the ability to infer more granular relationships between capsules on the

individual sample level when we can reduce the number of parameters specified. The primary

capability and emphasis of the capsule-inspired network approach is to compare capsules to each

other and directly relate them to particular outcomes of interest via the dynamic construction of a

bipartite network (gene-subtype relationships) as part of the training and prediction process. For

the *MethylCapsNet* analysis, we pre-selected a subset of genes previously shown to be implicated

in various types of brain cancer (see "Selection of Capsules for *MethylCapsNet* and

MethylSPWNet" in Methods). As such, we believe it would not be appropriate to test for

enrichment of these genes due to the pre-selection procedure that introduces a bias. Instead, we

derived modules of genes that the neural network deemed to have a coordinated DNAm response

in elucidating particular subtypes. Our modularity analysis projects the estimated bipartite graph

(gene-subtype) across samples into a univariate graph (gene-gene), then clusters the graph using

Louvain modularity to yield four modules of genes (green, red, blue, yellow) (Figure 5).

Here, we offered an example of the kinds of inferences that can be made from the resultant

unipartite network and subsequent clustering. For instance, the yellow module implicates

relationships between *WNT3A* and *EGFR*, heavily implicated in Igf and Wnt signaling. The red

module features the relationship between *FRZ* and *APC*, both of which are heavily involved in

WNT signaling (*APC* forms the complex to inhibit the accumulation of β-*catenin*, while WNT

binding to frizzled family receptors may degrade this inhibition and permit cell proliferation

[80]). Of the green module, *IDH3G* and *NPR3* (linked to energy metabolism, gene fusion, and

chromatin remodeling) were related to both *LRDD* (pro-apoptotic *MAPK* pathway) and *WIF1*

(both previously implicated WNT signaling suppressors) from the yellow module. *KIAA1549*,

related to astrocytomas and fused to *BRAF* for its progression to oncogenesis, was implicated

with *WNT1* in the blue module [81]. Insulin-like Growth Factor Binding Protein 2 (*IGFB2*;

glioma oncogene) of the red module appeared to be negatively correlated with many of the genes

across the yellow and green modules[82]. *TP53* (which lacked consequential methylation

patterns) and *MYC* [83], *MGMT,* and *TERT* share relationships with each other but not with the

other modules, perhaps highlighting how ubiquitous these somatic alterations are for

oncogenesis.

418
419 **Figure 5:** Clustermap of weighted bipartite network projection of select gene capsules' relationship to
420 various CNS tumors using the *MethylCapsNet* modeling approach; rows and columns are genes, row
421 colors denote modules (green, red, blue, yellow) of genes found using Louvain modularity; values in
422 matrix denote Pearson's correlation between genes
423

Despite having highlighted potentially interesting relationships, we acknowledge that there will

be a future opportunity to increase the search space of possible relationships between genes and

their coordinated response for bringing about subtypes of brain cancer. In the Supplementary

Material, we provide the routing matrix that was used to align each gene to a correspondent CNS

subtype, which is the predicted gene-subtype bipartite network averaged across individuals

(Supplementary Figure 5). We have also provided a locally deployable web application that

allows the user to interrogate their uncovered capsules and form networks on the individual level

and aggregated across patient subgroups or disease subtypes using gene-capsule-specific

embeddings (Supplementary Figure 6). For instance, in our supplemental material, we

demonstrate how the *MethylCaps* web application can be used to derive individual networks for

LGG and GBM, identifying *ANO9* and *EGFR,* respectively, as implicated in these conditions

(Supplementary Figure 7-8). These genes and their associated pathways have been heavily

implicated in tumorigenesis and gliomas [84,85].

Exploration of Alternative Capsule Formations and Cancer Subtypes

In this section, we briefly present results from a few of many alternative means of forming

capsules. Particularly, we consider the following scenarios for CNS tumor classification: 1)

MethylCapsNet is fit when a) only half the genes are retained from the original list (selected

randomly) and b) none of the genes are retained and instead randomly sampled from all genes

and 2) *MethylCapsNet* is fit using binned genomics regions, utilizing CpGs encapsulated in 1Mb

bins. In addition to these analyses, we also explore an integrated breast cancer dataset utilized for

PAM50 molecular classification[20,86,87] using a few different capsule configurations: 1)

MethylCapsNet is fit using a curated list of genes, 2) *MethylCapsNet* is fit using binned genomics

regions, utilizing CpGs encapsulated in 700kb bins, and 3) *MethylSPWNet* is fit using capsules

organized by CpG island promoters, formed by intersecting CpG island with gene promoter

annotations from the Illumina 450k database. A complete set of results can be found in the

supplementary material (Supplementary Tables 5-6; Supplementary Figure 9).

Discussion

Recent reviews and initial explorations discussed the potential utility of capsule-inspired

networks to relate biologically-organized capsules to each other and known disease outcomes

[27,88–90]. In this work, we set out to perform a preliminary evaluation that shows the

feasibility and suitability of DNA methylation capsules for deep learning analyses as a means to

organize CpG information to higher-order contexts to improve prediction and transparency while

uncovering instances of coordinated gene-level methylation patterns. In our analyses, we

compared several state-of-the-art predictive modeling methods for DNA methylation

classification of brain tumors. We demonstrated that capsule-based deep learning approaches

could achieve performance on par with existing deep learning models and prove better than

existing traditional machine learning frameworks for analyzing DNA methylation data. Our work

demonstrated the potential for new insights compared to other existing methylation-based tumor

classification schemes currently used, which are often based on a small subset of CpGs, and lack

built-in interpretation of the loci selected[8,91]. We demonstrated the efficacy of increasing the

use of the available CpGs on the Illumina 450k Array, ultimately using 200,000 loci before sub-

setting by context.

DNA methylation capsules focused on the gene level can disentangle important CpGs that might

otherwise be down-weighted in a feature-by-feature deep learning unsupervised or supervised

learning approach. These CpGs demonstrated substantial overlap with genes known to be related

to tumorigenesis in the brain, such as *NOTCH1*, *PTEN*, and *GNAS*. This is consistent with

previous studies that demonstrated mutations common in brain tumors, such as *IDH1*, are

correlated with disruptions in methylation.[10,92–97]

The context-specific CpG weight enrichment analyses suggest that within promoter regions,

island context is important for differentiating different CNS tumor subtypes, but taken as a

whole, regions outside of CpG promoter islands are important for capturing this heterogeneity.

Furthermore, outside of the promoter context (supposedly regions that better capture tumor

heterogeneity), the ability of intragenic CpGs to distinguish tumor subtypes is still dependent on

the promoter methylation status of the respective gene. Clustering of CpGs with the highest

weights at CpG islands, shores, gene bodies, and transcription start sites will help us understand

where the most diagnostically relevant sites are in the genome, but demands additional

investigation.

We also presented a few examples of the potential downstream applications of capsule-based

approaches. In particular, our framework demonstrated the ability to relate derived gene-level

measures of *MethylSPWNet* to known disease pathways via differential methylation analysis of

the gene-level embeddings and gene-gene co-methylation networks via WGCNA. Additionally,

we provided a preliminary interpretation of bipartite (gene-subtype) and unipartite (gene-gene)

networks, which can be derived by *MethylCapsNet* web framework. Finally, we explored

alternative means from which to form capsules. We expected the curation of genes to lead to

more accurate models. Contrary to our initial hypothesis, for CNS classification, random

capsules' selection appeared to still produce a highly accurate model. These results suggest either

the potential to uncover novel associations between genes and subtype or that these genes may

be co-methylated with other genes that have well-established relationships. The binned

genomics, fit using *MethylCapsNet* for classification tasks in brain and breast, were similar to the

leading methods. The island promoter capsules slightly underperformed, suggesting that these

capsules' selection alone does not contain enough information to distinguish PAM50 molecular

subtypes.

There are a few limitations to this work, presenting room for future improvements in the

analytical method. First, the included CpG loci selection is biased on limited sites available from

the Illumina Array platform. At present, the utilization of an Illumina methylation array platform

is more tractable due to lower technology costs and expertise required [98] than Whole Genome

Bisulfite Sequencing (WGBS) that requires substantial sequencing depth on the order of 100x for

comparable precision [99].

Second, a reduced set of genes were fit using the capsule-inspired network. It remains

challenging to run MethylCapsNet at scale due to the heavy computational demand and the large

number of free parameters in its current formulation. Since *MethylCapsNet* can only analyze

approximately one thousand capsules at a time, the capsule selection step is critical to the

method's successful application. This parameter space should be reduced by finding some

marriage between the scalability enabled by *MethylSPWNet* and perhaps greater transparency

offered by *MethylCapsNet*. Presently, we advise end-users to utilize *MethylSPWNet* when the

number of contexts under evaluation is large ($\geq$1000 capsules), or if the number of CpGs per

gene is small, and to utilize *MethylCapsNet* when the number of contexts under consideration is

smaller (<1000 capsules). Uncurated gene sets can be analyzed using *MethylSPWNet*, while

curated gene sets are best suited to *MethylCapsNet*, e.g., regions of the genome fragmented by

consistent windows or larger DNAm CpG modules that have been uncovered through methods

such as WGCNA. In addition, the adoption of capsule-inspired approaches that explicitly form

networks via their routing mechanisms presents a future area of research [89]. It is also assumed

that *MethylCapsNet* capsules that are more closely embedded are interacting, but it is not entirely

clear the nature of these interactions without incorporating gene expression data and methylated

Quantitative Trait Loci analyses.

While inspired by capsule networks, we also emphasize that these methods are not analogous to

capsule networks featured in computer vision tasks. While the new capsule-based approaches

were as accurate as fully connected approaches, this was done so under the constraint of sparse

connections, where such specification points to the validity of imposing these constraints. Given

the nature of the problem (classification amongst dozens of histological subtypes), intermediate

embeddings may reflect a more linearly separable subspace to subtypes of origin. Such a

subspace may require additional exploration/penalization to avoid potential biases pertaining to

the minimal redundant set of predictors to produce a subspace optimal for prediction. The

application of such methods does not preclude the potential for selection of genes due to

technical reasons such as noise, batch effects, and weight initializations, which are common to

many domains of application of neural networks. We attempted to account for such biases

through preprocessing methods on the data such as functional normalization and note that strict

interpretation of threshold cutoffs for methods devised for differential gene expression may not

be applicable. Thus, relaxation of the scope of features input into a pathway and other

enrichment analyses may potentially reduce bias so as long as limitations are appropriately

stated. Additionally, differences in tissue preparation (frozen, permanent) were not accounted

for, and however, given the high concordance between these preparation methods, we felt that

such adjustment was not necessary [100].

While DNAm deep learning methods with built-in interpretability do not yet exist, we hope these

methods, though constrained by potential limitations in design choice, may spur further research

into more interpretable capsule methods. Here, there is also an opportunity to further apply

concepts from topological data analysis (TDA), such as Mapper[101–105], to distill the key

functional relationships from high-dimensional, complex data.

Existing classification frameworks currently used in the clinical setting for aiding brain cancer

diagnosis only utilize a small subset of the total possible set of CpGs that can be measured.

Current modeling approaches can be difficult to trust or use to study new network biology until

they can consider a larger, more complete set of predictors. However, it is also important to note

that doing so would introduce additional noise into the modeling approach, but the incorporation

of prior biological knowledge can potentially help reduce noise while improving the detection of

biologically relevant signals. We note that underperformance could suggest selecting capsules

that may not be optimally aligned to the target task/dataset. By demonstrating that the

organization of CpGs into their respective genomic contexts, we present further opportunity to

reduce the feature space and disentangle correlation and collinearity between CpG sites to create

a new class of transparent, clinically tractable models. For instance, future classifiers should

include brain cell-type classification using DNAm data and incorporate it as covariates in the

prediction model, yet brain cell-type differentially methylated regions for deconvolution by

DNAm patterns is not well-established. The opportunity space of epigenetics research questions

is ample and poised to grow substantially as the field moves to expand reference-based

approaches to cell type deconvolution, include tandem assessments of other cytosine

modifications (hydroxymethylcytosine), and apply DNA methylation age clocks to questions of

biological aging. Despite having demonstrated the promising downstream analyses that users

may readily adopt through our framework, we acknowledge that there is ample opportunity to

develop related methods and their use cases further.

Conclusions

Here, we have demonstrated the feasibility and utility of DNAm based capsules for performing

disease classification and potentially determining dysregulated genes for these diseases. We

found that DNA methylation capsule methods can predict brain cancer subtypes with high

accuracy and present convenient means for organizing data over traditional techniques for

studying DNA methylation data. As such, we advocate for the organization of well-defined

DNAm capsules as a means to improve the accuracy, transparency, and broad applicability of

DNAm deep learning models. Future deep learning prognostic models that reimagine the

formation and incorporation of DNA methylation capsules, paired with cell type inference, gene

expression, and/or corroborating chromatin capture, may serve as grounds for the derivation of

unknown heterogeneity.

Methods

Overview of Framework

The *MethylCapsNet* methodology presents an extension of the *MethylNet* framework [20] and is

implemented as a command-line interface that allows the user to group CpGs into capsules and

then dynamically route the capsules to make a prediction and interpret the results. While this

approach draws inspiration from capsule networks featured in computer vision tasks,

MethylCapsNet is not explicitly a capsule network, as defined in previous works in this domain.

MethylCapsNet utilizes separate MLPs for every set of CpGs (one set per context) to derive

context-specific embeddings (separate context embeddings per each individual), and dynamic

routing processes force information from child capsules into disease/categorical outcomes

(Figure 1A). The information is hierarchical because each child capsule may only align with one

parent capsule. Once the capsule-inspired network is fit, graph structures that describe the

relationships between each individual's contexts can be derived by thresholding the correlation

between pairwise n-dimensional context embeddings. Highly conserved biological networks can

be derived by thresholding the number of individuals that share the same edge between the

contexts. The simplest genomic context considered are genes that the CpGs annotate to. Other

capsules can be defined by, for instance, genomic region or pathway/biological process

annotation. *MethylSPWNet* is a specialized neural network architecture that routes beta values

from the CpGs in each context into a single node representing the context (Figure 1B). Each

CpG is given a weight based on the importance of its contribution, both on the gene level and

towards the classification task as a whole. This information passes through additional neural

network layers that dynamically relate latent sets of predictors to outcomes of interest, whether

they be prognostic or diagnostic [53,106]. Much like Group LASSO approaches, group L1-

penalization can be utilized on the CpG weights routed to each gene to select relevant genes of

interest.

612
Figure 6: Description of Framework: a) User selects capsules to group sets of CpGs from their own
supplied list or a prespecified annotation set; b) User selects modeling approach, *MethylCapsNet*,
MethylSPWNet, *Group LASSO*; c) Hyperparameter search conducted to reveal ideal model specification;
d) Final models are fit, and capsules are interrogated for relationships with one another, relationships to
the outcome, and highly weighted CpGs; yellow indicates an important capsule; *MethylCapsNet* relates

the Capsule to each other per individual; *MethylSPWNet* locates important CpGs within a capsule and
contextualizes its location; input data into the algorithm is colored red
620

621 The software implementation (Figure 6) is comprised of modules pertaining to prediction and

622 interpretation tasks, which take into account the relationships and embeddings derived through

623 the training process.

Data Preparation

DNAm data from CNS tumors (n=3,897) were accessed from the GEO archive (GSE109381),

preprocessed using *PyMethylProcess* [21], and divided into 70%/10%/20% training, validation,

and testing sets (*MethylationArray* objects) via *PyMethylProcess*. The 200,000 most variable

CpG loci across the training samples were retained for analysis. Sets of CpGs were tracked to

genes, which were then selected to form capsules. The original set of 200,000 CpGs was used as

features for the *MethylNet* approach, the complete set of intersecting gene capsules with more

than five associated CpGs were used for the *MethylSPWNet* (n=10,341; 139,028 CpGs), and

Group LASSO approaches, and a reduced set of capsules (n=55), were utilized for

MethylCapsNet after manual curation and a hyperparameter search (see "Selection of Capsules

for *MethylCapsNet* and *MethylSPWNet*").

Description of Potential Downstream Analyses

After fitting a *MethylSPWNet* model (and *MethylCapsNet*), the user may further interrogate the

gene-level embeddings depending on the research question being addressed. The user may

explore how each gene relates to each outcome or how they relate to one another, the details of

which have been included in an informative flow diagram (Figure 7) (separate text describing

information that can be extracted after fitting *MethylCapsNet* can be found in the section

"Description of Capsule-Inspired Neural Network").

Differentially embedded genes (the extent to which gene-level embeddings vary between

subtypes versus normal) from gene-level values derived by the neural network embeddings in

each of GBM, LGG, and MB, were identified using the *limma* [107] package. This package

compares tumor to nontumor control tissue through least-squares regression and empirical Bayes

moderated F-tests, yielding FDR-adjusted p-values and log-odds ratios for the degree of

differential embedding. We profiled functionally enriched pathways using the g:Profiler package

[108] after selection of genes below an FDR-adjusted significance threshold and visualized the

results (relating pathways by the number of shared genes, clustering into higher-order pathways

via Markov clustering) using EnrichmentMap, as part of the Cytoscape network visualization

framework [109,110].

The pairwise correlation between *MethylSPWNet*-derived gene methylation was calculated using

Pearson's correlation coefficient. Weighted adjacency matrices were calculated from the

pairwise correlation matrices for each of the subtypes using the power adjacency function, which

takes the co-methylation to a power specified separately for each subtype. To further cluster the

genes, the weighted adjacency is transformed into a topological overlap matrix (*TOM*), defined

by the extent to which two genes share a third common gene. Finally, hierarchical clustering is

applied to derive the final modules of genes. Finally, to relate each module with the disease

subtype via the aforementioned least squares and empirical Bayes differential analyses methods,

we calculated eigengenes (1st principal component) for the genes in each module to further

reduce the design matrix (samples by modules) [107]. A large number of genes (on the order of

five thousand) for such a summary gene network plot may make plotting the individual genes

cumbersome and hard to understand, so we utilized Mapper[101,103,104], a tool from

Topological Data Analysis, to further summarize and portray the relationships between the genes

in the network summary plot.

Figure 7: Flow Diagram for Possible Downstream Applications of *MethylSPWNet*: A) User fits *MethylSPWNet* model to predict brain cancer subtypes; B) gene embedding matrix (samples by genes; in this example GBM vs Control) is extracted from the model from the test samples; user decides whether they want to **(C-E)** associate gene-level embeddings with disease outcome, or **(F-H)** relate genes to one another to imply functional relationships; C) user opts for pathways analysis; *Empirical Bayes* method is used to identify genes with differential embeddings between GBM and controls using an empirical bayes moderated linear model; D) significant genes may be passed into g:Profiler or *limma*'s internal functions

camera, *goana*, and *kegga*, for pathways enrichment over GO, KEGG, Reactome, etc. databases; E)
pathways are summarized and visualized using EnrichmentMap, accessed via RCy3; F) user opts for gene
correlation analysis (WGCNA), first calculating correlation between genes, then calculating topological
overlap over correlation transformed by power, hierarchical clustering is applied to deduce modules; G)
gene-gene networks and module membership is visualized using Mapper; H) modules related to GBM are
extracted using the *Empirical Bayes* method by comparing projections into first eigengene (samples by
modules matrix) for each module for GBM vs controls
685

CpG Island/Gene Context Analysis

Using the MethylSPWNet, each CpG is assigned a weight that relates the CpG to its associated

gene or genomic context. These CpG weights are learned by the neural network and can be used

to rank genes based on their relative importance (rank assigned by maximum absolute CpG

weight), an alternative measurement to the modularity analysis. Inspection of the weights of

CpGs within each gene can provide insight into sites and contexts that are important for

predicting brain cancer subtypes. Further, investigation of weights spatially across the genome

may give rise to important patterns and motifs that could warrant future investigation. In the

supplementary material, we first considered the contexts mentioned above independently and did

not consider the joint impact of context (e.g., did not associate with island-promoter regions,

which are generally considered to be regions more causally related to changes in their

expression). We then considered sites that were associated with island promoter regions

(including shore and shelf context; more causally associated with gene expression) and

separately compared the overlap of the CpGs correspondent to top positive and negative weights

to the CpGs that were unassociated with this context (open sea and not TSS200/1500). We

separately considered CpGs within the promoter regions. Finally, we considered intragenic CpGs

and whether or not their corresponding gene's promoter was methylated or unmethylated (as

operationalized by calculating a beta-value methylation cutoff via local minima in the

distribution of beta-values. The beta-value distribution, bimodally distributed, reflects the

distribution of proportion of methylated alleles across a bulk mixture of cells for individual CpG

sites. This distribution across CpG sites is typically estimated per individual(s). Beta values can

take on values between 0 and 1, but particularly concentrate closer to 0 or 1 to reflect that a site

is either "methylated" or "unmethylated". The intermediate proportions reflect scenarios from

which around half of the cells of the mixture are methylated at that site, which is uncommon, and

used to as the threshold to denote whether a site is methylated. Any CpG with a beta value above

the threshold was methylated. CpG methylation was averaged across each promoter and subject

to the threshold to determine methylation status). We calculated odds-ratios for

enrichment/depletion in these contexts using Fisher's exact tests. Without matching gene

expression information, we could not make any causal claims/inferences about how these

contexts modify gene expression to bring about these disease states.

Description of Capsule-Inspired Neural Network

The capsule-inspired network featured in this work operates by first finding representations of

the given CpG sets as denoted by the primary capsule formation. The features, CpGs, of the CpG

sets are fed into parallel implementations of a multi-layer perceptron, f_j, where the output

dimensions of each of the neural networks are the same. Thus, the dimensionality of the primary

capsules reflects the number of output neurons, a latent representation of each CpG set, times the

number of capsules, per individual. The mathematical formulation of this transformation is

presented below:

725
$$\overrightarrow{z_{gene_J}} = f_j\left(\overrightarrow{x_J}\right)$$

726   For a single individual, the capsules, represented by row vectors, are stacked to form a capsule

727   matrix:

728
$$\overleftrightarrow{Z} = \begin{bmatrix} \overrightarrow{z_{gene1}} \\ \vdots \\ \overrightarrow{z_{genen}} \end{bmatrix}$$

729   An affine transformation transforms the primary capsules, a set of learnable parameters that seek

730   to rotate, scale, shift the data, and encode information pertaining to the interactions between

731   capsules.

732
$$\overleftrightarrow{Z_*} = \overleftrightarrow{W} \overleftrightarrow{Z}$$

733   Each primary child capsule's information is then dynamically routed to parent hidden or output

734   capsules.

735
$$\overleftrightarrow{Y} = \sigma(\overleftrightarrow{CZ_*}) = sq\left(\begin{bmatrix} \overrightarrow{y_{class\,1}} \\ \vdots \\ \overrightarrow{y_{class\,m}} \end{bmatrix}\right)$$

736   Where:

738
$$\overrightarrow{y_{class\,j}} = sq\left(\sum_i C_{genei,classj} \overrightarrow{z_{gene\,i}}\right)$$

Dynamic routing aims to force the information encoded into each child to align with one parent

capsule, thus utilized to calculate $\overleftrightarrow{C} = \{C_{ij}\}$, a bipartite network relating the child-parent-capsule.

A vector of the same length represents each child as the output of the parent capsule. Analogous

to the non-linear transformation of the sum of the information output from the previous layer of

neurons for traditional neural networks, for each parent capsule, the child-capsule values are

summed, and then a non-linear transform called a squash function, $sq(\vec{x}) = \frac{\|\vec{x}\|^2}{1+\|\vec{x}\|^2}\frac{\vec{x}}{\|\vec{x}\|}$, is applied

to effectively zero-out, or *squash*, child capsules that do not agree with parent capsules.

Each child's contributions to a parent are weighted, but two constraints are imposed: First, the

weights from each child to its parents must sum to 1. Second, a reward for the alignment of a

child to exactly one parent is a dynamic routing by agreement mechanism. An iterative process

updates the weights between the child and parent by adding their dot product. The update

mechanism for calculating $\overleftrightarrow{C}$ is recapitulated below. After initializing $\vec{C_\iota} = softmax(\vec{\beta_\iota} = \vec{0})$ for

$r \in \{1, 2, 3, ...\}$ iterations:

753
$$\vec{C_\iota} = softmax(\vec{\beta_\iota})$$

754
$$\vec{Y_J} = sq\left(\sum_i C_{genei,classj} \overrightarrow{z_{gene\ i}}\right)$$

755
$$\beta_{ij} = \beta_{ij} + \overrightarrow{Y_{classj}} \cdot \overrightarrow{z_{gene\ i}}$$

This formula is simplified from its original derivation and utilizes a few notational shortcuts.

Applying this operation for r iterations per batch per training epoch effectively prunes the other

connections between the child and its parents as it converges on a single parent from which to

send its information. Each output capsule per individual, $\vec{Y_J}$, is represented by a vector in some n-

dimensional space. The output capsule with the highest L2-norm, $\|\vec{Y_J}\|_2$, is selected as the

predicted class, and a margin loss is applied to penalize the model when it fails to either

concretely have a very high ($m^+ = 0.9$) or very low probability ($m^- = 0.1$) of prediction.

764
$$L_{margin:\ classj} = \delta_{y_i,j}\ max(0, m^+ - \|\vec{Y_J}\|)^2 + \lambda(1 - \delta_{y_i,j})\ max(0, \|\vec{Y_J}\| - m^-)^2$$

The Kronecker's delta $\delta_{y_i,j}$ is equal to one when the outcome for individual i is equal to the j-th

class, thereby activating the left-hand margin loss that penalizes the model if the probability is

below $m^+ = 0.9$. On the right-hand of the equation, $\delta_{y_i,j}$ is equal to zero when the outcome for

individual i is not equal to the *j*-th class, thereby activating the right-hand margin loss that

penalizes the model if the probability is above $m^- = 0.1$.

The model is also penalized based on how much the original methylation array could be

constructed from the true class's output capsule via a decoder neural network, $\hat{X} \sim p_\phi(\vec{X}|\vec{Y_j})$:

$$L_{reconstruct} \propto \left(\hat{X} - \vec{X}\right)^2$$

Of the most interest to a biologist may be the primary capsule embeddings per individual, $\overrightarrow{Z_*}$,

which demonstrate interactions between these biological hypotheses and how the outcome of

interest is separable within certain genomic context, and the weights between the primary and

output capsules, $\overleftrightarrow{C}$, a bipartite graph demonstrates how these genomic regions are related

hierarchically and have implications for parent processes. The coordinated response of capsules

can also be derived through a bipartite projection of $\overleftrightarrow{C}$ into a unipartite network of capsules.

Secondarily, of importance are the concatenation of the primary capsules, which demonstrate

overall class separation, and the decoded output. Tweaking the embeddings or L2 norm of the

output capsules and decoding can potentially effectively generate methylation data conditionally

on outcomes of interest and interpolate between purified states, though this aspect was

unexplored due to prohibitive dimensionality.

Description of MethylSPWNet

MethylSPWNet is the deep learning analog of a Group LASSO Regression model. The beta

values for the CpGs for each gene, $\overrightarrow{x_j}$, is transformed into a single value, z_{genej}, through the

multiplication of a set of gene-specific CpG weight matrices, $\overrightarrow{w_j}$. These weights are updated

throughout the training process to minimize the divergence between observed and expected

outcomes. The magnitude of the weights dictates how much information from each CpG should

be considered. The final gene-level summary value is given by:

793
$$z_{genej} = \sigma(\vec{w_j} \cdot \vec{x_j})$$

794 The gene-level summary values are concatenated to form an array of gene-level summaries ($\vec{z} \in$

795 $\mathbb{R}^n$):

796
$$\vec{z} = [z_{gene1} \, z_{gene2} \, z_{gene3} \cdots z_{genen}]$$

797 The final prediction for the network can be obtained using the following transformation via an

798 MLP, f:

799
$$\hat{y} = f(\vec{z})$$

800
$$\hat{p} = softmax(\hat{y})$$

801 In the classification case, this predicted outcome is compared to the expected outcome via:

802
$$L_{CE} = \frac{-\sum_i \sum_c y_{i,c} log(\widehat{p_{i,c}})}{N}$$

803 We applied Group L1 regularization to these weights to cause certain genes to drop out,

804 returning genes important for the prediction of the cancer subtypes. The final LASSO penalty is

805 given by:

806
$$L_{L1} = \sum_j \sqrt{d_j} \, \left\| \overrightarrow{w_{gene\,j}} \right\|_2$$

Where d_j is the number of CpGs assigned to that gene. An intermediate layer of the neural

network, $\vec{z}$, stores gene-level summaries of DNAm information, and $\overrightarrow{w_{gene\,j}}$ contains the

importance of each CpG for a particular gene.

Here, we contrast this summary measure, $z_{genej} = \sigma(\vec{w_j} \cdot \vec{x_j})$ to a more traditional summary

measure, such as the median or mean methylation (mean displayed on the right): $\beta_{genej} = \frac{\Sigma_k \beta_{jk}}{d_j}$.

Assuming the mean as our measurement, for simplification, it can be seen that each CpG is given

equal weight $\frac{1}{d_j}$, while for *MethylSPWNet*, each CpG is given weight w_{jk}, which is learnable and

reflective of the relative contribution of the given methylation beta value to the aggregate

measure. A comparison between z_{genej} and β_{genej} can be found in the supplementary materials.

Hyperparameter Scans

MethylCapsNet includes the use of a hyperparameter optimization scheme, accessible

through the *methylcaps-hypscan* module. Currently offered by the package is the availability to

scan a number of hyperparameters, including the number of training epochs, length of the

genomic region, the minimum number of CpGs to constitute a capsule, weighting schemes for

reconstruction loss and survival loss, learning rate, in addition to other focused hyperparameters.

Additionally, the search of *MethylNet* model architecture, randomized neural network topologies,

was replaced by a framework that searches for the ideal number of neurons per neural network

layer, conditional upon the choice of the number of layers. There are three search strategies for

optimization, including randomized searches and Bayesian optimization techniques. This scheme

differs from *MethylNet*, as both the neural network topology and set of hyperparameters can be

optimized through the application of successive Gaussian processes to update some prior of

losses over the set of hyperparameters. However, the results presented in this manuscript utilized

the randomized search design. The jobs can be launched in parallel and scaled to meet the

demands of a larger compute cluster.

Capsule Generation

Capsules specify the groupings of CpGs of the *MethylationArray* object. Capsule selection has

been incorporated into the *hyperparameter_scan* and the *methylcaps-model* subcommands.

Application Programming Interface (API) access to capsule selection and the building may be

accessed through the *build_capsules* script. As mentioned in the results section, prespecified

capsules include the following Illumina methylation array annotations – UCSC_RefGene_Name,

UCSC_RefGene_Accession, UCSC_RefGene_Group, UCSC_CpG_Islands_Name,

Relation_to_UCSC_CpG_Island, Phantom, DMR, Enhancer, HMM_Island,

Regulatory_Feature_Name, Regulatory_Feature_Group, and DHS. Additionally, the following

GSEA gene sets may be queried: C5.BP, C6, C1, H, C3.MIR, C2.CGP, C4.CM, C5.CC,

C3.TFT, C5.MF, C7, C2.CP, C4.CGN. Users can also specify their own capsules through the

presentation of a pickled dictionary containing a DataFrame that maps each CpG to a context

name of choice. Capsule generation may also be accomplished by breaking up the entire hg19

genome into overlapping windows of fixed width [57] (*genomic_binned* selection). We

recommend the utilization of the Circos tool [111] for visualization of derived capsule

relationships using the *genomic_binned* option.

Selection of Capsules for *MethylCapsNet* and *MethylSPWNet*

For the training of *MethylSPWNet*, we utilized all genes that overlapped with the 200,000 most

variable CpGs across the CNS tumors. For *MethylCapsNet*, we could not utilize the complete set

of genes due to the number of free parameters, a gene list of 650 genes was manually curated for

MethylCapsNet that included genes related to WNT, SHH, DKK1, beta-catenin, SFRP, NPR3,

amongst others. This list was reduced to 55 genes via recognition of genes by domain experts

and thresholding of the minimum number of CpGs. As a further description, for both approaches,

hyperparameter scans were utilized for pruning genes that did not contain a minimum number of

CpGs (this threshold was varied via the hyperparameter scan), resulting in a lower number of

genes than originally specified (n=10,341). In future iterations of the capsule-inspired network-

based approach, gene selection constraints will be lifted via reduction of free parameters and the

adoption of explicit network building approaches.

Co-Methylation Embedding Modules

MethylSPWNet derived gene-level methylation summaries/embeddings were correlated to each

other and within their own set of top genes. Louvain modularity was performed on a k-nearest

neighbors graph of *MethylSPWNet* gene-level embeddings to establish preliminary modules. For

MethylSPWNet, the final gene co-methylation/embedding analysis was carried out on a subtype-

specific basis, done so through the use of WGCNA.

For *MethylCapsNet*, capsule-level embeddings were averaged across all individuals to form

overall embeddings. Though just as relevant, these approaches can be extended to capsule-level

embeddings on the individual level or aggregated across meaningful subgroups. To derive final

measures of coordinated response between capsules, we averaged the routing matrix coefficients

across the individuals to form a weighted bipartite graph and calculated a bipartite projection of

the graph to form a unipartite graph of capsules. We utilized the Louvain modularity algorithm to

discover hubs in this network and performed enrichment analyses on the pathway level using

enrichr [112] to describe these hubs.

Random Forest Approaches in Comparison

As a comparison to *MethylSPWNet* and *MethylCapsNet*, we adapted the Random Forest scheme

featured in a DNAm machine learning classification study. We selected 10k CpGs by first fitting

100 random forest models, each themselves fit on 10k randomly selected CpGs. Shapley

Additive Feature Explanations (SHAP) [113], was employed to determine the top CpGs from

each random forest run. The 10k CpGs with the highest average rank across the 100 random

forest models were selected for the final RF model. We note that we did not have access to the

original set of 10k CpGs featured in the previous classifier development study. The previous

study also utilized probability calibration methods to boost the model sensitivity and specificity,

which we avoided to ensure a proper comparison between methods.

Analysis of CpG Weights derived from *MethylSPWNet*

MethylSPWNet derives CpG-specific weights, $\vec{w}$, that relates each CpG to its respective gene.

We rank-ordered, reverse rank-ordered, and absolute-value reverse rank-ordered these lists to

yield CpGs that were important to differentiate the tumor types. We subset the first 1000 CpGs,

marked which genes they corresponded to, and tested for enrichment using enrichr in our

preliminary weight analysis. Finally, weights were also rank-ordered and reverse-rank ordered to

yield the set of top negative and positive weights, respectively, the CpGs correspondent to the

top number of CpGs (selected to highlight tendencies of enrichment and depletion) were related

to the various island and gene context.

Method to Cluster Gene-Level Brain Cancer Embeddings by Samples

Recall that embeddings for individuals for *MethylSPWNet* were given in the following form (the

design matrix is of dimensionality samples by genes):

$$\vec{z} = \begin{bmatrix} z_{gene1} & z_{gene2} & z_{gene3} & \cdots & z_{genen} \end{bmatrix}$$

For *MethylNet*, the embeddings are derived using the encoder:

$$\vec{z} = f(\vec{x})$$

Embeddings for individuals using the *MethylCapsNet* approach (of dimensionality samples by

genes by latent dimensions) can be obtained by either averaging or concatenating (an

aggregation, or *AGG* operator) the gene-level embeddings:

$$\overleftrightarrow{z} = AGG\left(\begin{bmatrix} \overrightarrow{z_{gene1}} \\ \vdots \\ \overrightarrow{z_{genen}} \end{bmatrix}\right)$$

Stacking these vectors for individuals would yield a design matrix that can be clustered using

methods such as hierarchical clustering. We implemented hierarchical clustering using *scikit-*

learn (>0.22) and found 14 clusters to compare against true labels of cell-of-origin, histological

subtype, and histological and molecular subtype using the v-measure statistic and cluster

separation using the Silhouette coefficient.

Web Application

We have developed a web application for the submission and investigation of *MethylCapsNet*

outputs. The web application features three modules. The first is the network projection model,

where capsules are related two to each other across subtypes, and network configurations can be

changed by having some users tweak the relationships between the capsules and conservation.

The second module displays routing information and the third module displays embedding

information. Usage is detailed in the wiki.

Analysis Hardware and Software

926   The analyses run for this work were optimized utilizing K80 GPUs at the Dartmouth Research

927   Computing Cluster. The algorithms were designed using Python 3.7, PyTorch version 1.1, and

928   CUDA 9.0.

Dataset Preprocessing

931   We acquired data from GEO accession GSE109381 preprocessed data using *PyMethylProcess*

932   and the subselected 200K of the most hypervariable CpGs (to focus on CpGs that may better

933   differentiate CNS tumor subtypes) after functional normalization was applied to the data. SNPs

934   and non-autosomal (sex chromosome) probes were omitted. Preprocessing steps have been

935   detailed in using the pipeline of *PyMethylProcess* [21].

Abbreviations

ANN – Artificial Neural Network
CGI – CpG Island
CIMP – CpG Island Methylator Phenotype
CNS – Central Nervous System
CpG – Cytosine Guanine Dinucleotide
DNAm – DNA Methylation
GBM – Glioblastoma Multiforme
LGG – Low-Grade Glioma
MB – Medulloblastoma
MLP – Multi-Layer Perceptron
ReLU – Rectified Linear Unit
Tanh – Hyperbolic Tangent
TDA – Topological Data Analysis
TOM – Topological Overlap Matrix
WGCNA – Weighted Gene Correlation Network Analysis

Declarations

Ethics Approval and Consent to Participate

Not applicable.

Consent for Publication

Not applicable.

Competing Interests

Not applicable.

Code Availability

The software (*MethylCapsNet*, *MethylSPWNet*) is open source and can be found on GitHub at https://github.com/Christensen-Lab-Dartmouth/MethylCapsNet, on PyPI under the tag *methylcapsnet*, and on Docker at *joshualevy44/methylcapsnet*. While new features may be developed for the *MethylCapsNet* framework, community contributions are welcome in the form of GitHub pull requests and issues. A test pipeline is available in the software implementation, a Wiki, help documentation, and example R scripts for possible downstream analyses can be found in the GitHub repository.

Data Availability

Data used in this study was acquired from GEO accessions GSE109381, GSE84207, and GSE75067. Test data is available in our GitHub repository.

Correspondence Statement

Correspondence and request for materials should be addressed to Joshua J. Levy; email: joshua.j.levy.gr@dartmouth.edu .

Competing Interests

Not applicable.

Funding

This work was supported by NIH grants R01CA216265, R01DE022772, and P20GM104416 to BCC, Dartmouth College Neukom Institute for Computational Science CompX awards to BCC and LJV, and training fellowship support for AJT from T32LM012204. CLP and JJL are supported through the Burroughs Wellcome Fund Big Data in the Life Sciences at Dartmouth.

Authors' Contributions

991 The conception and design of the study were contributed by JJL and BCC. Implementation,
992 programming, data acquisition, and analyses were by JJL. All authors contributed towards
993 refining the analytic plan and direction. All authors contributed to the writing and editing of the
994 manuscript. CLP and JJL tested the pipeline.
995

Acknowledgments
997 We would like to acknowledge Christian Haudenschild, Hildreth Robert Frost, and A. James
998 O'Malley for their thoughtful discussions.

References

1. Bell CG, Lowe R, Adams PD, Baccarelli AA, Beck S, Bell JT, et al. DNA methylation aging clocks: challenges and recommendations. Genome Biol. 2019;20:249.

2. Khavari DA, Sen GL, Rinn JL. DNA methylation and epigenetic control of cellular differentiation. Cell Cycle. 2010;9:3880–3.

3. Christensen BC, Houseman EA, Marsit CJ, Zheng S, Wrensch MR, Wiemels JL, et al. Aging and environmental exposures alter tissue-specific DNA methylation dependent upon CpG island context. PLoS Genet. 2009;5:e1000602.

4. Dedeurwaerder S, Defrance M, Calonne E, Denis H, Sotiriou C, Fuks F. Evaluation of the Infinium Methylation 450K technology. Epigenomics. 2011;3:771–84.

5. Moran S, Arribas C, Esteller M. Validation of a DNA methylation microarray for 850,000 CpG sites of the human genome enriched in enhancer sequences. Epigenomics. 2016;8:389–99.

6. Heyn H, Esteller M. DNA methylation profiling in the clinic: applications and challenges. Nature Reviews Genetics. 2012;13:679–92.

7. Dor Y, Cedar H. Principles of DNA methylation and their implications for biology and medicine. The Lancet. 2018;392:777–86.

8. Capper D, Jones DTW, Sill M, Hovestadt V, Schrimpf D, Sturm D, et al. DNA methylation-based classification of central nervous system tumours. Nature. 2018;555:469–74.

9. Hegi ME, Diserens A-C, Gorlia T, Hamou M-F, de Tribolet N, Weller M, et al. MGMT Gene Silencing and Benefit from Temozolomide in Glioblastoma. New England Journal of Medicine. 2005;352:997–1003.

10. Turcan S, Rohle D, Goenka A, Walsh LA, Fang F, Yilmaz E, et al. IDH1 mutation is sufficient to establish the glioma hypermethylator phenotype. Nature. 2012;483:479–83.

11. Noushmehr H, Weisenberger DJ, Diefes K, Phillips HS, Pujara K, Berman BP, et al.
Identification of a CpG Island Methylator Phenotype that Defines a Distinct Subgroup of Glioma.
Cancer Cell. 2010;17:510–22.

12. Christensen BC, Smith AA, Zheng S, Koestler DC, Houseman EA, Marsit CJ, et al. DNA
Methylation, Isocitrate Dehydrogenase Mutation, and Survival in Glioma. J Natl Cancer Inst.
2011;103:143–53.

13. J. Dabrowski M, Wojtas B. Global DNA Methylation Patterns in Human Gliomas and Their
Interplay with Other Epigenetic Modifications. Int J Mol Sci [Internet]. 2019 [cited 2020 Jul
21];20. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6678179/

14. Cavalli FMG, Remke M, Rampasek L, Peacock J, Shih DJH, Luu B, et al. Intertumoral
Heterogeneity within Medulloblastoma Subgroups. Cancer Cell. 2017;31:737-754.e6.

15. Maros ME, Capper D, Jones DTW, Hovestadt V, von Deimling A, Pfister SM, et al. Machine
learning workflows to estimate class probabilities for precision cancer diagnostics on DNA
methylation microarray data. Nature Protocols. 2020;15:479–512.

16. Rauschert S, Raubenheimer K, Melton PE, Huang RC. Machine learning and clinical
epigenetics: a review of challenges for diagnosis and classification. Clinical Epigenetics.
2020;12:51.

17. LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015;521:436–44.

18. Hinton GE. Connectionist learning procedures. Artificial Intelligence. 1989;40:185–234.

19. Krizhevsky A, Sutskever I, Hinton GE. ImageNet Classification with Deep Convolutional
Neural Networks. In: Pereira F, Burges CJC, Bottou L, Weinberger KQ, editors. Advances in
Neural Information Processing Systems 25 [Internet]. Curran Associates, Inc.; 2012 [cited 2019
Jun 9]. p. 1097–105. Available from: http://papers.nips.cc/paper/4824-imagenet-classification-
with-deep-convolutional-neural-networks.pdf

20. Levy JJ, Titus AJ, Petersen CL, Chen Y, Salas LA, Christensen BC. MethylNet: an automated
and modular deep learning approach for DNA methylation analysis. BMC Bioinformatics.
2020;21:108.

21. Levy JJ, Titus AJ, Salas LA, Christensen BC. PyMethylProcess - convenient high-throughput
preprocessing workflow for DNA methylation data. Bioinformatics. 2019;

22. Titus AJ, Wilkins OM, Bobak CA, Christensen BC. Unsupervised deep learning with
variational autoencoders applied to breast tumor genome-wide DNA methylation data with
biologic feature extraction. bioRxiv. 2018;433763.

23. Titus AJ, Bobak CA, Christensen BC. A New Dimension of Breast Cancer Epigenetics -
Applications of Variational Autoencoders with DNA Methylation. 2018 [cited 2019 Jun 15]. p.

140–5. Available from:
https://www.scitepress.org/PublicationsDetail.aspx?ID=kxmWGvGaZh0=&t=1

24. Angermueller C, Lee HJ, Reik W, Stegle O. DeepCpG: accurate prediction of single-cell DNA
methylation states using deep learning. Genome Biology. 2017;18:67.

25. Lundberg SM, Lee S-I. A Unified Approach to Interpreting Model Predictions. In: Guyon I,
Luxburg UV, Bengio S, Wallach H, Fergus R, Vishwanathan S, et al., editors. Advances in Neural
Information Processing Systems 30 [Internet]. Curran Associates, Inc.; 2017 [cited 2019 Jun 9].
p. 4765–74. Available from: http://papers.nips.cc/paper/7062-a-unified-approach-to-
interpreting-model-predictions.pdf

26. Ribeiro MT, Singh S, Guestrin C. "Why Should I Trust You?": Explaining the Predictions of
Any Classifier. arXiv:160204938 [cs, stat] [Internet]. 2016 [cited 2020 Feb 9]; Available from:
http://arxiv.org/abs/1602.04938

27. Camacho DM, Collins KM, Powers RK, Costello JC, Collins JJ. Next-Generation Machine
Learning for Biological Networks. Cell. 2018;173:1581–92.

28. Horvath S. DNA methylation age of human tissues and cell types. Genome Biol.
2013;14:R115.

29. Handl L, Jalali A, Scherer M, Eggeling R, Pfeifer N. Weighted elastic net for unsupervised
domain adaptation with application to age prediction from DNA methylation data.
Bioinformatics. 2019;35:i154–63.

30. Sun H, Wang S. Penalized logistic regression for high-dimensional DNA methylation data
with case-control studies. Bioinformatics. 2012;28:1368–75.

31. Zhou W, Lo S-H. Analysis of genotype by methylation interactions through sparsity-inducing
regularized regression. BMC Proceedings. 2018;12:40.

32. Choi J, Kim K, Sun H. New variable selection strategy for analysis of high-dimensional DNA
methylation data. J Bioinform Comput Biol. 2018;16:1850010.

33. Dong NT, Khosla M. Revisiting Feature Selection with Data Complexity. bioRxiv.
2019;754630.

34. Sun L, Namboodiri S, Chen E, Sun S. Preliminary Analysis of Within-Sample Co-methylation
Patterns in Normal and Cancerous Breast Samples. Cancer Inform.
2019;18:1176935119880516.

35. Rickabaugh TM, Baxter RM, Sehl M, Sinsheimer JS, Hultin PM, Hultin LE, et al. Acceleration
of age-associated methylation patterns in HIV-1-infected adults. PLoS ONE. 2015;10:e0119201.

36. Zhang J, Huang K. Pan-cancer analysis of frequent DNA co-methylation patterns reveals
consistent epigenetic landscape changes in multiple cancers. BMC Genomics. 2017;18:1045.

37. Gomez L, Odom GJ, Young JI, Martin ER, Liu L, Chen X, et al. coMethDMR: accurate
identification of co-methylated and differentially methylated regions in epigenome-wide
association studies with continuous phenotypes. Nucleic Acids Res. 2019;47:e98–e98.

38. Lien TG, Borgan Ø, Reppe S, Gautvik K, Glad IK. Integrated analysis of DNA-methylation and
gene expression using high-dimensional penalized regression: a cohort study on bone mineral
density in postmenopausal women. BMC Medical Genomics. 2018;11:24.

39. Ng B, Jafarzadeh S, Cole D, Goldenberg A, Mostafavi S. DNA Methylation Network
Estimation with Sparse Latent Gaussian Graphical Model. 2018.

40. Davies M, Volta M, Pidsley R, Lunnon K, Dixit A, Lovestone S, et al. Functional annotation of
the human brain methylome identifies tissue-specific epigenetic variation across brain and
blood. Genome biology. 2012;13:R43.

41. Cui Z-J, Zhou X-H, Zhang H-Y. DNA Methylation Module Network-Based Prognosis and
Molecular Typing of Cancer. Genes (Basel) [Internet]. 2019 [cited 2020 Feb 9];10. Available
from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6722866/

42. Mallona I, Aussó S, Díez-Villanueva A, Moreno V, Peinado MA. Modular dynamics of DNA
co-methylation networks exposes the functional organization of colon cancer cells' genome.
bioRxiv. 2018;428730.

43. Tremblay BL, Guénard F, Lamarche B, Pérusse L, Vohl M-C. Network Analysis of the Potential
Role of DNA Methylation in the Relationship between Plasma Carotenoids and Lipid Profile.
Nutrients. 2019;11:1265.

44. Mallik S, Bandyopadhyay S. WeCoMXP: Weighted Connectivity Measure Integrating Co-
Methylation, Co-Expression and Protein-Protein Interactions for Gene-Module Detection.
IEEE/ACM Trans Comput Biol Bioinform. 2018;

45. Wang F, Xu H, Zhao H, Gelernter J, Zhang H. DNA co-methylation modules in postmortem
prefrontal cortex tissues of European Australians with alcohol use disorders. Scientific Reports.
2016;6:1–11.

46. Bartlett TE, Olhede SC, Zaikin A. A DNA Methylation Network Interaction Measure, and
Detection of Network Oncomarkers. PLoS One [Internet]. 2014 [cited 2020 Feb 10];9. Available
from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3882261/

47. Horvath S, Zhang Y, Langfelder P, Kahn RS, Boks MPM, van Eijk K, et al. Aging effects on DNA
methylation modules in human brain and blood tissue. Genome Biol. 2012;13:R97.

48. Langfelder P, Horvath S. WGCNA: an R package for weighted correlation network analysis.
BMC Bioinformatics. 2008;9:559.

49. Akulenko R, Helms V. DNA co-methylation analysis suggests novel functional associations
between gene pairs in breast cancer samples. Hum Mol Genet. 2013;22:3016–22.

50. Affinito O, Palumbo D, Fierro A, Cuomo M, De Riso G, Monticelli A, et al. Nucleotide
distance influences co-methylation between nearby CpG sites. Genomics. 2020;112:144–50.

51. Hao J, Kim Y, Kim T-K, Kang M. PASNet: pathway-associated sparse deep neural network for
prognosis prediction from high-throughput data. BMC Bioinformatics. 2018;19:510.

52. Hao J, Masum M, Oh JH, Kang M. Gene- and Pathway-Based Deep Neural Network for Multi-
omics Data Integration to Predict Cancer Survival Outcomes. In: Cai Z, Skums P, Li M, editors.
Bioinformatics Research and Applications. Cham: Springer International Publishing; 2019. p.
113–24.

53. Borisov V, Haug J, Kasneci G. CancelOut: A Layer for Feature Selection in Deep Neural
Networks. In: Tetko IV, Kůrková V, Karpov P, Theis F, editors. Artificial Neural Networks and
Machine Learning – ICANN 2019: Deep Learning. Cham: Springer International Publishing; 2019.
p. 72–83.

54. Crawford J, Greene CS. Incorporating biological structure into machine learning models in
biomedicine. Current Opinion in Biotechnology. 2020;63:126–34.

55. Xie G, Dong C, Kong Y, Zhong JF, Li M, Wang K. Group Lasso Regularized Deep Learning for
Cancer Prognosis from Multi-Omics and Clinical Features. Genes (Basel) [Internet]. 2019 [cited
2020 Mar 28];10. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6471789/

56. Barthel FP, Johnson KC, Wesseling P, Verhaak RGW. Evolving Insights into the Molecular
Neuropathology of Diffuse Gliomas in Adults. Neurol Clin. 2018;36:421–37.

57. Quinlan AR, Hall IM. BEDTools: a flexible suite of utilities for comparing genomic features.
Bioinformatics. 2010;26:841–2.

58. Artemenkov A, Panov M. NCVis: Noise Contrastive Approach for Scalable Visualization. 2020
[cited 2020 May 6]; Available from: https://arxiv.org/abs/2001.11411v1

59. Szklarczyk D, Gable AL, Lyon D, Junge A, Wyder S, Huerta-Cepas J, et al. STRING v11:
protein–protein association networks with increased coverage, supporting functional discovery
in genome-wide experimental datasets. Nucleic Acids Res. 2019;47:D607–13.

60. Babic I, Mischel PS. Multiple functions of a glioblastoma fusion oncogene. J Clin Invest.
2013;123:548–51.

61. Parker BC, Annala MJ, Cogdell DE, Granberg KJ, Sun Y, Ji P, et al. The tumorigenic FGFR3-
TACC3 gene fusion escapes miR-99a regulation in glioblastoma. J Clin Invest. 2013;123:855–65.

62. Macy ME, Birks DK, Barton VN, Chan MH, Donson AM, Kleinschmidt-DeMasters BK, et al.
Clinical and molecular characteristics of congenital glioblastoma. Neuro Oncol. 2012;14:931–41.

63. Berezovsky AD, Poisson LM, Cherba D, Webb CP, Transou AD, Lemke NW, et al. Sox2
Promotes Malignancy in Glioblastoma by Regulating Plasticity and Astrocytic Differentiation.
Neoplasia. 2014;16:193-206.e25.

64. Ibrahim K, Abdul Murad NA, Harun R, Jamal R. Knockdown of Tousled-like kinase 1 inhibits
survival of glioblastoma multiforme cells. International Journal of Molecular Medicine.
2020;46:685–99.

65. Huang Q, Zhang X-W, Ma Y-S, Lu G-X, Xie R-T, Yang H-Q, et al. Up-regulated microRNA-299
corrected with poor prognosis of glioblastoma multiforme patients by targeting ELL2. Jpn J Clin
Oncol. 2017;47:590–6.

66. Krishnan R, Boddapati N, Mahalingam S. Interplay between human nucleolar GNL1 and
RPS20 is critical to modulate cell proliferation. Scientific Reports. 2018;8:11421.

67. Friesen C, Hormann I, Roscher M, Fichtner I, Alt A, Hilger R, et al. Opioid receptor activation
triggering downregulation of cAMP improves effectiveness of anti-cancer drugs in treatment of
glioblastoma. Cell Cycle. 2014;13:1560–70.

68. Pearson JRD, Regad T. Targeting cellular pathways in glioblastoma multiforme. Signal
Transduct Target Ther. 2017;2:17040.

69. Xiong A, Roy A, Spyrou A, Weishaupt H, Marinescu VD, Olofsson T, et al. Nuclear Receptor
Binding Protein 2 Is Downregulated in Medulloblastoma, and Reduces Tumor Cell Survival upon
Overexpression. Cancers (Basel) [Internet]. 2020 [cited 2020 Aug 9];12. Available from:
https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7352854/

70. de la Rocha AMA, Sampron N, Alonso MM, Matheu A. Role of SOX family of transcription
factors in central nervous system tumors. Am J Cancer Res. 2014;4:312–24.

71. Rivero-Hinojosa S, Lau LS, Stampar M, Staal J, Zhang H, Gordish-Dressman H, et al.
Proteomic analysis of Medulloblastoma reveals functional biology with translational potential.
acta neuropathol commun. 2018;6:48.

72. Qi Y, Gao Y. Clinical significance of miR-33b in glioma and its regulatory role in tumor cell
proliferation, invasion and migration. Biomarkers in Medicine. 2020;14:539–48.

73. Wang X, Huang Z, Wu Q, Prager BC, Mack SC, Yang K, et al. MYC-regulated Mevalonate
Metabolism Maintains Brain Tumor Initiating Cells. Cancer Res. 2017;77:4947–60.

74. Marx S, Xiao Y, Baschin M, Splittstöhser M, Altmann R, Moritz E, et al. The Role of Platelets
in Cancer Pathophysiology: Focus on Malignant Glioma. Cancers (Basel) [Internet]. 2019 [cited
2020 Aug 9];11. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6521321/

75. Wu X, Rauch TA, Zhong X, Bennett WP, Latif F, Krex D, et al. CpG island hypermethylation in
human astrocytomas. Cancer Res. 2010;70:2718–27.

76. Caponegro MD, Moffitt RA, Tsirka SE. Expression of neuropilin-1 is linked to glioma
associated microglia and macrophages and correlates with unfavorable prognosis in high grade
gliomas. Oncotarget. 2018;9:35655–65.

77. Xia Z, Ouyang D, Li Q, Li M, Zou Q, Li L, et al. The Expression, Functions, Interactions and
Prognostic Values of PTPRZ1: A Review and Bioinformatic Analysis. J Cancer. 2019;10:1663–74.

78. Panosyan EH, Lin HJ, Koster J, Lasky JL. In search of druggable targets for GBM amino acid
metabolism. BMC Cancer [Internet]. 2017 [cited 2020 Aug 9];17. Available from:
https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5331648/

79. Rodríguez-Paredes M, Esteller M. Cancer epigenetics reaches mainstream oncology. Nat
Med. 2011;17:330–9.

80. Chenn A. Wnt/β-catenin signaling in cerebral cortical development. Organogenesis.
2008;4:76–80.

81. Testa U, Castelli G, Pelosi E. Genetic Abnormalities, Clonal Evolution, and Cancer Stem Cells
of Brain Tumors. Med Sci (Basel) [Internet]. 2018 [cited 2020 Jul 1];6. Available from:
https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6313628/

82. Li T, Forbes ME, Fuller GN, Li J, Yang X, Zhang W. IGFBP2: integrative hub of developmental
and oncogenic signaling network. Oncogene. 2020;39:2243–57.

83. Ishak G, Leal MF, dos Santos NPC, Demachki S, Nunes CAM, do Nascimento Borges B, et al.
Deregulation of MYC and TP53 through genetic and epigenetic alterations in gallbladder
carcinomas. Clin Exp Med. 2015;15:421–6.

84. Jun I, Park HS, Piao H, Han JW, An MJ, Yun BG, et al. ANO9/TMEM16J promotes
tumourigenesis via EGFR and is a novel therapeutic target for pancreatic cancer. Br J Cancer.
2017;117:1798–809.

85. Hatanpaa KJ, Burma S, Zhao D, Habib AA. Epidermal Growth Factor Receptor in Glioma:
Signal Transduction, Neuropathology, Imaging, and Radioresistance. Neoplasia. 2010;12:675–
84.

86. Fleischer T, Tekpli X, Mathelier A, Wang S, Nebdal D, Dhakal HP, et al. DNA methylation at
enhancers identifies distinct breast cancer lineages. Nature Communications. 2017;8:1379.

87. Holm K, Staaf J, Lauss M, Aine M, Lindgren D, Bendahl P-O, et al. An integrated genomics
analysis of epigenetic subtypes in human breast tumors links DNA methylation patterns to
chromatin states in normal mammary cells. Breast Cancer Res. 2016;18:27.

88. Sabour S, Frosst N, Hinton GE. Dynamic Routing Between Capsules. arXiv:171009829 [cs]
[Internet]. 2017 [cited 2020 Jan 18]; Available from: http://arxiv.org/abs/1710.09829

89. Venkatraman S, S B, Sarma R. Building Deep, Equivariant Capsule Networks. 2019.

90. Wang L, Miao X, Zhang J, Cai J. MultiCapsNet: a interpretable deep learning classifier
integrate data from multiple sources. bioRxiv. 2019;570507.

91. Danielsson A, Nemes S, Tisell M, Lannering B, Nordborg C, Sabel M, et al. MethPed: a DNA
methylation classifier tool for the identification of pediatric brain tumor subtypes. Clin
Epigenetics. 2015;7:62.

92. Hovestadt V, Jones DTW, Picelli S, Wang W, Kool M, Northcott PA, et al. Decoding the
regulatory landscape of medulloblastoma using DNA methylation sequencing. Nature.
2014;510:537–41.

93. Baeza N, Weller M, Yonekawa Y, Kleihues P, Ohgaki H. PTEN methylation and expression in
glioblastomas. Acta Neuropathol. 2003;106:479–85.

94. Capaccione KM, Pine SR. The Notch signaling pathway as a mediator of tumor survival.
Carcinogenesis. 2013;34:1420–30.

95. Fan X, Matsui W, Khaki L, Stearns D, Chun J, Li Y-M, et al. Notch pathway inhibition depletes
stem-like cells and blocks engraftment in embryonal brain tumors. Cancer Res. 2006;66:7445–
52.

96. Li J, Yen C, Liaw D, Podsypanina K, Bose S, Wang SI, et al. PTEN, a putative protein tyrosine
phosphatase gene mutated in human brain, breast, and prostate cancer. Science.
1997;275:1943–7.

97. He X, Zhang L, Chen Y, Remke M, Shih D, Lu F, et al. The G protein α subunit Gαs is a tumor
suppressor in Sonic hedgehog-driven medulloblastoma. Nat Med. 2014;20:1035–42.

98. Pidsley R, Zotenko E, Peters TJ, Lawrence MG, Risbridger GP, Molloy P, et al. Critical
evaluation of the Illumina MethylationEPIC BeadChip microarray for whole-genome DNA
methylation profiling. Genome Biology. 2016;17:208.

99. Zhou L, Ng HK, Drautz-Moses DI, Schuster SC, Beck S, Kim C, et al. Systematic evaluation of
library preparation methods and sequencing platforms for high-throughput whole genome
bisulfite sequencing. Scientific Reports. 2019;9:10383.

100. Moran S, Vizoso M, Martinez-Cardús A, Gomez A, Matías-Guiu X, Chiavenna SM, et al.
Validation of DNA methylation profiling in formalin-fixed paraffin-embedded samples using the
Infinium HumanMethylation450 Microarray. Epigenetics. 2014;9:829–33.

101. Bodnar C, Cangea C, Liò P. Deep Graph Mapper: Seeing Graphs through the Neural Lens.
arXiv:200203864 [cs, stat] [Internet]. 2020 [cited 2020 Feb 20]; Available from:
http://arxiv.org/abs/2002.03864

102. Veen HJ van, Saul N, Eargle D, Mangham SW. Kepler Mapper: A flexible Python
implementation of the Mapper algorithm. Journal of Open Source Software. 2019;4:1315.

103. Wang T, Johnson T, Jie Z, Huang K. Topological Methods for Visualization and Analysis of
High Dimensional Single-Cell RNA Sequencing Data. Pacific Symposium on Biocomputing.
2019;24:350–61.

104. Rizvi AH, Camara PG, Kandror EK, Roberts TJ, Schieren I, Maniatis T, et al. Single-cell
topological RNA-Seq analysis reveals insights into cellular differentiation and development. Nat
Biotechnol. 2017;35:551–60.

105. Lum PY, Singh G, Lehman A, Ishkanov T, Vejdemo-Johansson M, Alagappan M, et al.
Extracting insights from the shape of complex data using topology. Scientific Reports.
2013;3:1236.

106. Singh D, Yamada M. FsNet: Feature Selection Network on High-dimensional Biological
Data. arXiv:200108322 [cs, stat] [Internet]. 2020 [cited 2020 Feb 22]; Available from:
http://arxiv.org/abs/2001.08322

107. Ritchie ME, Phipson B, Wu D, Hu Y, Law CW, Shi W, et al. limma powers differential
expression analyses for RNA-sequencing and microarray studies. Nucleic Acids Res.
2015;43:e47–e47.

108. Raudvere U, Kolberg L, Kuzmin I, Arak T, Adler P, Peterson H, et al. g:Profiler: a web server
for functional enrichment analysis and conversions of gene lists (2019 update). Nucleic Acids
Res. 2019;47:W191–8.

109. Shannon P, Markiel A, Ozier O, Baliga NS, Wang JT, Ramage D, et al. Cytoscape: A Software
Environment for Integrated Models of Biomolecular Interaction Networks. Genome Res.
2003;13:2498–504.

110. Gustavsen JA, Pai S, Isserlin R, Demchak B, Pico AR. RCy3: Network biology using Cytoscape
from within R. F1000Res [Internet]. 2019 [cited 2020 Jul 2];8. Available from:
https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6880260/

111. Krzywinski M, Schein J, Birol İ, Connors J, Gascoyne R, Horsman D, et al. Circos: An
information aesthetic for comparative genomics. Genome Res. 2009;19:1639–45.

112. Chen EY, Tan CM, Kou Y, Duan Q, Wang Z, Meirelles GV, et al. Enrichr: interactive and
collaborative HTML5 gene list enrichment analysis tool. BMC Bioinformatics. 2013;14:128.

113. Lundberg SM, Erion G, Chen H, DeGrave A, Prutkin JM, Nair B, et al. From local
explanations to global understanding with explainable AI for trees. Nature Machine
Intelligence. 2020;2:56–67.

1292