White matter tract-oriented deformation is dependent on real-time axonal fiber orientation

Zhou Zhou[1*], August G. Domel[1*], Xiaogai Li[2], Gerald Grant[3,4], Svein Kleiven[2+], David Camarillo[1,3,6+#], Michael Zeineh[5+#]

Department of Bioengineering, Stanford University, Stanford, CA, 94305, USA.

Neuronic Engineering, KTH Royal Institute of Technology, Stockholm, 14152, Sweden.

Department of Neurosurgery, Stanford University, Stanford, CA, 94305, USA.

Department of Neurology, Stanford University, Stanford, CA, 94305, USA.

Department of Radiology, Stanford University, Stanford, CA, 94305, USA.

Department of Mechanical Engineering, Stanford University, Stanford, CA, 94305, USA.

* Co-First Authors.

[+] Co-Senior Authors.

[#] Co-Corresponding Authors.

Abstract

Traumatic axonal injury (TAI) is a critical public health issue with its pathogenesis remaining largely elusive. Finite element (FE) head models are promising tools to bridge the gap between mechanical insult and localized brain response and resultant injury. In particular, the FE-derived deformation along the direction of white matter (WM) tracts (i.e., tract-oriented strain) has been shown to be an appropriate predictor for TAI. However, the evolution of fiber orientation in time during the impact and its potential influence on tract-oriented strain remained unknown. To address this question, the present study leveraged an embedded element approach to track real-time fiber orientation during impacts. A new scheme to calculate the tract-oriented strain was proposed by projecting the strain tensors from pre-computed simulations along the temporal fiber direction instead of its static counterpart directly obtained from diffuse tensor imaging. The results revealed that incorporating the real-time fiber orientation not only altered the direction but also amplified the magnitude of the tract-oriented strain, resulting in a generally more extended distribution and a larger volume ratio of WM exposed to high deformation along fiber tracts. Results of this study provide important insights into how best to incorporate fiber orientation in head injury models and derive the WM tract-oriented deformation from computational simulations, which is important for furthering our understanding of the underlying mechanisms of TAI.

Keywords

Introduction

Traumatic brain injury (TBI) is a critical public health problem associated with high mortality and morbidity, and high diagnosis and treatment costs. In the United States, the Center for Disease Control and Prevention reported that the annual number of TBI-induced emergency department visits was around 1.37 million, resulting in an estimated expense of 60.43 billion dollars.[1] A meta-analysis of injury data from 23 European countries revealed an overall TBI incidence rate of about 235 per 100000 and an average fatality rate of about 11 per 100.[2] In Europe in 2010, a cost of 33 billion euros associated with TBI was reported.[3] Although global effort has been made to reduce the occurrence and alleviate the detriment of TBI, neither TBI-related socioeconomic burden nor improved treatment outcome of TBI patients has been achieved.[4, 5]

This TBI challenge may be partially related to the clinical difficulties for TBI assessment and diagnosis.[6, 7] This may be particularly true for traumatic axonal injury (TAI), which is a frequent form of TBI.[8] The clinical outcome of axonal injury exhibits a broad spectrum of cognitive impairment and pathological severity, ranging from mild levels, that can be associated with a transient alteration in consciousness and subtle neurological complaints, to severe forms, that lead to prolonged coma accompanied by damage throughout the white matter (WM) of the brain.[9, 10] Clinical detection of axonal injury, especially mild axonal injury, is difficult because the brain often exhibits no identifiable structural alteration based on conventional neuroimaging techniques (e.g., computed tomography and magnetic resonance imaging).[11-13]

In parallel, *in vivo*, *ex vivo*, and *in vitro* experimental models have been used to understand the mechanisms of axonal injury and define appropriate criteria and corresponding thresholds for TAI prediction by relating controlled mechanical inputs to resultant morphological damage or functional alteration of experimental tissue.[4, 14-16] One of the most anatomically relevant mechanisms for TAI seems to be the tensile elongation of axonal fibers,[17-23] which instigates immediate or delayed disconnections between neurons within WM tracts and subsequent large-scale neurological deficits.

Based on this mechanism, any criteria related to the deformation of WM axonal fibers might be candidates for TAI prediction.

As an alternative to experiments, finite element (FE) head model is a numerical surrogate of the human head that can emulate the geometrical profiles and mechanical behavior of various intracranial components, as well as the interface condition among them. In recent decades, FE head models have been increasingly used to fill the knowledge gap between external loading and localized brain response and resultant injury.[24-28] Partially inspired by the aforementioned mechanism that axonal elongation triggers TAI occurrence, various endeavors have been made recently to obtain deformation along WM fiber tracts (i.e., the tract-oriented strain).[29-43] Of note, the tract-oriented strain is synonymous with axonal strain or fiber strain, which are both terms used in multiple studies.[38, 44] As was common in these efforts, an advanced neuroimaging technique called diffusion tensor imaging (DTI)[45] was exploited to delineate orientation information of fiber tracts and these orientation information can be combined with FE models. Three different techniques have been proposed thus far to integrate the orientation of WM tracts from DTI into TBI analysis: (1) Chatelin and colleagues[46] developed a post-processing technique to obtain the tract-oriented strain by projecting the strain tensors from pre-computed simulations onto the direction of fiber tracts. (2) Cloots and colleagues[31] and Giordano and coworkers[35] instead assigned a hyper-viscoelastic fiber-reinforced anisotropic material to the brain with the axonal fiber orientation integrated into the constitutive law to inform the fiber reinforcement. (3) Another numerical technique was proposed by Garimella and Kraft[34] to model whole-brain fiber tractography explicitly using an embedded element method. Despite these aforementioned technical disparities along with other model-specific computational choices, it has been repeatedly reported by several independent groups that tract-oriented strain was a more appropriate predictor for TAI than its isotropic counterparts (e.g., maximum principal strain, cumulative strain damage measures (CSDM)).[36, 38, 40, 44, 47, 48]

Although tract-oriented strain is a spatiotemporal-dependent variable and highly sensitive to the temporal variation of axonal fiber orientation,[49, 50] the evolution of fiber orientation in time

during an impact, as well as its potential influence on the tract-oriented strain, has rarely been reported in the literature. Only a few studies[37, 40] clarified that both the strain tensors from the pre-computed simulations and fiber orientation from DTI were commonly transformed into a skull-fixed coordinate system and then the strain tensors were projected onto the time-invariant fiber direction to obtain the tract-oriented strain. Such a transforming operation accounted for the variation of fiber orientation in relation to skull movement within the global coordinate system. Nevertheless, the axonal fiber might still be reoriented within the skull-fixed coordinate system owing to the brain deformation and brain-skull relative motion during impact.[40, 47] Thus, real-time tracking of the fiber direction and employing temporal fiber orientation to inform the calculation of tract-oriented strain have yet to be properly considered.

The aim of this study is to investigate real-time fiber orientation during head impacts and its resultant influence in the prediction of WM tract-oriented deformation. To achieve this, an embedded element approach was leveraged to monitor the temporal direction of fiber tracts in a previously established three-dimensional (3D) head model, from which the deviation of fiber orientation during impacts was quantified. By comparing two types of tract-oriented strains obtained via the projection of strain tensors in pre-computed simulations onto the temporal fiber orientation and its static counterpart from DTI, the influence of real-time fiber orientation on the tract-oriented strain was evaluated. We thus tested the hypothesis that the real-time fiber orientation affects both the direction and magnitude of tract-oriented strain, and consequently the distribution and extent of WM with high deformation along the fiber tracts.

Methods

Finite element head model

The FE model, referred to as the Baseline-model, used in this study was previously developed at the Royal Institute of Technology (KTH) in Stockholm by Kleiven[51] using LS-DYNA. The Baseline-model includes the scalp, skull, brain, meninges (i.e., dura mater and pia mater), intracranial

membranes (i.e., falx and tentorium), cerebrospinal fluid (CSF), eleven pairs of the largest parasagittal bridging veins, and a simplified neck with the extension of the spinal cord (Figure 1). The brain elements were further grouped to represent the primary brain components, including the cerebral gray matter (GM), cerebral WM, corpus callosum, thalamus, brainstem, midbrain, cerebellar GM, cerebellar WM, ventricles. Detailed information regarding the geometry discretization and material choice for each head component in the Baseline-model are available in previous studies by Kleiven.[51, 52] It is worth mentioning that the brain was simulated as an isotropic medium in the current study owing to the lack of consensus regarding the mechanical anisotropy of the brain.[53] Specifically, a second-order hyperelastic constitutive law was used to describe the nonlinear behavior of the brain tissue with additional linear viscoelastic terms to account for its rate dependence. Responses of the Baseline-model have shown good correlation with experiments of brain-skull relative motion,[25, 54] intracranial pressure,[55] skull fracture,[56] and brain strain.[57]

Figure 1 – (a) Isometric view of the finite element model of human head with the skull opened to expose the CSF and brain. A skull-fixed coordinate system and corresponding axes are illustrated with the origin at the center of gravity of the head. (b) Isometric view of cerebral white matter and intracranial sinuses. (c) Isometric view of deep brain structures and membranes.

Computation of tract-oriented strain with static fiber orientation

To obtain the deformation of brain tissue along the primary direction of fiber tracts, a post-processing technique was previously implemented in the Baseline-model by coupling the element-level strain response with fiber orientation information derived from DTI.[35, 37] The averaged tractography was obtained from the ICBM DTI-81 atlas,[58] which was aligned with the brain mask of the Baseline-model via an affine registration. For a given WM element in the Baseline-model, corresponding voxels in the DTI that occupied the same space as that of the WM element were identified, and then diffusion information of these identified voxels were averaged using equation (1), in order to more heavily weight the voxels closer to the WM element centroid:

$$T_{elem} = \frac{\sum_{i=1}^{N} T_i e^{-D_i}}{\sum_{i=1}^{N} e^{-D_i}}$$

(1)

where T_{elem} is the mean diffusion tensor calculated for each WM element; N is the number of selected DTI voxels for a given WM element; T_i is the D_i is the normalized distance from the center of the DTI voxel to the centroid of the WM element.

The eigenvector (v_o) of T_{elem} was obtained for each WM element and referred to as the original fiber orientation hereafter. Note that v_o was expressed with reference to the skull-fixed coordinate system (i.e., the coordinate system in Figure 1 (a)). The strain tensor for each WM element at each timestep was derived from the LS-DYNA solver and then transformed into the skull-fixed coordinate system, similar to the approach adopted by Sullivan and colleagues.[40] The tract-oriented strain was computed according to equation (2):

$$\varepsilon_{tract,o} = \epsilon_{skull} : \langle v_o \rangle \otimes \langle v_o \rangle$$

(2)

where $\varepsilon_{tract,o}$ is the tract-oriented strain projected along v_o; ϵ_{skull} is the Green-Lagrange strain tensor of WM elements in the skull-fixed coordinate system.

Details regarding the coupling protocol between DTI and FE brain model and computation of $\varepsilon_{tract,o}$ are available in previous studies by Giordano and coworkers.[35, 37] Given that v_o remained static during the whole post-processing procedure, the potential deviation of fiber orientation induced by brain-skull relative motion and brain deformation during the impact was not considered.

Implementation of embedded element method for real-time fiber orientation

Given the importance of the fiber orientation on the post-processing technique, an embedded element method was implemented in the Baseline-model to monitor the real-time fiber orientation during impact. For each WM element (serving as a master element), the inserted DTI-derived fiber orientation was concretely represented by an embedded truss element, which oriented in the same direction as that of v_o. As illustrated in Figure 2 (c), one node of the truss element was located at the centroid of its master element and the other fell within the boundary of the master element. Note that the truss element only served as an auxiliary to monitor the real-time fiber orientation and no extra stiffness and other physical properties were added by the truss element. Thus, the material properties of the truss element were represented by a null constitutive model in LS-DYNA with nominal density and cross-sectional area (Table 1).[59] Using this modeling strategy, the temporal orientation of the truss element and strain response of its master element were independent of the length of the embedded truss element, as detailed in Appendix A. Nodal motion of a given truss element was exclusively governed by its master element based on equation (3) and (4):[60]

Figure 2 – (a) Isometric view of the brain (in gray) with embedded truss elements (in blue). For better illustration, half of the brain is masked with the corpus callosum highlighted in red. (b) Top view of the truss elements within the corpus callosum. (c) Isometric view of a representative element in corpus callosum with a truss element embedded.

Table 1 – Material properties for the embedded truss elements.

Element type	Cross-sectional area (m^2)	Constitutive model	Density (kg/m^3)	Reference
Truss	1 e-11	MAT_NULL	1 e-11	[59]

$$v_i^{truss} = \sum_{j=1}^{8} N_j * v_j^{master} \tag{3}$$

$$a_i^{truss} = \sum_{j=1}^{8} N_j * a_i^{master} \tag{4}$$

where v_i^{truss} and a_i^{truss} are the velocity vectors and acceleration vectors of the nodes in the truss element, respectively; i = 1,2, which corresponds to the two nodes of a truss element; N_j is the shape function of the master element that hosts the truss element; v_j^{master} and a_j^{master} are the velocity vectors and acceleration vectors of the 8 nodes of the hexahedral elements (i.e., master element), respectively.

These two equations constrained both acceleration and velocity of the truss element to its master element along all directions. Consequently, potential variation in fiber orientation associated with brain deformation and brain-skull relative motion during the impacts were reflected by the temporal direction of the truss element, which was updated at each solution cycle of the time-marching simulation. Once the simulation was completed, both the strain tensors for all WM elements and the orientation of the embedded truss elements were obtained for each timestep and then transformed into the skull-fixed coordinate system. Instead of equation (2), equation (5) was used to calculate the updated tract-oriented strain as follows:

$$\varepsilon_{tract,u} = \epsilon_{skull} : \langle v_u \rangle \otimes \langle v_u \rangle \tag{5}$$

where $\varepsilon_{tract,u}$ is the tract-oriented strain projected along v_u. Here, v_u is the updated truss orientation output from LS-DYNA per each timestep and is expressed with reference to the skull-fixed coordinated system. Under the undeformed configuration, v_u equaled to v_o for all WM elements. This modified model is referred to as Truss-embedded-model hereafter.

Loading conditions

At Stanford University, instrumented mouthguards have been developed to measure six-degree-of-freedom head kinematics during in-game head impacts to athletes.[61, 62] Using these

instrumented mouthguards, over 500 head impacts in football have been video confirmed.[63] In the current study, two concussive impacts and ten randomly selected subconcussive impacts[64] were imposed to both the Baseline-model and Truss-embedded-model, respectively. Of these two concussive impacts, one resulted in the athlete suffering loss of consciousness, while the other was self-reported with post-concussive symptoms.[63] A summary of the acceleration peaks of all 12 selected impacts is listed in Table 2 with detailed acceleration profiles of the two concussive impacts exemplified in Figure 3.

In all the simulations, translational and rotational accelerations were applied to a node located at the center of gravity of the head and constrained to a rigidly modelled skull. A selectively reduced integration scheme was used for all the brain components and CSF. A typical simulation of 90 ms required about 10 hours for the Baseline-model and 11 hours for the Truss-embedded-model on a local Linux cluster using a single processor. The model responses were output at every 0.1 ms.

Table 2 – Peaks of translational acceleration and rotational acceleration and injury severity of the 12 cases considered in this study.

Case ID	Peak translation acceleration (g)				Peak rotational acceleration (krad/s^2)				Injury severity
	X	Y	Z	Magnitude	X	Y	Z	Magnitude	
Case 1	-40.6	100.4	-63.4	106.1	12.89	-3.06	-3.24	12.95	Concussion
Case 2	-61.1	-57.8	-45.8	84.2	4.21	5.14	-1.84	6.19	Concussion
Case 3	-10.3	11.6	-7.2	15.6	0.66	-0.81	-1.86	1.98	Sub-concussion
Case 4	-44.7	32.2	46.1	57.5	1.97	3.88	1.81	4.42	Sub-concussion
Case 5	-34.0	18.7	-22.5	42.0	0.64	-1.61	-0.55	1.65	Sub-concussion
Case 6	-14.3	10.7	15.5	17.6	0.61	1.87	-0.95	2.05	Sub-concussion
Case 7	-52.9	-22.6	-36.5	63.9	1.69	-5.22	1.51	5.27	Sub-concussion
Case 8	-25.4	5.2	-15.0	28.9	-0.42	-1.66	0.62	1.70	Sub-concussion
Case 9	33.5	-13.3	28.8	44.8	0.68	4.42	-0.32	4.45	Sub-concussion
Case 10	-46.0	5.9	30.5	46.3	0.57	-2.52	0.53	2.58	Sub-concussion
Case 11	-38.3	-15.4	-39.6	55.6	1.02	-5.21	0.70	5.22	Sub-concussion
Case 12	23.3	14.0	25.3	32.8	1.29	2.83	-0.82	2.91	Sub-concussion

Figure 3 – Head model loading condition for the two concussive cases. Note that the X, Y, and Z axes are the same as those in the skull-fixed coordinate system in Figure 1 (a).

Post-processing and data analysis

To quantify the variation of fiber orientation during the impacts, the relative angle between the two tract-oriented strain measures ($\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$) was calculated for each WM element at each timestep. To ascertain the effect of fiber orientation variation on the computation of tract-oriented strain, $\varepsilon_{tract,o}$ and $\varepsilon_{tract,u}$ were calculated for the Baseline-model with the fiber orientation originally obtained from DTI (i.e., equation (2)) and the Truss-embedded-model with the fiber orientation updated at each time step (i.e., equation (5)), respectively. The peak values of $\varepsilon_{tract,o}$ and $\varepsilon_{tract,u}$ were denoted by $\varepsilon_{tract,o}^{p}$ and $\varepsilon_{tract,u}^{p}$, respectively. To exclude the potential numerical artifacts, the 95th percentile $\varepsilon_{tract,o}^{p}$ and $\varepsilon_{tract,u}^{p}$ (referred to as $\varepsilon_{tract,o}^{p,95}$ and $\varepsilon_{tract,u}^{p,95}$, respectively) were presented for all the 12 impacts, similar to the strategies in previous studies.[65, 66]

To statistically determine the effect of the real-time fiber orientation on the tract-oriented strain, a Wilcoxon matched-pairs signed-rank test was performed to examine the difference between

$\varepsilon_{tract,o}^{p,95}$ and $\varepsilon_{tract,u}^{p,95}$. The threshold for significance was p<0.05. A detailed summary of the FE-derived variables is listed in Table 3.

Table 3 – Summary of the FE-derived variables.

$\varepsilon_{tract,o}$	Tract-oriented Green-Lagrange strain with fiber orientation originally obtained from DTI
$\varepsilon_{tract,u}$	Tract-oriented Green-Lagrange strain with fiber orientation updated at each time step
$\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$	Absolute value of the angle between the two tract-oriented strain measures
ε_p	First principal Green-Lagrange strain
$\varepsilon_{tract,o}^{p}$	The accumulated peak $\varepsilon_{tract,o}$, regardless of the time of occurrence
$\varepsilon_{tract,u}^{p}$	The accumulated peak $\varepsilon_{tract,u}$, regardless of the time of occurrence
ε_p^{p}	The accumulate peak ε_p, regardless of the time of occurrence
$\varepsilon_{tract,o}^{p,95}$	95[th] percentile of $\varepsilon_{tract,o}^{p}$ for the whole white matter elements
$\varepsilon_{tract,u}^{p,95}$	95[th] percentile of $\varepsilon_{tract,u}^{p}$ for the whole white matter elements
$\theta_{<\varepsilon_p,\varepsilon_{tract,o}>}$	Absolute value of the angle between ε_p and $\varepsilon_{tract,o}$
$\theta_{<\varepsilon_p,\varepsilon_{tract,u}>}$	Absolute value of the angle between ε_p and $\varepsilon_{tract,u}$

Results

To quantify the variation of fiber orientation during the impacts, the relative angle between the two tract-oriented strain measures was extracted. The time-history curves of maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ in six brain subregions are plotted in Figure 4 for the two concussive impacts. For Case 1, the maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ ranged from $15°$ in the brainstem to $31°$ in cerebral WM. For Case 2, the maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ varied from $9°$ in cerebellar WM to $25°$ in cerebral WM. Figure 5 (a) illustrates both the original and updated (blue and red, respectively) configurations of the truss elements embedded within the corpus callosum for Case 1. The element with maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ within the corpus callosum ($29°$) is shown in the enlarged view. A similar illustration was presented for Case 2 in Figure 5 (b) with the thalamus as the representative region, in which the maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ was $16°$. Element-wise $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ peaks for all WM elements in all 12 impacts are summarized in Figure 6. The data were presented in the form of mean value ± standard deviation with the values ranging from $3.0° \pm 1.9°$ in Case 5 to $10.2° \pm 5.2°$ in Case 1.

Figure 4 – Time-history curves of maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ in six brain subregions for two concussive impacts.

— Original configuration of the truss elements
— Updated configuration of the truss elements at the time with the maximum deviation of fiber orientation

Figure 5 – (a) Original and updated configurations of the truss elements embedded within the corpus callosum (in grey wire) for Case 1 with a whole-head thumbnail showing the view angle and a zoomed view showing the element (in bold black wire) with the largest deviation of fiber orientation in the corpus callosum. (b) Original and updated configurations of the truss elements embedded within the thalamus (in grey wire) in Case 2 with a whole-head thumbnail showing the view angle and a zoomed view showing the element (in bold black wire) with the largest deviation of fiber orientation. In both subfigures, the original configuration of the truss elements is colored in blue, while their updated counterparts in red. In both subfigures, the master elements in their undeformed configurations are also illustrated as reference.

Figure 6 – Summary of element-wise $\theta_{<\varepsilon_{tract,0},\varepsilon_{tract,u}>}$ peak for all 12 impacts in the form of mean value ± standard deviation.

To identify the effect of fiber orientation variation on the computation of tract-oriented strain, both $\varepsilon_{tract,o}$ and $\varepsilon_{tract,u}$ were calculated for these 12 selected impacts. For the two concussive impacts, the differences between the $\varepsilon_{tract,o}^{p,95}$ and $\varepsilon_{tract,u}^{p,95}$ across all WM elements were 21.27% for Case 1 (Figure 7 (a)), and 18.60% for Case 2 (Figure 7 (c)), respectively. All WM elements with their tract-oriented strain peaks over 0.14, a conservative threshold proposed by Brain and Meaney[67] to induce morphological damage to WM, were additionally identified to calculate the volume ratio of injured WM to the whole WM in the FE model. By comparing the injured WM element based on the two types of tract-oriented strains, a generally more extended distribution of injured WM elements was noted for $\varepsilon_{tract,u}^{p}$ in both concussive cases (Figure 7 (b) and Figure 7 (d)). In Case 1, the volume ratios of injured WM were 18.91% for $\varepsilon_{tract,o}$ and 25.7% for $\varepsilon_{tract,u}^{p}$. In Case 2, the volume ratio of injured WM increased from 3.42% to 6.12%, when switching the measure from $\varepsilon_{tract,o}^{p}$ to $\varepsilon_{tract,u}^{p}$. For the 10 subconcussive impacts, larger magnitudes were consistently noted for $\varepsilon_{tract,u}^{p,95}$ than $\varepsilon_{tract,o}^{p,95}$ with the difference varying from 8.07% (Case 4) to 26.66% (Case 5) (Figure 7 (e)). A Wilcoxon matched-pairs signed-rank test performed between $\varepsilon_{tract,o}^{p,95}$ and $\varepsilon_{tract,u}^{p,95}$ for all the 12 impacts showed the difference between the two types of tract-oriented strain was significant (p=0.002).

Figure 7 - (a) Comparison of 95th percentile maximum tract-oriented strain for Case 1; (b) Top view of white matter elements with tract-oriented strain peaks over 0.14 for Case 1. (c) Comparison of 95th percentile maximum tract-oriented strain for Case 2; (d) Side view of white matter elements with tract-oriented strain peaks over 0.14 for Case 2; (e) Comparison of 95th percentile maximum tract-oriented strain for 10 subconcussive cases. Note that Case 1 and Case 2 are concussive impacts. For all the 12 impacts, percentage value for the difference between $\varepsilon_{tract,o}^{p,95}$ and $\varepsilon_{tract,u}^{p,95}$ is listed in the bar figures.

To examine the relationship between the two types of tract-oriented strains and maximum principal strain, the time-history curves of these three strain measures as well as their relative angles for one representative element derived from the two concussive impacts were plotted (Figure 8). For Case 1, the representative element is the one with maximum fiber deviation in the corpus callosum (Figure 8 (a) and Figure 8 (c)). For Case 2, the representative element is the one with maximum fiber deviation in the midbrain (Figure 8 (b) and Figure 8 (d)). Regardless of impact cases, ε_p was larger

than the two types of tract-oriented strain, while $\varepsilon_{tract,u}$ was larger than $\varepsilon_{tract,o}$ (Figure 8 (a) and (b)). As plotted in Figure 8 (c) and (d), $\theta_{<\varepsilon_p,\varepsilon_{tract,u}>}$ was generally smaller than $\theta_{<\varepsilon_p,\varepsilon_{tract,o}>}$ for both impacts, which was particularly notable at the peaking time of $\varepsilon_{tract,u}$ identified by the gray dash lines. It was indicated that the direction of $\varepsilon_{tract,u}$ was more aligned with that of ε_p.

Figure 8 – (a) Time history curves of ε_p, $\varepsilon_{tract,o}$, and $\varepsilon_{tract,u}$ for one representative element in the corpus callosum with the maximum deviation of fiber orientation in Case 1. The relative angles between ε_p and two tract-oriented strains plotted in subfigure (c). The grey dash lines in subfigure (a) and (c) identify the peaking time of $\varepsilon_{tract,u}$ in Case 1. (b) Time history curves of ε_p, $\varepsilon_{tract,o}$, and $\varepsilon_{tract,u}$ for one representative element in the midbrain with the maximum deviation of fiber orientation in Case 2. The relative angles between the ε_p and the two tract-oriented strains plotted in subfigure (d). The grey dash lines in subfigure (b) and (d) identify the peaking time of $\varepsilon_{tract,u}$ in Case 2.

Discussion

The current study detailed the implementation of an embedded element approach to monitor the real-time fiber orientation in a 3D head model, revealing that fiber orientation was a temporal variable during the impacts. A new scheme was proposed to calculate the tract-oriented strain by resolving the strain tensors from pre-computed simulations along the temporal fiber orientation instead of its static counterpart directly obtained from the DTI. It was verified that incorporating the real-time fiber orientation significantly increases the tract-oriented strain and consequently contributes a generally more extended distribution and a larger volume ratio of WM with high deformation along the fiber tracts.

Being an orientation-dependent parameter, tract-oriented strain is highly sensitive to the variation of fiber orientation. By examining the relative angles between ε_p and two types of tract-oriented strain, it was found that the fiber tracts tended to be oriented toward the direction of ε_p during the impacts. Such a tendency of direction alignment was also noted in one *in vitro* experimental model: by visualizing the configurations of nerve fibers within the brain tissue samples before and after applying uniaxial stretch, Tamura and colleagues[68] observed that the directions of nerve fibers typically oriented to be more parallel to the stretching direction. The general congruency between the current study and the *in vitro* model increased the credibility of the presented computational results.

Besides quantifying the local deviation of fiber orientation, the current study also found that incorporating the real-time fiber orientation amplifies the magnitude of tract-oriented strain and the volume ratio of WM enduring high deformation along its axonal fiber orientation. Such a finding can be explained by the theory of continuum mechanics.[69] A given strain tensor can be projected onto arbitrary directions, resulting in different measures. The maximum principal strain (ε_p) is an invariant of the strain tensor calculated as its maximum eigenvalue, characterizing the largest stretch of an elemental volume along the corresponding eigenvector (i.e., the direction of ε_p). Thus, the more the fiber direction was aligned with the eigenvector, the closer the magnitude of tract-oriented strain was to that of ε_p. The tendency of directional alignment between the real-time fiber orientation and

that of ε_p provided a theoretical explanation for the elevated value observed from $\varepsilon_{tract,u}$ with respect to $\varepsilon_{tract,o}$. Such results also suggested that the tract-oriented deformation might be underestimated in previous studies [37, 40, 50] in which the strain tensor was projected onto a time-invariant vector directly obtained from the DTI (similar to the scheme used to compute $\varepsilon_{tract,o}$ in the current study).

Possibly because of incorporating fiber direction, tract-oriented strain has repeatedly been shown to be an appropriate mechanical parameter for TAI prediction.[36, 38, 40, 44, 47, 48] Nevertheless, the majority of computational studies exclusively employed the accumulated maximum principal strain (ε_p^p) and its derivatives (e.g., CSDM, rate of ε_p, the product of strain and strain rate) as injury predictors in TBI analysis. The current study proposed a new scheme to calculate the tract-oriented strain by incorporating the real-time fiber orientation (i.e., $\varepsilon_{tract,u}^p$). Thus, it is worth examining the relationship between the prevalently used ε_p^p and the newly calculated $\varepsilon_{tract,u}^p$. As illustrated in Figure 9, the model predicted larger ε_p^p than $\varepsilon_{tract,u}^p$ for both concussive impacts, consistent with previous finding[34, 42] that the principal strain was an over-prediction of $\varepsilon_{tract,u}^p$ for brain tissue. By simultaneously scrutinizing the data in Figure 8 and Figure 9, no consistent scaling from ε_p^p to $\varepsilon_{tract,u}^p$ can be detected, indicating that the local strain in the axonal fiber cannot be trivially correlated to the maximum principal strain without taking into account the real-time fiber orientation. It further motivated the necessity of incorporating the $\varepsilon_{tract,u}^p$ as the injury predictor in TBI analysis in the future, especially for TAI analysis.

Figure 9 - Element-wise relationship between ε_p^p and $\varepsilon_{tract,u}^p$ in Case 1 (a) and Case 2 (b).

The current study leverageD the embedded element approach to track the temporal fiber orientation during the simulations. It should be clarified again that the embedded truss elements only served as auxiliary for obtaining the updated orientation of fiber tracts without additional contribution to mechanical stiffness. Such a modeling strategy was deliberately designed to circumvent the issue of volume redundancy. In the embedded element approach, the master elements occupy the full volume of the model, including the volume of the embedded elements. Such an unphysical redundancy triggers a potential underestimation of strains and requires extra elimination.[34, 42] In the current study, the truss elements were simulated as a null constitutive model with nominal density and cross-sectional area. Per the benefit of this modeling strategy, brain strain response was independent of the addition of truss elements given no differences were noted in the strain responses between the Baseline-model and the Truss-embedded-model (Figure 10). This finding further verified that volume redundancy was indeed circumvented in the current study. It should also be clarified that the infinitesimal values for the material properties of truss elements (Table 1) were artificially defined and did not represent the structural dimension of the axonal fibers, similar to the strategy adopted by Wu and colleagues.[42] This was valid given the truss element was intended to only track the real-time fiber orientation without additional mechanical contribution. It should further be clarified that real-time fiber orientation was also considered in those studies that

the whole brain tractography was explicitly modelled,[34, 36, 42, 47] but they did not quantify the influence of real-time fiber orientation.

Figure 10 – Comparison of ε_p distribution in the brain between the Baseline-model and the Truss-embedded-model. Upper row: Coronal cut-sections of ε_p contour at 43 ms for Case 1. Lower row: Sagittal cut-sections of ε_p contour at 23 ms for Case 2.

The current study employed an isotropic constitutive law to represent the mechanical behavior of the brain tissue, similar to other works evaluating the tract-oriented strain.[38-40, 46, 70] This modeling choice was supported by the findings of mechanical testing that no significant mechanical dependency on fiber orientation was noted in the brain tissue.[71-74] Nevertheless, the authors acknowledged that there were a large number of mechanical testing studies instead reporting that brain tissue was mechanically anisotropic.[75-79] To date, several fiber-reinforced hyperelastic anisotropic constitutive models were implemented in the FE models to emulate the direction-dependence of the brain material, such as the Gasser-Ogden-Holzapfel model.[30, 31, 33, 35, 36, 41-43, 80] As was in common in these studies, a correlation between fractional anisotropy (FA) from DTI and fiber-contributed stiffness was assumed. The validity of such modeling assumptions required further verification.[53, 81] For those studies adopting the embedded element approach to explicitly represent the WM fiber tractography, the brain anisotropy can be alternatively simulated by assigning certain

mechanical stiffness to the embedded elements, such as the studies by Garimella and coworkers[34, 82] and Wu and colleagues.[42] As discussed above, this might run into the issue of volume redundancy, as is the case in the study by Garimella and Kraft.[34] Lately, both Garimella and coworkers[82] and Wu and colleagues[42] appropriately addressed the volume redundancy by subtracting the constitutive contribution of the embedded elements from their counterparts of the master elements. Whereas, given the paucity of material properties and geometric features that were directly measured from the axonal fibers themselves, a direct calibration on the constitutive material model for the fiber tractography remained to be performed.[42] Taken together, the authors acknowledged that no consensus has been reached yet, neither for the constitutive modeling of brain tissue nor for the mechanical contribution of axonal fibers in the FE models.[53, 83]

Limitations and future work

Although this study yielded new insights about integrating the real-time fiber orientation into the calculation of tract-oriented strain, certain limitations existed that required further investigation. First and foremost, to ensure computational efficiency, an FE model with relatively low mesh density was used in the current study. To map the orientation information from the DTI with a resolution of 1 mm to the FE model with a mean mesh size of 5.2 mm, a weighted-average approach was inevitably used, which partially caused loss of orientation information and might consequently affect the accuracy of tract-oriented strain.[34, 70] As detailed in the discussion, the strain-induced directional alignment between the real-time fiber orientation and that of ε_p provided a theoretical explanation for the elevated value of $\varepsilon_{tract,u}$ with respect to $\varepsilon_{tract,o}$. Moreover, the general agreement between the current study and a previous *in vitro* model[68] further supported our advocation of incorporating the real-time fiber orientation in the calculation of tract-orientation strain. In addition, the major finding revealed by the relatively coarse model in the current study was verified by another refined FE head model with a mean mesh size of around 1 mm,[39] comparable to the DTI resolution. Detailed

results revealed by the refined FE head model will be presented in a separate study focusing on the dependency of tract-oriented strain on the mesh size.

Compared to these studies[34, 36, 42] in which the whole brain tractography was explicitly incorporated with continuous fiber tracts, the fiber orientation was downsampled in the current study given that only one fiber orientation was assigned to each WM element. Whereas, tractography was not considered to be a gold-standard of white matter architecture (in fact, there is no gold standard yet).[84] Some of the known limitations of tractography include particular challenges in regions of crossing fibers with multiple orientations present within each voxel, which constitute a significant portion of WM. Future version of the proposed model[39] with a mesh resolution that is comparable to that of DTI can increase the number of embedded truss elements and potentially model fiber crossings by embedding multiple truss elements within one WM element.

Another potential limitation was that no relative motion between the truss elements and their master elements was permitted, similarly to the strategies adopted in other computational studies.[34, 36, 42] In contrary to the current study, a gradual coupling between the undulated axons and the surrounding glial cells secondary to mechanical stretching was previously noted in the guinea pig optic nerves[85] and the developing chick embryo spinal cord.[86] Considering the inter-species variation, extrapolation of the results derived from animal experiments to human subjects needs further verification.[87, 88] Moreover, the axonal architectures in the central nervous system exhibit region-dependency. For example, axonal undulation is less prominent in the cerebral region[89] with respect to optic nerves and spinal cord. Such a region-dependency further warrants caution regarding the extrapolation of results obtained from optic nerves and spinal cord to the cerebrum, cerebellum and brainstem as the regions of interest in the current study.

Conclusion

The present study employed an embedded element approach to monitor the real-time fiber orientation during head impacts and proposed a new scheme to calculate the tract-oriented strain by

projecting the strain tensors from pre-computed simulation along the temporal fiber direction instead of its static counterpart directly from the DTI. It was revealed that incorporating the real-time fiber orientation not only altered the direction but also amplified the magnitude of the tract-oriented strain, which led to a generally more extended distribution and a larger volume ratio of WM exposed to high deformation along the fiber tracts. This study provides guidance into how best to incorporate the fiber orientation in head injury models and derive the tract-oriented strain from computational simulations.

Acknowledgements

Drs. Michael Zeineh, Gerald Grant, and David Camarillo have received funding from the Pac-12 Conference's Student-Athlete Health and Well-Being Initiative and Taube Stanford Children's Concussion Initiative. The content of this article is solely the responsibility of the authors and does not necessarily represent the official views of funding agencies. The authors would like to thank Dr. Chiara Giordano for providing an earlier version of the Python code, which is adapted and further used for the computation of tract-oriented strain in this study. The technical support provided by Dr. Hao Chen from Livermore Software Technology Corporation, Livermore, CA (US) is gratefully acknowledged as well. The authors thank the Swedish Research Council (VR-2016-05314) for the support. The simulations were performed on resources provided by the Swedish National Infrastructure for Computing (SNIC) at the center for High Performance Computing (PDC).

Author Disclosure Statement

No competing financial interests exist.

References

1. Taylor, C.A., Bell, J.M., Breiding, M.J. and Xu, L. (2017). Traumatic brain injury–related emergency department visits, hospitalizations, and deaths—United States, 2007 and 2013. Morbidity and mortality weekly report. Surveillance summaries 66, 1-16.
2. Tagliaferri, F., Compagnone, C., Korsic, M., Servadei, F. and Kraus, J. (2006). A systematic review of brain injury epidemiology in Europe. Acta neurochirurgica 148, 255-268.
3. Olesen, J., Gustavsson, A., Svensson, M., Wittchen, H.U., Jönsson, B., Group, C.S. and Council, E.B. (2012). The economic cost of brain disorders in Europe. European journal of neurology 19, 155-162.

4. Meaney, D.F., Morrison, B. and Dale Bass, C. (2014). The mechanics of traumatic brain injury: a review of what we know and what we need to know for reducing its societal burden. Journal of biomechanical engineering 136, 021008.

5. Roozenbeek, B., Maas, A.I. and Menon, D.K. (2013). Changing patterns in the epidemiology of traumatic brain injury. Nature Reviews Neurology 9, 231-236.

6. Mondello, S., Schmid, K., Berger, R.P., Kobeissy, F., Italiano, D., Jeromin, A., Hayes, R.L., Tortella, F.C. and Buki, A. (2014). The challenge of mild traumatic brain injury: role of biochemical markers in diagnosis of brain damage. Medicinal research reviews 34, 503-531.

7. Lauterbach, M.D., Notarangelo, P.L., Nichols, S.J., Lane, K.S. and Koliatsos, V.E. (2015). Diagnostic and treatment challenges in traumatic brain injury patients with severe neuropsychiatric symptoms: Insights into psychiatric practice. Neuropsychiatric disease and treatment 11, 1601.

8. Gennarelli, T.A., Thibault, L.E. and Graham, D.I. (1998). Diffuse axonal injury: an important form of traumatic brain damage. The Neuroscientist 4, 202-215.

9. Povlishock, J., Becker, D., Cheng, C. and Vaughan, G. (1983). Axonal change in minor head injury. Journal of Neuropathology & Experimental Neurology 42, 225-242.

10. Smith, D.H. and Meaney, D.F. (2000). Axonal damage in traumatic brain injury. The neuroscientist 6, 483-495.

11. Bigler, E.D. and Maxwell, W.L. (2012). Neuropathology of mild traumatic brain injury: relationship to neuroimaging findings. Brain imaging and behavior 6, 108-136.

12. Noble, J.M. and Hesdorffer, D.C. (2013). Sport-related concussions: a review of epidemiology, challenges in diagnosis, and potential risk factors. Neuropsychology review 23, 273-284.

13. Shenton, M.E., Hamoda, H., Schneiderman, J., Bouix, S., Pasternak, O., Rathi, Y., Vu, M.-A., Purohit, M.P., Helmer, K. and Koerte, I. (2012). A review of magnetic resonance imaging and diffusion tensor imaging findings in mild traumatic brain injury. Brain imaging and behavior 6, 137-192.

14. LaPlaca, M.C., Simon, C., Prado, G.R. and Cullen, D. (2007). CNS injury biomechanics and experimental models. Progress in brain research 161, 13-26.

15. Montanino, A. (2020). Definition of axonal injury tolerances across scales: A computational multiscale approach. Stockholm, Sweden, KTH Royal Institute of Technology; 2020.

16. Morrison III, B., Elkin, B.S., Dollé, J.-P. and Yarmush, M.L. (2011). In vitro models of traumatic brain injury. Annual review of biomedical engineering 13, 91-126.

17. Bain, A.C., Raghupathi, R. and Meaney, D.F. (2001). Dynamic stretch correlates to both morphological abnormalities and electrophysiological impairment in a model of traumatic axonal injury. Journal of neurotrauma 18, 499-511.

18. Cater, H.L., Sundstrom, L.E. and Morrison III, B. (2006). Temporal development of hippocampal cell death is dependent on tissue strain but not strain rate. Journal of biomechanics 39, 2810-2818.

19. Elkin, B.S. and Morrison, B. (2007). Region-specific tolerance criteria for the living brain. Stapp car crash journal, 127-138.

20. Galbraith, J., Thibault, L. and Matteson, D. (1993). Mechanical and electrical responses of the squid giant axon to simple elongation. Journal of biomechanical engineering 115, 13-22.

21. Morrison, B., Cater, H., Wang, C., Thomas, F.C., Hung, C., Ateshian, G. and Sundstrom, L. (2003). A tissue level tolerance criterion for living brain developed with an in vitro model of traumatic mechanical loading. Stapp car crash journal 47, 93-105.

22. Smith, D.H., Wolf, J.A., Lusardi, T.A., Lee, V.M.-Y. and Meaney, D.F. (1999). High tolerance and delayed elastic response of cultured axons to dynamic stretch injury. Journal of Neuroscience 19, 4263-4269.

23. Tang-Schomer, M.D., Johnson, V.E., Baas, P.W., Stewart, W. and Smith, D.H. (2012). Partial interruption of axonal transport due to microtubule breakage accounts for the formation of periodic varicosities after traumatic axonal injury. Experimental neurology 233, 364-372.

24. Kimpara, H., Nakahira, Y., Iwamoto, M., Miki, K., Ichihara, K., Kawano, S. and Taguchi, T. (2006). Investigation of anteroposterior head-neck responses during severe frontal impacts using a brain-spinal cord complex FE model. Stapp car crash journal 50, 509-544.

25. Kleiven, S. and Hardy, W.N. (2002). Correlation of an FE Model of the Human Head with Local Brain Motion: Consequences for Injury Prediction. Stapp Car Crash journal 46, 123-144.

26. Mao, H., Zhang, L., Jiang, B., Genthikatti, V.V., Jin, X., Zhu, F., Makwana, R., Gill, A., Jandir, G. and Singh, A. (2013). Development of a finite element human head model partially validated with thirty five experimental cases. Journal of biomechanical engineering 135, 111002.

27. Takhounts, E., Eppinger, R., Campbell, J., Tannous, R., Power, E. and Shook, L. (2003). On the Development of the SIMon Finite Element Head Model. Stapp car Crash Journal 47, 107-133.

28. Zhou, Z., Li, X. and Kleiven, S. (2019). Biomechanics of acute subdural hematoma in the elderly: A fluid-structure interaction study. Journal of neurotrauma 36, 2099-2108.

29. Chatelin, S., Deck, C. and Willinger, R. (2013). An anisotropic viscous hyperelastic constitutive law for brain material finite-element modeling. Journal of biorheology 27, 26-37.

30. Cloots, R., Van Dommelen, J., Nyberg, T., Kleiven, S. and Geers, M. (2011). Micromechanics of diffuse axonal injury: influence of axonal orientation and anisotropy. Biomechanics and modeling in mechanobiology 10, 413-422.

31. Cloots, R.J., Van Dommelen, J., Kleiven, S. and Geers, M. (2013). Multi-scale mechanics of traumatic brain injury: predicting axonal strains from head loads. Biomechanics and modeling in mechanobiology 12, 137-150.

32. Colgan, N.C., Gilchrist, M.D. and Curran, K.M. (2010). Applying DTI white matter orientations to finite element head models to examine diffuse TBI under high rotational accelerations. Progress in biophysics and molecular biology 103, 304-309.

33. Ganpule, S., Daphalapurkar, N.P., Ramesh, K.T., Knutsen, A.K., Pham, D.L., Bayly, P.V. and Prince, J.L. (2017). A three-dimensional computational human head model that captures live human brain dynamics. Journal of neurotrauma 34, 2154-2166.

34. Garimella, H.T. and Kraft, R.H. (2017). Modeling the mechanics of axonal fiber tracts using the embedded finite element method. International journal for numerical methods in biomedical engineering 33, e2823.

35. Giordano, C., Cloots, R., Van Dommelen, J. and Kleiven, S. (2014). The influence of anisotropy on brain injury prediction. Journal of biomechanics 47, 1052-1059.

36. Hajiaghamemar, M., Wu, T., Panzer, M.B. and Margulies, S.S. (2019). Embedded axonal fiber tracts improve finite element model predictions of traumatic brain injury. Biomechanics and Modeling in Mechanobiology, 1-22.

37. Hernandez, F., Giordano, C., Goubran, M., Parivash, S., Grant, G., Zeineh, M. and Camarillo, D. (2019). Lateral impacts correlate with falx cerebri displacement and corpus callosum trauma in sports-related concussions. Biomechanics and modeling in mechanobiology 18, 631-649.

38. Ji, S., Zhao, W., Ford, J.C., Beckwith, J.G., Bolander, R.P., Greenwald, R.M., Flashman, L.A., Paulsen, K.D. and McAllister, T.W. (2015). Group-wise evaluation and comparison of white matter fiber strain and maximum principal strain in sports-related concussion. Journal of neurotrauma 32, 441-454.

39. Li, X., Zhou, Z. and Kleiven, S. (2020). A detailed and personalizable head model with axons for brain injury prediction: Sensitivity of brain strain to inter-subject variability of the brain and white matter tract morphology. bioRxiv. https://doi.org/10.1101/2020.05.20.105635.

40. Sullivan, S., Eucker, S.A., Gabrieli, D., Bradfield, C., Coats, B., Maltese, M.R., Lee, J., Smith, C. and Margulies, S.S. (2015). White matter tract-oriented deformation predicts traumatic axonal brain injury and reveals rotational direction-specific vulnerabilities. Biomechanics and modeling in mechanobiology 14, 877-896.

41. Wright, R.M., Post, A., Hoshizaki, B. and Ramesh, K.T. (2013). A multiscale computational approach to estimating axonal damage under inertial loading of the head. Journal of neurotrauma 30, 102-118.

42. Wu, T., Alshareef, A., Giudice, J.S. and Panzer, M.B. (2019). Explicit modeling of white matter axonal fiber tracts in a finite element brain model. Annals of biomedical engineering 47, 1908-1922.

43. Zhao, W. and Ji, S. (2019). White matter anisotropy for impact simulation and response sampling in traumatic brain injury. Journal of neurotrauma 36, 250-263.

44. Giordano, C. and Kleiven, S. (2014). Evaluation of axonal strain as a predictor for mild traumatic brain injuries using finite element modeling. Stapp car crash journal 58, 29-61.

45. Mori, S. and Zhang, J. (2006). Principles of diffusion tensor imaging and its applications to basic neuroscience research. Neuron 51, 527-539.

46. Chatelin, S., Deck, C., Renard, F., Kremer, S., Heinrich, C., Armspach, J.-P. and Willinger, R. (2011). Computation of axonal elongation in head trauma finite element simulation. Journal of the mechanical behavior of biomedical materials 4, 1905-1919.

47. Hajiaghamemar, M. and Margulies, S. (2020). Multi-scale white matter tract embedded brain finite element mode predicts the location of traumatic diffuse axonal injury. Journal of Neurotrauma. ahead of print. http://doi.org/10.1089/neu.2019.6791.

48. Zhao, W., Cai, Y., Li, Z. and Ji, S. (2017). Injury prediction and vulnerability assessment using strain and susceptibility measures of the deep white matter. Biomechanics and modeling in mechanobiology 16, 1709-1727.

49. Giordano, C., Zappalà, S. and Kleiven, S. (2017). Anisotropic finite element models for brain injury prediction: the sensitivity of axonal strain to white matter tract inter-subject variability. Biomechanics and modeling in mechanobiology 16, 1269-1293.

50. Wright, R.M. and Ramesh, K. (2012). An axonal strain injury criterion for traumatic brain injury. Biomechanics and modeling in mechanobiology 11, 245-260.

51. Kleiven, S. (2007). Predictors for traumatic brain injuries evaluated through accident reconstructions. Stapp car crash journal 51, 81-114.

52. Kleiven, S. (2005). Influence of direction and duration of impacts to the human head evaluated using the finite element method. In: *Proceedings of the IRCOBI Conference, Prague, Czech Republic*, pps. 21-23.

53. Budday, S., Ovaert, T.C., Holzapfel, G.A., Steinmann, P. and Kuhl, E. (2019). Fifty shades of brain: a review on the mechanical testing and modeling of brain tissue. Archives of Computational Methods in Engineering, 1-44.

54. Zhou, Z., Li, X. and Kleiven, S. (2019). Fluid–structure interaction simulation of the brain–skull interface for acute subdural haematoma prediction. Biomechanics and modeling in mechanobiology 18, 155-173.

55. Kleiven, S. (2006). Evaluation of head injury criteria using a finite element model validated against experiments on localized brain motion, intracerebral acceleration, and intracranial pressure. International Journal of Crashworthiness 11, 65-79.

56. Kleiven, S. (2006). Biomechanics as a forensic science tool: Reconstruction of a traumatic head injury using the finite element method. Scandinavian Journal of Forensic Science, 73-78.

57. Zhou, Z., Li, X., Kleiven, S., Shah, C.S. and Hardy, W.N. (2018). A Reanalysis of Experimental Brain Strain Data: Implication for Finite Element Head Model Validation. Stapp Car Crash Journal 62, 293-318.

58. Mori, S., Oishi, K., Jiang, H., Jiang, L., Li, X., Akhter, K., Hua, K., Faria, A.V., Mahmood, A. and Woods, R. (2008). Stereotaxic white matter atlas based on diffusion tensor imaging in an ICBM template. Neuroimage 40, 570-582.

59. Hallquist, J.O. (2020). LS-DYNA keyword user's manual. In: *Livermore Software Technology Corporation, USA*.

60. Chen, H. (2019). Methods of improving reinforced concrete structures via numerical simulations. Google Patents.

61. Camarillo, D.B., Shull, P.B., Mattson, J., Shultz, R. and Garza, D. (2013). An instrumented mouthguard for measuring linear and angular head impact kinematics in American football. Annals of biomedical engineering 41, 1939-1949.

62. Liu, Y., Domel, A.G., Yousefsani, S.A., Kondic, J., Grant, G., Zeineh, M. and Camarillo, D.B. (2020). Validation and Comparison of Instrumented Mouthguards for Measuring Head Kinematics and Assessing Brain Deformation in Football Impacts. arXiv:2008.01903.

63. Hernandez, F., Wu, L.C., Yip, M.C., Laksari, K., Hoffman, A.R., Lopez, J.R., Grant, G.A., Kleiven, S. and Camarillo, D.B. (2015). Six degree-of-freedom measurements of human mild traumatic brain injury. Annals of biomedical engineering 43, 1918-1934.

64. Laksari, K., Fanton, M., Wu, L.C., Nguyen, T.H., Kurt, M., Giordano, C., Kelly, E., O'Keeffe, E., Wallace, E. and Doherty, C. (2020). Multi-directional dynamic model for traumatic brain injury detection. Journal of Neurotrauma 37, 982-993.

65. Panzer, M.B., Myers, B.S., Capehart, B.P. and Bass, C.R. (2012). Development of a finite element model for blast brain injury and the effects of CSF cavitation. Annals of biomedical engineering 40, 1530-1544.

66. Zhou, Z., Li, X. and Kleiven, S. (2020). Biomechanics of periventricular injury. Journal of neurotrauma 37, 1074-1090.

67. Bain, A.C. and Meaney, D.F. (2000). Tissue-level thresholds for axonal damage in an experimental model of central nervous system white matter injury. J. Biomech. Eng. 122, 615-622.

68. Tamura, A., Nagayama, K., Matsumoto, T. and Hayashi, S. (2007). Variation in nerve fiber strain in brain tissue subjected to uniaxial stretch. Stapp car crash journal 51, 139-154.

69. Holzapfel, A.G. (2000). Nonlinear solid mechanics: A continuum approach for engineering. Wiley, Chichester.

70. Zhao, W., Ford, J.C., Flashman, L.A., McAllister, T.W. and Ji, S. (2016). White matter injury susceptibility via fiber strain evaluation using whole-brain tractography. Journal of neurotrauma 33, 1834-1847.

71. Budday, S., Sommer, G., Birkl, C., Langkammer, C., Haybaeck, J., Kohnert, J., Bauer, M., Paulsen, F., Steinmann, P. and Kuhl, E. (2017). Mechanical characterization of human brain tissue. Acta biomaterialia 48, 319-340.

72. MacManus, D.B., Pierrat, B., Murphy, J.G. and Gilchrist, M.D. (2017). Region and species dependent mechanical properties of adolescent and young adult brain tissue. Scientific reports 7, 1-12.

73. Pervin, F. and Chen, W.W. (2009). Dynamic mechanical response of bovine gray matter and white matter brain tissues under compression. Journal of biomechanics 42, 731-735.

74. Shuck, L.Z. and Advani, S.H. (1972). Rheological response of human brain tissue in shearing. Transactions of the ASME. J Biomech Eng 94, 905-911.

75. Arbogast, K.B. and Margulies, S.S. (1999). A fiber-reinforced composite model of the viscoelastic behavior of the brainstem in shear. Journal of biomechanics 32, 865-870.

76. Feng, Y., Okamoto, R.J., Namani, R., Genin, G.M. and Bayly, P.V. (2013). Measurements of mechanical anisotropy in brain tissue and implications for transversely isotropic material models of white matter. Journal of the mechanical behavior of biomedical materials 23, 117-132.

77. Jin, X., Zhu, F., Mao, H., Shen, M. and Yang, K.H. (2013). A comprehensive experimental study on material properties of human brain tissue. Journal of biomechanics 46, 2795-2801.

78. Prange, M.T. and Margulies, S.S. (2002). Regional, directional, and age-dependent properties of the brain undergoing large deformation. Journal of biomechanical engineering 124, 244-252.

79. Velardi, F., Fraternali, F. and Angelillo, M. (2006). Anisotropic constitutive equations and experimental tensile behavior of brain tissue. Biomechanics and modeling in mechanobiology 5, 53-61.

80. Giordano, C. and Kleiven, S. (2014). Connecting fractional anisotropy from medical images with mechanical anisotropy of a hyperviscoelastic fibre-reinforced constitutive model for brain tissue. Journal of the Royal Society Interface 11, 20130914.

81. Giordano, C. (2017). Development of an Anisotropic Finite Element Head Model for Traumatic Brain Injury Prediction. Stockholm, Sweden, KTH Royal Institute of Technology; 2017.

82. Garimella, H.T., Menghani, R.R., Gerber, J.I., Sridhar, S. and Kraft, R.H. (2019). Embedded finite elements for modeling axonal injury. Annals of Biomedical Engineering 47, 1889-1907.

83. de Rooij, R. and Kuhl, E. (2016). Constitutive modeling of brain tissue: current perspectives. Applied Mechanics Reviews 68.

84. Maier-Hein, K.H., Neher, P.F., Houde, J.-C., Côté, M.-A., Garyfallidis, E., Zhong, J., Chamberland, M., Yeh, F.-C., Lin, Y.-C. and Ji, Q. (2017). The challenge of mapping the human connectome based on diffusion tractography. Nature communications 8, 1-13.

85. Bain, A.C., Shreiber, D.I. and Meaney, D.F. (2003). Modeling of microstructural kinematics during simple elongation of central nervous system tissue. J. Biomech. Eng. 125, 798-804.

86. Hao, H. and Shreiber, D.I. (2007). Axon Kinematics Change During Growth and Development. Journal of Biomechanical Engineering 129, 511-522.

87. Seok, J., Warren, H.S., Cuenca, A.G., Mindrinos, M.N., Baker, H.V., Xu, W., Richards, D.R., McDonald-Smith, G.P., Gao, H. and Hennessy, L. (2013). Genomic responses in mouse models poorly mimic human inflammatory diseases. Proceedings of the National Academy of Sciences 110, 3507-3512.

88. Smith, D.H., Nonaka, M., Miller, R., Leoni, M., Chen, X.-H., Alsop, D. and Meaney, D.F. (2000). Immediate coma following inertial brain injury dependent on axonal damage in the brainstem. Journal of neurosurgery 93, 315-322.

89. Mikula, S., Binding, J. and Denk, W. (2012). Staining and embedding the whole mouse brain for electron microscopy. Nature methods 9, 1198-1201.

Appendix A: Sensitivity analysis on the length of embedded truss elements

A sensitivity analysis was conducted to investigate the dependency of fiber orientation variation (i.e., $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$) and strain response on the length of the embedded truss element. For the strain response, the first principal Green-Lagrange strain (i.e., ε_p) and tract-oriented Green-Lagrange strain (characterized by $\varepsilon_{tract,u}^{p}$ and $\varepsilon_{tract,u}^{p,95}$) were selected, both of which were parameters of interest in the current study. A detailed definition for these symbols is available in Table 3 in the "Post-processing and data analysis" section of this current study.

To achieve this analysis, three models were developed with the length of embedded truss elements as 2 mm (Model 1), 1 mm (Model 2), and 0.5 mm (Model 3), respectively (Figure A1). For a given truss element that was correspondingly embedded within a white matter (WM) element (serving as a master element), one node located at the centroid of the master element and the other fell within the boundary of the master element. The orientation of the truss element was obtained from the diffusion tensor imaging (DTI) via a weighted-average procedure as detailed in the "Computation of tract-oriented strain with static fiber orientation" section of this current study. Material properties of the truss elements and the coupling strategy between truss elements and WM elements were the same as that detailed in the "Implementation of embedded element method for fiber orientation modeling" section of this current study. Thus, the only difference among the three

models was the length of the truss elements. A concussive impact (i.e., Case 1 as detailed in the "Loading conditions" section of this current study) was imposed on three models, respectively.

Figure A1 – (a) Isometric view of the brain (in gray) in Model 1 with the embedded truss elements as 2 mm (in blue). (b) Isometric view of the brain (in gray) in Model 2 with the embedded truss elements as 1 mm (in blue). (c) Isometric view of the brain (in gray) in Model 3 with the embedded truss elements as 0.5 mm (in blue). In all subfigures, half of the brain is masked for better illustration and an enlarged view is provided for a representative element to illustrate the length of the truss element.

Figure A2 plots the time-history curves of maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ in six brain subregions. It can be noted that the maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ was insensitive to the length of the truss elements given that the curves predicted by the three models overlapped with each other.

Figure A2 – Time history curves of maximum $\theta_{<\varepsilon_{tract,o},\varepsilon_{tract,u}>}$ in six brain subregion predicted by the three models for Case 1.

Figure A3 shows the coronal cut-section ε_p contour without notable variation among the three models. For the tract-oriented strain, the three models predicted the identical value of $\varepsilon_{tract,u}^{p,95}$ as 0.22 (Figure A4 (a)). Same distributions of WM elements with $\varepsilon_{tract,u}^p$ over 0.14 were also noted among the three models (Figure A4 (b)).

Figure A3 – Coronal cut-section of ε_p contour predicted by the three models at 43 ms for Case 1.

Figure A4 – (a) Comparison of $\varepsilon_{tract,u}^{p,95}$ predicted by the three models for Case 1; (b) Top view of WM elements with $\varepsilon_{tract,u}^p$ over 0.14 for Case 1.

Based on the identical response revealed by the three models, it can be concluded that, under the condition that a truss element oriented along a predefined direction with both ends within the same master element, neither the deviation of fiber orientation nor the brain strain response was sensitive to the length of the embedded truss elements.