InterPepRank: Assessment of Docked Peptide Conformations by a Deep Graph Network

Isak Johansson-Åkhe[1]   Claudio Mirabello[1]
Björn Wallner[1,*]

September 7, 2020

Abstract

Motivation: Peptide-protein interactions between a smaller or disordered peptide stretch and a folded receptor make up a large part of all protein-protein interactions. A common approach for modeling such interactions is to exhaustively sample the conformational space by fast-fourier transform based docking, and then refining a select top percentage of decoys. Commonly, the methods capable of ranking the decoys for selection in short enough time for larger scale studies rely only on first-principle energy terms derived directly from structure such as electrostatics, van der Waals forces, or on precalculated statistical pairwise potentials.

Results: In this work, we present InterPepRank for peptide-protein complex scoring and ranking. InterPepRank is a machine-learning based method which encodes the structure of the complex as a graph; with physical pairwise interactions as edges and evolutionary features such as PSSM and sequence conservation as nodes. The graph representation is trained to predict the LRMSD of decoys by using edge-conditioned graph convolutions on a large set of peptide-protein complexes, and performance is maximised by an ensembled prediction of variying network architectures. InterPepRank is tested on an independent test set with no targets sharing CATH family nor 30% sequence identity with any target in training or validation data. On this set, InterPepRank has a mean AUC of 0.70 for finding peptide-protein complexes with LRMSD<4Å. This is an improvement compared to other state-of-the-art ranking methods that have a mean AUC in the 0.59-0.66 range. When included as the selection-method for selecting decoys for refinement in a previously established peptide docking pipeline, InterPepRank improves the number of Medium and High quality models produced by 80 and 40% respectively, proving its usefulness in decoy selection.

Availability: The program is available from: *http://wallnerlab.org/InterPepRank*

Contact: Björn Wallner bjorn.wallner@liu.se

Supplementary information: Supplementary data are available at *BioRxiv* online.

1   Introduction

Interactions between a short stretch of amino acid residues and a larger protein receptor, referred to as peptide-protein interactions, make up approximately 15-40% of all inter-protein interactions (Petsalaki and Russell, 2008), and are involved in and regulate vital biological processes (Midic *et al.*, 2009; Tu *et al.*, 2015). These short peptide stretches are often disordered when unbound or part of larger disordered regions (Petsalaki and Russell, 2008; Neduva, Victor *et al.*, 2005). Because of their inherent flexibility predicting peptide-protein interaction complexes is difficult.

However, since the peptide ligand is a smaller molecule, it is possible to exhaustively sample the binding space by fast-Fourier transform docking (FFT docking). Classically, this requires a close to correct rigid receptor and ligand, but as shown in (Alam *et al.*, 2017), a set of poses derived from protein fragments with sequence similar to the peptide can consistently produce conformations near the native bound conformation. While the strength of FFT-docking is the exhaustive search of docking space, the problem, as we will show, is that the energy function used is a limited approximation of the binding affinity, and thus even though the method samples many near-native decoys it often fails to separate them from poor decoys. Additionally, rigid-body-docking needs to be followed up with much more computationally expensive refinement to reliably produce native contacts and binding modes.

A workflow previously shown to be successful is to rescore and refine promising decoys using a more advanced energy-function, such as Rosetta (Raveh *et al.*, 2010). Indeed, previous works have shown great success in the peptide-protein docking area by combining FFT-based docking with Rosetta refinement (Alam *et al.*, 2017). However, because of the cost in computational time in running refinement, only a subset if the FFT-generated decoys can be used. This selection is based on the energy function of the FFT method, resulting in unnecessary refinement of several decoys unsalvageable by the refinement protocol.

An improvement to this approach would be to run all decoys through a fast and accurate re-scoring algorithm to select decoys for refinement, rather than relying on energy functions constrained to FFT-compatibility. Many methods have been developed for the rescoring of protein-protein complexes, some examples include: PyDock evaluates decoys based on pairwise electrostatic potentials and desolvation energy (Pallara *et al.*, 2017; Cheng *et al.*, 2007). Zrank and Zrank2 utilizes van der Waals in excess of electrostatics and desolvation (Pierce and Weng, 2007, 2008). OPUS-PSP uses orientation-dependent packing and knowledge-based repulsive energy (Lu *et al.*, 2008). SIPPER uses statistical residue-pair potentials derived from a curated interaction-set (Pons *et al.*, 2011). However, most rescoring methods for docked complexes are not optimized for the peptide-protein problem, and to the best of our knowledge still rely on either physics-based manually defined energy-functions, or knowledge-based and empirically tested energy-function approximations, that do not take evolutionary information of the target into account. More advanced methods using machine learning, like ProQDock (Basu and Wall-

ner, 2016), have running times unfeasible for application on a large set of decoys and are better suited for evaluating a small set of refined models.

Within structural bioinformatics, Graph Convolutional Networks (GCNs) have seen increased use recently through applications such as PipGCN which uses a pairwise classification architecture and evolutional features to predict protein-protein binding sites (Fout *et al.*, 2017), the GCN of (Gligorijevic *et al.*, 2019) which feeds pre-trained LSTM sequence feature extraction to a graph network to classify protein function, EGCN which uses edge-based graph convolutions to score protein-protein complexes with the use of simple features such as side-chain charge and hydrophobicity (Cao and Shen, 2019), and GCNN of (Zamora-Resendiz and Crivelli, 2019) which encodes spatial information into the residue-nodes to classify proteins. A Graph Convolutional Network eschews the spatial limitations of a classic convolutional network and allows for the direct definition of spatial relationships on a case-by-case basis. It passes information along pre-defined edges between nodes rather than by proximity in the input-matrix, while still allowing for complex information, such as evolutionary information, to be encoded in the nodes.

In this work, we present a fast, novel, rescoring algorithm utilizing GCNs to represent the peptide-protein complex with the added context of evolutionary information. The GCNs is capable of quickly sift through and rank the complete space of conformations generated by FFT-methods and improving the selection of decoys for subsequent refinement.

2 Materials and Methods

2.1 IPD0220 Dataset

A set of 6,857 interacting peptide-protein pairs taken from the PDB (Berman *et al.*, 2000) at 15/10/2018 was redundancy reduced by 30% sequence identity down to 711 pairs and divided into three parts: a test set of 51 targets, validation set of 50 targets, and training set of 610 targets. In this case, a peptide-protein interaction is defined as a peptide of 25 or fewer residues sharing a contact surface of at least 400Å^2 with a receptor of 50 residues or more. The construction of the sets was constrained so that no receptor in a set shared CATH family (Dawson *et al.*, 2017) annotation with any receptor from another set. In the case a receptor lacked CATH annotation, it was aligned to all other receptors with TM-align (Zhang and Skolnick, 2005) and classified as part of any family where it matched any receptor with a TM-score (Zhang and Skolnick, 2004) of 0.4 or more.

2.2 Peptide-Protein Docked Decoys

To train, validate, and test the method, a large number of varied structure decoys were needed. To achieve more variety and difficulty in the training and test sets respectively, the peptide conformations were generated rather than using the native conformations alone. For each target in the IPD0220 dataset, 50 different peptide conformations were generated

using the Rosetta fragment-picker (Gront *et al.*, 2011). Each of these conformations were exhaustively docked on the surface of their receptors by PIPER fast-fourier-transform based docking (Kozakov *et al.*, 2006), generating 70,000 decoys for each conformation for each target in the validation and test sets. To enable rapid method development, only a random subset 2,500 decoys per target were used in the validation.

2.2.1 Training Set Augmentation

To increase the variety of training set decoys, decoys were generated for all peptide-protein pairs sharing sequence similarity to those in the training set, but still different in both sequence and CATH family from the validation and test sets, rather than only using the redundancy-reduced representatives of the training set. Decoys were generated for each of the expanded number of 2,536 training targets. However, the number of decoys which could be contributed to training by each CATH family was limited by the median number of correct decoys each CATH family produced, to still limit bias while simultaneously covering a larger space of varied structures and decoys. What constitutes a correct decoy is defined under the Metrics category below. On average, each target could contribute 426 decoys.

To ensure that each of the training, validation, and test sets represent the total dataset, the distribution of LRMSD, of all decoys for each set were compared with Kolmogorov-Smirnov test to the distribution of all data not in the set. These tests showed that the sets could not be said to represent different distributions (p-values >0.37).

2.3 Metrics

Several different metrics are used to evaluate the performance of Inter-PepRank and other methods benchmarked.

2.3.1 Metrics for Rigid-Body-Docked decoys - Correct Decoys

In the perspective of ranking rigid-body-docked decoys, a decoy is defined as correct if it has the peptide positioned within 4.0Å ligand root-mean square deviation (LRMSD) of the native conformation. This limit was selected both as it is within the reported limit of when the Rosetta Flex-PepDock refinement protocol can reliably refine decoys to sub-Ångström precision (Raveh *et al.*, 2010), and since it is below the CAPRI limit for an acceptable prediction of a docked peptide-protein complex (Lensink *et al.*, 2017).

Since the goal of the method presented herein is not to produce final high-quality predictions, but rather to select which rigid-body-docked decoys are worth refining, a higher cutoff than the sub-Ångström high-quality model cutoff was selected.

Model Quality	LRMSD	iRMSD	fnat
Acceptable	below 5.0 Å	below 2.0 Å	above 20%
Medium	below 2.0 Å	below 1.0 Å	above 50%
High	below 1.0 Å	below 0.5 Å	above 80%

Table 1: CAPRI criteria for peptide-protein docked model quality (Lensink *et al.*, 2017). iRMSD is the root mean square deviation of residues at the native interface. Fnat is the fraction native residue-residue contacts recalled.

2.3.2   Metrics for Refined Models - Acceptable, Medium, High

Later in the paper, the quality of models refined from the rigid-body-docked decoys by the Rosetta FlexPepDock refinement is discussed. In this case, molecular details of interaction and sub-Ångström positioning of the peptide becomes relevant, and the more lax definition of a correct decoy established earlier needs to be supplemented. The CAPRI standard for judging refined peptide-protein docked complexes can be found in table (Lensink *et al.*, 2017).

2.3.3   ROC

A receiving operand characteristic-curve (ROC-curve) measures how two metrics change in relation to each-other, here False Positive Rate (FPR) and True Positive Rate (TPR), as the threshold for scoring is varied.

False Positive Rate is defined as:

$$FPR = \frac{FP}{N}$$

where FP is the number of decoys incorrectly identified as correct and N is the total number of incorrect decoys in the set.

True Positive Rate is defined as:

$$TPR = \frac{TP}{P}$$

where TP is the number of correctly identified correct decoys and P is the total number of correct decoys in the set.

2.4   Representation and Architecture

2.4.1   Decoy Representation

The graph network utilizes edge-conditioned graph convolutions, where the input is a set of nodes, each one described by a set of input features, as well as edges of different types between nodes. In this case, nodes represent individual residues of a decoy and edges denote different types of interactions between couples of residues. In this study, the node features used were Amino Acid Code (one-hot encoded, 21 values to account for unknown residues), a Position-Specific Scoring Matrix (21 values including gaps, Eq. 1), Self-Entropy (21 values, including gaps, Eq. 2), and

one variable denoting if the residue belongs to the peptide or receptor (1 value), for a total of 64 features. Multiple sequence alignments for calculation of PSSM and self-entropy were acquired by running HHBLITS 2.0.15 with uniclust30 as the database.

$$PSSM_i = -\log \frac{p_i}{p_{bi}} \tag{1}$$

$$S_i = -p_i \log \frac{p_i}{p_{bi}} \tag{2}$$

where p_i is the frequency of the amino acid on position i recurring at that position in the multiple sequence alignment and p_{bi} is the background probability of that amino acid.

Four types of one-hot-encoded edges were used: self-edges to allow the passing on of information to the same residue in consecutive layers, covalent edges denoting the existence of a covalent bond between two residues, proximity edges between each pair of residues with any heavy atoms within 4.5Å, and a summarizing identity to mark the presence of any edge. For each decoy, only 100 nodes and the vertices that connected them were used; the peptide and the residues of the receptor closest to the peptide. This means that if the peptide is 25 residues long and the receptor 170 residues, the 100 nodes would include the 25 peptide residues as well as the 75 residues from the receptor which were closest to any peptide amino acid. For cases where all the residues in the complex amount to fewer than 100, zero-padding is used.

2.4.2 Network Architecture

The network was implemented as a small, simple, feed-forward graph convolutional network, and a graphical representation of it is available in Figure 1. Before any convolutions were applied, the node feature Amino Acid Code (one-hot encoded 21 value feature) was passed through an Embedding Layer to reduce dimensionality and thus also the number of weights, limiting overfitting. Embedding layers are small network architectures for mapping discrete labels onto continuous space, are frequently used in areas such as language processing (Mikolov *et al.*, 2013), and have previously successfully been used to describe amino acids (Mirabello and Wallner, 2019).

Next, the node features were passed through a varied number of Edge Convolution Layers (Simonovsky and Komodakis, 2017), with ReLU activation between each layer, taking the output of the last layer as node features for the next, while keeping the same edge features throughout. Edge Convolution Layers learn filters as a function of both node and edge features, and apply these filters along the edges of the graph.

The output from each convolution layer was concatenated together before global pooling of all node features, followed by 2 dense layers before prediction. During training, a dropout ranging between 0.1 and 0.25 was applied to the edge features. Different sizes of the Edge Convolution and Dense outputs were explored, as well as different methods for Pooling, see below.

The network was implemented using Spektral and Keras (Chollet *et al.*, 2015), using the layers proposed by (Simonovsky and Komodakis, 2017), and trained with the TensorFlow backend (Abadi *et al.*, 2015).

The networks were trained as classifiers to predict to which bin of S-normalized LRMSD the decoys belong:

$$LRMSD_{SN} = \frac{1}{1 + (\frac{d}{4.0})^2} \tag{3}$$

where d is the distance to native position. The bins were defined by dividing the 0.0 to 1.0 S-normalized LRMSD range in evenly distributed parts, according to how many labels the architecture was trained with. When used for prediction, the bins were summarized by a weighted average based on the S-normalized LRMSD the bins represent.

In an early stage of the study, other architectures and representations were explored, including using simple graph convolutions without conditioned edges, and using traditional 3D-convolutional networks on a voxelized space around the ligand in a 20×20×20 Å box. These were discarded because of their low performance as measured on the validation data. For example, while top100 per target enrichment over random averaged to roughly 2 to 14 on the validation set when using edge conditioned graph convolutions, the best voxel representation net only managed a top100 per target enrichment over random of 1.66.

2.4.3 Parameter Optimization and Ensembling

Parameters and hyperparameters of the net were optimized to maximize performance on the validation set. Additionally, to increase the predicting power of InterPepRank with little impact on runtime, some of the best-performing trained nets were employed together as an ensemble by averaging their outputs.

3 Results and Discussion

In this work we have developed InterPepRank, a machine-learning based method which encodes the structure of peptide-protein complex as a graph; with physical pairwise interactions as edges and evolutionary features such as PSSM and sequence conservation as nodes. The graph representation is trained to predict the LRMSD of decoys by using edge-conditioned graph convolutions on a large set of peptide-protein complexes. Different network architectures were tried and the nine best (0-8) on validation are shown in Figure 2, details on specific network architecture in the Supplementary Information. To maximize performance a subset of these were used as an ensemble predictor, averaging over their output; best ensemble used all networks except 5 and 6.

3.1 Comparison to Established methods

To put the performance of InterPepRank into perspective, we compared its ranking strength to several established state-of-the-art protein-protein

complex scoring methods: PIPER (Kozakov *et al.*, 2006), pyDock3 (Cheng *et al.*, 2007), and ZRANK (Pierce and Weng, 2007). PIPER was run with the same rotation and energy matrices as when part of the peptide-protein docking protocol PIPER-FlexPepDock (Alam *et al.*, 2017). Although both pyDock3 and ZRANK are optimized for the scoring of protein-protein complexes, pyDock3 was recently shown to efficiently identify near-native peptide decoys in the sixth CAPRI edition (Pallara *et al.*, 2017), and ZRANK is included as one of the currently leading fast available protein-protein scoring functions according to (Moal *et al.*, 2013) and (Yan and Huang, 2019), amongst others. It should be noted that PIPER was used to generate the decoys of this study.

As discussed in the introduction, currently there is a lack of ready-to-use scoring functions developed specifically for peptide-protein complexes. Technically, the Rosetta FlexPepDock protocol can be run in a mode which only applies its scoring function without changing the structure. However, Rosetta scoring tends to perform poorly on structures which have not been at least relaxed through the Rosetta relax protocol, in addition to being comparatively slow as compared to the other scoring methods presented herein. In the Supplementary Information, the performance of scoring with Rosetta FlexPepDock scoring-only can be found (Supplementary Figure 1 and Supplementary Table 11).

Overall InterPepRank is much better than ZRANK, pyDock3 and PIPER at assessing the absolute quality of individual decoys in comparison to both other decoys from the same target and between targets, see Figure 3, with an AUC of 0.905 compared to 0.71 and 0.69 for pyDock3 and ZRANK, respectively. PIPER is slightly worse with AUC 0.66. This is unsurprising as the other scoring methods investigated are dependent on complex size and primary structure composition.

More interesting to the case at hand, selecting decoys for further refinement, is looking at the ability to rank decoys for individual targets. InterPepRank is still slightly better compared to Zrank (average AUC 0.70 vs 0.66 for Zrank), see Figure 4. But the margin is not as large as for the overall ranking. We speculate that the reason for this discrepancy might be that InterPepRank is optimized for assessing the overall quality.

3.1.1 Run-time and Large-scale Studies

Although slower than Zrank, the InterPepRank still operate well within the realm of possibility of use in large-scale studies, see Table 2. Additionally, most of the time (circa 95%) of InterPepRank is spent preparing the graph-input to the net, something which could be optimized as compiled code rather than run as a python script.

3.2 Proof of concept: Improving the PIPER-FlexPepDock pipeline

The purpose of InterPepRank is to provide an accurate rescoring step for selecting which decoys from FFT-based rigid-body-docking are worth further refining to achieve sub-Ångström docked complexes. The PIPER-FlexPepDock pipeline (Alam *et al.*, 2017) uses FFT-based PIPER to dock

Method	pyDock3	Zrank	InterPepRank
Mean Time (min)	664.4	9.2	100.6
Median Time (min)	574.9	7.2	85.4
60 residue receptor (min)	293.1	2.9	57.2
472 residue receptor (min)	1372.6	24.7	249.2

Table 2: Average runtime over all targets for the different methods to evaluate 70000 decoys, as measured in minutes, assuming all relevant files are available for each target. In the case of the 60 residue receptor and 472 residue receptor rows, it is instead the average runtime to evaluate 70000 decoys over the 50 different peptide conformations. All calculations were performed on a single CPU core of Intel Xeon Gold 6130 running on CentOS 7, and when applicable an Nvidia GeForceRTX 2080 Ti graphics card was available. If InterPepRank is run completely on CPU, add approximately 30 minutes to the runtime.

peptides of varying conformations onto a receptor surface, selects 12500 decoys for further refinement by the Rosetta FlexPepDock protocol, and lastly clusters the top 1% of the refined decoys to make final docking predictions.

As a proof of concept, the full PIPER-FlexPepDock pipeline was run on the entire test-set both as is, and with InterPepRank, Zrank, or py-Dock3 selecting decoys for refinement rather than relying on the output-score of PIPER. The results were analyzed according to the CAPRI standard of classifying docked peptide-protein structures as compared to their native structures (Lensink *et al.*, 2017), and can be found in Table 3. It should be noted that many of the peptides in the test set are longer than the maximum length investigated in the original PIPER-FlexPepDock paper, explaining the overall decrease in performance as compared to that paper. As seen in the table, both InterPepRank and Zrank are capable of improving the performance of PIPER-FlexPepDock if inserted as a function selecting decoys for refinement. While the inclusion of Zrank leads to a higher number of Acceptable models as per the CAPRI standard, the inclusion of InterPepRank leads to a higher yield of both Medium and High quality models. This is in line with the ROC-curves in FIgure 4, where Zrank can be seen to have fewer decoys for which it shows a ROC AUC below 0.5 than InterPepRank, but where the average and median AUC of InterPepRank are higher.

This is also reflected in the overall distribution LRMSD of the decoys sent for refinement by InterPepRank and Zrank: while InterPepRank both in mean and median selects more decoys with lower LRMSD, Zrank performs a wider sampling of conformations resulting in a generally lower number of low LRMSD decoys, but meaning more targets have at least one low LRMSD decoy, see Supplementary Figure 2.

3.2.1 Improving Runtime with Score Threshold

InterPepRank score is independent from protein and receptor size and composition, and only depends on the relative quality of each decoy,

Re-scoring Method	Acceptable	Medium	High
InterPepRank	15.33	**9.66**	**3.33**
Zrank	**18.0**	7.0	2.33
pyDock3	13.33	5.0	0.0
None (PIPER)	13.66	5.33	2.33

Table 3: For how many of the targets in the test-set the modified PIPER-FlexPepDock pipeline produced models of the different quality measures among the top 10 results. As Rosetta FlexPepDock is a Monte-Carlo based approach, the part of the pipeline utilizing the FlexPepDock protocol and onwards was run in triplicates and the results averaged.

which can be seen in Figure 3 showing InterPepRank can sort decoys even between targets. Because of this, it should be possible to introduce a score-threshold to avoid refining guaranteed bad decoys, as predicted by the InterPepRank score, rather than simply picking the top X decoys for refinement.

Indeed, adding an InterPepRank score cutoff of 0.47 for picking decoys for refinement rather than always picking the top 12,500 decoys reduces the median number of decoys refined per target to 10,000, while at least one High- or Medium-quality decoy will be produced for just as many targets as picking the top 12.500 decoys for refinement by InterPepRank without the threshold, and 95% of all targets which have at least one Acceptable decoy among the 12,500 will still have at least one.

Considering the median run-time of FlexPepDock refinement being 1.55 minutes on the same systems used for the re-scoring method speed benchmark, this results in the usage of an InterPepRank threshold saving on average 3,875 minutes of run-time, more than making up for the extra minutes spent running InterPepRank.

3.3 Example

As seen in previous works, machine learning methods for prediction of binding sites tend to predict protein-protein binding sites as potential peptide-protein binding sites, often resulting in difficulties in differentiating an interaction with the correct binding site from an interaction with another site, like one for protein-protein binding, or even crystal contacts (Johansson-Åkhe *et al.*, 2020, 2018). A problem with shape-complementarity or electrostatics based methods on the other hand is their preference for conformations which maximize the number of contacts.

In this study, an example of a target difficult to both kinds of methods would be Siah1 (PDB ID: 4i7b). Its asymmetric unit, as well as many structural homologues, display it in a dimeric conformation, with the peptide binding at the opposite side of the protein. Additionally, there is a secondary hydrophobic groove which could maximize contacts with a potential peptide and has the same charge-distribution as the correct binding site. See Figure 5. While the true site shows an average evolu-

tionary entropy of 0.520 and the dimerization site shows a similar entropy of 0.521, the hydrophobic groove shows less conservation with an entropy of 0.544 and the rest of the protein surface shows 0.603.

For this target, InterPepRank identified several locally favorable positions for the peptide, see Figure 6. The three wells roughly represent distances to the native peptide from decoys close to the native peptide, decoys bound at the hydrophobic groove by the helix, and decoys bound at the false dimerization site, respectively. These sites have average InterPepRank scores of 0.531, 0.496, and 0.465, respectively, while decoys bound over the rest of the protein surface average an InterPepRank score of 0.381. Similarly, the energy-based methods also report a lower average for the true binding site (-38.286 for Zrank and -3.150 for pyDock3) compared to the alternative sites (-30.4451 and -3.9 for the hydrophobic groove by the helix, and 4.145 and 3.108 for the dimerization site) and the rest of the protein surface (-7.142 and 4.742 respectively), albeit with some variation as pyDock3 generally prefers the groove by the helix to the correct site and Zrank ranks the dimerization site even worse than the rest of the surface. For InterPepRank, this shows that the method doesn't simply pick decoys arranged at conserved sites, but judges on more metrics, which is also supported by the fact that the length of the receptor multiple sequence alignment as well as the quality of alignments therein do not correlate with the quality of prediction (R < 0.1), and that simpler Machine Learning models with the same architecture but less edge information perform worse (data not shown).

Similar scatter-plots for all test-targets and all methods benchmarked can be found in the Supplementary Information.

4   Conclusions

We have presented InterPepRank, a peptide-protein complex scoring and ranking method for use of rescoring and selecting coarse rigid-body-docking decoys for further refinement. InterPepRank uses both the structure of the complex and evolutionary features such as PSSM and sequence conservation to achieve high accuracy scoring in manageable computational time. The structure and the features are encoded in a graph representation where physical interactions between peptide and protein are represented as edges and the features are encoded in the nodes. The graph representation is trained using graph convolutions on a large set of peptide-protein complexes to predict the quality as measured by LRMSD. To maximize performance, the output of an ensemble of different network architectures are averaged in the final prediction.

On an independent test set not used to train and validate the method, InterPepRank has a mean AUC of 0.70 for finding peptide-protein complexes with LRMSD<4Å. This is an improvement compared to other ranking methods that have a mean AUC in the 0.59-0.66 range.

When inserted in the PIPER-FlexPepDock pipeline, InterPepRank consistently improves the performance of the pipeline by improving the selection of decoys for refinement, resulting in a 40% increase in High quality models produced, and a 80% increase in Medium quality models produced,

together with the possibility of reducing the overall computational time without loss in performance by filtering decoys by InterPepRank score.

In addition to selecting peptide-protein complexes for all-atom refinement, InterPepRank should prove useful for providing a cross-target comparable scoring function.

Acknowledgments

This work was supported by a Swedish Research Council grant, 2016-05369, The Swedish e-Science Research Center, and the Foundation Blance-flor Boncompagni Ludovisi, née Bildt. The computations were performed on resources provided by the Swedish National Infrastructure for Computing (SNIC) at the National Supercomputer Centre (NSC) in Linköping.

References

Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., Levenberg, J., Mané, D., Monga, R., Moore, S., Murray, D., Olah, C., Schuster, M., Shlens, J., Steiner, B., Sutskever, I., Talwar, K., Tucker, P., Vanhoucke, V., Vasudevan, V., Viégas, F., Vinyals, O., Warden, P., Wattenberg, M., Wicke, M., Yu, Y., and Zheng, X. (2015). TensorFlow: Large-scale machine learning on heterogeneous systems. Software available from tensorflow.org.

Alam, N., Goldstein, O., Xia, B., Porter, K. A., Kozakov, D., and Schueler-Furman, O. (2017). High-resolution global peptide-protein docking using fragments-based PIPER-FlexPepDock. *PLoS computational biology*, **13**(12), e1005905.

Basu, S. and Wallner, B. (2016). Finding correct protein–protein docking models using proqdock. *Bioinformatics*, **32**(12), i262–i270.

Berman, H. M., Westbrook, J., Feng, Z., Gilliland, G., Bhat, T. N., Weissig, H., Shindyalov, I. N., and Bourne, P. E. (2000). The protein data bank. *Nucleic Acids Research*, **28**(1), 235–242.

Cao, Y. and Shen, Y. (2019). Energy-based graph convolutional networks for scoring protein docking models. *arXiv preprint arXiv:1912.12476*.

Cheng, T. M.-K., Blundell, T. L., and Fernandez-Recio, J. (2007). pydock: electrostatics and desolvation for effective scoring of rigid-body protein–protein docking. *Proteins: Structure, Function, and Bioinformatics*, **68**(2), 503–515.

Chollet, F. *et al.* (2015). Keras.

Dawson, N. L., Lewis, T. E., Das, S., Lees, J. G., Lee, D., Ashford, P., Orengo, C. A., and Sillitoe, I. (2017). Cath: an expanded resource to predict protein function through structure and sequence. *Nucleic acids research*, **45**(D1), D289–D295.

Fout, A., Byrd, J., Shariat, B., and Ben-Hur, A. (2017). Protein interface prediction using graph convolutional networks. In *Advances in neural information processing systems*, pages 6530–6539.

Gligorijevic, V., Renfrew, P. D., Kosciolek, T., Leman, J. K., Cho, K., Vatanen, T., Berenberg, D., Taylor, B. C., Fisk, I. M., Xavier, R. J., *et al.* (2019). Structure-based function prediction using graph convolutional networks. *bioRxiv*, page 786236.

Gront, D., Kulp, D. W., Vernon, R. M., Strauss, C. E., and Baker, D. (2011). Generalized fragment picking in rosetta: design, protocols and applications. *PloS one*, **6**(8), e23294.

Johansson-Åkhe, I., Mirabello, C., and Wallner, B. (2018). Predicting protein-peptide interaction sites using distant protein complexes as structural templates. *bioRxiv*, page 398768.

Johansson-Åkhe, I., Mirabello, C., and Wallner, B. (2020). Interpep2: Global peptide-protein docking using interaction surface templates. *Bioinformatics*.

Kozakov, D., Brenke, R., Comeau, S. R., and Vajda, S. (2006). Piper: an fft-based protein docking program with pairwise potentials. *Proteins: Structure, Function, and Bioinformatics*, **65**(2), 392–406.

Lensink, M. F., Velankar, S., and Wodak, S. J. (2017). Modeling proteinprotein and proteinpeptide complexes: CAPRI 6th edition. *Proteins: Structure, Function, and Bioinformatics*, **85**(3), 359–377.

Lu, M., Dousis, A. D., and Ma, J. (2008). Opus-psp: an orientation-dependent statistical all-atom potential derived from side-chain packing. *Journal of molecular biology*, **376**(1), 288–301.

Midic, U., Oldfield, C. J., Dunker, A. K., Obradovic, Z., and Uversky, V. N. (2009). Protein disorder in the human diseasome: unfoldomics of human genetic diseases. *BMC Genomics*, **10 Suppl 1**, S12.

Mikolov, T., Chen, K., Corrado, G., and Dean, J. (2013). Efficient representation of word representations in vector space. In *Proceedings of the international workshop on learning representations (ICLR)*.

Mirabello, C. and Wallner, B. (2019). rawmsa: End-to-end deep learning using raw multiple sequence alignments. *PloS one*, **14**(8).

Moal, I. H., Torchala, M., Bates, P. A., and Fernández-Recio, J. (2013). The scoring of poses in protein-protein docking: current capabilities and future directions. *BMC bioinformatics*, **14**(1), 286.

Neduva, Victor, Linding, Rune, Su-Angrand, Isabelle, Stark, Alexander, de Masi, Federico, Gibson, Toby J, Lewis, Joe, Serrano, Luis, and Russell, Robert B (2005). Systematic discovery of new recognition peptides mediating protein interaction networks. *PLoS biology*, **3**(12), e405.

Pallara, C., Jiménez-García, B., Romero, M., Moal, I. H., and Fernández-Recio, J. (2017). pydock scoring for the new modeling challenges in docking: Protein–peptide, homo-multimers, and domain–domain interactions. *Proteins: Structure, Function, and Bioinformatics*, **85**(3), 487–496.

Petsalaki, E. and Russell, R. B. (2008). Peptide-mediated interactions in biological systems: new discoveries and applications. *Current opinion in biotechnology*, **19**(4), 344–350.

Pierce, B. and Weng, Z. (2007). Zrank: reranking protein docking predictions with an optimized energy function. *Proteins: Structure, Function, and Bioinformatics*, **67**(4), 1078–1086.

Pierce, B. and Weng, Z. (2008). A combination of rescoring and refinement significantly improves protein docking performance. *Proteins: Structure, Function, and Bioinformatics*, **72**(1), 270–279.

Pons, C., Talavera, D., De La Cruz, X., Orozco, M., and Fernandez-Recio, J. (2011). Scoring by intermolecular pairwise propensities of exposed residues (sipper): a new efficient potential for protein- protein docking. *Journal of chemical information and modeling*, **51**(2), 370–377.

Raveh, B., London, N., and Schueler-Furman, O. (2010). Sub-angstrom modeling of complexes between flexible peptides and globular proteins. *Proteins: Structure, Function, and Bioinformatics*, **78**(9), 2029–2040.

Simonovsky, M. and Komodakis, N. (2017). Dynamic edge-conditioned filters in convolutional neural networks on graphs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3693–3702.

Tu, W. B., Helander, S., Pilstål, R., Hickman, K. A., Lourenco, C., Jurisica, I., Raught, B., Wallner, B., Sunnerhagen, M., and Penn, L. Z. (2015). Myc and its interactors take shape. *Biochimica et Biophysica Acta*, **1849**(5), 469–483.

Yan, Y. and Huang, S.-Y. (2019). Pushing the accuracy limit of shape complementarity for protein-protein docking. *BMC bioinformatics*, **20**(25), 696.

Zamora-Resendiz, R. and Crivelli, S. (2019). Structural learning of proteins using graph convolutional neural networks. *bioRxiv*, page 610444.

Zhang, Y. and Skolnick, J. (2004). Scoring function for automated assessment of protein structure template quality. *Proteins: Structure, Function, and Bioinformatics*, **57**(4), 702–710.

Zhang, Y. and Skolnick, J. (2005). TM-align: a protein structure alignment algorithm based on the TM-score. *Nucleic acids research*, **33**(7), 2302–2309.

Figure 1: The basic architecture of the InterPepRank nets. Note that the output from the Edge Convolution and Embedding layers have been denoted as X, since different values were tested. Throughout the net, the ReLU activation function is applied after each convolution.

Figure 2: AUC on validation targets for the different individual network architectures, the final ensemble method and an ensemble including all architectures. The network architectures are numbered from 0 through 8, and the ensemble methods are named after the included architectures. The ensemble 0123478 shows optimal performance on the validation data. A detailed description of the architectures and their differences can be found in the Supplementary Information.

Figure 3: ROC-curves for using the method scores to separate low-LRMSD decoys from other decoys. Zrank, pyDock3, and PIPER are normalized by the total length of receptor and peptide.

Figure 4: ROC-curves for the different methods, each target is represented by 1 curve. The area under the curve (AUC) displayed in the graphs is the average and median over all targets.

Figure 5: Siah1 in complex with a synthetic peptide (PDB-ID 4i7b). Siah1 is shown in black, the native conformation of the peptide is shown in green, the other chain in the asymmetric unit is shown in gray, and an example peptide conformation maximizing interaction in the alternate groove is shown in pink.

(a) InterPep (b) Zrank

Figure 6: Scatterplot of InterPepRank predicted score (a) and Zrank predicted score (b) versus LRMSD for all decoys of 4i7b chains A (receptor) and B (peptide). Each decoy is colored by the backbone RMSD of the peptide to its native conformation if superimposed.