Distributional Transformation improves Decoding Accuracy when Predicting Chronological Age from Structural MRI

Joram Soch [1,2,3,*]

[1] *Berlin Center for Advanced Neuroimaging, Charité – Universitätsmedizin Berlin, corporate member of Freie Universität Berlin, Humboldt-Universität zu Berlin, and Berlin Institute of Health, Berlin, Germany*

[2] *Berlin Center for Computational Neuroscience, Berlin, Germany*

[3] *German Center for Neurodegenerative Diseases, Göttingen, Germany*

Correspondence*:
BCCN Berlin, Philippstraße 13, Haus 6, 10115 Berlin, Germany
joram.soch@charite.de, joram.soch@bccn-berlin.de, Joram.Soch@DZNE.de

ABSTRACT

When predicting a certain subject-level variable (e.g. age in years) from measured biological data (e.g. structural MRI scans), the decoding algorithm does not always preserve the distribution of the variable to predict. In such a situation, distributional transformation (DT), i.e. mapping the predicted values to the variable's distribution in the training data, might improve decoding accuracy. Here, we tested the potential of DT within the 2019 Predictive Analytics Competition (PAC) which aimed at predicting chronological age of adult human subjects from structural MRI data. In a low-dimensional setting, i.e. with less features than observations, we applied multiple linear regression, support vector regression and deep neural networks for out-of-sample prediction of subject age. We found that (i) when the number of features is low, no method outperforms linear regression; and (ii) except when using deep regression, distributional transformation increases decoding performance, reducing the mean absolute error (MAE) by about half a year. We conclude that DT can be advantageous when predicting variables that are non-controlled, but have an underlying distribution in healthy or diseased populations.

Keywords: structural neuroimaging, machine learning, decoding, prediction, structural MRI, chronological age, distributional transformation, continuous variables

1 INTRODUCTION

In recent years, probabilistic modelling (Stephan and Mathys, 2014) and machine learning (Rutledge et al., 2019) have been increasingly applied to psychiatric populations and problems, leading to the creation of a whole new field of research called "Computational Psychiatry" (Huys et al., 2016).

The prediction of human age from biological data holds a large promise for computational psychiatry, because biologically predicted age may serve as an important biomarker for a number of human phenotypes (Cole et al., 2017). For example, brain-predicted age may be an indicator for the memory decline associated with neurodegenerative disorders such as Alzheimer's disease (AD; Lin et al., 2018).

The 2019 Predictive Analytics Competition[1] (PAC), held before the the 25th Annual Meeting of the Organization for Human Brain Mapping[2] (OHBM), addressed this research question by asking teams to predict chronological age of human subjects from raw or preprocessed structural magnetic resonance imaging (sMRI) data using a self-chosen machine learning (ML) approach.

Because brain structure changes significantly when becoming older, age can be predicted from sMRI with considerable precision (Cole et al., 2017), usually quantified as mean absolute error (MAE). Brain-predicted age difference (BPAD), i.e. the difference between age predicted from sMRI and actual age, can either be a sign of "accelerated" ($BPAD > 0$) or "decelerated" ($BPAD < 0$) brain aging. Accelerated brain aging has been associated with lower levels of education and physical exercise (Steffener et al., 2016), less meditation (Luders et al., 2016) and an increased mortality risk, among others (Cole et al., 2018).

While early attempts at predicting human age from functional MRI (Dosenbach et al., 2010) have used decoding algorithms such as support vector machines (SVM), more recent ML-based decoding from structural MRI have focused on deep learning (Plis et al., 2014), specifically using convolutional neural networks (CNN) to predict chronological age (Cole et al., 2017, 2018; Jiang et al., 2020), AD disease state (Lin et al., 2018) or even body mass index (Vakli et al., 2020) from anatomical brain data.

With a complex series of linear and non-linear optimizations involved in those decoding algorithms, it is clear that the distribution of predicted values of the target variable (e.g. chronological age) will not be exactly identical to the distribution of those values learned from (i.e. the training data). Here, we introduce distributional transformation (DT), a post-processing method for ML-based decoding, which allows to circumvent this problem by matching predictions to the training distribution.

Applied to out-of-sample ML prediction, DT operates by transforming the distribution of predicted values into the distribution of learned values of the variable of interest. In this way, prediction of the target variable (here: chronological age) is not only achieved by reconstructing it from the test set features (here: structural MRI), but additionally aided by looking at the training set samples, such that predictions are more likely to be in a realistic range for that particular target variable.

In this study, we apply DT to PAC 2019 data, while predicting chronological age using either multiple linear regression (GLM), support vector regression (SVR) and deep neural networks (DNN). In summary, we find that (i) multiple linear regression outperforms all other methods in a low-dimensional feature space and (ii) distributional transformation reduces prediction error for linear regression and SVR, but not DNN regression.

---

[1] https://www.photon-ai.com/pac2019

[2] https://github.com/ohbm/OpenScienceRoom2019/issues/10

2 METHODS

2.1 Structural MRI data

Data supplied within the 2019 Predictive Analysis Competition (PAC) included structural scans from
$n_1 = 2640$ training set and $n_2 = 660$ validation set subjects which were all healthy adults. The analyses
reported here exclusively used the pre-processed grey matter (GM) and white matter (WM) density images
supplied during the competition (for pre-processing details, see Cole et al., 2017). Covariates included
subjects' gender and site of image acquisition; data were acquired at 17 different sites. Subjects' age in
years was supplied for the training set (2640 values), but not shared and only after the competition released
for the validation set (660 values). The ratio of training to validation set size is 4:1 (see Table 1).

2.2 Feature extraction

The Automated Anatomical Labeling (AAL; Tzourio-Mazoyer et al., 2002) atlas parcellates the human
brain into 90 cortical and 26 cerebellar regions. We used the AAL label image (supplied with MRIcroN[3]
and also available from the TellMe package[4]) and resliced it to the first pre-processed GM image in order
to match image dimensions and voxel size. We then extracted average GM and WM density from all 116
regions from the pre-processed structural images for each subject.

Acquisition site information was transformed into 17 indicator regressors and subject gender information
was transformed into a $+1/-1$ regressor. Together with the extracted GM and WM densities, this constituted
design matrices for training and validation data having $p = 2 \times 116 + 17 + 1 = 250$ columns (see Figure 1).

2.3 Decoding algorithms

73 Let y_1 and y_2 be the $n_1 \times 1$ and $n_2 \times 1$ training and validation data vector and let X_1 and X_2 be the $n_1 \times p$
74 and $n_2 \times p$ training and validation design matrix.

2.3.1 Multiple linear regression

76 Multiple linear regression proceeds by estimating regression coefficients via ordinary least squares (OLS)
77 from the training data

$$\hat{\beta}_1 = (X_1^{\mathrm{T}} X_1)^{-1} X_1^{\mathrm{T}} y_1 \tag{1}$$

78 and generating predictions by multiplying the design matrix with estimated regression coefficients in the
79 validation data

$$\hat{y}_2 = \hat{f}_1(X_2) = X_2 \hat{\beta}_1 \ . \tag{2}$$

2.3.2 Support vector regression

81 Support vector regression (SVR) was implemented in MATLAB using `fitrsvm`. A support vector
82 machine was calibrated using the training data and then used to predict age in the validation data:

---

[3] https://people.cas.sc.edu/rorden/mricron/install.html

[4] https://github.com/JoramSoch/TellMe

$$\hat{g}_1 \leftarrow \texttt{fitrsvm}(X_1, y_1)$$
$$\hat{y}_2 = \hat{g}_1(X_2) \tag{3}$$

2.3.3 Deep neural network regression

Deep neural network (DNN) regression was implemented in MATLAB using `trainNetwork`. Before training, non-indicator regressors in X_1 and X_2 were z-scored, i.e. mean-subtracted and divided by standard deviation:

$$x^*_{1j} = \frac{x_{1j} - \bar{x}_{1j}}{\hat{\sigma}_{1j}}, \quad x^*_{2j} = \frac{x_{2j} - \bar{x}_{2j}}{\hat{\sigma}_{2j}}, \quad j = 1, \ldots, p \,. \tag{4}$$

The network consisted of six layers (see Table 2) following a MathWorks tutorial[5] on deep learning for linear regression and was solved in training using the Adam optimizer. The number of epochs was set to 100, with a mini batch size of 20, an initial learning rate of 0.01 and a gradient threshold of 1. Similarly to SVR, training and prediction proceeded as follows:

$$\hat{h}_1 \leftarrow \texttt{trainNetwork}(X^*_1, y_1, \texttt{layers}, \texttt{options})$$
$$\hat{y}_2 = \hat{h}_1(X^*_2) \tag{5}$$

2.4 Distributional transformation

Because the distribution of predicted age values will not exactly match the distribution of validation set age and likely also deviates from the distribution of training set age, one can apply an additional distributional transformation (DT) step after prediction.

DT uses cumulative distribution functions[6] (CDFs). Let X and Y be two random variables. Then, X is distributionally transformed to Y by replacing each observation of X by that value of Y which corresponds to the same quantile as the original value, i.e.

$$\tilde{x} = F_Y^{-1}\left(F_X(x)\right) \tag{6}$$

where F_X is the CDF of X and F_Y^{-1} is the inverse CDF of Y. Note that DT preserves the complete ordering of X, but changes its CDF to that of Y (see Appendix A).

Here, we apply DT to the predicted ages $\hat{y}_2$, with the goal of mapping them to the distribution of the training ages y_1 by calculating

$$\tilde{y}_{2i} = F_1^{-1}\left(\hat{F}_2(\hat{y}_{2i})\right), \quad i = 1, \ldots, n_2 \tag{7}$$

---

[5] https://de.mathworks.com/help/deeplearning/ug/sequence-to-sequence-regression-using-deep-learning.html, accessible in MATLAB as `openExample('nnet/SequencetoSequenceRegressionUsingDeepLearningExample')`

[6] https://statproofbook.github.io/D/cdf

where $\hat{F}_2$ is the empirical CDF of $\hat{y}_2$ and F_1^{-1} is the inverse empirical CDF of y_1, obtained in MATLAB
using `ecdf` (see Appendix B).

After the transformation, the ranks of all predictions $\hat{y}_{2i}$ are still the same, but the empirical CDF of $\tilde{y}_2$
matches that of y_1. In other words, we receive something that looks like the training age values in terms of
age distribution, but is still predicted from the validation brain data.

The rationale behind this is that, if training and validation set are unbiased, representative and unsystematic
samples from the underlying population, then sampling from the training data should in itself be a good
prediction strategy for the validation data (Brodersen et al., 2010). For example, because it can be suspected
that mean age has been controlled for when dividing into training and validation data, the age distributions
in training and validation data should be close to each other.

2.5 Performance assessment

After generating predictions for the validation set, we assessed decoding accuracy using multiple measures
of correlation (see Table 3) between predicted ages $\hat{y}_2$ and actual ages y_2. During the PAC 2019, Objective
1 was to minimize the mean absolute error. Objective 2 was to minimize Spearman's rank correlation
coefficient between y_2 and $(y_2 - \hat{y}_2)$, as it is desirable that the brain-predicted age difference (BPAD) is
not correlated with age. After assessing performance in the validation set, we conducted several statistical
analyses.

2.6 Statistical analyses

First, we submitted absolute errors (AE) between actual and predicted age to Wilcoxon signed-rank tests[7]
in order to test for significant reduction of the MAE between decoding algorithms (linear regression, SVR,
DNN) and prediction methods (with and without DT). This non-parametric test was chosen due to the
presumably non-normal distribution of absolute errors.

Second, we calculated the empirical Kullback-Leibler (KL) divergence[8] of the distribution of actual
ages from the distributions of predicted ages. The KL divergence is a non-negative distance measure for
probability distributions; the more similar two distributions are, the closer it is to zero. Thus, we expect
substantial reductions of the KL divergence after applying DT.

Third, we ran two-sample Kolmogorov–Smirnov (KS) tests[9] between predicted age values and validation
set ages, against the null hypothesis that predicted values and validation ages are from the same continuous
distribution. Consequently, similarly to the KL divergence, we expect less significant or non-significant
results from the KS test after applying DT.

Finally, for purely illustrative purposes, we investigated the influence of model parameters for the most
successful method of age prediction (linear regression with DT). To this end, we concatenated training and
validation data (because no out-of-sample testing was needed for this analysis) and calculated parameter
estimates for regression coefficients and noise variance

---

[7] https://de.mathworks.com/help/stats/signrank.html

[8] https://statproofbook.github.io/D/kl

[9] https://de.mathworks.com/help/stats/kstest2.html

$$\hat{\beta} = (X^{\mathrm{T}}X)^{-1}X^{\mathrm{T}}y$$

$$\hat{\sigma}^2 = \frac{1}{n-p}(y - X\hat{\beta})^{\mathrm{T}}(y - X\hat{\beta}) \tag{8}$$

136 which were then used to calculate standard error and confidence interval for each estimated model parameter
137 (Ashburner et al., 2003, ch. 7, eq. 42; ch. 8, eq. 9)

$$\mathrm{SE}(\hat{\beta}_j) = \sqrt{\hat{\sigma}^2 c_j^{\mathrm{T}}(X^{\mathrm{T}}X)^{-1}c_j}$$

$$\mathrm{CI}_{1-\alpha}(\hat{\beta}_j) = \left[\hat{\beta}_j - \mathrm{SE}(\hat{\beta}_j) \cdot z_{1-\frac{\alpha}{2}}, \; \hat{\beta}_j + \mathrm{SE}(\hat{\beta}_j) \cdot z_{1-\frac{\alpha}{2}}\right] \tag{9}$$

138 where c_j is a contrast vector of only zeros except for a single one in j-th position (i.e. testing β_j against 0) ,
139 z_{1-p} is the $(1-p)$-quantile from the standard normal distribution ("z-score") and the confidence level was
140 set to $(1-\alpha) = 90\%$ (such that $z_{1-\frac{\alpha}{2}} = 1.645$).

141 The complete data analysis as well as resulting decoding accuracies can be reproduced using the contents
142 of a GitHub repository (see Data Availability Statement).

3 RESULTS

3.1 Influence of decoding algorithm

Qualitatively, prediction performance can be assessed via scatterplots of predicted age against actual age in the validation set (see Figure 2). Quantitatively, the ranking is similar across all measures of correlation (see Figure 3): multiple linear regression performs best ($r = 0.91$, MAE = 5.07 yrs), but only mildly outperforms deep neural network regression ($r = 0.89$, MAE = 5.18 yrs) and strongly outperforms support vector regression ($r = 0.83$, MAE = 6.82 yrs). This is true for measures which are to be maximized (R^2, R^2_{adj}, r, r_{SC}) as well as for measures which are to be minimized (MAE, RMSE, Obj. 2). Wilcoxon signed-rank tests indicated significantly lower absolute errors for linear regression, except when compared to DNN without applying DT (see Table 4).

3.2 Influence of distributional transformation

When comparing predicted against actual age, one can see that SVR and DNN predictions deviate quite some amount from the actual distribution (see Figure 2, top-middle and top-right), especially by not predicting very high ages (SVR: $\max(\hat{y}_2) = 71.25$ yrs; DNN: $\max(\hat{y}_2) = 75.68$ yrs), whereas linear regression creates a more homogeneous picture (see Figure 2, top-left), but also predicts very low ages ($\min(\hat{y}_2) = 1.06$ yrs).

DT improves the decoding accuracy of linear regression (MAE: $5.07 \rightarrow 4.58$ yrs) and SVR (MAE: $6.82 \rightarrow 6.11$ yrs), reducing their MAE by about half a year. For DNN, the error actually goes up (MAE: $5.18 \rightarrow 5.42$ yrs). Similar results are observed when considering other measures. Wilcoxon signed-rank tests indicated significantly lower absolute errors when applying DT after linear regression and SVR and significantly higher absolute errors when applying DT after DNN regression (see Table 4).

DT especially benefits Objective 2 of PAC 2019, as the Spearman correlation of brain-predicted age difference with age itself goes down considerably for all decoding algorithms when applying DT (see Figure 3, right), thus increasing the independence of prediction error from predicted variable.

When not applying DT (see Figure 4, top row), DNN yields the smallest KL divergence (KL = 0.073), with predictions almost being in the correct range ($17 \leq y_2 \leq 89$), whereas linear regression achieves lower correspondence and SVR suffers from making a lot medium-age predictions ($40 \leq \hat{y}_2 \leq 60$) and there not being a lot middle-aged subjects in the training and validation sample. When applying DT (see Figure 4, middle row), all methods give rise to the same histogram of predicted ages and have the same and minimally possible distance to the actual distribution (KL = 0.027). Still, despite having the same distribution, prediction performance differs between methods (see Figure 3).

These findings are also reflected in results from KS tests which indicate significant differences of actual and predicted age distributions before (see Figure 4, top row), but not after (see Figure 4, middle row) DT was applied to predicted age values. Moreover, it can be seen in the graphical display of the distributional transformations themselves (see Figure 4, bottom row) which deviate stronger from the diagonal line for higher KL divergences before application of DT (see Figure 4).

3.3 Influence of regression coefficients

In order to see which features aided successful prediction of age when using multiple linear regression, we report parameter estimates and compute confidence intervals (see Figure 5). These results show that (i) there was no effect of gender on age, putatively because gender was controlled when splitting the data; (ii)

182 there were only mild site effects, putatively because the whole age range was sampled at each site; and (iii)
183 regional GM and WM densities both contributed to the predictions, as variables from both groups have
184 significant effects on subject age (see Figure 5).

4   DISCUSSION

185 We have applied distributional transformation (DT), a post-processing method for prediction analyses
186 based on machine learning (ML), to predict chronological age from structural MRI scans in a very large
187 sample of healthy adults (Cole et al., 2017). By using DT, we were able to significantly reduce the mean
188 absolute error (MAE) of linear regression and support vector regression, but not deep learning regression.

4.1   Distributional transformation

DT can be particularly advantageous when predicting variables which are hard to control experimentally
(esp. biological phenotypes), but the distribution of which is known through the availability of training
data. The rationale behind distributional transformation for ML-based prediction is simple:

1. A lot of target variables have a natural range into which their values must fall:
a. Human age cannot be smaller than zero (or at least, smaller than -9 months), is rarely larger than
100 years and has thus far not exceeded 122 years.
b. Intelligence quotients (IQ) are (by construction) normally distributed with mean 100 and standard
deviation 15.
c. Physical parameters such as weight and height fall into typical ranges differing by gender and age.
d. Probabilities and frequencies, e.g. proportions of correct responses, are bound to the interval $[0, 1]$.
2. When associations between target variable and feature space are learned by sending training samples
through a complex machinery of linear and non-linear optimizations, some test set predictions will
likely be outside these areas, thereby violating the natural range of the target variable.
3. Distributional transformation brings the predictions back into the natural range by putting them in
reference to the training set samples, but preserving the ranks obtained when reconstructing from the
test set features.

The extent to which this transformation will work naturally depends on how precise the cumulative
distribution functions of training samples and predicted values can be estimated. Generally speaking, those
estimates will be more precise, the more samples are available to generate them.

Note that DT assumes independent subsets and identical distributions. This means, (i) training and
validation set must be independent from each other in order not to introduce dependencies between data
used for training an algorithm and data used for reporting its performance; and (ii) training and validation
samples must be drawn from the same underlying distribution in order to justify the assumption that they
have the same cumulative distribution function. The first requirement is usually met when samples are
independent from each other (e.g. subjects); the second requirement is usually met when the variable of
interest (e.g. age) does not influence whether samples are in the training or validation set.

With the present data set, we were able to show that DT improves age prediction from structural MRI
using some methods (i.e. linear regression or SVR), reducing the MAE by about half year (see Figure 2,
left and middle). Notably, DT does not increase prediction precision when the decoding algorithm (e.g.
DNN regression) generates test set predictions that already have a similar distribution as the training set

samples. This can also be seen from the fact that DT does not substantially change the distribution of DNN
predictions (see Figure 4, right) which is in clear contrast to linear regression and SVR.

It is also noteworthy that DT substantially reduced the correlation between brain-predicted age difference
(BPAD) and actual age (see Figure 3, right). This is a highly desirable property, because it means that the
prediction error is less dependent on subjects' age and prediction tends to work as good for a 20-year-old
as it works for an 80-year-old adult – which is why this quantity was an objective in the PAC 2019 (see
Section 2.5) and this finding makes our work complementary to other approaches attempting to reduce bias
in brain age estimation (Cole et al., 2018; Beheshti et al., 2019).

Our explanation for the observed reduction is that DT distributes predicted values more evenly across
the age spectrum, thereby avoiding negative prediction errors for older subjects (not predicted as being
old) and positive prediction errors for younger subjects (not predicted as being young) – a phenomenon
commonly observed (see e.g. Beheshti et al., 2019, Fig. 1). This is also compatible with the fact that linear
regression covered the age range more broadly, especially for old ages (see Figure 2, left and Figure 4, top),
and achieved the lowest Spearman correlation coefficient with and without applying DT.

4.2 Limitations

The limitations of our study are three-fold:

• First, we were operating in a low-dimensional setting with fewer features than observations (here:
$n = 2640 > 250 = p$). Our analyses therefore do *not* show that DT also improves decoding accuracy
in high-dimensional settings (where $n < p$) such as decoding from voxel-wise structural data. Previous
studies suggest that DNNs outperform simpler methods in this regime (Plis et al., 2014; Cole et al.,
2017), but this does not preclude that DT further improves accuracy of CNN predictions.

• Second, we were performing feature extraction using an *a priori* selected brain atlas (here: by extracting
from AAL regions). Our analyses therefore do *not* show that DT also improves decoding accuracy
under other feature extraction methods or after feature dimensionality reduction. The results reported
in this study suggest that DT works well with region-based feature extraction and relatively simple
decoding algorithms (linear regression, SVR), but that does not preclude that DT also improves
prediction after voxel-based feature extraction.

• Third, we were exclusively analyzing data from healthy subjects (here: by using PAC 2019 data). Our
results therefore do *not* apply to clinically relevant groups such as subjects suffering from Alzheimer's
disease (AD) or mild cognitive impairment (MCI). Because structural MRI data contain signatures of
chronological age and disease status in patients as well (Lin et al., 2018), we expect DT to also show
its merits in those clinical contexts – provided that training and validation set constitute representative
samples from the underlying population.

4.3 Conclusion

Our results suggest that, when combining distributional transformation with relatively simple decoding
algorithms (e.g. linear regression or SVR), predicting chronological age from structural MRI can reach
acceptable decoding accuracies in short time. We have provided an algorithm for DT (see Appendix)
that can be easily added as a post-processing step to ML-based prediction analyses. Future studies may
investigate whether the DT methodology might also be beneficial in other areas of computational psychiatry
than brain age prediction.

5 APPENDIX

260 **A Proof of distributional transformation**

261 Let X and Y be two random variables. Then, X is distributionally transformed to Y by replacing each
262 observation of X by that value of Y which corresponds to the same quantile as the original value (see
263 Section 2.4), i.e.

$$\tilde{x} = F_Y^{-1}\left(F_X(x)\right) \ . \tag{A.1}$$

264 where $F_X(x)$ is the cumulative distribution function (CDF) of X and $F_Y^{-1}(y)$ is the inverse CDF of Y.
265 Consequently, the CDF of $\tilde{X}$ follows as

$$
\begin{aligned}
F_{\tilde{X}}(y) &= \Pr(\tilde{x} \leq y) \\
&= \Pr\left(F_Y^{-1}\left(F_X(x)\right) \leq y\right) \\
&= \Pr\left(F_X(x) \leq F_Y(y)\right) \\
&= \Pr\left(x \leq F_X^{-1}\left(F_Y(y)\right)\right) \\
&= F_X\left(F_X^{-1}\left(F_Y(y)\right)\right) \\
&= F_Y(y)
\end{aligned}
\tag{A.2}
$$

266 which shows that $\tilde{X}$ and Y have the same CDF and are thus identically distributed.

267 **B Code for distributional transformation**

268 The following code distributionally transforms `x` to `y` in MATLAB:

```
269 01   function xt = MD_trans_dist(x, y)
270 02   % _
271 03   % Distributional Transformation
272 04   % FORMAT xt = MD_trans_dist(x, y)
273 05   %     x  - source data, data to be transformed
274 06   %     y  - reference data, target for transformation
275 07   %     xt - transformed data, x mapped to y
276 08
277 09   % calculate CDFs
278 10   [f1, x1] = ecdf(x);
279 11   [f2, x2] = ecdf(y);
280 12
281 13   % transform x
282 14   xt = zeros(size(x));
283 15   for i = 1:numel(x)
284 16       j1 = find(x1==x(i));
285 17       j1 = j1(end);
286 18     [m, j2] = min(abs(f2-f1(j1)));
287 19       xt(i)  = x2(j2);
288 20   end;
289 21   clear m j1 j2
```

CONFLICT OF INTEREST STATEMENT

290 The author has no conflict of interest, financial or otherwise, to declare.

AUTHOR CONTRIBUTIONS

291 JS conceived, implemented and performed data analysis; created figures and tables; and wrote the paper.

FUNDING

292 This work was supported by the Bernstein Computational Neuroscience Program of the German Federal
293 Ministry of Education and Research (BMBF grant 01GQ1001C).

ACKNOWLEDGMENTS

294 The author would like to thank Carsten Allefeld for discussing the linear regression analysis and the
295 distributional transformation method.

296 We acknowledge support from the German Research Foundation (DFG) and the Open Access Publication
297 Fund of Charité – Universitätsmedizin Berlin.

DATA AVAILABILITY STATEMENT

Data analyzed in this study were available online during the 2019 Predictive Analytics Competition. For
this work, no raw images, but only pre-processed maps were used (see Section 2.1). Requests for data
release should be directed to Tim Hahn[10] and Ramona Leenings[11].

MATLAB code for (i) feature extraction from pre-processed data, (ii) decoding analyses underlying the
results presented in this paper and (iii) results display to reproduce the figures shown in this paper can be
found in an accompanying GitHub repository[12].

REFERENCES

Ashburner, J., Friston, K., and Penny, W. (eds.) (2003). *Human Brain Function* (Elsevier), 2nd edn.
Beheshti, I., Nugent, S., Potvin, O., and Duchesne, S. (2019). Bias-adjustment in neuroimaging-based brain
age frameworks: A robust scheme. *NeuroImage: Clinical* 24, 102063. doi:10.1016/j.nicl.2019.102063
Brodersen, K. H., Ong, C. S., Stephan, K. E., and Buhmann, J. M. (2010). The Balanced Accuracy and Its
Posterior Distribution. In *2010 20th International Conference on Pattern Recognition* (Istanbul, Turkey:
IEEE), 3121–3124. doi:10.1109/ICPR.2010.764
Cole, J. H., Poudel, R. P., Tsagkrasoulis, D., Caan, M. W., Steves, C., Spector, T. D., et al. (2017).
Predicting brain age with deep learning from raw imaging data results in a reliable and heritable
biomarker. *NeuroImage* 163, 115–124. doi:10.1016/j.neuroimage.2017.07.059

---

[10] mailto:hahnt@wwu.de
[11] mailto:leenings@uni-muenster.de
[12] https://github.com/JoramSoch/PAC_2019

Cole, J. H., Ritchie, S. J., Bastin, M. E., Valdés Hernández, M. C., Muñoz Maniega, S., Royle, N., et al.
(2018). Brain age predicts mortality. *Molecular Psychiatry* 23, 1385–1392. doi:10.1038/mp.2017.62

Dosenbach, N. U. F., Nardos, B., Cohen, A. L., Fair, D. A., Power, J. D., Church, J. A., et al. (2010).
Prediction of Individual Brain Maturity Using fMRI. *Science* 329, 1358–1361. doi:10.1126/science.
1194144

Huys, Q. J. M., Maia, T. V., and Frank, M. J. (2016). Computational psychiatry as a bridge from
neuroscience to clinical applications. *Nature Neuroscience* 19, 404–413. doi:10.1038/nn.4238

Jiang, H., Lu, N., Chen, K., Yao, L., Li, K., Zhang, J., et al. (2020). Predicting Brain Age of Healthy Adults
Based on Structural MRI Parcellation Using Convolutional Neural Networks. *Frontiers in Neurology* 10,
1346. doi:10.3389/fneur.2019.01346

Lin, W., Tong, T., Gao, Q., Guo, D., Du, X., Yang, Y., et al. (2018). Convolutional Neural Networks-Based
MRI Image Analysis for the Alzheimer's Disease Prediction From Mild Cognitive Impairment. *Frontiers*
in Neuroscience 12, 777. doi:10.3389/fnins.2018.00777

Luders, E., Cherbuin, N., and Gaser, C. (2016). Estimating brain age using high-resolution pattern
recognition: Younger brains in long-term meditation practitioners. *NeuroImage* 134, 508–513. doi:10.
1016/j.neuroimage.2016.04.007

Plis, S. M., Hjelm, D. R., Salakhutdinov, R., Allen, E. A., Bockholt, H. J., Long, J. D., et al. (2014). Deep
learning for neuroimaging: a validation study. *Frontiers in Neuroscience* 8. doi:10.3389/fnins.2014.
00229

Rutledge, R. B., Chekroud, A. M., and Huys, Q. J. (2019). Machine learning and big data in psychiatry:
toward clinical applications. *Current Opinion in Neurobiology* 55, 152–159. doi:10.1016/j.conb.2019.
02.006

Steffener, J., Habeck, C., O'Shea, D., Razlighi, Q., Bherer, L., and Stern, Y. (2016). Differences between
chronological and brain age are related to education and self-reported physical activity. *Neurobiology of*
Aging 40, 138–144. doi:10.1016/j.neurobiolaging.2016.01.014

Stephan, K. E. and Mathys, C. (2014). Computational approaches to psychiatry. *Current Opinion in*
Neurobiology 25, 85–92. doi:10.1016/j.conb.2013.12.007

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N., et al. (2002).
Automated Anatomical Labeling of Activations in SPM Using a Macroscopic Anatomical Parcellation
of the MNI MRI Single-Subject Brain. *NeuroImage* 15, 273–289. doi:10.1006/nimg.2001.0978

Vakli, P., Deák-Meszlényi, R. J., Auer, T., and Vidnyánszky, Z. (2020). Predicting Body Mass Index From
Structural MRI Brain Images Using a Deep Convolutional Neural Network. *Frontiers in Neuroinformatics*
14, 10. doi:10.3389/fninf.2020.00010

TABLES

out-of-sample prediction	k-fold cross-validation	number of subjects
training	training	2376
	testing	264
validation	reporting	660

Table 1. Data dimensions and cross-validation. During the competition (second column), the model was developed using 10-fold cross-validation within the training data, before performance was reported on the withheld data set. In the context of this paper (first column), age is predicted out-of-sample in the validation data without cross-validation.

MATLAB command	Description	Parameters
`sequenceInputLayer`	inputs 1D data into network	250 features
`lstmLayer`	long short-term memory (LSTM) layer; learns long-range dependencies between features	125 hidden units
`fullyConnectedLayer`	multiplies with weight matrix and adds bias	50 output units
`dropoutLayer`	sets elements to zero with given probability	$p = 0.5$
`fullyConnectedLayer`	multiplies with weight matrix and adds bias	1 output unit
`regressionLayer`	outputs scalar prediction from network	–

Table 2. Layers of the deep neural network. The network employed for DNN regression consisted of six layers which were designated for using deep learning on regression problems.

Measure	Description
R^2	coefficient of determination ("R-squared")
R^2_{adj}	adjusted coefficient of determination
r	Pearson correlation coefficient
r_{SC}	Spearman's rank correlation coefficient
MAE	mean absolute error (Objective 1)
RMSE	root mean squared error
Obj. 2	Objective 2 from PAC 2019

Table 3. Measures of prediction performance. For PAC 2019 Objectives, see main text.

Statistic	Method	GLM	SVR	DNN
predicition performance	without DT	$r = 0.91, \mathrm{MAE} = 5.07$	$r = 0.83, \mathrm{MAE} = 6.82$	$r = 0.90, \mathrm{MAE} = 5.18$
	with DT	$r = 0.93, \mathrm{MAE} = 4.58$	$r = 0.86, \mathrm{MAE} = 6.11$	$r = 0.90, \mathrm{MAE} = 5.42$
comparison of models	without DT	–	$z = -7.44, p < 0.001$	$z = 0.23, p = 0.817$
	with DT	–	$z = -5.95, p < 0.001$	$z = -4.12, p < 0.001$
comparison of methods	with DT vs. without DT	$z = -4.90, p < 0.001$	$z = -4.78, p < 0.001$	$z = 4.04, p < 0.001$

Table 4. Prediction performance across models and methods. The first row lists performance measures for three decoding algorithms (GLM, SVR, DNN) and two prediction methods (without DT, with DT). The second row reports results from Wilcoxon signed-rank tests comparing GLM against SVR and DNN (thus no entries in the GLM column). The third row reports results from Wilcoxon signed-rank tests comparing each decoding algorithm with and without DT. Negative z-values indicate significantly lower absolute errors for GLM (second row) or DT (third row), respectively. Abbreviations: GLM = multiple linear regression; SVR = support vector regression; DNN = deep neural network regression; DT = distributional transformation.

FIGURES

Figure 1. Data vector (left) and design matrix (right) for training set (top) and validation set (bottom). In the design matrices, rows correspond to subjects and columns correspond to brain regions and covariates. Regressors specifying grey matter (GM) and white matter (WM) densities as well as site covariates are separated by vertical black lines.

Figure 2. Predicted vs. actual age for validation set subjects. Solid black lines denote the identity function and dashed black lines are regression lines. Also reported are correlation coefficients (*r*) and mean absolute errors (MAE) for each analysis (see Figure 3). Abbreviations: GLM = multiple linear regression; SVR = support vector regression; DNN = deep neural network regression; DT = distributional transformation.

Figure 3. Prediction performance across models, methods and measures. For each performance measure, decoding accuracy is given for multiple linear regression (green), support vector regression (red) and deep neural network regression (blue), with and without distributional transformation (DT). Abbreviations: see Table 3.

Figure 4. Empirical distributions of actual age (yellow), predicted age (top row) and transformed age (middle row). Each panel shows relative frequencies, i.e. number of occurences divided by total number of subjects. The applied distributional transformation is shown for each decoding algorithm (bottom row), with the diagonal line denoting the identity function. The empirical KL divergence was always computed relative to the validation age distribution (middle row, left), thus this distribution has $\text{KL} = 0$. Also reported are statistics from a two-sample Kolmogorov-Smirnov test between predicted values and validation ages, thus $D = 0$ and $p = 1$ for validation set age. Abbreviations: GLM = multiple linear regression; SVR = support vector regression; DNN = deep neural network regression; DT = distributional transformation; KL = Kullback-Leibler divergence.

Figure 5. Parameter estimates and confidence intervals from linear regression, obtained when combining training and validation data into one data set. For each regressor, the estimated coefficient is plotted as a bar and a 90 % confidence interval is reported as well. Model parameters are also reported as being significantly different from zero (* $p < 0.05$; ** $p < 0.001$; *** $p < 0.05/250$).