Revealing the relevant spatiotemporal scale underlying whole-brain dynamics

Xenia Kobeleva [1 2 3], Ane López-González [2], Morten L. Kringelbach [4 5 6], Gustavo Deco [2, 7, 8, 9]

(1) Department of Neurology, University of Bonn, Venusberg-Campus 1, 53127 Bonn, Germany

(2) Center for Brain and Cognition, Computational Neuroscience Group, Department of Information and Communication Technologies, Universitat Pompeu Fabra, 08018 Barcelona, Spain

(3) German Center for Neurodegenerative Diseases (DZNE), Bonn, Venusberg-Campus 1, 53127 Bonn, Germany

(4) Department of Psychiatry, University of Oxford, Oxford OX3 7JX, United Kingdom

(5) Centre for Eudaimonia and Human Flourishing, University of Oxford, Oxford OX3 7JX, United Kingdom

(6) Center for Music in the Brain, Department of Clinical Medicine, Aarhus University, 8000 Aarhus, Denmark

(7) Institució Catalana de la Recerca i Estudis Avançats (ICREA), 08010 Barcelona, Spain

(8) Department of Neuropsychology, Max Planck Institute for Human Cognitive and Brain Sciences, 04103 Leipzig, Germany

(9) School of Psychological Sciences, Monash University, Melbourne, Clayton, VIC 3800, Australia

Corresponding author: Dr. Xenia Kobeleva, Department of Neurology, University of Bonn, Venusberg-Campus 1, 53127 Bonn, Germany; email: xkobeleva (at) gmail (dott) com

Abstract

The brain rapidly processes and adapts to new information by dynamically switching between activity in whole-brain functional networks. In this whole-brain modelling study we investigate the relevance of spatiotemporal scale in whole-brain functional networks. This is achieved through estimating brain parcellations at different spatial scales (100-900 regions) and time series at different temporal scales (from milliseconds to seconds) generated by a whole-brain model fitted to fMRI data. We quantify a fingerprint of healthy dynamics quantifying the richness of the dynamical repertoire at each spatiotemporal scale by computing the entropy of switching activity between whole-brain functional networks. The results show that the optimal relevant spatial scale is around 300 regions and a temporal scale of around 150 milliseconds. Overall,

36   this study provides much needed evidence for the relevant spatiotemporal scales needed to
37   make sense of neuroimaging data.

39   **Keywords:** modeling, spatiotemporal, brain dynamics, functional connectivity, brain networks

Introduction

The brain can rapidly process and adapt to new information through the flexible transitioning
between multiple states. Functional neuroimaging studies demonstrate how the macroscopic
brain organization dynamically changes during these transitions of multiple functional states,
even in the absence of an active task (Tang et al. 2012; Stitt et al. 2017; Liégeois et al. 2019).
There has been convincing evidence that brain dynamics rest on the orchestrated activity of
several networks of brain regions which transition in recurring patterns over time (Alexandrov
1999; Meer et al. 2020). These transitions between brain networks have been associated with
to cognition and (ab)normal behaviour (Engel et al. 2001; Thompson et al. 2013; Vidaurre et
al. 2017; Liégeois et al. 2019; Lurie et al. 2020; Yoo et al. 2020). However, a fundamental
question remains, namely at which particular spatiotemporal scale the whole-brain functional
networks are able to optimally transition.

The current body on research on spatiotemporal scales of the dynamical behaviour of whole-
brain networks is limited, since empirical studies of different spatial and temporal scales are
challenging. In human neuroimaging studies, spatiotemporal scales have a restricted range
for each modality. The spatial resolution of fMRI is now down to less than a millimetre but it is
not clear if this is the right scale for capturing the richness of information processing across the
whole-brain. Similarly, the spatial resolution of MEG depends on the sensors and it has been
shown that beamforming can only separate up to around 70 regions across the whole-brain
with significant drop in signal in deeper regions. Even if the acquisition of whole-brain imaging
is now around 0.7 seconds, the temporal resolution of fMRI is limited by the haemodynamics
of the BOLD signal.

Dynamic whole-brain models offer an elegant opportunity to overcome the limitations of the
restricted spatiotemporal scales in experimental research (Yuan et al. 2018; Deco et al. 2019;
Cornblath et al. 2020). Using a whole-brain network model, in our previous research we were
able to compare the complexity of dynamic switching behaviour of whole-brain networks
across different time scales from milliseconds to seconds (Deco et al. 2019). In this study, we
extend our previous work on different temporal scales (i.e. the temporal resolution) in a whole-
brain network model (Deco et al. 2019) by adding a spatial dimension to the analysis (i.e. the
number of regions) and explore the switching behaviour of networks across spatiotemporal
scales (i.e. taking into account both spatial and temporal scales). By doing so, we attempt to

answer the question at which spatiotemporal scale macroscopic whole-brain functional
networks can provide optimal richness of repertoire. Thus, our study has implications for a
better understanding of the dynamical reconfiguration of whole-brain functional networks over
time. We aim at providing a quantification of how best to choose appropriate neuroimaging
modalities and parcellation techniques when investigating the dynamics of whole-brain
functional networks, keeping the balance between maximum information content and
computational complexity of the analysis. In this study we focus on the dynamic behaviour of
macroscopic, functional brain networks and use the simplest form to quantify the richness of
the dynamical repertoire, using an entropy measure.
82

To achieve our goal, we explore the switching behaviour of whole-brain functional networks at
spatial scales from 100 to 900 regions both in empirical time series extracted from resting-
state fMRI with fixed temporal scales as well as in simulated time series with various temporal
scales from milliseconds to seconds. We determine the relevant spatiotemporal scale by
comparing the entropy of the switching activity. In information theory, entropy describes the
level of variability of a given variable (Shannon 1948). By focusing on the behaviour of whole-
brain networks, we focus on *relevant* information in brain dynamics and find the maximum of
the entropy, which allows us to choose the most *optimal* spatiotemporal scale. In the discussion
of our results, we derive recommendations for neuroimaging researchers, highlighting our
finding that the relevant spatial scale for analyses of brain dynamics is around 300 regions and
at an optimal temporal scale of around 150 milliseconds and thus contribute to an empirical
basis of relevant parameters for studies of brain dynamics.
95

Methods

97 We adapted the existing comparing different time scales (Deco et al. 2019) to incorporate
98 different spatial scales. Images were created using Biorender, Inkscape, Connectome
99 Workbench and the Matplotlib library within Python.
100

Data acquisition and preprocessing

We used resting state functional MRI data from 100 unrelated subjects of the Human
Connectome Project (HCP; Van Essen et al. 2013) with a mean age of 29.1 ± 3.7 years. The
HCP study was approved by the local ethical committees and informed consent was obtained
from all subjects. Six subjects were discarded as the resulting FC matrices consisted of at least
one not available row at parcellations with more than 800 regions (due to the sparsity of the
networks). We further chose one of the four available resting-state fMRI scans of about 15
minutes duration (TR of 0.72 sec). During fMRI acquisition, subjects were instructed to keep
their eyes open while looking at a fixation cross. A full description of the imaging parameters

and minimal preprocessing pipeline can be found in Glasser et al. (2013). In short, after correction for motion, gradient and susceptibility distortions the fMRI data was aligned to an anatomical image. The aligned functional image was then corrected for intensity bias, demeaned and projected to a common surface space, which resulted in a cifti-file.

All fMRI data was filtered between 0.1 and 0.01 Hz to retain the relevant frequency range for further analyses of the BOLD signal. We obtain structural and functional matrices in different spatial scales using the Schaefer parcellation, which optimizes local gradient and global similarity measures of the fMRI signal in various spatial scales ranging from 100 to 900 regions (Schaefer et al. 2018). In both fMRI datasets time series were extracted with the help *Workbench Command* provided by the HCP.

To create a structural connectome as a basis for the whole-brain model, we generated a structural connectome depicting the number of fibers in the required spatial scales. We used the diffusion MRI dataset from the HCP database, that uses high-quality scanning protocols with an acquisition time of 89 minutes for each of the 32 participants, resulting in above-average normative diffusion MRI data. The data has already been preprocessed and made available to the public within the Lead-DBS software package (Setsompop et al. 2013; Horn et al. 2017). In brief, the data were processed using a generalized q-sampling imaging algorithm as implemented in *DSI studio* (http://dsi-studio.labsolver.org). The data were segmented and co-registered using *SPM 12*. Restricted by a coregistered white-matter mask, 200,000 fibers were sampled within each participant using a Gibbs' tracking approach (Kreher et al. 2008) and normalized into MNI space via DARTEL transforms (Ashburner 2007; Horn and Blankenburg 2016). We used the standardized methods from *Lead-DBS toolbox* version 2.0 (Horn et al. 2018) to obtain structural connectomes for the same parcellation schemes as for the functional data, selecting tracts that both started and ended within the specified parcellation scheme.

Whole-brain modeling using the DMF model

The use of fMRI signals would normally limit our study in the temporal dimension. To overcome this shortcoming, we use a whole-brain model which allows us simulate data in varying timescales from milliseconds to seconds, while a comparable structure of the signal. We create a dynamic mean field (DMF) model, which is conceptually based on interconnected regions containing excitatory and inhibitory neuronal pools (Deco et al. 2013).

A summary of the individual steps that were taken to create the model can be found in Figure 1. The model consists of a network of brain regions that emit spontaneous neuronal signals. The number of the brain regions is defined by the spatial scale. Each of these regions consists

of excitatory (*E*) and inhibitory (*I*) neuronal pools that reciprocally influence each other locally

within each region. We further assume that these regions interact via long-range connections,

as given by the connection weights of the structural connectome (Deco et al. 2014).

These assumptions are implemented through a modified DMF model based on the original

reduction first proposed by Wong and Wang (2006). In the model used in this study, NMDA

receptors mediate excitatory currents $I^{(E)}$ and GABA-A receptors mediate inhibitory currents

$I^{(I)}$. Inhibitory sub-populations communicate reciprocally with excitatory sub-populations on a

local level. Excitatory sub-populations are additionally linked to other excitatory sub-

populations via long-range connections, representing the effect of NMDA receptors. These

long-range connections are based on the number of fiber tracts given by the structural

connectome (see description above). The connections are then tuned by a global scaling factor

G that linearly scales all synaptic strengths.

The following set of coupled differential equations are used to create the DMF model:

$$I_n^{(E)} = W_E I_0 + w_+ J_{NMDA} S_n^{(E)} + G J_{NMDA} \sum_p C_{np} S_p^{(E)} - J_n S_n^{(I)} \tag{1}$$

$$I_n^{(I)} = W_I I_0 + J_{NMDA} S_n^{(E)} - S_n^{(I)} \tag{2}$$

$$r_n^{(E)} = H^{(E)}\left(I_n^{(E)}\right) = \frac{g_E\left(I_n^{(E)} - I_{thr}^{(E)}\right)}{1 - \exp\left(-d_E g_E (I_n^{(E)} - I_{thr}^{(E)})\right)} \tag{3}$$

$$r_n^{(I)} = H^{(I)}\left(I_n^{(I)}\right) = \frac{g_I\left(I_n^{(I)} - I_{thr}^{(I)}\right)}{1 - \exp\left(-d_I g_I (I_n^{(I)} - I_{thr}^{(I)})\right)} \tag{4}$$

$$\frac{dS_n^{(E)}(t)}{dt} = -\frac{S_n^{(E)}}{\tau_{NMDA}} + \left(1 - S_n^{(E)}\right)\gamma r_n^{(E)} + \sigma v_n(t) \tag{5}$$

$$\frac{dS_n^{(I)}(t)}{dt} = -\frac{S_n^{(E)}}{\tau_{GABA}} + r_n^{(I)} + \sigma v_n(t) \tag{5}$$

For each inhibitory (*I*) and excitatory (*E*) neuronal pool in every brain region *n*, the vector $I_n^{(E,I)}$

Represents the total input current (in nanoamperes), the vector $r_n^{(E,I)}$ stands for the firing rate

(in hertz) and the vector $S_n^{(E,I)}$ denotes the synaptic gating. The total input currents that are

received by the neuronal pools are converted by the neuronal response functions $H^{(E,I)}$ into

firing rates $r_n^{(E,I)}$. Here, the gain factors g_E = 310 nC^{-1} and g_I = 310 nC^{-1} are used to determine

the slope of *H*. When the threshold currents of $I_{thr}^{(E)}$ = 0.403 nA and $I_{thr}^{(I)}$ = 0.288 nA are reached,

the firing rates increase linearly with the input currents. The shape of the curvature of H around

I_{thr} is defined by the constants d_E = 0.16 and d_i = 0.087. The average synaptic gating of the

excitatory pools $S_n^{(E)}$ is controlled by the NMDA receptors with a decay time constant τ_{NMDA} =

0.1 s and γ = 0.641(transformed into ms). The average synaptic gating of the inhibitory pools

$S_n^{(I)}$ is controlled by the GABA receptors with a decay time constant τ_{GABA} = 0.01 s (transformed

into ms). All excitatory synaptic couplings are weighted by J_{NMDA} = 0.15 nA and the weight of

the recurrent excitation w_+= 1.4. The overall effective external input is I_0 = 0.382 nA with W_E =

1 and W_I = 0.7. We add standard Gaussian noise v_n with an amplitude of σ = 0.01 nA. To

mimic a resting state condition, the weight of feedback inhibition J_n is adjusted for each

excitatory subpopulation to obtain a firing rate $r_n^{(E)}$ ~ 3 Hz. This was done using a regulatory

mechanism called Feedback Inhibition Control, which was shown to mimic resting state activity

better (Deco et al. 2014).

It is then possible to retrieve separate temporal scales from the simulated neuronal data by

binning the time series. However, first the neuronal time series had to be fitted to the empirical

BOLD time series (by adjusting G) to ensure a biologically plausible signal. Therefore, we

transformed the neuronal signal from the model into a simulated BOLD signal and then

compared the simulated and empirical signals (see below). We employed the Balloon-

Windkessel hemodynamic model using all biophysical parameters as stated in (Stephan et al.

2007). The model is described by the following equations:

195
$$\frac{ds_n}{dt} = 0.5\, r_n^{(E)} + 3 - ks_n - \gamma(f_n - 1) \tag{6}$$

196
$$\frac{df_n}{dt} = s_n \tag{7}$$

197
$$\tau\frac{dv_n}{dt} = f_n - v_n^{a^{-1}} \tag{8}$$

199
$$\tau\frac{dq_n}{dt} = \frac{f_n(1-\rho)^{f_n^{-1}}}{\rho} - \frac{q_n v_n^{a^{-1}}}{v_n} \tag{9}$$

200   This model describes a vasodilatory signal s_n which is altered by autoregulatory feedback.

201   Depending on s_n, the blood flow f_n leads to changes of the deoxyhemoglobin content q_n and

202   blood volume v_n. τ is the time constant, ρ is the resting oxygen fraction and a represents the

203   venous resistance. For each region n the BOLD signal B_n is a static nonlinear function of q_n

204   and v_n:

205
$$B_n = V_0\left[k_1(1-q_n) + k_2\left(1-\frac{q_n}{v_n}\right) + k_3(1-v_n)\right] \tag{10}$$

206   To focus on the functionally relevant frequency range, we band-pass filtered the simulated

207   BOLD signals using the same filter as for the empirical data with a bandpass between 0.1 and

208   0.01 Hz (Achard et al. 2006; Glerean et al. 2012).

Agreement between empirical and simulated data

To achieve biologically plausible signal statistics in the simulated time series at each scale, we performed the fitting to the empirical signals by adjusting G to have a maximal agreement in two different metrics: the metastability, and phase consistency matrices (see below). Each of these metrics represents different dynamical properties of the BOLD signal. Previous research has showed that these adding dynamical metrics such as metastability and phase consistency matrices are better at constraining dynamical working points of dynamical whole-brain models than using static metrics such as FC only (Deco et al. 2017, 2019; Saenger et al. 2017). These metrics were computed for each value of G (between 0 and 2.5 in steps of 0.025) in the simulated data and for the empirical data and compared as described below. Due to multiple spatial scales, the creation of the model was very compute-intensive, e.g. to replicate the time series of 10 subjects from the HCP dataset at a neuronal timescale using a parcellation of 400 regions with different G-values from 0 to 2.5 about 80-100 GB of RAM & 30 days of computation were required. Therefore, we restricted the simulations to 10 iterations, representing time series of a group of 10 subjects. To prove that our analyses were generalizable to a larger group of healthy subjects, we did 100 iterations of the model fitting to empirical time series of a group of 10 subjects from the HCP dataset, that were randomly selected at each iteration.

Dynamical measures used for the fitting:

Metastability: The metastability represents the overall variability of oscillations (Wildie and Shanahan 2012; Deco et al. 2017). It is calculated as the standard deviation of the Kuramoto order parameter R(t) across time, which depicts the average phase $\varphi_k(t)$ in a given region k across n regions.

$$R(t) = \frac{|\sum_{k=1}^{n} e^{i\varphi_k(t)}|}{n} \tag{11}$$

The phases were derived from the data by detrending the filtered fMRI time series and then applying the Hilbert transform. When $R = 1$ all phases are fully synchronized, while $R = 0$ indicates a complete desynchronization of all phases. We calculated the differences between the empirical and simulated metastability. This has been previously proven to be suitable to define the dynamical working point of dynamical whole-brain models (Deco et al. 2017; Saenger et al. 2017).

Phase consistency matrices: We calculated the phase coherence matrix by evaluating the instantaneous phase at each time point t of every region j and then computing the phase difference across all regions. We measured the similarity of these phase coherence matrices over t to create a *phase consistency matrix*. This resulted in a representation of spatiotemporal

fluctuations of phases. To compare between empirical and simulated data, we calculated the
Kolmogorov-Smirnov distance between the empirical and simulated distribution of the phase
consistency matrices. The Kolmogorov-Smirnov distance quantifies the maximal difference
between two distribution functions of two samples and is minimized by the optimal value of G
(Saenger et al. 2017).

Furthermore, we checked whether we retrieved comparable numbers of functional networks in
the empirical and simulated data (see Figure S1 in the supplementary data).

Extraction of whole-brain functional networks using independent component analysis and calculation of entropy

The summary of the analytical steps can be seen in Figure 2. The simulated and empirical time
series were available in different spatial scales. In the case of the simulated signal, we aimed
to retrieve the simulated neuronal time series at separate temporal scales in the range of
milliseconds to seconds (see Figure 2A). To do so, the simulated neuronal time series were
binned by averaging the signals in windows of the width of the timescale, each time bin
corresponding to a time point of the newly created time series. As this approach led to multiple
fine-grained time series with a high computational cost of the analysis, we were only able to
simulate the time series across all temporal scales up to a spatial scale of 400 regions. We
created simulated time series at group level by performing 10 iterations (representing 10
subjects).

In the case of the empirical time series, we extracted a group of 10 subjects from the data by
randomly selecting 10 subjects. We concatenated their time series to retrieve functional
networks on a group level (using the same group size as in the simulation to ensure
comparability). To make the analysis robust to interindividual variability, we repeated this
process 100 times. The temporal scale of the empirical data was determined by the TR (HCP:
720 ms). Given only one temporal scale we were able to extract functional networks in a spatial
scale from 100 to 900 regions.

In each temporal scale (given by the TR in the empirical data or the bin size in the simulated
data), the time series were binarized using the point-process binarization algorithm for BOLD
signals (Tagliazucchi et al. 2012). Here, the time series were normalized using a z-score
transformation and depending on a threshold the time series were set to 0 or 1, resulting in an
event matrix (see the right panel of Figure 2A). Next, the event matrix was normalized using
z-score transformation, so that the event matrix in each brain region would have null mean and
unitary variance. This procedure has been shown to be robust to threshold choices and is a

classical method to reduce dimensionality of dynamical data (Tagliazucchi et al. 2012). We

then continued the analysis with the normalized event matrix *e* (with the dimension: number of

regions *i* x number of time points *b*).

To estimate the number of functional networks, we applied an adaptation of an eigenvalue

analysis for assessing the statistical significance of resulting networks (Peyrache et al. 2010;

Deco et al. 2019), as introduced by Lopes-dos-Santos, Ribeiro, and Tort (2013). This method

finds the number of principal components within the event matrix that have significantly larger

eigenvalues compared to a normal random matrix that follows a probability function, as

specified in Marčenko and Pastur (1967). As can be seen in Figure 2B (left panel), after

determining the number of functional networks, we extracted these functional networks by

applying an independent component analysis to the event matrix *e*. This procedure resulted in

a resulting in a network matrix w_{ic} (with dimension: number of brain regions *i* x functional

networks *c).*

Lastly, we tracked the activity of the functional networks over time (see right panel of Figure

2B). Through projection of the binarized event matrix onto the network matrix, the similarity

between each functional network *c* and the whole-brain activity at each time point *b* could be

assessed. This resulted in an activity matrix *A* (with the dimension: functional networks *c* x time

points *b*):

$$A_{cb} = e_b^T P_c e_b \tag{12}$$

303 with the event matrix *e* and the projection matrix P . The projection matrix P is defined as:

$$P_c = \vec{w}_c \otimes \vec{w}_c = \vec{w}_c \vec{w}_c^T \tag{13}$$

where $\otimes$ is the outer product operator, $\vec{w}_c$ is the one of the extracted functional networks from

the event matrix (the column of the matrix w_c) and e_b is the *b* column of the event matrix (events

at time point *b*).

After retrieving the activity of each functional network over time, we calculated its probability

of occurrence. We calculated the ratio of activity of each functional network in relation to overall

activity (activity of all networks over time), resulting in the probability of each network *c* over

time:

$$p(c) = \sum_b A_{cb} / \sum_{c,b} A_{cb} \tag{14}$$

314 where *b* corresponds to each time point.

315 Using these probabilities, we computed the entropy of occurrence of each network *c*. The

316 entropy represents the richness of switching activity between functional networks, adapted

317 from the concept of entropy by Shannon (1948):

$$H = -\sum_c p(c)\log(p(c)) \tag{15}$$

As the number of functional networks increased with higher spatial scales, we performed a
normalization of the entropy. The normalization was done by dividing the entropy by the
logarithm of the resulting number of networks for each spatial scale. By doing so, it was
possible to compare across spatial scales. We then compared the entropy of network switching
across spatial and temporal scales (see Figure 2C). We did a pairwise comparison of entropy
of spatial scales using Wilcoxon tests in the empirical data and the simulated data (at the
optimal temporal scale and at the temporal scale = TR).

Results

We aimed to describe the optimal spatiotemporal scale that captured the highest information
content about the temporal evolution of functional networks (as evidenced by the switching
activity). We extracted time series at different parcellations at different spatial scales (from 100
to 900 regions) in the empirical data. Furthermore, we created a dynamic mean-field model to
create time series at various temporal scales from milliseconds to seconds (Figure 1) and a
spatial scale between 100 and 400 regions. We extracted functional networks from both
simulated and empirical time series using independent component analysis. We then explored
the probability of occurrence of these functional networks over time. We calculated the entropy
of these probabilities' occurrence of each network, which represents the diversity of switching
activity between functional networks (Figure 2). By restricting our analysis to functional
networks (as opposed to raw time series), we ensured that the information we gained on the
temporal dynamics (as measured by switching activity) was relevant for whole-brain
information processing.

Agreement between empirical and simulated data

The DMF model is a neuronal model that recreates inhibitory and excitatory synaptic dynamics
(including AMPA, GABA and NMDA receptors) following the structure given by the underlying
anatomical connectivity. By using the steps detailed in Figure 1 and following the constraints
of anatomical connectivity as provided by the structural connectome, we were able to create
realistic neuronal time series at the scale of milliseconds to seconds using the DMF model. To
ensure the robustness of the model, we fitted the resulting simulated BOLD time series to the
empirical BOLD time series. Here, we defined a good fitting where the differences in
metastability and the Kolmogorov-Smirnov statistics of the phase consistency matrices
reached a minimum (see Figure S1). As can be seen in Figure S1, the fitting resulted in an
optimum at a global coupling value G between 1.55 and 1.85 (depending on the spatial scale
used).

In both the simulated and empirical data, some of the resulting networks resembled known

classical resting state networks (see Figure 4). As our study focused on the dynamical

alteration of functional networks, we aimed to ensure that the properties of the resulting

functional networks from the simulation were comparable to the properties of the networks

derived from the empirical time series. Therefore, we compared the number of functional

networks derived from the simulated BOLD time series (see Figure S2). Here, the number of

functional networks and its change across spatial scales (i.e., an increase of functional

networks with increasing number of regions) were more in agreement with the empirical

functional networks.

Entropy of switching of whole-brain functional networks

The switching of whole-brain functional networks over time and their probabilities of occurrence

allowed us to estimate entropy H as a representation of the information content of the functional

network activity at various spatiotemporal scales from a probabilistic perspective. We display

the entropy of spatiotemporal networks as a function of the spatial and temporal scale using

empirical (Figure 3A) and simulated time series (Figure 3B). As the number of networks was

contingent on the spatial scale used, we corrected the entropy for the logarithm of the number

of networks to be able to compare across different spatial scales.

We discovered an inverted U-shape form of the entropy H as a function of probability of

spatiotemporal networks across time. Regarding the spatial scale, the H reached the highest

value at a scale of 300 regions (mean simulated H = 0.957, mean empirical H = 0.951), but

with only a small decrease at scales with 100 (mean simulated H = 0.949, mean empirical H =

0.946) or 400 regions (mean simulated H = 0.938, mean empirical H = 0.946). At spatial scales

above 400 regions (analysis only present in empirical data, see Figure 4A), we observed a

further drop in entropy (down to mean empirical H = 0.916 at 900 regions).

Beside the comparison across spatial scales, the simulated time series allowed us to compare

the temporal scales (Figure 3B). Regarding the temporal scale, we found the highest entropy

at an average scale of 150 ms (ranging from 140 to 160 ms, depending on the spatial scale

used). Using finer or coarser temporal scales led a much greater drop in entropy (lowest value:

mean simulated H = 0.5957) than a change of spatial scales.

Taking both spatial and temporal scales into account, the highest level of entropy could be

found at a temporal scale of 150 ms and a spatial scale of 300 regions (see Figure 3 B3). The

optimal temporal scale of 150 milliseconds persisted at all simulated spatial scales. Also, the

effect of temporal scale on entropy was greater than the effect of spatial scale.

Of note, H was always higher when using the empirical dataset in comparison to the simulated

time series even when using the temporal scale (see Figure 3A vs. Figure 3 B1), reflecting the

variability given by the empirical time series (and signals not accounted for in the dynamic

mean field model).

Discussion

In this study, we investigated the most relevant spatiotemporal scale of fundamental

macroscopic dynamical processes, such as the transitions between whole-brain functional

networks. We followed the temporal behaviour of functional whole-brain networks at different

spatial scales and at fine-grained temporal scales from milliseconds to seconds (using a

realistic whole-brain dynamic mean field model). In both empirical and simulated datasets, we

generated evidence that the entropy of network switching followed an inverted U-shaped curve

with a maximum at a spatial scale at about 300 regions and at a temporal scale of about 150

milliseconds. Of note, the optimal temporal scale of about 150 milliseconds persisted at all

simulated spatial scales from 100 to 400 regions, indicating an absent interaction effect

between spatial and temporal scales. Also, the effect of the temporal scale on entropy was

much greater than the effect of spatial scale. Given the close agreement of results using

simulated and empirical time series, our whole-brain network model offers an excellent

opportunity to bridge analyses of brain dynamics across different neuroimaging modalities at

different spatiotemporal scales, e.g. fMRI and EEG data.

Previous studies have performed comparisons between spatial scales in regard to various

metrics, such as the reproducibility of resulting networks, agreement with anatomical

connectivity, and prediction accuracy of neuropsychiatric conditions (Craddock et al. 2011;

Arslan et al. 2018; Dadi et al. 2019; Messé 2019). However, all these studies focused on the

average functional connectivity, without considering the dynamics of these networks. Only

Proix et al. (2016) investigated the effect of spatial scale on the information content of brain

dynamics by decomposing the time series using a principle component analysis in a whole-

brain network model and found the highest eigenvalue at around 140 regions. Higher spatial

scales led to an oversampling with a relative reduction of connectome density, leading to more

segregated regions and an overall reduction of transmission information content across

regions. Although these results are promising, they focused on separate regions rather than

whole-brain networks.

Our study is the first to examine spatial and temporal scales simultaneously with a focus on
brain dynamics of whole-brain networks. Given the significant evidence that maximal entropy
of brain dynamics is associated with maximal transmission of information (Lungarella and
Sporns 2006; Rämö et al. 2007; Shew et al. 2011; Wang et al. 2018) and is associated with
cognitive performance (Niu et al. 2018; Liu et al. 2020) and consciousness (Mashour and
Hudetz 2018), we chose to describe the richness of whole-brain network activity using the
entropy of whole-brain network switching. Selecting the most informative spatiotemporal scale
during analyses of brain dynamics can help to focus the analysis on relevant information about
the dynamical behaviour of brain networks, while reducing the amount of noise (Fornito 2010),
avoiding oversampling (Proix et al. 2016) and optimizing the computational cost of the analysis,
i.e. removing subnetworks that are barely active and contribute little to the overall network
activity.

Our findings have several implications for future research of brain dynamics. First, we were
able to reproduce the finding of the optimal temporal scale of about 150 milliseconds using
another dataset (Deco et al. 2019). Our findings reflect experimental results of temporal
dynamics of conscious processes that operate at similar temporal scales and typically involve
a rapid temporal sequence of information stabilization and transfer (Koenig et al. 2002; Van
De Ville et al. 2010; Wutz et al. 2014; Salti et al. 2015; Mai et al. 2019). On top of that, our
study shows that the optimal temporal scale does not depend on the spatial scale, i.e. an
optimal scale of about 150 milliseconds persists across all spatial scales. For researchers
aiming to extract the most relevant information content in their analyses of brain dynamics, we
therefore advise to either use neuroimaging modalities operating at this optimal temporal scale
(e.g. MEG or EEG) (Michel and Koenig 2018) or augment their analyses with whole-brain
modeling, which allows to take other temporal scales into consideration. Second, our study
provides an empirical basis for choosing the spatial scale for neuroimaging analyses with a
focus on brain dynamics of whole-brain functional networks. We provided evidence that a
spatial scale of about 300 regions is sufficient to capture the most relevant information on
macroscopic brain dynamics. While lower scales may be associated with a loss of information,
higher spatial scales introduce irrelevant and possibly more noisy functional networks. Our
recommendations, based on empirical data rather than arbitrary choices, might contribute to
harmonizing analyses of brain dynamics across scales.

Limitations and outlook
There are several limitations in our methodological approach. First, we used independent
component analysis to derive whole-brain functional networks at different scales. As any other
higher-order statistical method, independent component analysis is not free of underlying

assumptions and especially assumes maximal spatial independence of the networks (Jutten
and Herault 1991). Future studies could consider additional analyses using other metrics such
as network measures. However, as Arslan et al. (2018) and Hilger et al. (2020) demonstrated
in their studies (Arslan et al. 2018; Hilger et al. 2020), many network measures are largely
altered by the spatial scale and appropriate correction techniques should be used for such
analyses across scales.
470
Second, our analysis was focused on the spatial scales of dynamical behaviour of whole-brain
networks. Depending on the size of the networks of interest, other spatial and temporal scales
might be relevant. Future studies could therefore consider exploring brain dynamics of cellular-
level networks using microscale imaging tools such as optical imaging. Methods aiming at
analytically bridging macro- and microscales are currently under investigation (Weiskopf et al.
2015; Larivière et al. 2019; Gao et al. 2020).
477
478 Third, both the estimation of the whole-brain functional networks as well as the calculation of
479 the entropy of the network switching activity was done on a group level. Comparing the entropy
480 of network switching on an individual level would allow to relate individual cognition to
481 dynamical behaviour of brain networks.
482
483 Overall, our results suggest that whole-brain functional brain networks operate at an optimum
484 of about 300 regions and a timescale of about 150 milliseconds. We contribute to the
485 understanding of the dynamical behaviour of whole-brain networks, which could inspire future
486 human neuroimaging studies to harmonize spatiotemporal scales and use dynamical models
487 to create connections between micro- and macroscopic scales.
488

Funding
This work was supported by a short-term fellowship of the European Molecular Biology
Organization (n. 7366) and by an InEurope fellowship of the International Brain Research
Organization of XK. AL is supported by Swiss National Science Foundation Sinergia grant no.
170873. GD is supported by AWAKENING Using whole-brain models perturbational
approaches for predicting external stimulation to force transitions between different brain
states (ref. PID2019-105772GB-I00, AEI FEDER EU), funded by the Spanish Ministry of
Science, Innovation and Universities (MCIU), State Research Agency (AEI) and European
Regional Development Funds (FEDER), by HBP SGA3 Human Brain Project Specific Grant
Agreement 3 (Grant Agreement No. 945539), funded by the EU H2020 FET Flagship program
and by SGR Research Support Group support (ref. 2017 SGR 1545), funded by the Catalan
Agency for Management of University and Research Grants (AGAUR). MLK is supported by

the ERC Consolidator Grant: CAREGIVING (n. 615539), Center for Music in the Brain, funded

by the Danish National Research Foundation (DNRF117), and Centre for Eudaimonia and

Human Flourishing funded by the Pettit and Carlsberg Foundations.

References

Achard S, Salvador R, Whitcher B, Suckling J, Bullmore E. 2006. A resilient, low-frequency, small-world human brain functional network with highly connected association cortical hubs. J Neurosci Off J Soc Neurosci. 26:63–72.

Alexandrov YI. 1999. Physiological Regularities of the Dynamics of Individual Experience and the "Stream of Consciousness", in Neural Bases and Psychological Aspects of Consciousness, Teddei-Ferretti, C., and Musio, C., Eds., Singapore: World Scientific, 1999, p. 201. In: Neural Bases and Psychological Aspects of Consciousness. Singapore: World Scientific. p. 201.

Arslan S, Ktena SI, Makropoulos A, Robinson EC, Rueckert D, Parisot S. 2018. Human brain mapping: A systematic comparison of parcellation methods for the human cerebral cortex. NeuroImage. 170:5–30.

Ashburner J. 2007. A fast diffeomorphic image registration algorithm. NeuroImage. 38:95–113.

Cornblath EJ, Ashourvan A, Kim JZ, Betzel RF, Ciric R, Adebimpe A, Baum GL, He X, Ruparel K, Moore TM, Gur RC, Gur RE, Shinohara RT, Roalf DR, Satterthwaite TD, Bassett DS. 2020. Temporal sequences of brain activity at rest are constrained by white matter structure and modulated by cognitive demands. Commun Biol. 3:1–12.

Craddock RC, James GA, Holtzheimer PE, Hu XP, Mayberg HS. 2011. A whole brain fMRI atlas generated via spatially constrained spectral clustering. Hum Brain Mapp. 33:1914–1928.

Dadi K, Rahim M, Abraham A, Chyzhyk D, Milham M, Thirion B, Varoquaux G, Alzheimer's Disease Neuroimaging Initiative. 2019. Benchmarking functional connectome-based predictive models for resting-state fMRI. NeuroImage. 192:115–134.

Deco G, Cruzat J, Kringelbach ML. 2019. Brain songs framework used for discovering the relevant timescale of the human brain. Nat Commun. 10:583.

Deco G, Kringelbach ML, Jirsa VK, Ritter P. 2017. The dynamics of resting fluctuations in the brain: metastability and its dynamical cortical core. Sci Rep. 7:3095.

Deco G, Ponce-Alvarez A, Hagmann P, Romani GL, Mantini D, Corbetta M. 2014. How Local Excitation–Inhibition Ratio Impacts the Whole Brain Dynamics. J Neurosci. 34:7886–7898.

Deco G, Ponce-Alvarez A, Mantini D, Romani GL, Hagmann P, Corbetta M. 2013. Resting-state functional connectivity emerges from structurally and dynamically shaped slow linear fluctuations. J Neurosci Off J Soc Neurosci. 33:11239–11252.

Engel AK, Fries P, Singer W. 2001. Dynamic predictions: oscillations and synchrony in top-down processing. Nat Rev Neurosci. 2:704–716.

Fornito. 2010. Network scaling effects in graph analytic studies of human resting-state fMRI data. Front Syst Neurosci.

Gao R, van den Brink RL, Pfeffer T, Voytek B. 2020. Neuronal timescales are functionally dynamic and shaped by cortical microarchitecture. eLife. 9:e61277.

Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S, Webster M, Polimeni JR, Van Essen DC, Jenkinson M, WU-Minn HCP Consortium. 2013. The minimal preprocessing pipelines for the Human Connectome Project. NeuroImage. 80:105–124.

Glerean E, Salmi J, Lahnakoski JM, Jääskeläinen IP, Sams M. 2012. Functional magnetic resonance imaging phase synchronization as a measure of dynamic functional connectivity. Brain Connect. 2:91–101.

Hilger K, Fukushima M, Sporns O, Fiebach CJ. 2020. Temporal stability of functional brain modules associated with human intelligence. Hum Brain Mapp. 41:362–372.

Horn A, Blankenburg F. 2016. Toward a standardized structural–functional group connectome in MNI space. NeuroImage. 124:310–322.

Horn A, Li N, Dembek TA, Kappel A, Boulay C, Ewert S, Tietze A, Husch A, Perera T, Neumann W-J, Reisert M, Si H, Oostenveld R, Rorden C, Yeh F-C, Fang Q, Herrington TM, Vorwerk J, Kühn AA. 2018. Lead-DBS v2: Towards a comprehensive pipeline for deep brain stimulation imaging. NeuroImage. 184:293–316.

Horn A, Reich M, Vorwerk J, Li N, Wenzel G, Fang Q, Schmitz-Hübsch T, Nickl R, Kupsch A,
Volkmann J, Kühn AA, Fox MD. 2017. Connectivity Predicts Deep Brain Stimulation
Outcome in Parkinson Disease. Ann Neurol. 82:67–78.
Jutten C, Herault J. 1991. Blind separation of sources, part I: An adaptive algorithm based on
neuromimetic architecture. Signal Process. 24:1–10.
Koenig T, Prichep L, Lehmann D, Sosa PV, Braeker E, Kleinlogel H, Isenhart R, John ER.
2002. Millisecond by Millisecond, Year by Year: Normative EEG Microstates and
Developmental Stages. NeuroImage. 16:41–48.
Kreher BW, Mader I, Kiselev VG. 2008. Gibbs tracking: a novel approach for the reconstruction
of neuronal pathways. Magn Reson Med. 60:953–963.
Larivière S, Vos de Wael R, Paquola C, Hong S-J, Mišić B, Bernasconi N, Bernasconi A,
Bonilha L, Bernhardt BC. 2019. Microstructure-Informed Connectomics: Enriching
Large-Scale Descriptions of Healthy and Diseased Brains. Brain Connect. 9:113–127.
Liégeois R, Li J, Kong R, Orban C, Van De Ville D, Ge T, Sabuncu MR, Yeo BTT. 2019. Resting
brain dynamics at different timescales capture distinct aspects of human behavior. Nat
Commun. 10:2317.
Liu M, Liu X, Hildebrandt A, Zhou C. 2020. Individual Cortical Entropy Profile: Test–Retest
Reliability, Predictive Power for Cognitive Ability, and Neuroanatomical Foundation.
Cereb Cortex Commun. 1.
Lopes-dos-Santos V, Ribeiro S, Tort ABL. 2013. Detecting cell assemblies in large neuronal
populations. J Neurosci Methods. 220:149–166.
Lungarella M, Sporns O. 2006. Mapping Information Flow in Sensorimotor Networks. PLOS
Comput Biol. 2:e144.
Lurie DJ, Kessler D, Bassett DS, Betzel RF, Breakspear M, Kheilholz S, Kucyi A, Liégeois R,
Lindquist MA, McIntosh AR, Poldrack RA, Shine JM, Thompson WH, Bielczyk NZ,
Douw L, Kraft D, Miller RL, Muthuraman M, Pasquini L, Razi A, Vidaurre D, Xie H,
Calhoun VD. 2020. Questions and controversies in the study of time-varying functional
connectivity in resting fMRI. Netw Neurosci. 4:30–69.
Mai A-T, Grootswagers T, Carlson TA. 2019. In search of consciousness: Examining the
temporal dynamics of conscious visual perception using MEG time-series data.
Neuropsychologia. 129:310–317.
Marčenko VA, Pastur L. 1967. Distribution of eigenvalues for some sets of random matrices.
Math USSR Sb. 1:457–483.
Mashour GA, Hudetz AG. 2018. Neural Correlates of Unconsciousness in Large-Scale Brain
Networks. Trends Neurosci. 41:150–160.
Meer JN van der, Breakspear M, Chang LJ, Sonkusare S, Cocchi L. 2020. Movie viewing elicits
rich and reliable brain state dynamics. Nat Commun. 11:5004.
Messé A. 2019. Parcellation influence on the connectivity-based structure–function
relationship in the human brain. Hum Brain Mapp. 41:1167–1180.
Michel CM, Koenig T. 2018. EEG microstates as a tool for studying the temporal dynamics of
whole-brain neuronal networks: A review. NeuroImage, Brain Connectivity Dynamics.
180:577–593.
Niu Y, Wang B, Zhou M, Xue J, Shapour H, Cao R, Cui X, Wu J, Xiang J. 2018. Dynamic
Complexity of Spontaneous BOLD Activity in Alzheimer's Disease and Mild Cognitive
Impairment Using Multiscale Entropy Analysis. Front Neurosci. 12.
Peyrache A, Benchenane K, Khamassi M, Wiener SI, Battaglia FP. 2010. Principal component
analysis of ensemble recordings reveals cell assemblies at high temporal resolution. J
Comput Neurosci. 29:309–325.
Proix T, Spiegler A, Schirner M, Rothmeier S, Ritter P, Jirsa VK. 2016. How do parcellation
size and short-range connectivity affect dynamics in large-scale brain network models?
NeuroImage. 142:135–149.
Rämö P, Kauffman S, Kesseli J, Yli-Harja O. 2007. Measures for information propagation in
Boolean networks. Phys Nonlinear Phenom. 227:100–104.
Saenger VM, Kahan J, Foltynie T, Friston K, Aziz TZ, Green AL, van Hartevelt TJ, Cabral J,
Stevner ABA, Fernandes HM, Mancini L, Thornton J, Yousry T, Limousin P, Zrinzo L,
Hariz M, Marques P, Sousa N, Kringelbach ML, Deco G. 2017. Uncovering the

underlying mechanisms and whole-brain dynamics of deep brain stimulation for Parkinson's disease. Sci Rep. 7:9882.

Salti M, Monto S, Charles L, King J-R, Parkkonen L, Dehaene S. 2015. Distinct cortical codes and temporal dynamics for conscious and unconscious percepts. eLife. 4.

Schaefer A, Kong R, Gordon EM, Laumann TO, Zuo X-N, Holmes AJ, Eickhoff SB, Yeo BTT. 2018. Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic Functional Connectivity MRI. Cereb Cortex. 28:3095–3114.

Setsompop K, Kimmlingen R, Eberlein E, Witzel T, Cohen-Adad J, McNab JA, Keil B, Tisdall MD, Hoecht P, Dietz P, Cauley SF, Tountcheva V, Matschl V, Lenz VH, Heberlein K, Potthast A, Thein H, Van Horn J, Toga A, Schmitt F, Lehne D, Rosen BR, Wedeen V, Wald LL. 2013. Pushing the limits of in vivo diffusion MRI for the Human Connectome Project. NeuroImage. 80:220–233.

Shannon CE. 1948. A Mathematical Theory of Communication. Bell Syst Tech J. 27:379–423.

Shew WL, Yang H, Yu S, Roy R, Plenz D. 2011. Information capacity and transmission are maximized in balanced cortical networks with neuronal avalanches. J Neurosci Off J Soc Neurosci. 31:55–63.

Stephan KE, Weiskopf N, Drysdale PM, Robinson PA, Friston KJ. 2007. Comparing hemodynamic models with DCM. NeuroImage. 38:387–401.

Stitt I, Hollensteiner KJ, Galindo-Leon E, Pieper F, Fiedler E, Stieglitz T, Engler G, Nolte G, Engel AK. 2017. Dynamic reconfiguration of cortical functional connectivity across brain states. Sci Rep. 7:1–14.

Tagliazucchi E, Balenzuela P, Fraiman D, Chialvo DR. 2012. Criticality in large-scale brain FMRI dynamics unveiled by a novel point process analysis. Front Physiol. 3:15.

Tang Y-Y, Rothbart MK, Posner MI. 2012. Neural correlates of establishing, maintaining, and switching brain states. Trends Cogn Sci. 16:330–337.

Thompson GJ, Magnuson ME, Merritt MD, Schwarb H, Pan W-J, McKinley A, Tripp LD, Schumacher EH, Keilholz SD. 2013. Short-time windows of correlation between large-scale functional brain networks predict vigilance intraindividually and interindividually. Hum Brain Mapp. 34:3280–3298.

Van De Ville D, Britz J, Michel CM. 2010. EEG microstate sequences in healthy humans at rest reveal scale-free dynamics. Proc Natl Acad Sci. 107:18179–18184.

Van Essen DC, Smith SM, Barch DM, Behrens TEJ, Yacoub E, Ugurbil K. 2013. The WU-Minn Human Connectome Project: An overview. NeuroImage, Mapping the Connectome. 80:62–79.

Vidaurre D, Smith SM, Woolrich MW. 2017. Brain network dynamics are hierarchically organized in time. Proc Natl Acad Sci. 114:12827–12832.

Wang DJJ, Jann K, Fan C, Qiao Y, Zang Y-F, Lu H, Yang Y. 2018. Neurophysiological Basis of Multi-Scale Entropy of Brain Complexity and Its Relationship With Functional Connectivity. Front Neurosci. 12.

Weiskopf N, Mohammadi S, Lutti A, Callaghan MF. 2015. Advances in MRI-based computational neuroanatomy: from morphometry to in-vivo histology. Curr Opin Neurol. 28:313–322.

Wildie M, Shanahan M. 2012. Metastability and chimera states in modular delay and pulse-coupled oscillator networks. Chaos Interdisc J Nonlinear Sci. 22:043131.

Wong K-F. 2006. A Recurrent Network Mechanism of Time Integration in Perceptual Decisions. J Neurosci. 26:1314–1328.

Wutz A, Weisz N, Braun C, Melcher D. 2014. Temporal Windows in Visual Processing: "Prestimulus Brain State" and "Poststimulus Phase Reset" Segregate Visual Transients on Different Temporal Scales. J Neurosci. 34:1554–1565.

Yeo BT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman JL, Smoller JW, Zöllei L, Polimeni JR, Fischl B, Liu H, Buckner RL. 2011. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. J Neurophysiol. 106:1125–1165.

Yoo HB, Moya BE, Filbey FM. 2020. Dynamic functional connectivity between nucleus accumbens and the central executive network relates to chronic cannabis use. Hum Brain Mapp. 41:3637–3654.

672 Yuan J, Li X, Zhang J, Luo L, Dong Q, Lv J, Zhao Y, Jiang X, Zhang S, Zhang W, Liu T. 2018.
673   Spatio-temporal modeling of connectome-scale brain network interactions via time-
674   evolving graphs. NeuroImage. 180:350–369.

 Figures

Simulated time series   Model fitting   Empirical time series

Figure 1. Whole-brain modeling steps to create simulated functional time series fitted to empirical BOLD data. Using a whole-brain network

model such as the dynamic mean field model allows us to accurately create time series data at different temporal scales. Local dynamics of each

region given by a *parcellation* are generated by a *dynamic mean field model* and coupled through the *structural connectome* (as provided by the

numbers of fiber tracts estimated from diffusion-weighted imaging). To fit the resulting neuronal time series to the empirical BOLD time series, we

employ a *Balloon-Windkessel hemodynamic model* to create simulated BOLD time series. The simulated time series are *fitted* to the empirical time

series using metrics of metastability and phase similarity matrix distributions.

A. Extraction of different spatial and temporal scales

Neuronal time series with 100 regions

Number of regions

Time

Neuronal time series with 400 regions

Number of regions

Time

Binning of time series

Number of regions

Time

Bin size

Binned time series with bin size = 20ms

Time

Event matrix based on bin size = 20ms

Events over time

Binned time series with bin size = 200ms

Time

Event matrix based on bin size = 200ms

Events over time

B. Extraction of functional networks using ICA and tracking of network activity over time

Contribution of region to the network

Regions

Functional networks

C. Calculation of the optimal spatiotemporal scale

Entropy

optimal spatiotemporal scale

Spatial scale A

Spatial scale B

Temporal scale

Figure 2. Extraction and tracking of whole-brain functional networks at different spatial and temporal scales using the whole-brain model.

A. We simulate neuronal time series at different spatial scales (from 100 to 400 regions). We then create different bin sizes of the time series (using

bins from 10ms to 3000ms), the bin size corresponds to the temporal scale. The binned time series are binarized using a point process paradigm,

resulting in an event matrix.

B. We extract whole-brain functional networks using independent component analysis, resulting in a network matrix (see ribbon plot) These networks

are tracked over time by projecting the event matrix onto the networks, resulting in an activity matrix (not displayed).

C. The richness of the switching between functional networks is estimated by calculating the entropy of their switching probability. The entropy is

compared across spatial and temporal scales.

A. Empirical (spatial scale)

B. Model (spatiotemporal scale)

B1. Spatial scale (TR)

B2. Spatial scale
(at optimal temporal scale)

B3. Temporal scale

Figure 3. Entropy of the temporal probability of whole-brain functional networks in different spatial and temporal scales of the empirical (A) and simulated data (B). The entropy is calculated across spatial scales in the empirical data with a fixed temporal scale of 720 ms (corresponding to the TR). The simulated data gives the opportunity to explore different spatial scales at the temporal scale of the TR, 720 ms, (B1) as well as at the optimal temporal scale of 150 ms (B2). Beyond that it can be also used to explore various temporal scales and spatial scales simultaneously (B3). Both the empirical and simulated data show that the highest entropy can be found at a spatial scale of 300 regions with only a minor decrease in entropy at a spatial scale of 200 regions (marked by a red box in A and B1-B2). The highest entropy can be found at a temporal scale of 150 ms across all spatial scales (B3). Each datapoint depicts a random group of 10 subjects in the empirical data or a simulation trial simulating a group of 10 subjects. Statistical significance of comparisons between spatial scales is indicated with "ns" meaning a p-value > 0.05, * meaning < 0.05, *** meaning 0.001 (FDR-corrected).

SIMULATED   EMPIRICAL

Default Mode Network

Central Visual Network

Temporal Parietal Network

705 **Figure 4. Examples of group whole-brain functional networks rendered on the standard brain.** The left column has been retrieved from the

706 simulated time series (using a TR = 720 ms), the right column from the empirical time series. Some of these networks have a high overlap with

707 classical resting state networks (Yeo et al. 2011) such as the Default Mode Network, Central Visual Network and Temporal Parietal Network.