Application of subject-specific adaptive mechanical loading for bone

healing in a mouse tail vertebral defect.

Angad Malhotra[1], Matthias Walle[1], Graeme R. Paul[1], Gisela A. Kuhn[1], Ralph Müller[1]*.

[1]Institute for Biomechanics, ETH Zurich, Zurich, Switzerland.

*Corresponding author:

Ralph Müller, PhD

Institute for Biomechanics

ETH Zurich

Leopold-Ruzicka-Weg 4

8093 Zurich, Switzerland

Email: ram@ethz.ch

Abstract

Methods to repair bone defects arising from trauma, resection, or disease, continue to be sought after. Cyclic mechanical loading is well established to influence bone (re)modelling activity, in which bone formation and resorption are correlated to micro-scale strain. Based on this, the application of mechanical stimulation across a bone defect could improve healing. However, if ignoring the mechanical integrity of defected bone, loading regimes have a high potential to either cause damage or be ineffective. This study explores real-time finite element (rtFE) methods that use three-dimensional structural analyses from micro-computed tomography images to estimate effective peak cyclic loads in a subject-specific and time-dependent manner. It demonstrates the concept in a cyclically loaded mouse caudal vertebral bone defect model. Using rtFE analysis combined with adaptive mechanical loading, mouse bone healing was significantly improved over non-loaded controls, with no incidence of vertebral fractures. Such rtFE-driven adaptive loading regimes demonstrated here could be relevant to clinical bone defect healing scenarios, where mechanical loading can become patient-specific and more efficacious. This is achieved by accounting for initial bone defect conditions and spatio-temporal healing, both being factors that are always unique to the patient.

Introduction

The management of critical-size bone defects continues to present surgical challenges. Trauma and bone resection can lead to lengthy recovery times or amputation. The use of autografts is the current gold standard, however, is quantity-limited and accounts for 20% of the complications[1]. Despite advances in biomaterial development and understanding of signaling mechanisms, the search for improved treatment methods of such bone defects continues.

One treatment method of interest is mechanical loading of bone. Mechanical interactions have a long-established relationship to bone physiology, leading to earlier concepts of micromotion during bone defect healing[2], and the significance of fracture instability in healing outcomes[3,4]. The effects of mechanical forces on bone healing have been previously reviewed[5,6]; mechanical loading is likely to depend on frequency[7] and cycle number[8], influences mesenchymal stem cell differentiation[9], and has a role in guiding healing towards primary and secondary bone healing pathways[10]. In contrast, mechanical loading and relative motion of fragments showed little to no benefit in other studies[11,12], though the timing of the changes of the mechanical environment in relation to healing phases could also play a role[13]. This further highlights the need to understand the mechanical environment in and around bone defects during healing. This mechanical environment of bone includes the relevant surrounding hard and soft tissues, and their interaction as subject to Newtonian mechanics, which allows computational exploitation for assessing the loading history and relationship to morphological changes[14]. However, the translation of these load-driven bone (re)modelling concepts to highly unique bone defect healing scenarios is lacking. Another current challenge that arises is how to determine the force that needs to be applied in a subject-specific manner in order to have a maximal mechanobiological cue without damaging the bone.

Finite element (FE) analysis is a well-proven approach to understand micro-scale strains and has been previously successfully used to correlate strain and in vivo bone (re)modelling activities in mice[15–17]. In such workflows, bone mechanoregulation can be studied non-invasively by combining imaging and

computational FE-derived strain estimation methods[18]. With advances in computational power, the

time needed to calculate voxel-based strains relevant for bone healing has drastically shortened in the

last decade. Depending on the complexity and resolution deemed suitable, it is possible to do this

immediately after imaging to limit unnecessary or additional handling and anesthesia in mice. This

concept is concurrently presented in a mouse femoral defect model[19,20], and in combination introduce

the concept of real-time finite element (rtFE) analysis to describe this approach. Since mechanical

loading is effective only within a certain strain window[21], maintaining the applied loading within this

window is critical. Loading too high risks damage (Supplementary Fig. S1a) and loading too low risks

no effect. FE analysis can be used to estimate the optimal forces, and the rtFE method builds on this

by streamlining the process of imaging, analysis, and treatment.

Two factors are relevant for determination of the appropriate loading conditions: the defect itself; and

its changes due to healing. First, every defect is unique in shape, size, and location. This, in

combination with the surrounding structural anatomy, will influence how strain is transferred across

the region. Second, inherent differences between an individual's healing capabilities will always exist.

When bone heals, the tissue-level stiffness increases. If constant stimuli are applied, micro-level

strains will decrease as bone forms and reinforces the defect. This would lead to a lowering of the

regional strain, and result in sub-optimal loading conditions. Therefore, applying individualized and

adapting loading regimes that factor in the defect and its unique healing has high potential to promote

bone healing, not only in mice, but in humans, where these two factors can vary widely case to case.

Applying loads to a bone defect, and imaging it at the necessary resolution, are fundamental

requirements of this study. A previously described method enabled the loading of mouse vertebrae[22–

24], and importantly, allowed high-resolution scanning of the vertebrae. This was recently advanced on

to investigate the loading frequency effect on mouse vertebral bone parameters[25]. To investigate

specifically bone defect healing in this current study, a caudal vertebral bone defect model was

developed, which could be incorporated into the previously successfully used workflows. This model

is straightforward, reproducible and facilitates biomaterial placement[26]. In comparison to commonly

used mouse hind leg models, the vertebral model can reduce the complexity and uncertainty within the

FE simulation. For example, hind leg models can have more complex boundary conditions due to

more complex joint constraints of the limb, greater influence from external bodyweight loadings due

to gravity, and higher internal muscle-bone loads applied by the mouse during ambulation[27].

Furthermore, the vertebral model requires no surgical fixation, and allows for early loading post-

surgery due to the high initial stability of the defect region compared to osteotomy-based models. This

lack or presence of fixation can make comparisons difficult, even if one considers that the

mechanobiological responses are consistent. Overall, the vertebral defect model introduced here

provides another anatomical location to advance theories of bone mechanoregulation during defect

healing.

Longitudinal time-lapsed imaging with micro-computed tomography (micro-CT) is a suitable method

to image bone at the early stages of healing[28]. This can provide short time interval snapshots of the

healing progression and create high-resolution datasets for FE simulations. This time-lapsed imaging

method is currently most feasible in smaller animals, and has been previously demonstrated in

vertebrae[22], and recently within both mouse femoral defect models[29], and to assess longer-term

morphological changes of intact mouse vertebrae[25,30]. This method is highly relevant here to provide

weekly insights into the subject-specific healing progression, and when used in combination with the

rtFE methods, it enables in vivo assessment and proportional changes to the loading conditions

simultaneously.

The objective of this study was to test the feasibility and effect of subject-specific adaptive mechanical

loading to treat bone defects. This was investigated in a newly developed mouse vertebral defect

model that allowed mechanical loading across the vertebrae, as well as high-resolution imaging for

rtFE analyses. As humans also share similarities to bone loading responses[31], such a workflow could

pave the way for patient-specific loading regimes that increase the effect and repeatability of

mechanical loading regimes for bone regeneration strategies.

Results

General observations

All mice tolerated the defect surgery procedure well, with no impaired movement or indications of

pain, except one, which was euthanized out of precaution immediately after surgery due to perceived

excessive bleeding during surgery. None of the remaining mice experienced adverse effects from the

rtFE procedure, with no fractures or additional pain due to the workflow. One additional mouse was

euthanized after one week due to increasing and persistent swelling and signs of osteolysis in the

adjacent vertebrae around the pins. Furthermore, one defect was excluded from the data analysis

because it was drilled through two cortices. In total, this resulted in groups of 6 (control) and 7 (rtFE

loading) mice.

The rtFE method implemented in the study increased the total anesthesia time from approximately 22

minutes for the classic procedure to approximately 30 minutes. This additional time was the

computing time and adjustment of the loading device and is a downside of the rtFE method

(Supplementary Fig. S3). No difference in the time to regain consciousness was noted, and all mice

recovered from the anesthesia as expected. Force increased significantly over time ($F_{(3,18)}=25.8$,

$p<0.001$), with the initial average peak-to-peak force of the cyclic load calculated for the rtFE loading

groups was 4.3N (±0.7), and significantly increased per week, first to 4.5 (±0.5), then to 4.8 (±0.4),

and to 5.2N (±0.3) in the final week of loading.

Healing progressed appositionally from the ventral and lateral internal surfaces of the bone (Fig. 1a).

There were no signs of cortical bridging. Dense trabecular bone formed in regions where it would

bridge to adjacent surfaces (Fig. 1b), stabilizing the defect against the applied loading and consequent

bending moment induced by the defect asymmetry.

139
140 **Figure 1. Time lapsed imaging and overlay of formation and resorption on a weekly basis. (a)**
141 Time lapsed images of representative animals from both groups. **(b)** Weekly overlays show formation
142 and resorption patterns from 1 to 4 weeks post-surgery. Bone formed within the defect without cortical
143 bridging. Red/yellow: bone volume formed at week 1, 2, 3, and 4. Blue/purple: bone volume resorbed
144 at week 1, 2, 3, and 4.

Longitudinal assessment of bone defect healing

Two volumes were created to differentiate between the initial empty defect space, and the existing

surrounding bone. These were the defect centre (DC) and the defect periphery (DP). (Fig. 2a). Within

DC (Fig. 2b), a significant interaction was present for bone volume fraction (BV/TV) between time

and loading ($F(1,4)=8.90$, $p<0.005$)). At week 2, 3 and 4, loading significantly increased BV/TV over

controls ($p<0.05$). BV/TV increased significantly over time in both loading and control groups

($p<0.005$). In the DP, both time ($F(1,4)=164.7$, $p<0.005$)) and the loading ($F(1,4)=5.34$, $p=0.041$) had

significant overall effects on BV/TV (Fig. 2c).

Figure 2. Longitudinal changes in bone volume fraction. (a) The vertebrae were divided into a
defect centre (DC) and defect periphery (DP). **(b)** BV/TV within the DCsignificantly increased with
the rtFE loading from week 2 compared to controls. **(c)** BV/TV within DP was also found to be
influenced, but not to the same magnitude or extent as the DC.

Overall, loading (F(1,3)=12.6, p<0.001)) and time (F(1,3)=23.2, p<0.001) had a significant effect on

the DC bone formation rate (BFR/DC). Loading significantly increased BFR/DC over controls

between weeks 1-2 (F(1,3)=5.83, p=0.013), and weeks 3-4 (F(1,3)=4.39, p=0.042), though did not

reach significance for weeks 2-3 (F(1,3)=2.05, p=0.159) (Fig. 3a). Loading did not largely affect the

DP bone formation rate (BFR/DP) or DP bone resorption rate (BRR/DP) at any time (Fig. 3b). Also,

overall, loading did not have a large effect on BRR/DC or BRR/DP compared to control mice (Fig. 3).

Figure 3. Longitudinal changes in formation and resorption volume fractions. (a) Loading
influenced the BFR/DC compared to controls, and reached significance at postoperative weeks 2 and
4, while loading did not appear to influence BRR/DC compared to controls. **(b)** Loading did not
significantly influence either BFR/DP or BRR/DP compared to controls, at any time interval.

Mechanics of bone volume changes

After 4 weeks, none of the vertebrae had recovered their pre-surgery axial stiffness based on the

applied forces. From week 2 onwards, the treatment had a significant positive effect on FE-calculated

stiffness (p<0.05, Supplementary Fig. S2a). There was also a significant positive Pearson's correlation

between BV/TV in the DC, and FE-calculated normalized stiffness (r=0.907, n=51, p<0.005,

Supplementary Fig. S2b), while in the DP the correlation to normalized stiffness was significant, but

lower (r=0.809, n=51, p<0.005). A pattern was noted in the probability of formation, quiescence, or

resorption events within the combined DC and DP regions; they were largely related to effective strain

(EFF). The effective strain as a percentile of the max effective strain (EFF/EFF$_{MAX}$) was used to find

the conditional probability of a (re)modelling event occurring due to strain. During the first week of

healing, bone formed with a random conditional probability (cp(x) = 33.3%). However, in subsequent

weeks, bone formed in the upper half of the strain field (cpF(x > 50 %) > 33.33 %). The probability

for resorption was the highest within the first 30% of occurred strain leading to a small strain window

where bone was predominantly quiescent between 30% and 50% (Fig. 4a). This pattern also occurred

in control animals (Fig. 4b) where physiological strains were simulated with FE analysis (Fig. 5).

When comparing the loading and control cases, the curvature of the formation, resorption and

quiescence profiles in the loading cases had steeper and more pronounced curve sections compared to

the control cases. There was also a small shift towards lower EFF/EFF$_{MAX}$ being formative with

loading.

Figure 4. Conditional probabilities of formation and resorption events within the combined DC and DP regions. Effective strain as a ratio of the maximum effective strain value (EFF/EFF$_{MAX}$)). **(a)** Higher ratios of EFF/EFF$_{MAX}$ led to formation activity in treatment groups, and lower ratios led to resorption activity, regardless whether externally loaded in the treatment group, or in **(b)** control animals with an assumed axial strain.

Figure 5. Representative sample depicting formation and resorption relationship with effective strain. Regions of higher effective strain tended to formation, while lower effective strain tended to resorption.

Discussion

While the influence of mechanical loading on bone (re)modelling is known, implementing this to defect healing creates other challenges. These arise as two aspects, being the changed mechanical environment due to the initial defect, and its unknown healing thereafter.

This study showed that by introducing an rtFE approach to an existing loading set-up[22], bone defect healing could be significantly improved over no-treatment controls. Importantly, this approach succeeded in avoiding any incidence of fracture due to overloading, and in principle, homogenized strain across different defect shapes, sizes, and healing progressions. Adaption of the loading within the mechanical environment is not novel in itself, with mixed reports on the effectiveness of dynamization[12,32], in which a change in stiffness of external fixators is adapted over healing periods. Adding to these existing concepts, this study estimated individualized loads to apply during healing; the rtFE approach allows much greater accuracy in the control of strain, as opposed to generic or pre-determined adaptive regimes.

Loading started at two days after the defect was created, at which time the mice were still relatively young at fourteen weeks old. The bone response to loading has previously been shown to have some age-dependency on mice around this age, where six week old mice had a more exaggerated response to loading compared to ten and sixteen week old mice[33]. Hence, it could be questioned whether the positive effect found in this study would also be repeated in older mouse. In this regard, it has been reported that after sixteen weeks old, aging has less of an influence on the response to loading[30]. At fourteen weeks old, the mice in this study are near the border of this apparent age threshold. As such, prior studies suggest the positive effect of this rtFE loading could be beneficial into adulthood and beyond, though further studies would be needed to confirm this.

The timing of loading after bone injury is a topic of debate. In general, loading is known to influence

cell activity and function due to tissue deformation and fluid flow[34]. Furthermore, it influences both

spatial and temporal biological responses at multiple scales[35,36]. This aspect is more important in the

case of bone healing, where multiple overlapping phases exist. Early loading from two days onwards

has been reported less effective than delayed loading at two weeks[37]. However, it has also been

reported that early cyclic loading may increase oxygen transport to the defect region[38], promoting the

longer term regeneration response. As differences in bone parameters were already noted after two

weeks in this study, it seems that early loading of three sessions per week is potentially more effective

than delayed loading, especially as subject-specific adaptive loading will be in an efficient range

without risking damage to early callus structures.

The new bone that formed within the defect did not appear to be simply recreating the pre-defect bone

structure, but to be forming based on other factors. During the defect healing, strain appeared to guide

bone (re)modelling activities, more so than an inherent sense of prior bone anatomy. Bone appeared to

form in compensation for the asymmetry of the defected bone, without cortical bridging, but with

densely arranged trabecular bone within the marrow cavity in a conical, V-like shape. This formation

pattern supports the idea of a univerisal cellular mechanobiological response regardless of the location

within the body, or the presence of fixation implants. This aligns with concepts of bone resorption

being caused by either disuse or stress-shielding, where the cells respond to the loads they experience

depending on their mechanical state, and not of the cause of the change. Further, the axial mechanical

stiffness over the four weeks, as assessed with FE, did not recover to its pre-defect strength,

suggesting that healing would continue into the future. The model was newly developed, and the level

of impairment over longer time periods would require further characterization of the model. As this

study duration was only four weeks, it is unclear whether (re)modelling would eventually result in a

structure similar to the native vertebra over time, or even have healed completely given more time.

Regardless, bone formation during early healing was related to and guided by bone strain (Fig. 5).

This applied to both the loaded and the control group, which could be exposed to physiological strain

that may peak at 4N[14]. Strain-induced bone (re)modelling principles have been previously

recognized[15,16], in which loading favors formation over resorption[17].

This principle is evident elsewhere, where in a study of mouse femoral fractures, fracture site

remodeling after three weeks has shown to be consistent with previously considered remodeling

theories[39]. However, such comparisons to other locations within the body can be confounded by non-

biomechanical factors. For example, the difference in the presence of bone marrow and stem cells,

cancellous and cortical bone ratios, and the large muscles surrounding the femur that supply blood and

cytokines. While different locations in the body have different factors that can influence healing,

similarities do exist between different bone defect models. This study developed and used a confined

partial defect model. When comparing this healing to an externally-fixated mouse femoral full

osteotomy defect model, mechanical loading from the fourth week onwards also significantly

increased BV/TV in the defect centre region. One difference though was the patterns in the BFR and

BRR once loading began[19]. Of relevance here is the phase of healing in which loading begins. In the

femoral full osteotomy model, a four week loading delay was implemented to allow for bridging

across the defect void. Thus, the inflammatory phase of healing has passed when loading begins. In

comparison, the partial vertebral defect used in this study allows for loading within the first week after

defect creation, during the early inflammatory phase of healing. When comparing healing in the

controls in the weeks following defect creation, the BFR and BRR showed similarities in responses

between both the osteotomy and partial defect models. It is clear that many confounding factors exist

when making such comparisons, including the timing of loading, the healing phase which loading

begins, the anatomical location and defect differences. Despite these differences, the bone healing

responses to loading within the defect centre and periphery were comparable between these very

different defect types. Overall, this further supports a universal relationship between bone healing and

loading in mice. Future experiments could confirm this by extending the timeline of loading past four

weeks in this vertebral model, by starting loading in later weeks, or by creating a full osteotomy

variation of this partial defect vertebral model. Comparisons to intact vertebrae also support the

relationship between healing and loading. The conditional probabilities of formation, quiescence and

resorption (Fig. 4) in this defect study correlate with prior studies of intact vertebra, where

(re)modelling events have a relationship to the strain percentile, and that loading may slightly shift the

strain percentile in which formation events occur[15,25]. Considering the above studies, this rtFE study

also supports these mechanoregulation theories and further validates the principle in mouse vertebral

bone defect healing as well.

Over 80% of the variance (r=0.907, R^2=0.823) in BV/TV could be accounted for by change in FE-

calculated normalized stiffness, and this demonstrates the rtFE approach's ability to estimate the

loading intensity that should be applied. This provided some validation of the rtFE methods used. The

FE method, however, only accounted for purely axial compression, aligned to the principal component

of the vertebra. In reality, the vertebra was able to vibrate in different modes as it would be

constrained differently to the FE models. Therefore, it would have inevitably had some external

bending and rotational components not factored in simplified FE analyses. Despite this, the relatively

high correlation provides suitable confidence in the rtFE protocol. It kept the actual computational

processing time to around two minutes, to avoid the well-known effects of animal anesthesia and its

possibility to confound the results[40]. Additionally, this correlation is noteworthy considering a

dynamic in vivo load was simplified to a static linear simulation. Such linear simulations have

previously been reported to be appropriate[41] and capture this dynamic behavior via a static apparent

modulus[42]. Meanwhile, future improvements to computational non-linear analyses may provide future

insights[43]. Overall, while assumptions and simplifications exist, this approach was able to balance

computational accuracy and cost, and provide confirmation of the usefulness of the rtFE method.

This study did not compare subject-specific adaptive loading group to any traditional, non-adaptive,

non-subject-specific loading group. Mechanical loading is well-established to enhance bone healing,

and this has been extensively demonstrated in a variety of animal models using various loading

modalities. But many questions remain on how to implement this knowledge into practice, where

defects and their healing progression can vary widely. This study developed and implemented an

objective 3-dimensional imaging and analysis method to assess a defect and its healing, and

demonstrated how this could be linked to a known effective loading regime while reducing secondary

fracture risks (Supplementary Fig. S1). This overall approach attempts to foresee technological

progress and tools that could be more reliable than, for example, subjective grading scales of fractures

based on 2-dimensional imaging with subsequent loading based on this assigned grading scale. In this

regard, this study does not provide evidence that the complex, objective methodology presented in this

study provides improved outcomes compared to a simpler subjective analysis and/or non-adaptive

loading regime. Future studies could be designed to investigate if such a benefit truly exists between

these approaches. In principle, though, a leaning towards objective, (semi-)quantitative analyses have

historically prevailed over subjective, qualitative analyses, and this study attempts to follow this path.

As discussed, assumptions and simplifications created several limitations to this study which cover

both animal and computational aspects. For the animal aspects, the mice were relatively young, the

healing was not completed within the four weeks, and three mice were excluded which reduced study

power. Defects were created using relatively basic tools, and while this provides simplicity and an

ability to apply the model, it also introduces some variability in the defect volume across animals.

However, this is factored for in the BV/TV calculation. The pinning of the adjacent vertebra also

lacked certain control in position and angle, which creates unknowns in how the defect vertebra is

loaded, and the modes it vibrates in considering the semi-constrained nature. Future studies could be

extended past four weeks in older mice, improve the defect precision and repeatability, and increase

pinning control. As for the computational aspects, one of the greatest limitations is the simplifications

in the FE model. Firstly, the materials and models are linear elastic, which would not capture any non-

linear behaviour of vibration or visco-elastic effects. Material properties of the modelled discs were

that of bone, and all surrounding and void voxels not designated as bone were assigned a Young's

modulus of 3MPa, including what would be muscle or air. As such, both the disc and non-bone

regions are therefore stiffer than reality. Many of these computational limitations relate to the micro-

FE solver, ParOSol[44]; however, these compromises enabled the efficient use of running the FE

remotely on a supercomputer, which created the possibility for near real-time results. While

computational power is itself a limitation, future studies could explore methods to more accurately

model such a dynamic system, and further validate the simplifications and assumptions used.

To translate this approach to patients, not only would further research and development be needed, but

that technological advancements to continue. Most obviously, the computational and hardware

technology used in this study is not currently available to clinicians. Secondly, any patient-specific

solutions within the FE-realm require computational assumptions to be made, which requires further

expertise when applying case-by-case. These current limitations in translatability will likely be

overcome as technology develops, this study demonstrates the possibilities the future research can

strive towards, once technology and methods inevitably catch up for use in the larger-scales needed for

humans.

In conclusion, individualized real-time adaptive loading can be achieved through a combination of

micro-CT imaging, followed immediately by FE-solved strain distribution, and finally rescaling and

application of a cyclic loading force accordingly. Further investigation is needed to compare this to

traditional non-adaptive methods. This rtFE approach is highly relevant for clinical scenarios where

bone fractures and their healing progression are unique. This approach optimizes loading intensity,

and has the potential to reduce the risk of re-fracture or ineffective mechanical loading, thus improving

the healing of bone defects.

Materials and Methods

Study design and surgery

Approval was obtained for the animal experiments from the cantonal ethics committee from the

Kantonales Veterinäramt Zurich (Zurich, Switzerland, ZH029/18) prior to the study, and all

experiments were performed in accordance with Swiss animal welfare act and ordinance, and

ARRIVE guidelines. The study included two groups: an rtFE loading group, that were adaptively

loaded (3.2-5.5N, 10Hz, 5 minutes, 3000 cycles), and; a control group, that received sham loading

(0N) and similar handling. Groups were allocated by block randomization within a larger study, with

sample sizes estimated from previous similar research within the laboratory[15], in which 2 groups for a

repeated (4) measures ANOVA using G*Power (β=0.8, α=0.05, f =0.7, number measurements=4,

correlation=0.8) estimated a total sample size of 16 (n=8 per group). All surgical, scanning and

loading procedures were performed under isoflurane anesthesia (induction 5%, maintenance 1-2%, in

O_2). To be able to apply loading, three weeks prior to defect surgery, stainless steel pins (Fine Science

Tools, Heidelberg, Germany) were inserted in the fifth and seventh caudal vertebrae under

fluoroscopic control, as previously described (4). Perioperative analgesia (25 mg/L, Tramal®,

Gruenenthal GmbH, Aachen, Germany) was delivered via the drinking water for pre-emptive pain

relief two days prior to the defect surgery, and for three days post-surgery. All surgeries were

performed by the same surgeon. For both groups, defects of approximately 0.8mm x 1.5mm were

placed on the dorsal surface of the sixth caudal vertebrae of female fourteen-week old C57Bl/6JRj

(Janvier Labs, Saint-Berthevin, France) mice using an electric rotary drill (Micro Drill, Harvard

Apparatus, Holliston MA, United States) with 0.6mm and 0.8mm burs. This created an elongated void

running along the dorsal aspect of the vertebrae (Supplementary Fig. S3). Humane endpoints included

fracture, infection, bodyweight loss of > 15%, or inability to freely eat or drink.

Imaging and finite element methods

Vertebral defects were scanned at 10.5 µm resolution on the day of surgery, and weekly thereafter,

using an in vivo micro-CT (vivaCT 40, Scanco Medical AG, Brüttisellen, Switzerland, 55 kVp, 350

ms integration time, and 145 µA). The resulting images were used as input for the rtFE procedure for

animals in the loading group. Loading mice were kept under anesthesia during the image

reconstruction and FE calculation.

The reconstructed images were Gaussian filtered (sigma 1.2, support 1) to reduce noise, and

thresholded to assign material properties. Voxels within the threshold range from 395 mgHA/cm^3 to

745 mgHA/cm^3 were regarded as bone. This bone was assigned isotropic linear elastic material

properties with a Young's modulus between 4 GPa and 12.8 GPa, in threshold steps of 25 mgHA/cm^3,

in proportion with their density [45]. The Young's modulus of soft tissue was set to 3 MPa for values

lower than 395 mgHA/cm^3. The Poisson's ratio was set to 0.3. Vertebra geometry was aligned to the

principal axis of the coordinate system in the z-direction. To achieve an even force distribution across

the bone and to counter numerical issues with the solver, discs of 1.68 mm diameter with a Young's

modulus of 12.8 GPa were added at the distal and proximal ends of the vertebrae, similar to previously

used[17]. The outer surface of the distal disc was fixated using Dirichlet boundary conditions. The outer

surface of the proximal disc was deformed by 1% by applying a pure compressive force in the normal

(z) direction. Each model was solved using the ParOSol solver[44], running at the Swiss National

Supercomputing Centre (CSCS, Lugano, Switzerland) with 64 CPUs, taking less than 2 minutes in

computing time. Effective strain was used as the output measurement for its ability to capture

inhomogeneity in newly formed bone tissue. The dynamic character of the loading was not considered,

in alignment with previous studies reporting that static simulations capture the main features and

evolution of the mechanical environment[41], while keeping computational complexity and time down.

To calculate the rescaled force suitable for the individual defect and healing progression, strain

distributions were rescaled with a model intact vertebra with an 8N loading force used as the

reference[30]. The 93rd percentile of strain resulting from the linear elastic FE model was used to rescale

the loading force from 1% deformation to the intact reference strain level. It is accepted that the strain

window most effective for bone modeling is between 800 and 2000 micro-strain[21]. Further, bone fails

when $1 - 7\%$ of the tissue units within the volume exceed 7000 micro strain[46]. To ensure that the

strain distribution in the defect model satisfies both requirements, the 99th percentile of strain derived

from five normal intact vertebrae of mice at similar age was used as a reference, and strain distribution

in the defect vertebrae down-scaled by this factor (ratio=93rd Defect/99th Intact, Supplementary Fig.

1b). This rescaled force was individual to each mouse and adjusted after imaging (Supplementary Fig.

S3), in what is termed real-time, as the bone is relatively unchanged during this period of scanning and

computation.

Animal model and loading

The first loading was applied two days after defect surgery, and three times per week thereafter. The defect vertebra was loaded via the pins in adjacent vertebrae using an in-house cyclic loading device, at 10Hz and 3000 cycles (5 minutes), similarly to previously reported[15]. The rescaled force calculated from the rtFE pipeline was used until the following weekly scan was completed, to balance the radiation exposure from imaging and the accuracy of the rescaled force. The rescaled force corresponded to the peak-to-peak cyclic loading, with 0.5N being the base position of the lower peak to avoid any inadvertent negative loads. Control mice were handled in a similar manner, and placed in the loading device immediately after their scan for 5 minutes without any loading applied. The control mice did not undergo the wait time associated with the rtFE computation.

Analysis of bone defect healing

For evaluation, two regions of interest were defined from the baseline defect scan of each animal (Fig. 1a). The defect centre (DC) included the bony surface surrounding the defect (1 layer of voxels) as well as the space inside the defect. Region of interest determination was automated using a Hough transformation feature extraction technique by overfitting a cylinder to the medullary cavity and subsequently excluding any volume considered as existing bone within the created DC region. The defect periphery (DP) covered the remaining bone volume up to the start of the growth plates, as well as a dilated offset of 10 voxels to capture bone formation outside of the baseline cortical bone (Fig. 1a).

Bone volume fraction (BV/TV) was calculated in the DC (BV_{DC}/TV_{DC}) and in the DP (BV_{DP}/TV_{DP}) and normalized to their initial total volumes per region and per animal to calculate percentages[47]. Dynamic bone morphometric parameters were calculated in the DC and DP regions by registering binary micro-CT images acquired at consecutive weeks which were overlaid to compute regions of

formation (F), quiescence (Q) and resorption (R) that could be analyzed morphometrically to yield

bone formation rate (BFR) and bone resorption rate (BRR)[16,17] in the DC (BFR_{DC} and BRR_{DC}) and in

the DP (BFR_{DP} and BRR_{DP}), which is normalized to the respective initial volume, to calculate

percentages per week, as shown previously[48].

After registration, images were gauss-filtered ($\sigma = 1.2$, support 1) and thresholded to a binary image at

395mgHA/cm3 (corresponding to 4 GPa). Effective strain relevant to the (re)modelling events on the

bone surface was estimated using FE analysis as per the rtFE solving pipeline. By combing surface

(re)modelling events with corresponding surface effective strains, correlations and conditional

probabilities could be investigated in the DC and DP, similarly to previously reported[15].

Linear mixed-effects modelling was used for the statistical analysis (SPSS 24.0.0.0). Fixed-effects

were allocated to: the time; and treatment. Random-effects were allocated to: the animal, to account

for the natural differences in healing between different mice; and the animals' specific defect volumes.

Assumptions were tested by analyzing the residuals of the fitted model. Post-hoc tests with multiple

pairwise comparisons were corrected with Bonferroni criteria. Data is reported as mean (±SD), unless

otherwise stated. Reporting of statistics follows guidelines from the Publication Manual of the

American Psychological Association (APA). A p-value of $p < 0.05$ was considered statistically

significant unless reported otherwise.

Data availability

All necessary data generated or analyzed during the present study are included in this published article

and its Supplementary Information files (preprint available on bioRxiv 2020.09.13.295402; doi:

https://doi.org/10.1101/2020.09.13.295402). Additional information related to this paper may be

requested from the authors.

References

1. Myeroff, C. & Archdeacon, M. Autogenous bone graft: Donor sites and techniques. *Journal of Bone and Joint Surgery - Series A* (2011) doi:10.2106/JBJS.J.01513.

2. Goodship, A. E. & Kenwright, J. The influence of induced micromovement upon the healing of experimental tibial fractures. *J. Bone Joint Surg. Br.* **67**, 650–5 (1985).

3. Schell, H. *et al.* The course of bone healing is influenced by the initial shear fixation stability. *J. Orthop. Res.* (2005) doi:10.1016/j.orthres.2005.03.005.

4. Epari, D. R., Kassi, J. P., Schell, H. & Duda, G. N. Timely fracture-healing requires optimization of axial fixation stability. *J. Bone Jt. Surg. - Ser. A* (2007) doi:10.2106/JBJS.F.00247.

5. Betts, D. C. & Müller, R. Mechanical regulation of bone regeneration: Theories, models, and experiments. *Frontiers in Endocrinology* (2014) doi:10.3389/fendo.2014.00211.

6. Meakin, L. B., Price, J. S. & Lanyon, L. E. The contribution of experimental in vivo models to understanding the mechanisms of adaptation to mechanical loading in bone. *Frontiers in Endocrinology* (2014) doi:10.3389/fendo.2014.00154.

7. Warden, S. J. & Turner, C. H. Mechanotransduction in the cortical bone is most efficient at loading frequencies of 5-10 Hz. *Bone* (2004) doi:10.1016/j.bone.2003.11.011.

8. Yang, H., Embry, R. E. & Main, R. P. Effects of loading duration and short rest insertion on cancellous and cortical bone adaptation in the mouse tibia. *PLoS One* (2017) doi:10.1371/journal.pone.0169519.

9. Salisbury Palomares, K. T. *et al.* Mechanical stimulation alters tissue differentiation and molecular expression during bone healing. *J. Orthop. Res.* (2009) doi:10.1002/jor.20863.

10. Thompson, Z., Miclau, T., Hu, D. & Helms, J. A. A model for intramembranous ossification during fracture healing. *J. Orthop. Res.* (2002) doi:10.1016/S0736-0266(02)00017-7.

11. Augat, P., Merk, J., Wolf, S. & Claes, L. Mechanical stimulation by external application of cyclic tensile strains does not effectively enhance bone healing. *J. Orthop. Trauma* (2001) doi:10.1097/00005131-200101000-00010.

12. Claes, L. *et al.* Early dynamization by reduced fixation stiffness does not improve fracture healing in a rat femoral osteotomy model. *J. Orthop. Res.* (2009) doi:10.1002/jor.20712.

13. Claes, L. *et al.* Late Dynamization by Reduced Fixation Stiffness Enhances Fracture Healing in a Rat Femoral Osteotomy Model. *J. Orthop. Trauma* (2011) doi:10.1097/BOT.0b013e3181e3d994.

14. Christen, P., Van Rietbergen, B., Lambers, F. M., Müller, R. & Ito, K. Bone morphology allows estimation of loading history in a murine model of bone adaptation. *Biomech. Model. Mechanobiol.* (2012) doi:10.1007/s10237-011-0327-x.

15. Schulte, F. A. *et al.* Local Mechanical Stimuli Regulate Bone Formation and Resorption in Mice at the Tissue Level. *PLoS One* (2013) doi:10.1371/journal.pone.0062172.

16. Schulte, F. A., Lambers, F. M., Kuhn, G. & Müller, R. In vivo micro-computed tomography allows direct three-dimensional quantification of both bone formation and bone resorption parameters using time-lapsed imaging. *Bone* (2011) doi:10.1016/j.bone.2010.10.007.

17. Lambers, F. M., Schulte, F. A., Kuhn, G., Webster, D. J. & Müller, R. Mouse tail vertebrae adapt to cyclic mechanical loading by increasing bone formation rate and decreasing bone resorption rate as shown by time-lapsed in vivo imaging of dynamic bone morphometry. *Bone* (2011) doi:10.1016/j.bone.2011.08.035.

18. Christen, P. & Müller, R. In vivo Visualisation and Quantification of Bone Resorption and Bone Formation from Time-Lapse Imaging. *Current Osteoporosis Reports* (2017) doi:10.1007/s11914-017-0372-1.

19. Wehrle, E., Paul, G. R., né Betts, D. C. T., Kuhn, G. A. & Müller, R. Individualized cyclic mechanical loading improves callus properties during the remodelling phase of fracture healing in mice as assessed from time-lapsed in vivo imaging. *bioRxiv* 2020.09.15.297861 (2020) doi:10.1101/2020.09.15.297861.

20. Paul, G. R., Wehrle, E., Tourolle, D. C., Kuhn, G. A. & Müller, R. Reducing variance in a mouse defect healing model: Real-time Finite Element Analysis allows homogenization of tissue scale strains. *bioRxiv* 2020.09.02.274878 (2020) doi:10.1101/2020.09.02.274878.

21. Frost, H. M. A determinant of bone architecture. The minimum effective strain. *Clin. Orthop. Relat. Res.* (1983) doi:10.1097/00003086-198305000-00047.

22. Webster, D. J., Morley, P. L., van Lenthe, H. H. & Müller, R. A novel in vivo mouse model for mechanically stimulated bone adaptation - A combined experimental and computational validation study. *Comput. Methods Biomech. Biomed. Engin.* (2008) doi:10.1080/10255840802078014.

23. Webster, D. *et al.* Mechanical loading of mouse caudal vertebrae increases trabecular and cortical bone mass-dependence on dose and genotype. *Biomech. Model. Mechanobiol.* (2010) doi:10.1007/s10237-010-0210-1.

24. Webster, D., Wirth, A., Van Lenthe, G. H. & Müller, R. Experimental and finite element analysis of the mouse caudal vertebrae loading model: Prediction of cortical and trabecular bone adaptation. *Biomech. Model. Mechanobiol.* (2012) doi:10.1007/s10237-011-0305-3.

25. Scheuren, A. C. *et al.* Mechano-regulation of bone adaptation is controlled by the local in vivo environment and logarithmically dependent on loading frequency. *bioRxiv* 2020.05.15.097998 (2020) doi:10.1101/2020.05.15.097998.

26. Harris, J. S., Bemenderfer, T. B., Wessel, A. R. & Kacena, M. A. A review of mouse critical size defect models in weight bearing bones. *Bone* (2013) doi:10.1016/j.bone.2013.02.002.

27. Speirs, A. D., Heller, M. O., Duda, G. N. & Taylor, W. R. Physiologically based boundary conditions in finite element modelling. *J. Biomech.* (2007) doi:10.1016/j.jbiomech.2006.10.038.

28. Wehrle, E. *et al.* Evaluation of longitudinal time-lapsed in vivo micro-CT for monitoring fracture healing in mouse femur defect models. *Sci. Rep.* (2019) doi:10.1038/s41598-019-53822-x.

29. Tourolle né Betts, D. C. *et al.* The association between mineralised tissue formation and the mechanical local in vivo environment: Time-lapsed quantification of a mouse defect healing model. *Sci. Rep.* **10**, 1–10 (2020).

30. Lambers, F. M. *et al.* Bone adaptation to cyclic loading in murine caudal vertebrae is maintained with age and directly correlated to the local micromechanical environment. *J. Biomech.* (2015) doi:10.1016/j.jbiomech.2014.11.020.

31. Christen, P. *et al.* Bone remodelling in humans is load-driven but not lazy. *Nat. Commun.* (2014) doi:10.1038/ncomms5855.

32. Glatt, V., Bartnikowski, N., Quirk, N., Schuetz, M. & Evans, C. Reverse dynamization influence of fixator stiffness on the mode and efficiency of large-bone-defect healing at different doses of rhBMP-2. *J. Bone Jt. Surg. - Am. Vol.* (2016) doi:10.2106/JBJS.15.01027.

33. Main, R. P., Lynch, M. E. & Van Der Meulen, M. C. H. Load-induced changes in bone stiffness and cancellous and cortical bone mass following tibial compression diminish with age

560  in female mice. *J. Exp. Biol.* (2014) doi:10.1242/jeb.085522.

561 34. Vetsch, J. R., Betts, D. C., Müller, R. & Hofmann, S. Flow velocity-driven differentiation of
562  human mesenchymal stromal cells in silk fibroin scaffolds: A combined experimental and
563  computational approach. *PLoS One* (2017) doi:10.1371/journal.pone.0180781.

564 35. Glatt, V., Evans, C. H. & Tetsworth, K. A concert between biology and biomechanics: The
565  influence of the mechanical environment on bone healing. *Frontiers in Physiology* (2017)
566  doi:10.3389/fphys.2016.00678.

567 36. Paul, G. R., Malhotra, A. & Müller, R. Mechanical Stimuli in the Local In Vivo Environment
568  in Bone: Computational Approaches Linking Organ-Scale Loads to Cellular Signals. *Current
569  Osteoporosis Reports* (2018) doi:10.1007/s11914-018-0448-6.

570 37. Hausherr, T. C. *et al.* Effect of temporal onsets of mechanical loading on bone formation inside
571  a tissue engineering scaffold combined with cell therapy. *Bone Reports* (2018)
572  doi:10.1016/j.bonr.2018.04.008.

573 38. Witt, F., Duda, G. N., Bergmann, C. & Petersen, A. Cyclic mechanical loading enables solute
574  transport and oxygen supply in bone healing: An in vitro investigation. *Tissue Eng. - Part A*
575  (2014) doi:10.1089/ten.tea.2012.0678.

576 39. Isaksson, H. *et al.* Remodeling of fracture callus in mice is consistent with mechanical loading
577  and bone remodeling theory. *J. Orthop. Res.* (2009) doi:10.1002/jor.20725.

578 40. Balcombe, J. P., Barnard, N. D. & Sandusky, C. Laboratory routines cause animal stress.
579  *Contemp. Top. Lab. Anim. Sci.* (2004).

580 41. Huiskes, R., Rulmerman, R., Van Lenthe, G. H. & Janssen, J. D. Effects of mechanical forces
581  on maintenance and adaptation of form in trabecular bone. *Nature* (2000)
582  doi:10.1038/35015116.

583 42. Sarver, J. J. & Elliott, D. M. Mechanical differences between lumbar and tail discs in the
584  mouse. *J. Orthop. Res.* (2005) doi:10.1016/j.orthres.2004.04.010.

585 43. Sas, A., Ohs, N., Tanck, E. & van Lenthe, G. H. Nonlinear voxel-based finite element model
586  for strength assessment of healthy and metastatic proximal femurs. *Bone Reports* (2020)
587  doi:10.1016/j.bonr.2020.100263.

588 44. Flaig, C. A highly scalable memory efficient multigrid solver for μ-finite element analyses.
589  (2012). doi:10.3929/ethz-a-007613965.

590 45. Mulder, L., Koolstra, J. H., den Toonder, J. M. J. & van Eijden, T. M. G. J. Intratrabecular
591  distribution of tissue stiffness and mineralization in developing trabecular bone. *Bone* **41**, 256–
592  265 (2007).

593 46. Pistoia, W. *et al.* Estimation of distal radius failure load with micro-finite element analysis
594  models based on three-dimensional peripheral quantitative computed tomography images. *Bone*
595  (2002) doi:10.1016/S8756-3282(02)00736-6.

596 47. Bouxsein, M. L. *et al.* Guidelines for assessment of bone microstructure in rodents using
597  micro-computed tomography. *J. Bone Miner. Res.* **25**, 1468–1486 (2010).

598 48. Tourolle né Betts, D. C. *et al.* The association between mineralised tissue formation and the
599  mechanical local in vivo environment: Time-lapsed quantification of a mouse defect healing
600  model. *Sci. Rep.* (2020) doi:10.1038/s41598-020-57461-5.

Acknowledgements

The authors thank Nicholas Ohs, Duncan C. Tourolle for computational assistance, Ariane C. Scheuren, Charlotte Roth for animal assistance, and the Swiss National Supercomputing Centre (CSCS) for computational time. The authors thank Dr. Dr. Esther Wehrle for serving as deputy animal study director for this project providing advice on study design, surgery training, and veterinary support druing the animal experiments. AM is also grateful for the funding from the William Harvey International Translational Research Academy (WHRI-Academy, PCOFUND-GA-2013-608765), and the European Commission under the Marie Curie Co-funding of Regional, National and International Programmes (COFUND). The research leading to these results has received funding from the People's Program (Marie Curie Actions) of the European Union's Seventh Framework Programme (FP7/2007-2013) under REA grant agreement number 608765 This project also has received funding from the European Research Council (ERC) under the FP7/2007-2013, entitled Advanced MechAGE, ERC-2016-ADG-741883.

Author Information

Affiliation

Institute for Biomechanics, ETH Zurich, Zurich, Switzerland.

Angad Malhotra, Matthias Walle, Graeme R. Paul, Gisela A. Kuhn, Ralph Müller.

Contributions

The study was designed by AM, GAK, and RM. The computational rtFE aspects were developed by AM, MW, and GRP, and performed remotely by MW. The animal experimental aspects were developed and performed by AM and GAK. Statistical and data analyses were performed by AM and MW. The manuscript was prepared by AM, and all authors reviewed and approved the final manuscript.

Additional Information

Competing interests statement

The authors declare no competing interests.

Figure Legends

Figure 1. Time lapsed imaging and overlay of formation and resorption on a weekly basis. (a) Time lapsed images of representative animals from both groups. **(b)** Weekly overlays show formation and resorption patterns from 1 to 4 weeks post-surgery. Bone formed within the defect without cortical bridging. Red/yellow: bone volume formed at week 1, 2, 3, and 4. Blue/purple: bone volume resorbed at week 1, 2, 3, and 4.

Figure 2. Longitudinal changes in bone volume fraction. (a) The vertebrae were divided into a defect centre (DC) and defect periphery (DP). **(b)** BV/TV within the DCsignificantly increased with the rtFE loading from week 2 compared to controls. **(c)** BV/TV within DP was also found to be influenced, but not to the same magnitude or extent as the DC.

Figure 3. Longitudinal changes in formation and resorption volume fractions. (a) Loading influenced the BFR/DC compared to controls, and reached significance at postoperative weeks 2 and 4, while loading did not appear to influence BRR/DC compared to controls. **(b)** Loading did not significantly influence either BFR/DP or BRR/DP compared to controls, at any time interval.

Figure 4. Conditional probabilities of formation and resorption events within the combined DC and DP regions. Effective strain as a ratio of the maximum effective strain value (EFF/EFF$_{MAX}$)). **(a)** Higher ratios of EFF/EFF$_{MAX}$ led to formation activity in treatment groups, and lower ratios led to resorption activity, regardless whether externally loaded in the treatment group, or in **(b)** control animals with an assumed axial strain.

Figure 5. Representative sample depicting formation and resorption relationship with effective strain. Regions of higher effective strain tended to formation, while lower effective strain tended to resorption.