1   Running head: Brain-Environment Alignment

3   Brain-Environment Alignment during Movie Watching Predicts Cognitive-Affective

4   Function in Adulthood

5   Raluca Petrican, Kim S. Graham and Andrew D. Lawrence

Cardiff University Brain Research Imaging Centre (CUBRIC), School of Psychology, Cardiff

University, Maindy Road, Cardiff, CF24 4HQ, United Kingdom. Corresponding author:

petricanr@cardiff.ac.uk (R.P.)

Conflict of interest. The authors declare no competing interests.

Acknowledgments. K.S.G. and A.D.L. were funded by grants from the Medical Research

Council (MR/N01233X/1) and a Wellcome Trust Strategic Award (104943/Z/14/Z). Data were

provided by the Cambridge Centre for Ageing and Neuroscience (Principal Investigator:

Lorraine K. Tyler; funders: the Biotechnology and Biological Sciences Research Council, the

Medical Research Council Cognition & Brain Sciences Unit and the European Union Horizon

2020 LifeBrain project) and the Human Connectome Project, WU-Minn Consortium (Principal

Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657; funders: the 16 NIH

Institutes and Centers that support the NIH Blueprint for Neuroscience Research and the

McDonnell Center for Systems Neuroscience at Washington University).

23   Abstract

BOLD fMRI studies have provided compelling evidence that the human brain demonstrates

substantial moment-to-moment fluctuations in both activity and functional connectivity patterns.

While the role of brain signal variability in fostering cognitive adaptation to ongoing

environmental demands is well-documented, the relevance of moment-to-moment changes in

functional brain architecture is still debated. To probe the role of architectural variability in

naturalistic information processing, we used neuroimaging and behavioural data collected during

movie watching by the Cambridge Centre for Ageing and Neuroscience (N = 642, 326 women)

and the Human Connectome Project (N = 176, 106 women). Both moment-to-moment and

contextual change-evoked architectural variability increased from young to older adulthood.

However, coupling between moment-to-moment changes in functional brain architecture and

concrete environmental features was stronger at younger ages. Architectural variability (both

momentary and context-evoked) was associated with age-distinct profiles of network

communication, specifically, greater functional integration of the default mode network in older

adulthood, but greater informational flow across neural networks implicated in environmentally

driven attention and control (cingulo-opercular, salience, ventral attention) in younger adulthood.

Whole-brain communication pathways anchored in default mode regions relevant to episodic and

semantic context creation (i.e., angular and middle temporal gyri) contributed to greater brain

reconfiguration in response to narrative context changes, as well as stronger coupling between

moment-to-moment changes in functional brain architecture and changes in concrete

environmental features. Cognitive adaptation was directly linked to levels of brain-environment

alignment, but only indirectly associated with levels of architectural variability. Specifically,

stronger coupling between moment-to-moment variability in brain architecture and concrete

environmental features predicted poorer cognitive adaptation (i.e., fluid IQ) and greater

affectively driven environmental vigilance. Complementarily, across the adult lifespan, higher

fluid (but not crystallized) IQ was related to stronger expression of the network communication

profile underlying momentary and context-based architectural variability during youth. Our

results indicate that the adaptiveness of dynamic brain reconfiguration during naturalistic

information processing changes across the lifespan due to the associated network communication

profiles. Moreover, our findings on brain-environment alignment complement the existing

literature on the beneficial consequences of modulating brain signal variability in response to

environmental complexity. Specifically, they imply that coupling between moment-to-moment

variability in functional brain architecture and concrete environmental features may index a bias

towards perceptually-bound, rather than conceptual processing, which hinders affective

functioning and strategic engagement with the external environment.

Keywords: Event Cognition, Functional Networks, Dynamic Connectivity, Fluid Intelligence,

Ageing, Anxiety

Brain-Environment Alignment during Movie Watching Predicts Cognitive-Affective Function in

63   Adulthood

BOLD fMRI studies testify to the importance of acknowledging the highly dynamic

nature of the human brain in order to better understand its lifespan developmental trajectory

(Garrett et al., 2015, 2017, 2020; Grady & Garrett, 2014; Poldrack & Shine, 2018). A substantial

portion of this research has focused on moment-to-moment brain signal variability and provided

compelling evidence that its flexible modulation based on current task requirements (e.g.,

external vs. internal attentional focus, difficulty level) is key to optimal functioning (Garrett et

al., 2020; Grady & Garrett, 2018; Roberts, Grady, & Addis, 2020). Conversely, age-related

cognitive deficits are thought to stem from age-related decay in the ability to adjust brain signal

variability in response to ongoing demands (Garrett, Kovacevic, McIntosh, & Grady, 2013a). A

consensus emerging from this literature is that brain signal variability is likely to provide the

basis for neural flexibility, underpinning the capacity of a brain to tune into the dynamics of the

external world and respond in a differentiated manner to a wide range of environmental stimuli

(Garrett et al., 2020; Grady & Garrett, 2018; Padmanabhan & Urban, 2010).

Importantly, the human brain demonstrates substantial moment-to-moment fluctuations

not only in activity, but also in functional connectivity patterns (Poldrack & Shine, 2018) .

However, the relevance of architectural variability is still debated, with some studies

underscoring its role in maturation and learning, whereas others point to its association with

accelerated cognitive ageing in later life (Bassett et al., 2011, 2013; Hutchison & Morton, 2015;

Mujica-Parodi et al., 2020).

Here, we seek to probe this issue further by testing whether, similar to signal variability,

fluctuations in functional neural architecture can facilitate alignment of brain-environment

dynamics and, thus, contribute to flexible responding to the external world. To this end, we

estimate patterns of whole-brain functional reconfiguration during movie watching, a dynamic

cognition paradigm well-suited for characterising individual and ageing-related differences in

real-life information processing (Bottenhorn et al., 2019; Demirtas et al., 2019; Geerligs, Cam-

Can, & Campbell, 2018; Simony et al., 2016; Sonkusare, Breakspear, & Guo, 2019). We thus

capitalise on evidence that the human mind readily breaks down the continuous influx of

environmental information into meaningful units, which it uses to predict and encode ongoing

experiences (Baldwin & Kosie, 2020; Kurby & Zacks, 2008). Such segmentation processes

unfold at multiple timescales and give rise to a nested event hierarchy, which spans relatively

frequent and readily processed low-level featural fluctuations (e.g., object presence/absence) to

more sporadic and abstract, slower processed, high-level changes to the "working event model"

underlying an ongoing experience (Baldassano et al., 2018; Zacks, 2020).

Applying insights from the literature on brain signal variability, here, we investigate

whether neural architectural variability associated with (1) moment-to-moment fluctuations in

concrete environmental features and (2) changes to the more abstract "working event model"

could also be a reflection of a brain's dynamic range, specifically, of its capacity to respond in a

more differentiated manner and, thus, better adapt to the external world (McDonnell & Ward,

2011). To this end, we tested whether either type of architectural variability predicts fluid

intelligence, a mental capacity reliant on well-differentiated perceptual representations of the

external world, which supports flexible updating of event representations and successful

adaptation to novel environments (Cattell, 1971; Colzato, van Wouwe, Lavender, & Hommel,

2006; Duncan, Assem, & Shashidhara, 2020; Duncan, Chylinskia, Mitchell, & Bhandaric, 2017).

To probe the specificity of any observed effects, we included a crystallized intelligence measure,

which, as an index of accumulated knowledge, was not expected to be linked to our presumed

indices of neural flexibility (i.e., the two types of architectural variability).

Brain signal variability has been shown to decline with ageing and, thus, contribute to

some of the cognitive deficits observed in older adulthood (Garrett, Kovacevic, McIntosh, &

Grady, 2010; Garrett et al., 2020). Consequently, our second objective was to establish whether

levels of moment-to-moment and context-based architectural variability also fluctuate across the

adult lifespan and whether any such fluctuations are linked to age-related differences in fluid

intelligence. If either type of architectural variability reflects neural flexibility, then we would

expect it to decline in older adulthood, just like brain signal variability does (Garrett et al., 2010,

2013a), with its decline predicting fluid intelligence decrements. If, on the other hand, greater

functional brain reconfiguration during movie watching is an index of architectural instability

and, thus, deficient neural functioning, as it has been reported for resting state and experimental

task paradigms (cf. Mujica-Parodi et al., 2020), then we would expect it to increase with age,

with increments in variability predicting decrements in fluid intelligence.

Beyond mean variability levels, environmentally-driven modulation of brain signal

variability, presumably a more sensitive index of context-based neural differentiation, has been

uniquely linked to superior cognitive functioning (Garrett et al., 2020). Consequently, our third

objective was to probe whether strength of coupling between neural architectural changes and

changes in concrete environmental features would predict fluid intelligence beyond mean levels

of moment-to-moment architectural variability. To gauge the affective relevance of alignment in

brain organisation-concrete environment dynamics, we included depression and anxiety scales

because the two capture complementary affectively-driven biases in attention (i.e., towards

abstract, internally generated versus concrete, external information), which shape naturalistic

information processing (Belzung, Wilner, & Philippot, 2015; Brewin, Gregory, Lipton, &

Burgess, 2010; Hermans, Henckens, Joels, & Fernandez, 2014; Sherrill, Kurby, Lilly, &

Magliano, 2019; Sylverster et al., 2012). If greater coupling between changes in brain

architecture and concrete environmental features reflects stronger neural tuning to the dynamics

of the external world, then we would expect it to be positively linked to anxiety, but negatively

linked to depression (Petrican, Saverino, Rosenbaum, & Grady, 2015).

Studies on brain signal variability underscore the adaptiveness of activity fluctuations in

functionally specific regions and networks, most widely, those involved in attending to the

external world (visual, salience [SAL], dorsal attention [DAN], Garrett et al., 2020; Grady &

Garrett, 2018). Similarly, literature on adaptive architectural variability supporting learning

highlights its association with greater functional integration of systems involved in external

attention and environmentally driven control (SAL, DAN, cingulo-opercular [CON]), but weaker

integration of these systems with the network generally implicated in self-generated cognition

(default mode network, [DMN]) (Finc et al., 2020). These findings thus raise the possibility that

it may not be levels of architectural variability per se, but rather their associated network

communication profiles which determine the adaptiveness of functional brain reconfiguration

during real-life information processing. Hence, our fourth objective was to test whether moment-

to-moment and context-based architectural variability are associated with distinct patterns of

network integration across the adult lifespan and whether it is these age-distinct network profiles,

rather than variability levels, that predict fluid intelligence. With age, modulation of brain signal

variability in response to external environmental stimuli declines, while the functional

dominance of systems implicated in internal cognition increases (Garrett et al., 2013a; Grady &

Garrett, 2018; Spreng & Turner, 2019). Consequently, we anticipated that greater architectural

variability would be associated with greater informational flow (i.e., integration) over systems

involved in external processing (CON, SAL, DAN, ventral attention [VAN], perceptual systems)

at younger ages, but greater functional integration of the DMN in older adulthood. As an

exploratory analysis, we further sought to link event perception processes across multiple

timescales by characterising brain region-specific patterns of informational flow which support

brain-environment alignment with respect to both contextual and concrete featural changes.

To gauge variability in functional brain architecture, we adopted a graph theoretical

approach (see Method for details), similar to the one previously used to probe the adaptiveness of

dynamic neural reconfiguration during learning (Bassett et al., 2011, 2013). An advantage of this

approach is that architectural variability is defined at the level of the whole-brain for each

individual separately. This means that changes in specific neural connections are

"contextualized" with respect to how the remaining connections change, an aspect which we

deemed important for enhancing the sensitivity of our analyses given prior evidence of

idiosyncrasies in brain organisation (cf. Gordon et al., 2017).

The present report is structured as follows. Part 1 focuses on a healthy adult lifespan

sample from the Cambridge Centre for Ageing and Neuroscience. Its purpose is to investigate

whether (1) levels of moment-to-moment versus context-based architectural variability fluctuate

across the adult lifespan, whether (2) they are associated with age-distinct profiles of network

integration (i.e., informational flow) and whether (3) any such age differences in levels of

architectural variability or in their associated network profiles predict differences in fluid

intelligence. Part 2 is based on data from a separate sample of healthy young adult participants

in the Human Connectome Project. Its aim is two-fold. The first is to probe the cognitive (i.e.,

fluid intelligence) and affective (i.e., depression/anxiety) relevance of alignment in neural

architectural fluctuations and changes in concrete environmental features. The second is to link

event segmentation processes across multiple time scales by characterising patterns of brain

region-specific informational flow underlying dynamic brain reconfiguration in response to both

abstract contextual changes and concrete featural fluctuations.

Part 1: Cam-Can Sample

Methods

Participants. We included the largest number of participants from Stage II of the

Cambridge Ageing and Neuroscience (Cam-Can) study with available fMRI data in the movie

watching condition (N = 642, age range: 18-88 yrs [M = 54 yrs, SD = 19 yrs]).

The majority of participants (N = 589) were predominantly right-handed (handedness

measure > 0). The sample included 316 men (32 between 18 and 29, 49 between 30 and 39, 48

between 40 and 49, 48 between 50 and 59, 57 between 60 and 69 , 50 between 70 and 79, 32

between 80 and 88 years of age) and 326 women (42 between 18 and 29, 46 between 30 and 39,

57 between 40 and 49, 45 between 50 and 59, 48 between 60 and 69 , 58 between 70 and 79, 30

between 80 and 88 years of age).

All participants were cognitively healthy (MMSE > 24) and met the hearing, vision, and

English language ability criteria necessary for the completing experimental tasks (Taylor et al.,

2017). They were also screened for any neurological and serious psychiatric conditions, as well

as for physical conditions or bodily implants that may render their participation unsafe (Taylor et

al., 2017). Participants provided informed consent in accordance with the Cambridgeshire

research ethics board (Shafto et al., 2014).

Out-of-scanner measures.

Fluid intelligence. Participants completed the pen-and-paper version of the Cattell

Culture Fair Test, Scale 2 Form A (Cattell, 1971; Cattell & Cattell, 1973) in which they had to

select the correct answer from multiple alternatives and record it on an answer sheet. The test

contains four subtests with distinct non-verbal "puzzles": series completion, classification,

matrices and conditions. Unbeknownst to the participants, each subtest is timed, such that 3, 4, 3

and 2.5 minutes are allocated for subtest 1, 2, 3 and 4, respectively. Correct responses receive a

score of 1 for a maximum score of 46.

Crystallized intelligence. The proverb comprehension test was used as an index of

crystalized intelligence (Crawford & Stankov, 1996). In this task, participants provide the

meaning of three common proverbs in English, which are presented on a computer screen

(Shafto et al., 2014). Their responses are recorded digitally and scored by experimenters as

incorrect or a "don't know" response (0), partly correct but literal rather than abstract (1), or fully

correct and abstract (2). The highest possible score is 6.

In-scanner task. Participants watched a shortened version of Alfred Hitchcock's black-

and-white television drama "Bang! You're Dead" (Hitchcock, 1961; Hasson et al., 2008, 2010)

edited from 30 min to 8 min while maintaining the plot (Shafto et al., 2014). The movie was

selected to be engaging and unfamiliar to the participants.

fMRI data acquisition. Images were acquired with a 3T Siemens TIM Trio

System (32-channel coil). T1-weighted anatomical scans were acquired with a MPRAGE

sequence (TR = 2250 ms, TE = 2.99 ms, flip angle=9°, FOV = 256 mm x 240 mm x 192 mm, 1

mm isotropic voxels, GRAPPA acceleration factor = 2). Functional images were acquired with a

multi-echo EPI sequence (TR=2470 ms, [TE=9.4 ms, 21.2 ms, 33 ms, 45 ms, 57 ms], flip

angle=78°, FOV = 192 x 192 mm, 32 axial slices of 3.7 mm thickness, acquired in descending

order with 20% gap, voxel size of 3 mm × 3 mm x 4.4 mm).

fMRI data preprocessing. The main preprocessing and analysis steps for both samples

are presented in Figure 1. For the Cam-Can data, preprocessing began with the averaging of the

corresponding images from the multiple echos. We opted for a simple average, rather than a

weighted sum, in order to maximize comparability with the HCP data, which did not contain

multiple echos. We reasoned that our strategy was defensible in light of evidence that simple

averaging yields similar improvements in 3T image quality as weighted summing (Kettinger et

al., 2016; Poser, Versluis, Hoogduin, & Norris, 2006). Subsequently, we performed image

processing in SPM12 (Wellcome Department of Imaging Neuroscience, London, UK).

Specifically, we corrected for slice timing differences and rigid body motion (which included

unwarping), spatially normalized the images to the standard Montreal Neurological Institute

(MNI)-152 template, and smoothed them (full-width half-maximum, 6 mm).

Additional denoising. Because motion can significantly impact functional connectivity

measures (Power et al., 2012; Van Dijk et al., 2012), we implemented several additional

preprocessing steps to address this potential confound. First, after extracting the BOLD time

series from our regions-of-interest (ROIs, see below), but prior to computing the ROI-to-ROI

correlations, we used the Denoising step in the CONN toolbox (version 17c; Whitfield-Gabrieli

& Nieto-Castanon, 2012) to apply further physiological and rigid motion corrections.

Specifically, linear regression was used to remove from the BOLD time series of each ROI the

BOLD time series of the voxels within the MNI-152 white matter and CSF masks, respectively

(i.e., the default CONN option of five CompCor-extracted principal components for each,

Behzadi, Restom, Liau, & Liu, 2007), the 6 realignment parameters, their first-order temporal

derivatives and their associated quadratic terms (24 regressors in total, cf. Bolt et al., 2017). The

residual BOLD time series were bandpass filtered (0.008 Hz< f < 0.09 Hz), linearly detrended

and despiked (all three are default CONN denoising steps). Following these corrections (which

did not include global signal regression) (Murphy & Fox, 2017), an inspection of each subject's

histogram of voxel-to-voxel connectivity values revealed a normal distribution, approximately

centered around zero, which would suggest reduced contamination from physiological and

motion-related confounds (cf. Whietfield-Gabrieli & Castanon, 2012). Nonetheless, in all

hypothesis testing analyses, we controlled for the average relative (i.e., volume-to-volume)

displacement per participant, a widely used motion metric (Power et al., 2012, 2015;

Satterthwaite et al., 2013).

fMRI data analysis.

ROI time series. 229 nodes for 10 core large-scale functional brain networks (i.e.,

default-mode [DMN], frontoparietal [FPC], cingulo-opercular [CON], salience [SAL], dorsal

attention [DAN], ventral attention [VAN], somatomotor [SM], subcortical [SUB], auditory

[AUD] and visual [VIS]) were defined for each participant as spherical ROIs (radius 5 mm)

centered on the coordinates of the regions reported in Power et al. (2011) and assigned network

labels corresponding to the graph analyses from this earlier article. We selected the Power et al.

atlas because it was created by taking into account both the task-related activation (derived meta-

analytically) and the resting state connectivity patterns of the component voxels for each ROI.

Thus, this atlas provided an optimal parcellation scheme for charactering functional brain

reorganization during a naturalistic cognition condition that, due to the lack of an explicit task,

was likely to share significant similarities with a resting state condition (Vanderwal et al., 2017).

The ROIs were created in FSL (Smith et al., 2004), using its standard 2 mm isotropic

space, with each ROI containing 81 voxels. These template space dimensions were selected

because they yielded the most adequate spatial representation of the Power atlas. The 229 ROIs

represent a subset of the 264 putative functional areas proposed by Power et al. (2011). The 229

ROIs were selected because, based on Power et al.'s analyses, they showed relatively

unambiguous membership to one of the ten large-scale functional networks outlined above.

Fit of the Power atlas to the present dataset. To evaluate the homogeneity of the Power

ROIs across the Cam-Can adult lifespan sample (cf. Iraji et al., 2020), we used an approach that

is conceptually similar to those recently used in the literature (Gordon et al., 2016; Siegel et al.,

2016). Specifically, we used the CONN toolbox to compute the radial similarity contrast (RSC)

for each voxel in the Power atlas. As implemented in CONN, the RSC reflects the amount of

similarity in whole brain connectivity patterns between a voxel and its neighbours in each of the

three space directions (x,y,z), and is thus a 3 dimensional construct (see also Kim et al., 2010). If

a node is functionally homogenous, then the RSC of its voxels should be relatively similar (i.e.,

across the entire ROI, there should be a consistent degree of similarity among the component

voxels' whole brain connectivity patterns). To test this hypothesis, for each participant, we

conducted a principal components analysis of the RSC of the 81 voxels within each ROI (i.e., for

each participant, one ROI constituted one case, whereas the RSC of one voxel within a given

ROI constituted a variable). As a measure of similarity among the RSC of all voxels within a

node across all nodes, we took the percent of variance explained by the first component extracted

through the analysis just described (see also Gordon et al., 2016; Siegel et al., 2016). Because,

as previously mentioned, RSC is a three-dimensional vector, this set of analyses yielded, for each

participant, three indices of average similarity in global functional connectivity patterns among

all voxels within a given ROI. The three indices were significantly positively correlated across

participants (Spearman's *rho*s from .17 to .24, all ps < .0001), which is why we averaged them to

create a summary measure of ROI functional homogeneity. A correlational analysis, based on

100,000 permutation samples, revealed a modest, but significant negative relationship between

age and the average similarity in global functional connectivity patterns among the component

voxels of the Power ROIs (Spearman's *rho* of -.21, $p = 10^{-5}$). As expected, given that the Power

ROIs were validated on a sample corresponding in age to the first decade of the Cam-Can

sample, a second robust regression analysis revealed no evidence of significant quadratic age

effects on the functional homogeneity of the Power ROIs ($p > 0.56$). Based on these results, the

summary measure of ROI functional homogeneity was introduced as a covariate in all hypothesis

testing analyses.

Fit of the Power network assignment to the present dataset. To estimate the fit of Power

et al.'s (2011) network assignments to the present data, we used the same algorithm utilized by

these authors for community detection, i.e., Infomap (Lancichinetti & Fortunato, 2009; Rosvall

& Berstrom, 2008). We ran our analyses using Infomap Online (D. Edler & M. Rosvall)

available at www.mapequation.org/infomap.

Following Power et al. (2011), we conducted all our community detection analyses on

group-averaged ROI-to-ROI correlation matrices. To test whether Power et al.'s (2011) network

assignments provide an equally adequate fit to the present connectivity data across the lifespan,

we first averaged the individuals' ROI-to-ROI correlation matrices, obtained from CONN,

separately within each of the seven decades. Next, we used the Brain Connectivity Toolbox

(BCT, Rubinov & Sporns, 2010) to threshold each of the seven matrices at the same tie densities

used by Power et al. (2011) for the areal graph (i.e., 2% to 10% tie density in increments of 1%).

BCT was subsequently utilized to write the thresholded matrices into a Pajek *.net format and

the resulting files were inputted into Infomap. Infomap was run with the option of extracting a

one-level structure (i.e., no nested modules), which is the format of Power et al.'s (2011) atlas as

is publicly available. Finally, we used again the BCT to compute the normalized mutual

information index (NMI; range: 1 [perfect similarity] to 0 [no similarity at all]) as a measure of

similarity between Power et al.'s network assignments and those outputted by Infomap for the

connectivity data from each of the Cam-Can's seven decades (Fornito, Zalesky & Bullmore,

2016). As can be seen in Figure 2, across all tie densities, the network structure from each of the

seven age groups exhibited equivalent levels of similarity with that proposed by Power et al.

(2011). These results thus suggest that Power et al.'s network structure provide an adequate fit to

the present connectivity data across the lifespan (i.e., the NMI values were similar to those

documented by Power et al. when comparing network structure across cohorts).

Functional connectivity analyses. Pairwise coupling among the 229 ROIs was estimated

in CONN. Pairwise correlations among all the ROIs were expressed as Fisher's z-scores.

Consistent with existing practices aimed at maximizing interpretability of results in network

neuroscience studies of individual or group differences (e.g., sex or age, Betzel et al., 2014;

Satterthwaite et al., 2015), we used both positive and negative z-scores to compute the indices of

interest for all connectivity analyses. We reasoned that such an approach would be particularly

well-justified in our present case since global signal regression, an artefact removal technique

that generates negative correlations whose interpretation is still controversial, was not part of our

preprocessing pipeline (for further discussion on the validity of the negative correlations

obtained with the CONN toolbox, see Whitfield-Gabrieli & Nieto-Castanon, 2012).

To characterize individual differences in dynamic network structure, we used a combined

window and clustering based approach (Iraji et al., 2020; Lurie et al., 2020). Thus, we broke

down the movie into partially overlapping 40 s long windows for a total of 177 windows. This

window length was selected in light of prior evidence that it both maximizes detection of

individual differences in dynamic network reconfiguration and enables identification of a stable

functional core (Leonardi & Van De Ville, 2015; Preti, Bolton, de Ville, 2017; Telesford et al.,

2016; for similar window sizes in dynamic connectivity analyses of HCP data, see also Chen et

al., 2016). Thus, pairwise coupling among the 229 ROIs was estimated in CONN using a sliding

window of 40 s in length (~ 16 volumes), with one TR (2.47 s) gap and a "hanning weighting"

(i.e., greater weight to the scans in the middle of the window relative to the ones at the periphery)

applied to all the time points within a window. The use of a hanning weighting was intended to

reduce the autocorrelation in the fMRI data series and, thus, maximize the opportunity to detect

differences in functional brain organization between adjacent windows.

Network-level analyses. All the network-level metrics were computed using the Brain

Connectivity Toolbox (BCT, Rubinov & Sporns, 2010) and the Network Community Toolbox

(Bassett, D.S. [2017, November]. Network Community Toolbox. Retrieved from

http://commdetect.weebly.com/), as described below.

Community detection. Rather than being computed directly, the degree to which a

network can be fragmented into well-delineated and non-overlapping communities or modules is

estimated using optimization algorithms, which sacrifice some degree of accuracy for processing

speed (Fornito et al., 2016; Rubinov & Sporns, 2010). Here, the optimal whole-brain division

into constituent communities was estimated using a Louvain community detection algorithm

implemented in the BCT. This algorithm partitions a network into non-overlapping groups of

nodes with the goal of maximizing an objective modularity quality function, Q (Betzel &

Bassett, 2017; Rubinov & Sporns, 2011; Sporns & Betzel, 2016). There are multiple strategies

for estimating community structure based on sliding window data, as was the case of our movie

viewing data. Specifically, multilayer modularity algorithms (Bassett et al., 2011; Braun et al.,

2015; Mucha et al., 2010) can provide important insights into community dynamics at multiple

time scales. Nonetheless, such algorithms require estimation of additional free parameters (e.g.,

the temporal coupling parameter between two adjacent temporal windows). Since we feared that

estimation of the temporal coupling parameter could act as a potential confound when comparing

connectivity results across the multiple samples included in the analysis, we used the same

procedure to estimate community structure independently in each sliding window (see also Chen

et al., 2016), as described below.

For signed networks, such as the ones investigated in our study, optimization of the Q

function can be achieved by either placing equal weight on maximizing positive within-module

connections and minimizing negative within-module connections or by putting a premium on

maximizing positive connections, which have been argued to be of greater biological

significance (Fornito et al., 2016; Rubinov & Sporns, 2011). Although we verified that all the

reported results emerge with either formula, for the sake of simplicity and because we agree with

their argument regarding the greater importance of positive weights in determining node

grouping into communities, we report here the results based on Rubinov and Sporns's modularity

formula (cf. Chen et al., 2016; Rubinov & Sporns, 2011). In this formulation, the contribution of

positive weights to Q is not affected by the presence of negative weights in the network, whereas

the contribution of negative weights to Q decreases with an increase in positive weights.

The adapted modularity function Q^*, proposed by Rubinov and Sporns (2011) is written

as

$Q^* = \frac{1}{v^+} \sum_{ij}(w^+_{ij} - \gamma e^+_{ij})\delta_{M_i M_j} - \frac{1}{v^+ + v^-}\sum_{ij}(w_{ij}^- - \gamma e^-_{ij})\delta_{M_i M_j},$

where $\delta_{MiMj} = 1$ if nodes i and j are in the same module and $\delta_{MiMj} = 0$ otherwise; v^+ and v^-

constitute the sum of all positive (w^+) and all negative (w^-) weights in the network, respectively;

$w^\pm_{ij}$ represent the actual within-module positive or negative connection weights with $w^\pm \in (0,1]$;

γ is a resolution parameter determining the size of the identified modules; $e^\pm_{ij}$ is the within-

module connection strength expected by chance and defined, for each node-to-node (i,j)

connection as $e^\pm_{ij} = \frac{s_i^\pm s_j^\pm}{v^\pm}$, with $s^\pm_i$ and $s^\pm_j$ being the sum of all positive or all negative

connection weights of node i and j, respectively, while $v^\pm$ is the sum of all positive or all negative

connection weights in the network.

To account for the near degeneracy of the modularity landscape (i.e., many near-optimal

ways of partitioning a network into non-overlapping communities, Good et al., 2010) and for

changes in community structure due to variations in the estimation parameters, the community

detection algorithm was each initiated 100 times for three values of the spatial resolution

parameter, centered around the default value of 1 (cf. Betzel & Bassett, 2017; Braun et al., 2015;

Chen et al., 2016). Based on the results of these analyses, run separately for each of the three

spatial resolution values, a consensus partition (i.e., whole-brain division into constituent

communities) was estimated for each participant in each movie window (cf. Bassett et al., 2013;

Lancichinetti & Fortunato, 2012).

Functional brain reorganization: Window-to-window versus context-based. Using the

Network Community Toolbox, we estimated similarity in functional brain organization (i.e.,

community structure derived with the Louvain algorithm, as described above) between

consecutive windows based on the adjusted normalized mutual information index [AMI],

corrected for chance (Vinh, Epps, & Bailey, 2010). An index of window-to-window functional

brain reorganization was computed by subtracting from 1 the average AMI across all pairs of

temporally adjacent windows. This index combines spontaneous (i.e., stimulus-independent)

window-to-window functional reconfiguration with reconfiguration driven by low-level,

window-to-window perceptual fluctuations (e.g., presence/absence of objects, people).

Employing the event boundaries identified by independent raters in Ben-Yakov and

Henson (2018) with a keypress when they felt that "one event [meaningful unit] ended and

another began", we selected pairs of non-overlapping 40 s windows, separated by ~ 5 to 7 s,

which belonged to adjacent narrative segments (12 windows in total). Functional brain

reorganization in response to high-level narrative context boundaries was estimated by

subtracting from 1 the average AMI across all such pairs of temporally adjacent windows. This

index reflects functional reconfiguration related to event boundaries, as well as stimulus-

independent and lower-level reconfiguration indicative of featural changes (e.g.,

presence/absence of objects, people).

Network-based diversity in functional interactions. The participation coefficient

assesses the diversity of a node's intermodular connections (i.e., the extent to which a node

interacts with nodes outside its native community) (Chen et al., 2016; Rubinov & Sporns, 2010).

Here, a node's native community was the one to which it was assigned in Power et al. (2011), the

study that validated the functional atlas. It is worth pointing out that because our participation

coefficient is based on a static community structure, it is not subject to the drawbacks associated

with the participation coefficients derived from temporally varying communities (Thompson et

al., 2020).

A node's participation coefficient was based on the consensus partitions corresponding to

each of the 177 sliding windows and was given by the formula

$P_i = 1 - \sum_{m \in M} (\frac{k_i(m)}{k_i})^2$, where

P_i is the participation coefficient of node i, M is the set of communities from a given

partition (in our case, the whole-brain partition into communities, as described by Power et al.

[2011]), $k_i(m)$ corresponds to the number of times that node i and all the nodes in community m

have been assigned to the same community across all time windows, and k_i is the number of

times that node i and the remaining 228 nodes have been assigned to the same community across

all time windows. In our case, higher participation coefficients characterised nodes that tended to

show an equal number of interactions (where interaction means assignment to the same

community within a sliding window) with nodes from all the functional networks identified by

Power et al.

Brain-behavior analyses

Canonical correlation analysis (CCA). To characterize the relationship between

functional brain reorganization (i.e., changes in community structure) and network-level

diversity in functional interactions, we used canonical correlation analysis (CCA, Hotelling,

1936) with cross-validation procedures (cf. Hair et al., 2008). CCA is a multivariate technique,

which seeks maximal correlations between two sets of variables by creating linear combinations

(i.e., canonical variates) from the variables within each set. Recently, CCA has been successfully

used to investigate brain-behavior relationships in large datasets (see Smith et al., 2015;

Tsvetanov et al., 2016; Wang et al. 2020). CCA was implemented in Matlab using the canoncorr

module. In order to obtain reliable estimates of correlations between the brain or behavioral

variables and their corresponding variates, it is generally recommended that CCA be performed

on a sample size at least ten times the number of variables in the analysis (Hair, Anderson,

Tatham, & Black, 1998), a criterion which was exceeded in all analyses reported below.

The performance of our CCA-derived models was tested by using a 10-fold cross

validation procedure. Specifically, in the CCAs involving age, network participation and

functional brain reconfiguration, the data were broken down into ten folds, all but two containing

64 participants for a total of 642 participants. For the CCAs involving fluid and crystallised

intelligence, all but three of the ten folds of testing data contained 61 participants for a total of

613 participants. For both sets of CCAs, discovery analyses were conducted on nine folds of data

and the resulting CCA weights were employed to derive predicted values of the brain and

behavioral variate in the left-out ("test") fold. This procedure was repeated until each of the ten

folds served as "test" data once. The correlation between the predicted brain and behavioral

variates across all testing folds was evaluated using a permutation test with 100,000 samples (cf.

Smith et al., 2015).

To describe the relationship between the behavioral or brain variables and their

corresponding variates across all the testing folds, we include correlations between the observed

value of a brain or behavioral variable and the predicted value of its corresponding variate, as

well as standardized coefficients, analogous to multiple regression coefficients, which indicate

the unique association between the observed value of a behavioral or brain variable and the

predicted value of its corresponding variate. For each of the two sets of CCAs, when evaluating

the relationship between the predicted values of the two variates or the relationship between the

actual value of each variable and the predicted value of its corresponding variate, we controlled

for gender, handedness, subject-specific motion and subject-specific ROI functional

homogeneity (RSC). 95% confidence intervals (CI) for each correlation and standardized

regression-like coefficient were obtained by using the bootci function in Matlab (with default

settings and 100,000 bootstrap samples).

The correlation and standardized regression-like coefficients described above are

analogous to canonical loadings and canonical weights, respectively (see also Tsvetanov et al.,

2016; Vatansever et al., 2017), with the only difference being that they are computed in the test,

rather than the discovery, folds and, thus, reflect more conservative effect estimates.

Partial least squares analysis (PLS). To identify patterns of ROI community

participation that are specific to functional brain reorganization related to low-level featural

versus high-level contextual changes/narrative event boundaries, we used partial least squares

correlation often referred to as *PLS* (Krishnan et al., 2011), a multivariate technique that can

identify in an unconstrained, data-driven manner, neural patterns (i.e., latent variables or LVs)

related to individual differences variables (behavioral PLS). PLS was implemented using a series

of Matlab scripts, which are available for download at https://www.rotman-

baycrest.on.ca/index.php?section=345. In the behavioral PLS analyses we conducted, one matrix

comprised residual scores on functional brain reorganization linked to event boundaries (i.e.,

average [1- AMI] across all neighbouring windows from different narrative segments from

which age and average window-to-window functional brain reorganization were partialled out)

(PLS 1) or average window-to-window functional brain reorganization (i.e., average [1- AMI]

across all temporally adjacent windows from which age and average functional brain

reorganization linked to event boundaries were partialled out) (PLS 2), whereas the second

491 matrix contained each participant's ROI participation matrices (Krishnan et al., 2011). Each

492 matrix entry corresponded to the participation coefficient of one ROI from one subject.

493   In all the reported analyses, the significance of each LV was determined using a

494 permutation test with 100000 permutations (in the permutation test, the rows of the ROI

495 participation data are randomly reordered, Krishnan et al., 2011). In the case of our present

496 analyses, PLS assigned to each ROI a weight, which reflected the respective ROI's contribution

497 to a specific LV. The reliability of each ROI's contribution to a particular LV was tested by

498 submitting all weights to a bootstrap estimation (100000 bootstraps) of the standard errors (SEs,

499 Efron, 1981) (the bootstrap samples were obtained by sampling with replacement from the

500 participants, Krishnan et al., 2011). We opted to use 100000 permutations and 100000 bootstrap

501 samples (the same value used for the other bootstrapping and permutation-based testing herein

502 reported) in order to increase the stability of the reported results, since these parameters are

503 several orders greater than the standard ones (i.e., 500 permutations/100 bootstrap samples),

504 recommended by McIntosh and Lobaugh (2004) for use in PLS analyses of neuroimaging data.

505 A bootstrap ratio (BSR) (weight/SE) of at least 3 in absolute value was used as a threshold for

506 identifying those ROIs that made a significant contribution to the identified LVs. The BSR is

507 analogous to a z-score, so an absolute value greater than 2 is thought to make a reliable

508 contribution to the LV (Krishnan et al., 2011), although for neuroimaging data BSR absolute

509 values greater than 3 tend to be used (McIntosh & Lobaugh, 2004).

510 **Results**

511   **Window-to-window and narrative context-based brain reorganization increase with**

512 **age; neither is linked to intelligence beyond age.** We ran ten discovery CCAs to characterise

513 the relationship of window-to-window and narrative-based functional reconfiguration with age,

as well as fluid and crystallised intelligence. The discovery CCAs identified one significant

mode, which was validated across all test sets (r of .15, $p = 7 * 10^{-5}$). This mode indicated that

greater functional brain reconfiguration (i.e., reduced similarity in community structure between

temporally adjacent windows, as well as neighbouring windows from distinct narrative

segments) typifies older individuals with lower fluid intelligence scores (see Figure 3-a, d). An

inspection of the standardized coefficients revealed that the link between greater architectural

variability and intelligence is mostly due to age (i.e., older individuals tend to have lower fluid

intelligence scores relative to younger individuals, see Figure 3-b, e).

Window-to-window and narrative context-based brain reorganization are linked to

distinct patterns of network participation as a function of age. Ten discovery CCAs were

conducted to probe the relationship between diversity in the functional interactions of the ten

networks from the Power atlas (i.e., the average participation coefficient across all the ROIs

within each network) and age-linked patterns of window-to-window versus narrative context-

based brain reorganization. The discovery CCAs detected two significant modes, which were

validated across all test sets (rs of .50 and .31, respectively, both ps of 10^{-5}). The first mode

indicated that, at older ages, functional brain reorganization is associated with greater

participation of networks involved in self-guided cognition and creation of situation models

during event perception (DMN), as well as top-down control (FPC) and attention (DAN), but

reduced participation of networks implicated in environmentally driven processing (CON, AUD,

SAL and VAN, see Figure 4). The second mode suggested that, at younger ages, stronger brain

reconfiguration was linked to greater global participation, but particularly for the network

involved in environmental vigilance and control maintenance (CON, cf. Figure 5).

The network participation profile linked to brain reconfiguration at younger ages,

predicts fluid IQ independent of age and beyond levels of window-to-window /context -

based reconfiguration; neither network participation profile predicts crystallised IQ. A

robust regression analysis, conducted in Matlab with default settings (bisquare robust fitting

weight function with a tuning constant of 4.685) and using fluid IQ as the outcome, revealed its

significant positive association with the network participation profile linked to brain

reconfiguration during, younger ($b = .083$, $SE = .031$, $t(602) = 2.643$, $p =.008$), but not older ($b =$

$-.053$, $SE = .037$, $t(602) = -1.433$, $p =.153$), ages (covariates included window-to-window and

context-based brain reconfiguration, respectively, age, sex, handedness, crystallised IQ, the

summary motion metric and the summary ROI homogeneity metric) (see Figure 6). The

corresponding robust regression analysis using crystallised IQ as the outcome unveiled no

significant associations with either participation profile (both ps > .66). In neither robust

regression analysis did levels of window-to-window or context-based functional reconfiguration

made a significant contribution to either fluid or crystallised intelligence (all ps > .25).

A subset of DMN ROIs predicts reconfiguration linked to narrative context

boundaries, independent of age and window-to-window reconfiguration level. The

behavioral PLS analysis identified one ROI participation LV ($p = .0005$) which was significantly

linked to reorganization in response to movie event boundaries, independent of age and window-

to-window brain reconfiguration levels ($r = .25$, 99% CI= [.25; .45]). Ten ROIs, all but one in the

DMN, made a reliable contribution (absolute value BSR > 3) to this LV (insula, angular gyrus

[AG], middle temporal gyrus [MTG], posterior cingulate cortex [PCC], superior frontal gyrus

[SFG], dorsomedial and ventromedial prefrontal cortex [dmPFC, vmPFC], see Figure 7-a).

Subsequently, we conducted a decoding analysis in Neurosynth (Yarkoni et al., 2011),

focused on the central voxel within each of the ROIs robustly linked by PLS to brain

reconfiguration in response to event boundaries, in order to shed some light on their previously

documented functional associations. As can be seen in Figure 7-b, the analysis revealed that the

strongest z-score-based (Neurosynth z-scores > 4) associations were with "memory",

"autobiographical", "episodic", "retrieval", "mind" and "remembering". These decoding results

are compatible with the interpretation that brain sensitivity to narrative context boundaries is

uniquely associated with greater functional integration of ROIs that are relevant to the formation

of ongoing event representations and play a key role in internally guided mnemonic processes

(Honey, Newman, & Schapiro, 2017; Stawarczyk, Bezdek, & Zacks, 2019).

A subset of DMN, VIS and FPC ROIs predicts window-to-window reconfiguration,

independent of age and event boundary-based reconfiguration level. This second

behavioural PLS analysis identified one ROI participation LV ($p = .0002$) which was

significantly linked to window-to-window reorganization, independent of age and narrative

context-based brain reconfiguration levels ($r = .26$, 99% CI= [.26; .46]). Nine ROIs,

encompassing the DMN (dmPFC, SFG), VIS (fusiform gyrus [FG], inferior occipital gyrus

[IOG]), and FPC (inferior parietal lobule [IPL], medial frontal gyrus [MFG]) made a reliable

contribution (absolute value BSR > 3) to this LV (see Figure 8-a).

A decoding analysis in Neurosynth, similar to the one conducted for narrative context-

based reconfiguration, revealed that the ROIs linked to window-to-window brain reconfiguration

showed strongest functional associations with "visual", "memory", "objects", "language",

"social", "mind", and "retrieval" (see Figure 8-b). This functional web was quite distinct from

the one observed for the ROIs uniquely associated with context-based reconfiguration.

581   **Part 2: HCP Sample**

Participants. This sample included 176 unrelated participants, whose data had been

released as part of the HCP 1200 subjects data package in March 2017. This sample represented

the largest number of participants from the HCP 1200 subjects data release who were unrelated

to one another and who had available data on all the demographic, behavioral and fMRI

assessments of interest.

The majority of participants (N = 163) were right-handed. The sample included 70

younger men (21 between 22 and 25, 35 between 26 and 30, and 14 between 31 and 36 years of

age) and 106 younger women (1 between 22 and 25, 49 between 26 and 30, and 56 between 31

and 36 years of age). Although age is presented here in the range format, as advocated by the

HCP team (see Van Essen et al., 2012 for the rationale behind this age reporting strategy in HCP

data releases), all our brain-behavior analyses used participants' actual age in years, as available

in the HCP restricted data release.

All participants were screened for a history of neurological and psychiatric conditions

and use of psychotropic drugs, as well as for physical conditions or bodily implants that may

render their participation unsafe. Diagnosis with a mental health disorder and structural

abnormalities, as revealed by the MRI structural scans, were also exclusion criteria. Participants

provided informed consent in accordance with the HCP research ethics board.

Out-of-scanner measures.

Fluid IQ. Form A of an abbreviated measure of the Raven's Progressive Matrices (RPM;

Bilker et al., 2012), a non-NIH Toolbox measure, gauged participants' abstract reasoning skills

(i.e., nonverbal fluid IQ). This task features patterns made up of 2x2, 3x3 or 1x5 arrangements of

squares, with one of the squares missing. Participants must select one of five response choices

that best fits the missing square on the pattern. The task has 24 items and 3 bonus items, arranged

in order of increasing difficulty. The task is stopped though if the participant makes 5

consecutive incorrect responses. In line with existing guidelines (Bilker et al., 2012; Gray,

Chabris, & Braver, 2003; Gray et al., 2005), total number of correct responses was used as a

measure of abstract reasoning.

***Subclinical depression and anxiety*.** To assess relatively stable subclinical variations in

depression and anxiety, we used participants' scores on the DSM-oriented depression and anxiety

scales (see below for details). Both sets of scores were derived from participants' responses to

relevant items on the Achenbach Adult Self-Report (ASR) instrument for ages 18–59

(Achenbach, 2009). The ASR contains a total of 123 statements relevant to psychological

functioning and requires participants to rate on a 3-point scale (0 *not true*, 1 somewhat or

sometimes true, 2 *very true or often true*) how well each item described them over the previous

six months. The DSM-oriented depression scale includes items such as "I am unhappy, sad, or

depressed". The DSM-oriented anxiety scale includes items such as " I worry about my future".

Out-of-scanner control measures.

***Current negative emotion experience*.** Participants completed the NIH Toolbox Negative

Affect Survey, which assesses separately current levels of experienced sadness (e.g., "I felt sad.",

"I felt like a failure."), anger (e.g., "I felt angry.", "I felt bitter about things."), and fear (e.g., "I

felt frightened.', "I had a racing or pounding heart."), respectively. The measure requires

participants to rate on a 5-point scale (1 *never* to 5 *always*) how often they experienced the

relevant emotion within the past seven days. Scores on the sadness, anger and fear subscales

were averaged to create an index of current negative emotional state, which was entered as a

covariate in all the hypothesis testing analyses.

In-scanner task. Participants completed four movie viewing runs over two scanning

sessions on two separate days. Each run was about 15 minutes long and comprised 1 to 4.3

minutes long excerpts from Hollywood movies, as prepared and published by Cutting, Brunick,

and Candan (2012), and independent films, freely available under Creative Commons Licensing.

All four movie runs include a Vimeo repeat clip at the end, which was not included in the

analyses. In each run, 20 s of rest (i.e., black screen with "REST" in white text) precede the

beginning and follow the end of each movie clip.

Movie features. To quantify low-level featural fluctuations in the movie task, we used the

output of the semantic feature coding conducted by Jack Gallant's laboratory (cf. Huth,

Nishimoto, Vu, & Gallant, 2012) and available as part of the HCP1200 Subjects Data Release.

By using this semantic feature coding, we were able to characterise the extent to which window-

to-window reconfiguration in functional architecture is yoked to ongoing, meaningful

fluctuations in the external environment. Each movie frame is coded for the presence/absence

(0/1) of 859 semantic elements recorded as nouns (N = 629), verbs (N = 229) and adjective(s) (N

=1). Our analyses focused on semantic features listed as nouns, which we took to reflect

environmental attributes (e.g., presence of objects, people, buildings) and semantic features listed

as verbs, which reflected actions performed by the movie characters or natural phenomena. As

we detail below, the brain data corresponding to each movie was broken down into 40 s second

sliding windows, moved in increments of 2 s. The binary semantic feature matrices

corresponding to each sliding window from the brain data were averaged. In these averaged

matrices, the value in each cell signified the percentage of frames within a sliding window when

an entity or action was present. As in the brain data, window-to-window similarity in semantic

features was indexed with the adjusted mutual information index (AMI) (Vinh et al., 2012), with

each unique value in the averaged semantic features for each window acting as a community

label.

fMRI data acquisition. Images were acquired with a customized Siemens 3T

"Connectome Skyra" scanner housed at Washington University in St. Louis (32-channel coil).

Pulse and respiration were measured during scanning. Functional images were acquired with a

multiband EPI sequence (TR=1000 ms, TE=22.2 ms, flip angle=45°, FOV = 208 x 208 mm, 85

slices of 1.6×1.6 mm in-plane resolution, 1.6 mm thick, no gap). Two of the movie runs were

acquired with an anterior-to-posterior, while the other two with a posterior-to-anterior, phase

encoding sequence (so that phase encoding sequence effects could cancel each other out over the

all runs).

fMRI data preprocessing. The present report used the minimally preprocessed movie

watching data from the HCP 1200 subjects data release. These data have been preprocessed with

version 3 of the HCP spatial and temporal pipelines (Smith et al., 2013; for specification of

preprocessing pipeline version, see http://www.humanconnectome.org/data). Spatial

preprocessing involved removal of spatial and gradient distortions, correction for participant

movement, bias field removal, spatial normalization to the standard Montreal Neurological

Institute (MNI)-152 template (2 mm isotropic voxels), intensity normalization to a global mean

and masking out of non-brain voxels. Subsequent temporal preprocessing steps involved weak

high-pass temporal filtering with the goal of removing linear trends in the data.

Additional denoising. Because motion can significantly impact functional connectivity

measures (Power et al., 2012; Van Dijk et al., 2012), we implemented the same additional

preprocessing steps used to address this potential confound in the Cam-Can data. Specifically, in

the CONN toolbox (version 17c; Whitfield-Gabrieli & Nieto-Castanon, 2012), linear regression

was used to remove from the BOLD time series of each ROI the BOLD time series of the voxels

within the MNI-152 white matter and CSF masks, respectively (i.e., the default CONN option of

five CompCor-extracted principal components for each, Behzadi, Restom, Liau, & Liu, 2007),

the 6 realignment parameters, their first-order temporal derivatives and their associated quadratic

terms (24 regressors in total, cf. Bolt et al., 2017), as well as the main movie effects, obtained by

convolving a boxcar task design function with the hemodynamic response function, and their

first temporal order derivative (cf. Braun et al., 2015; Vatansever et al., 2015; Westphal, Wang,

& Rissman, 2017). The last denoising step was implemented in order to isolate movie-related

functional coupling from mere co-activation effects corresponding to the beginning and end of a

movie clip (i.e., two regions that are both activated at the beginning of a movie clip and de-

activated at its end, although they do not "communicate" with one another throughout the movie

clip). The residual BOLD time series were bandpass filtered (0.008 Hz< f < 0.09 Hz), linearly

detrended and despiked (all three are default CONN denoising steps). Following these

corrections (which again did not include global signal regression), an inspection of each subject's

histogram of voxel-to-voxel connectivity values revealed a normal distribution, approximately

centered around zero, which would suggest reduced contamination from physiological and

motion-related confounds (cf. Whietfield-Gabrieli & Castanon, 2012). Nonetheless, in

supplementary analyses, accompanying all the brain-behavior tests, we confirmed that all the

reported effects were not driven by individual differences in motion, as they remained unchanged

after controlling for the average relative (i.e., volume-to-volume) displacement per participant, a

widely used motion metric (Power et al., 2012, 2015; Satterthwaite et al., 2013).

fMRI data analysis.

***ROI time series*.** We followed the same steps as in the Cam-Can data in order to extract

the timeseries from 229 ROIs from the Power et al. (2011) atlas.

***Functional connectivity analyses*.** Pairwise coupling among the 229 ROIs was estimated

in CONN, separately for each of the 14 movies. Periods of rest between consecutive movie clips

were eliminated from the analyses. As in the Cam-Can data, the pairwise correlations among all

the ROIs were expressed as Fisher's z-scores, all of which (i.e., positive and negative alike) were

subsequently used to compute the indices of interest for all connectivity analyses.

To characterize individual differences in dynamic network structure, we broke down each

movie clip into partially overlapping 40 s long windows for a total of 1152 windows. Similar to

the Cam-Can analyses, pairwise coupling among the 229 ROIs was estimated in CONN using a

sliding window of 40 s in length (40 volumes) with a two-TR gap in-between windows and a

"hanning weighting" (i.e., greater weight to the scans in the middle of the window relative to the

ones at the periphery) applied to all the time points within a window.

***Network-level analyses*.** We followed the same steps as in the Cam-Can data with the

following exceptions. We only computed similarity in functional brain organization (i.e.,

community structure) between consecutive windows, since, due to the shorter duration and the

structure of the HCP movie clips, narrative event boundaries were less legible and, as such, did

not constitute a point of inquiry. Instead, to index brain sensitivity to object- versus action-

related changes, we computed the Spearman's rank correlation between window-to-window

similarity in functional brain organisation (i.e., community structure) and window-to-window

noun- versus verb-based semantic similarity. Because we were specifically interested in brain-

(noun/verb-based) movie *coupling*, overall window-to-window brain reconfiguration was

regressed out from both indices. The two residual brain-movie (noun- vs. verb-based) couplings

were used in all the reported analyses. Participation coefficients for each of the 229 ROIs were

computed as in the Cam-Can dataset.

Reliability analyses. To test whether a unitary construct can be extracted for each neural

index of interest across all 14 movies, we conducted separate reliability analyses on the 42 values

associated with each index (i.e., three values for each of the 14 movies, corresponding to the

community detection estimates obtained with a spatial resolution parameter of .95, 1, 1.05).

Since subject motion can impact such reliability estimates, we present the relevant Cronbach's

alpha values, both before and after regressing out subject level average frame-to-frame

displacement (see Preprocessing above for the additional motion effect removal procedures

already implemented). Additionally, to reflect the variables used in our analyses, for the brain-

(noun/verb-based) movie coupling, we present reliability estimates based on data from which we

regressed out both subject motion and spontaneous window-to-window functional brain

reconfiguration.

For the window-to-window brain organisation similarity index, we obtained Cronbach's

alphas of .87 and of .89 (with regression of the motion summary statistic). The brain-(noun)

movie coupling index showed Cronbach's alphas of .66 and of .68 (with regression of motion

and window-to-window brain reconfiguration). For the brain-(verb) movie coupling index, we

observed Cronbach's alphas of .65 and of .62 (with regression of motion and window-to-window

brain reconfiguration). Across all 229 ROIs, the participation coefficients showed Cronbach's

alphas between .76 and .98 (both with and without regression of the summary motion statistic).

Brain-behavior analyses

Canonical correlation analysis (CCA). We used canonical correlation analysis (CCA,

Hotelling, 1936) with cross-validation procedures (cf. Hair et al., 2008) in order to characterize

the relationships between our neural indices of interest (coupling between movie features and

functional brain reorganization; ROI-specific diversity in functional interactions), as well as

between the relevant brain (coupling between window-to-window changes in movie features and

functional brain reorganization [dissimilarity in community structure]) and behavioral (fluid IQ,

subclinical depression, subclinical anxiety) variables. Age was introduced in the CCAs in order

to probe potential developmentally specific effects (Ofen et al., 2012; Petrican & Grady, 2017).

As recommended in the literature (Hair et al., 1998), all CCAs were based on sample sizes more

than ten times the number of variables in the analysis (Hair, Anderson, Tatham, & Black, 1998).

As in the Cam-Can data, the performance of our CCA-derived models was tested by

using a 10-fold cross validation procedure. Specifically, the data were broken down into ten

folds, six of which contained 18 participants (the remaining folds contained 17 participants

each). The cross-validation procedure and relevant model descriptors were identical to those in

the Cam-Can data. In both sets of CCAs, when evaluating the relationship between the predicted

values of the two variates or the relationship between the actual value of each variable and the

predicted value of its corresponding variate, we controlled for gender, handedness, subject-

specific motion, years of education. In CCA 1 (see Figure 9) we additionally controlled for

current negative emotional experience to ensure that the observed associations are not due to

global negative mood around the time of testing.

Results

Anxious younger adults with lower fluid IQ show greater brain sensitivity to object-

based, but not action-based changes in the external environment. Ten discovery CCAs were

conducted to probe the relationship between age, fluid IQ, anxiety and depression, on one hand,

and coupling of functional brain reconfiguration with semantic feature (noun vs. verb-based)

changes across all 14 movies. The discovery CCAs detected one significant mode, which was

validated across all test sets (*r* of .20, *p* = .004). This mode indicated that greater functional brain

reconfiguration as a function of object-based, but not action-based changes, typifies anxious

younger adults with lower fluid IQ scores (see Figure 9 for the correlation [panels a, d] and the

standardized coefficients [panels b, e] of the ROI participation variables on their corresponding

canonical variate across all test CCAs, as well as the scatter plot describing the linear association

between the ROI participation variate and the brain-object-based movie coupling across all the

"test" folds [panel c]).

772   **Greater brain sensitivity to object-based environmental changes is linked to greater**

whole-brain participation of parietal and medial temporal areas involved in

autobiographical and episodic memory. We conducted ten discovery CCAs, probing the link

between brain-environment coupling based on object-based variations and participation of the

eleven ROIs uniquely linked in the Cam-Can to brain reconfiguration evoked by high-level,

narrative context changes. Because we were interested specifically in brain-environment

coupling with respect to object-related variations (due to its relevance to cognitive-affective

adaptation, as shown in the previous set of CCAs), we regressed out from the brain-index not

only global window-to-window brain reconfiguration (as in the prior analysis), but also brain-

environment coupling based on narrative action changes. Age was introduced in this analysis to

probe whether its link to brain-environment coupling is independent of the narrative ROI

participation patterns (in the Cam-Can, the ROI participation profiles were shown to contribute

to high-level context-based reconfiguration irrespective of age, but it was unclear whether the

same would be true with to lower-level featural fluctuations).

One significant mode emerged from the discovery CCAs, which was replicated across all

test sets (r of .19, p = .005). This mode indicated that stronger brain-environment coupling (with

respect to object-based fluctuations) was associated with greater participation across most of the

Cam-Can ROIs at younger ages, but particularly the medial temporal and parietal ROIs, which,

based on Neurosynth decoding, were most relevant to "memory", "autographical", "episodic"

and "retrieval" (see Figure 10 for the correlation [panel a] and the standardized coefficients

[panel b] of the ROI participation variables on their corresponding canonical variate across all

test CCAs, the scatter plot describing the linear association between the ROI participation variate

and the brain-object-based movie coupling across all the "test" folds [panel c], as well as the

results of the Neurosynth decoding analysis constrained to the ROIs that showed robust

correlations with the extracted covariate in panel [a]).

798   **Discussion**

Extending prior literature on the role of brain signal variability in fostering a more

differentiated and flexible response to the environment (e.g., Garrett et al., 2013a,b, 2015, 2020;

Grady & Garrett, 2018), we provide novel evidence that the adaptiveness of both moment-to-

moment and context-based fluctuations in whole-brain functional architecture varies across the

lifespan as a function of the underlying network communication profiles. We further demonstrate

that enhanced brain-environment alignment with respect to concrete featural fluctuations is

stronger at younger ages, but associated with adverse implications for both cognitive and

affective adaptation (i.e., fluid intelligence, depression/anxiety). Finally, we document the

network integration profiles that link functional brain reconfiguration at multiple timescales and

are, thus, likely to be key to understanding the dynamics behind typical and atypical variations in

event processing.

Using a naturalistic, dynamic cognition paradigm in an adult lifespan sample, we

demonstrate that the adaptiveness of functional brain reconfiguration hinges on the associated

patterns of whole-brain network participation. Specifically, superior cognitive adaptability (i.e.,

higher fluid intelligence, Cattell, 1971) was not linked to variability in functional neural

architecture per se, but rather to a network participation profile implicated in dynamic brain

reconfiguration in younger adulthood. This profile reflects a pattern of whole-brain functional

integration anchored in networks implicated in vigilance and control maintenance (CON), as

well as environmentally driven attention (VAN) and behavioural regulation (SAL) (see Figure 5-

a, Corbetta & Shulman, 2002; Sadaghiani & D'Esposito, 2015; Seeley et al., 2007; Sridharan,

Levitin, & Menon, 2008). These results thus dovetail nicely with findings from the literature on

brain signal variability, thereby implying that the beneficial consequences of both signal and

architectural variability are likely to involve neural tuning to the dynamics of the external world

(Garrett et al., 2013a, 2020; Grady & Garrett, 2018). Our findings are also compatible with

extant theory which suggests that flexibility in the interactions of cognitive control networks,

particularly CON, are a key contributor to fluid intelligence (Barbey, 2018; Duncan et al., 2020).

Overall, our results imply that adaptive patterns of dynamic brain reconfiguration during movie

watching are linked to greater whole-brain informational flow through a system implicated in

maintaining current task demands (i.e., CON, Dosenbach et al., 2006, 2008) and which is thus

very well-positioned to support the "working event model" of an ongoing experience

(Radvansky & Zacks, 2017).

Complementarily, the participation profile linked to variability in functional architecture

during older adulthood was typified by reduced CON, VAN, and SAL participation and, instead,

reflected most strongly the diverse interactions of the networks involved in self-guided cognition

(DMN) and top-down control (FPC), in particular, but also of those implicated in goal-directed

attention (DAN) and visual processing (Andrews-Hanna, Saxe & Yarkoni, 2014; Corbetta et al.,

2000; Spreng et al., 2010) (see Figure 4-a). Our finding that functional brain reconfiguration in

older adulthood depends on neural communication pathways grounded in the DMN and FPC

complements current theories of cognitive ageing, which posit that age-related declines in the

ability to engage strategically with the external environment in the here-and-now are

compensated by drawing on accumulated world knowledge (Spreng & Turner, 2019). This age-

related semanticisation, stemming from progressively stronger functional coupling between the

DMN and the FPC (Turner & Spreng, 2015), helps preserve task performance in contexts where

prior knowledge is relevant (Umanath & Marsh, 2014). One such context may be event

segmentation, where performance preservation with ageing may be due to increasing reliance on

semantic knowledge (rather than perceptual representations) during event perception (Radvansky

& Dijkstra 2007). This conjecture is compatible with recent findings of ageing-related activity

reductions in canonical episodic memory areas, but not schematic processing areas, in response

to narrative event boundaries observed in the Cam-Can sample, an effect that emerges despite

the lack of age-related differences in behavioural event segmentation (Reagh, Delarazan, Garber,

& Ranganath, 2020). Importantly, though, we did not find a significant association between

crystallized intelligence (i.e., semantic knowledge) and the participation profile typifying

architectural variability in older age. Hence, rather than reflecting ageing-related semanticisation,

this network profile may simply indicate ageing-related deficits in DMN disengagement, which

may underpin its greater functional integration, as observed here (Samu et al., 2017). Further

research is needed to shed light on the role of DMN during naturalistic cognition in older

adulthood.

856   Complementing findings on the adaptiveness of modulating brain signal variability based

on environmental complexity (e.g., Garrett et al., 2020), our study provided novel insights into

the adverse functional implications linked to coupling in the dynamics of whole-brain

architecture and concrete environmental features. Specifically, prior evidence indicates that

anxiety and depression are associated with divergent processing biases, which impact event

perception (Belzung et al., 2015; Brewin et al., 2010; Petrican et al., 2015; Sherrill et al., 2019).

Accordingly, we find that subclinical anxiety is linked to increased brain-environment alignment,

implying greater tuning into the dynamics of the external perceptual world (Figure 9-a, b), while

an opposite tendency, consistent with attentional disengagement from concrete environmental

dynamics in the here-and-now, is observed for subclinical depression (Figure 9-e). Brain

sensitivity to concrete featural fluctuations was also associated with poorer fluid intelligence.

This implies that environmental entrainment, a plausible marker of preferential reliance on

sensory-bound, rather than more abstract mental representations, which is linked to high levels of

both state and trait anxiety, may prevent successful strategic processing (Hermans et al., 2014;

Matthews, Yiend, & Lawrence, 2006; Sylverster et al., 2012). Importantly, these effects were

specific to brain sensitivity to object/spatial layout fluctuations and did not extend to brain

sensitivity to action-based changes, which have been found to support typical event segmentation

processes from childhood onwards (Levine, Buchsbaum, Hirsh-Pasek, & Golinkoff, 2019;

Magliano & Zacks, 2011; Swallow, Kemp, & Simsek, 2018).

Our study also contributed novel evidence on the overlapping network communication

profiles underlying brain-environment alignment with respect to both higher-level contextual and

lower-level featural fluctuations. In both cases, brain-environment coupling was associated with

greater whole-brain informational flow (i.e., participation) in a subset of canonical DMN ROIs,

including the left AG, left MTG, PCC and left SFG, the majority of which had been implicated

in event memory reactivation (Chen et al., 2017). The AG and PCC play key roles in recollection

(Ranganath & Ritchey, 2012; Ritchey & Cooper, 2020; Rugg & Vilberg, 2013) and have been

widely implicated in the integration of multimodal information at longer timescales, thereby

supporting the creation of the so-called "situation/event models"(Bonnici, Richter, Yazar, &

Simmons, 2016; Chen et al., 2016; Radvansky & Zacks, 2017; Stawarcyzk et al., 2019; Yazar,

Bergstrom, & Simmons, 2017). The left AG, in particular, plays a causal role in episodic context

creation during perception by acting as an online buffer for combining past and currently

presented information (Branzi, Pobric, Jung, & Lambon Ralph, 2019; Humphreys & Lambon

Ralph, 2015). Expanding this literature, we document the role of AG in integrating information

across the whole brain during event perception in order to align the external environmental and

internal neural dynamics. The AG seems thus to be well-placed to contribute to cognitive

adaptability (i.e., fluid IQ), together with "multiple demand" cognitive control areas (Barbey,

2018; Duncan et al., 2020) by shifting attentional focus from a featural, sensory-bound to a more

abstract processing mode in a context-specific manner.

The left MTG demonstrated a similarly robust association with functional brain

reconfiguration triggered by both high and low-level environmental changes. Like AG, this

region underpins updating of semantic features related to the present context (Branzi,

Humphreys, Hoffman, & Lambon Ralph, 2020), while uniquely partaking into the controlled

retrieval of semantic information (Hoffman, McClelland, & Lambon-Ralph, 2018). The MTG

and AG could, plausibly, make complementary contributions to context creation and updating

(Kurby & Zacks, 2008). Specifically, the AG-centered participation profile may provide the low-

level, episodic perceptual detail from which a strong sense of sensory vividness and grounding in

the here-and-now stem (Ramanan, Piguet, & Irish, 2018). Complementarily, the MTG-linked

participation profile may support continual updating of the underlying semantic structure based

on the influx of environmental information and controlled retrieval of already stored world

knowledge, thereby synching the "working event model" with the ongoing experience

(Hoffmann et al., 2018; Zacks, 2020).

Future studies are warranted to address limitations of our present research. First, use of a

larger battery of movies (as in HCP), covering diverse artistic interests and production dates,

with a strong narrative plot that allows reliable extraction of narrative event boundaries (as in

Cam-Can), is needed to characterise hierarchical event perception dynamics. Second, inclusion

of a full lifespan sample, as well as complementary cross-sectional/longitudinal designs may

elucidate the role of brain-environment entrainment during developmental stages characterised

by distinct learning needs (Baldwin & Kosie, 2020). Third, although behavioural event

segmentation is largely preserved in healthy ageing (Kurby & Zacks, 2018; Reagh et al., 2020;

Sargent et al., 2013), future studies probing the link between event segmentation performance

and its neural substrates across the lifespan would be critical in furthering our understanding of

developmental differences in information processing. Fourth, research employing alternate

methods for estimating dynamic brain reconfiguration would elucidate the boundary conditions

of the effects herein documented (Gonzalez-Castillo & Bandettini, 2018; Iraji et al., 2020).

In sum, we demonstrate that the adaptiveness of dynamic brain reconfiguration during

naturalistic event cognition varies across the lifespan based on the associated patterns of network

interaction. Specifically, similar to brain signal variability, the adaptiveness of architectural

variability seems to hinge on its relevance to enhanced processing of the external world.

Complementing the literature on environmental modulation of brain signal variability, we further

show that brain-environment alignment with respect to concrete, featural fluctuations is a

potential indicator of perceptually bound processing, which is more pronounced in younger

adulthood and carries adverse implications not only for affective adjustment, but also for

cognitive adaptation to novel environments. Finally, we characterise network communication

profiles which link event segmentation processes across multiple timescales by providing

perceptual and semantic scaffolding to context formation during perception, as well as during the

subsequent episodic retrieval of these event representations.

Materials & Correspondence. Correspondence and material requests should be addressed to

R.P. (petricanr@cardiff.ac.uk).

Data statement. The raw data are available from https://camcan-archive.mrc-

cbu.cam.ac.uk/dataaccess/ (Cam-Can) and

https://db.humanconnectome.org/app/template/Login.vm;jsessionid=90091F006B15D5FA1D1D

9C3ED2D465DD (HCP) upon completion of the relevant data use agreements.

Code availability. We used already existing code, as specified in the main text.

References

Andrews-Hanna, J.R., Smallwood, J.S., & Spreng, R.N. (2014). The default network and self-

generated thought: Component processes, dynamic control, and clinical relevance. *Annals*

of New York Academy of Sciences - Year in Cognitive Neuroscience Special Issue, 1316,

29-52.

Baldwin, D.A. & Kosie, J.E. (2020). How Does the Mind Render Streaming Experience as

Events?. *Topics in Cognitive Sciences*. doi:10.1111/tops.12502

Barbey, A.K. (2018). Network neuroscience theory of human intelligence. *Trends in Cognitive*

Sciences, *22*, 8-20.

Barch, D.M., Burgess, G.C., Harms, M.P., Petersen, S.E., Schlaggar, B.L., Corbetta, M., Glasser,

M.F., Curtiss, S., Dixit, S., Feldt, C., Nolan, D., Bryant, E., Hartley, T., Footer, O., Bjork,

J.M., Poldrack. R., Smith, S., Johansen-Berg, H., Snyder, A.Z., & Van Essen DC; for the

WU-Minn HCP Consortium (2013). Function in the human connectome: Task-fMRI and

individual differences in behavior. *NeuroImage, 80*, 169-189.

Bassett, D.S., Wymbs, N.F., Rombach, M.P., Porter, M.A., Mucha, P.J., & Grafton, S.T.

(2013). Task-based core-periphery organisation of human brain dynamics. *PLoS*

Computational Biology, 9, e1003171.

Bassett, D. S., Wymbs, N. F., Porter, M. A., Mucha, P. J., Carlson, J. M., & Grafton, S. T.

(2011). Dynamic reconfiguration of human brain networks during learning. *Proceedings*

of the National Academy of Sciences of the United States of America, 108, 7641-7646.

Belayachi, S. & Van der Linden, M. (2015) Exploring the parsing of dynamic action in checking

proneness. *Behaviour Change, 32,* 93-103.

Belzung, C., Wilner, P., & Philippot, P. (2015) Depression: from psychopathology to

pathophysiology. *Current Opinion in Neurobiology, 30,* 24-30.

Betzel, R. F., & Bassett, D. S. (2017). Multi-scale brain networks. *NeuroImage, 160*, 73-83.

Betzel, R. F., Byrge, L., He, Y., Goñi, J., Zuo, X., & Sporns, O. (2014). Changes in structural

and functional connectivity among resting-state networks across the human

lifespan. *NeuroImage, 102*, 345-357.

Betzel, R. F., Fukushima, M., He, Y., Zuo, X., & Sporns, O. (2016). Dynamic fluctuations

coincide with periods of high and low modularity in resting-state functional brain

networks. *NeuroImage, 127*, 287-297.

Bolt, T., Nomi, J. S., Rubinov, M., & Uddin, L. Q. (2017). Correspondence between evoked and

intrinsic functional brain network configurations. *Human Brain Mapping, 38*, 1992-

2007.

Bonnici, H.M., Richter, F.R., Yazar, Y., & Simons, J.S. (2016). Multimodal feature integration

in the angular gyrus during episodic and semantic retrieval. *Journal of Neuroscience, 36*,

5462–71.

Branzi, F.M., Humphreys, G.F., Hoffman, P., & Lambon Ralph, M.A. (2020) Revealing the

neural networks that extract conceptual gestalts from continuously evolving or changing

semantic contexts. *NeuroImage*. https://doi.org/10.1016/j.neuroimage.2020.116802.

Braun, U., Schäfer, A., Walter, H., Erk, S., Romanczuk-Seiferth, N., Haddad, L., . . . Bassett, D.

S. (2015). Dynamic reconfiguration of frontal brain networks during executive cognition

in humans. *PNAS Proceedings of the National Academy of Sciences of the United States*

of America, 112, 11678-11683.

Brewin, C. R., Gregory, J. D., Lipton, M., & Burgess, N. (2010). Intrusive images in

psychological disorders: Characteristics, neural mechanisms, and treatment implications.

Psychological Review, 117, 210–232.

Buckner, R. L., Krienen, F. M., Castellanos, A., Diaz, J. C., & Yeo, B. T. T. (2011). The

organization of the human cerebellum estimated by intrinsic functional

connectivity. *Journal of Neurophysiology, 106*, 2322-2345.

Cao, H., Plichta, M. M., Schäfer, A., Haddad, L., Grimm, O., Schneider, M., . . . Tost, H. (2014).

Test–retest reliability of fMRI-based graph theoretical properties during working

memory, emotion processing, and resting state. *NeuroImage, 84*, 888-900.

Cattell, R.B. (1971) *Abilities: Their structure, growth, and action*. Boston: Houghton Mifflin.

Cattell, R.B. & Cattell, H.E.P. (1973) *Measuring intelligence with the culture fair tests*.

Champaign, IL: The Institute for Personality and Ability Testing.

Chan, M., Park, D.C., Savalia, N.K., Petersen, S.E., & Wig, G.S. (2014). Decreased segregation

of brain systems across the healthy adult lifespan. *Proceedings of the National Academy

of Sciences of the United States of America, 111*, E4997–E5006.

Chang, C. & Glover, G.H. (2010). Time-frequency dynamics of resting state brain connectivity

measured with fMRI. *NeuroImage 50*, 81–98.

Chen, J., Leong, Y.C., Honey, C.J., Yong, C.H., Norman, K.A., & Hasson, U. (2017). Shared

memories reveal shared structure in neural activity across individuals. *Nature

Neuroscience, 20*, 115-130.

Chen, J., Honey, C.J., Simony, E., Arcaro, M.J., Norman, K.A., & Hasson, U. (2016). Accessing

real-life episodic information from minutes versus hours earlier modulates hippocampal

and high-order cortical dynamics. *Cerebral Cortex, 26,* 3428-3441.

Chen, T., Cai, W., Ryali, S., Supekar, K., & Menon, V. (2016). Distinct global brain dynamics

and spatiotemporal organization of the salience network. *PLoS Biology, 14*, 21.

Chiou, R., Humphreys, G. F, & Lambon Ralph, M. A. (2020) Bipartite functional fractionation

within the default network supports disparate forms of internally oriented cognition,

Cerebral Cortex. DOI: 10.1093/cercor/bhaa130

Cicchetti, D. V., & Sparrow, S. A. (1981). Developing criteria for establishing interrater

reliability of specific items: Applications to assessment of adaptive behavior. *American*

Journal of Mental Deficiency, 86, 127-137.

Colzato L.S., Wouwe N.C. van, Lavender T. & Hommel B. (2006), Intelligence and cognitive

flexibility: Fluid intelligence correlates with feature "unbinding" across perception and

action. *Psychonomic Bulletin & Review, 13*, 1043-1048.

Corbetta, M., Kincade, J. M., Ollinger, J. M., McAvoy, M. P., & Shulman, G. L. (2000).

Voluntary orienting is dissociated from target detection in human posterior parietal

cortex. *Nature Neuroscience, 3*, 292-297.

Corbetta, M. & Shulman, G.L. (2002). Control of goal-directed and stimulus-driven attention in

the brain. *Nature Reviews Neuroscience, 3*, 201–215.

Crawford, J.D. & Stankov, L. (1996). Age differences in the realism of confidence judgements:

A calibration study using tests of fluid and crystallized intelligence. *Learning and*

Individual Differences, 8, 83-103.

Cutting, J.E., Brunick, K.L., & Candan, A. (2012). Perceiving event dynamics and parsing

Hollywood films. *Journal of Experimental Psychology: Human Perception and*

Performance, 38, 1476-90.

D'Argembeau, A., & Van, d. L. (2006). Individual differences in the phenomenology of mental

time travel: The effect of vivid visual imagery and emotion regulation

strategies. *Consciousness and Cognition: An International Journal, 15*, 342-350.

Daselaar, S. M., Rice, H. J., Greenberg, D. L., Cabeza, R., LaBar, K. S., & Rubin, D. C. (2008).

The spatiotemporal dynamics of autobiographical memory: Neural correlates of recall,

emotional intensity, and reliving. *Cerebral Cortex, 18*, 217-229.

Dixon, M. L., De la Vega, A., Mills, C., Andrews-Hanna, J., Spreng, R., Cole, M. W., Christoff,

K. (2018) Heterogeneity within the frontoparietal control network and its relationship to

the default and dorsal attention networks. *Proceedings of the National Academy of*

Sciences of the United States of America, 115, E1598–E1607.

Duncan, J., Assem, M., & Shashidhara, S. (2020) Integrated intelligence from distributed brain

activity. *Trends in Cognitive Sciences.* https://doi.org/10.1016/j.tics.2020.06.012

Duncan, J., Chylinski, D., Mitchell, D.J., & Bhandari, A. (2017) Fluid intelligence and cognitive

segmentation. *Proceedings of the National Academy of Sciences of the United States of*

America, 114, 5295-5299.

Finc, K., Bonna, K., He, X., Lydon-Staley, D.M., Kuhn, S., Duch, W., & Bassett, D.S. (2020)

Dynamic reconfiguration of functional brain networks during working memory training.

Nature Communications, 11, 2435.

Fornito, A., Zalesky, A., & Bullmore, E. T. (2016). Fundamentals of Brain Network Analysis. (1

ed.) Academic Press.

Fox, M. D., Snyder, A. Z., Vincent, J. L., Corbetta, M., Van Essen, D. C., & Raichle, M. E.

(2005). The human brain is intrinsically organized into dynamic, anticorrelated functional

networks. *Proceedings of the National Academy of Sciences of the United States of*

America, 102, 9673-9678.

Freton, M., Lemogne, C., Bergouignan, L., Delaveau, P., Lehéricy, S., & Fossati, P. (2014). The

eye of the self: Precuneus volume and visual perspective during autobiographical

memory retrieval. *Brain Structure & Function, 219*, 959-968.

Garrett, D.D., Epp, S.M., Kleemeyer, M., Lindenberger, U., and Polk, T.A. (2020). Higher

performing older adults upregulate brain signal variability in response to feature-rich

sensory input. *NeuroImage, 217*, 116836.

Garrett, D.D., Kovacevic, N., McIntosh, A.R., & Grady, C.L. (2013a). The modulation of BOLD

variability between cognitive states varies by age and processing speed. *Cerebral Cortex,*

23, 684–693.

Garrett, D.D., Kovacevic, N., McIntosh, A.R., & Grady, C.L. (2011). The importance of being

variable. *Journal of Neuroscience,* 31, 4496–4503.

Garrett, D.D., Lindenberger, U., Hoge, R.D., & Gauthier, C.J. (2017). Age differences in brain

signal variability are robust to multiple vascular controls. *Scientific Reports, 7*, 10149.

Garrett, D.D., Nagel, I.E., Preuschhof, C., Burzynska, A.Z., Marchner, J., Wiegert, S.,

Jungehülsing, G., Nyberg, L., Villringer, A., Li, S-C., Heekeren, H.E., Bäckman, L., &

Lindenberger, U. (2015). Amphetamine modulates brain signal variability and working

memory in younger and older adults. *Proceedings of the National Academy of Sciences of*

the United States of America, 112, 7593-7598.

Garrett, D.D., Samanez-Larkin, G.R., MacDonald, S.W., Lindenberger, U., McIntosh, A.R., &

Grady, C.L. (2013b). Moment-to-moment brain signal variability: a next frontier in

human brain mapping? *Neuroscience and Biobehavioral Reviews, 37*, 610–624.

Geerligs, L., Cam-CAN, & Campbell, K.L. (2018) Age-related differences in information

processing during movie watching. *Neurobiology of Aging, 72*, 106-120.

Gilson, M., Deco, G., Friston, K.J., Hagmann, P., Mantini, D., Betti, V., Romani, G.L., &

Corbetta, M. (2018) Effective connectivity inferred from fMRI transition dynamics

during movie viewing points to a balanced reconfiguration of cortical interactions.

NeuroImage, 180, 534-546.

Gonzalez-Castillo, J. & Bandettini, P. A. (2018) Task-based dynamic functional connectivity:

Recent findings and open questions. *NeuroImage, 180,* 526-533.

Gordon, E.M., Laumann, T.O., Gilmore, A.W., Newbold, D.J., Greene, D.J., Berg, J.J., ... &

Dosenbach, N.U.F. (2017). Precision functional mapping of individual human brains.

Neuron, 95, 791–807.

Grady, C.L. & Garrett, D.D. (2018). Brain Signal Variability is Modulated as a Function of

Internal and External Demand in Younger and Older Adults. *NeuroImage, 169*, 510-523.

Grady, C.L. & Garrett, D.D. (2014). Understanding variability in the BOLD signal and why it

matters for aging. *Brain Imaging and Behavior, 8*, 274–283.

Gur, R.C., Ragland, J.D., Moberg, P.J., Bilker, W.B., Kohler, C., Siegel, S.J., Gur, R.E. (2001a).

Computerized neurocognitive scanning: II. The profile of schizophrenia.

Neuropsychopharmacology, 25, 777–788.

Gur, R.C., Ragland, J.D., Moberg, P.J., Turner, T.H., Bilker, W.B., Kohler, C., Siegel, S.J., &

Gur, R.E. (2001b). Computerized neurocognitive scanning: I. Methodology and

validationin healthy people. *Neuropsychopharmacology, 25,* 766–776.

Gur, R.C., Richard, J., Hughett, P., Calkins, M.E., Macy, L., Bilker, W.B., Brensinger, C., &

Gur, R.E. (2010). A cognitive neuroscience-based computerized battery for efficient

measurement of individual differences: standardization and initial construct validation.

Journal of Neuroscience Methods, 187, 254–262.

Hasson, U., Chen, J., & Honey, C.J. (2015). Hierarchical process memory: memory as an

integral component of information processing. *Trends in Cognitive Sciences, 19*, 304-

313.

Hermans, E.J., Henckens, M.J.A.G., Joëls, M., Fernández, G. (2014). Dynamic adaptation of

large-scale brain networks in response to acute stressors. *Trends in Neurosciences, 37*,

304–314.

Hitchcock, A. (1961). Bang! You're Dead Los Angeles: National Broadcasting Company

(NBC).

Hoffman, P., McClelland, J.L., Lambon Ralph, M.A. (2018). Concepts, control, and context: A

connectionist account of normal and disordered semantic cognition. *Psychological*

Review, 125, 293-328.

Honey, C.J., Newman, E.L., & Schapiro, A.C. (2017). Switching between internal and external

modes: a multi-scale learning principle. *Network Neuroscience, 1*, 339–356.

Humphreys, G.F. & Lambon Ralph, M.A. (2015). Fusion and Fission of Cognitive Functions in

the Human Parietal Cortex. *Cerebral Cortex, 25*, 3547-3560.

Iraji, A., Faghiri, A., Lewis, N., Fu, Z., Rachakonda, S. & Calhoun, V.D. (2020) Tools of the

trade: Estimating time-varying connectivity patterns from fMRI data. *Social Cognitive*

and Affective Neuroscience, nsaa114. https://doi.org/10.1093/scan/nsaa114

Irish, M., Halena, S., Kamminga, J., Tu, S., Hornberger, M., Hodges, J. (2015). Scene

construction impairments in Alzheimer's disease: A unique role for the posterior

cingulate cortex. *Cortex, 73*, 10-23.

Hair, J.F., Tatham, R.L., Anderson, R.E . & Black, W, (1998) Multivariate data analysis. (Fifth

Ed.) Prentice-Hall: London.

Hair Jr., J.F., Black, W.C., Babin, B.J. & Anderson, R.E. (2009) Multivariate Data Analysis.

(Seventh Ed.) Prentice Hall: Upper Saddle River, 761.

Hasson, U., Landesman, O., Knappmeyer, B., Vallines, I., Rubin, N., & Heeger, D.J. (2008)

Neurocinematics: The neuroscience of film. *Projections, 2*, 1–26.

Hasson, U., Malach, R., & Heeger, D.J. (2010) Reliability of cortical activity during natural

stimulation. *Trends in Cognitive Sciences, 14*, 40–48.

Hebscher, M., Levine, B., & Gilboa, A. (2018). The precuneus and hippocampus contribute to

individual differences in the unfolding of spatial representations during episodic

autobiographical memory. *Neuropsychologia, 110*, 123-133.

Hutchison, R.M. & Morton, J.B. (2015) Tracking the brain's functional coupling dynamics over

development. *Journal of Neuroscience*, *35*, 6849–6859.

Hutchison, R.M., Womelsdorf, T., Gati, J.S., Everling, S., & Menon, R.S. (2013). Resting-state

networks show dynamic functional connectivity in awake humans and anesthetized

macaques. *Human Brain Mapping, 34*, 2154–2177.

1135
Huth, A.G., Nishimoto, S., Vu, A., & Gallant, J.L. (2012). A continuous semantic space

describes the representation of thousands of object and action categories across the

human brain. *Neuron*, 76, 1210-1224.

Kashtan, N. & Alon, U. (2005) Spontaneous evolution of modularity and network motifs.

Proceedings of the National Academy of Sciences, 102, 13773–13778.

Kashtan, N., Noor, E., & Alon, U. (2007) Varying environments can speed up evolution.

Proceedings of the National Academy of Sciences, 104, 13711–13716.

Kettinger, A., Hill, C., Vidnyánszky, Z., Windischberger, C., & Nagy, Z. (2016). Investigating

the Group-Level Impact of Advanced Dual-Echo fMRI Combinations. *Frontiers in*

Neuroscience, 10: 571.

Kurby, C. A., & Zacks, J. M. (2018). Preserved neural event segmentation in healthy older

adults. *Psychology and Aging, 33*, 232.

Kurby, C.A. & Zacks, J.M. (2011). Age differences in the perception of hierarchical structure in

events. *Memory & Cognition, 39*, 75–91.

Lancichinetti, A. & Fortunato, S. (2009) Community detection algorithms: A comparative

analysis. *Physical Review E, 80*, 056117.

Laumann, T. O., Snyder, A. Z., Mitra, A., Gordon, E. M., Gratton, C., Adeyemo, B., . . .

Petersen, S. E. (2017). On the stability of BOLD fMRI correlations. *Cerebral Cortex, 27*,

4719-4732.

Lenhard, W. & Lenhard, A. (2014). Hypothesis Tests for Comparing Correlations. available:

https://www.psychometrica.de/correlation.html. Bibergau (Germany): Psychometrica.

DOI: 10.13140/RG.2.1.2954.1367

Leonardi, N., & Ville, V. D. (2015). On spurious and real fluctuations of dynamic functional

connectivity during rest. *NeuroImage, 104*, 430-436.

Levine, D., Buchsbaum, D., Hirsh-Pasek, K., & Golinkoff, R. M. (2019). Finding events in a

continuous world: A developmental account. *Developmental Psychobiology, 61*, 376-389.

Lurie, D.J., Kessler, D., Bassett, D.S., Betzel, R.F., Breakspear, M., Kheilholz, S.…& Calhoun,

V.D. (2020). Questions and controversies in the study of time-varying functional

connectivity in resting fMRI. *Network Neuroscience, 4*, 30-69.

Magliano, J.P. & Zacks, J. M. (2011). The impact of continuity editing in narrative film on event

segmentation. *Cognitive Sciences, 35,* 1489–1517.

Marusak, H. A., Calhoun, V. D., Brown, S., Crespo, L. M., Sala-Hamrick, K., Gotlib, I. H., &

Thomason, M. E. (2017). Dynamic functional connectivity of neurocognitive networks in

children. *Human Brain Mapping, 38*, 97-108.

Mathews, A. Yiend, J. & Lawrence, A.D. (2004) Individual Differences in the Modulation of

Fear-Related Brain Activation by Attentional Control. *Journal of Cognitive*

Neuroscience, 16, 1683-1694.

McDonnell, M.D. & Ward, L.M. (2011). The benefits of noise in neural systems: bridging theory

and experiment. *Nature Reviews Neuroscience, 12*, 415–426.

Murphy, K. & Fox, M.D. (2017) Towards a consensus regarding global signal regression for

resting state functional connectivity MRI. *NeuroImage, 154*, 169-173.

Ofen, N., Chai, X.J., Schuil, K.D., Whitfield-Gabrieli, S., & Gabrieli, J.D. (2012) The

development of brain systems associated with successful memory retrieval of scenes.

Journal of Neuroscience, 32, 10012–10020.

Padmanabhan, K. & Urban, N.N. (2010). Intrinsic biophysical diversity decorrelates neuronal

firing while increasing information content. *Nature Neuroscience, 13*, 1276–1282.

Petrican, R. & Grady, C.L. (2017). Contextual and developmental differences in the neural

architecture of cognitive control. *Journal of Neuroscience, 37,* 7711-7726.

Petrican, R., Saverino, C., Rosenbaum, R.S. and Grady, C. (2015). Inter-individual differences in

the experience of negative emotion predict variations in functional brain architecture.

NeuroImage, 123, 80-88.

Poldrack, R. & Shine, J.M. (2018) Principles of dynamic network reconfiguration across diverse

brain states. *NeuroImage, 180,* 396-405.

Poser, B.A., Versluis, M. J., Hoogduin, J. M., & Norris, D. G. (2006). BOLD contrast sensitivity

enhancement and artifact reduction with multiecho EPI: Parallel-acquired

inhomogeneity-desensitized fMRI. *Magnetic Resonance in Medicine, 55*, 1227–1235.

Power, J.D., Cohen, A.L., Nelson, S.M., Wig, G.S., Barnes, K.A., ...& Petersen, S. E. (2011)

Functional network organization of the human brain. *Neuron, 72*, 665–678.

Power, J.D., Barnes, K.A., Snyder, A.Z., Schlaggar, B.L., & Petersen, S.E. (2012). Spurious but

systematic correlations in functional connectivity MRI networks arise from subject

motion. *NeuroImage, 59*, 2142-2154.

Power, J. D., Schlaggar, B. L., & Petersen, S. E. (2015). Recent progress and outstanding issues

in motion correction in resting state fMRI. *NeuroImage, 105*, 536-551.

Preti, M. G., Bolton, T. A. W., & Ville, V. D. (2017). The dynamic functional connectome:

State-of-the-art and perspectives. *NeuroImage, 160*, 41-54.

Radvansky, G. A. & Dijkstra, K. (2007). Aging and situation model processing. *Psychonomic*

Bulletin Review, 14, 1027–42

Radvansky, G. A., & Zacks, J. M. (2017). Event boundaries in memory and cognition. *Current*

Opinion in Behavioral Sciences, 17, 133-140.

Ramanan, S., Piguet, O., Irish, M. (2018). Rethinking the role of the angular gyrus in

remembering the past and imagining the future: The Contextual Integration Model. *The*

Neuroscientist, 24, 342-352.

Ranganath, C. & Ritchey, M. (2012). Two cortical systems for memory-guided behaviour.

Nature Reviews Neuroscience, 13, 713-726.

Reagh, Z.M., Delarazan, A.I., Garber, A., & Ranganath, C. (2020). Aging alters neural activity at

event boundaries in the hippocampus and Posterior Medial network. *Nature*

Communications, 11, 3980.

Richter, F.R., Cooper, R.A., Bays, P.M., & Simons, J.S. (2016). Distinct neural mechanisms

underlie the success, precision, and vividness of episodic memory. *Elife*, 5.

Rissman, J., Chow, T.E., Reggente, N., Wagner, A.D. (2016). Decoding fMRI signatures of real-

world autobiographical memory retrieval. *Journal of Cognitive Neuroscience, 28*, 604–

20.

Ritchey, M. & Cooper, R. (2020) Deconstructing the Posterior Medial Episodic Network. *Trends*

in Cognitive Sciences, 24, 451 – 465.

Rosvall, M. & Bergstrom, C.T. (2008). Maps of random walks on complex networks reveal

community structure. *Proceedings of the National Academy of Sciences of the United*

States of America, 105, 1118-1123.

Rubinov, M. & Sporns O. (2010) Complex network measures of brain connectivity: uses and

interpretations. *NeuroImage, 52*,1059–1069.

Rubinov, M. & Sporns O. (2011) Weight-conserving characterization of complex functional

brain networks. *NeuroImage, 56*,2068-2079.

Rugg, M.D. & Vilberg, K.L. (2013). Brain networks underlying episodic memory retrieval.

Current Opinion in Neurobiology, 23, 255–60.

Sadaghiani, S. & D'Esposito, M. (2015) Functional characterization of the cingulo-opercular

network in the maintenance of tonic alertness. *Cerebral Cortex, 25*, 2763–2773.

Sargent, J. Q., Zacks, J. M., Hambrick, D. Z., Zacks, R. T., Kurby, C. A., Bailey, H. R., . . .

Beck, T. M. (2013). Event segmentation ability uniquely predicts event memory.

Cognition, 129, 241–255.

Satterthwaite, T.D., Wolf, D.H., Ruparel, K., Erus, G., Elliott, M.A., Eickhoff, S.B., Gennatas,

E.D., Jackson, C., Prabhakaran, K.,Smith, A., Hakonarson, H., Verma, R., Davatzikos,

C., Gur, R.E., & Gur, R.C. (2013). Heterogeneous impact of motion on fundamental

patterns of developmental changes in functional connectivity during youth. *NeuroImage,*

83, 45–57.

Satterthwaite, T. D., Wolf, D. H., Roalf, D. R., Ruparel, K., Erus, G., Vandekar, S., . . . & Gur,

R. C. (2015). Linked sex differences in cognition and functional connectivity in youth.

Cerebral Cortex, 25(9), 2383-2394.

Schultz, D. H., & Cole, M. W. (2016). Higher intelligence is associated with less task-related

brain network reconfiguration. *The Journal of Neuroscience, 36*, 8551-8561.

Shafto, M.A., Tyler, L.K., Dixon, M., Taylor, J.R., Rowe, J.B., Cusack, R., Calder, A.J.,

Marslen-Wilson, W.D., Duncan, J., Dalgleish, T., Henson, R.N., Brayne, C., Matthews,

F.E.; Cam-CAN (2014) The Cambridge Centre for Ageing and Neuroscience (Cam-

CAN) study protocol: a cross-sectional, lifespan, multidisciplinary examination of

healthy cognitive ageing. *BMC Neurology, 14*, 204.

Sherrill, A.M., Kurby, C.A., Lilly, M.M. & Magliano, J.P. (2019) The effects of state anxiety on

analogue peritraumatic encoding and event memory: Introducing the stressful event

segmentation paradigm, *Memory, 27*, 124-136,

Sherry, A., & Henson, R. K. (2005). Conducting and interpreting canonical correlation analysis

in personality research: A user-friendly primer. *Journal of Personality Assessment, 84*,

37-48.

Smith, S. M., M. Jenkinson, M.W. Woolrich, C.F. Beckmann, T.E.J. Behrens, … & P.M.

Matthews (2004). Advances in functional and structural MR image analysis and

implementation as FSL. *NeuroImage, 23*, 208-219.

Smith, S.M., Beckmann, C.F., Andersson, J., Auerbach, E.J., Bijsterbosch, J., Douaud, G., et al.

(2013). Resting-state fMRI in the Human Connectome Project. *NeuroImage, 80,* 144–

168.

Smith, S. M., Nichols, T. E., Vidaurre, D., Winkler, A. M., Behrens, T. E. J., Glasser, M. F., . . .

Miller, K. L. (2015). A positive-negative mode of population covariation links brain

connectivity, demographics and behavior. *Nature Neuroscience, 18*, 1565-1567.

Sporns, O. & Betzel, R.F. (2016). Modular brain networks. *Annual Review of Psychology, 67*,

613-640.

Spreng, R.N., Stevens, W.D., Chamberlain, J.P., Gilmore, A.W., Schacter, D.L., 2010. Default

network activity, coupled with the frontoparietal control network, supports goal-directed

cognition. *NeuroImage, 53*, 303–317.

Spreng, R.N. & Turner, G.R. (2019) The shifting architecture of cognition and brain function in

older adulthood. *Perspectives on Psychological Science, 14*, 523 –542.

Stawarcyzk, D., Bezdek, M. A., & Zacks, J. M. (2019). Event representations and predictive

processing: The role of the midline default network core. *Topics in Cognitive Science*, 1-

23.

Swallow, K.M., Kemp, J.T., & Simsek, A.C. (2018) The role of perspective in event

segmentation. *Cognition, 177*, 249-262.

Sylvester, C.M., Corbetta, M., Raichle, M.E., Rodebaugh, T.L., Schlaggar, B.L., Sheline, Y.I.,

Zorumski, C.F., & Lenze, E.J. (2012) Functional network dysfunction in anxiety and

anxiety disorders. *Trends in Neurosciences, 35*, 527-535.

Taylor, J.R., Williams, N., Cusack, R., Auer, T., Shafto, M.A., Dixon, M., Tyler, L.K., Cam-

CAN, Henson, R.N. (2017). The Cambridge Centre for Ageing and Neuroscience (Cam-

CAN) data repository: Structural and functional MRI, MEG, and cognitive data from a

cross-sectional adult lifespan sample. *NeuroImage, 144*, 262-269.

Telesford, Q. K., Lynall, M., Vettel, J., Miller, M. B., Grafton, S. T., & Bassett, D. S. (2016).

Detection of functional brain network reconfiguration during task-driven cognitive

states. *NeuroImage, 142*, 198-210.

Thakral, P.P., Madore, K.P., & Schacter, D.L. (2017). A role for the left angular gyrus in

episodic simulation and memory. *Journal of Neuroscience, 37*, 8142–9.

Thompson, W.H., Kastrati, G., Finc, K., Wright, J., Shine, J.M., & Poldrack, R.A. (2020) Time-

varying nodal measures with temporal community structure: A cautionary note to avoid

misinterpretation. *Human Brain Mapping, 41*, 2347-2356. doi: 10.1002/hbm.24950.

Tsvetanov, K. A., Henson, R. N. A., Tyler, L. K., Razi, A., Geerligs, L., Ham, T. E., & Rowe, J.

B. (2016). Extrinsic and intrinsic brain network connectivity maintains cognition across

the lifespan despite accelerated decay of regional brain activation. *The Journal of*

Neuroscience, 36, 3115-3126.

Tulving, E. (2002) Episodic memory: From mind to brain. *Annual Review of Psychology, 53,* 1-

25.

Tulving, E. (1985). Memory and consciousness. *Canadian Psychology/Psychologie*

Canadienne, 26, 1-12.

Turner, G. R., & Spreng, R. N. (2015). Prefrontal engagement and reduced default network

suppression co-occur and are dynamically coupled in older adults: The default-executive

coupling hypothesis of aging. *Journal of Cognitive Neuroscience, 27*, 2462–2476.

Umanath, S., & Marsh, E. J. (2014). Understanding how prior knowledge influences memory in

older adults. *Perspectives on Psychological Science, 9*, 408–426.

Uncapher, M.R. & Rugg, M.D. (2009). Selecting for Memory? The Influence of Selective

Attention on the Mnemonic Binding of Contextual Information. *Journal of Neuroscience,*

29, 8270-8279.

Vanderwal, T., Eilbott, J. Finn, E.S., Craddock, R.C., Turnbull, A. & Castellanos, F.X. (2017)

Individual differences in functional connectivity during naturalistic viewing conditions.

NeuroImage, 157, 521-530.

Vannucci, M., Pelagatti, C., Chiorri, C., & Mazzoni, G. (2016). Visual object imagery and

autobiographical memory: Object imagers are better at remembering their personal

past. *Memory, 24*, 455-470.

Vatansever, D., Menon, D. K., Manktelow, A. E., Sahakian, B. J., & Stamatakis, E. A. (2015).

Default mode dynamics for global functional integration. *The Journal of*

Neuroscience, 35, 15254-15262.

Vatansever, D., Bzdok, D., Wang, H., Mollo, G., Sormaz, M., Murphy, C., . . . Jefferies, E.

(2017). Varieties of semantic cognition revealed through simultaneous decomposition of

intrinsic brain connectivity and behaviour. *NeuroImage, 158*, 1-11.

Vatansever, D., Menon, D. K., & Stamatakis, E. A. (2017). Default mode contributions to

automated information processing. *PNAS Proceedings of the National Academy of*

Sciences of the United States of America, 114, 12821-12826.

Vinh, N.X, Epps, J., & Bailey, J. (2010). Information theoretic measures for clusterings

comparison: Variants, properties, normalization and correction for chance. *Journal of*

Machine Learning Research, 11, 2837-2854.

Wagner, A.D., Shannon, B.J., Kahn, I., & Buckner, R.L. (2005). Parietal lobe contributions to

episodic memory retrieval. *Trends in Cognitive Sciences, 9*, 445–53.

Wang, H.-T., Smallwood, J., Mourao-Miranda, J., Xia, C.H., Satterthwaite, T.D., Bassett, D.S.

& Bzdok, D. Finding the needle in a high-dimensional haystack: Canonical correlation

analysis for neuroscientists. *NeuroImage*, 216, 116745.

Westphal, A. J., Reggente, N., Ito, K. L., & Rissman, J. (2016). Shared and distinct contributions

of rostrolateral prefrontal cortex to analogical reasoning and episodic memory

retrieval. *Human Brain Mapping, 37*, 896-912.

Wheatley, T., Milleville, S.C., & Martin, A. (2007). Understanding animate agents: distinct roles

for the social network and mirror system. *Psychological Science, 18*, 469–474.

Wheeler, M. E., & Buckner, R. L. (2004). Functional-anatomic correlates of remembering and

knowing. *NeuroImage, 21*, 1337–1349.

Whitfield-Gabrieli, S. & Nieto-Castanon, A. (2012). CONN: a functional connectivity toolbox

for correlated and anticorrelated brain networks. *Brain Connectivity, 2*, 125-141.

Wig, G.S., Schlaggar, B.L.,Petersen,S.E. (2011). Concepts and principles in the analysis of brain

networks. *Annals of the New York Academy of Sciences,1224*, 126–146.

Xia, M., Wang, J., & He, Y. (2013) BrainNet Viewer: A Network Visualization Tool for Human

Brain Connectomics. *PLoS ONE 8*: e68910.

Yarkoni, T., Poldrack, R. A., Nichols, T. E., Van Essen, D. C., & Wager, T. D. (2011). Large-

scale automated synthesis of human functional neuroimaging data. *Nature Methods, 8*,

665–670.

Yazar, Y., Bergstrom, Z.M., & Simons, J.S. (2017). Reduced multimodal integration of memory

features following continuous theta burst stimulation of angular gyrus. *Brain Stimulation,*

10, 624–9.

Yeo, B. T. T., Krienen, F. M., Sepulcre, J., Sabuncu, M. R., Lashkari, D., Hollinshead, M., . . .

Buckner, R. L. (2011). The organization of the human cerebral cortex estimated by

intrinsic functional connectivity. *Journal of Neurophysiology, 106*, 1125-1165.

Zacks, J. M.. (2020). Event perception and memory. *Annual Review of Psychology, 71*, 165-191.

Figure 1. *Schematic representation of the main preprocessing and analysis steps across both samples.*

Figure 2. Network structure in each of the seven age groups of the Cam-Can sample during movie watching at 2-10% tie densities shows similar levels of similarity to that reported by Power et al.' (2011) across various cohorts during rest. The colored lines show the normalized mutual information index (NMI), a highly used metric of similarity in community assignment, for each age group and tie density scrutinized.

Figure 3. *Age, intelligence and functional brain reconfiguration*. The scatter plot in panel (c) is based on standardized variables. In panel (a), white boxes correspond to coefficients that were not robust across all the bootstrapping samples. Gender, handedness, ROI homogeneity and the summary motion metric were introduced as covariates.

Figure 4. *Functional brain reconfiguration and network participation in older adulthood*. The scatter plot in panel (c) is based on standardized variables. In panels (a) and (b), white boxes correspond to coefficients that were not robust across all the bootstrapping samples. Gender, handedness, ROI homogeneity and the summary motion metric were introduced as covariates.

Figure 5. *Functional brain reconfiguration and network participation in younger adulthood*. The scatter plot in panel (c) is based on standardized variables. In panel (a), white boxes correspond to coefficients that were not robust across all the bootstrapping samples. Gender, handedness, ROI homogeneity and the summary motion metric were introduced as covariates.

robust *p*-value = .008

Figure 6. Scatterplot describing the association between the fluid intelligence score and the network participation profile linked to functional reconfiguration in younger adulthood, after controlling for all the covariates described in the text.

Figure 7. Panel (a). Results of the PLS analysis, showing the ROIs that demonstrated robust associations with context-based functional brain reconfiguration across the lifespan. The brain regions were visualized with the BrainNet Viewer (http://www.nitrc.org/projects/bnv/) (Xia et al., 2013). ROI colours reflect Power et al.'s network assignments (orange, DMN; pink, AUD). Panel (b) Results of the Neurosynth decoding analysis based on the ROIs in panel (a).

Figure 8. Panel (a). Results of the PLS analysis, showing the ROIs that demonstrated robust associations with window-to-window functional brain reconfiguration across the lifespan. The brain regions were visualized with the BrainNet Viewer (http://www.nitrc.org/projects/bnv/) (Xia et al., 2013). ROI colours reflect Power et al.'s network assignments (orange, DMN; blue, VIS; yellow, FPC). Panel (b) Results of the Neurosynth decoding analysis based on the ROIs in panel (a).

Figure 9. Brain-movie coupling and cognitive-affective function in the HCP sample. The scatter plot in panel (c) is based on standardized variables. In panel (a), white boxes correspond to coefficients that were not robust across all the bootstrapping samples. Gender, handedness, years of education, the summary motion metric and current negative emotional experience were introduced as covariates.

Figure 10. *The ROI participation profile linked to brain-object-based movie coupling.* The scatter plot in panel (c) is based on standardized variables. In panels (a) and (b), white boxes correspond to coefficients that were not robust across all the bootstrapping samples. Gender, handedness, years of education and the summary motion metric were introduced as covariates. Panel (d) presents the results of the Neurosynth decoding analysis based on the ROIs in panel (a).