RESEARCH

Struct2Graph: A graph attention network for structure based predictions of protein-protein interactions

Mayank Baranwal[1,2*], Abram Magner[3], Jacob Saldinger[4], Emine S. Turali-Emre[5,†], Paolo Elvati[6,†], Shivani Kozarekar[4], J. Scott VanEpps[5,7,8], Nicholas A. Kotov[4,5,8,9], Angela Violi[4,6,10] and Alfred O. Hero[5,11,12,13,14]

*Correspondence:
baranwal.mayank@tcs.com
[1]Division of Data and Decision
Sciences, Tata Consultancy
Services Research, Mumbai, India
[2]Systems & Control Engineering
Group, Indian Institute of
Technology, Bombay, India
Full list of author information is
available at the end of the article
†Equal contributor

Abstract

Background: Development of new methods for analysis of protein-protein interactions (PPIs) at molecular and nanometer scales gives insights into intracellular signaling pathways and will improve understanding of protein functions, as well as other nanoscale structures of biological and abiological origins. Recent advances in computational tools, particularly the ones involving modern deep learning algorithms, have been shown to complement experimental approaches for describing and rationalizing PPIs. However, most of the existing works on PPI predictions use protein-sequence information, and thus have difficulties in accounting for the three-dimensional organization of the protein chains.

Results: In this study, we address this problem and describe a PPI analysis based on a graph attention network, named *Struct2Graph*, for identifying PPIs directly from the structural data of folded protein globules. Our method is capable of predicting the PPI with an accuracy of 98.89% on the balanced set consisting of an equal number of positive and negative pairs. On the unbalanced set with the ratio of 1:10 between positive and negative pairs, Struct2Graph achieves a five-fold cross validation average accuracy of 99.42%. Moreover, Struct2Graph can potentially identify residues that likely contribute to the formation of the protein-protein complex. The identification of important residues is tested for two different interaction types: (a) Proteins with multiple ligands competing for the same binding area, (b) Dynamic protein-protein adhesion interaction. Struct2Graph identifies interacting residues with 30% sensitivity, 89% specificity, and 87% accuracy.

Conclusions: In this manuscript, we address the problem of prediction of PPIs using a first of its kind, 3D-structure-based graph attention network (code available at https://github.com/baranwa2/Struct2Graph). Furthermore, the novel mutual attention mechanism provides insights into likely interaction sites through its unsupervised knowledge selection process. This study demonstrates that a relatively low-dimensional feature embedding learned from graph structures of individual proteins outperforms other modern machine learning classifiers based on global protein features. In addition, through the analysis of single amino acid variations, the attention mechanism shows preference for disease-causing residue variations over benign polymorphisms, demonstrating that it is not limited to interface residues.

Keywords: protein-protein interaction; deep learning; structure-based prediction; graph attention network

Introduction

Protein–protein interactions (PPIs) are fundamental to many biological processes. Analysis of the human proteome suggests that the majority of proteins function not alone but rather as part of multi-unit complexes [1]. Indeed, PPIs are the central part of signal transduction, metabolic regulation, environmental sensing, and cellular organization [2]. In these processes, PPIs can alter enzyme kinetics, facilitate substrate channeling, form new binding sites, render a protein inactive, or modify the specificity of a protein with respect to a substrate [3]. Due to the ubiquitous presence of PPIs in living systems, being able to characterize these interactions promises to further our understanding of cellular processes [4] and provide an indispensable tool for disease treatment and drug discovery [5, 6]. PPI and their mathematical description are also essential for creation of protein analogs from other nanoscale building blocks, including but not limited to, lipids [7], sugars [8], polymers [9], nanoscale conjugates [10], and inorganic nanoparticles [11, 12, 13].

A number of strategies have been employed to decode PPIs. Traditionally, high throughput experimental techniques such as two-hybrid screens [14], tandem-affinity purification [15], and mass spectrometry [16] have been applied to create protein interaction networks. Concerns about insufficient accuracy [17], low experimental throughput [18] and high cost [19] of these methods, however, have motivated computational approaches that can complement traditional and robotic experimental protocols. Computational methods can predict whether proteins will interact based on data for the proteins' genetic context, amino acid sequences, or structural information. Genomics analyses consider factors such as gene fusion [20], conservation across common species (phylogenetic profiling) [21], and evolutionary history [22] when determining if a pair of proteins interact.

Typical computational techniques for PPI analysis use the amino acid sequences of the two proteins to determine whether interactions occur [23, 24]. A number of features such as frequency of common sub-sequences [25] and auto-covariance [26] have been proposed to convert sequences of different lengths into a uniformly sized representation. Sequence based methods have recently been able to leverage protein databases and machine learning techniques to make high accuracy predictions. Three-dimensional (3D) structure of protein-protein complexes from sequence can be predicted by CO-threading algorithm, (COTH) that recognizing templates of protein complexes from solved complex structural databases. COTH aligns amino acid chain sequences using scoring functions and structural information [27]. The DeepPPI model [28] predicts interactions using an artificial neural network, which takes as input a feature vector that captures the composition, distribution, and order of the sequence. DeepFE [29] uses natural language processing algorithms on amino acid sequences to create low dimensional embeddings of the sequence suitable as inputs for neural network analysis. DeepFE, in particular, has been shown to be quite effective, and achieves prediction accuracy of 94.78% and 98.77% on *S. cerevisiae* and human datasets, respectively. In fact, most deep learning based methods have been shown to achieve high PPI prediction accuracy [30, 31] owing to their significantly larger representation power. In addition to relying purely on sequence-based information, modern machine learning methods often incorporate network-level information for PPI prediction. In a PPI network, each node represents a protein,

while edges between them represent interactions. Thus, predicting interactions be-
tween any two nodes is a link-prediction problem in disguise. Recent methods have
leveraged the network structure, along with using vectorized representation of amino
acid sequences, to obtain stronger prediction performance [32, 33, 34, 35, 36, 13].

Despite their success, the above sequence based approaches do not generalize
to broader classes of chemical compounds of similar scale as proteins that are
equally capable of forming complexes with proteins that are not based on amino
acids, and thus lack of an equivalent sequence-based representation. While the
interaction of proteins with DNA can be accurately predicted [37], the methods
for machine learning-based predictions for protein complexes with high molecular
weight lipids [7], sugars [8], polymers [9], dendrimers [38] and inorganic nanopar-
ticles [11, 12] that receive much attention in nanomedicine and nanodiagnos-
tics [39, 40], are not widely known among experimentalists [41, 42, 43, 44, 45, 46, 47],
although substantial strides in this direction were made with the development of
unified structural descriptors for proteins and nanoparticles [13]. As a consequence,
predictive computational approaches that take into account the structure of proteins
and their variable non-proteinatious, biomimetic, and non-biological counterparts
become possible. Some methods predict interactions using the 3D structure of the
proteins [48, 49] use a knowledge-based approach to assess the structural similarity
of candidate proteins to a template protein complex. As this methodology requires
detailed information on the larger complex, template-free docking approaches [50]
analyze the unbound protein components and identify the most promising interac-
tions from a large set of potential interaction sites. While docking methods have
shown success for some proteins, they face difficulty with proteins undergoing con-
formational changes during interaction [51]. Many of these structural approaches
have also served as the basis for machine learning models. Zhang et al. developed
PrePPI [52] which uses amino acid sequence, and phylogenetic features as inputs
to a naive Bayes classifier. Northey et al. developed IntPred [53] which segments
proteins into a group of patches that incorporates 3D structural information into
a feature set to predict interaction with a multi-layer perception network. These
models are trained on carefully curated interaction databases describing both bi-
nary interactions between proteins, and corresponding interfacing sites or atoms.

In this work, we make the first step toward a generalized method to assess
supramolecular interactions of proteins with other nanostructures. The proposed
method determines the probability of formation of protein-protein complexes on a
nanoscale representation of proteins from crystallographic data, as contrasted to
amino-acid amino sequence information. We develop a mutual graph attention net-
work and a corresponding computational tool, *Struct2Graph*, to predict PPIs solely
from 3D structural information. Instead of using several protein specific features,
such as, hydrophobicity, solvent accessible surface area (SASA), charge, frequency
of *ngrams*, etc., Struct2Graph uses a graph based representation of a protein glob-
ule obtained using *only* the 3D positions of atoms. This graph based interpreta-
tion allows for neural message passing [54] for efficient representation learning of
proteins. Struct2Graph builds upon our prior work on metabolic pathway predic-
tion [55], where it is shown that an equivalent graph-based structural representation
of small molecules and peptides coupled with graph convolutional network, signif-
icantly outperforms other classifiers that involve computing various biochemical

features as inputs. This approach also leverages generalization of graph theory to describe complex nanoscale assemblies similar to PPI [56].

Beyond the high accuracy of its PPI predictions, Struct2Graph offers a number of advantages. Similarly to the ML algorithms exploiting the idea of geometrical biomimetics, Struct2Graph only requires the 3D structure of individual proteins. Furthermore, while in this paper we focus on protein interactions, by using only the positions of atoms in our analysis, this framework can be generalized to other molecular structures where 3D information is available. Moreover, Struct2Graph is also able to provide insight into the nature of the protein interactions. Through its attention mechanism, the model can potentially identify residues that likely contribute to the formation of the protein-protein complex. Unlike other models, Struct2Graph is able to produce this data in an unsupervised manner and thus does not require protein complex information which are often unavailable [57].

The key contributions of the proposed work can be summarized as:

- **Graph convolutional network for PPI prediction:** Struct2Graph uses a multi-layer graph convolutional network (GCN) for PPI prediction from the structural data of folded protein globules. The proposed approach is general and can be applied to other nanoscale structures where 3D information is available.

- **Curation of PPI database:** A large PPI database comprising of only direct/physical interaction of *non-homologous* protein pairs[1] is curated, along with information on the corresponding PDB files. Special emphasis is based on curation of PDB files based on the length of the chain ID and highest resolution within each PDB file to ensure capturing of the most complete structure information of the protein of interest.

- **State-of-the-art prediction performance:** Our method is capable of correctly predicting the PPIs with an accuracy of 98.89% on the balanced set consisting of an equal number of positive and negative pairs. On the unbalanced set with the ratio of 1:10 between positive and negative pairs, Struct2Graph achieves a five-fold cross validation average accuracy of 99.42%. Struct2Graph outperforms not only the classical feature-based machine learning approaches, but also other modern deep-learning approaches, such as Deep-PPI and DeepFE-PPI that use sequence information and feature selection for PPI prediction.

- **Unsupervised prediction of important residues:** The novel mutual attention mechanism can potentially identify important residues for the formation of the protein-protein complex. This importance can stem from either direct participation in the interaction process (i.e., binding site) or indirectly through contribution to appropriate protein folding that allows formation of the correct binding site geometry. The identification of important residues is tested for two different interaction types (neither part of the training set): (a) Proteins with multiple ligands competing for the same binding area, (b)

---

[1]Based on the pairwise homology analysis comprising of 3677 unique proteins in our database, only 0.3% of the proteins were found to have BLAST e-value < 0.05 and 0.26% has < 0.001, indicating statistically insignificant homologous relationships.

Dynamic protein-protein adhesion interaction. Struct2Graph identifies interacting residues with 30% sensitivity, 89% specificity, and 87% accuracy.

- **Analysis of single amino acid variation (SAV) dataset:** Disease-causing mutations are known to be preferentially located within the interface core, as opposed to the rim. Of the known 2724 disease-causing SAVs and 1364 polymorphisms, our attention mechanism identifies 33.55% of all disease-causing SAVs as important (attention weights within top-20%), while 85.30% of all polymorphisms are identified as *un*important by the proposed attention mechanism, indicating significant overlap between the previously established SAV study and the important residues identified by the proposed attention mechanism.

Materials and methods

PPI Database

Struct2Graph focuses on structure-based predictions and interaction sites of the protein pairs. Our PPI database is therefore produced based on only direct/physical interactions of proteins. To build a large physical interaction database, comprising of only *heterologous* pairs, we searched all possible databases available (STRING, BioGRID, IntAct, MINT, BIND, DIP, HPRD, APID, OpenWetWare). Not all PPI databases use the same publications and same ontologies to report the interactions. Consequently, it is not surprising that each database reports PPI differently. Therefore, only up to a 75% concordance between all PPI databases is achieved [58]. For Struct2Graph, two of the largest compiled databases, IntAct [59] and STRING [60] are chosen for further analysis, and results are compared to each other to find the true interactions. Only concordant matches between these two databases are chosen. Struct2Graph database is compiled from commonly studied organism's (*Saccharomyces cerevisiae*, *Homo sapiens*, *Escherichia coli*, *Caenorhabditis elegans* and *Staphylococcus aureus*) PPIs. For these organisms, IntAct provides 427,503 PPIs, and STRING provides 852,327 PPIs.

STRING distinguishes the type of interactions as "activation", "binding", "catalysis", "expression", "inhibition" and "reaction". IntAct, on the other hand, describe the type of interactions as "association", "physical association", "direct association/interaction", and "colocalization". Only "direct association/interactions" from IntAct and "binding" from STRING were considered as physical interactions. We only choose concordant pairs of physical interactions from both databases. Therefore, extracting only physical interaction data from the rest of the interactions reduces the actual number of PPIs to 12,676 pairs for IntAct and 446,548 pairs for STRING. Negative PPI is extracted from the work that derives negative interaction from large-scale two-hybrid experiments [61]. The negative protein-protein pairs from the two-hybrid system are compared further with the database constructed from STRING and INTact, and only the pairs that are not involved in any interaction at all, are chosen. We further exclude the co-localized protein pairs in our analysis. Structure information for Struct2Graph is obtained from PDB files. Hence, we only used the pairs which have associated PDB files. This reduces the total number of pairs to 117,933 pairs (4698 positive and 112,353 negatives). Some proteins are well-studied as they are in the scope of current medical and biotechnological interest. As a result, there is more than one cross-reference to PDB files since

various structures are accessible for these proteins. To find the proteins matched
with PDB files, all proteins from the database are matched with UniProt accession
numbers (UniProt Acc) and mapped with PDB files in UniProt [62]. Unfortunately,
not all proteins are crystallized fully in each PDB file, and random choice of PDB
file may cause incomplete information of the binding site of the protein. Therefore,
we curated the PDB files based on the length of the chain ID and highest resolu-
tion within each PDB file to ensure that we capture the most complete structure
information of the protein of interest. The chain length and the resolution of each
protein's crystal structure were obtained from the RCSB website [63]. The complete
set of negative pairs was reduced to 5036 pairs to create a fairly balanced training
sample with an approximately equal number of positive and negative pairs. For this
curated database consisting of only heterologous pairs, we defined two classes, "0"
for non-interacting (negative: not forming complexes) pairs and "1" for interacting
(positive: forming complexes) pairs.

Mutual graph attention network for protein-protein pairs

We present a novel multi-layer mutual graph attention network (GAT) based archi-
tecture for PPI prediction task, summarized in Fig 1. We refer to this architecture
as *Struct2Graph*, since the inputs to the proposed GAT are coarse grained structural
descriptors of a query protein-protein pair. Struct2Graph outputs the probability of
interaction between the query proteins. Struct2Graph uses two graph convolutional
networks (GCNs) with weight sharing, and a mutual attention network to extract
relevant geometric features related to query protein pairs. These extracted features
are then concatenated and fed to a feedforward neural network (FNN) coupled with
a `SoftMax` function, which finally outputs a probability of the two classes - '0' (neg-
ative pairs) and '1' (positive pairs). This section first describes the preprocessing
and fingerprinting procedure specifying how spatial information on protein pairs
are converted into corresponding protein graphs, and then elaborates on different
components of the Struct2Graph deep learning architecture.

Figure 1 Struct2Graph schematic. Struct2Graph graph convolutional network (GCN) for
incorporating mutual attention for PPI prediction. The GCN classifies whether or not a protein
pair ($X^{(1)}$ and $X^{(2)}$ on far left) interacts and predicts the interaction sites (on far right).

Protein structure graph

The purpose of the graph construction step is to capture the salient geometry of
the proteins in a way that is amenable to further dimensionality reduction by the

neural network. There are many possible ways of constructing a graph from spatial   213
coordinates of individual atoms, and each captures a different level of detail about   214
the geometry of the protein [13]. For instance, the protein-contact graph described   215
in [64] adds edges between three nearest neighbors and identifies the nodes as he-   216
lices, sheets, and turns. Ralaivola et al. [65] uses molecular fingerprints to prescribe   217
contact graphs for chemical compounds. Pires et al. [66] employs a distance-based   218
approach for constructing protein graphs by encoding distance patterns between   219
constituent atoms. Cha et al. [13] pioneered multidimentional protein graphs with   220
embedded chemical, geometrical and graph theoretical descriptors. Our approach to   221
constructing protein graphs is inspired by the latter, however, it is generalizable to   222
other non-protein structures as well. We first aggregate atoms into the amino acids   223
that they constitute and define the position of an amino acid to be the average of   224
the positions of its constituent atoms. These amino acids form the vertices of the   225
protein graph. An edge is placed between two vertices if the distance between them   226
is less than some threshold. Unlike the previous studies with 7Å threshold [13], in   227
this work, we use a threshold of 9.5Å for creating a protein graph from the mean   228
positions of amino acids. This threshold was obtained empirically so as to render   229
the underlying graph fully connected, while simplifying the graph representation.   230
Note that while we use amino acids as constituent vertices of the protein graphs,   231
the approach can be easily extended to multiresolution representation, where a ver-   232
tex represents two or more amino acids. The coarse-grained representation opens   233
up new possibilities for studying other nanoscale components of protein complexes,   234
such as, lipids and polysaccharides, since, lowering the level of representation from   235
all-atom to submolecular can be easily generalized to other non-protein entities.   236
Graphs with greater structural refinement can also be obtained by using functional   237
groups as amino acids. Moreover, this geometric construction of protein graphs   238
ensures that salient geometric features, such as spatial proximity of non-adjacent   239
amino acids along the polypeptide chain are captured. A sequence based represen-   240
tation of proteins might not capture this geometrical structure as well (see Fig 2).   241

The graph construction approach converts spatial information associated with a   242
protein into an equivalent protein graph object $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ is the set of   243
vertices and $\mathcal{E}$ is the set of edges between them. In the context of protein graph in   244
Fig 2, $v_i \in \mathcal{V}$ is the i^{th} amino acid and $e_{ij} \in \mathcal{E}$ represents an edge between i^{th} and   245
j^{th} amino acids, satisfying their proximity within the specified threshold of 9.5Å.   246
These graph objects must be embedded into real-valued vector space in order to   247
employ our machine learning framework. We use 1-neighborhood subgraphs [55]   248
induced by the neighboring vertices and edges at 1-hop distance from a vertex. A   249
dictionary of all unique subgraphs is constructed by scanning all protein graphs in   250
the training database. Thus, each vertex within a protein is equivalently represented   251
by an element in the dictionary.   252

Graph convolutional network acting on protein graphs   253

A graph convolutional network (GCN) maps graphs to real-valued *embedding vec-*   254
tors in such a way that the geometry of the embedding vectors reflects similari-   255
ties between the graphs. The embedding portion of the GCN works as follows. To   256
each vertex $v_i \in \mathcal{V}$, we associate a d-dimensional feature vector, which encodes the   257

Figure 2 Protein and protein graph. Illustration of extracted protein structure graph (right) from the corresponding PDB description of a peptide segment (left) of the *S. cerevisiae* alpha-factor receptor. The graph is extracted by thresholding the distances between amino acids. The helical structure of the protein (left) gets captured in the corresponding protein graph (right) where, for example, amino acid 4 is linked with amino acid 7.

1-neighborhood subgraph induced by the neighboring vertices and edges at 1-hop distance from a vertex. This is in contrast to explicit inclusion of amino acid specific features, such as, hydrophobicity, solvent accessible surface area (SASA), charge, etc. In our encoding, similar to other studies [67, 55], each element of the dictionary of subgraphs is assigned a random unit-norm vector.

Each layer of the GCN updates all vertex features by first replacing each vertex feature by a normalized average over vertex features of all 1-hop neighboring vertices. This is followed by an affine transformation given by the trained weight matrices and bias parameters. In order to impart expressivity to the GCN architecture, each coordinate of the resulting affine transformed embedding vector is passed through a nonlinear activation function, such as, rectified linear unit (ReLU) or sigmoid activations. This process is repeated for all the subsequent layers, and the output of the final layer is the newly transformed embedding (feature) vector that is propagated further to the mutual attention network. Here, the number of layers is a hyperparameter, while the weight matrices are learned from the training data in order to optimize performance of the entire system on the interaction prediction task.

More concisely, given input protein graphs $\mathcal{G}^{(1)}, \mathcal{G}^{(2)}$ with adjacency matrices $A^{(1)}, A^{(2)}$ consisting of N_1, N_2 vertices (amino acids), and quantities $X_0^{(1)} \in \mathbb{R}^{N_1 \times d}$, $X_0^{(2)} \in \mathbb{R}^{N_2 \times d}$ representing the d-dimensional embedding of the vertex subgraphs of the query protein-protein pair, respectively, an l-layer GCN updates vertex embeddings using the following update rule:

$$X_{t+1}^{(m)} = \text{ReLU}\left(\tilde{A}^{(m)} X_t^{(m)} W_t\right), \quad \text{for all } t \in \{0, \cdots, l-1\}, \tag{1}$$

where $\tilde{A}^{(m)} = \left(\hat{D}^{(m)}\right)^{-\frac{1}{2}} \hat{A}^{(m)} \left(\hat{D}^{(m)}\right)^{-\frac{1}{2}}$ denotes the normalized adjacency matrices, and $m \in \{1, 2\}$. Here, $\hat{A}^{(m)} = A^{(m)} + I$ and $\hat{D}^{(m)}$ is the degree matrix of $\hat{A}^{(m)}$.

Parameters W_t denote the weight matrix associated with the t^{th}-layer of the GCN.   277
The feature embeddings $X_l^{(1)} \in \mathbb{R}^{N_1 \times d}$ and $X_l^{(2)} \in \mathbb{R}^{N_2 \times d}$ produced by the final   278
layer of GCN are fed to a mutual attention network and hereafter denoted as $h^{(1)}$ 279
and $h^{(2)}$, respectively, for notational convenience.   280

Mutual attention network for PPI prediction   281

The purpose of the proposed mutual attention network is two fold: (a) extract rel-   282
evant features for the query protein-protein pair that *mutually* contribute towards   283
prediction of physical interaction of proteins, (b) combine embedding matrices of   284
dissimilar dimensions $N_1 \times d$ and $N_2 \times d$ to produce a representative single out-   285
put embedding vector of dimension $(2d)$. Attention mechanisms were originally in-   286
troduced for interpreting sequence-to-sequence translation models by allowing the   287
models to attend differently to different parts of the encoded inputs. Since then, it   288
has been adapted in other fields of deep learning, such as, computer vision [68], and   289
bioinformatics [67].   290

The mutual attention mechanism proposed in this work computes attention
weights $[\alpha_{ij}] \in \mathbb{R}^{N_1 \times N_2}$ and context vectors $s^{(1)} \in \mathbb{R}^d$, $s^{(2)} \in \mathbb{R}^d$ from the GCN-
transformed hidden embeddings $h^{(1)}$ and $h^{(2)}$. The attention weights are computed
as:

$$\alpha_{ij} = w^{\intercal} \tanh \left(U h_i^{(1)} + V h_i^{(2)} \right), \tag{2}$$

where $U, V \in \mathbb{R}^{d \times d}$ and $w \in \mathbb{R}^d$ are parameters of the mutual attention network
that are trained in an end-to-end fashion along with the weights of the GCN. These
attention weights are then translated to context vectors $s^{(1)}, s^{(2)}$ using the following
knowledge selection procedure:

$$
\begin{aligned}
\eta_i^{(1)} &= \frac{1}{N_2} \sum_{j=1}^{N_2} \alpha_{ij}, & \eta_j^{(2)} &= \frac{1}{N_1} \sum_{i=1}^{N_1} \alpha_{ij} \\
p_i^{(1)} &= \frac{\exp\left(\eta_i^{(1)}\right)}{\sum_{k=1}^{N_1} \exp\left(\eta_k^{(1)}\right)}, & p_j^{(2)} &= \frac{\exp\left(\eta_j^{(2)}\right)}{\sum_{k=1}^{N_2} \exp\left(\eta_k^{(2)}\right)}. \\
s^{(1)} &= \sum_{i=1}^{N_1} p_i^{(1)} h_i^{(1)}, & s^{(2)} &= \sum_{j=1}^{N_2} p_j^{(2)} h_j^{(2)}
\end{aligned}
\tag{3}
$$

Here $p_i^{(1)}$ and $p_j^{(2)}$ denote the relative weights of the amino acids i and j of the   291
query protein-protein pair that contribute towards interaction prediction. Those   292
vertices whose learned attention weights are large are likely to represent residues   293
that participate directly or indirectly towards forming protein-protein complex.   294

The context vectors $s^{(1)}$ and $s^{(2)}$ are then concatenated into a single context
vector of dimensions $2d$, which is used as input to a single-layer, fully connected
feedforward neural network (FNN) represented by $f(\cdot)$ to produce a two-dimensional
output vector. The FNN is parameterized by another weight matrix to be learned
in an end-to-end manner. A final `SoftMax` layer is applied to produce a probability,
one for each of the possible classes: 0 or 1, as shown in Equation (4). This output

represents the classifier's prediction of the probability that the two input proteins interact.

$$y_{\text{out}} = \texttt{SoftMax}\left(f\left(\texttt{concat}\left[s^{(1)}, s^{(2)}\right]\right)\right) \tag{4}$$

Results

As part of our assessment, we compare the performance of Struct2Graph for PPI predictions against a number of recent machine learning models. These methods include: (a) DeepFE model [29], where we train the natural language processing network on the same database used in the original publication and feed the embeddings into a fully connected feedforward neural network. (b) DeepPPI [28], where we extract 1164 sequence features related to the amino acid composition, distribution, and order. A separate neural network is used for each protein in the protein-protein pair and their outputs are concatenated into a final network for classification. Furthermore, as was done in the original publication [28], we implement these features into a number of traditional machine learning models [69], such as (c) Gaussian naive Bayes (GaussianNB) classifier, (d) Quadratic discriminant analysis (QDA), (e) k-nearest neighbor (k-NN) classifier, (f) Decision tree (DT) classifier, (g) Random forest (RF) classifier, (h) Adaboost classifier, and (i) Support vector classifier (SVC) [70]. All models are implemented in Python 3.6.5 on an Intel i7-7700HQ CPU with 2.8GHz x64-based processor. For common machine learning classifiers, such as, GaussianNB, QDA, SVC, RF, DT, k-NN and Adaboost, we use the readily available implementation in the scikit-learn [69] module. Deep learning classifiers, in particular, DeepPPI [71] and DeepFE-PPI [72] are implemented in Keras [73], while Struct2Graph is implemented in PyTorch [74].

For Struct2Graph, the hyperparameters of the models are tuned in order to achieve the reported accuracies. The tuning is obtained by performing grid search over the set of possible hyperparameter settings. The hyperparameters of our Struct2Graph implementation are as follows: `optimizer`: Adam optimizer [75] with learning rate $\lambda = 10^{-3}$ and rate-decay of 0.5 per 10 epochs; `total epochs`: 50; `number of GCN layers`: $l = 2$; `GCN embedding dimension`: $d = 20$; `loss function`: binary cross-entropy. For other competing methods, we use the tuned hyperparameters that are adopted from the original publications.

Performance on balanced databases

Table 1 summarizes the comparisons of Struct2Graph and various machine learning models for PPI prediction for a five-fold stratified cross validation study. In the cross validation, the 10004 pairs (4698 positive and 5036 negatives) are randomly partitioned into five subsamples of equal size. Of these five subsamples, a single subsample is retained as the validation data for testing various machine learning models, and the remaining four subsamples are used as training data. In order to reduce the training time with our Struct2Graph model, 800 pairs are randomly sampled with replacement among the 8003 pairs (80%) in each epoch, and the performance on the randomly chosen 800 pairs is used to update the parameters of the neural network. This modification not only reduces the training time considerably, but also injects noise into the training data to avoid any potential overfitting.

The performance is reported for various measures, such as, accuracy, precision, recall, specificity or the true negative rate, Matthews correlation coefficient (MCC), F_1-score, area under the receiver operating characteristic curve (ROC-AUC), and negative predictive value (NPV) (see Tables 1-10). For a balanced training set (Table 1), Struct2Graph outperforms any other existing machine learning models in the literature for all the measures (except for the recall, NPV, and ROC-AUC scores) with an average accuracy and precision of 98.89% and 99.50%, respectively. This is despite the fact that we significantly downsample the number of pairs in each epoch during the training process of the proposed Struct2Graph model.

Note from Table 1 that while QDA outperforms Struct2Graph in terms of recall and NPV scores, it does very poorly in terms of other measures indicating that the QDA classifier largely predicts positive interactions resulting in low false negative counts. Another observation is that the performance of Struct2Graph is only slightly better than that of another deep learning PPI model, DeepFE-PPI for this balanced training set. However, as discussed below, DeepFE-PPI does not perform as well for unbalanced training set, where positive interactions are underrepresented among all interactions, a case that often arises in practice.

The primary purpose of k-fold cross validation study is to measure the generalization capabilities of a model. Bootstrap resampling, on the other hand, is primarily used to establish empirical distribution functions for a widespread range of statistics. It works by performing sampling with replacement from the original dataset, and at the same time assuming that the data points that have not been chosen, are the test dataset. We repeat this procedure several times and compute the average score as estimation of the performances of various classifiers. Table 2 summarizes the comparisons of Struct2Graph and various machine learning models on a balanced dataset for PPI prediction for a bootstrap resampling method repeated over five times. As before, we downsample the number of pairs in each epoch during the training process of the Struct2Graph in order to speed up computation and avoid any potential overfitting. The performance statistics for the Struct2Graph method with bootstrap resampling are very similar to the ones obtained with a five-fold cross-validation study. Struct2Graph is shown to outperform other existing machine learning models for all the measures (except for the recall and NPV scores) with an average accuracy and precision of 98.96% and 99.40%, respectively. Interestingly, the performances of the DeepPPI and the DeepFE-PPI methods are marginally worse than that of the Random Forest classifier on the balanced set. However, as the class imbalance increases, DeepFE-PPI is shown to outperform the Random Forest classifier. We have, thus, also included the Random Forest classifier for comparative analysis on the unbalanced datasets.

Performance on unbalanced database

In most practical scenarios, the number of negative pairs is expected to be larger than positive pairs, since only a small fraction of protein pairs interact within all possible pairs. We thus evaluate the performance of the deep learning models, Deep-PPI and DeepFE-PPI against the proposed Struct2Graph model on various unbalanced training sets, where the number of negative pairs outnumber the positive pairs. These results are summarized in Tables 3-6 for several databases with varying ratios of positive to negative pairs: (a) 1:2 (2518 positive and 5036 negative),

Table 1 Five-fold cross-validation performance analysis of several machine learning methods on balanced dataset (1:1). Note that the proposed Struct2Graph method outperforms all other methods on the majority of metrics.

Method	Performance (%) on Balanced training set - 1:1			
	Accuracy	Precision	Recall	Specificity
GaussianNB	72.14±2.91	98.41±0.51	45.05±6.10	99.24±0.30
QDA	78.66±3.44	70.43±3.41	**99.42±0.40**	57.90±7.12
k−NN	94.19±0.56	99.49±0.08	88.83±1.10	99.54±0.07
Decision Trees	96.20±0.43	97.59±0.28	94.75±0.99	97.66±0.29
Random Forest	98.86±0.29	99.45±0.19	98.27±0.49	99.45±0.19
Adaboost	97.85±0.26	98.76±0.18	96.92±0.51	98.78±0.18
SVC	98.49±0.33	99.44±0.18	97.53±0.61	99.45±0.18
DeepPPI	97.22±0.44	98.26±0.82	96.14±0.88	98.29±0.83
DeepFE-PPI	98.64±0.32	99.16±0.28	98.12±0.51	99.17±0.28
Struct2Graph	**98.89±0.24**	**99.50±0.36**	98.37±0.34	**99.45±0.42**
Method	MCC	F1-score	ROC-AUC	NPV
GaussianNB	52.69±4.38	61.53±6.00	95.24±0.33	64.46 ± 2.37
QDA	63.06±5.23	82.40±2.27	78.66±3.43	**99.05±0.58**
k−NN	88.89±1.02	93.86±0.63	98.79±0.21	89.92±0.89
Decision Trees	92.45±0.84	96.15±0.46	96.36±0.30	95.23±0.61
Random Forest	97.74±0.58	98.86±0.30	**99.63±0.08**	98.30±0.46
Adaboost	95.72±0.52	97.83±0.27	99.20±0.08	96.94±0.50
SVC	97.01±0.66	98.48±0.34	**99.63±0.09**	97.58±0.59
DeepPPI	94.47±0.87	97.19±0.44	99.28±0.11	96.23±0.81
DeepFE-PPI	97.29±0.64	98.64±0.32	99.52±0.09	98.14±0.50
Struct2Graph	**97.79±0.49**	**98.94±0.20**	99.55±0.16	98.24±0.42

(b) 1:3 (1679 positive and 5036 negative), (c) 1:5 (1007 positive and 5036 nega-tive), and (d) 1:10 (504 positive and 5036 negative). Note that the positive pairs for unbalanced databases are selected randomly from the set of curated positive pairs. Struct2Graph again outperforms its deep-learning counterparts consistently for this unbalanced case. Struct2Graph improvement increases when the ratio be-tween positive and negative pairs becomes increasingly skewed. For instance, when the ratio of positive and negative pairs is 1:10, the precision and recall statistics for the Struct2Graph model are 97.54% and 96.43%, respectively, which are higher by 0.98% and 2.14%, respectively than the performance of the next best deep-learning model, DeepFE-PPI.

Bootstrap resampling yields a very similar conclusion, where the Struct2Graph is again shown to outperform its deep-learning counterparts, as well as the Random Forest classifier, consistently for several unbalanced cases (see Tables 7-10). When the ratio of positive and negative pairs is 1:10, the accuracy, precision and recall statistics for the Struct2Graph model are 99.26%, 97.04% and 95.59%, respectively, which are higher by 0.76%, 0.58% and 7.73%, respectively than the performance of the next best deep-learning model, DeepFE-PPI.

While a ratio of 1 : 10 reflects a significant class imbalance between positive and negative examples, the class imbalance in a protein interactome can potentially be of the order of 1 : 100 or even larger. In the absence of a PPI database (consisting of 3D-structural information) with such huge class imbalance, prevalence-corrected Precision-Recall Curves (PRCs) have been adopted [76] that reduce the false pos-itive rate at the expense of the true positive rate. Figure 3 depicts the prevalence-corrected PRCs on the balanced (1:1) for several PPI classifiers. The computation of precision is suitably modified with $r = 100$ [76] for an expected ratio of 1:100 for pos-itive to negative samples in the real-world data. PRCs best summarize the trade-off

Table 2 Bootstrap resampling performance analysis of several machine learning methods on balanced dataset (1:1). Note that the proposed Struct2Graph method outperforms all other methods on the majority of metrics.

Method	Performance (%) on Balanced training set - 1:1			
	Accuracy	Precision	Recall	Specificity
GaussianNB	71.90±3.19	99.01±0.38	46.39±5.95	99.47±0.23
QDA	54.46±0.93	53.28±0.77	**99.96±0.06**	5.30±1.74
k−NN	92.77±0.22	99.38±0.13	86.62±0.50	99.41±0.11
Decision Trees	95.15±0.51	97.13±0.38	93.41±0.88	97.03±0.31
Random Forest	98.70±0.11	99.39±0.18	98.10±0.14	99.35±0.18
Adaboost	96.61±0.25	97.83±0.40	95.60±0.21	97.71±0.44
SVC	98.05±0.19	99.35±0.15	96.87±0.28	99.32±0.15
DeepPPI	97.16±0.40	98.04±0.96	96.27±0.84	98.06±0.98
DeepFE-PPI	98.41±0.12	98.81±0.50	98.11±0.45	98.73±0.55
Struct2Graph	**98.96±0.19**	**99.40±0.09**	98.57±0.35	**99.47±0.09**
Method	MCC	F1-score	ROC-AUC	NPV
GaussianNB	53.40±4.44	62.93±5.81	96.04±0.12	63.30 ± 2.72
QDA	16.43±2.53	69.50±0.66	52.63±0.84	**99.37±0.83**
k−NN	86.36±0.40	92.56±0.30	98.32±0.16	87.31±0.38
Decision Trees	95.23±0.55	95.27±0.54	94.21±0.71	93.18±0.81
Random Forest	97.41±0.22	98.74±0.11	99.58±0.07	97.97±0.17
Adaboost	93.25±0.50	96.70±0.23	99.00±0.09	95.36±0.29
SVC	96.13±0.37	98.10±0.20	99.53±0.09	96.71±0.28
DeepPPI	94.36±0.81	97.14±0.40	99.05±0.14	96.34±0.78
DeepFE-PPI	96.82±0.25	98.45±0.12	99.52±0.05	97.99±0.20
Struct2Graph	**97.91±0.38**	**98.98±0.19**	**99.62±0.17**	98.50±0.33

Table 3 Five-fold cross-validation performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:2).

Method	Performance (%) on Unbalanced training set - 1:2			
	Accuracy	Precision	Recall	Specificity
DeepPPI	97.40±0.44	98.64±0.61	93.52±1.64	99.35±0.30
DeepFE-PPI	98.91±0.09	99.00±0.32	97.71±0.33	99.51±0.16
Struct2Graph	**99.03±0.24**	**99.13±0.25**	**98.11±0.58**	**99.53±0.13**
Method	MCC	F1-score	ROC-AUC	NPV
DeepPPI	94.16±0.97	96.00±0.72	99.19±0.21	96.85±0.76
DeepFE-PPI	97.54±0.20	98.35±0.13	**99.56±0.08**	**99.86±0.16**
Struct2Graph	**97.87±0.51**	**98.62±0.32**	99.47±0.20	98.97±0.34

Table 4 Five-fold cross-validation performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:3).

Method	Performance (%) on Unbalanced training set - 1:3			
	Accuracy	Precision	Recall	Specificity
DeepPPI	98.19±0.58	98.73±0.40	93.98±2.43	99.59±0.13
DeepFE-PPI	98.96±0.27	98.30±0.46	97.52±0.88	99.44±0.15
Struct2Graph	**99.30±0.22**	**99.17±0.44**	**98.19±1.09**	**99.71±0.13**
Method	MCC	F1-score	ROC-AUC	NPV
DeepPPI	95.15 ± 1.55	96.28 ± 1.24	99.27±0.14	98.03±0.78
DeepFE-PPI	97.21±0.72	97.90±0.55	**99.51±0.11**	99.18±0.29
Struct2Graph	**98.20±0.56**	**98.67±0.41**	99.49±0.21	**99.33±0.38**

between the true positive rate and the positive predictive value (PPV) for a classifier using different probability thresholds. The AUC (area under curve) in Figure 3(i) nearly approaches unity, thus guaranteeing excellent discrimination capability of the proposed Struct2Graph architecture. Figure 4 depicts the prevalence-corrected PRCs for the deep-learning classifiers on the unbalanced (1:10) dataset. As before, the AUC for the Struct2Graph architecture almost approaches unity.

Table 5 Five-fold cross-validation performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:5).

Method	Performance (%) on Unbalanced training set - 1:5			
	Accuracy	Precision	Recall	Specificity
DeepPPI	97.78±0.45	98.33±0.39	88.20±2.74	**99.70±0.07**
DeepFE-PPI	98.97±0.27	98.19±0.49	95.60±1.52	99.65±0.10
Struct2Graph	**99.13±0.18**	**98.49±0.85**	**96.63±0.93**	99.68±0.19
Method	MCC	F1-score	ROC-AUC	NPV
DeepPPI	91.87±1.68	92.97±1.53	98.69±0.50	97.69±0.52
DeepFE-PPI	96.28±1.00	96.87±0.85	**99.56±0.25**	99.12±0.30
Struct2Graph	**97.03±0.56**	**97.55±0.45**	99.17±0.25	**99.26±0.23**

Table 6 Five-fold cross-validation performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:10).

Method	Performance (%) on Unbalanced training set - 1:10			
	Accuracy	Precision	Recall	Specificity
DeepPPI	98.24±0.49	95.83±2.60	84.33±4.23	99.63±0.23
DeepFE-PPI	99.17±0.33	96.56±1.09	94.19±2.87	99.67±0.10
Struct2Graph	**99.42±0.14**	**97.54±1.28**	**96.43±2.49**	**99.73±0.16**
Method	MCC	F1-score	ROC-AUC	NPV
DeepPPI	88.95±3.14	89.66±2.94	97.18±1.24	98.45±0.41
DeepFE-PPI	94.91±2.07	95.35±1.90	**99.48±0.32**	99.42±0.29
Struct2Graph	**96.65±1.12**	**96.96±1.07**	99.45±0.70	**99.63±0.22**

Heterogeneity of the PPI database

The success of any machine learning algorithm is based on the quality of training data it is presented with. Of the 4698 positive and 5036 negative examples spanned across 3677 unique proteins, we first want to make sure that the learning algorithms are not biased towards memorizing the training data [77], since some of the proteins in the database are involved in positive only or negative only interactions. Figure 5 shows the distribution of number of interactions per protein that are involved in positive only interactions. It can be seen that nearly 82% of the unique proteins are involved in four or fewer positive only interactions. Consequently, for a classifier to memorize the training data and not learn to predict positive interactions would be extremely difficult without each protein appearing in a relatively large number of PPI instances.

Table 7 Bootstrap resampling performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:2).

Method	Performance (%) on Unbalanced training set - 1:2			
	Accuracy	Precision	Recall	Specificity
Decision Trees	94.86±0.58	95.67±1.29	89.48±0.79	97.79±0.67
Random Forest	98.74±0.15	99.10±0.17	97.33±0.44	99.45±0.09
DeepPPI	97.91±0.38	98.37±0.69	95.32±1.40	99.21±0.34
DeepFE-PPI	98.53±0.20	98.41±0.62	97.37±0.31	99.16±0.31
Struct2Graph	**98.91±0.24**	**99.17±0.15**	**97.89±0.17**	**99.52±0.27**
Method	MCC	F1-score	ROC-AUC	NPV
Decision Trees	88.69±1.28	92.47±0.82	93.66±0.58	94.47±0.50
Random Forest	97.25±0.33	98.20±0.22	99.71±0.08	98.56±0.24
DeepPPI	95.29±0.85	96.81±0.60	99.29±0.25	97.70±0.67
DeepFE-PPI	96.76±0.45	97.88±0.31	99.41±0.17	98.59±0.09
Struct2Graph	**97.59±0.51**	**98.43±0.30**	**99.73±0.18**	**98.87±0.16**

Table 8 Bootstrap resampling performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:3).

Method	Performance (%) on Unbalanced training set - 1:3			
	Accuracy	Precision	Recall	Specificity
Decision Trees	95.72±0.46	95.55±0.74	87.98±1.63	98.52±0.26
Random Forest	98.80±0.14	98.29±0.33	97.15±0.34	99.39±0.11
DeepPPI	97.78±0.36	98.43±0.42	92.60±1.38	99.51±0.13
DeepFE-PPI	98.86±0.11	98.42±0.54	97.30±0.31	99.43±0.20
Struct2Graph	**99.01±0.16**	**98.83±0.37**	**97.42±0.51**	**99.59±0.13**
Method	MCC	F1-score	ROC-AUC	NPV
Decision Trees	88.88±1.14	91.60±0.88	93.26±0.81	95.78±0.61
Random Forest	96.90±0.39	97.72±0.29	99.72±0.05	98.98±0.10
DeepPPI	94.04±0.98	95.42±0.77	99.06±0.47	97.58±0.44
DeepFE-PPI	97.08±0.28	97.85±0.20	99.34±0.11	99.03±0.05
Struct2Graph	**97.46±0.42**	**98.12±0.32**	**99.75±0.20**	**99.08±0.18**

Table 9 Bootstrap resampling performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:5).

Method	Performance (%) on Unbalanced training set - 1:5			
	Accuracy	Precision	Recall	Specificity
Decision Trees	95.56±0.45	94.14±0.79	80.91±2.12	98.87±0.16
Random Forest	98.38±0.19	98.25±0.65	92.82±1.07	99.63±0.13
DeepPPI	97.96±0.46	97.13±2.71	90.58±3.21	99.44±0.57
DeepFE-PPI	98.90±0.31	98.20±0.29	95.64±1.75	99.61±0.07
Struct2Graph	**99.16±0.17**	**98.29±0.64**	**97.08±1.01**	**99.69±0.13**
Method	MCC	F1-score	ROC-AUC	NPV
Decision Trees	84.72±1.33	87.01±1.18	89.89±1.04	95.82±0.55
Random Forest	94.53±0.70	95.45±0.61	99.66±0.15	99.03 ± 0.11
DeepPPI	92.58±1.66	93.66±1.46	98.96±0.13	98.15±0.61
DeepFE-PPI	96.24±1.11	96.89±0.94	99.49±0.11	99.05±0.16
Struct2Graph	**97.03±0.51**	**97.53±0.41**	**99.71±0.26**	**99.40±0.23**

Table 10 Bootstrap resampling performance analysis of deep-learning based machine learning methods on unbalanced dataset (1:10).

Method	Performance (%) on Unbalanced training set - 1:10			
	Accuracy	Precision	Recall	Specificity
Decision Trees	96.63±0.46	91.66±1.47	73.14±2.93	99.26±0.14
Random Forest	97.85±0.25	95.87±0.68	82.12±2.28	99.61±0.06
DeepPPI	98.09±0.77	95.30±3.86	83.29±7.49	99.58±0.37
DeepFE-PPI	98.50±0.46	96.56±0.38	87.86±5.00	99.66±0.05
Struct2Graph	**99.26±0.15**	**97.04±0.70**	**95.59±0.73**	**99.67±0.10**
Method	MCC	F1-score	ROC-AUC	NPV
Decision Trees	80.13±2.06	81.33±1.99	86.20±1.48	97.07±0.45
Random Forest	87.60±1.12	88.44±1.11	99.49±0.22	98.03±0.32
DeepPPI	88.01±4.96	88.69±4.82	96.65±1.60	98.35±0.73
DeepFE-PPI	91.27±2.80	91.92±2.72	99.50±0.20	98.69±0.24
Struct2Graph	**95.90±0.60**	**96.31±0.52**	**99.54±0.22**	**99.50±0.12**

Figure 3 Prevalence corrected precision-recall curves for the balanced database.
(a) AdaBoost classifier, (b) GaussianNB classifier, (c) kNN classifier, (d) SVC, (e) Decision tree classifier, (f) Random forest classifier, (g) DeepPPI classifier, (h) DeepFE-PPI classifier, (i) Struct2Graph (ours) classifier.

Similarly, of the 3677 unique proteins, 104 unique proteins are involved in negative only interactions (do not form complexes). Figure 6 shows the distribution of number of interactions per protein that are involved in negative only interactions. As seen in the histogram, the total number of proteins with negative only interactions appearing in more than five PPI examples is very small (81), and comprise of only 2.2% of the entire PDB database considered in our work. Thus, the distribution of data makes it implausible for learning algorithms to perform well just by memorizing the training data. The dataset also consists of 120 unique proteins that are involved in both positive and negative interactions. These 120 unique proteins appear in 6335 PPI instances in our database. Hence, it would be nearly impossible for any classifier to simply memorize the training data, and still be able to predict the interactions almost accurately on the test or validation set.

We further validate this by building a random forest classifier that is supplied with an input vector of length 3677. The specific choice of length of the input vector is directly related to the number of unique proteins in the database. We first create a dictionary of all the unique proteins and note down the order in which these unique proteins appear in the dictionary. Then, each unique protein is represented by a 3677-long unit vector with all but one coordinate being zero. The coordinate corresponding to the order of the protein in the dictionary is marked as 1. For predicting the interaction of two proteins, say proteins A and B, the unit vectors are summed and supplied to the random forest classifier as an input. Recall that the sum operation is permutation invariant, and thus interaction prediction

Figure 4 Prevalence corrected precision-recall curves for the unbalanced database.
(a) DeepPPI classifier, (b) DeepFE-PPI classifier, (c) Struct2Graph (ours) classifier.

Table 11 Memorization test for the PPI database

Database	Accuracy on Train-Set	Accuracy on Test-Set
Balanced (1:1)	91.17%	91.07%
Unbalanced (1:2)	66.98%	50.43%
Unbalanced (1:3)	75.25%	50.23%
Unbalanced (1:5)	83.53%	50.43%
Unbalanced (1:10)	91.04%	50.33%

for the pair (protein A, protein B) is identical to that for the pair (protein B, protein A). Table 11 summarizes the performance of the random forest classifiers on balanced and unbalanced datasets, trained using only the labels of protein pairs and disregarding any structural information. In the balanced scenario, the classifier can be trained with a reasonable accuracy of $\sim 91\%$ on both training and test sets. This is still significantly smaller than accuracies obtained using Struct2Graph and other deep-learning based classifiers on the balanced set. However, as the training database is made more realistic (i.e., biased towards significantly abundant negative examples), the performance on the training set drops, while the performance on the test set is completely random ($\sim 50\%$), i.e., the random forest classifier acts like a random predictor. In the extreme scenario, (1:10 ration between positive and negative examples), the training accuracy appears improved, largely because every time the classifier predicts a negative interaction, it is likely to be correct since the training set has an abundance of negative examples. However, on the test set comprising of approximately equal number of positive or negative examples, the prediction accuracy is still around 50% indicating zero learning.

Discussion

The success of Struct2Graph is attributed to the thorough analysis of structural 3D information embedded in the form of a graph, which predicts interactions better than sequence-based approaches [13]. In addition, Struct2Graph can potentially identify residues that likely contribute to the formation of the protein-protein complex. This is achieved by considering the probability tuples $\{(p_i, p_j)\}$ of different amino acids during the knowledge selection process described in Equation (3). These probabilities capture the relative importance of amino acids and thus reflect different amino acids' contributions towards interaction prediction. The amino acids with large relative probabilities (top 20%) are identified as important for the formation of the protein-protein complex. This importance can stem from either direct participation in the interaction process (i.e., binding site) or indirectly through contribution

Figure 5 Histogram of proteins with only positive interactions. Of the 3677 unique PDBs, 3453 PDBs are involved in only positive interactions, i.e., among all the protein-protein pair instances in our database, these 3453 proteins do not feature in any non-complex forming instance. Moreover, of the 3453 PDBs with only positive interactions, nearly 82% unique PDBs are involved in fewer than 4 PPI examples. Consequently, for a classifier to memorize data and not "learn" to predict interactions would be extremely difficult without each PDB appearing in a relatively large number of PPI instances.

to appropriate protein folding that allows formation of the correct binding site geometry.

A demonstration of the potential of Struct2Graph to identify specific interaction sites was performed on two example cases (neither part of the training set) with well-described interacting residues from protein pairs in the literature. Specifically, we studied two different interaction types: 1) A protein with multiple ligands competing for the same binding area [78]; and 2) A dynamic protein-protein adhesion interaction [79]. The reported interacting residues in these complexes are compared with the Struct2Graph's highest probability residues (top 20%) using standard 2x2 confusion matrices. In aggregate (i.e., two case examples with a total of three interacting pairs), Struct2Graph identifies interacting residues with 30% sensitivity, 89% specificity, and 87% accuracy. It should be noted that these protein pair examples are not in the training set, and Struct2Graph identifies these residues through its knowledge selection process in a completely unsupervised manner. Besides, as noted above, the identified residues could be critical for ensuring correct protein folding conformation and therefore *indirectly* important for predicting binding, but not captured by traditional analysis that focuses only on the specific interacting residues identified in the literature. Detailed results for each example are described:

1) **HMGB1 and PSMα_1 compete for binding TLR4**: Phenol soluble modulins (PSMs), short, amphipathic, helical peptides [80], play a crucial role in *Staphylococcus aureus* virulence, one of the most common causes of human bacterial infections worldwide [81]. *S. aureus* has seven PSMs (PSM$\alpha_1 - \alpha_4$, PSM$\beta_1 - \beta_2$, and

Figure 6 Histogram of proteins with only negative interactions. Of the 3677 unique PDBs, only 104 PDBs are involved in just the negative interactions, i.e., among all the protein-protein pair instances in our database, these 104 proteins do not feature in any complex forming instance. Moreover, of the 104 PDBs, 23 PDBs appear in less than 5 PPI examples. The total number of proteins that are involved in more than 5 PPI examples is a very small number (81), i.e., only 2.2% of the entire PDB database considered in our work.

δ-toxin) which have multiple functions including, cytolysis, biofilm structuring, and inflammatory activation via cytokine release and chemotaxis. PSMs specifically trigger the release of high mobility group box-1 protein (HMGB1). Toll-like receptor-4 (TLR4) interacts with HMGB1 activating nuclear factor NF-κB and proinflammatory cytokines production [82]. However, *S. aureus* PSMs$\alpha_1 - \alpha_3$ significantly inhibit HMGB1-mediated phosphorylation of NF-κB by competing with HMGB1 via interactions with the same residues of TLR4 domain [78]. As such, the specific interacting residues for these pairs HMGB1:TLR4 (2LY4 : 3FXI) and PSMα_1:TLR4 (5KHB : 3FXI) have been well described [78].

Struct2Graph identifies interacting residues of the HMGB1:TLR4 pair with 90% accuracy in which the top 9 predicted residues for TLR4 fall within the reported active cavity (residues rank 336-477). In addition, among the top 20% predicted residues of HMGB1 were the specific interacting residues Tyr^{16} and Lys^{68}. For the PSMα_1:TLR4 pair, Struct2Graph identifies interacting residues with 92% accuracy. Again the top predicted residues fall within the previously identified TLR4 active cavity (336-477). For PSMα_1, interacting residues Gly^2 and Val^{10} were correctly identified. While the overall sensitivity for detecting an interacting residue is $\sim 20\%$ for this example, Struct2Graph was able to predict that PSMα_1 interacts with TLR4 in the same area as the HMGB1 binding site. More specifically, the predicted binding sites for both on TLR4 have 94% concordance. Figures 7a and 7b shows the residues predicted to be essential and highlights how Struct2Graph predicts a similar site for both interactions.

2) **SdrG-Fibrinogen Adhesion**: Microbial attachment to host tissues is a crucial step in most bacterial infections. Gram-positive pathogens such as Staphylococci, Streptococci, and Enterococci contain multiple cell wall-anchored proteins that act as an adhesin to mediate bacterial attachment to host tissues. These adhesin mediating interactions have been termed MSCRAMMs (microbial surface components recognizing adhesive matrix molecules) [83]. SdrG is an MSCRAMM of *Staphylococcus epidermidis* that binds to the $B\beta$ chain of human fibrinogen (Fg) via dynamic "dock, lock, and latch" mechanism [79].

Struct2Graph was used to evaluate the interaction between SdrG (PDB:r19A) and a synthetic peptide with homologous sequence to its binding site in Fg (PDB:r17C). Interacting residues between SdrG and the synthetic Fg peptide homolog were predicted with 75% accuracy. Among the high probability residues identified in SdrG were 9 exact matches to those in the literature [79]. This included, Pro^{337}, Ser^{338}, Leu^{340}, Phe^{344}, Gln^{425}, Ser^{437}, Tyr^{577}, Asp^{578}, and Asn^{579}. Figure 7c shows the residues predicted to be essential for the interaction.

These results show that Struct2Graph provides insight into key residues involved in the protein-protein interaction without any training data on the specific nature of these interactions. A complete summary of the residues identified by Struct2Graph for the preceding examples is included in the supplementary material (see Additional File 1). Any high probability residues identified but not confirmed as directly interacting may have indirect effects through maintaining appropriate 3D conformation of the protein.

Figure 7 Important residue prediction by Struct2Graph for three example scenarios. (a) TLR4 with HMGB1, (b) TLR4 with $PSM\alpha_1$, (c) SdrG and Fibrinogen adhesion. The different colored residues encode different information: (i) Red: Top-20% residues identified important by Struct2Graph, (ii) Yellow: Actual binding site not identified to be important by Struct2Graph, (iii) Green: True binding site overlapping with a residue identified important by Struct2Graph, (iV) Purple: neither important, nor actual interaction site. Recall that both HMGB1 and $PSM\alpha_1$ are known to compete for the same binding sites on TLR4, and this is reflected in the Struct2Graph predictive analysis as well.

In addition to these specific binding examples, we consider the ability of our attention mechanism to predict useful residues across a broader dataset. Our attention mechanism does not necessarily predict interaction sites, but rather residues which are important to protein interactions regardless of their proximity to the interface. It has been observed that residues throughout the entire peptide chain can drive interactions [84]. Therefore, the attention mechanism will identify residues regardless of location that significantly alter interaction propensity. To demonstrate this, we analyze the single amino acid variation (SAV) dataset presented in [85] (please refer to

the supporting information `Additional File 2` for the human SAV dataset). The
authors in [85] performed a large-scale structural analysis of human single amino
acid variations (SAVs) and demonstrated that disease-causing mutations are prefer-
entially located within the interface core, as opposed to the rim. Their work analyzed
a total of 3282 disease-causing SAVs and 1699 benign polymorphisms occurring in
705 proteins. It is established that the disease-causing SAVs were 49% more likely
to occur in the interface core rather than the rim and were 72% more likely to occur
in the interface core than in the non-interacting protein surface, thus clearly demon-
strating a different contribution of core and rim regions to human disease. On the
other hand, 78.7% of polymorphisms were found to reside within surface-accessible
residues (241 in interface residues and 1096 in surface non-interface residues), i.e,
polymorphisms are less likely to be located in the interface core compared to the
rim.

Since the work in [85] primarily dealt with human database, there is sufficient
overlap between their dataset and the PPI database used in our manuscript. Of the
overlapping 2724 disease-causing SAVs (spanning across 342 unique proteins) and
1364 polymorphisms (spanning across 528 unique proteins), our attention mecha-
nism identifies 33.55% of all disease-causing SAVs as important (attention weights
within top-20%), while 85.30% of all polymorphisms are identified as *un*important
by the proposed attention mechanism, indicating significant overlap between the
previously established SAV study and the important residues identified by the pro-
posed attention mechanism.

Conclusion

Struct2Graph, a GCN-based mutual attention classifier, to accurately predict in-
teractions between query proteins exclusively from 3D structural data is proposed.
Since the prior study showed that the geometrical and graph theoretical descriptors
may be sufficient for description of PPI [13], Struct2Graph does not directly use de-
scriptors, such as sequence information, hydrophobicity, surface charge and solvent
accessible surface area, and thus can be generalized to a broader class of nanoscale
structures that can be represented in similar fashion. This study demonstrates that
a relatively low-dimensional feature embedding learned from graph structures of
individual proteins outperforms other modern machine learning classifiers based on
global protein features. Our GCN-based classifier achieves state-of-the-art perfor-
mance on both balanced and unbalanced datasets.

Moreover, the mutual attention mechanism provides insights into important
residues that are likely to contribute towards interaction through direct or indirect
participation. This is achieved through its knowledge selection process in a com-
pletely unsupervised manner. The identification of important residues is tested for
two different interaction types: (a) Protein with multiple ligands competing for the
same binding area, (b) Dynamic protein-protein adhesion interaction. Struct2Graph
identifies interacting residues with 30% sensitivity, 89% specificity, and 87% accu-
racy. Finally, through the analysis of single amino acid variations, the attention
mechanism shows preference for disease-causing residue variations over benign ones,
demonstrating that it is not limited to interface residues. This connection between
the unsupervised discovery of interaction sites and graph representation of proteins

is possible thanks to the somewhat limited type of atoms and bond patterns that commonly occur in such molecules, which makes it possible to characterize properties on local atomistic arrangements. Overall, the proposed framework is general and, while subject to availability of corresponding training data, can be made to predict other kinds of complex sets of collective supramolecular interactions between proteins and nanoscale species of different chemical composition.

Funding and Acknowledgements

AV, JSV, PE, MB, AM and SK acknowledge the support from the BlueSky Initiative from the University of Michigan College of Engineering. AOH acknowledges the support from ARO W911NF-19-1-0269 and ARO W911NF-14-1-0359. AV and JS acknowledge the support from DARPA HR00111720067. NAK expresses gratitude to Vannewar Bush DoD Fellowship ONR N000141812876. The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Abbreviations

PPI: Protein-Protein Interaction; **GAT**: Graph Attention Network; **GCN**: Graph Convolutional Network

Availability of data and materials

The source code, along with the PPI database, is available at https://github.com/baranwa2/Struct2Graph.

Competing interests

The authors declare that they have no competing interests.

Authors' contributions

Mayank Baranwal: Methodology, Software, Analysis, Writing - original draft. **Abram Magner:** Methodology, Software, Analysis. **Jacob Saldinger:** Validation of PPI results, Comparison with existing methods. **Emine S. Turali-Emre:** Data curation, Validation, Writing - PPI database and interaction site prediction sections. **Shivani Kozarekar:** Data curation. **Paolo Elvati:** Methodology - representation and properties of molecules, Conceptualization, Writing - review & editing. **J. Scott VanEpps:** Writing - review & editing, Supervision - PPI database. **Nicholas A. Kotov:** Methodology - graph representation of proteins and other nanostructures, Writing - review & editing, Supervision - PPI database. **Angela Violi:** Conceptualization, Writing - review & editing, Supervision. **Alfred O. Hero:** Conceptualization, Writing - review & editing, Supervision.

Author details

[1]Division of Data and Decision Sciences, Tata Consultancy Services Research, Mumbai, India. [2]Systems & Control Engineering Group, Indian Institute of Technology, Bombay, India. [3]Department of Computer Science, University of Albany, SUNY, Albany, USA. [4]Department of Chemical Engineering, University of Michigan, Ann Arbor, USA. [5]Department of Biomedical Engineering, University of Michigan, Ann Arbor, USA. [6]Department of Mechanical Engineering, University of Michigan, Ann Arbor, USA. [7]Department of Emergency Medicine, University of Michigan, Ann Arbor, USA. [8]Biointerfaces Institute, University of Michigan, Ann Arbor, USA. [9]Department of Materials Science & Engineering, University of Michigan, Ann Arbor, USA. [10]Biophysics Program, University of Michigan, Ann Arbor, USA. [11]Department of Electrical Engineering & Computer Science, University of Michigan, Ann Arbor, USA. [12]Department of Statistics, University of Michigan, Ann Arbor, USA. [13]Program in Applied Interdisciplinary Mathematics, University of Michigan, Ann Arbor, USA. [14]Program in Bioinformatics, University of Michigan, Ann Arbor, USA.

References

1. Berggård, T., Linse, S., James, P.: Methods for the detection and analysis of protein–protein interactions. PROTEOMICS **7**(16), 2833–2842 (2007). doi:10.1002/pmic.200700131
2. Braun, P., Gingras, A.-C.: History of protein-protein interactions: From egg-white to complex networks. PROTEOMICS **12**(10), 1478–1498 (2012). doi:10.1002/pmic.201100563
3. Phizicky, E.M., Fields, S.: Protein-protein interactions: Methods for detection and analysis. Microbiological reviews **59**(1), 94–123 (1995). doi:10.1128/MMBR.59.1.94-123.1995
4. Ito, T., Chiba, T., Ozawa, R., Yoshida, M., Hattori, M., Sakaki, Y.: A comprehensive two-hybrid analysis to explore the yeast protein interactome. Proceedings of the National Academy of Sciences **98**(8), 4569–4574 (2001). doi:10.1073/pnas.061034498
5. Fry, D.C.: Protein–protein interactions as targets for small molecule drug discovery. Biopolymers **84**(6), 535–552 (2006). doi:10.1002/bip.20608
6. D. Coelho, E., P. Arrais, J., Luis Oliveira, J.: From Protein-Protein Interactions to Rational Drug Design: Are Computational Methods Up to the Challenge?. Current Topics in Medicinal Chemistry **13**(5), 602–618 (2013). doi:10.2174/1568026611313050005
7. Mashaghi, S., Jadidi, T., Koenderink, G., Mashaghi, A.: Lipid nanotechnology. International journal of molecular sciences **14**(2), 4242–4282 (2013)
8. Peppas, N.A., Huang, Y.: Nanoscale technology of mucoadhesive interactions. Advanced drug delivery reviews **56**(11), 1675–1687 (2004)
9. Lee, S.-M., Nguyen, S.T.: Smart nanoscale drug delivery platforms from stimuli-responsive polymers and liposomes. Macromolecules **46**(23), 9169–9180 (2013)
10. Meng, H., Nel, A.E.: Use of nano engineered approaches to overcome the stromal barrier in pancreatic cancer. Advanced drug delivery reviews **130**, 50–57 (2018)

11. Kotov, N.A.: Inorganic nanoparticles as protein mimics. Science **330**(6001), 188–189 (2010)

12. Bhandari, S., Mondal, D., Nataraj, S., Balakrishna, R.G.: Biomolecule-derived quantum dots for sustainable optoelectronics. Nanoscale Advances **1**(3), 913–936 (2019)

13. Cha, M., Emre, E.S.T., Xiao, X., Kim, J.-Y., Bogdan, P., VanEpps, J.S., Violi, A., Kotov, N.A.: Unifying structural descriptors for biological and bioinspired nanoscale complexes. Nature Computational Science **2**(4), 243–252 (2022)

14. Uetz, P., Giot, L., Cagney, G., Mansfield, T.A., Judson, R.S., Knight, J.R., Lockshon, D., Narayan, V., Srinivasan, M., Pochart, P., Qureshi-Emili, A., Li, Y., Godwin, B., Conover, D., Kalbfleisch, T., Vijayadamodar, G., Yang, M., Johnston, M., Fields, S., Rothberg, J.M.: A comprehensive analysis of protein–protein interactions in Saccharomyces cerevisiae. Nature **403**(6770), 623–627 (2000). doi:10.1038/35001009

15. Gavin, A.-C., Bösche, M., Krause, R., Grandi, P., Marzioch, M., Bauer, A., Schultz, J., Rick, J.M., Michon, A.-M., Cruciat, C.-M., Remor, M., Höfert, C., Schelder, M., Brajenovic, M., Ruffner, H., Merino, A., Klein, K., Hudak, M., Dickson, D., Rudi, T., Gnau, V., Bauch, A., Bastuck, S., Huhse, B., Leutwein, C., Heurtier, M.-A., Copley, R.R., Edelmann, A., Querfurth, E., Rybin, V., Drewes, G., Raida, M., Bouwmeester, T., Bork, P., Seraphin, B., Kuster, B., Neubauer, G., Superti-Furga, G.: Functional organization of the yeast proteome by systematic analysis of protein complexes. Nature **415**(6868), 141–147 (2002). doi:10.1038/415141a

16. Ho, Y., Gruhler, A., Heilbut, A., Bader, G.D., Moore, L., Adams, S.-L., Millar, A., Taylor, P., Bennett, K., Boutilier, K., Yang, L., Wolting, C., Donaldson, I., Schandorff, S., Shewnarane, J., Vo, M., Taggart, J., Goudreault, M., Muskat, B., Alfarano, C., Dewar, D., Lin, Z., Michalickova, K., Willems, A.R., Sassi, H., Nielsen, P.A., Rasmussen, K.J., Andersen, J.R., Johansen, L.E., Hansen, L.H., Jespersen, H., Podtelejnikov, A., Nielsen, E., Crawford, J., Poulsen, V., Sorensen, B.D., Matthiesen, J., Hendrickson, R.C., Gleeson, F., Pawson, T., Moran, M.F., Durocher, D., Mann, M., Hogue, C.W.V., Figeys, D., Tyers, M.: Systematic identifcation of protein complexes in Saccharomyces cerevisiae by mass spectrometry. Nature **415**, 4 (2002)

17. Sprinzak, E., Sattath, S., Margalit, H.: How Reliable are Experimental Protein–Protein Interaction Data? Journal of Molecular Biology **327**(5), 919–923 (2003). doi:10.1016/S0022-2836(03)00239-0

18. Skrabanek, L., Saini, H.K., Bader, G.D., Enright, A.J.: Computational Prediction of Protein–Protein Interactions. Molecular Biotechnology **38**(1), 1–17 (2008). doi:10.1007/s12033-007-0069-2

19. Kaake, R.M., Wang, X., Huang, L.: Profiling of protein interaction networks of protein complexes using affinity purification and quantitative mass spectrometry. Molecular & cellular proteomics **9**(8), 1650–1665 (2010)

20. Marcotte, E.M., Pellegrini, M., Ng, H.-L., Rice, D.W., Yeates, T.O., Eisenberg, D.: Detecting protein function and protein-protein interactions from genome sequences. Science **285**(5428), 751–753 (1999). doi:10.1126/science.285.5428.751

21. Sun, J., Li, Y., Zhao, Z.: Phylogenetic profiles for the prediction of protein–protein interactions: How to select reference organisms? Biochemical and Biophysical Research Communications **353**(4), 985–991 (2007). doi:10.1016/j.bbrc.2006.12.146

22. Pazos, F., Valencia, A.: Similarity of phylogenetic trees as indicator of protein–protein interaction. Protein Engineering, Design and Selection **14**(9), 609–614 (2001). doi:10.1093/protein/14.9.609

23. Hashemifar, S., Neyshabur, B., Khan, A.A., Xu, J.: Predicting protein–protein interactions through sequence-based deep learning. Bioinformatics **34**(17), 802–810 (2018)

24. Zhang, F., Song, H., Zeng, M., Li, Y., Kurgan, L., Li, M.: Deepfunc: a deep learning framework for accurate prediction of protein functions from protein sequences and interactions. Proteomics **19**(12), 1900019 (2019)

25. Shen, J., Zhang, J., Luo, X., Zhu, W., Yu, K., Chen, K., Li, Y., Jiang, H.: Predicting protein-protein interactions based only on sequences information. Proceedings of the National Academy of Sciences **104**(11), 4337–4341 (2007). doi:10.1073/pnas.0607879104

26. Guo, Y., Yu, L., Wen, Z., Li, M.: Using support vector machine combined with auto covariance to predict protein–protein interactions from protein sequences. Nucleic Acids Research **36**(9), 3025–3030 (2008). doi:10.1093/nar/gkn159

27. Mukherjee, S., Zhang, Y.: Protein-protein complex structure predictions by multimeric threading and template recombination. Structure **19**(7), 955–966 (2011)

28. Du, X., Sun, S., Hu, C., Yao, Y., Yan, Y., Zhang, Y.: DeepPPI: Boosting Prediction of Protein–Protein Interactions with Deep Neural Networks. Journal of Chemical Information and Modeling **57**(6), 1499–1510 (2017). doi:10.1021/acs.jcim.7b00028

29. Yao, Y., Du, X., Diao, Y., Zhu, H.: An integration of deep learning with feature embedding for protein–protein interaction prediction. PeerJ **7**, 7126 (2019). doi:10.7717/peerj.7126

30. Shi, Q., Chen, W., Huang, S., Wang, Y., Xue, Z.: Deep learning for mining protein data. Briefings in bioinformatics **22**(1), 194–218 (2021)

31. Humphreys, I.R., Pei, J., Baek, M., Krishnakumar, A., Anishchenko, I., Ovchinnikov, S., Zhang, J., Ness, T.J., Banjade, S., Bagde, S.R., et al.: Computed structures of core eukaryotic protein complexes. Science **374**(6573), 4805 (2021)

32. Liu, L., Ma, Y., Zhu, X., Yang, Y., Hao, X., Wang, L., Peng, J.: Integrating sequence and network information to enhance protein-protein interaction prediction using graph convolutional networks. In: 2019 IEEE International Conference on Bioinformatics and Biomedicine (BIBM), pp. 1762–1768 (2019). IEEE

33. Zhang, D., Kabuka, M.: Multimodal deep representation learning for protein interaction identification and protein family classification. BMC bioinformatics **20**(16), 1–14 (2019)

34. Yue, X., Wang, Z., Huang, J., Parthasarathy, S., Moosavinasab, S., Huang, Y., Lin, S.M., Zhang, W., Zhang, P., Sun, H.: Graph embedding on biomedical networks: methods, applications and evaluations. Bioinformatics **36**(4), 1241–1251 (2020)

35. Yang, F., Fan, K., Song, D., Lin, H.: Graph-based prediction of protein-protein interactions with attributed signed graph embedding. BMC bioinformatics **21**(1), 1–16 (2020)

36. Huang, K., Xiao, C., Glass, L.M., Zitnik, M., Sun, J.: Skipgnn: predicting molecular interactions with skip-graph networks. Scientific reports **10**(1), 1–16 (2020)

37. Rastogi, C., Rube, H.T., Kribelbauer, J.F., Crocker, J., Loker, R.E., Martini, G.D., Laptenko, O., Freed-Pastor,

W.A., Prives, C., Stern, D.L., *et al.*: Accurate and sensitive quantification of protein-dna binding affinity. Proceedings of the National Academy of Sciences **115**(16), 3692–3701 (2018)

38. Khandare, J., Calderon, M., Dagia, N.M., Haag, R.: Multifunctional dendritic polymers in nanomedicine: opportunities and challenges. Chemical Society Reviews **41**(7), 2824–2848 (2012)

39. Pelaz, B., Alexiou, C., Alvarez-Puebla, R.A., Alves, F., Andrews, A.M., Ashraf, S., Balogh, L.P., Ballerini, L., Bestetti, A., Brendel, C., *et al.*: Diverse applications of nanomedicine. ACS nano **11**(3), 2313–2381 (2017)

40. Xu, L., Wang, X., Wang, W., Sun, M., Choi, W.J., Kim, J.-Y., Hao, C., Li, S., Qu, A., Lu, M., *et al.*: Enantiomer-dependent immunological response to chiral nanoparticles. Nature **601**(7893), 366–373 (2022)

41. Cha, S.-H., Hong, J., McGuffie, M., Yeom, B., VanEpps, J.S., Kotov, N.A.: Shape-dependent biomimetic inhibition of enzyme by nanoparticles and their antibacterial activity. ACS nano **9**(9), 9097–9105 (2015)

42. Kadiyala, U., Turali-Emre, E.S., Bahng, J.H., Kotov, N.A., VanEpps, J.S.: Unexpected insights into antibacterial activity of zinc oxide nanoparticles against methicillin resistant staphylococcus aureus (mrsa). Nanoscale **10**(10), 4927–4939 (2018)

43. Patra, J.K., Das, G., Fraceto, L.F., Campos, E.V.R., del Pilar Rodriguez-Torres, M., Acosta-Torres, L.S., Diaz-Torres, L.A., Grillo, R., Swamy, M.K., Sharma, S., *et al.*: Nano based drug delivery systems: recent developments and future prospects. Journal of nanobiotechnology **16**(1), 71 (2018)

44. Duncan, R.: Polymer conjugates as anticancer nanomedicines. Nature reviews cancer **6**(9), 688–701 (2006)

45. Bouffard, E., El Cheikh, K., Gallud, A., Da Silva, A., Maynadier, M., Basile, I., Gary-Bobo, M., Morere, A., Garcia, M.: Why anticancer nanomedicine needs sugars? Current medicinal chemistry **22**(26), 3014–3024 (2015)

46. Torrice, M.: Does nanomedicine have a delivery problem? ACS Publications (2016)

47. Zamboni, W.C., Torchilin, V., Patri, A.K., Hrkach, J., Stern, S., Lee, R., Nel, A., Panaro, N.J., Grodzinski, P.: Best practices in cancer nanotechnology: perspective from nci nanotechnology alliance. Clinical cancer research **18**(12), 3229–3241 (2012)

48. Fukuhara, N., Kawabata, T.: HOMCOS: A server to predict interacting protein pairs and interacting sites by homology modeling of complex structures. Nucleic Acids Research **36**, 185–189 (2008). doi:10.1093/nar/gkn218

49. Ghoorah, A.W., Devignes, M.-D., Smaïl-Tabbone, M., Ritchie, D.W.: Spatial clustering of protein binding sites for template based protein docking. Bioinformatics **27**(20), 2820–2827 (2011). doi:10.1093/bioinformatics/btr493

50. Ohue, M., Matsuzaki, Y., Uchikoga, N., Ishida, T., Akiyama, Y.: MEGADOCK: An All-to-All Protein-Protein Interaction Prediction System Using Tertiary Structure Data. Protein & Peptide Letters **21**(8), 766–778 (2013). doi:10.2174/09298665113209990050

51. Szilagyi, A., Zhang, Y.: Template-based structure modeling of protein–protein interactions. Current Opinion in Structural Biology **24**, 10–23 (2014). doi:10.1016/j.sbi.2013.11.005

52. Zhang, Q.C., Petrey, D., Deng, L., Qiang, L., Shi, Y., Thu, C.A., Bisikirska, B., Lefebvre, C., Accili, D., Hunter, T., Maniatis, T., Califano, A., Honig, B.: Structure-based prediction of protein–protein interactions on a genome-wide scale. Nature **490**(7421), 556–560 (2012). doi:10.1038/nature11503

53. Northey, T.C., Barešić, A., Martin, A.C.R.: IntPred: A structure-based predictor of protein–protein interaction sites. Bioinformatics **34**(2), 223–229 (2018). doi:10.1093/bioinformatics/btx585

54. Gilmer, J., Schoenholz, S.S., Riley, P.F., Vinyals, O., Dahl, G.E.: Neural message passing for quantum chemistry. In: Proceedings of the 34th International Conference on Machine Learning-Volume 70, pp. 1263–1272 (2017). JMLR. org

55. Baranwal, M., Magner, A., Elvati, P., Saldinger, J., Violi, A., Hero, A.O.: A deep learning architecture for metabolic pathway prediction. Bioinformatics (2019). doi:10.1093/bioinformatics/btz954. btz954. https://academic.oup.com/bioinformatics/advance-article-pdf/doi/10.1093/bioinformatics/btz954/31911448/btz954.pdf

56. Jiang, W., Qu, Z.-b., Kumar, P., Vecchio, D., Wang, Y., Ma, Y., Bahng, J.H., Bernardino, K., Gomes, W.R., Colombari, F.M., et al.: Emergence of complexity in hierarchically organized chiral particles. Science (2020)

57. Zhu, H., Du, X., Yao, Y.: Convsppis: identifying protein-protein interaction sites by an ensemble convolutional neural network with feature graph. Current Bioinformatics **15**(4), 368–378 (2020)

58. Lehne, B., Schlitt, T.: Protein-protein interaction databases: keeping up with growing interactomes. Human genomics **3**(3), 291 (2009)

59. Orchard, S., Ammari, M., Aranda, B., Breuza, L., Briganti, L., Broackes-Carter, F., Campbell, N.H., Chavali, G., Chen, C., Del-Toro, N., *et al.*: The mintact project—intact as a common curation platform for 11 molecular interaction databases. Nucleic acids research **42**(D1), 358–363 (2014)

60. Szklarczyk, D., Gable, A.L., Lyon, D., Junge, A., Wyder, S., Huerta-Cepas, J., Simonovic, M., Doncheva, N.T., Morris, J.H., Bork, P., *et al.*: String v11: protein–protein association networks with increased coverage, supporting functional discovery in genome-wide experimental datasets. Nucleic acids research **47**(D1), 607–613 (2019)

61. Trabuco, L.G., Betts, M.J., Russell, R.B.: Negative protein–protein interaction datasets derived from large-scale two-hybrid experiments. Methods **58**(4), 343–348 (2012)

62. Bateman, A.: Uniprot: A universal hub of protein knowledge. In: Protein Science, vol. 28, pp. 32–32 (2019). Wiley 111 River St, Hoboken 07030-5774, NJ USA

63. Burley, S.K., Berman, H.M., Bhikadiya, C., Bi, C., Chen, L., Di Costanzo, L., Christie, C., Dalenberg, K., Duarte, J.M., Dutta, S., *et al.*: Rcsb protein data bank: biological macromolecular structures enabling research and education in fundamental biology, biomedicine, biotechnology and energy. Nucleic acids research **47**(D1), 464–474 (2019)

64. Borgwardt, K.M., Ong, C.S., Schönauer, S., Vishwanathan, S., Smola, A.J., Kriegel, H.-P.: Protein function prediction via graph kernels. Bioinformatics **21**(suppl_1), 47–56 (2005)

65. Ralaivola, L., Swamidass, S.J., Saigo, H., Baldi, P.: Graph kernels for chemical informatics. Neural networks

18(8), 1093–1110 (2005)

66. Pires, D.E., Ascher, D.B., Blundell, T.L.: mcsm: predicting the effects of mutations in proteins using graph-based signatures. Bioinformatics **30**(3), 335–342 (2014)

67. Tsubaki, M., Tomii, K., Sese, J.: Compound–protein interaction prediction with end-to-end learning of neural networks for graphs and sequences. Bioinformatics **35**(2), 309–318 (2018)

68. Xu, K., Ba, J., Kiros, R., Cho, K., Courville, A., Salakhudinov, R., Zemel, R., Bengio, Y.: Show, attend and tell: Neural image caption generation with visual attention. In: International Conference on Machine Learning, pp. 2048–2057 (2015)

69. Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., *et al.*: Scikit-learn: Machine learning in python. Journal of machine learning research **12**(Oct), 2825–2830 (2011)

70. Ben-Hur, A., Ong, C.S., Sonnenburg, S., Schölkopf, B., Rätsch, G.: Support vector machines and kernels for computational biology. PLoS Comput Biol **4**(10), 1000173 (2008)

71. Du, X., Sun, S., Hu, C., Yao, Y., Yan, Y., Zhang, Y.: DeepPPI: boosting prediction of protein–protein interactions with deep neural networks. GitHub (2017)

72. Yao, Y., Du, X., Diao, Y., Zhu, H.: An integration of deep learning with feature embedding for protein–protein interaction prediction. GitHub (2019)

73. Gulli, A., Pal, S.: Deep Learning with Keras. Packt Publishing Ltd, ??? (2017)

74. Ketkar, N.: Introduction to pytorch. In: Deep Learning with Python, pp. 195–208. Springer, ??? (2017)

75. Kingma, D.P., Ba, J.: Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980 (2014)

76. Dick, K., Green, J.R.: Reciprocal perspective for improved protein-protein interaction prediction. Scientific reports **8**(1), 1–12 (2018)

77. Brown, G., Bun, M., Feldman, V., Smith, A., Talwar, K.: When is memorization of irrelevant training data necessary for high-accuracy learning? In: Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing, pp. 123–132 (2021)

78. Chu, M., Zhou, M., Jiang, C., Chen, X., Guo, L., Zhang, M., Chu, Z., Wang, Y.: Staphylococcus aureus phenol-soluble modulins $\alpha 1-\alpha 3$ act as novel toll-like receptor (tlr) 4 antagonists to inhibit hmgb1/tlr4/nf-κb signaling pathway. Frontiers in Immunology **9**, 862 (2018)

79. Ponnuraj, K., Bowden, M.G., Davis, S., Gurusiddappa, S., Moore, D., Choe, D., Xu, Y., Hook, M., Narayana, S.V.: A "dock, lock, and latch" structural model for a staphylococcal adhesin binding to fibrinogen. Cell **115**(2), 217–228 (2003)

80. Mehlin, C., Headley, C.M., Klebanoff, S.J.: An inflammatory polypeptide complex from staphylococcus epidermidis: isolation and characterization. The Journal of experimental medicine **189**(6), 907–918 (1999)

81. Tayeb-Fligelman, E., Tabachnikov, O., Moshe, A., Goldshmidt-Tran, O., Sawaya, M.R., Coquelle, N., Colletier, J.-P., Landau, M.: The cytotoxic staphylococcus aureus psmα3 reveals a cross-α amyloid-like fibril. Science **355**(6327), 831–833 (2017)

82. Wang, Y., Weng, H., Song, J.F., Deng, Y.H., Li, S., Liu, H.B.: Activation of the hmgb1-tlr4-nf-κb pathway may occur in patients with atopic eczema. Molecular Medicine Reports **16**(3), 2714–2720 (2017)

83. Patti, J.M., Höök, M.: Microbial adhesins recognizing extracellular matrix macromolecules. Current opinion in cell biology **6**(5), 752–758 (1994)

84. Fu, X., Wang, Y., Song, X., Shi, X., Shao, H., Liu, Y., Zhang, M., Chang, Z.: Subunit interactions as mediated by "non-interface" residues in living cells for multiple homo-oligomeric proteins. Biochemical and Biophysical Research Communications **512**(1), 100–105 (2019). doi:10.1016/j.bbrc.2019.03.004

85. David, A., Sternberg, M.J.: The contribution of missense mutations in core and rim residues of protein–protein interfaces to human disease. Journal of molecular biology **427**(17), 2886–2898 (2015)

Figures

Figure 1 Struct2Graph schematic. Struct2Graph graph convolutional network (GCN) for incorporating mutual attention for PPI prediction. The GCN classifies whether or not a protein pair ($X^{(1)}$ and $X^{(2)}$ on far left) interacts and predicts the interaction sites (on far right).

Figure 2 Protein and protein graph. Illustration of extracted protein structure graph (right) from the corresponding PDB description of a peptide segment (left) of the *S. cerevisiae* alpha-factor receptor. The graph is extracted by thresholding the distances between amino acids. The helical structure of the protein (left) gets captured in the corresponding protein graph (right) where, for example, amino acid 4 is linked with amino acid 7.

Figure 3 Prevalence corrected precision-recall curves for the balanced database. (a) AdaBoost classifier, (b) GaussianNB classifier, (c) kNN classifier, (d) SVC, (e) Decision tree classifier, (f) Random forest classifier, (g) DeepPPI classifier, (h) DeepFE-PPI classifier, (i) Struct2Graph (ours) classifier.

Figure 4 Prevalence corrected precision-recall curves for the unbalanced database. (a) DeepPPI classifier, (b) DeepFE-PPI classifier, (c) Struct2Graph (ours) classifier.

Figure 5 Histogram of proteins with only positive interactions. Of the 3677 unique PDBs, 3453 PDBs are involved in only positive interactions, i.e., among all the protein-protein pair instances in our database, these 3453 proteins do not feature in any non-complex forming instance. Moreover, of the 3453 PDBs with only positive interactions, nearly 82% unique PDBs are involved in fewer than 4 PPI examples. Consequently, for a classifier to memorize data and not "learn" to predict interactions would be extremely difficult without each PDB appearing in a relatively large number of PPI instances.

Figure 6 Histogram of proteins with only negative interactions. Of the 3677 unique PDBs, only 104 PDBs are involved in just the negative interactions, i.e., among all the protein-protein pair instances in our database, these 104 proteins do not feature in any complex forming instance. Moreover, of the 104 PDBs, 23 PDBs appear in less than 5 PPI examples. The total number of proteins that are involved in more than 5 PPI examples is a very small number (81), i.e., only 2.2% of the entire PDB database considered in our work.

Figure 7 Important residue prediction by Struct2Graph for three example scenarios. (a) TLR4 with HMGB1, (b) TLR4 with $PSM\alpha_1$, (c) SdrG and Fibrinogen adhesion. The different colored residues encode different information: (i) Red: Top-20% residues identified important by Struct2Graph, (ii) Yellow: Actual binding site not identified to be important by Struct2Graph, (iii) Green: True binding site overlapping with a residue identified important by Struct2Graph, (IV) Purple: neither important, nor actual interaction site. Recall that both HMGB1 and $PSM\alpha_1$ are known to compete for the same binding sites on TLR4, and this gets reflected in the Struct2Graph predictive analysis as well.

List of Tables

Additional Files

Additional File 1 — Supplementary Material
This file contains details of important residues identified by Struct2Graph for test pairs discussed in Figure 7.
Additionally, the supporting information also sheds light on creating protein embeddings using Struct2Graph.