1   **The N300: An Index For Predictive Coding Of Complex Visual Objects and Scenes**

3   [1]Manoj Kumar, [2]Kara D. Federmeier, [2]Diane M. Beck

[1]Princeton Neuroscience Institute, Princeton University, Princeton, NJ, USA.

[2]Department of Psychology, Program in Neuroscience, and the Beckman Institute for
Advanced Science and Technology, University of Illinois at Urbana-Champaign, Urbana,
IL, USA.

Corresponding Author: Manoj Kumar

Email: mk35@princeton.edu

Kumar ORCID 0000-0002-4911-2885
Federmeier ORCID 0000-0002-7815-1808
Beck ORCID 0000-0001-9802-5828
15

Classification

BIOLOGICAL SCIENCES

Psychological and Cognitive Sciences

Keywords

N300, predictive coding, visual perception, statistical regularities

Author Contributions

All authors worked together to design the study and analysis plan and to interpret the
results and write the paper. Data collection and processing were done by M.K. with
guidance from K.D.F.

This PDF file includes:

28   Main Text
29   Figures 1 to 3
30   Tables 1 to 2

Abstract

The bulk of support for predictive coding models has come from the models' ability to simulate known perceptual or neuronal phenomena, but there have been fewer attempts to identify a reliable neural signature of predictive coding. Here we propose that the N300 component of the event-related potential (ERP), occurring 250-350 ms post-stimulus-onset, may be such a signature of perceptual hypothesis testing operating at the scale of whole objects and scenes. We show that N300 amplitudes are smaller to representative ("good exemplars") compared to less representative ("bad exemplars") items from natural scene categories. Integrating these results with patterns observed for objects, we establish that, across a variety of visual stimuli, the N300 is responsive to statistical regularity, or the degree to which the input is "expected" (either explicitly or implicitly) by the system based on prior knowledge, with statistically regular images, which entail reduced prediction error, evoking a reduced response. Moreover, we show that the measure exhibits context-dependency; that is, we find the N300 sensitivity to category representativeness only when stimuli are congruent with and not when they are incongruent with a category pre-cue, suggesting that the component may reflect the ease with which an image matches the current hypothesis generated by the visual system. Thus, we argue that the N300 ERP component is the best candidate to date for an index of perceptual hypotheses testing, whereby incoming sensory information for complex visual objects and scenes is accessed against contextual predictions generated in mid-level visual areas.

Significance Statement

Predictive coding models postulate that our perception of visual sensory input is guided by prior knowledge and the situational context, such that it is facilitated when the input matches expectation and hence produces less prediction error. Here, we show that an electrophysiological measure, the N300, matches the features hypothesized for a measure of predictive coding: complex scenes (like objects) elicit less N300 activity when they are statistically regular (e.g., more representative of their categories), in a manner that itself is context dependent. We thus show that the N300 provides a window into the interaction of context, prediction, and visual perception.

Introduction

The stars in the night sky are not arranged in the shape of a great bear and there is no

rabbit on the moon; it is our prior knowledge of these shapes that invokes such

descriptions. Increasingly, it is clear that more generally our perception does not depend

on the sensory stimulus alone but is also dynamically influenced by our prior knowledge

(Smith & Loschky, 2019; Caddigan et al., 2017; Lupyan, 2017; Vo & Wolfe, 2013; Voss

et al., 2012; Summerfield et al., 2006). Indeed, many models of perception include some

form of perceptual hypothesis testing (PHT), in which perception, a hard inverse

problem, is conceived of as a process of generating a hypothesis on the basis of both

sensory input and prior knowledge and the current context (Clark, 2013; Gregory, 1980;

Hochberg, 1981; Huang & Rao, 2011; Rock, 1983; Helmholtz, 1925). Recently, one

class of PHT models has garnered increased interest: hierarchical predictive coding

models (Friston, 2005; Rao & Ballard, 1999; Spratling, 2010), which posit that each area

of, for example, visual cortex learns statistical regularities from the world that it then

uses, jointly with the input from the preceding area, to make predictions about the

stimulus. In particular, the prediction and incoming sensory signal are proposed to

undergo an iterative matching process at each stage of the processing hierarchy, with

the prediction feeding back on the preceding area. The mismatch ("prediction error"), if

any, between the prediction and the incoming sensory signal is then propagated to

higher layers in the processing hierarchy, revising the weights of the hypotheses, until

the feedback matches the incoming signal and the error is zero (Friston, 2005; Lange et

al., 2018; Rao & Ballard, 1999). These predictive coding models have risen to

prominence in recent years, in part because they represent an efficient coding scheme

for the complexity of the visual world and, perhaps more importantly, because they posit

a role for the abundant feedback connections known to exist between visual areas. The

bulk of support for predictive coding models has come from the models' ability to

simulate known perceptual or neuronal phenomena (reviewed (Spratling, 2016)), but

there have been fewer attempts to identify a reliable neural signature of predictive

coding. Here we propose that the N300 component of the event-related potential (ERP)

may be just such a signature of predictive coding mechanisms in occipitotemporal visual

cortex, operating at the scale of whole objects and scenes.

What would characterize a good measure of predictive coding in visual processing?

First, it should be observed to a variety of types of visual stimuli (objects, faces, natural

scenes) across most or all viewing conditions. More importantly, it should be responsive

to statistical regularity, or the degree to which the input is "expected" (either explicitly or

implicitly) by the system based on prior knowledge. In particular, the measured response

should increase with increasing irregularity, in keeping with the increased iterations, or

inference-based error, proposed to occur when an item does not match the prediction.

Finally, the measure should show context-dependency, as statistical regularities need to

be sensitive to the immediate context in order to be of use to the system.

Here we show that the N300 ERP component meets all three criteria and thus may

serve as a signature of hierarchical inference/predictive coding mechanisms for complex

visual stimuli in occipitotemporal cortex. The N300 is a negative going component with a

frontal scalp distribution that peaks around 300 ms after the onset of a visual stimulus. It

is sensitive to global perceptual properties of visual input (Mcpherson & Holcomb, 1999;

Schendan & Kutas, 2002, 2003) but not to manipulations limited to low level visual

features (e.g., color, or small-scale line segments; (Schendan & Kutas, 2007) that are

known to be processed in early visual cortex. Thus, the N300 is a "late" visual

component, with likely generators in occipitotemporal cortex (Schendan, 2019;

Sehatpour et al., 2006). It immediately precedes access to multimodal semantic memory

(reflected in the N400, which is observed later in time than the N300 when both are

present; (Kutas & Federmeier, 2011)), and is therefore well positioned to capture the

iterative, knowledge- and context-sensitive process of visual processing of the global

features of the stimuli as proposed by predictive coding models.

Importantly, as hypothesized by predictive coding models, the amplitude of the N300

increases for less "expected" (i.e., less statistically regular) stimuli. The N300 is larger to

pictorial stimuli that lack a global structure as compared to when the global structure of

the object is clearly discernible (Schendan & Kutas, 2003). The N300 is also sensitive to

repetition, with a reduced amplitude for repeated presentations; importantly, however,

N300 repetition effects (but not those on earlier components) depend on knowledge, as

they are larger when the visual stimulus is meaningful (Schendan & Maher, 2009; Voss

et al., 2010; Voss & Paller, 2007). Similarly, and critically, N300 amplitudes are sensitive

to a variety of factors that reflect the degree to which an object fits with prior experience.

For example, N300 amplitudes are sensitive to the canonical view of an object; an open

umbrella oriented horizontally (non-canonical) elicits a larger N300 amplitude than an

open umbrella oriented vertically (Schendan & Kutas, 2003; Vo & Wolfe, 2013).

Amplitude modulations are also linked to factors such as object category membership,

presence of category-diagnostic object features, and (rated) match to object knowledge

(Gratton et al., 2009; Schendan, 2019; Schendan & Maher, 2009). This pattern of data

suggests that the N300 may be a good marker for not only the global structure of an

object but the degree to which the input matches learned statistical regularities more

generally, with larger N300 amplitudes for stimuli that do not match predictions based on

learned regularities and hence require further processing. Indeed, Schendan (2019) has

come to a similar conclusion, arguing that the N300 reflects "object model selection," in

which the input is matched to possible known objects.

Although the N300 conforms to a number of the criteria outlined above, there are a few

open questions that need to be addressed in order to better situate the component as a

potential neural correlate of hierarchical inference or predictive coding. Thus far, the

N300 has primarily been elicited in response to objects, sometimes in the context of a

scene (Lauer et al., 2020; Mudrik et al., 2010; Vo & Wolfe, 2013), but still ostensibly to

an object. If the N300 reflects a general signature of hierarchical inference or predictive

coding, then it should be elicited by other meaningful visual stimuli, such as natural

scenes. In fact, scrambled scenes (created by recombining parts of the scene image into

a random jigsaw) elicit larger N300 amplitudes than do intact and identified scenes

(Pietrowsky et al., 1996). Because the scrambled scenes were degraded, however, it is

not clear whether these effects simply reflect the disruption to global structure or a

deviation from statistical regularity more generally. Here we use intact scenes that are

either highly representative of their category (e.g., good exemplars of that category) or

less representative of their category (bad exemplars). Importantly, all the images are

good photographs of real world scenes (i.e., they are not degraded); they are statistically

regular or irregular by virtue of how representative they are of their category. A highly

representative exemplar of its category, by definition, contains more information about its

category and thus serves as a better initial prediction (i.e., has high statistical regularity).

We ask whether such statistically regular and irregular stimuli elicit differential N300s, as

would be hypothesized if this component is a measure of hierarchical inference or

predictive coding.

We have previously found that good scene exemplars are more readily detected than

bad exemplars (Caddigan et al., 2010, 2017) that is, participants are better at

discriminating briefly presented and masked intact photographs from fully phase-

scrambled versions when those images are good exemplars of their category (i.e.,

beaches, forests, mountains, city streets, highways, and offices). Importantly, again,

there were no artificially introduced objects in any of the bad exemplars nor were they

impoverished or degraded in any way. Instead their good and bad status derived entirely

from how representative they were of the category being depicted (established in a

separate Amazon Mechanical Turk rating task). Although category was relevant to the

choice of stimuli and whether they were designated good or bad, it was completely

irrelevant to the judgement being made (was the stimuli an intact photo or noise?).

Nonetheless, participants had significantly higher sensitivity (d') for good than bad

exemplars (Caddigan et al., 2010, 2017), suggesting that good exemplars perceptually

cohere sooner than bad exemplars. Relatedly, the categories of those same good

exemplars are better decoded, using fMRI multi-voxel pattern analysis, than are the

categories of the bad exemplars in a number of visual areas, including V1 and the

parahippocampal place area (PPA; (Torralbo et al., 2013)). Interestingly, the BOLD

signal for those same bad exemplars is larger than that for good exemplars in the PPA

(Torralbo et al., 2013), in keeping with predictions from hierarchical predictive coding

(i.e., increased activity for the less statistically regular images). The poorer detection with

brief presentations, weaker representations in the brain, and greater activity evoked by

bad than good scene exemplars make these stimuli good candidates for eliciting a

neural signature of hierarchical predictive coding.

In **Experiment 1**, we recorded scalp EEG while participants viewed good and bad scene

exemplars and made a good/bad judgment. If the N300 serves as an index of matching

incoming stimuli to learned statistical regularities, then N300 amplitude should be

smaller for good exemplars of natural scenes than the bad exemplars. In **Experiment 1**

participants viewed the stimuli without any forewarning of what to expect (category and

good/bad status were fully randomized; see **Figure 1A**). In **Experiment 2**, however, we

then manipulated the expectations of the participants at the beginning of each trial by

presenting a word cue (e.g., 'Beach') that either matched the upcoming scene's category

(on 75% of trials) or mismatched the upcoming image category (e.g., preceding a forest

with the 'Beach' cue; see **Figure 1B**). If the N300 reflects the process of matching the

input to statistical regularities, it should also be sensitive to the particular template (i.e.,

statistical regularity) activated on that trial, as predicted by the cue.

Figure 1. Schematic of one trial in each of the experiments. **A.** In **Experiment 1**, a fixation cross was shown in the center of screen for a randomly chosen interval between 1000-2000 ms. A good or bad exemplar image from one of the six categories was then presented for 200ms, followed by a fixation cross. After a delay of 1000ms, the subjects respond to the question "Good or Bad?" with a button press and the next trial begins. **B.** In **Experiment 2,** the trial sequence is similar to **Experiment 1** with the following differences. At the start of each trial a word cue (e.g., "Beach") from one of six categories (beaches, city streets, forests, highways, mountains, and offices) is shown. At the end of the trial the subjects make a delayed response, with a button press, to the question "Yes or No?" ("Yes" if the image matches the cue and "No" otherwise) and the next trial begins. On 25% of the trials, there is a mismatch between the word cue and the image category. **C.** A sample of good and bad exemplars from each category used in our study.

Results

Experiment 1

Behavior

To motivate participants to attend to the scenes, we asked participants to make a

delayed response on each trial, judging whether the exemplar was a good or bad

exemplar of the scene category to which it was presumed to belong. Participants labeled

most good exemplars as "good" (mean = 86.2%, std. dev = 13.9%) and labeled bad

exemplars as "bad" about half the time (mean = 56.2%, std. dev = 15.6%). All trials were

used for the ERP analyses, irrespective of the choice of the participants.

ERPs

Grand-averaged ERPs at eight representative sites are plotted in **Figure 2**. Responses

to good and bad exemplars can be seen to diverge beginning around 250 ms after

stimulus onset, with greater negativity for bad exemplars than for good exemplars. The

polarity, timing, and frontal scalp distribution of this initial effect is consistent with prior

work describing the N300 (Mcpherson & Holcomb, 1999; Schendan & Kutas, 2002,

2003, 2007); see **Supplementary Information** for a formal distributional analysis.

<u>N300</u>

To characterize the good/bad effect on the N300, mean amplitudes were measured from

all 11 frontal electrode sites between 250 and 350 ms (see **Methods** for more details).

Bad exemplars elicited significantly larger (more negative) N300 responses (mean = -6.4

μV) than did good exemplars (mean = -5.3 μV); t(19)=-5.4 and Bayes factor = 737.7

(**Table 1**). In other words, we see the predicted differential response to statistically

irregular exemplars (bad exemplars) as compared to the statistically regular exemplars

(good exemplars). The larger amplitude for the bad exemplars, as compared to the good

exemplars aligns with PHT predictions that would posit greater inference error, and,

hence, greater iterative processing for the bad exemplars as compared to the good

exemplars. These results also confirm that the N300 indexes a match to statistical

regularities of natural scenes and thus extend the validity of the N300 to not only objects,

or objects in scene contexts, but more broadly to complex natural scenes.

Post N300 Components

Although the N300 was the component of primary interest, to more completely

characterize the brain's response to the scenes, we also examined good/bad differences

in later time windows encompassing the N400 (350-500 ms) and Late Positive Complex

(LPC) (500-800 ms). The details of the analyses and results are provided in the

Supplementary Information and summarized here. N400 responses, which index

multimodal semantic processing, were larger for bad (-3.3 μV) than for good exemplars

(-2.2 μV), suggesting that items that better fit their category allow facilitated semantic

access. We note however, that given the similar scalp distribution of the N300 and the

N400 to picture stimuli (Ganis et al., 1996), it is difficult to tell where the boundary of the

two components might be and thus how much the N400 pattern might be influenced by

the preceding N300. LPC responses were larger -- more positive – to good (4.5 μV) than

to bad (3.3 μV) exemplars. The LPC amplitude is known to positively correlate with

confidence in decision making (Finnigan et al., 2002). Larger LPC responses to good

items, therefore, is consistent with the behavioral pattern in which good exemplars were

classified more consistently than bad exemplars.

Figure 2.

Figure 2. Grand average ERP waveforms for good (blue) and bad (maroon) exemplars
in **Experiment 1** are shown at 8 representative electrode sites distributed over the head.
Plotted channel locations are marked as triangles on the schematic of the scalp.
Negative voltage is plotted upwards. The waveforms differ over frontal sites beginning in
the N300 time-window (250-350 ms), with greater negativity for bad exemplars as
compared to good exemplars. The bar plot gives mean amplitude over the 11 frontal
electrode sites (darkened electrode sites on the schematic of the scalp) used for the

primary statistical analyses. The error bars plotted are within-subject confidence
intervals. N=20.

Table 1. Experiment 1, mean amplitudes in the N300 time-window (250-350 ms) over

11 frontal electrode sites (see **Figure 2**), along with t-test and Bayes factor values. The

N300 response to bad exemplars is more negative (larger) than that to good exemplars.

The t- test and Bayes factor calculations compared the within subject Good/Bad

difference to 0.

Condition	N	Mean (μV)	Mean Bad/Good Difference (μV)	Bad/Good Difference 95% C.I.	t(19)	p	Bayes Factor
Bad	20	-6.4±0.61					
			-1.05	-1.46 to -0.64	-5.4	3.3E-05	747.7
Good	20	-5.3±0.61					

283 Note: ± values reflect the normed standard deviation within subjects. C.I. = confidence

284 interval.

285
286 **Experiment 2**
287

The good/bad difference observed in **Experiment 1** was elicited without any expectation

regarding the specific category to be presented (i.e., category and good/bad status were

completely randomized). Thus, the particular template or statistical regularity with which

the image was compared must have been initially elicited by the input itself. In

Experiment 2, we preceded each image with a word cue that either matched or

mismatched the upcoming category. If the N300 difference observed in **Experiment 1**

reflects the matching of incoming stimuli to learned statistical regularities, we should be

able to modulate that difference by activating either the appropriate (match cue) or

inappropriate (mismatch cue) statistical regularity. In particular, since neither a good nor

a bad exemplar (e.g., of a beach) should be a better match to an inappropriate category

(e.g., a forest) we should see an elimination of the N300 difference between good and

bad exemplars when the cue mismatches the current category.

Behavior

On each trial, participants were asked to respond if the stimulus matched the verbal cue

("Yes" or "No") via a button press. In the match condition, participants responded "Yes"

with a higher degree of accuracy for good exemplars (mean = 98.7%, std. dev = 2.4%)

than for bad exemplars (mean= 67.9% and std. dev = 14.6%). In the mismatch condition,

wherein the exemplars did not fit the cued category, participants responded "No" with

similar accuracy for good (mean = 95.9%, std. dev = 4.6%) and bad exemplars (mean =

94.0% and std. dev = 5.5%). All trials were used for the ERP analyses.

ERPs

Scenes elicited an N300 response (**Figure 3**) with similar timing, polarity and scalp

distribution to that observed in **Experiment 1**; see the **Supplementary Information** for

a formal distributional analysis. Analyses of N300 mean amplitudes were conducted

using the same time window (250-350 ms) and frontal electrode sites as in **Experiment**

1, here comparing good and bad exemplars under the two cueing conditions: match and

mismatch.

<u>N300</u>

In the match condition, when the scene is congruent with the verbal cue, we replicate the

N300 effect of **Experiment 1** for the good and bad exemplars, with a frontally distributed

negativity that is larger for the bad exemplars than the good exemplars (**Figure 3, Table**

2). Importantly, and as predicted, this N300 difference between good and bad exemplars

is notably reduced – indeed, likely absent altogether (Bayes factor 0.33) – in the

mismatch condition, consistent with the idea that the N300 is indexing the fit of the

incoming stimulus to the template activated by the verbal cue; that is, neither a good or

bad exemplar of category A represents a better match to a template for category B.

For completeness, and to compare the N300 in our experiment with its characterization

in the existing literature, we also performed an ANOVA across multiple factors:

Good/Bad x Cueing (Match/Mismatch) x Anteriority x Laterality x Hemisphere (see

Supplementary Information for results of the distributional analysis). There was a main

effect of Good vs. Bad (bad larger than good; $(F(1,19) =15.34)$ and an interaction

between Good/Bad and Cueing $(F(1,19) =5.87)$, with larger Good/Bad effects when the

scene matched the cue. The main effect of Cueing was not significant $(F(1,19) =0)$.

Figure 3

Figure 3. Grand average ERP waveforms for the good-match (solid-blue), bad-match
(solid-maroon), good-mismatch (dashed-blue), and bad-mismatch (dotted-maroon)
conditions in **Experiment 2** are shown at the same 8 representative electrode sites. In
the match condition, responses to good and bad exemplars differ in the N300 time-
window (250-350 ms), with greater negativity for bad exemplars as compared to good
exemplars, over frontal sites (darkened electrode sites on the schematic of the scalp). In
the mismatch condition, the differences between good and bad exemplars on the N300
are diminished/eliminated. The bar plot gives the grand average mean of the ERP
amplitude over the 11 frontal electrode sites (darkened electrode sites on the schematic
of the scalp) used for the primary statistical analyses (N = 20). The plotted error bars are
within-subject confidence intervals.

Table 2. The grand average mean values, in the N300 time-window (250-350 ms),

shown for 11 frontal electrode sites (see **Figure 3**), along with t-test and Bayes factor

values. There is strong evidence (large Bayes factor) for greater negativity of the N300

for bad exemplars as compared to good exemplars when the cue matches the stimulus.

When there is a mismatch between the cue and the stimulus there is no evidence (small

Bayes factor) for the difference between good and exemplars in the N300 time-window.

The t- test and Bayes factor calculations compared the within subject Good/Bad

difference to 0.

Condition	Cue	N	Mean (μV)	Mean Bad/ Good Difference (μV)	Bad/Good Difference 95% C.I.	t(19)	p	Bayes Factor
Bad	Match	20	-7.1±0.94	-2.06	-2.6 to -1.5	-7.4	5.6E-07	30457
Good	Match	20	-5.1±1.07					
Bad	Mismatch	20	-6.4±1.64	-0.47	-1.7 to 0.73	-0.82	0.42	0.31
Good	Mismatch	20	-6.0±1.64					

Note: ± values reflect the normed standard deviation within subjects.

<u>Post N300 Components</u>

Again, for completeness, we also examined effects on the N400 (350-500 ms) and Late

Positive Complex (LPC) (500-800 ms). These are presented in full in the

Supplementary Information and summarized here. Given prior work (reviewed in

(Kutas & Federmeier, 2011)), we expected the N400 to be particularly sensitive to the

match between the verbal cue and the scene category. Indeed, overall, N400 responses

to good scenes that matched the verbal cue were facilitated (more positive: -3.5 μV)

than to good scenes that mismatched their cues (-5.6 μV), consistent with the large

literature on N400 semantic priming (See Table S3). Moreover, we replicated the effect

in **Experiment 1**: N400 amplitudes were also larger for bad (-5.3 μV) than for good

exemplars (-3.5 μV) in the match condition, although, again, we cannot rule out influence

from the prior N300 effects on the observed pattern. We see an interaction of Good/Bad

x Cuing in the N400 window (F =18.56; p =0.0004; E =1), with the largest facilitation for

good exemplars in the match condition. LPCs were larger (more positive) for good

exemplars in the match condition (2.7 μV) compared to both bad exemplars (0.4 μV) in

the match condition (replicating **Experiment 1**) and to either scene type in the mismatch

condition (Good: 0.22 μV; Bad: 0.99 μV), presumably reflecting the increased ease and

confidence of responding to the good match items (see **Table S4**).

Discussion

We proposed that the N300 component of the ERP reflects the impact of hierarchical

predictive coding on late stage visual processing during which global features of the

stimulus are being processed. Across many studies, larger (more negative) N300

responses have been observed for conditions that might be characterized as statistically

irregular (Mudrik et al., 2010; Pietrowsky et al., 1996; Schendan & Kutas, 2002, 2003,

2007; Vo & Wolfe, 2013). However, thus far, the literature has examined only the

response to objects, objects in scenes, or to artificially degraded stimuli. If the N300

more broadly reflects a late visual stage predictive coding, then it should be sensitive to

statistical regularity represented at later visual processing stages more generally, not

just in the context of object processing and artificial manipulations of global structure. To

this end, here we showed that the N300 is also sensitive to the difference between good

(statistically regular) and bad (statistically irregular) exemplars of natural scenes.

Predictive coding posits a larger inference error in processing statistically irregular items

(bad exemplars) as compared to statistically regular items (good exemplars), and,

consistent with this, in **Experiment 1**, N300 responses were larger for the statistically

irregular exemplars. These data, in combination with prior experiments, show that the

N300 indeed manifests the expected response properties for a general index of

predictive coding mechanisms for late stage visual processing of complex objects and

scenes.

Across the literature, the kinds of stimuli distinguished by the N300 do not just differ in

low level attributes but encompass global structure, canonical viewpoints, probable

views of objects in scene contexts, and, in our own experiment, the category-level

representativeness of the stimuli. We would like to collectively refer to these properties

as learned statistical regularities. It is this collection of statistical regularities, which might

be called a *template*, that can aid the rapid categorization and identification of stimuli.

Thus, we can think of the differences on the N300 component as an indicator of the

degree to which an incoming exemplar can be matched with a template, with greater

negativity for a stimulus when it doesn't match a template as compared to when it does.

In **Experiment 1**, neither scene category nor exemplar status (good or bad) was

predictable from trial to trial, and thus the statistical regularity driving the observed effect

must have been acquired over the life time (i.e., learning what does and does not

constitute a good exemplar of a category), rather than within the context of the

experiment. However, a key attribute of PHT models, of which predictive coding is a

popular example, is that the hypotheses that are generated are sensitive to the current

context. If the N300 reflects a template matching process, such that the input is

compared against a contextually relevant learned statistical regularity, then the N300

sensitivity to statistical regularity should vary by context.

In **Experiment 2,** therefore, we set up expectations for a particular category on each trial

using a word cue, with the aim of pre-activating a particular scene category template.

Critically, on 25% of trials the scene did not match the cued category. We found that the

N300 is indeed sensitive to regularities cued by the current context. When the scenes,

both good and bad exemplars, were congruent with the cued category, we observed a

significant effect of statistical regularity (good versus bad) in the N300 time-window,

replicating the results from **Experiment 1**. Here the good exemplar provides a better

match to the activated template than the bad exemplars, and thus the reduced inference

error or iterative matching is reflected in the amplitude of the N300. In the mismatching

condition, however, the presented stimulus, again whether a good or bad exemplar of its

own category, does not match the cued template (e.g., a "Forest" template has been

cued but a good or bad beach scene was presented). In this case, notably, we failed to

observe a reliable difference between the N300 to good and bad exemplars. In the

language of predictive coding models, similar inference errors would be generated for

both statistically regular (good) and irregular (bad) exemplars that mismatch the

activated template, as they would both violate the predicted regularities or at least

neither good nor bad exemplars of another category should violate the predicted

regularities more than the other. Thus, the N300 not only indexes statistical regularities

learned over a lifetime, but also shows sensitivity to the expectations (predictions)

generated within the current context. Thus, again the N300 conforms to characteristics

expected of a neural signature of predictive coding.

The N300 Indexes Perceptual Hypothesis Testing

We can think of visual identification and categorization as a cascade of processes,

starting with identification of low level visual features, followed by perceptual grouping of

features, and then appreciation of the "whole" visual form of objects and scenes, after

which processing moves beyond the visual modality into multi-modal semantics and

decision making. PHT mechanisms can work within and across each of these stages. In

the context of object processing, prior work on the N300 has posited it as an index of

object model selection, an intermediate stage in the process of object identification and

categorization (Schendan, 2019; Schendan & Kutas, 2002, 2003, 2007). Having

extended the N300 differences to natural scenes, we propose that the N300 reflects

PHT mechanisms in this intermediate stage more broadly, not just object selection.

Similar to other work (Schendan, 2019), we believe that the N300 reflects processing at

the point wherein the input is matched to items in memory with similar perceptual

structures. However, our data show that this process is not limited to objects and that it

makes use of variety of statistical regularities learned from the world, including those

critical for processing both objects and scenes.

The broadened view of the N300 as being reflective of a general visual template

matching process would suggest that its source be occipitotemporal visual areas.

Indeed, the N300 response to objects has been source localized to occipitotemporal

visual areas (Schendan & Lucia, 2010; Sehatpour et al., 2006). Although the N300 for

scenes has not yet been source localized, a high-density ERP study on scene

categorization localized activity in the 200-300 ms time window to these same

occipitotemporal visual areas (Greene & Hansen, 2020). Moreover, our prior fMRI work

with good and bad scene exemplars (Torralbo et al., 2013) would suggest that the N300

for scenes originates in the PPA, a region known to preferentially process natural scenes

(Epstein & Kanwisher, 1998). Using the same good and bad scene exemplars as in our

experiments, we found that, in the PPA, bad exemplars elicited a greater BOLD signal

than good exemplars (Torralbo et al., 2013), mirroring the effect we observed for the

N300. Interestingly, in that same PPA region of interest we observed that good

exemplars were better decoded than bad exemplars; that is, we were better able to

predict the scene category presented on the basis of activity patterns when the scene

was a good exemplar than when it was bad (Torralbo et al., 2013). In other words, it was

not the case that reduced activity for good exemplars reflected a weaker representation

but instead likely reflected a more efficient representation, an interpretation that aligns

nicely with our characterization of the N300 effect as one of visual template matching in

occipitotemporal cortex. These templates can be rapidly activated via pattern completion

mechanisms in occipitotemporal cortex (Cowell et al., 2019; Cutler et al., 2019; Hindy et

al., 2016; Norman & O'Reilly, 2003). We suggest that the N300 may be interpreted as a

component that reflects the iterative processing, as posited by PHT, in occipitotemporal

cortical regions, which helps match previously learned regularities of objects and scenes

with the incoming stimulus.

Although we are arguing that the N300 indexes PHT for late stage visual processing of

complex visual objects and scenes, it is possible that other components could index PHT

at other stages of processing. For example, PHT matching low level sensory features,

such as gratings (Kok et al., 2012), to hypotheses about such low level features should

occur at earlier stages in the processing hierarchy. These PHT processes maybe

reflected in other ERP components, such as the visual mismatch negativity (Oxner et

al., 2019), or even earlier ERP components that index expected features, like the P1

(Boutonnet & Lupyan, 2015).

The N300 may thus index the "final" stage of visual PHT, at the transition into

multimodal, semantic processing. Immediately after the N300, ERP responses to

complex objects and scenes are characterized by an N400, which we also observe in

our experiment. The N400 is widely accepted as a signature of multi-modal semantic

processing, elicited by not only visual words and pictures, but also meaningful stimuli in

other modalities (see review Kutas & Federmeier, 2011), whereas the N300 seems to be

about visual perceptual structure (Schendan, 2019; Schendan & Kutas, 2002, 2003,

2007). In some cases, it may be difficult to disentangle the precise contributions of the

N300 and N400 to observed effects of object categorization and match to object

knowledge (Gratton et al., 2009; Schendan, 2019; Schendan & Maher, 2009) since the

N400 is known to be sensitive to the fit between, e.g., a picture and its context

(Federmeier & Kutas, 2002; Ganis et al., 1996). Importantly, however, this does not

impact the critical effect of our good versus bad scenes, as neither contain contextually

inappropriate items, nor, in **Experiment 1,** did we set up any context prior to an image

(i.e., the scene category is unpredictable).

Conclusion

We have argued that the N300 serves as an index of PHT at the level of whole-objects

and scenes. Using statistically regular and irregular exemplars of natural scenes, we

showed that items that do not match our known regularities, the statistically irregular

exemplars, and hence should lead to larger inference errors evoked a large N300

amplitude than statistically regular exemplars. We not only showed that the N300 is

sensitive to current context, by pre-activating a context with a verbal cue, but that it

behaves like a template matching process in which statistically regular images procure

their advantage by virtue of matching the current contextual prediction; that is, the N300

was differentially sensitive to good and bad exemplars of a category only when that

category was expected. Our work not only extends prior work on the N300 to natural

scenes but it suggests that the N300 reflects a general template/model selection process

of the sort proposed by PHT models, such as predictive coding. We propose that the

N300 indexes visual inference processing in a late visual time-window that occurs at the

boundary between vision and the next stage of multi-modal semantic processing.

Further studies will be needed to explore the full range of the N300 response. For

example, does it require that the object or scene is attended or might it proceed more

automatically. Can it be modulated by contexts setup in different modalities (e.g.,

auditory inputs: speech, sounds)? Regardless, we propose that the N300 can serve as a

useful marker of knowledge guided visual processing of objects and scenes, with

templates based on prior knowledge serving as hypotheses for visual inference as

posited by PHT.

Methods

<u>Participants</u>

The data for **Experiment 1** came from 20 right-handed college-age subjects (mean age

= 24.36 years, range = 18 to 33 years, 12 women), and the data for **Experiment 2** from

a separate set of 20 right-handed subjects (mean age = 22.44; range 18-30 years; 14

women). In both experiments, participants gave written, informed consent and were

compensated for their participation in the study with course credit or cash. The study

was approved by the Institutional Review Board of the University of Illinois at Urbana-

Champaign. All participants were right-handed, as assessed by the Edinburgh Inventory

(Oldfield, 1971) and none had a history of neurological disease, psychiatric disorders, or

brain damage.

<u>Materials and Procedures</u>

ERP-eliciting stimuli were pictures of natural scenes from six categories: beaches,

forests, mountains, city streets, highways and offices (**Figure 1C**). These images were

collected from the internet and rated for their representativeness of the named category

on Amazon Mechanical Turk (Torralbo et al., 2013). The 60 top rated images were used

as good exemplars for each category, and the 60 lowest rated images were used as bad

exemplars for each category (for details on the choice of good and bad exemplars see

(Torralbo et al., 2013)). Images were resized to 340 x 255 pixels and presented on a

black background with a fixation cross at the center. The images were randomly

presented at one of three locations: the center of the scene, 2 degrees to the left of

fixation, or 2 degrees to right of fixation, with a total of 120 good images and 120 bad

images presented at each location. Here, we report only results for centrally-presented

images (lateral presentation was used to separately answer questions about

hemispheric biases in scene processing that are outside the scope of this manuscript).

In **Experiment 1**, participants were instructed at the beginning of the study that they

would be seeing good and bad exemplars of six scene categories and that their task at

the end of each trial was to indicate via button press whether the image was a good or a

bad exemplar of its category. Participants first practiced with 9 trials to acclimatize to the

task environment, and these images were not repeated in the main experiment. Then,

they completed 3 blocks each consisting of an equal number of trials, for a total of 240

centrally presented trials (trials were also presented to the left and right visual fields in

each block). The trial counts for centrally presented stimuli, for each category (good and

bad combined) are as follows: beaches = 39; cities = 41; forests = 38; highways = 42;

mountains = 36; offices = 44. Participants were seated at a distance of 100 cm from the

screen, and the images subtended a visual angle of 7.65° x 5.73° (width x height).

Subjects were instructed to maintain fixation on the central fixation cross and to try to

minimize saccades and eye blinks during stimulus presentation. As depicted in **Figure**

1A, each trial began with a fixation cross presented on a blank screen for a duration

jittered between 1000-2000 seconds (to reduce the impact of slow, anticipatory

components on the ERP signal). The scene image, either a good exemplar or a bad

exemplar from one of the six categories, was presented for a duration of 200 ms,

followed by a fixation cross on a blank screen for 500 ms. At the end of the trial a prompt

with "Good or Bad?" was displayed on the screen, and participants pressed one of two

response buttons, held in each hand (counterbalanced across participants), to indicate

their judgment. The experiment lasted for approximately one hour and fifteen minutes.

Subjects were given two five-minute breaks at roughly 25 minutes and 60 minutes from

the start of the experiment.

Experiment 2 was identical to **Experiment 1**, except that each trial began with a word

cue, presented for 500 ms (**Figure 1B**), which corresponded to one of the six scene

categories used in the experiment: Beach, City Street, Forest, Highway, Mountain, and

Office. For each category, we ensured that five trials of each type (good and bad

exemplars) were mismatched. There were thus 75% matched trials (15 trials each of

good and bad within each of the six scene categories) and 25% mismatched trials, for a

total of 90 matched trials and 30 mismatched trials. Instead of making a good or bad

judgment, at the end of each trial participants were prompted to respond "yes" or "no,"

with a button press, to the question of whether or not the picture had matched the cue.

Hand used to respond "yes" or "no" was counterbalanced.

<u>ERP Setup and Analysis</u>

EEG was recorded from 26 channels of passive electrodes that were equidistantly

arranged on the scalp, referenced online to the left mastoid and re-referenced offline to

the average of the left and right mastoids. Additional electrodes placed on the outer

cantus of each eye and on the orbital ridge below the left eye were used to monitor

saccadic eye movements and blinks. Impedances were kept below 5 KΩ for scalp

channels and 10 KΩ for eye channels. The signal was bandpass filtered online (0.02 Hz

- 100 Hz) and sampled at 250 Hz. Trials with artifacts due to horizontal eye movements

or signal drift were rejected using fixed thresholds calibrated for individual subjects.

Trials with blinks were either rejected, or, for subjects with higher numbers of blink

artifacts (12 in **Experiment 1** and 8 in **Experiment 2**), were corrected using a blink

correction algorithm (Dale, 1994). We confirmed that the analytical results were

unchanged if blinks were rejected instead of corrected. On average, in **Experiment 1**,

6.83% of good exemplar trials and 9.04% of bad exemplar trials were rejected due to

artifacts and no condition had fewer than 63 trials per subject in the analysis. In

Experiment 2, in the match condition, 10.8% of good exemplar trials and 11.09% of bad

exemplar trials were rejected due to artifacts and no condition had fewer than 56 trials

per subject in the analysis. In the mismatch condition, 10.38% of good exemplar trials

and 13.89% of bad exemplar trials were rejected due to artifacts and no condition had

fewer than 19 trials per subject in the analysis.

ERPs were epoched for a time period spanning 100 ms before stimulus onset to 920 ms

after stimulus onset, with the 100 ms prestimulus interval used as the baseline. This

processed signal was then averaged for each condition within each subject. A digital

bandpass filter (0.2 Hz - 30 Hz) was applied before measurements were taken from the

ERPs. Based on prior work showing that the N300 is frontally distributed and occurs

between 250 ms to 350 ms (Federmeier & Kutas, 2001; Schendan & Kutas, 2002,

2003), we measured N300 mean amplitudes in this time window across the 11 frontal

electrode sites: MiPf, LLPf, RLPf, LMPf , RMPf , LDFr , RDFr , LMFr , RMFr , LLFr , and

RLFr (first letter: R=right, L=left, Mi=midline; second letter: L=lateral, M=medial,

D=dorsal; Pf = prefrontal and Fr= frontal). Statistics were computed using R (R Core

Team, 2020). Specifically, we used the functions t.test, to compute t-tests, and ttestbf

(from the package: BayesFactor) to compute Bayes Factors. The t- test and Bayes

factor calculations compared the measured condition difference to 0. For within-subject

calculations of confidence intervals, we used the function summarySEwithin() that is

based on (Morey, 2008).

For completeness, we also analyzed two ERP components in the time-window after the

N300: the N400 and the Late Positive Complex (LPC). Prior work examining the N400 to

pictures has shown a frontal distribution (Ganis et al., 1996), and thus we again used the

11 frontal electrode sites, but now in the time-window 350-500 ms. For the LPC we

chose posterior sites in the time-window of 500-800 ms based on prior work

characterizing the distribution and timing of the LPC (Finnigan et al., 2002).

Acknowledgments
637

We would like to thank Yanqi Zhang for assistance with running subjects in **Experiment**

1, and Resh Gupta, and Nirupama Mehrotra for helping with **Experiment 1** data

collection. We also thank Rami Alsaqri, Johan Saelens, Daria Niescierowicz, and

Benjamin D. Schmitt for helping with data collection in **Experiment 2**. We would like to

acknowledge funding provided by ONR MURI (DMB) and by NIH (R01 AG026308) and

the James S. McDonnell foundation (KDF).

References

Boutonnet, B., & Lupyan, G. (2015). Words Jump-Start Vision: A Label Advantage in

Object Recognition. *Journal of Neuroscience*, *35*(25), 9329–9335.

https://doi.org/10.1523/JNEUROSCI.5111-14.2015

Caddigan, E., Choo, H., Fei-Fei, L., & Beck, D. M. (2017). Categorization influences

detection: A perceptual advantage for representative exemplars of natural scene

categories. *Journal of Vision*, *17*(1), 21. https://doi.org/10.1167/17.1.21

Caddigan, E., Walther, D. B., Fei-Fei, L., & Beck, D. M. (2010). Perceptual differences

between natural scene categories. OPAM 2010 18th Annual Meeting. *Visual*

Cognition, *18*(10), 1498–1502.

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of

cognitive science. *Behavioral and Brain Sciences*, *36*(03), 181–204.

https://doi.org/10.1017/S0140525X12000477

Cowell, R. A., Barense, M. D., & Sadil, P. S. (2019). A Roadmap for Understanding

Memory: Decomposing Cognitive Processes into Operations and Representations.

ENeuro, *6*(4). https://doi.org/10.1523/ENEURO.0122-19.2019

Cutler, R. A., Duff, M. C., & Polyn, S. M. (2019). Searching for Semantic Knowledge: A

Vector Space Semantic Analysis of the Feature Generation Task. *Frontiers in*

Human Neuroscience, *13*. https://doi.org/10.3389/fnhum.2019.00341

Dale, A. M. (1994). *Source localization and spatial discriminant analysis of event-*

related potentials: Linear approaches (brain cortical surface). Dissertation

Abstracts International.

Epstein, R., & Kanwisher, N. (1998). A cortical representation of the local visual

environment. *Nature*, *392*(6676), 598–601. https://doi.org/10.1038/33402

Federmeier, K. D., & Kutas, M. (2001). Meaning and modality: Influences of context,

semantic memory organization, and perceptual predictability on picture

processing. *Journal of Experimental Psychology: Learning, Memory, and*

Cognition, *27*(1), 202. http://psycnet.apa.org/journals/xlm/27/1/202/

Federmeier, K. D., & Kutas, M. (2002). Picture the difference: Electrophysiological

investigations of picture processing in the two cerebral hemispheres.

Neuropsychologia, *40*(7), 730–747.

http://kutaslab.ucsd.edu/people/kutas/pdfs/2002.N.730.pdf

Finnigan, S., Humphreys, M. S., Dennis, S., & Geffen, G. (2002). ERP 'old/new'effects:

Memory strength and decisional factor (s). *Neuropsychologia*, *40*(13), 2288–

2304. http://www.sciencedirect.com/science/article/pii/S0028393202001136

Friston, K. (2005). A theory of cortical responses. *Philosophical Transactions of the*

Royal Society B: Biological Sciences, *360*(1456), 815–836.

https://doi.org/10.1098/rstb.2005.1622

Ganis, G., Kutas, M., & Sereno, M. I. (1996). The Search for "Common Sense": An

Electrophysiological Study of the Comprehension of Words and Pictures in

Reading. *Journal of Cognitive Neuroscience*, *8*(2), 89–106.

https://doi.org/10.1162/jocn.1996.8.2.89

Gratton, C., Evans, K. M., & Federmeier, K. D. (2009). See what I mean? An ERP study

of the effect of background knowledge on novel object processing. *Memory &*

Cognition, *37*(3), 277–291. https://doi.org/10.3758/MC.37.3.277

Greene, M. R., & Hansen, B. C. (2020). Disentangling the Independent Contributions of

Visual and Conceptual Features to the Spatiotemporal Dynamics of Scene

Categorization. *The Journal of Neuroscience*, JN-RM-2088-19.

https://doi.org/10.1523/JNEUROSCI.2088-19.2020

Gregory, R. L. (1980). Perceptions as Hypotheses. *Philosophical Transactions of the*

Royal Society of London. B, Biological Sciences, *290*(1038), 181–197.

https://doi.org/10.1098/rstb.1980.0090

Helmholtz, H. von. (1925). *Treatise on physiological optics, Bd. 3: The perceptions of*

vision (English translation of the 3rd edition., Vol. 3). The Optical Society of

America. https://echo.mpiwg-

berlin.mpg.de/ECHOdocuView?url=/permanent/library/HS7FH69N/pageimg&to

cMode=thumbs&viewMode=index&pn=17&mode=imagepath

Hindy, N. C., Ng, F. Y., & Turk-Browne, N. B. (2016). Linking pattern completion in the

hippocampus to predictive coding in visual cortex. *Nature Neuroscience*, *19*(5),

665–667. https://doi.org/10.1038/nn.4284

Hochberg, J. (1981). On cognition in perception: Perceptual coupling and unconscious

inference. *Cognition*, *10*(1), 127–134. https://doi.org/10.1016/0010-

0277(81)90035-4

Huang, Y., & Rao, R. P. N. (2011). Predictive coding. *Wiley Interdisciplinary Reviews:*

Cognitive Science, *2*(5), 580–593. https://doi.org/10.1002/wcs.142

Kok, P., Jehee, J. F. M., & de Lange, F. P. (2012). Less is more: Expectation sharpens

representations in the primary visual cortex. *Neuron*, *75*(2), 265–270.

https://doi.org/10.1016/j.neuron.2012.04.034

Kutas, M., & Federmeier, K. D. (2011). Thirty years and counting: Finding meaning in

the N400 component of the event related brain potential (ERP). *Annual Review of*

Psychology, *62*, 621–647. https://doi.org/10.1146/annurev.psych.093008.131123

Lange, F. P. de, Heilbron, M., & Kok, P. (2018). How Do Expectations Shape

Perception? *Trends in Cognitive Sciences*, *22*(9), 764–779.

https://doi.org/10.1016/j.tics.2018.06.002

Lauer, T., Willenbockel, V., Maffongelli, L., & Võ, M. L.-H. (2020). The influence of

scene and object orientation on the scene consistency effect. *Behavioural Brain*

Research, *394*, 112812. https://doi.org/10.1016/j.bbr.2020.112812

Lupyan, G. (2017). Changing What You See by Changing What You Know: The Role of

Attention. *Frontiers in Psychology*, *8*. https://doi.org/10.3389/fpsyg.2017.00553

Mcpherson, W. B., & Holcomb, P. J. (1999). An electrophysiological investigation of

semantic priming with pictures of real objects. *Psychophysiology*, *36*(1), 53–65.

http://onlinelibrary.wiley.com/doi/10.1017/S0048577299971196/abstract

Morey, R. D. (2008). Confidence intervals from normalized data: A correction to

Cousineau (2005)." 4.2 (2008):61. Web. *Reason*, 61.

Mudrik, L., Lamy, D., & Deouell, L. Y. (2010). ERP evidence for context congruity

effects during simultaneous object–scene processing. *Neuropsychologia*, *48*(2),

507–517. https://doi.org/10.1016/j.neuropsychologia.2009.10.011

Norman, K. A., & O'Reilly, R. C. (2003). Modeling hippocampal and neocortical

contributions to recognition memory: A complementary-learning-systems

approach. *Psychological Review*, *110*(4), 611–646. https://doi.org/10.1037/0033-

295X.110.4.611

Oldfield, R. C. (1971). The assessment and analysis of handedness: The Edinburgh

inventory. *Neuropsychologia*, *9*(1), 97–113. https://doi.org/10.1016/0028-

3932(71)90067-4

Oxner, M., Rosentreter, E. T., Hayward, W. G., & Corballis, P. M. (2019). Prediction

errors in surface segmentation are reflected in the visual mismatch negativity,

independently of task and surface features. *Journal of Vision*, *19*(6), 9–9.

https://doi.org/10.1167/19.6.9

Pietrowsky, R., Kuhmann, W., Krug, R., Molle, M., Fehm, H. L., & Born, J. (1996).

Event-related brain potentials during identification of tachistoscopically presented

pictures. *Brain and Cognition*, *32*(3), 416–428.

http://www.sciencedirect.com/science/article/pii/S0278262696900743

R Core Team. (2020). *R: A language and environment for statistical computing. R

Foundation for Statistical Computing, Vienna, Austria.* https://www.R-

project.org/

Rao, R. P. N., & Ballard, D. H. (1999). Predictive coding in the visual cortex: A

functional interpretation of some extra-classical receptive-field effects. *Nature

Neuroscience*, *2*(1), 79–87. https://doi.org/10.1038/4580

Rock, I. (1983). *The Logic Of Perception*. Cambridge: MIT Press.

Schendan, H. E. (2019). Memory influences visual cognition across multiple functional

states of interactive cortical dynamics. In *Psychology of Learning and Motivation*

(Vol. 71, pp. 303–386). Elsevier. https://doi.org/10.1016/bs.plm.2019.07.007

Schendan, H. E., & Kutas, M. (2002). Neurophysiological evidence for two processing

times for visual object identification. *Neuropsychologia*, *40*(7), 931–945.

http://www.sciencedirect.com/science/article/pii/S0028393201001762

Schendan, H. E., & Kutas, M. (2003). Time course of processes and representations

supporting visual object identification and memory. *Journal of Cognitive*

Neuroscience, *15*(1), 111–135.

http://www.mitpressjournals.org/doi/abs/10.1162/089892903321107864

Schendan, H. E., & Kutas, M. (2007). Neurophysiological evidence for the time course of

activation of global shape, part, and local contour representations during visual

object categorization and memory. *Journal of Cognitive Neuroscience*, *19*(5),

734–749. http://www.mitpressjournals.org/doi/abs/10.1162/jocn.2007.19.5.734

Schendan, H. E., & Lucia, L. C. (2010). Object-sensitive activity reflects earlier

perceptual and later cognitive processing of visual objects between 95 and 500ms.

Brain Research, *1329*, 124–141. https://doi.org/10.1016/j.brainres.2010.01.062

Schendan, H. E., & Maher, S. M. (2009). Object knowledge during entry-level

categorization is activated and modified by implicit memory after 200 ms.

NeuroImage, *44*(4), 1423–1438.

https://doi.org/10.1016/j.neuroimage.2008.09.061

Sehatpour, P., Molholm, S., Javitt, D. C., & Foxe, J. J. (2006). Spatiotemporal dynamics

of human object recognition processing: An integrated high-density electrical

mapping and functional imaging study of "closure" processes. *NeuroImage*,

29(2), 605–618. https://doi.org/10.1016/j.neuroimage.2005.07.049

Smith, M. E., & Loschky, L. C. (2019). The influence of sequential predictions on scene-

gist recognition. *Journal of Vision*, *19*(12), 14–14.

https://doi.org/10.1167/19.12.14

Spratling, M. W. (2010). Predictive Coding as a Model of Response Properties in

Cortical Area V1. *Journal of Neuroscience*, *30*(9), 3531–3543.

https://doi.org/10.1523/JNEUROSCI.4911-09.2010

Spratling, M. W. (2016). Predictive coding as a model of cognition. *Cognitive*

Processing, *17*(3), 279–305. https://doi.org/10.1007/s10339-016-0765-6

Summerfield, C., Egner, T., Greene, M., Koechlin, E., Mangels, J., & Hirsch, J. (2006).

Predictive Codes for Forthcoming Perception in the Frontal Cortex. *Science*,

314(5803), 1311–1314. https://doi.org/10.1126/science.1132028

Torralbo, A., Walther, D. B., Chai, B., Caddigan, E., Fei-Fei, L., & Beck, D. M. (2013).

Good Exemplars of Natural Scene Categories Elicit Clearer Patterns than Bad

Exemplars but Not Greater BOLD Activity. *PLoS ONE*, *8*(3), e58594.

https://doi.org/10.1371/journal.pone.0058594

Vo, M. L.-H., & Wolfe, J. M. (2013). Differential Electrophysiological Signatures of

Semantic and Syntactic Scene Processing. *Psychological Science*, *24*(9), 1816–

1823. https://doi.org/10.1177/0956797613476955

Voss, J. L., Federmeier, K. D., & Paller, K. A. (2012). The potato chip really does look

like Elvis! Neural hallmarks of conceptual processing associated with finding

novel shapes subjectively meaningful. *Cerebral Cortex (New York, N.Y.: 1991)*,

22(10), 2354–2364. https://doi.org/10.1093/cercor/bhr315

Voss, J. L., & Paller, K. A. (2007). Neural correlates of conceptual implicit memory and

their contamination of putative neural correlates of explicit memory. *Learning &*

Memory, *14*(4), 259–267. https://doi.org/10.1101/lm.529807

Voss, J. L., Schendan, H. E., & Paller, K. A. (2010). Finding meaning in novel geometric

shapes influences electrophysiological correlates of repetition and dissociates

perceptual and conceptual priming. *NeuroImage*, *49*(3), 2879–2889.

https://doi.org/10.1016/j.neuroimage.2009.09.012

The N300: An Index For Predictive Coding Of Complex Visual Objects and Scenes

Manoj Kumar, Kara D. Federmeier, Diane M. Beck

Corresponding Author: Manoj Kumar

Email: mk35@princeton.edu

This PDF file includes:

 Supplementary Information

Experiment 1

N300 Distributional Analysis

To compare the N300 in our experiment with its characterization in the existing literature,

we also performed an ANOVA in the time-window 250-350 ms across the 16 scalp

channels that could be divided into 2 levels of Hemisphere (right and left scalp sites), 2

levels of Laterality (lateral and medial scalp sites), and 4 levels of Anteriority (prefrontal,

frontal, central/parietal, and occipital scalp sites). In addition to confirming the main

effect of Good vs. Bad (bad larger than good) $(F(1,19) =11.97; p=0.0026, E=1)$, there

were interactions of Good/Bad with both Laterality $(F(1,19)=7.35; p=0.014; E=1)$ and

Anteriority $(F(3,57) =11.97; p<0.0001; E=0.5336)$, as well as three-way interactions:

Good/Bad x Hemisphere x Anteriority $(F(3,57)=3.13; p=0.0324; E=0.8353)$, and

Good/Bad x Laterality x Anteriority $(F(3,57)=6.79; p=0.0005; E=0.7571)$. Overall, N300

responses were observed over both left and right hemisphere sites and were largest

over the front of the head and larger over medial compared to lateral electrode sites.

Over frontal sites, the effect of Laterality was more pronounced and there was a

tendency for larger effects over left compared to right hemisphere sites. These results

show that the topographic distribution of the N300 effect for natural scenes has a similar

distributional profile as the N300 for objects (Schendan & Kutas, 2002, 2003, 2007).

Post N300 Components

Table S1. The grand average mean values in the N400 time-window (350-500 ms),

shown for 11 frontal electrode sites along with t-test and Bayes factor values. The N400

for the bad exemplars is larger (more negative) than that for the good exemplars. The t-

test and Bayes factor calculations compared the within-subject Good/Bad difference to

0.

Condition	N	Mean (μV)	Bad/Good Difference Mean (μV)	Bad/Good Difference 95% C.I.	t(19)	p	Bayes Factor
Bad	20	-3.3±0.96					
			-1.14	-1.78 to -0.50	-3.74	0.0014	27.3
Good	20	-2.2±0.96					

Note: ± values reflect the normed standard deviation within subjects.

LPC

Table S2: The grand average mean values, in the LPC time-window (500-800 ms),

shown for 15 posterior electrode sites (LMCe, RMCe, LDCe, RDCe, MiCe, MiPa, LLTe,

RLTe, LDPa, RDPa, LLOc, RLOc, LMOc, RMOc, MiOc) along with t-test and Bayes

factor values. The LPC for bad exemplars has a smaller mean amplitude than for the

good exemplars. The t- test and Bayes factor calculations compared the within subject

Good/Bad difference to 0.

Condition	N	Mean (μV)	Bad/Good Difference Mean (μV)	Bad/Good Difference 95% C.I.	t(19)	p	Bayes Factor
Bad	20	3.3±1.1					
			-1.17	-1.91 to -0.43	-3.3	0.0036	12.1
Good	20	4.5±1.1					

Note: ± values reflect the normed standard deviation within subjects.

Experiment 2

N300 Distributional Analysis with Cuing

A novel feature of **Experiment 2** was the use of a verbal precue. Prior work on the

N300, including our own **Experiment 1**, has not used a verbal precue. Thus, to see how

the distributional properties of the N300 effect under cued conditions compare to that in

prior work, we performed an ANOVA analysis using identical electrode sites as in the

ANOVA analysis for **Experiment 1**, with identical groupings: 2 levels of Hemisphere

(right and left scalp sites), 2 levels of Laterality (lateral and medial scalp sites), and 4

levels of Anteriority (prefrontal, frontal, central/parietal, and occipital scalp sites). We

replicate the main effect of **Experiment 1** with Good vs. Bad (bad larger than good;

$F(1,19) = 15.34$; $p= 0.0009$, E=1). The topographic distribution of this effect is significant

in the following interactions: Good/Bad x Hemisphere (F(1,19) =5; p= 0.0375, E=1);

Good/Bad x Laterality (F(1,19) =21.1; p =0.0002, E=0.5336); Good/Bad x Anteriority

(F(3,57) =7.13; p =0.0004, E=0.4030). N300 effects were observed over both left and

right hemisphere sites, with the left hemisphere showing somewhat larger effects as

compared to the right hemisphere, and, as in **Experiment 1**, were larger over medial

than lateral sites and larger over the front of the head.

We also see an interaction of Good/Bad x Cueing (F(1,19) =5.87; p= 0.0255, E=1) with

large N300 effects the stimuli matched the cue, but negligible effects in the mismatch

condition. There was a 3-way interaction of Good/Bad x Cueing x Laterality (F(1,19)

=4.83; p= 0.0406, E=1), because N300 effects were larger over medial than lateral sites

in the match condition, with the effect being eliminated in the mismatch condition.

N400: The Effects of Cuing

The N400 indexes a match to semantic expectancy, and we performed an ANOVA

analysis in the N400 time-window (350-500 ms) to examine the effects of semantic

expectancy in **Experiment 2**, although, we do not claim that the N400 effects are

completely independent of the preceding N300 effects in our experiment. Prior work has

shown that the N300 and N400 are functionally dissociable (Federmeier & Kutas, 2002;

Gratton et al., 2009), but their similar response pattern to, e.g., incongruent and

congruent items, can make separating them challenging under some circumstances

(Draschkow et al., 2018). For the N400, we see a main effect of Cuing (F =13.35; p

=0.0017; E =1) with a smaller N400 amplitude for the matched condition as compared to

the mismatched condition. We also see a significant interaction of Good/Bad x Cuing (F

=18.56; p =0.0004; E =1), with the good exemplars in the match condition having the

smallest amplitude as compared to the good and bad exemplars in the match- and-

mismatched condition. There is also a 3-way interaction of Good/Bad x Laterality x

Anteriority (F(3,57) = 2.96; p = 0.0411; E = 0.8875) in the N400 time-window.

Table S3. The grand average mean values, in the N400 time-window (350-500 ms),

shown for 11 frontal electrode sites. The t- test and Bayes factor calculations compared

the within subject Good/Bad difference to 0.

Condition	Cue	N	Mean (μV)	Difference (μV)	Bad/Good Difference 95% C.I.	t(19)	p	Bayes Factor
Bad	Match	20	-5.3±0.98	-1.82	-2.5 to -1.15	-5.67	1.8E-05	1287.4
Good	Match	20	-3.5±1.41					
Bad	Mismatch	20	-4.7±1.65	-0.47	-0.42 to 2.25	-1.44	0.17	0.56
Good	Mismatch	20	-5.6±2.06					

Note: ± values reflect the normed standard deviation within subjects.

LPC

For the LPC, we examined differences in the 500-800 ms time window, encompassing

the Late Positive Complex (LPC), over 15 posterior sites (identical to the sites for the

analysis in **Experiment 1**). We replicate the main effect of Good/Bad with a larger LPC

amplitude for good as compared to bad exemplars (F = 4.84; p = 0.0403; E =1). The

LPC is known to index confidence in decision making (Finnigan et al., 2002) and the

main effect of Cuing in **Experiment 2** aligns with this understanding, with the match

condition showing a larger LPC amplitude as compared to the mismatch condition (F =

19.69; p =0.0003; E=1). The interaction of Good/Bad x Cuing is also significant (F =9.82;

p =0.0003; E =1) with the good match having the largest LPC amplitude as compared to

the Good mismatch, Bad match, and Bad mismatch conditions.

Table S4. The grand average mean values, in the LPC time-window (500-800 ms),

shown for 15 posterior electrode sites. The t- test and Bayes factor calculations

compared the Good/Bad difference to 0.

Condition	Cue	N	Mean (μV)	Mean Bad/Good Difference (μV)	Bad/Good Difference 95% C.I.	t(19)	p	Bayes Factor
Bad	Match	20	0.4±0.98					
Good	Match	20	2.7±1.09	-2.24	-2.94 to 1.54	-6.69	2.1E-06	9014.4
Bad	Mismatch	20	0.9±1.66					
Good	Mismatch	20	0.22±1.61	0.68	-0.56 to 1.93	1.15	0.26	0.41

Note: ± values reflect the normed standard deviation within subjects.

SI References

Draschkow, D., Heikel, E., Võ, M. L.-H., Fiebach, C. J., & Sassenhagen, J. (2018). No

evidence from MVPA for different processes underlying the N300 and N400

incongruity effects in object-scene processing. *Neuropsychologia*, *120*, 9–17.

https://doi.org/10.1016/j.neuropsychologia.2018.09.016

Federmeier, K. D., & Kutas, M. (2002). Picture the difference: Electrophysiological

investigations of picture processing in the two cerebral hemispheres.

Neuropsychologia, *40*(7), 730–747.

http://kutaslab.ucsd.edu/people/kutas/pdfs/2002.N.730.pdf

Finnigan, S., Humphreys, M. S., Dennis, S., & Geffen, G. (2002). ERP 'old/new' effects:

Memory strength and decisional factor (s). *Neuropsychologia*, *40*(13), 2288–

2304. http://www.sciencedirect.com/science/article/pii/S0028393202001136

Gratton, C., Evans, K. M., & Federmeier, K. D. (2009). See what I mean? An ERP study

of the effect of background knowledge on novel object processing. *Memory &*

Cognition, *37*(3), 277–291. https://doi.org/10.3758/MC.37.3.277

Schendan, H. E., & Kutas, M. (2002). Neurophysiological evidence for two processing

times for visual object identification. *Neuropsychologia*, *40*(7), 931–945.

http://www.sciencedirect.com/science/article/pii/S0028393201001762

Schendan, H. E., & Kutas, M. (2003). Time course of processes and representations

supporting visual object identification and memory. *Journal of Cognitive*

Neuroscience, *15*(1), 111–135.

http://www.mitpressjournals.org/doi/abs/10.1162/089892903321107864

Schendan, H. E., & Kutas, M. (2007). Neurophysiological evidence for the time course of

activation of global shape, part, and local contour representations during visual

object categorization and memory. *Journal of Cognitive Neuroscience*, *19*(5),

734–749. http://www.mitpressjournals.org/doi/abs/10.1162/jocn.2007.19.5.734