Influence of sensory modality and control dynamics on human path integration

Akis Stavropoulos[1*], Kaushik J. Lakshminarasimhan[2*], Jean Laurens[3], Xaq Pitkow[4,5], Dora E. Angelaki[1,4,6]

[1] Center for Neural Science, New York University, New York, NY, USA

[2] Center for Theoretical Neuroscience, Columbia University, New York, NY, USA

[3] Ernst Strüngmann Institute (ESI) for Neuroscience in Cooperation with Max Planck Society, Frankfurt, Germany

[4] Department of Neuroscience, Baylor College of Medicine, Houston, TX, USA

[5] Department of Electrical and Computer Engineering, Rice University, Houston, TX, USA

[6] Tandon School of Engineering, New York University, New York, NY, USA

* Equal Author Contribution

Correspondence:

Prof. Dora E. Angelaki

Email: da93@nyu.edu

Center for Neural Science, Mayer 901

New York University, NY 10003

Abstract

Path integration is a widely-studied sensorimotor computation to infer latent dynamical states. How different sensory pathways and movement dynamics constrain this computation is unclear. We studied the influence of sensory observation (visual/vestibular) and latent control dynamics (velocity/acceleration) on human path integration using a novel motion-cueing algorithm. Sensory modality and control dynamics were both varied randomly across trials, as participants controlled a joystick to steer to a memorized target location in virtual reality. Visual and vestibular steering cues allowed comparable accuracies only when participants controlled their acceleration, suggesting that vestibular signals, on their own, fail to support accurate path integration in the absence of sustained acceleration. Nevertheless, performance in all conditions was highly sensitive to the underlying control dynamics, a result that was well explained by a bias in the dynamics estimation. This work demonstrates that people need an accurate internal model of control dynamics when navigating in volatile environments.

Introduction

Imagine driving a car on a muddy or icy road, where steering dynamics can change rapidly. To avoid crashing, one must rapidly infer the new dynamics and respond appropriately to keep the car on the desired path. Conversely, when you drive out of an ice patch, control dynamics change again, compelling you to re-adjust your steering. The quality of sensory cues may also vary depending on environmental factors (e.g. reduced visibility in fog or twilight, sub-threshold vestibular stimulation under near-constant travel velocity). Humans are adept at using time-varying sensory cues to adapt quickly to a wide range of latent control dynamics in volatile environments. However, the relative contributions of different sensory modalities and the precise impact of latent

control dynamics on goal-directed navigation remain poorly understood. Here we study this using path integration.

Path integration, a natural computation in which the brain uses dynamic sensory cues to infer the evolution of latent world states to continuously maintain a self-position estimate, has been studied in humans, but past experimental paradigms imposed several constraints. First, in many tasks, the motion was passive and/or restricted along predetermined, often one-dimensional, trajectories (Klatzky et al., 1998; Jürgens & Becker, 2006; Petzschner & Glasauer, 2011; Campos et al., 2012; Tramper & Medendorp, 2015). Second, unlike time-varying actions that characterize navigation under natural conditions, participants' responses were often reduced to single, binary end-of-trial decisions (Horst et al., 2015; Chrastil et al., 2016; Koppen et al., 2019). Third, even studies that explored contributions of different sensory modalities in naturalistic settings failed to properly disentangle vestibular from motor cues generated during active locomotion (Kearns et al., 2002; Campos et al., 2010; Bergmann et al., 2011; Chen et al., 2017). Furthermore, different constraints have led to conflicting findings on the contribution of vestibular cues to path integration (Jürgens & Becker, 2006; Campos et al., 2010; Horst et al., 2015; Tramper & Medendorp, 2015; Koppen et al., 2019; Chrastil et al., 2019).

There is a tight link between path integration and spatial navigation on the one hand and internal models and control dynamics on the other. To accurately estimate self-motion, we rely not only on momentary sensory evidence but also on knowledge of motion dynamics. Knowledge of the control dynamics makes the sensory consequences of actions predictable, allowing for more dexterous steering. However, although there is a large body of research focused on dynamics and adaptation for motor control (Shadmehr & Mussa-Ivaldi, 1994; Lackner & Dizio, 1994; Krakauer et al., 1999; Takahashi et al., 2001; Burdet et al., 2001; Kording et al., 2007; Berniker et al., 2010), studies of perceptual inference of latent dynamics during navigation have been limited. For example, it has previously been shown that the history of linear (Petzschner & Glasauer, 2011) and angular (Prsa et al., 2015) displacements affects how participants process sensory input in the current trial. Moreover, we previously observed that false expectations about the magnitude of self-motion can have a drastic effect on path integration (Lakshminarasimhan et al., 2018). We wondered whether prior expectations about the *temporal dynamics* of self-motion can also propagate over time to influence navigation.

To explore how temporal dynamics influence navigation across sensory modalities (visual, vestibular, or both), we have built upon a naturalistic paradigm of path integration in which participants navigate to a briefly-cued target location using a joystick to control their velocity in a virtual visual environment (Lakshminarasimhan et al., 2018). Here, we generalize this framework by varying both the control dynamics (joystick control varied along a continuum from velocity to acceleration) and the available sensory cues (vestibular, visual, or both). To achieve this, we designed a motion-cueing algorithm (MC) to render self-motion stimuli according to a joystick control input of maintained accelerations while maintaining correspondence between visual (optic flow) and inertial cues. Using a motion platform with six degrees of freedom to approximate the accelerations that an observer would feel under the imposed control dynamics, we ensured that the MC algorithm would generate matching visual and vestibular cues to closely approximate the desired self-motion (see **Methods**, **Suppl. Fig. S2**). The development of the MC algorithm represents a departure from classical paradigms of navigation research in humans (Chrastil et al., 2019; Israël et al., 1996; Koppen et al., 2019; Seemungal et al., 2007; Horst et al., 2015), as it helps eliminate artificial constraints while still allowing for the isolation of different sensory contributions, most notably vestibular/somatosensory cues, during active, volitional, steering.

We found that participants' steering responses were biased (undershooting), and the biases were more prominent in the vestibular condition. Furthermore, steering biases were strongly modulated by the underlying control dynamics. These findings suggest that inertial cues alone lack the reliability to support accurate path integration

81 in the absence of sustained acceleration, and that an accurate internal model of control dynamics is needed to
82 make use of sensory observations when navigating in volatile environments.

Figure 1: (A) Experimental set up. Participants sit on a 6-degrees-of-freedom motion platform with a coupled rotator that allowed unlimited yaw displacements. Visual stimuli were back-projected on a screen (see **Methods**). The joystick participants used to navigate in the virtual world is mounted in front of the participants' midline. **(B)** Schematic view of the experimental virtual environment. Participants use a joystick to navigate to a cued target (*yellow disc*) using optic flow cues generated by ground plane elements (*brown triangles; Visual and Combined conditions only*). The ground plane elements appeared transiently at random orientations to ensure they cannot serve as spatial or angular landmarks. **(C) Left:** Overhead view of the spatial distribution of target positions across trials. *Red dot* shows the starting position of the participant. Positions were uniformly distributed within the participant's field of view. **Right:** Movement trajectories of one participant during a representative subset of trials. Starting location is denoted by the *red dot*. **(D)** Control dynamics. **Left:** Simulated maximum pulse joystick input (*max joystick input = 1*) (see also **Fig. S1**). This input is lowpass filtered to mimic the existence of inertia. The time constant of the filter varies across trials (time constant τ). In our framework, maximum velocity also varies according to the time constant τ of each trial to ensure comparable travel times across trials (see **Methods** – *Control Dynamics*). **Right:** the same joystick input (scaled by the corresponding maximum velocity for each τ) produces different velocity profiles for different time constants ($\tau = 0.6s$ corresponds to *velocity control*; $\tau = 3s$ corresponds to *acceleration control*; τ values varied randomly along a continuum across trials, see **Methods**). Also depicted is the brief cueing period of the target at the beginning of the trial (gray zone, *1 second* long). **(E)** Markov decision process governing self-motion sensation (**Methods** – Equation 1). u, v, and o denote joystick input, movement velocity, and sensory observations, respectively, and subscripts denote time indices. Note that due to the 2-D nature of the task, these variables are all vector-valued, but we depict them as scalars for the purpose of illustration. By varying the time constant, we manipulated the control dynamics (*i.e.*, the degree to which the current velocity carried over to the future, indicated by the thickness of the horizontal lines) along a continuum such that the joystick position primarily determined either the participant's velocity (top; *thin lines*) or acceleration (bottom; *thick lines*) (compare with **(D)** top and bottom, respectively). Sensory observations were available in the form of vestibular (left), optic flow (middle), or both (right).

Results
Task structure
85 Human participants steered towards a briefly-cued target location on a virtual ground plane, with varying sensory
86 conditions and control dynamics interleaved across trials. Participants sat on a motion platform in front of a screen

displaying a virtual environment (**Fig. 1A**). Stereoscopic depth cues were provided using polarizing goggles. On each trial, a circular target appeared briefly at a random location (drawn from a uniform distribution within the field of view; **Fig. 1B,C**) and participants had to navigate to the remembered target location in the virtual world using a joystick to control linear and angular self-motion. The virtual ground plane was defined visually by a texture of many small triangles which independently appeared only transiently; they could therefore only provide optic-flow information and could not be used as landmarks. The self-motion process evolved according to Markov dynamics, such that the movement velocity at the next time step depended only on the current joystick input and the current velocity (**Methods** – Equation 1).

A time constant for the control filter (control timescale) governed the control dynamics: in trials with a *small* time constant and a fast filter, joystick position essentially controlled velocity, providing participants with responsive control over their self-motion, resembling regular road-driving dynamics. However, when the time constant was *large* and the control filter was slow, joystick position mainly controlled acceleration, mimicking high inertia under viscous damping, as one would experience on an icy road where steering is sluggish (**Fig. 1D** right and **1E** – top vs bottom). For these experiments, as the control timescale changed, the maximum velocity was adjusted so that the participant could reach the typical target in about the same amount of time on average. This design ensured that the effect of changing control dynamics would not be confused with the effect of integrating sensory signals over a longer or shorter time.

Concurrently, we manipulated the modality of sensory observations to generate three conditions: 1) a *vestibular* condition in which participants navigated in darkness, and sensed only the platform's motion (note that this condition also engages somatosensory cues, see **Methods**), 2) a *visual* condition in which the motion platform was stationary and velocity was signaled by optic flow, and 3) a *combined* condition in which both cues were available (**Fig. 1E** – left to right). Across trials, sensory conditions were randomly interleaved while manipulation of the time constant followed a bounded random walk (**Methods** – Equation 2). Participants did not receive any performance-related feedback.

Effect of sensory modality

We first compared the participants' stopping locations on each trial to the corresponding target locations, separately for each sensory condition. We calculated the radial distance $\tilde{r}$ and angular eccentricity $\tilde{\theta}$ of the participants' final position relative to the initial position (**Fig. 2A**), and compared them to the initial target distance r and angle θ, as shown for all trials (all time constants together) of a typical participant in **Fig. 2B, C**. This revealed biased performance with notable undershooting (participants stopped short of the true target location), in both distance and angle, which was well described by a linear model without intercept (Radial Distance $R^2 \pm$ standard deviation – vestibular: 0.39±0.05, visual: 0.67±0.09, combined: 0.64±0.10; Angular Eccentricity $R^2 \pm$ standard deviation – vestibular: 0.80±0.14, visual: 0.96±0.03, combined: 0.97±0.02. Adding a non-zero intercept term offered negligible improvement; Radial Distance ΔR^2 – vestibular: 0.02±0.02, visual: 0.03±0.03, combined: 0.03±0.02; Angular Eccentricity ΔR^2 – vestibular: 0.02±0.03, visual: 0.01±0.01, combined: 0.01±0.01). We refer to the slope of the linear regression as '*response gain*': a response gain of unity indicates no bias, while gains larger (smaller) than unity indicate overshooting (undershooting). As shown with the example participant in **Fig. 2B, C**, there was substantial undershooting in the vestibular condition, whereas performance was relatively unbiased under the combined and visual conditions. These results were consistent across participants (**Fig. 2D**, mean radial gain ± standard deviation – vestibular: 0.76±0.25, visual: 0.88±0.23, combined: 0.85±0.22, mean angular gain ± standard deviation – vestibular: 0.79±0.22, visual: 0.98±0.14, combined: 0.95±0.12).

Figure 2: (A) Geometric definition of analysis variables. **(B), (C)** Example participant: Comparison of the radial distance $\tilde{r}$ of an example participant's response (final position) against the radial distance r of the target (B), as well as the angular eccentricity of the participant's response $\tilde{\theta}$ versus target angle θ (C), across all trials for one participant, colored according to the sensory condition (*green: vestibular, orange: visual, purple:* combined visual and vestibular). Radial and angular response gains were defined as the slope of the corresponding regressions. Black dashed lines show unity slope, and the solid lines represent slopes of the regression fits (intercept set to 0). **(D)** All participants: Radial and angular gains in each sensory condition plotted for each individual participant. *Ellipses* show 68% confidence intervals of the distribution of data points for the corresponding sensory condition. *Diamonds* (centers of the ellipses) represent the mean radial and angular response gains across participants. Dashed lines indicate unbiased radial or angular position responses. Solid diagonal line has unit slope.

Effect of control dynamics

To examine whether control dynamics affected the response gain, we performed three complementary analyses. First, we recomputed response gains by stratifying the trials into three groups of equal size based on the time constants. We found that smaller time constants (velocity control) were associated with smaller response gains (**Fig. 3A**; **Table 1**). This relationship was most pronounced in the vestibular condition, where larger time constants (acceleration control) resulted in better (closer to ideal) performance (**Fig. 3A**, green; see Discussion). Control dynamics had a smaller but considerable effect on steering responses in the visual and combined conditions, with participants exhibiting modest overshooting (undershooting) when the time constant was large (small) (**Fig. 3A**, orange/purple).

Second, we performed a fine-grained version of the above analysis by computing residual errors, *i.e.* deviation from the mean responses predicted using target location as a predictor (**Methods** – Equation 3). We found a significant correlation between residual errors and the time constant across trials (**Fig. 3B and C**, **Table 2**, see **Methods**). This correlation was substantially stronger in the vestibular condition (Mean Pearson's $r \pm$ SEM: Radial component – vestibular: 0.52±0.02, visual: 0.36±0.03, combined: 0.37±0.03; Angular component – vestibular: 0.23±0.02, visual: 0.23±0.03, combined: 0.26±0.03). Thus, for a given target distance, participants tended to travel further when the time constant was larger (acceleration control).

Third, to quantify the contribution of the time constant in the participants' responses, we expanded the linear model to accommodate a dependence of response (final stopping position) on the target location, the time constant, and the interaction between the two variables. A partial correlation analyses revealed that the time constant contributed substantially to participants' response gain, albeit only through the interaction term (**Suppl. Fig. S3**; see **Methods** – Equation 4). Again, the contribution of the time constant-dependent term was much greater for the vestibular condition (**Fig. 3D**), especially for the radial distance (*p*-values of difference in coefficient values across modalities obtained by a paired *t*-test − Radial: vestibular vs visual: $p < 10^{-4}$, vestibular vs combined: $p < 10^{-4}$; Angular: vestibular vs visual: $p = 0.016$, vestibular vs combined: $p = 0.013$). Thus, all

three independent analyses revealed a substantial influence of control dynamics on steering response gain, which was exaggerated for the vestibular, as compared to the visual and combined conditions.

Figure 3: Effect of control dynamics on participants' responses. (A) Participant average of radial and angular response gains in each condition, with trials grouped into tertiles of increasing time constant τ. Error bars denote ±1 SEM. **(B)** Effect of time constant τ on radial (**left**) and angular (**right**) residual error, for an example participant. *Solid lines* represent linear regression fits and *ellipses* the 68% confidence interval of the distribution for each sensory condition. *Dashed lines* denote zero residual error (*i.e.* stopping location matches mean response) **(C)** Correlations of radial (ε_r) and angular (ε_θ) residual errors with the time constant for all participants. *Ellipses* indicate the 68% confidence intervals of the distribution of data points for each sensory condition. Solid diagonal line has unit slope. Across participants, radial correlations, which were larger for the vestibular condition, were greater than angular correlations (See also **Table 2**). **(D)** Linear regression coefficients for the prediction of participants' response location (final position: $\tilde{r}, \tilde{\theta}$; **left** and **right**, respectively) from initial target location (r, θ) and the interaction between initial target location and the time constant ($r\tau, \theta\tau$) (all variables were standardized before regressing, see **Methods**). *Asterisks* denote statistical significance of the difference in coefficient values of the interaction terms across sensory conditions (paired t-test; *: p<0.05, **: p<0.01, ***: p<0.001; *see* main text). *Error bars* denote ±1 SEM. Note a qualitative agreement between the terms that included target location only and the gains calculated with the simple linear regression model (**Fig. 2B**).

We have shown previously that accumulating sensory noise over an extended time (~10s) would lead to a large uncertainty in the participant's beliefs about their position, causing them to undershoot (Lakshminarasimhan et al. 2018). The exact amount of undershooting depends both on the reliability of self-motion cues, which determines the instantaneous uncertainty in the self-motion estimate, and on travel duration, which governs how much uncertainty is accumulated while navigating to the target. The observed differences in navigation performance across sensory modalities can be readily attributed to greater measurement noise (lower reliability) in vestibular signals. On the other hand, we observed performance differences across control dynamics within each sensory modality, so those differences cannot be attributed to differences in the reliability of self-motion cues (instantaneous uncertainty). However, it might seem that this effect of control dynamics must be due to either differences in travel duration or velocity profiles, which would both affect the accumulated uncertainty. The first is unlikely because we adjusted stimulus parameters to ensure that the travel time and average velocity were similar across different control dynamics (**Suppl. Fig. S4A**, **Methods** – Equation 1.2-1.10). The latter is also an

unlikely explanation since the expected effect of the different velocity profiles on the participants' responses is the opposite of the observed effect of the control dynamics (**Suppl. Fig. S4B**). Consequently, unlike the effect of sensory modality on response gain, neither instantaneous nor accumulated differences in the uncertainty can fully account for the influence of control dynamics, *i.e.* the time constant. Instead, we will now show that the data are well explained by strong prior expectations about motion dynamics that cause a bias in estimating the time constant.

Modelling the effect of control dynamics across sensory modalities

Figure 4: (A) *Left*: Illustration of the Bayesian estimator model. We fit three parameters: the standard deviation of likelihood and prior ($\sigma_{likelihood}$, σ_{prior}) and the mean of the prior (μ_{prior}) of the normally distributed variable $\varphi = \log \tau$ (*black dotted box*). Likelihood function is centered on the log-transformation of the actual τ, $\varphi^* = \log \tau^*$ (*Black dashed line*). The time constant estimate $\hat{\tau}$ was chosen to be the median of the distribution over τ, which corresponds to the median $\hat{\varphi}$ over φ, $\hat{\tau} = \exp(\hat{\varphi})$, (*red dotted box; red dashed line*; see **Methods**). *Middle*: Control dynamics implied by the actual time constant τ (top; gray shade) and the estimated time constant $\hat{\tau}$ (bottom; red shade). u, v, and o denote joystick input, movement velocity, and sensory observations respectively, and subscripts denote time indices. $\hat{v}$ denotes the inferred velocity implied by the model. Misestimation of the time constant leads to erroneous velocity estimates about self-motion $\hat{v}$ which result in biased position beliefs. *Right*: Illustration of the actual (black) and believed (red) trajectories produced by integrating (box) the actual velocity v and the estimated velocity $\hat{v}$, respectively. *Yellow dot* denotes the starting position. **(B)** Comparison of correlations between real and subjective residual errors with τ. On the right, participant averages of these correlations are shown. *Colored bars*: 'Subjective' correlations, *Open bars*: Actual correlations. Error bars denote ±1 SEM across participants. *Asterisks* denote the level of statistical significance of differences between real and subjective correlations (*: $p<0.05$, **: $p<0.01$, ***: $p<0.001$).

From a normative standpoint, to optimally infer movement velocity, one must combine sensory observations with the knowledge of the time constant. Misestimating the time constant would produce errors in velocity estimates, which would then propagate to position estimates, leading control dynamics to influence response gain (**Fig. 4A**, middle-right). This is akin to misestimating the slipperiness of an ice patch on the road causing an inappropriate steering response, that would culminate in a displacement that differs from the intended one (**Suppl. Fig. S5**). However, in the absence of performance-related feedback, participants would be unaware of this discrepancy, wrongly believing that the actual trajectory was indeed the intended one. We tested the hypothesis that participants misestimated the time constant using a two-step model that reconstructs the participants' believed trajectories according to their *point estimate* of the time constant τ, as follows. First, a Bayesian observer model infers the participant's belief about τ on individual trials, *i.e.* the subjective posterior distribution over the time constant on a logarithmic scale (τ inference step; **Fig. 4A**, left). Second, we used the median of that belief to reconstruct the believed trajectory by integrating the actual joystick input according to the estimated time constant on that trial (integration step), resulting in a believed stopping location (**Fig. 4A**, middle-right). In the absence of bias (response gain of one), the believed stopping locations should land on or near the target. However, various unmeasurable fluctuations in that belief across trials should lead to variability clustered around the target location. When the behavior is biased (response gain different from one, as was the case here – **Fig. 2D**), this cluster should instead be centered around the participants' *mean* belief for that target location (determined from their biased responses and henceforth referred to as *mean stopping location*). Since the participants' goal is to stop as close to their perceived target location as possible, the deviation of believed stopping locations from the mean stopping location for a given target should be small. We call this deviation the *subjective* residual error. Therefore, we inferred the parameters of the Bayesian model separately for each participant by minimizing the *subjective* residual errors induced by the control dynamics using the principle of least-squares (see **Methods** for further details). We next describe the parameters of the Bayesian model and then describe the results of fitting the model to our data.

Because the time constant τ is always positive, we model both the prior distribution and the likelihood function over the variable $\varphi = \log \tau$ as Gaussians in log-space. We parameterized both the prior and the likelihood with a mean (μ) and standard deviation (σ). The parameters of the prior (μ, σ) were allowed to freely vary across sensory conditions but assumed to remain fixed across trials. On each trial, the likelihood was assumed to be centered on the actual value of the log time-constant τ^* on that trial according to $\mu = \varphi^* = \log \tau^*$ and was therefore not a free parameter, but its width σ was free to vary across sensory conditions. Thus, for each sensory condition, we fit three parameters: the σ of the likelihood, as well as the σ and μ of the prior. As mentioned above, we fit the model to minimize the difference between their believed stopping locations and their experimentally-measured mean stopping location (*subjective* residual errors), using a least-squares approach (**Methods**) and obtained one set of parameters for each condition. Finally, the participant's estimated time-constant $\hat{\tau}$ on each trial was taken to be the median of the best-fit model, which equals the median of the distribution over φ (**Fig. 4A**, left). By integrating the subject's joystick inputs on each trial using $\hat{\tau}$ rather than the actual time-constant τ, we computed the believed stopping location and the subjective residual errors implied by the best-fit model.

We then compared the correlations between the time constant and the *real* (from **Fig. 3B,C**) or *subjective* residual errors, separately for radial and angular components. Because participants try to stop at their believed target location, the believed stopping position should depend only on target location and not on the control dynamics. Any departure would suggest that participants *knowingly* failed to account for the effect of the control dynamics, which would manifest as a dependence of the *subjective* residual errors on the time constant τ. In other words, a good model of the participants' beliefs would predict that the *subjective* residual errors should be uncorrelated with the time constant τ. In all cases, we observed that the correlation between residual error and time constant was indeed significantly smaller when these errors were computed using the *subjective* (believed) rather than *real* stopping location (**Fig. 4B**). In fact, subjective residual errors were completely uncorrelated with the time constant

(see **Methods**), suggesting that the apparent influence of control dynamics on behavioral performance was entirely because participants misestimated the time constant of the underlying dynamics.

The relationship between real and model-estimated time constants for all participants can be seen in **Fig. 5A**. In the vestibular condition, all participants consistently misestimated τ, exhibiting a substantial regression towards the mean (**Fig. 5A**, green). This effect was much weaker in the visual condition. Only a few participants showed relatively flat estimates, with the majority showing smaller departures from ideal estimates (*dashed line*). The data for the combined condition followed a similar trend, with properties between those in the visual and vestibular conditions (**Fig. 5A**, purple). Thus, the relatively weaker influence of control dynamics on response gain in the visual and combined conditions was due to participants' improved estimates of the time constant when optic flow was available.

Figure 5: Model parameters. (A) Relationship between the model-estimated and actual time constant across all participants in vestibular (green), visual (orange) and combined (purple) conditions. Participant averages are superimposed (*thick lines*). *Dashed line*: unbiased estimation. **(B)** Fitted model parameters: standard deviation (σ) of likelihood and prior and mean (μ) of prior. Error bars denote ±1 SEM. *Dashed lines* represent the corresponding values of the sampling distribution of $\varphi = \log \tau$, which is normal (see **Methods**). For all conditions, the prior distribution's μ was comparable and σ was smaller than the corresponding μ and σ of the actual sampling distribution (sampling distribution μ: 0.58 $\log s$ – *p*-value of prior μ difference obtained by bootstrapping – vestibular: $p = 0.012$, visual: $p = 0.48$; combined: $p = 0.055$; sampling distribution σ: 0.40 $\log s$ – p-value of prior σ difference obtained by bootstrapping – vestibular: $p < 10^{-7}$, visual: $p < 10^{-7}$; combined: $p = 0.009$). *Asterisks* denote the level of statistical significance of differences in the fitted parameters across conditions (*: p<0.05, **: *p*<0.01, ***: p<0.001).

Inaccuracies in the estimated time constant can be understood by examining the model parameters (**Fig. 5B**). The width σ of the likelihood function was significantly larger in the vestibular condition than other conditions (**Fig. 5B** left, green bar; mean likelihood σ ± standard SEM – vestibular: 0.48±0.10, visual: 0.16±0.03, combined: 0.19±0.05; p-value of likelihood σ paired differences obtained by bootstrapping - vestibular vs visual: $p < 10^{-7}$, vestibular vs combined: $p = 0.0003$; visual vs combined: $p = 0.27$). On the other hand, σ of the prior was significantly smaller (**Fig. 5B** middle, green bar; mean σ ± SEM – vestibular: 0.04±0.02, visual: 0.23±0.04, combined: 0.22±0.07; p-value of prior σ paired differences obtained by bootstrapping - vestibular vs visual: $p < 10^{-7}$, vestibular vs combined: $p = 0.0015$; visual vs combined: $p = 0.44$). Thus, participants' estimate of the control dynamics in the vestibular condition was plagued by a combination of strong prior and weak likelihood. Consequently, there is stronger relative weighting of the prior over the likelihood, which explains the much stronger regression towards the mean in **Fig. 5A**.

Alternative models

Figure 6: Comparison of the correlations between the actual τ and the subjective residual errors implied by three different τ-estimation models (Bayesian estimation with a Static prior (*S; light bars*), Bayesian estimation with a Dynamic prior (*D; dark bars*), Fixed estimate (*F; spotted bars*)). We tested the hypotheses that either the prior distribution should not be static or that the participants ignored changes in the control dynamics and navigated according to a fixed time constant across all trials (fixed τ-estimate model; see **Methods**). For this, we compared the correlations between the subjective residual error and the actual trial τ that each model produces. The Dynamic prior model performs similarly to the Static prior model in all conditions, indicating that a static prior is adequate in explaining our data (p-values of paired t-test between correlation coefficients of the two models: Distance – vestibular: p = 0.33, visual: p = 0.73, combined: p = 0.47; Angle – vestibular: p = 0.38, visual: p = 0.91, combined: p = 0.37). For visual and combined conditions, the fixed τ model not only fails to minimize the correlations but, in fact, strongly reverses it, for both distance (*left*) and angle (*right*). Since these correlations arise from the believed trajectories that the fixed τ model produces, this suggests that participants knowingly stop before their believed target location for higher time constants. Model performance was only comparable in the vestibular condition, where the average correlation of the fixed τ model (F) was contained within the 95% confidence intervals (CI) of the static prior Bayesian model (S), for both distance and angle (Distance – F: mean Pearson's correlation coefficient $\rho = 0.03$, S: 95% CI of Pearson's correlation coefficient $\rho = [-0.09\ 0.18]$; Angle – F: mean Pearson's correlation coefficient $\rho = -0.01$, S: 95% CI of Pearson's correlation coefficient $\rho = [-0.11\ 0.10]$). Error bars denote ± 1 SEM.

To test whether our assumption of a static prior distribution over time constants was reasonable, we fit an alternative Bayesian model in which the prior distribution was updated iteratively on every trial, as a weighted average of the prior on the previous trial and the current likelihood over φ (Dynamic prior model; see **Methods**). For this version, we once again modeled the likelihood and prior as normal distributions over the log- transformed variable, φ, where the likelihood was centered on the actual φ and was therefore not a free parameter. Thus, we fit three parameters: σ of the likelihood and the prior and μ of the initial prior. On each trial, the relative weighting of prior and likelihood responsible for the update of the prior depended solely on the relationship between their corresponding σ (*i.e.* relative widths). The performance between the static and dynamic prior models was comparable in all conditions, for both distance and angle, suggesting that a static prior is adequate in explaining the participants' behavior on this task (**Fig. 6;** *light* versus *dark bars*). In line with our expectations, when updating the prior in the dynamic model, the weighting of the previous-trial prior received significantly more weight in the vestibular condition (in the range of [0,1]; mean prior weights ± SEM – vestibular: 0.67±0.07, visual: 0.31±0.08, combined: 0.36±0.09; p-value of paired weight differences obtained by bootstrapping - vestibular vs visual: $p = 6 \cdot 10^{-4}$, vestibular vs combined: $p = 8 \cdot 10^{-4}$; visual vs combined: $p = 0.29$). Likewise, to test whether participants used sensory observations at all to estimate control dynamics, we compared the static prior Bayesian model to a parsimonious model that assumed a fixed time constant across all trials (*i.e.* completely ignoring changes in control dynamics). This latter model can be understood as a Bayesian model instantiated with a very strong static prior. In line with our expectations (see **Fig. 5A**), this latter model performed comparably in the vestibular condition, but substantially worse in the visual and combined conditions (**Fig. 6**). This suggests that optic flow, but not vestibular signals, primarily contributes to inferring the latent velocity dynamics.

Discussion

We showed that human participants can navigate using different sensory cues and that changes in the control dynamics affect their performance. Specifically, we showed that participants can path integrate to steer towards a remembered target location quite accurately in the presence of optic flow. In contrast, inertial (vestibular/somatosensory cues) alone lacked the reliability to support accurate path integration, leading to substantially biased responses under velocity control. Performance was also influenced by the changing control dynamics in all sensory conditions. Because control dynamics were varied on a trial-by-trial basis, sensory cues were crucial for inferring those dynamics. We used probabilistic inference models to show that the observed responses are consistent with estimates of the control dynamics that were biased toward the center of the experimental distribution. This was particularly strong under the vestibular condition such that the response gain substantially increased as the motion dynamics tended towards acceleration control. Although control dynamics were correlated across trials, our models showed that participants did not take advantage of those correlations to improve their estimates.

Relation to past work

In the paradigm used here, participants actively controlled linear and angular motion, allowing us to study multisensory path integration in two dimensions with few constraints. This paradigm was made possible by the development of a motion-cueing (MC) algorithm to render visual and vestibular cues either synchronously or separately. In contrast, previous studies on human path integration used restricted paradigms in which motion was either one dimensional or passively rendered, and participants' decisions where typically reduced to end-of-trial binary evaluations of relative displacement (Campos et al., 2012; Chrastil et al., 2016, 2019; Jürgens & Becker, 2006; Koppen et al., 2019; Horst et al., 2015; Tramper & Medendorp, 2015). As a result, findings from past studies that evaluate the contributions of different sensory modalities to self-motion perception (Chrastil et al., 2019; Israël et al., 1996; Koppen et al., 2019; Seemungal et al., 2007; Horst et al., 2015) may be more limited in generalizing to real-world navigation.

Our results show that, at least in humans, navigation is driven primarily by visual cues under conditions of near-constant travel velocity (velocity control). This dominance on vision suggests that the reliability of the visual cues is much higher than vestibular cues, as corroborated by the data from the combined condition in which performance resembles the visual condition. This makes sense because the vestibular system is mainly sensitive to acceleration, exhibiting higher sensitivity to higher-frequency motion compared to the visual system (Karmali et al., 2014). Consequently, it may only be reliable when motion is dominated by acceleration. This interpretation is further supported by the observation that participants' vestibular performance was a lot less biased in the regime of acceleration joystick control, where accelerations are prolonged during navigation.

Experimental constraints in past navigation studies have also precluded examining the influence of control dynamics. In fact, the importance of accurately inferring control dynamics, which are critical for predicting the sensory consequences of actions, has largely been studied in the context of limb control and motor adaptation (Burdet et al., 2001; Kording et al., 2007; Krakauer et al., 1999; Lackner & Dizio, 1994; Shadmehr & Mussa-Ivaldi, 1994; Takahashi et al., 2001). Here, we provide evidence for the importance of accurately inferring control dynamics in the context of path integration and spatial navigation. Although participants were not instructed to expect changes in the latent dynamics and received no feedback, we showed that they nevertheless partly compensated for those dynamics while exhibiting a bias toward prior expectations about these dynamics. This biased estimation of control dynamics led to biased path integration performance. This result is analogous to findings about the effect of changing control dynamics in motor control: first, adaptation to the dynamics happens even in the absence of performance-related feedback (Batcho et al., 2016; Lackner & Dizio, 1994) and, second, this adaptation relies on prior experience (Arce et al., 2009) and leads to systematic errors when knowledge of

the dynamics is inaccurate (Körding et al., 2004). Thus, participants try to exploit the additional information that the dynamics contain about their self-motion in order to achieve the desired displacement.

Task performance was substantially worse in the vestibular condition, in a manner suggesting that vestibular inputs lack the reliability to precisely estimate control dynamics on individual trials. Nevertheless, the vestibular system could still facilitate inference by integrating trial history to build expectations about their statistics. Consistent with this, the mean of the prior distribution over the dynamics fit to data was very close to the mean of the true sampled distribution, suggesting that even if within-trial vestibular observations are not sufficient, participants possibly combine information about the dynamics across trials to construct their prior beliefs. This is consistent with the findings of (Prsa et al., 2015), where vestibular cues were used to infer an underlying pattern of magnitude of motion across trials. However, the measurement of the dynamics in that study substantially differs from ours: here, motion dynamics are inferred using self-motion cues within each trial whereas in (Prsa et al., 2015), the dynamics were inferred by integrating observations about the magnitude of the displacement across trials. If vestibular cues can in fact support inference of dynamics, a common processing mechanism could be shared across sensory modalities. Overall, this finding highlights the importance of incorporating estimates of the control dynamics in models of self-motion perception and path integration.

Limitations and future directions

Note that restrictions of our motion platform limited the range of velocities that could be tested, allowing only for relatively small velocities (see **Methods**). Consequently, trial durations were long, but the motion platform also restricted total displacement, so we could not test larger target distances. We previously studied visual path integration with larger velocities and our results in the visual and combined conditions are comparable for similar travel times (as trials exceeded durations of 10 seconds, undershooting became more prevalent; Lakshminarasimhan et al., 2018). However, it is unclear how larger velocities (and accelerations) would affect participants' performance (especially under the vestibular condition) and whether the present conclusions are also representative of the regime of velocities not tested.

For the sake of simplicity, we modeled each trial's control dynamics as a single measurement per trial when, in reality, participants must infer the dynamics over the course of a trial using a dynamic process of evidence accumulation. Although we were able to explain the experimental findings of the influence of control dynamics on steering responses with our model, this approach could be expanded into a more normative framework using hierarchical Bayesian models (Mathys et al., 2011) to infer subjective position estimates by marginalizing over possible control dynamics.

One interesting question is whether providing feedback would eliminate the inference bias of the control dynamics estimation and future studies should explicitly test this hypothesis. Furthermore, it would be interesting to jointly introduce sensory conflict and manipulate sensory reliability to study dynamic multisensory integration such that sensory contributions during navigation can be better disentangled. Although it has been shown that cue combination takes place during path integration (Tcheang et al., 2011), previous studies have had contradicting results regarding the manner in which body-based and visual cues are combined (Campos et al., 2010; Chrastil et al., 2019; Koppen et al., 2019; Petrini et al., 2016; Horst et al., 2015). Since visual and vestibular signals differ in their sensitivity to different types of motion (Karmali et al., 2014), the outcomes of their integration may depend on the self-motion stimuli employed. Combined with hierarchical models of self-motion inference that considers the control dynamics, it is possible to develop an integrated, multi-level model of navigation, while constraining dramatically the hypothesized brain computations and their neurophysiological correlates.

Methods
EQUIPMENT AND TASK

15 participants (9 Male, 6 Female; all adults in the age group 18-32) participated in the experiments. Apart from two participants, all participants were unaware of the purpose of the study. Experiments were first performed in the above two participants before testing others. All experimental procedures were approved by the Institutional Review Board at Baylor College of Medicine and all participants signed an approved consent form.

Experimental setup

The participants sat comfortably on a chair mounted on an electric motor allowing unrestricted yaw rotation (Kollmorgen motor DH142M-13-1320, Kollmorgen, Radford, VA), itself mounted on a six-degree-of-freedom motion platform (comprised of MOOG 6DOF2000E, Moog Inc., East Aurora, NY). Participants used an analog joystick (M20U9T-N82, CTI electronics, Stratford, CT) with two degrees of freedom and a circular displacement boundary to control their linear and angular speed in a virtual environment based on visual and/or vestibular feedback. The visual stimulus was projected (Canon LV-8235 UST Multimedia Projector, Canon USA, Melville, NY) onto a large rectangular screen (width × height: 158 × 94 cm) positioned in front of the participant (77 cm from the rear of the head). Participants wore crosstalk free ferroelectric active-shutter 3D goggles (RealD CE4s, ColorLink Japan, Ltd., Tokyo, Japan) to view the stimulus. Participants wore headphones generating white noise to mask the auditory motion cues. The participants' head was fixed on the chair using an adjustable CIVCO FirmFit Thermoplastic face mask (CIVCO, Coralville, IA).

Spike2 software (Power 1401 MkII data acquisition system from Cambridge Electronic Design Ltd., Cambridge, United Kingdom) was used to record joystick and all event markers for offline analysis at a sampling rate of $833\frac{1}{3}$ Hz.

Visual stimulus

Visual stimuli were generated and rendered using C++ Open Graphics Library (OpenGL) by continuously repositioning the camera based on joystick inputs to update the visual scene at 60 Hz. The camera was positioned at a height of 70cm above the ground plane, whose textural elements whose lifetimes were limited ($\sim$250ms) to avoid serving as landmarks. The ground plane was circular with a radius of 37.5m (near and far clipping planes at 5cm and 3750cm respectively), with the participant positioned at its center at the beginning of each trial. Each texture element was an isosceles triangle (base × height 5.95 × 12.95 cm) that was randomly repositioned and reoriented at the end of its lifetime. The floor density was held constant across trials at $\rho = 2.5$ elements/m^2. The target, a circle of radius 25cm whose luminance was matched to the texture elements, flickered at 5Hz and appeared at a random location between $\theta = \pm38°$ of visual angle at a distance of $r = 2.5 - 5.5$ m (average distance $\bar{r} = 4$ m) relative to where the participant was stationed at the beginning of the trial. The stereoscopic visual stimulus was rendered in an alternate frame sequencing format and participants wore active-shutter 3D goggles to view the stimulus.

Behavioral task – Visual, Inertial and Multisensory motion cues

Participants were asked to navigate to a remembered target ('firefly') location on a horizontal virtual plane using a joystick, rendered in 3D from a forward-facing vantage point above the plane. Participants pressed a button on the joystick to initiate each trial and were tasked with steering to a randomly placed target that was cued briefly at the beginning of the trial. A short tone at every button push indicated the beginning of the trial and the appearance of the target. After one second, the target disappeared, which was a cue for the participant to start steering. During steering, visual and/or vestibular/somatosensory sensory feedback was provided (see below). Participants were instructed to stop at the remembered target location, and then push the button to register their final position and start the next trial. Participants did not receive any feedback about their performance. Prior to the first session, all participants performed about ten practice trials to familiarize themselves with joystick movements and the task structure.

The three sensory conditions (visual, vestibular, combined) were randomly interleaved. In the visual condition, participants had to navigate towards the remembered target position given only visual information (optic flow). Visual feedback was stereoscopic, composed of flashing triangles to provide self-motion information but no landmark. In the vestibular condition, after the target disappeared, the entire visual stimulus was shut off too, leaving the participants to navigate in complete darkness using only vestibular/somatosensory cues generated by the motion platform. In the combined condition, participants were provided with both visual and vestibular information during their movement.

Independently of the manipulation of the sensory information, the properties of the motion controller also varied from trial to trial. Participants experienced different time constants in each trial, which affected the type and amount of control that was required to complete the task. In trials with short time constants, joystick position mainly controlled velocity, whereas in trials with long time constants, joystick position approximately controlled the acceleration (explained in detail in *Control Dynamics* below).

Joystick control

Participants navigated in the virtual environment using a joystick placed in front of the participant's midline, in a holder mounted on the bottom of the screen. This ensured that the joystick was parallel to the participant's vertical axis, and its horizontal orientation aligned to the forward movement axis. The joystick had two degrees of freedom that controlled linear and angular motion. Joystick displacements were physically bounded to lie within a disk, and digitally bounded to lie within a square. Displacement of the joystick over the anterior-posterior (AP) axis resulted in forward or backward translational motion, whereas displacement in the left-right (LR) axis resulted in rotational motion. The joystick was enabled after the disappearance of the target. To avoid skipping trials and abrupt stops, the button used to initiate trials was activated only when the participant's velocity dropped below 1 cm/s.

The joystick controlled both the visual and vestibular stimuli through an algorithm that involved two processes. The first varied the <u>control dynamics (CD)</u>, producing velocities given by a lowpass filtering of the joystick input, mimicking an inertial body under viscous damping. The time constant for the control filter (control timescale) was varied from trial to trial, according to a correlated random process as explained below.

The second process was a <u>motion cueing (MC)</u> algorithm applied to the output of the CD process, which defined physical motion that approximated the accelerations an observer would feel under the desired control dynamics, while avoiding the hardwired constraints of the motion platform. This motion cueing algorithm trades translation for tilt, allowing extended acceleration without hitting the displacement limits (24 cm).

These two processes are explained in detail below.

Control Dynamics (CD)

Inertia under viscous damping was introduced by applying a lowpass filter on the control input, following an exponential weighted moving average with a time constant that slowly varied across trials. On each trial, the system state evolved according to a first-order Markov process in discrete time, such that the movement velocity at the next time step depended only on the current joystick input and the current velocity. Specifically, the vertical and horizontal joystick positions u_t^v and u_t^ω determined the linear and angular velocities v_t and ω_t as

$$v_{t+1} = \alpha v_t + \beta_v u_t^v \qquad \text{and} \qquad \omega_{t+1} = \alpha \omega_t + \beta_\omega u_t^\omega \qquad (1.1)$$

The time constant τ of the lowpass filter determined the coefficient α (**Fig. S1A**):

$$\alpha = e^{-\Delta t/\tau} \qquad (1.2)$$

Sustained maximal controller inputs of $u_t^v = 1$ or $u_\omega^v = 1$ produce velocities that saturate at

$$v_{\text{max}} = \beta_v/(1 - \alpha) \qquad \text{and} \qquad \omega_{\text{max}} = \beta_\omega/(1 - \alpha) \qquad (1.3)$$

We wanted to set v_{max} and ω_{max} in such a way that would ensure that a target at an average linear or angular
displacement x is reachable in an average time T, regardless of τ. This constrains the input gains β_v and β_ω. We
derived these desired gains based on a 1D bang-bang control model (*i.e.* purely forward movement, or pure
turning) which assumes maximal positive control until time s, followed by maximal negative control until time
T (**Fig.S1A**). Although we implemented the leaky integration in discrete time with a frame rate of 60Hz, we
derived the input gains using continuous time and translated them to discrete time.

The velocity at any time $0 \leq t \leq T$ during the control is:

$$\frac{v_t}{v_{\text{max}}} = \begin{cases} 1 - e^{-t/\tau} & 0 < t \leq s \\ -1 + \left(\frac{v_s}{v_{\text{max}}} + 1\right)e^{-\frac{t-s}{\tau}} & s < t < T \end{cases} \qquad (1.4)$$

438 where v_s is the velocity at the switching time s when control switched from positive to negative, given by:

$$v_s = v_{\text{max}}\left(1 - e^{-s/\tau}\right) \qquad (1.5)$$

439 By substituting v_s into Eq. (1.4) and using the fact that at time T, the controlled velocity should return to 0, we
440 obtain an expression that we can use to solve for s:

$$v_T = 0 = -1 + \left(\frac{v_{\text{max}}\left(1 - e^{-s/\tau}\right)}{v_{\text{max}}} + 1\right)e^{-\frac{T-s}{\tau}} \qquad (1.6)$$

441 Observe that v_{max} cancels in this equation, so the switching time s is independent of v_{max} and therefore also
442 independent of the displacement x (see also **Fig. S1A**):

$$s = \tau \ln\left(\frac{1 + e^{T/\tau}}{2}\right) \qquad (1.7)$$

443 Integrating the velocity profile of Equation 1.4 to obtain the distance travelled by time T, substituting the switch
444 time s (**Fig. S1A**), and simplifying, we obtain:

$$x = x_T = 2\,\tau\,v_{\text{max}}\ln\left(\cosh\frac{T}{2\tau}\right) \qquad (1.8)$$

445 We can then solve for the desired maximum linear speed v_{max} for any time constant τ, average displacement x
446 and trial duration T:

$$v_{\text{max}}(\tau) = \frac{x}{2\tau}\frac{1}{\ln\cosh(T/2\tau)} \qquad (1.9)$$

447 Similarly, the maximum angular velocity was: $\omega_{\text{max}}(\tau) = \frac{\theta}{2\tau}\frac{1}{\ln\cosh(T/t)}$, where θ is the angle we want our
448 participant to be able to turn within the average time T.

449 These equations can also be re-written in terms of a dimensionless time $z = \tau/T$ (duration of trial in units of the
450 time constant) and average velocities $\bar{v} = x/T$ and $\bar{\omega} = \theta/T$:

$$v_{\text{max}} = \bar{v}\,\frac{1/2z}{\ln\cosh(1/2z)} \qquad \omega_{\text{max}} = \bar{\omega}\,\frac{1/2z}{\ln\cosh(1/2z)} \qquad (1.10)$$

451 where θ is the average angle we want the participants to be able to steer within time T.

452 Setting control gains according to Equation 1.9 allows us to manipulate the control timescale τ, while
453 approximately maintaining the average trial duration for each target location (**Fig. S1B**). Converting these

maximal velocities into discrete-time control gains using Equations 1.1–1.3 gives us the desired inertial control dynamics.

Slow changes in time constant

The time constant τ was sampled according to a temporally correlated log-normal distribution. The log of the time constant, $\phi = \log \tau$, followed a bounded random walk across trials according to (**Fig. S1C**)

$$\phi_{t+1} = c\,\phi_t + \eta_t \tag{2}$$

The marginal distribution of ϕ was normal, $N(\mu_\phi, \sigma_\phi^2)$, with mean $\mu_\phi = \frac{1}{2}(\ln \tau_- + \ln \tau_+)$ and standard deviation $\sigma_\phi = \frac{1}{4}(\ln \tau_+ - \ln \tau_-)$, which ensured that 95% of the velocity timescales lay between τ_- and τ_+. The velocity timescales changed across trials with their own timescale τ_ϕ, related to the update coefficient by $c = e^{-\Delta t/\tau_\phi}$, where we set Δt to be one trial and τ_ϕ to be two trials. To produce the desired equilibrium distribution of ϕ we set the scale of the random walk Gaussian noise $\eta \sim N(\mu_\eta, \sigma^2{}_\eta)$ with $\mu_\eta = \mu_\phi(1 - c)$ and $\sigma_\eta^2 = \sigma_\phi^2(1 - c^2)$.

Motion Cueing algorithm (MC)

Each motion trajectory consisted of a linear displacement in the 2D virtual space combined with a rotation in the horizontal plane. While the motion platform could reproduce the rotational movement using the yaw motor (which was unconstrained in movement range and powerful enough to render any angular acceleration or speed in this study), its ability to reproduce linear movement was limited by the platform's maximum range of $25\ cm$ and maximum velocity of $50\ cm/s$. To circumvent this limitation, we designed a MC algorithm that takes advantage of the gravito-inertial ambiguity inherent to the vestibular organs (Angelaki & Dickman, 2000; Fernandez et al., 1972; Fernandez & Goldberg, 1976).

Specifically, the otolith organs in the inner ear sense both linear acceleration (A) and gravity (G), *i.e.* they sense the gravito-inertial acceleration (GIA): $F = G + A$. Consequently, a forward acceleration of the head (a_x, expressed in g, with 1g = 9.81 m/s^2) and a backward pitch (by an angle θ, in radians) will generate a total gravito-inertial acceleration $Fx = \theta + a_x$. The MC took advantage of this ambiguity to replace linear acceleration by tilt. Specifically, it controlled the motion platform to produce a total GIA (**Fig. S2**, 'Desired Platform GIA') that matched the linear acceleration of the simulated motion in the virtual environment. As long as the rotation that induced this simulated acceleration was slow enough, the motion felt subjectively like changing linear acceleration.

This control algorithm was based on a trade-off where the high-pass component of the simulated inertial acceleration (**Fig. S2**, 'Desired Platform Linear Acceleration') was produced by translating the platform, whereas the low-pass component was produced by tilting the platform (**Fig. S2**, 'Desired Platform Tilt').

Even though this method is generally sufficient to ensure that platform motion remains within its envelope, it does not guarantee it. Thus, the platform's position, velocity and acceleration commands were fed though a sigmoid function f (**Fig. S2**, 'Platform Limits'). This function was equal to the identity function ($f(x) = x$) as long as motion commands were within 75% of the platform's limits, so motion commands were unaffected. When motion commands exceed this range, the function bends smoothly to saturates at a value set slightly below the limit, this preventing the platform from reaching its mechanical range (in position, velocity or acceleration) while ensuring a smooth trajectory. Thus, if the desired motion exceeds 75% of the platform's performance envelope, the actual motion of the platform is diminished, such that the total GIA actually experienced by the participant ('Actual Platform GIA') may not match the desired GIA. If left uncorrected, these GIA errors would result in a mismatch between inertial motion and the visual VR stimulus. To prevent these mismatches, we designed a loop

that estimates GIA error and updates the simulated motion in the visual environment. For instance, if the joystick input commands a large forward acceleration and the platform is unable to reproduce this acceleration, then the visual motion is updated to represent a slower acceleration that matches the platform's motion. Altogether, the IC and MC algorithms are applied sequentially as follows: 1) The velocity signal produced by the IC process controls the participant's attempted motion in the virtual environment. 2) The participant acceleration in the VR environment is calculated and inputted to the MC algorithm ('Desired Platform GIA'). 3) The MC cueing computes the platform's motion commands and the actual platform GIA is computed. 4) The difference between the Desired GIA motion actual GIA (GIA error) is computed and used to update the motion in the virtual environment. 5) The updated position is sent to the visual display.

QUANTIFICATION AND STATISTICAL ANALYSIS

Customized MATLAB code was written to analyze data and to fit models. Depending on the quantity estimated, we report statistical dispersions either using 95% confidence interval, standard deviation, or standard error in the mean. The specific dispersion measure is identified in the portion of the text accompanying the estimates. For error bars in figures, we provide this information in the caption of the corresponding figure. We report and describe the outcome as significant if $p < 0.05$.

Estimation of response gain

In each sensory condition, we first computed the τ-independent gain for each participant; we regressed (without an intercept term) each participant's response positions $(\tilde{r}, \tilde{\theta})$ against target positions (r, θ) separately for the radial ($\tilde{r}$ vs r) and angular ($\tilde{\theta}$ vs θ) coordinates, and the radial and angular response gains (g_r, g_θ) were quantified as the slope of the respective regressions (**Fig 2A**). In addition, we followed the same process to calculate gain terms within three τ groups of equal size (**Fig. 3A**).

Correlation between residual error and time constant τ

To evaluate the influence of the time constant on the steering responses, we computed the correlation coefficient between the time constants and the residual errors from the mean response (estimated using the response gain) for distance and angle. Under each sensory condition, the radial residual error (ε_r) for each trial i was given by:

$$\varepsilon_{r,i} = \tilde{r}_i - g_r r_i \tag{3.1}$$

where $\tilde{r}_i$ is the radial response, and the mean radial response is given by multiplying the target distance r_i by the radial gain g_r. Similarly, the angular residual error (ε_θ) was calculated as:

$$\varepsilon_{\theta,i} = \tilde{\theta}_i - g_\theta \theta_i \tag{3.2}$$

Regression model containing τ

To assess the manner in which the time constant affected the steering responses, we augmented the simple linear regression models for response gain estimation mentioned above with τ-dependent terms (**Suppl. Fig. S3**; τ and $\tau * r$ for radial response $\tilde{r}$, τ and $\tau * \theta$ for angular response $\tilde{\theta}$). Subsequently, we calculated the Pearson linear partial correlations between the response positions and each of the three predictors.

Estimation of τ-dependent gain

To quantify the extent to which the time constant modulates the response gain, we linearly regressed each participant's response positions $(\tilde{r}, \tilde{\theta})$ against target positions (r, θ) and the interaction between target positions and the time constant τ according to:

$$\tilde{r} = b_r r + a_r r\tau \quad \text{and} \quad \tilde{\theta} = b_\theta \theta + a_\theta \theta\tau \tag{4.1}$$

Where b_r, b_θ and a_r, a_θ are the coefficients of the target locations and the interaction terms, respectively. All quantities were first standardized by dividing them with their respective standard deviation, to avoid size effects of the different predictors. This form allows for modulation of the response gain by the time constant, which is clear when the target location is factored out:

$$\tilde{r} = r(b_r + a_r\tau) \quad \text{and} \quad \tilde{\theta} = \theta(b_\theta + a_\theta\tau) \tag{4.2}$$

Rationale behind modeling approach

We tested the hypothesis that the τ-dependent errors in steering responses arise from participants misestimating control dynamics on individual trials. Specifically, if participants' estimate of the time constant τ differs from the actual value, then their *believed* trajectories (computed using the estimated τ) would differ accordingly from the *actual* trajectories along which they travelled. believed stopping locations should land on or near the target. However, various unmeasurable fluctuations in that belief across trials should lead to variability clustered around the target location Because participants try to stop on their believed target location, the *believed* stopping locations, subject to unmeasurable fluctuations of the belief across trials, should be distributed evenly around the participant's mean response (mean belief), after adjusting for the average response gain. This is so because, if the distribution of believed responses depended on the time constant, then that would imply that participants willingly misestimated the control dynamics. Mathematically, the *subjective* residual errors (deviation of the believed stopping location from the mean response for a given target; see **Methods:** *Correlation between residual error and time constant τ*) should be distributed evenly around zero and be uncorrelated with the time constant τ. Therefore, a good model of the participants' beliefs should predict that subjective residual errors are statistically independent of the time constant.

Bayesian observer model for τ estimation

To account for the effect of the time constant τ on steering performance, we considered a two-step observer model that uses a measurement m of the real time constant τ and a prior distribution over hypothesized time constants in logarithmic scale to compute an estimate $\hat{\tau}$ on each trial (first step), and then integrates the actual joystick input using that estimate to reconstruct the participant's believed trajectory (second step). We formulated our model in the logarithmic space of $\varphi = \log\tau$, therefore the prior distribution over the hypothesized time constants $p(\varphi)$ was assumed to be normal in log-space with mean, μ_{prior} and standard deviation, σ_{prior}. The measurement distribution $p(m|\varphi)$ was also assumed to be normal in log-space with mean φ, and standard deviation $\sigma_{measure}$. Note that whereas the prior $p(\varphi)$ remains fixed across trials of a particular sensory modality, the mean of measurement distribution is governed by φ and thus varies across trials. For each sensory modality, we fit three parameters, $\Theta \ni \{\mu_{prior}, \sigma_{prior}, \sigma_{measure}\}$.

Model fitting

When inferring the participant's beliefs about the control dynamics, we computed the posterior distribution on trial i as $p(\varphi|m_i) \propto p(\varphi)p(m_i|\varphi)$ (**Fig. 4A**, left) and then selected the median over φ (equal to the maximum a posteriori estimate), which corresponds to the median over τ and was back-transformed from log-space to obtain an estimate of the time constant $\hat{\tau}_i$ for that trial:

$$\hat{\tau}_i = \exp\left\{\underset{\varphi}{\mathrm{argmax}}\ p(\varphi|m_i)\right\} \tag{5}$$

Subsequently, $\hat{\tau}$ is used to integrate the actual joystick input and produce the participant's believed trajectory, according to (**Equation 1.1-1.10**) in the *Control Dynamics* (CD) section.

The Bayesian model had 3 free parameters $\Theta \ni \{\mu_{\text{prior}}, \sigma_{\text{prior}}, \sigma_{\text{measure}}\}$. We fit the model by assuming that participants stop as close to the target as possible given their understanding of the task. Specifically, we minimized the mean squared error (MSE) between the measured mean stopping position (computed using the response gains g_r and g_θ from **Equation 3**) and our model of the participant's believed stopping location $\hat{\mathbf{x}}_i$ given the inferred dynamics $\hat{\tau}_i$. For each sensory condition:

$$\Theta^* = \underset{\Theta}{\text{argmin}} \ \frac{1}{n}\sum_{i=1}^{n}\{\hat{\mathbf{x}}_i(\hat{\tau}_i, \mathbf{u}_i) - \mathbf{G}\,\mathbf{x}_i^{\text{tar}}\}^2 \tag{6}$$

where, for each trial i, $\hat{\mathbf{x}}_i$ is the believed participant's position, $\hat{\tau}_i$ is the estimated time constant, $\mathbf{u}_i$ is the time series of the joystick control input, $\mathbf{x}_i^{\text{tar}}$ is the actual target position, $\mathbf{G}$ is the response gain matrix determined from g_r and g_θ, and n is the total number of trials.

Model validation

To evaluate the performance of our model, we examined the correlations between the *subjective* residual error and τ that are given by the model. The subjective residual error is defined as the difference between the believed (subjective) stopping location that a model produces and the mean response of the actual trajectories, adjusted for the response gain. The subjective residual errors are calculated for the radial and angular components of the response separately, according to **Equation 3** (where actual responses $\tilde{r}, \tilde{\theta}$ are substituted by believed responses $\hat{\tilde{r}}, \hat{\tilde{\theta}}$, respectively). Ideally, these correlations should not exist for the model predictions (explained in text; **Fig. 4B**). We determined the statistical significance of the model-implied correlations by adjusting for multiple comparisons (required level of statistical significance: p=0.0085). To assess the performance of the Bayesian model, we compared the correlations between believed and actual stopping location with the time constant (**Fig. 4B**; Wilcoxon signed-rank test).

Dynamic prior model

Since the time constant changes randomly across trials, we tested whether the history of time constants influenced the estimate $\hat{\tau}$. If true, the Bayesian model would imply a prior distribution over $\varphi = \log \tau$ that is dynamically changing according to the recent history of time constants, rather than being fixed. To explore this possibility, we repeated the two-step model outlined above, with the difference that the mean of the prior distribution is updated at every trial i by a weighted average of the mean prior in the previous trial and the current measurement over φ:

$$\mu_{\text{prior},i} = (1-k)\,\mu_{\text{prior},i-1} + k\,\varphi_i \ \text{ where: } \ k = \frac{\sigma_{\text{prior}}^2}{\sigma_{\text{prior}}^2 + \sigma_{\text{measure}}^2} \tag{7}$$

As k indicates, the relative weighting between prior and measurement on each trial depends solely on their relative widths, σ. This model assumes that across trials, σ_{prior} remains fixed within each sensory condition.

Sensory-independent model

As another alternative to the Bayesian model with a static prior, we also constructed a model where participants ignored changes in the time constants and navigated according to a fixed estimate $\hat{\tau}$ across all trials in each sensory condition. This model had only one free parameter: the time constant estimate $\hat{\tau}$, which was integrated with the actual joystick input of each trial to reconstruct the believed trajectory of the participant. We fit $\hat{\tau}$ for each sensory

condition by minimizing the MSE between the believed stopping location and the mean response (according to **Equation 6**).

Model comparison

To compare the static prior Bayesian model against the dynamic prior Bayesian and the sensory-independent models, we compared the correlations between believed stopping locations and time constants that each model produces (**Fig. 6**; paired Student's t-test).

DATA AND SOFTWARE AVAILABILITY

MATLAB code implementing all quantitative analyses in this study is available online (https://github.com/ AkisStavropoulos/matlab_code). Datasets generated by this study are available from the corresponding author upon reasonable request.

Acknowledgements

We thank Jing Lin and Jian Chen for their technical support, and Baptiste Caziot and Panagiotis Alefantis for their useful insights. This work was supported by the National Institute of Health, grants NIH R01-NS120407 and and R01 DC014678.

Competing interests

The authors declare no competing interests.

Supplemental Material

Suppl. Figure S1: (A) Example dynamics for bang-bang control. Position, velocity, and controls are shown. Control switches at time s and ends at time T. **(B)** Maximal velocity (blue) needed for bang-bang control to produce a desired average velocity $\bar{u} = x/T$, as a function of the fraction of trial duration given by the time constant, τ/T. When the time constant is a small fraction of the trial (velocity control), the max velocity equals the average velocity (orange line). When the time constant is much longer than a trial (acceleration control), the maximum velocity grows as $4\tau/T$ (green), although this speed is never approached since braking begins before the velocity approaches equilibrium. **(C)** Example dynamics for control behavior. *Left*: log-normal distribution of control time constants τ. *Right*: example random walk in $\log \tau$ space.

Suppl. Figure S2: A) Flow diagram of Motion Cueing algorithm (MC). The participant pilots themself in a simulated environment using a joystick. The motion cueing algorithm aims at controlling a platform such that the sum of inertial and gravitational acceleration experienced when sitting on the platform (*desired platform GIA*, blue; the curve illustrates an example profile consisting of a single rectangular waveform) matches the linear acceleration experienced in the simulated virtual environment. "Desired" refers to the fact that the motion platform may not be able to match this acceleration exactly. The desired GIA is fed through a step impulse function to compute the *desired linear acceleration* of the platform. The difference between the desired linear acceleration and GIA is used to compute the *desired platform tilt*. The desired platform motion (linear and tilt motion) are passed through a controller that restricts its motion to the actuator's limits (in term of linear and angular acceleration, velocity, and position). The two actuator output commands are sent to the platform and are also used to compute the *actuator GIA* which is actually rendered by the platform. To ensure that the inertial motion produced by the platform matches the motion in the simulated environment, the actuator GIA is compared to the desired linear acceleration to compute an *actuator GIA error* feedback signal, which updates the simulated motion. **B)** Acceleration profile of an actual trial. The first panel shows the desired GIA of the participant for that trial. The second and third panels show the desired linear acceleration (red) and desired tilt acceleration (green), respectively. The fourth panel shows the final GIA achieved (blue) and the GIA error (magenta). **C)** Correspondence between visual acceleration and platform GIA (blue), measured independently from the motion cueing algorithm using an inertial measurement unit mounted next to the participant's head. There is an almost perfect match between the two. The gray histogram indicates the range of acceleration experienced by the participant.

Suppl. Figure S3: (A) Partial correlation coefficients for prediction of stopping distance $\tilde{r}$ (relative to starting position) from initial target distance (r), τ, and the interaction of the two ($r\tau$), for all participants across sensory conditions. Values at each bar group represent the average coefficient value across participants ±1 standard deviation. The contribution of the τ-only term was considered insignificant across all conditions. The simplified version of this model would be: $\tilde{r} = r(\alpha + \gamma\tau)$, which implies that the radial gain is τ-dependent. **(B)** Partial correlation coefficients for prediction of stopping angle $\tilde{\theta}$ (relative to starting position) from initial target angle (θ), τ, and the interaction of the two ($\theta\tau$), for all participants across sensory conditions. Values at each bar group represent the average coefficient value across participants ±1 standard deviation. In agreement with the findings for the response distance, the contribution of the τ-only term was considered insignificant across all conditions. The simplified version of this model would be: $\tilde{\theta} = \theta(\alpha + \gamma\tau)$, which implies that the angular gain is also τ-dependent.

Suppl. Figure S4: A. Correlation coefficients between the time constant and travel duration **(left)** or average travel velocity **(right)** across trials for all participants. *Colors of circles* indicate the sensory condition (*green*: vestibular, *orange*: visual, *purple*: combined). *Open and filled circles* denote statistical significance according to the legend. No consistent effect of the time constant on either travel duration or average velocity across participants was observed. Specifically, correlations are distributed around zero across all sensory conditions for both travel duration and average velocity with only a subset of participants exhibiting statistical significance (*filled circles*). We designed the control dynamics based on a bang-bang controller such that we ensure travel duration, and consequently average velocity, is comparable across time constants (**Suppl. Fig. S1A**, see **Methods**). Bang-bang control implies maximal positive control (forward and angular motion), followed by maximal negative control (braking) until stopping at a desired location. The type of control that participants actually implement would vary from this ideal control model, allowing for the range of correlation coefficients between the time constant and trial duration that we observe here.

B. Left: Uncertainty (variance) of instantaneous self-motion velocity estimation. Illustration of a linear (*blue*) and a quadratic (*orange*) model of velocity estimation uncertainty as a function of the instantaneous velocity magnitude. The uncertainty of velocity estimates is accumulated over time to produce uncertainty in position. According to Lakshminarasimhan et al 2018, higher uncertainty in position leads to more undershooting of the target locations. In this experiment, performance tended towards overshooting for higher time constants. Since different time constants produce different velocity profiles, we wanted to test whether the effect of the time constant on performance could be attributed to differences in the accumulated uncertainty of the different velocity profiles. **Right:** Correlation between time constant and accumulated uncertainty for the linear and quadratic models. Error bars denote ± 1 SEM. We found that the accumulated uncertainty is positively correlated with the time constant for both models (adding an intercept term to the models did not qualitatively change the results). This means that higher time constants yield larger uncertainty and, therefore, participants should undershoot more. However, this is the opposite of the observed effect of the time constant on the responses. Hence, differences in accumulation of perceptual uncertainty cannot account for it.

Suppl. Figure S5: Changes in travel distance for a given control input under different control dynamics. Whether in the domain of velocity (*top*) or acceleration control (*bottom*), a control input that is appropriate to reach a certain target distance (*horizontal black dashed line*) under only a certain time constant (*red vertical line*) will produce erroneous displacements under any other time constant (*blue line*). For smaller time constants, the intended distance will be undershot, whereas larger time constants will lead to overshooting. In other words, assuming that the *red vertical line* denotes the believed dynamics of a controller, a larger actual time constant (underestimation) will lead to overshooting (relative to the intended displacement; *horizontal black dashed line*). Inversely, overestimation of the time constant would lead to undershooting. Note that, for acceleration control we chose a bang-bang controller such that we can demonstrate that this holds true whether there is braking at the end of the trial or not.

Radial Bias Table

	vestibular	visual	combined
τ: [0.34 - 1.53]	0.649 ± 0.056	0.818 ± 0.057	0.786 ± 0.055
τ: [1.53 - 2.16]	0.733 ± 0.063	0.871 ± 0.059	0.836 ± 0.056
τ: [2.16 - 8.89]	0.902 ± 0.077	0.944 ± 0.061	0.917 ± 0.058

Angular Bias Table

	vestibular	visual	combined
τ: [0.34 - 1.53]	0.731 ± 0.053	0.919 ± 0.036	0.902 ± 0.032
τ: [1.53 - 2.16]	0.770 ± 0.060	0.984 ± 0.038	0.944 ± 0.029
τ: [2.16 - 8.89]	0.878 ± 0.061	1.024 ± 0.040	1.012 ± 0.033

Table 1: Average radial (top) and angular (bottom) behavioral response gains across participants, for groups of time constant τ magnitudes (mean ± SEM).

Radial Correlations

	vestibular	visual	combined
Subject 1	r = 0.585, p = $4.2 \cdot 10^{-45}$	r = 0.502, p = $1.2 \cdot 10^{-37}$	r = 0.617, p = $1.0 \cdot 10^{-59}$
Subject 2	r = 0.622, p = $5.5 \cdot 10^{-43}$	r = 0.338, p = $7.4 \cdot 10^{-12}$	r = 0.377, p = $2.9 \cdot 10^{-14}$
Subject 3	r = 0.433, p = $3.5 \cdot 10^{-25}$	r = 0.280, p = $2.7 \cdot 10^{-11}$	r = 0.374, p = $8.7 \cdot 10^{-20}$
Subject 4	r = 0.492, p = $9.1 \cdot 10^{-31}$	r = 0.494, p = $3.1 \cdot 10^{-31}$	r = 0.350, p = $2.1 \cdot 10^{-15}$
Subject 5	r = 0.411, p = $4.4 \cdot 10^{-17}$	r = 0.314, p = $3.4 \cdot 10^{-10}$	r = 0.360, p = $3.7 \cdot 10^{-13}$
Subject 6	r = 0.601, p = $2.0 \cdot 10^{-58}$	r = 0.233, p = $1.2 \cdot 10^{-08}$	r = 0.233, p = $1.2 \cdot 10^{-08}$
Subject 7	r = 0.606, p = $1.6 \cdot 10^{-44}$	r = 0.522, p = $1.5 \cdot 10^{-31}$	r = 0.474, p = $1.1 \cdot 10^{-25}$
Subject 8	r = 0.477, p = $9.6 \cdot 10^{-34}$	r = 0.255, p = $5.7 \cdot 10^{-10}$	r = 0.294, p = $4.6 \cdot 10^{-13}$
Subject 9	r = 0.478, p = $1.0 \cdot 10^{-22}$	r = 0.517, p = $7.9 \cdot 10^{-27}$	r = 0.523, p = $6.3 \cdot 10^{-28}$
Subject 10	r = 0.573, p = $7.2 \cdot 10^{-39}$	r = 0.497, p = $4.7 \cdot 10^{-28}$	r = 0.576, p = $3.5 \cdot 10^{-39}$
Subject 11	r = 0.375, p = $5.9 \cdot 10^{-16}$	r = 0.224, p = $2.1 \cdot 10^{-06}$	r = 0.144, p = 0.002
Subject 12	r = 0.522, p = $2.1 \cdot 10^{-39}$	r = 0.341, p = $1.3 \cdot 10^{-16}$	r = 0.319, p = $1.1 \cdot 10^{-14}$
Subject 13	r = 0.512, p = $1.1 \cdot 10^{-38}$	r = 0.385, p = $1.4 \cdot 10^{-21}$	r = 0.401, p = $4.7 \cdot 10^{-23}$
Subject 14	r = 0.461, p = $8.3 \cdot 10^{-30}$	r = 0.241, p = $1.3 \cdot 10^{-08}$	r = 0.276, p = $7.0 \cdot 10^{-11}$
Subject 15	r = 0.703, p = $1.7 \cdot 10^{-61}$	r = 0.214, p = $1.1 \cdot 10^{-05}$	r = 0.213, p = $1.3 \cdot 10^{-05}$

Angular Correlations

	vestibular	visual	combined
Subject 1	r = 0.254, p = $1.9 \cdot 10^{-08}$	r = 0.302, p = $1.8 \cdot 10^{-13}$	r = 0.437, p = $2.3 \cdot 10^{-27}$
Subject 2	r = 0.156, p = 0.002	r = 0.287, p = $8.6 \cdot 10^{-09}$	r = 0.270, p = $9.2 \cdot 10^{-08}$
Subject 3	r = 0.301, p = $2.2 \cdot 10^{-12}$	r = 0.274, p = $7.3 \cdot 10^{-11}$	r = 0.351, p = $1.7 \cdot 10^{-17}$
Subject 4	r = 0.315, p = $1.3 \cdot 10^{-12}$	r = 0.299, p = $1.7 \cdot 10^{-11}$	r = 0.343, p = $8.9 \cdot 10^{-15}$
Subject 5	r = 0.153, p = 0.003	r = 0.291, p = $6.7 \cdot 10^{-09}$	r = 0.387, p = $3.8 \cdot 10^{-15}$
Subject 6	r = 0.292, p = $5.9 \cdot 10^{-13}$	r = 0.121, p = 0.003	r = 0.224, p = $4.8 \cdot 10^{-08}$
Subject 7	r = 0.098, p = 0.042	r = 0.356, p = $2.4 \cdot 10^{-14}$	r = 0.275, p = $6.0 \cdot 10^{-09}$
Subject 8	r = 0.346, p = $2.0 \cdot 10^{-17}$	r = -0.004, p = 0.920	r = 0.005, p = 0.902
Subject 9	r = 0.093, p = 0.071	r = 0.349, p = $4.1 \cdot 10^{-12}$	r = 0.348, p = $3.1 \cdot 10^{-12}$
Subject 10	r = 0.294, p = $4.7 \cdot 10^{-10}$	r = 0.336, p = $9.6 \cdot 10^{-13}$	r = 0.235, p = $9.0 \cdot 10^{-07}$
Subject 11	r = 0.064, p = 0.183	r = -0.032, p = 0.507	r = 0.027, p = 0.575
Subject 12	r = 0.271, p = $1.2 \cdot 10^{-10}$	r = 0.278, p = $2.7 \cdot 10^{-11}$	r = 0.333, p = $5.6 \cdot 10^{-16}$
Subject 13	r = 0.238, p = $1.2 \cdot 10^{-08}$	r = 0.312, p = $2.5 \cdot 10^{-14}$	r = 0.255, p = $1.0 \cdot 10^{-09}$
Subject 14	r = 0.215, p = $4.3 \cdot 10^{-07}$	r = 0.138, p = 0.001	r = 0.217, p = $3.7 \cdot 10^{-07}$
Subject 15	r = 0.328, p = $1.2 \cdot 10^{-11}$	r = 0.134, p = 0.006	r = 0.137, p = 0.005

Table 2: Pearson's correlation coefficient (r) and corresponding p-value (p) for radial (top) and angular (bottom) correlation between residual error and the time constant τ across participants.

Appendix: Implementation of MC algorithm

STEP 1:

In the first step, the participant's velocity is being transformed into the VR (screen) coordinates. This transformation is necessary to deduce centrifugal components from the participants' trajectory, and include them in the motor commands:

$$v_{t+1}^{VR,x} = v_{t+1}^{JS} \cdot \cos\left(\varphi_t^{VR}\right)$$

$$v_{t+1}^{VR,y} = v_{t+1}^{JS} \cdot \sin\left(\varphi_t^{VR}\right)$$

$$\omega_{t+1}^{VR} = \omega_{t+1}^{JS}$$

Where $v^{VR,x}$ and $v^{VR,y}$ is the linear velocity of the participant in VR coordinates, ω^{VR} is the angular velocity of the VR system, and φ^{VR} is the direction of the platform in space.

STEP 2:

As mentioned before, the arena diameter is finite, and it is necessary to keep track of the participant's position in the arena, to avoid "crashing" on the invisible walls. In this step, the participant's velocity is slowed down when the participant approaches the boundaries of the arena, to account for a "smooth crash".

STEP 3:

Here, the current acceleration is calculated in the VR coordinates $(a^{VR,x}, a^{VR,y})$. This is also where the GIA error feedback loop (see STEP 10) updates the VR acceleration.

$$\alpha_{t+1}^{VR,x} = \frac{v_{t+1}^{VR,x} - v_t^{VR,x} + \frac{dt}{\tau_{MC}} \cdot (v_t^{VR,x} - \hat{v}_t^{VR,x})}{dt}$$

$$\alpha_{t+1}^{VR,y} = \frac{v_{t+1}^{VR,y} - v_t^{VR,y} + \frac{dt}{\tau_{MC}} \cdot (v_t^{VR,y} - \hat{v}_t^{VR,y})}{dt}$$

Where $\hat{v}_t$ is the updated velocity from the previous timestep (τ_{MC} explained in STEP 10). After the acceleration is obtained, it is being transformed back to the participant's coordinates $\left(a^{sub,x}, a^{sub,y}\right)$:

$$\alpha_{t+1}^{sub,x} = \alpha_{t+1}^{VR,x} \cdot \cos\left(\varphi_t^{VR}\right) + \alpha_{t+1}^{VR,y} \cdot \sin\left(\varphi_t^{VR}\right)$$

$$\alpha_{t+1}^{sub,y} = -\alpha_{t+1}^{VR,x} \cdot \sin\left(\varphi_t^{VR}\right) + \alpha_{t+1}^{VR,y} \cdot \cos\left(\varphi_t^{VR}\right)$$

STEP 4:

Now, the acceleration a^{sub} in participant's coordinates, is being transformed into Platform coordinates to take into account the orientation of the participant onto the motion platform (φ_t^{moog}), which is controlled by the yaw motor. For instance, if the participant faces towards the left of the platform and accelerates forward in egocentric coordinates, then the platform should move to the left:

$$\alpha_{t+1}^{desired,x} = \alpha_{t+1}^{sub,x} \cdot \cos\left(\varphi_t^{moog}\right) - \alpha_{t+1}^{sub,y} \cdot \sin\left(\varphi_t^{moog}\right)$$

$$\alpha_{t+1}^{desired,y} = \alpha_{t+1}^{sub,x} \cdot \sin\left(\varphi_t^{moog}\right) + \alpha_{t+1}^{sub,y} \cdot \cos\left(\varphi_t^{moog}\right)$$

Where $\alpha_{t+1}^{desired,x}$ is the desired platform acceleration.

STEP 5:

This is the Motion-Cueing (MC) step. Here, the amount of tilt and translation that will be commanded is computed, based on the tilt-translation trade-off we set. First, the platform's desired acceleration is computed by applying a step response function $f(t)$ to the acceleration input:

$$a^{\text{MC},x}(t) = \int_0^{+\infty} a^{\text{desired},x}(t) \cdot f(t - s) \, ds$$

Where:

$$f(t) = k_1 \cdot e^{-t/T_1} + k_2 \cdot e^{-t/T_2} + k_3 \cdot e^{-t/T_3},$$

$$T = [.07 \quad .3 \quad 1], \quad K = [-0.4254 \quad 1.9938 \quad -0.5684]$$

These coefficients were adjusted to respect the following constraints:

-$f(0) = 1$, i.e. the output would correspond to the input at $t = 0$. This was chosen to ensure that the high-frequency content of the motion would be rendered by translating the platform.

-$\int_0^{\infty} f = 0$: This was chosen to ensure that, if the input was an infinitely long acceleration, the motion of the platform would stabilize to a point where the linear velocity was 0.

-$df/dt = 0$ at $t = 0$. This was chosen because tilt velocity of the platform is equal to $-df/dt$. Since the tilt velocity at t<0 is zero, this constraint ensures that tilt velocity is continuous and prevents excessive angular acceleration at t=0.

The same process is repeated for the y component of the acceleration.

Finally, the amount of tilt (θ, in degrees) is calculated based on the difference between the desired platform motion and the deliverable motion:

$$\theta_{t+1}^{\text{MC},x} = \sin^{-1}\left(\frac{a_{t+1}^{\text{moog},x} - a_{t+1}^{\text{MC},x}}{g}\right)$$

$$\theta_{t+1}^{\text{MC},y} = \sin^{-1}\left(\frac{a_{t+1}^{\text{moog},y} - a_{t+1}^{\text{MC},y}}{g}\right)$$

Where $g = 9.81 \, m/s^2$.

STEP 6:

Afterwards, the tilt velocity and acceleration are being calculated:

$$\dot{\theta}_{t+1}^{\text{MC},x} = \frac{\theta_{t+1}^{\text{MC},x} - \theta_t^{\text{MC},x}}{dt}, \quad \dot{\theta}_{t+1}^{\text{MC},y} = \frac{\theta_{t+1}^{\text{MC},y} - \theta_t^{\text{MC},y}}{dt}$$

$$\ddot{\theta}_{t+1}^{\text{MC},x} = \frac{\dot{\theta}_{t+1}^{\text{MC},x} - \dot{\theta}_t^{\text{MC},x}}{dt}, \quad \ddot{\theta}_{t+1}^{\text{MC},y} = \frac{\dot{\theta}_{t+1}^{\text{MC},y} - \dot{\theta}_t^{\text{MC},y}}{dt}$$

In a next step, we compute the motion command that should be sent by the platform. Note that the platform is placed at a height h below the head. Therefore, tilting the platform by an angle θ induces a linear displacement of the head corresponding to $-h \cdot \theta \cdot \pi/180$. Therefore, a linear displacement is added to the platform's motion to compensate for this. Next, we limit the platform's acceleration, velocity and position commands to ensure that they remain within the limit of the actuators. For this purpose, we define the following function $f_{\lambda,x_{max}}(x)$:

$$\begin{cases} if \ |x| \le \lambda \cdot x_{max}, & f_{\lambda,x_{max}}(x) = x \\ else \ if \ |x| \le (2-\lambda)\cdot x_{max}, & f_{\lambda,x_{max}}(x) = x_{max}.sign(x).\left[|x/x_{max}| - \dfrac{1}{4.(1-\lambda)}.(|x/x_{max}| - \lambda)^2\right] \\ if \ |x| > (2-\lambda)\cdot x_{max}, & f_{\lambda,x_{max}}(x) = sign(x).x_{max} \end{cases}$$

This function is designed so that if the input x increases continuously, e.g. $x(t) = t$, then the output $f_{\lambda,x_{max}}(x(t))$ will be identical to x until x reaches a threshold $\lambda \cdot x_{max}$. After this, the output will decelerate continuously ($\dfrac{d\ f_{\lambda,x_{max}}(x(t))}{dt} = constant$) until it stops at a value x_{max}. We fed the platform's acceleration, velocity and position command through this function, as follows:

$$a_{t+1}^{moog,x} = f_{\lambda,a_{max}}(a_{t+1}^{MC,x} + h \cdot \ddot{\theta}_{t+1}^{MC,x} \cdot \pi/180)$$

$$v_{t+1}^{moog,x} = f_{\lambda,v_{max}}(v_t^{moog,x} + dt.a_{t+1}^{moog,x})$$

$$x_{t+1}^{moog,x} = f_{\lambda,x_{max}}(x_t^{moog,x} + dt.x_{t+1}^{moog,x})$$

The same operation takes place for the y component of the acceleration, as well as for the platform velocity and position. The process is repeated for the tilt command itself.

We set $\lambda = 0.75$ and $a_{max} = 4\ m/s^2$, $v_{max} = 0.4\ m/s$, $x_{max} = 0.23\ m$, $\ddot{\theta}_{max} = 300\ °/s$, $\dot{\theta}_{max} = 30\ °/s$ and $\theta_{max} = 10°$, slightly below the platform's and actuator physical limits. This ensured that the platform's motion matched exactly the motion cueing algorithm's output, as long as it stayed within 75% of the platform's range. Otherwise, the function f ensured a smooth trajectory and, as detailed in STEP 8 to 10, a feedback mechanism was used to update the participant position in the VR environment, so as to guarantee that visual motion always matched inertial motion.

STEP 7:

The motor commands for tilt and translation are being sent to the platform:

$$[x_{t+1}^{moog}, y_{t+1}^{moog}, \theta_{t+1}^{moog,x}, \theta_{t+1}^{moog,y}]$$

STEP 8:

Because of STEP 6, the total Gravito-Inertial Acceleration (GIA) of the platform may differ from what is commanded by the motion cueing algorithm. To detect and discrepancy, we computed the GIA provided by the platform:

$$v_{t+1}^{actual,x} = \dfrac{(x_{t+1}^{moog} - x_t^{moog})}{dt}, \qquad v_{t+1}^{actual,y} = \dfrac{(y_{t+1}^{moog} - y_t^{moog})}{dt}$$

$$a_{t+1}^{actual,x} = \dfrac{(v_{t+1}^{actual,x} - v_t^{actual,x})}{dt}, \qquad a_{t+1}^{actual,y} = \dfrac{(v_{t+1}^{actual,y} - y_v^{actual,y})}{dt}$$

$$GIA_{t+1}^{actual,x} = a_{t+1}^{actual,x} + g \cdot \sin\theta_{t+1}^{moog,x} - h \cdot \ddot{\theta}_{t+1}^{moog,x} \cdot \pi/180$$

$$GIA_{t+1}^{actual,y} = a_{t+1}^{actual,y} + g \cdot \sin\theta_{t+1}^{moog,y} - h \cdot \ddot{\theta}_{t+1}^{moog,y} \cdot \pi/180$$

STEP 9:

We transform platform's GIA, into participant's reference frame:

$$GIA_{t+1}^{\mathrm{sub},x} = GIA_{t+1}^{\mathrm{actual},x} \cdot \cos \varphi_t^{\mathrm{moog}} + GIA_{t+1}^{\mathrm{actual},y} \cdot \sin \varphi_t^{\mathrm{moog}}$$

$$GIA_{t+1}^{\mathrm{sub},y} = -GIA_{t+1}^{\mathrm{actual},x} \cdot \sin \varphi_t^{\mathrm{moog}} + GIA_{t+1}^{\mathrm{actual},y} \cdot \cos \varphi_t^{\mathrm{moog}}$$

Also, the error e^{sub} between the obtained GIA and desired GIA (from STEP 3) is calculated, and fed through the same sigmoid function ($\lambda = .75$, $GIA_{max} = 1\ ^m/_{s^2}$) discussed previously, to avoid computational instability in the case of a big mismatch:

$$e_{t+1}^x = f_{\lambda,GIA_{max}}(GIA_{t+1}^{\mathrm{sub},x} - a_{t+1}^{\mathrm{sub},x})$$

$$e_{t+1}^y = f_{\lambda,GIA_{max}}(GIA_{t+1}^{\mathrm{sub},y} - a_{t+1}^{\mathrm{sub},y})$$

STEP 10:

The GIA error is now used to update the system in the case of a mismatch. First, it is transformed into VR coordinates. Then, the velocity and position in VR coordinates are recomputed based on the joystick input and on the error signal:

$$e_{t+1}^{\mathrm{VR},x} = e_{t+1}^{\mathrm{sub},x} \cdot \cos \varphi_t^{\mathrm{VR}} - e_{t+1}^{\mathrm{sub},y} \cdot \sin \varphi_t^{\mathrm{VR}}$$

$$e_{t+1}^{\mathrm{VR},y} = e_{t+1}^{\mathrm{sub},x} \cdot \sin \varphi_t^{\mathrm{VR}} + e_{t+1}^{\mathrm{sub},y} \cdot \cos \varphi_t^{\mathrm{VR}}$$

$$\hat{v}_{t+1}^{\mathrm{VR},x} = \hat{v}_t^{\mathrm{VR},x} + (a_{t+1}^{\mathrm{VR},x} + e_{t+1}^{\mathrm{VR},x}) \cdot dt$$

$$\hat{v}_{t+1}^{\mathrm{VR},y} = \hat{v}_t^{\mathrm{VR},y} + (a_{t+1}^{\mathrm{VR},y} + e_{t+1}^{\mathrm{VR},y}) \cdot dt$$

$$x_{t+1}^{\mathrm{VR},x} = x_t^{\mathrm{VR},x} + \hat{v}_{t+1}^{\mathrm{VR},x} \cdot dt$$

$$x_{t+1}^{\mathrm{VR},y} = x_t^{\mathrm{VR},y} + \hat{v}_{t+1}^{\mathrm{VR},y} \cdot dt$$

$$\varphi_{t+1}^{\mathrm{VR}} = \varphi_t^{\mathrm{VR}} + \omega_t^{\mathrm{VR}} \cdot dt$$

Note that the error signal is also fed into the acceleration in VR coordinates (see STEP 3). Ideally, linear acceleration should be computed based on the updated velocity value at time t i.e.:

$$\alpha_{t+1}^{\mathrm{VR},x} = \frac{v_{t+1}^{\mathrm{VR},x} - \hat{v}_t^{\mathrm{VR},x}}{dt}$$

However, we found that this led to numerical instability, and instead we introduced a time constant $\tau_{\mathrm{MC}} = 1s$ in the computation, as shown in STEP 3.

References

Angelaki, D. E., & Dickman, J. D. (2000). Spatiotemporal processing of linear accelerations: Primary afferent and central vestibular neuron responses. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.2000.84.4.2113

Arce, F., Novick, I., Shahar, M., Link, Y., Ghez, C., & Vaadia, E. (2009). Differences in context and feedback result in different trajectories and adaptation strategies in reaching. *PLoS ONE*. https://doi.org/10.1371/journal.pone.0004214

Batcho, C. S., Gagné, M., Bouyer, L. J., Roy, J. S., & Mercier, C. (2016). Impact of online visual feedback on motor acquisition and retention when learning to reach in a force field. *Neuroscience*. https://doi.org/10.1016/j.neuroscience.2016.09.020

Bergmann, J., Krauß, E., Münch, A., Jungmann, R., Oberfeld, D., & Hecht, H. (2011). Locomotor and verbal distance judgments in action and vista space. *Experimental Brain Research*. https://doi.org/10.1007/s00221-011-2597-z

Berniker, M., Voss, M., & Kording, K. (2010). Learning priors for bayesian computations in the nervous system. *PLoS ONE*. https://doi.org/10.1371/journal.pone.0012686

Burdet, E., Osu, R., Franklin, D. W., Milner, T. E., & Kawato, M. (2001). The central nervous system stabilizes unstable dynamics by learning optimal impedance. *Nature*. https://doi.org/10.1038/35106566

Campos, J. L., Butler, J. S., & Bülthoff, H. H. (2012). Multisensory integration in the estimation of walked distances. *Experimental Brain Research*. https://doi.org/10.1007/s00221-012-3048-1

Campos, J. L., Byrne, P., & Sun, H. J. (2010). The brain weights body-based cues higher than vision when estimating walked distances. *European Journal of Neuroscience*. https://doi.org/10.1111/j.1460-9568.2010.07212.x

Chen, X., McNamara, T. P., Kelly, J. W., & Wolbers, T. (2017). Cue combination in human spatial navigation. *Cognitive Psychology*. https://doi.org/10.1016/j.cogpsych.2017.04.003

Chrastil, E. R., Nicora, G. L., & Huang, A. (2019). Vision and proprioception make equal contributions to path integration in a novel homing task. *Cognition*. https://doi.org/10.1016/j.cognition.2019.06.010

Chrastil, E. R., Sherrill, K. R., Hasselmo, M. E., & Stern, C. E. (2016). Which way and how far? Tracking of translation and rotation information for human path integration. *Human Brain Mapping*. https://doi.org/10.1002/hbm.23265

Fernandez, C., & Goldberg, J. M. (1976). Physiology of peripheral neurons innervating otolith organs of the squirrel monkey. I. Response to static tilts and to long duration centrifugal force. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.1976.39.5.970

Fernandez, C., Goldberg, J. M., & Abend, W. K. (1972). Response to static tilts of peripheral neurons innervating otolith organs of the squirrel monkey. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.1972.35.6.978

Israël, I., Bronstein, A. M., Kanayama, R., Faldon, M., & Gresty, M. A. (1996). Visual and vestibular factors influencing vestibular "navigation." *Experimental Brain Research*. https://doi.org/10.1007/BF00227947

Jürgens, R., & Becker, W. (2006). Perception of angular displacement without landmarks: Evidence for Bayesian fusion of vestibular, optokinetic, podokinesthetic, and cognitive information. *Experimental Brain Research*. https://doi.org/10.1007/s00221-006-0486-7

Karmali, F., Lim, K., & Merfeld, D. M. (2014). Visual and vestibular perceptual thresholds each demonstrate better precision at specific frequencies and also exhibit optimal integration. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.00332.2013

Kearns, M. J., Warren, W. H., Duchon, A. P., & Tarr, M. J. (2002). Path integration from optic flow and body senses in a homing task. *Perception*. https://doi.org/10.1068/p3311

Klatzky, R. L., Loomis, J. M., Beall, A. C., Chance, S., & Golledge, R. G. (1998). Spatial updating of selfposition and orientation during real. *Psychological Science*.

Koppen, M., Horst, A. C. T., & Pieter Medendorp, W. (2019). Weighted Visual and Vestibular Cues for Spatial Updating during Passive Self-Motion. *Multisensory Research*. https://doi.org/10.1163/22134808-20191364

Körding, K. P., Ku, S. P., & Wolpert, D. M. (2004). Bayesian integration in force estimation. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.00275.2004

Kording, K. P., Tenenbaum, J. B., & Shadmehr, R. (2007). The dynamics of memory as a consequence of optimal adaptation to a changing body. *Nature Neuroscience*. https://doi.org/10.1038/nn1901

Krakauer, J. W., Ghilardi, M. F., & Ghez, C. (1999). Independent learning of internal models for kinematic and dynamic control of reaching. *Nature Neuroscience*. https://doi.org/10.1038/14826

Lackner, J. R., & Dizio, P. (1994). Rapid adaptation to Coriolis force perturbations of arm trajectory. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.1994.72.1.299

Lakshminarasimhan, K. J., Petsalis, M., Park, H., DeAngelis, G. C., Pitkow, X., & Angelaki, D. E. (2018). A Dynamic Bayesian Observer Model Reveals Origins of Bias in Visual Path Integration. *Neuron*. https://doi.org/10.1016/j.neuron.2018.05.040

Mathys, C., Daunizeau, J., Friston, K. J., & Stephan, K. E. (2011). A Bayesian foundation for individual learning under uncertainty. *Frontiers in Human Neuroscience*. https://doi.org/10.3389/fnhum.2011.00039

Petrini, K., Caradonna, A., Foster, C., Burgess, N., & Nardini, M. (2016). How vision and self-motion combine or compete during path reproduction changes with age. *Scientific Reports*. https://doi.org/10.1038/srep29163

Petzschner, F. H., & Glasauer, S. (2011). Iterative Bayesian estimation as an explanation for range and regression effects: A study on human path integration. *Journal of Neuroscience*. https://doi.org/10.1523/JNEUROSCI.2028-11.2011

Prsa, M., Jimenez-Rezende, D., & Blanke, O. (2015). Inference of perceptual priors from path dynamics of passive self-motion. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.00755.2014

Seemungal, B. M., Glasauer, S., Gresty, M. A., & Bronstein, A. M. (2007). Vestibular perception and navigation in the congenitally blind. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.01321.2006

Shadmehr, R., & Mussa-Ivaldi, F. A. (1994). Adaptive representation of dynamics during learning of a motor task. *Journal of Neuroscience*. https://doi.org/10.1523/jneurosci.14-05-03208.1994

Takahashi, C. D., Scheidt, R. A., & Reinkensmeyer, D. J. (2001). Impedance control and internal model formation when reaching in a randomly varying dynamical environment. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.2001.86.2.1047

Tcheang, L., Bülthoff, H. H., & Burgess, N. (2011). Visual influence on path integration in darkness indicates a multimodal representation of large-scale space. *Proceedings of the National Academy of Sciences of the United States of America*. https://doi.org/10.1073/pnas.1011843108

ter Horst, A. C., Koppen, M., Selen, L. P. J., & Pieter Medendorp, W. (2015). Reliability-based weighting of visual and vestibular cues in displacement estimation. *PLoS ONE*. https://doi.org/10.1371/journal.pone.0145015

Tramper, J. J., & Medendorp, W. P. (2015). Parallel updating and weighting of multiple spatial maps for visual stability during whole body motion. *Journal of Neurophysiology*. https://doi.org/10.1152/jn.00576.2015