A deep learning algorithm to translate and classify cardiac

electrophysiology: From induced pluripotent stem cell-derived

cardiomyocytes to adult cardiac cells

Parya Aghasafari PhD[1], Pei-Chi Yang PhD[1], Divya C. Kernik PhD[2], Kauho Sakamoto PhD[4], Yasunari

Kanda PhD[5], Junko Kurokawa PhD[4], Igor Vorobyov PhD[1,6] and Colleen E. Clancy PhD[1,3]

[1] Department of Physiology and Membrane Biology
University of California Davis, Davis, CA
10
11   [2] Washington University in St. Louis
12
13   [4] Department of Bio-Informational Pharmacology
14   School of Pharmaceutical Sciences
15   University of Shizuoka
16   Shizuoka, Japan
17
18   [5] Division of Pharmacology
19   National Institute of Health Sciences
20   Kanagawa, Japan
21
22   [6] Department of Pharmacology
23   University of California, Davis, CA
24
25   [3] Correspondence: Colleen E. Clancy, Ph.D.
26   University of California, Davis
27   Tupper Hall, RM 4303
28   Davis, CA 95616-8636
29   Email: ceclancy@ucdavis.edu
30
31   Phone: 530-754-0254

32   Word count:
33   Subject code: Artificial Intelligence, Machine Learning, Deep Learning, Computational Biology,
34   Arrhythmias, Pharmacology.
35   Short title: Translation of cardiac action potential from immature to mature

Abstract

The development of induced pluripotent stem cell-derived cardiomyocytes (iPSC-CMs) has been a critical in vitro advance in the study of patient-specific physiology, pathophysiology and pharmacology. We designed a new deep learning multitask network approach intended to address the low throughput, high variability and immature phenotype of the iPSC-CM platform. It was trained using simulated action potential (AP) data and applied to classify cells into the drug-free and drugged categories and to predict the impact of electrophysiological perturbation across the continuum of aging from the immature iPSC-CMs to the adult ventricular myocytes. The phase of the AP extremely sensitive to perturbation due to a steep rise of the membrane resistance was found to contain the key information required for successful network multitasking. We also demonstrated successful translation of both experimental and simulated iPSC-CM AP data validating our network by prediction of experimental drug-induced effects on adult cardiomyocyte APs by the latter.

Introduction

The development of novel technologies has resulted in new ways to study cardiac function and rhythm disorders [1]. One such technology is the induced pluripotent stem cell-derived cardiomyocyte (iPSC-CMs) *in vitro* model system [2]. The iPSC-CM system constitutes a powerful *in vitro* tool for preclinical assessment of cardiac electrophysiological impact and drug safety liabilities in a human physiological context [3-8]. Moreover, because iPSC-CMs can be cultured from patient specific-cells, it has shown to be an ideal model system for patient-based medicine [8-10].

While utilization of *in vitro* iPSC-CMs allows for testing of responses to drugs and understanding physiological mechanisms [11-14], there is still a major inherent limitation of the approach: The complex differentiation process to create iPSC-CMs results in a model of cardiac electrical behavior that resembles fetal cardiomyocytes. Hallmarks of the immature phenotype include spontaneous beating, immature calcium handling, presence of developmental currents, and significant differences in the relative contributions of repolarizing potassium currents compared to adult cardiomyocytes (adult-CMs) [15-17]. The profound differences between the immature iPSC-CMs and the adult-CMs have led to persistent questions about the utility and applicability of the iPSC-CM action potential (AP) to predict relevant drug impacts on adult human electrophysiology [18, 19].

Several recent studies have proposed computational frameworks to address the primary limitation in using iPSC-CMs and animal cardiomyocytes for drug screening [11, 12, 20, 21]. The innovative studies described by Tvieto and colleagues [9, 10] presented a translation algorithm that identified a mapping function to identify the relationships between the parameters that are defined by key ion channel conductances in the iPSC-CM APs and the adult-CM APs. In another study by Gong and Sobie, additional insights were revealed through application of an efficient partial least squares regression (PLSR) methodology to translate key physiological features between iPSC-CMs and adult-CMs. They also demonstrated the potential to translate between species, between drug-free and simple drugged models as well as between healthy and diseased phenotypes [20].

Koivumäki et al. also tried to address the problem of iPSC-CMs immaturity by establishing a novel

in silico mathematical model for iPSC-CMs, which can estimate adult-CM behavior [22].

The efficacy of the linear translation algorithms used in the earlier studies relies on a collection of

underlying assumptions [20]. One described by Tvieto et al. is that cardiac protein expression levels

would differ but their functional properties remain invariant during maturation and that a drug

will modify protein function in the same way for iPSC-CMs and the adult-CMs [11]. Tvieto et al.

also acknowledged the difficulty in minimizing the cost function that measures the differences

between the initial and target parameters, which therefore required a brute force search

algorithm for minimization. One possible explanation for the difficulty in cost function

minimization is that linear translation may not capture the nonlinearities comprising the actual

underlying physiological differences [20]. Another underlying assumption with linear translation is

the required representation of drug effects as a simple pore-block, modeled as a reduction in the

maximal conductance of the channel [11, 20]. The earlier studies employed a biased method in

that they rely on *a priori* parameter identification and extraction from voltage and calcium traces

to allow feature mapping from immature to mature conditions [11, 20]. Earlier translators must

also consider drug-free and drugged conditions independently.

In this study, we describe a deep learning multitask network that simultaneously performs

translation and classification of signals from simulated cardiac myocytes for both drug-free and

drugged conditions and we demonstrate its utility for translating and predicting experimental data

as well. The multitask network is an unbiased approach in that the user does not predefine the

important parameters of the system. Rather, the network learns from the data to define important

parameter regimes and data ranges. The new approach is indifferent to the underlying form of the

models and can translate time series data from any source. Moreover, the deep learning approach

accepts non-linearity of the system, makes no assumptions about changes in cardiac protein

expression and function during maturation and can successfully translate simple pore block and

complex conformation state-dependent channel – drug interaction. The network learns from all

of these data sources for robust and successful translation, suggesting broad applicability.

Artificial neural networks are increasingly used to advance personalized medicine [23-27]. Long-

short-term-memory (LSTM) based networks, which are capable of learning order dependence in

sequence prediction problems [28], have been widely used for cardiac monitoring purposes [29-

31]. They have been used to extract important biomarkers from raw ECG signals [32-34] and help

clinicians to accurately detect common heart failure biomarkers in ECG screenings [32, 35-39].

LSTM networks, which can catch existing temporal information in the electronic health records

(EHR), have been highlighted as the best predictive models using real time data [40]. LSTM based

classifiers have also empowered early arrhythmia detection by automatically classifying

arrhythmias using ECG features [41-45]. In addition, deep learning algorithms have been employed

to predict drug-induced arrhythmogenicity associated with blockade of the delayed rectifier K^+

channel current (I_{Kr}) in the CMs encoded by human ether-à-go-go-related gene (hERG) [46] for

sets of small molecules in drug discovery and screening process [46-51].

Here, we implemented a deep learning LSTM based multitask network to classify iPSC-CM AP

traces into drug-free and drugged categories and translate them into adult-CM AP waveforms. To

collect robust realistic simulated data for training the multitask network, we paced simulated

cardiac myocytes with the addition of a physiological noise current at matching cycle lengths for

Kernik *in silico* iPSC-CMs [52] and O'Hara-Rudy *in silico* human adult-CMs [53] to generate a

population of drug-free simulated cardiac myocyte data. To ensure that our model could perform

for both drug-free and drugged iPSC-CM and adult-CM APs simultaneously, we simulated drugged

samples via both a simple drug-induced I_{Kr} block model of hERG channel conduction, G_{Kr}, reduction

by *1-50%* and a complex Markov model of conformation-state dependent I_{Kr} block in the presence

of a clinical concentration, *2.72 ng/mL*, of a potent hERG blocking drug dofetilide from our recent

study [46]. We evaluated the multitask network performance on a test dataset and showed

excellent performance to translate and classify signals in the form of time-resolved AP traces. We

performed an ablation study to reveal the most important iPSC-CM AP information for network

translation into adult-CM APs by removing iPSC-CM AP values during various time frames (feature

ablation). We also explored the importance of individual LSTM network building blocks and how

decoupling of the translation and classification tasks affected overall network performance. We

then showed how proposed multitask network can be applied even to scarce experimental data,

which was also used to validate the model.

In this study we show that developments in iPSC-CM experimental technology and cardiac

electrophysiological modeling and simulation of iPSC-CMs can be leveraged for the application of

artificial neural networks (ANN) as a universal approximator [54] to find the most accurate

mapping function which is capable of learning nonlinear relationships to predict disease

phenotype and drug response in cardiac myocytes from immaturity to maturation.

Results

In this study, we set out to build a multitask network that would perform two distinct tasks: The

first task is to classify iPSC-CM APs into drug-free and drugged categories. The second goal is to

translate iPSC-CM APs into corresponding adult-CM AP waveforms. To collect the data for training

the multitask network, we simulated a population of 208 AP waveforms for both Kernik *in silico*

human iPSC-CMs [52] (Figure 1E blue) and O'Hara-Rudy *in silico* human adult-CMs [53] (Figure 1F

blue). We ensured consistency across a population of simulated myocytes by applying

physiological noise at the matching the cycle lengths into the iPSC-CMs and adult-CMs. The cell

variability in each population is intended to represent the individual variability that is observed in

a drug-free human population [52, 53, 55]. An average AP trace from the population is shown in

Figure 1A for iPSC-CMs and Figure 1B for adult-CMs. In Figure 1 panels C and D, the ionic currents

underlying the *in silico* iPSC-CM APs and adult-CM APs show marked differences, one reason for

the broadly expressed concerns about the applicability of utilizing immature iPSC-CM APs in the

study of human disease and pharmacology. The substantial current differences illustrate the

necessity of a generalized approach to perform translation from immature myocytes into mature

myocytes. To ensure that our multitask network could perform over a range of conditions and

model forms, we simulated drugged iPSC-CM and adult-CM APs via both a simple I_{Kr} drug block

model of G_{Kr} reduction by *1-50%* (250 samples in Figure 1E, F green) and a complex model of

conformation-state dependent I_{Kr} block in the presence of *2.72 ng/mL* dofetilide (300 samples in

Figure 1E, F purple). We combined the drug-free and drugged models with simple and complex I_{Kr}

block model schemes (758 samples) for training the multitask network. The differences in key

parameters, upstroke velocity (V_{max}), maximum diastolic potential (MDP) and action potential

durations (APD) across the three conditions are tabulated and shown in Figure 1G.

Figure 1. Cellular action potential (AP) and ionic currents for iPSC-CMs and adult-CMs (O'Hara-

Rudy human ventricular action potentials). Comparison of Cellular APs in the baseline model of

(A) iPSC-CMs and (B) adult-CMs at a matched cycle length of 982 ms. (C – D) Simulated ionic

current (I_{CaL}, I_{Kr}, I_{Ks}, I_{to}, I_{K1}) profiles during (C) iPSC-CM and (D) adult-CM APs. (E) APs of

spontaneously beating iPSC-CM cells (n =208) and (F) adult-CM APs at matched cycle lengths

were simulated after incorporating physiological noise currents as drug-free (blue) and drugged

I_{Kr} modeled as simple G_{Kr} reduction by *1-50%* I_{Kr} block (green) and a complex model of

conformation-state dependent I_{Kr} block in the presence of *2.72 ng/mL* dofetilide (purple). (G)

Comparison between iPSC-CM and adult-CM drug-free and drugged models with simple and

complex I_{Kr} block model schemes (as indicated in right column), including upstroke velocity

(V_{max}), maximum diastolic potential (MDP) and action potential duration (APD).

Next, we applied a digital forward and backward data filtering technique [56] to the simulated

iPSC-CM and adult-CM AP traces (Figure 2 left panels). Since we applied physiological noise to

introduce a source of variability (as observed in human populations) in our model simulations, we

assessed the possible phase distortion for AP waveforms following noise filtering. In Figure 2 (right

panels), the distribution of iPSC-CM and adult-CM AP duration at 90% repolarization (APD_{90}) values

are shown. The near superimposition of the histogram distributions assures that noise filtering

does not change the AP waveform morphology or time course and primarily removes existing

vertical noises. Panel A and B show simulated drug-free iPSC-CM and adult-CM APs and

corresponding APD_{90} distribution with physiological noise in blue and after applying the noise

filtering technique in black for iPSC-CM APs and red for adult-CM APs. The same plots are

illustrated for drugged AP traces with simple *1-50%* I_{Kr} block (Figure 2C and D) and with complex

I_{Kr} block model in the presence of *2.72 ng/mL* dofetilide (Figure 2E and F). Next, we normalized

drug-free and drugged noise-filtered iPSC-CM APs and adult-CM APs to use them as input and

output, respectively, for training the multitask network.

Figure 2. Application of a digital forward and backward data filtering technique to simulated iPSC-CM and adult-CM APs population (left panels) indicates zero phase distortion for APD_{90} value distributions (right panels) for: (A) drug-free iPSC-CM APs with physiological noise in blue and after applying the noise filtering technique in black; (B) drug-free adult-CM APs – blue and red traces; (C) drugged iPSC-CM APs with *1-50% I_{Kr}* block – green and black traces; (D) drugged

199   adult-CM APs with *1-50%* I_{Kr} block – green and red traces; (E) drugged iPSC-CM APs with *2.72*

200   *ng/mL* dofetilide – purple and black traces. (F) drugged adult-CM APs with *2.72 ng/mL* dofetilide

201   –purple and red traces.

The building blocks of the multitask network are illustrated in Figure 3A. The multitask network

receives preprocessed simulation generated iPSC-CM AP waveforms (noise-filtered and

normalized) as input and scans whole AP time series values through two stacked LSTM layers

(Figure 3A, D). The LSTM layers remember the most important iPSC-CM AP values (features) they

need to perform the translation and classification tasks and passes the information to two fully

connected layers (Figure 3A, E), one for the translation task to predict the corresponding adult-

CM AP waveform (Figure 3B) and one for the classification task to classify iPSC-CM APs into drug-

free and drugged categories (Figure 3C).

Figure 3. The building blocks of the multitask network. (A) The general overview of the multitask network presented in this study. (B) The translation task to reconstruct adult-CM APs from corresponding iPSC-CM APs. (C) The classification task to classify iPSC-CM APs into drug-free and drugged categories. (D) The logic flow process in the LSTM layers. (E) The architecture of the implemented fully connected layers in the multitask network.

The workflow for training and evaluating the multitask network is depicted in Figure 4. As described above, we generated simulated drug-free and drugged iPSC-CM and adult-CM APs and applied a noise filtering technique to the AP waveforms. The waveforms were then normalized in a data preprocessing step for more efficient training of the multitask network. We used preprocessed iPSC-CM APs as the network input and adult-CM APs along with corresponding drug-free and drugged labels as network outputs, respectively. Next, we randomly split input and output data in 70:10:20 ratio into three subcategories: training, validation, and test data sets. We used the training dataset for training the multitask network to simultaneously perform translation and

classification. The mean squared error, R^2-score [57] and error in adult-CM APD_{90} prediction were

used as evaluation metrics for the translation task. For the classification task, area under the

receiver operating characteristic (AUROC) curve [58], network prediction accuracy, precision and

recall [59] were used to evaluate the network performance. To prevent overfitting, we calculated

the evaluation metrics for both tasks using validation data during each iteration of training and

compared those with values from the training dataset. When the model performance on the

training dataset exhibited degradation relative to the validation dataset, we ceased training and

tuning of the network hyperparameters. We evaluated the underlying mechanisms that inform

the network performance by using a holdout test data set to perform an ablation study. The

ablation study allowed us to identify the most important information for network performance

and is an indicator of the data that the network deems most important to remember to allow

accurate translation into adult-CM APs (feature ablation). Finally, we performed a type of network

component dissection by sequentially eliminating individual LSTM layers or the classification task

to determine if all elements of the network are important to the overall performance.

Figure 4. Machine learning workflow in this study: 1) Data preprocessing includes noise-filtering and normalization of the drug-free and drugged iPSC-CM and adult-CM APs; 2) Incorporating the preprocessed iPSC-CM APs as input and adult-CM APs and corresponding labels (drug-free (0) and drugged (1)) of iPSC-CM APs as targets into the multitask network; 3) Splitting the input and target data into training, validation and test set, and using training and validation set for training and tuning the network hyperparameters; 4) Comparing the network performance for training set and validation set to decide when to stop training and tuning the network hyperparameters; 5) Testing the overall multitask network performance using holdout test dataset and removing the LSTM layers, classification task (model ablation) and iPSC-CM AP values at different time frames (feature ablation) to study the performance of the network in the absence of its building blocks.

Figure 5 and Table 1 illustrate the overall multitask network performance for translation and classification tasks for the training and test data sets. Panels A and D in Figure 5 represent iPSC-CM APs (black), which were used for training and testing the multitask network, respectively.

 Panels B and E depict the comparison between simulated (red) and translated (cyan) adult-CM APs

254 used for the training and testing the network. The comparison between histogram distribution of

255 APD$_{90}$ values for simulated and translated adult-CM APs in Figure 5C and F show good agreement

256 in terms of the frequency of virtual cells with similar APD.

Figure 5. The performance of the multitask network for translating iPSC-CM APs into adult-CM
APs. (A) The iPSC-CM APs used for training the multitask network contained a variety of drug-
free and drugged action potential morphologies (Training set). (B) Comparison between
simulated (red) and translated adult-CM APs (cyan) in the training set. (C) Comparison between
the histogram distribution of APD$_{90}$ values for simulated and translated adult-CM APs in the
training set. (D) Dedicated iPSC-CM APs for testing the performance of the multitask network
(Test set) (E) Comparison between simulated (red) and translated adult-CM APs (cyan) in the test
set. (F) Comparison between histogram distribution of APD$_{90}$ values for simulated and translated
adult-CM APs in the test set.

The performance evaluation metrics for both the translation and classification tasks are listed in

Table 1. The multitask network exhibits high accuracy in performing translation, despite large

variability in APDs and regardless of the underlying model form. The network is able to translate

iPSC-CM APs into adult-CM APs with less than *0.003* mean-squared error (MSE), *0.99* R^2_score and

less than *4%* error in APD$_{90}$ prediction for both training and test datasets. To evaluate the network

performance for the classification task we compared the AUROC, prediction accuracy, recall and

precision for both training and test datasets. The multitask network proved to perform well in

categorizing iPSC-CM APs into drug-free and drugged waveforms with approximately *90%*

accuracy (Table 1). Finally, we performed a type of network component dissection by sequentially

eliminating individual LSTM layers or the classification task to determine if all elements of the

network are important to the overall performance. The impact of removing these elements of the

network on the network performance is shown in Table 1.

Table 1. Statistical measures for evaluating the performance of the multitask network for both
iPSC-CM AP trace classification into drug-free and drugged categories and their translation into
adult-CM APs for training and test datasets as well as the effect of removing LSTM layers and
classification task on the network performance.

Translation			
Performance metrics	MSE	R^2_score	Error in APD_{90} prediction
Training dataset	0.0027	0.992	3.41%
Test dataset	0.0029	0.991	3.60%
Remove LSTM layers test dataset	0.0031	0.991	3.78%
Remove classification task test dataset	0.0034	0.990	4.33%
Classification			
Performance metrics	AUROC	Accuracy	Recall	Precision
Training dataset	0.93	92%	0.92	0.93
Test dataset	0.91	92%	0.92	0.92
Remove LSTM layers test dataset	0.90	92%	0.90	0.91

Next, we performed a "computational" ablation study as a correlate to the types of physiological

ablations that are used to examine the roles and functions of a physiological system [60, 61]. We

tested how the performance of the multitask network would change by removing various

information contained within specified time frames as shown in Figure 6A. To reveal the most

important iPSC-CM AP information for translation into adult-CM APs, we did not allow the network

to process data from within designated time frames from the iPSC-CM APs (feature ablation). We

then retrained the multitask network by setting the missing information equal to zero and

compared the calculated MSE in adult-CM APs translation (red bars) with the recorded MSE for

multitask network (green line) when it was provided full access to the complete iPSC-CM AP data.

We observed that network is extremely sensitive to information contained within the *400-500 ms*

timeframe (blacked dashed bar in Figure 6A).

This result suggests that the most important information needed to distinguish adult-CM AP

signals from iPSC-CM AP signals is contained in a particular region of the AP plateau. The

timeframe of the AP between 400 and 500 ms (Figure 6A), corresponds to a phase of exquisite

sensitivity to perturbation. We have identified this particular AP range in an earlier study as the

phase when the membrane resistance of the myocyte increases markedly (Figure 6B) [62]. This

occurs as the inward and outward currents balance each other, leading to a net whole cell current

that is nearly constant so that dI → 0, dV/dI → ∞ (Figure 6C), followed by a rapid reduction in

outward current. Figure 6D demonstrates that individual current densities have a period of inward

and outward current balance followed by rapid changes in I_{Kr} and other repolarizing currents at

400-500 ms time interval.

Figure 6. The feature ablation study on the proposed multitask network is performed by
removing iPSC-CM AP values during different time frames and evaluating their importance on
adult-CM AP translation. The largest effect (most important information) is observed at *400-500*
ms interval (dotted black line). (A) Comparison between intact multitask network MSE (cyan line)
and obtained MSE values for adult-CM AP translation during removal of indicated time frames
within iPSC-CM APs (red bars). (B) AP trace (green) and membrane resistance (red) as a function
of simulation time indicating very high values (as dI → 0, dV/dI → ∞) for the latter at *400-500*

ms. (C) Total current density, I$_{total}$, demonstrates a plateau followed by a rapid decline at *400-500*
ms. (D) Individual current densities indicate a period of inward and outward current balance
followed by rapid changes in *I$_{kr}$* and other repolarizing components at *400-500 ms* time interval.

319
We next set out to demonstrate the real-world utility of the multitask classification and translation

network by applying the network to experimental data. We used experimental iPSC-CM APs from

the Kurokawa lab (Figure 7A) as the input data into the multitask network and translated to

predicted adult-CM APs as shown in Figure 7B. The translation notably resulted in a reduction in

variability in APD in the adult translated cells, consistent with our simulated results and with

previous experimental observations [18, 63]. In an additional validation of the multitask network,

we undertook a test of the network to accurately translate drug block in iPSC-CMs to adult AP

effects and then compared the predicted results with measured experimental data [53]. We first

simulated iPSC-CM APs with *50%* block of *I$_{kr}$*. We then used these simulated APs as an input for

the multitask network and used the output from the translation task to predict *50%* block on adult-

CMs. In Figure 7C, the translated drugged APD$_{90}$ values are shown as turquoise asterisks plotted

against simulations from O'Hara-Rudy adult-CM APs with *50% I$_{kr}$* block (red curve) and

experimental *50%* block of *I$_{kr}$* by *1μM* E-4031 (blue squares) [53]. These data validate that the

effects of drug block in iPSC-CMs can be successfully translated to predict its effect on adult human

cardiomyocyte APs.

335
336

Figure 7. Translation of experimentally recorded iPSC-CM APs into adult-CM APs to validate the
multitask network performance. (A) Experimentally recorded iPSC-CM APs from the Kurokawa
lab. (B) Translated adult-CM APs from experimentally recorded iPSC-CM APs via the multitask
network. (C) Comparing translated adult-CM APD_{90} values with *50% I_{Kr}* block (turquoise asterisks)

with previously published simulated (red curve for drugged and black for drug-free control) and

experimental (blue squares) values from O'Hara-Rudy study [1] indicates model validation.

Discussion

In this study, we developed a data-driven deep learning approach to address well known

shortcomings in the induced pluripotent stem cell-derived cardiomyocyte (iPSC-CM) platform. A

concern with iPSC-CM is that the data collection results in measurements from immature action

potentials, and it is unclear if these data reliably indicate impact in the adult cardiac environment

[14, 64-68]. Here, we set out to demonstrate a new way to allow translation of results from the

iPSC-CM to a mature adult cardiac response. The deep learning network also revealed new

mechanisms that are critical to convert iPSC-CM APs to mature adult cardiac APs.

Application of a deep learning artificial neural network to simultaneously translate and classify

signals from simulated iPSC-CMs for both drug-free and drugged conditions has several key

advantages. Because there is no need for the multitask network user to *a priori* define the

important system parameters, the approach is by definition an unbiased model. A key part of the

"artificial intelligence" is learning from the data to make decisions about which elements of the

data are the most important. Another benefit is the model-agnostic approach in that the learning

network is indifferent to the underlying form of the models and can readily translate time series

data from any source. The non-linearity of the system is accepted by the deep learning approach,

and there are no assumptions made about cardiac protein expression levels and changes in their

function during cardiomyocyte maturation. The deep learning artificial neural network can

successfully translate simple pore block and complex conformation state-dependent channel –

drug interaction models. The network can learn from multiple sources of data even when they are

generated from different models and learns from all the data sources concurrently for robust and

successful translation. All of these aspects of the technology presented here suggest broad

applicability for use across ages, species and conditions and we demonstrate its utility for

translating and predicting experimental data.

The multitask network presented here performed well in the setting of the noted variability in

measurements from iPSC-CM APs. As described in Figure 1, we utilized a modeling and simulation

approach from our recent study [52, 69] to generate a population of iPSC-CM action potentials

that incorporate variability comparable to that in experimental measurements. Utilizing simulated

data presented a unique opportunity: We were able to generate large amounts of data that were

used both to train and optimize the network and then to test the network with specifically

designated distinct simulated data sets. Utilizing simulated data to train a deep learning network

may constitute a widely applicable approach that could be used to train variety of networks to

perform multiple functions where access to comparable experimental data is not feasible.

The multitask network exhibits high accuracy in performing translation, despite large variability in

APDs and regardless of the underlying model form (Figure 5 and Table 1). The network was able

to translate iPSC-CM APs into adult-CM APs with less than *0.003* mean-squared error (MSE), *0.99*

R^2_score and less than *4%* error in APD_{90} prediction for both the training and test dataset. To

evaluate the network performance for the classification task we compared the AUROC, prediction

accuracy, recall and precision for both training and test datasets. The multitask network proved to

perform well in categorizing iPSC-CM APs into drug-free and drugged waveforms with

approximately *90%* accuracy (Table 1). Finally, we performed a type of network component

dissection by sequentially eliminated individual LSTM layers or the classification task to determine

if all elements of the network are important to the overall performance. The impact of removing

these elements of the network on its performance is shown in Table 1. The studies show that the

multi-task network conferred additional benefit over considering the translation task alone. For

example, we noted that adding the classification task to distinguish drug-free and drugged action

potentials could improve the performance of the translation task (Table 1).

When we performed an ablation study to prevent the deep learning network from using

information within prespecified time windows, the results revealed that the most important

information needed to predict adult-CM APs from iPSC-CM AP signals is contained in the phase of

the AP between 400 and 500 ms (Figure 6). This result suggests that the most important

information needed to distinguish iPSC-CM AP signals from adult-CM AP signals is contained in the

range of the AP that corresponds to a phase of exquisite sensitivity to perturbation. We have

identified this particular AP range in an earlier study as the phase when the membrane resistance

of the myocyte increases markedly (Figure 6B) [62].This occurs as the inward and outward currents

balance each other, leading to a net whole cell current that is unchanging (dI $\rightarrow$ 0, dV/dI $\rightarrow$ ∞),

followed by a rapid reduction in the outward current (Figure 6C and D).

Following the optimization and demonstration of the network as an accurate tool for both

translating and classifying data, we then used the same network to translate experimentally

obtained data. We showed that the proposed network can effectively take experimental data as

an input from immature iPSC-CM APs and translate those data to produce adult action potential

waveforms. It is notable that the variation observed in the adult-CM AP duration is smaller

compared to iPSC-CM APDs (Figure 7A-B). This has been observed both experimentally [18, 63]

and in our simulated cell environment [52, 69] . Although the simulated iPSC-CM has a large initial

calcium current (Figure 1C) compared to the simulated adult-CM (Figure 1D), the amplitude of

currents flowing through adult-CM action potential plateau is notably larger. The immature iPSC-

CM cells have low conductance during the AP plateau rendering it comparably higher resistance.

For this reason, small perturbations to the iPSC-CM APs have a larger impact on the resulting AP

duration than observed in adult cells [62]. We also used simulated iPSC-CM APs subject to *50%*

block of I_{Kr}. We translated those data to adult-CM APs and then compared with the previously

reported impact of *50%* I_{Kr} block on adult human cell APs from experiments [53] and noted

excellent agreement thereby providing validation of our network.

In this study, we show that a deep learning network can be applied to classify cells into the drug-

free and drugged categories and can be used to predict the impact of electrophysiological

perturbation across the continuum of aging from the immature iPSC-CM action potential to the

adult ventricular myocyte action potential. We translated experimental immature APs into mature

APs using the proposed network and validated the output of some key model simulations with

experimental data. The multitask network in this study was used for translation of iPSC-CMs to

adult APs but could be readily extended and applied to translate data across species and classify

data from a variety of systems. Also, another extension of the technology presented here is to

predict the impact of naturally occurring mutations and other genetic variations [70].

Methods

Simulated data for training and testing the multitask network:

The drug-free iPSC-CM and adult-CM action potentials

The Kernik *in silico* iPSC-CM baseline cells were paced from resting steady-state. The O'Hara-Rudy

in silico endocardial cell model was used for the baseline adult-CMs [53]. The control adult-CMs

were paced at the cycle length of *982 ms* to match the cycle length of the last beat of the

spontaneously depolarizing iPSC-CM AP. The iPSC-CM AP populations (n =208) were generated by

incorporating physiological noise (see **Simulated physiological noise currents** section below). The

adult-CMs were paced with noise for *100* beats after reaching steady state at the matching cycle

length of the last beat of iPSC-CM AP populations. The numerical method used for updating the

voltage was Forward Euler method [71].

A simple drug-induced 1-50% I_{Kr} block model through G_{Kr} reduction

The iPSC-CMs and the adult-CMs populations were paced with 1-50% I_{Kr} block with 1% increments.

This was accomplished by scaling down hERG channel (I_{Kr}) conduction, G_{Kr} , by the fraction of the

block, $G_{Krscale}$, in the $0.50 - 0.99$ range with 0.01 decrements (see central rows in Fig. 1G). The

adult-CM model was simulated at five varying beating rates for each percentage of block that

matches to the last beat of iPSC-CMs with *1-50% I_{Kr}* block (n = 250). For example, one drugged

adult-CM (*50% I_{Kr}* inhibition) was paced at cycle length of *1047 ms* to match the cycle length of

the last beat of iPSC-CMs AP with *50% I_{Kr}* block.

Complex model of conformation-state dependent I_{Kr} block in the presence of 2.72 ng/mL dofetilide

The I_{Kr} channel Hodgkin-Huxley model in both iPSC-CM and adult-CM AP models was replaced with

a drug − hERG channel interaction Markov model (see bottom rows in Fig. 1G) that we have

previously published [72]. iPSC-CM (*n* = 300) and adult-CM AP populations (*n* = 300) were generated with physiological noise in the presence of *2.72 ng/mL* dofetilide, a potent hERG channel blocker. The adult-CM populations were paced with dofetilide for 100 beats after reaching steady state at the matching cycle length of the last beat of iPSC-CM AP populations with dofetilide as described above.

Simulated physiological noise currents:

Simulated noise current was added to the last 100 paced beats in the simulated AP models, and simulated APs were recorded at the 2000th paced beat in single cells. This noise current was modeled using the equation from [55],

$$V_{t+\Delta t} = V_t - \frac{I(V_t)\Delta t}{C_m} + \xi n\sqrt{\Delta t} \qquad (1)$$

Where $n \in N(0,1)$ is a random number from a Gaussian distribution, and Δt is the time step. $\xi = 0.3$ is the diffusion coefficient, which is the amplitude of noise. The noise current was generated and applied to membrane potential, V_t, throughout the last 100 beats of simulated time course.

Experimental iPSC-CMs:

Human iPSC-CMs (201B7, RIKEN BRC, Tsukuba, Japan) were cultured and subcultured on *SNL76/7* feeder cells as described in detail previously [73]. Cardiomyocyte differentiation was performed as described [73]. Commercially available iCell-cardiomyocytes (FUJIFILM Cellular Dynamics, Inc., Tokyo, Japan) were cultured according to the manual provided from the company. Action potentials were recorded with the perforated configuration of the patch-clamp technique as described in detail previously [73]. Measurements were performed at *36 ± 1 °C* with the external solution composed of (in *mM*): *NaCl* (*135*), *NaH₂PO₄* (*0.33*), *KCl* (*5.4*), *CaCl₂* (*1.8*), *MgCl₂* (*0.53*), glucose (*5.5*), *HEPES*, *pH 7.4*. To achieve patch perforation (*10-20 MΩ*; series resistances), amphotericin B (*0.3-0.6 µg/mL*) was added to the internal solution composed of (in *mM*): aspartic acid (*110*), *KCl* (30), *CaCl₂* (*1*), adenosine-*5'*-triphosphate magnesium salt (*5*), creatine phosphate disodium salt (*5*), *HEPES* (*5*), *EGTA* (*11*), *pH 7.25*. In quiescent cardiomyocytes, action potentials were elicited by passing depolarizing current pulses (*2 ms* in duration) of suprathreshold intensity (*120 %* of the minimum input to elicit action potentials) with a frequency at *1 Hz* unless noted otherwise.

The multitask network architecture:

The multitask network was comprised of two stacked LSTM layers followed by independent fully

connected layers (Figure 3A) for the classification and translation tasks.   The LSTM layers

memorized the important information the network needed to perform two discussed tasks and

then transferred the extracted information (features) into the subsequent fully connected layers

to translate iPSC-CM APs into adult-CM AP waveforms (Figure 3B) and classify iPSC-CM APs into

drug-free and drugged categories (Figure 3C).

Long-short term memory (LSTM) layers (Figure 3D):

We used LSTM layers as the first two layers of the multitask network to promote network temporal

information learning which data in a sequence was important to keep or to throw away. At each

time step, the LSTM cell took in three different pieces of information, the current input data

(AP_{iPSC_t}), incoming short-term memory (hidden state) (h_{t-1}) and incoming long-term memory

(cell state) (C_{t-1}). The LSTM layers were responsible for extracting the most important

information while scanning the AP traces using the short- and long-term memory components.

The short-term memory weighted the importance of AP values at subsequent time steps and long-

term memory has been using the short-term memory to decide the overall importance of all AP

values from the beginning (t = 0 ms) to the end (t = 701 ms) for performing classification and

translation tasks. The LSTM cells contained internal mechanisms called gates. The gates were

neural network with weights (w) and bias terms (b) that regulated the flow of information at each

time step before passing on the long-term and short-term information to the next cell [74]. These

gates are called input gate, forget gate, and output gate (Figure 3D).

The forget gate, as the name implies, determined which information from the long-term memory

should be kept or discarded. This was done by multiplying the incoming long-term memory by a

forget vector generated by the current input (AP_{iPSC_t}) and incoming short-term memory (h_{t-1}).

To obtain the forget vector, the incoming short-term memory and current input were passed

through a sigmoid function (σ_f) [75]. The output vector of sigmoid function, F_t, (Eq. 2) was a binary

comprising 0s and 1s and was then multiplied by the incoming long-term memory (C_{t-1}). to

choose, which parts of the long-term memory were retained.

$$F_t = \sigma_f\left(w_f AP_{iPSC_t} + w_f h_{t-1} + b_f\right) \quad t \in \{0,1,\dots,701\} \tag{2}$$

The input gate decided what new information is being stored in current long-term memory (C_t).

It considered the current input (AP_{iPSC_t}) and the incoming short-term memory (h_{t-1}) and

transformed the values to be between 0 (unimportant) and 1 (important) using a sigmoid

activation function (σ_i) (Eq. 3). The second layer in input gate took the incoming short-term

memory (h_{t-1}) and current input (AP_{iPSC_t}) and passed them through a hyperbolic tangent

activation function ($tanh_i$) to regulate the network computation (Eq. 4).

$$I_t = \sigma_i\left(W_i AP_{iPSC_t} + W_i h_{t-1} + b_i\right) \quad t \in \{0,1,\dots,701\} \tag{3}$$

$$S_t = tanh_i\left(w_s AP_{iPSC_t} + w_s h_{t-1} + b_s\right) \tag{4}$$

The outputs from the forget and input gates then underwent a pointwise addition to find the

current long-term memory (C_t) (Eq . 5), which was then passed on to the next cell.

$$C_t = F_t * C_{t-1} + I_t * S_t \tag{5}$$

Finally, the output gate utilized current input (AP_{iPSC_t}) and the incoming short-term memory

(h_{t-1}) and passed them into a sigmoid function (σ_o) (Eq. 6). Then the current long-term memory

(C_t) passed through a $tanh$ activation function ($tanh_o$) and the outputs from these two processes

were multiplied to produce the current short-term memory h_t (Eq. 7).

$$O_t = \sigma_o\left(w_o AP_{iPSC_t} + w_o h_{t-1} + b_o\right) \tag{6}$$

$$h_t = O_t * tanh_o(C_t) \tag{7}$$

The short-term and long-term memory produced by these gates were carried over to the next cell

for the process to be repeated. The output of LSTM layers for each time step (h_t) was obtained

from the short-term memory, also known as the hidden state, and was subsequently passed into

fully connected layers to perform the translation and classification tasks as described below.

Fully connected layers (Figure 3E):

The fully connected neural network layers contained input, hidden and output layers (Figure 2E)

with various numbers of neurons (l_r). Every neuron in a layer was connected to neurons in the

next layer [76]. Fully connected layers received the output of LSTM layers as input. The fully

connected layers calculated a weighted sum of LSTM outputs and added a bias term to the

outputs. These data were then passed to an activation function (f) to define the output for each

neuron (Eqs. 8 and 9) [77].

$$a_j^k = f(Z_j^k) \qquad (8)$$

$$Z_j^k = W_{i,j}^k * a_j^{k-1} + b^k \qquad (9)$$

Where $k \in \{1, \dots, n\}$ and (i, j) represent the number of hidden layers and neurons in each pair of

subsequent hidden layers (l_r, l_{r+1}). The optimized values for these parameters were found via

hyperparameter tunning where, a^k is each neuron output where $a^0 \in \{h_1, \dots, h_m\}$ is the LSTM

layers output and the input to the fully connected layers and a^{n+1} is the network output:

$\hat{y} \in \{y_{t_i}, y_{c_i}\}$ where y_{t_i} and y_{c_i} are the outputs for translation and classification tasks, respectively.

We first assigned random values to all network parameters θ_t; each neuron weight $(W_{i,j})$ (Figure

3E), bias term (b) which is a constant added to calculate the neurons output and other network

hyperparameters (the number of hidden layers, the number of neurons for each hidden layer and

activation functions for each hidden layer) to start the optimization process for finding the best

network infrastructure. Next, we estimated the network errors using mean squared error, MSE

(Eq. 10) and cross-entropy loss functions (Eq. 11) to map the translation and classification tasks

[54, 78], respectively.

$$MSE = \frac{1}{m} \sum_{i=1}^{n} \left\| y_{t_i} - \hat{y}_{t_i} \right\|^2 \qquad (10)$$

$$CrossEntropy = -\left(y_{c_i} \log(\hat{y}_{c_i}) + (1 - y_{c_i}) \log(1 - \hat{y}_{c_i}) \right) \qquad (11)$$

where m is the total number of LSTM layers outputs (h_m) and y_{t_i} and $\hat{y}_{t_i}$ are the simulated and

translated adult-CM APs (the network output for translation task). The y_{c_i} is binary indicator of

class labels for iPSC-CM APs (0 for drug-free or 1 for drugged categories) and $\hat{y}_{c_i}$ is predicted

probability of APs being classified into the discussed classes. We used sum of both loss functions

(Eq. 12) to calculate the overall network error (J) for both translation and classification tasks during

the network training process. We updated network parameters (θ_{t+1}) using adaptive momentum

estimation (ADAM) optimization algorithm [79] based on the average gradient of overall loss

function with respect to the network parameters for 64 randomly selected simulated AP traces

(mini-batch = 64) at each training iteration (Eqs. 13-15).

$J(\theta_t) = CrossEntropy_{Classification}(\theta_t) + \text{MSE}_{Translation}(\theta_t)$ (12)

$\theta_{t+1} = \theta_t - \frac{\alpha.\hat{m}_t}{\sqrt{\hat{v}_t}+\epsilon}$, $\theta_t \in \{W_{i,j}^n, b_j^{\ n}\}$ (13)

$\hat{m}_t = \frac{m_t}{1-\beta_1}$,   where $m_t = (1-\beta_1)\nabla J(\theta_t) + \beta_1 m_{t-1}$ (14)

$\hat{v}_t = \frac{v_t}{1-\beta_2}$,   where $v_t = (1-\beta_2)\big(\nabla J(\theta_t)\big)^2 + \beta_2 v_{t-1}$ (15)

We used a rectified linear unit (ReLu) [80] as activation function in Eq. 8 to calculate the output

for each hidden layer neuron at each training iteration. We used dropout regularization [81] to

randomly drop neurons with 0.2 probability of elimination along with their connections from the

LSTM and fully connected layers during training to reduce the overfitting. We kept updating the

network parameters using ADAM optimization algorithm (Eq. 13) to find global minimum of loss

function (Eq. 12). We computed the exponential average of the gradient (Eq. 14) as well as the

square of the gradient (Eq. 15) for each parameter (θ_t) where α is the learning rate equal to 0.001,

β_1, β_2 are first and second momentum coefficients equal to *0.9* and *0.999*, and ϵ is a small term

equal to *1e-8* preventing division by zero.

587   Computational workflow (Figure 4)

We first preprocessed iPSC-CM and adult-CM APs by applying a digital forward and backward data

filtering technique [56] and normalizing the AP values for more efficient training process. Next, we

split the preprocessed data in 70:10:20 ratio into training, validation and test data sets,

respectively, and implemented the network architecture using Pytorch [82]. During the training

process the multitask network received iPSC-CM AP time course data as inputs and predicted

adult-CM AP time courses. The network also received the category (drug-free and drugged) of the

iPSC-CM AP data. The network next calculated the MSE (Eq. 10) between predicted AP waveforms

and the expected waveforms for adult-CM APs. It also calculated cross-entropy (Eq. 11) between

the predicted category for the iPSC-CM AP and the expected value. The cross-entropy was added

to the calculated MSE to determine the total loss for training. The ADAM optimization algorithm

was then used to update the network weights and bias terms.

We performed updating the network parameters (Eq. 13) and monitored the network

performance for the training and validation data sets until the point at which the network

performance on the training data set began to degrade compared to the validation dataset. This

process was used to identify the optimal number of iterations (epochs = 300) for the training

process. The last trained network was designated as the best possible model to perform both

translation and classification tasks. We then used a holdout test dataset and calculated MSE (Eq.

10), R^2_score (Eqs. 16-17 below) and the error in prediction for adult-CM APD_{90} as evaluation

metrics to assess the performance of the network for translation task and the area under the

receiver operating characteristic (AUROC) curve, accuracy, recall and precision to measure

capability of network for classification task as described below. The network codes have been

made   publicly   available   at   Clancy   lab   Github.

(https://github.com/ClancyLabUCD/Multitask_network)

Evaluation metrics for the translation and classification tasks

As we discussed, we used MSE and cross-entropy loss functions for performance evaluation of

translation and classification tasks. In addition to MSE, we computed R^2_score [57] (Eqs. 16,17) to

measure how close the translated adult-CM AP $(\hat{y}_{t_i})$ was to the expected simulated adult-CM AP

(y_{t_i}). We compared the histogram distribution of simulated and translated adult-CM APD_{90} values

and the error in APD_{90} prediction to assess the accuracy of network prediction.

$$\bar{\hat{y}}_{t_i} = \frac{1}{m}\sum_{i=1}^{m} \hat{y}_{t_i} \tag{16}$$

$$R^2 = \frac{\Sigma_i(\hat{y}_{t_i} - \bar{\hat{y}}_{t_i})}{\Sigma_i\left(y_{t_i} - \bar{y}_{t_i}\right)} \tag{17}$$

We used AUROC to measure the capability of the model to distinguish between drug-free and

drugged iPSC-CM APs [58]. AUROC is the area under the Receiver Operating Characteristic (ROC)

curve, which is a plot of the false positive rate (FPR), the probability that the network classified

drug-free iPSC-CM APs into drugged categories (FP) (Eq. 18) versus the true positive rate (TPR) or

recall, the probability that the network correctly classified drugged iPSC-CM APs into drugged

category (TP) (Eq. 19). AUROC close to 1 indicated a model with a desirable measure of

separability, while a poor model had AUROC near 0, which means that it had poor separability.

In addition, we used recall, accuracy, and precision to describe the performance of the network

for the classification task [13], where the accuracy and precision indicated the proportion of all

correct, TP + true negatives (TN), i.e., predicted drug-free APs (Eq. 20) and correct positive

identifications (Eq. 21). False negatives (FN) in Eqs. 19-20 were the total number of drugged iPSC-

CM APs classified as drug-free.

$$\text{FPR} = \frac{FP}{FP+TN} \qquad (18)$$

$$\text{Recall} = \frac{TP}{TP+FN} \qquad (19)$$

$$\text{Accuracy} = 100 * \frac{TP + TN}{TP+TN+FP+FN} \qquad (20)$$

$$Precision = \frac{TP}{TP+FP} \qquad (21)$$

References

1. Shaheen, N., et al., *Human induced pluripotent stem cell-derived cardiac cell sheets*
expressing genetically encoded voltage indicator for pharmacological and arrhythmia
studies. Stem cell reports, 2018. **10**(6): p. 1879-1894.
https://doi.org/10.1016/j.stemcr.2018.04.006
2. Leyton-Mange, J.S., et al., *Rapid cellular phenotyping of human pluripotent stem cell-*
derived cardiomyocytes using a genetically encoded fluorescent voltage sensor. Stem cell
reports, 2014. **2**(2): p. 163-170. https://doi.org/10.1016/j.stemcr.2014.01.003
3. Sun, N., et al., *Patient-specific induced pluripotent stem cells as a model for familial*
dilated cardiomyopathy. Sci Transl Med, 2012. **4**(130): p. 130ra47.
https://doi.org/10.1126/scitranslmed.3003552
4. Lan, F., et al., *Abnormal calcium handling properties underlie familial hypertrophic*
cardiomyopathy pathology in patient-specific induced pluripotent stem cells. Cell Stem
Cell, 2013. **12**(1): p. 101-13. https://doi.org/10.1016/j.stem.2012.10.010
5. Burridge, P.W., et al., *Human induced pluripotent stem cell-derived cardiomyocytes*
recapitulate the predilection of breast cancer patients to doxorubicin-induced
cardiotoxicity. Nat Med, 2016. **22**(5): p. 547-56. https://doi.org/10.1038/nm.4087

6. Doss, M.X. and A. Sachinidis, *Current challenges of iPSC-based disease modeling and therapeutic implications.* Cells, 2019. **8**(5): p. 403. https://doi.org/10.3390/cells8050403

7. Collins, T.A., M.G. Rolf, and A. Pointon, *Current and future approaches to nonclinical cardiovascular safety assessment.* Drug Discovery Today, 2020. https://doi.org/10.1016/j.drudis.2020.03.011

8. Wu, J.C., et al., *Towards precision medicine with human iPSCs for cardiac channelopathies.* Circulation research, 2019. **125**(6): p. 653-658. https://doi.org/10.1161/CIRCRESAHA.119.315209

9. Sayed, N., C. Liu, and J.C. Wu, *Translation of human-induced pluripotent stem cells: from clinical trial in a dish to precision medicine.* Journal of the American College of Cardiology, 2016. **67**(18): p. 2161-2176. http://dx.doi.org/10.1016/j.jacc.2016.01.083

10. Matsa, E., J.H. Ahrens, and J.C. Wu, *Human induced pluripotent stem cells as a platform for personalized and precision cardiovascular medicine.* Physiological Reviews, 2016. **96**(3): p. 1093-1126. https://doi.org/10.1152/physrev.00036.2015

11. Tveito, A., et al., *Inversion and computational maturation of drug response using human stem cell derived cardiomyocytes in microphysiological systems.* Scientific reports, 2018. **8**(1): p. 1-14. https://doi.org/10.1038/s41598-018-35858-7

12. Tveito, A., et al., *Computational translation of drug effects from animal experiments to human ventricular myocytes.* Scientific Reports, 2020. **10**(1): p. 1-11. https://doi.org/10.1038/s41598-020-66910-0

13. Sube, R. and E.A. Ertel, *Cardiomyocytes Derived from Human Induced Pluripotent Stem Cells: An In-Vitro Model to Predict Cardiac Effects of Drugs.* Journal of Biomedical Science and Engineering, 2017. **10**(11): p. 527. https://doi.org/10.4236/jbise.2017.1011040

14. Navarrete, E.G., et al., *Screening drug-induced arrhythmia using human induced pluripotent stem cell–derived cardiomyocytes and low-impedance microelectrode arrays.* Circulation, 2013. **128**(11_suppl_1): p. S3-S13. https://doi.org/10.1161/CIRCULATIONAHA.112.000570

15. Lieu, D.K., et al., *Mechanism-based facilitated maturation of human pluripotent stem cell-derived cardiomyocytes.* Circ Arrhythm Electrophysiol, 2013. **6**(1): p. 191-201. https://doi.org/10.1161/CIRCEP.111.973420

16. Veerman, C.C., et al., *Immaturity of human stem-cell-derived cardiomyocytes in culture: fatal flaw or soluble problem?* Stem Cells Dev, 2015. **24**(9): p. 1035-52. https://doi.org/10.1089/scd.2014.0533

17. Tu, C., B.S. Chao, and J.C. Wu, *Strategies for Improving the Maturity of Human Induced Pluripotent Stem Cell-Derived Cardiomyocytes.* Circ Res, 2018. **123**(5): p. 512-514. https://doi.org/10.1161/CIRCRESAHA.118.313472

18. Blinova, K., et al., *International multisite study of human-induced pluripotent stem cell-derived cardiomyocytes for drug proarrhythmic potential assessment.* Cell reports, 2018. **24**(13): p. 3582-3592. https://doi.org/10.1016/j.celrep.2018.08.079

19. Sala, L., M. Bellin, and C.L. Mummery, *Integrating cardiomyocytes from human pluripotent stem cells in safety pharmacology: has the time come?* British journal of pharmacology, 2017. **174**(21): p. 3749-3765. https://doi.org/10.1111/bph.13577

20. Gong, J.Q. and E.A. Sobie, *Population-based mechanistic modeling allows for quantitative predictions of drug responses across cell types.* NPJ systems biology and applications, 2018. **4**(1): p. 1-11. https://doi.org/10.1038/s41540-018-0047-2

21.   de Korte, T., et al., *Unlocking personalized biomedicine and drug discovery with human
induced pluripotent stem cell–derived Cardiomyocytes: fit for purpose or forever elusive?*
Annual Review of Pharmacology and Toxicology, 2020. **60**: p. 529-551.
https://doi.org/10.1146/annurev-pharmtox-010919-023309
22.   Koivumäki, J.T., et al., *Structural immaturity of human iPSC-derived cardiomyocytes: in
silico investigation of effects on function and disease modeling.* Frontiers in physiology,
2018. **9**: p. 80. https://doi.org/10.3389/fphys.2018.00080
23.   Alhusseini, M.I., et al., *Machine Learning to Classify Intracardiac Electrical Patterns
During Atrial Fibrillation: Machine Learning of Atrial Fibrillation.* Circulation:
Arrhythmia and Electrophysiology, 2020. **13**(8): p. e008160.
https://doi.org/10.1161/CIRCEP.119.008160
24.   Rogers, A.J., et al., *Machine Learned Cellular Phenotypes Predict Outcome in Ischemic
Cardiomyopathy.* Circulation Research, 2020.
https://doi.org/10.1161/CIRCRESAHA.120.317345
25.   Sevakula, R.K., et al., *State-of-the-Art machine learning techniques aiming to improve
patient outcomes pertaining to the cardiovascular system.* Journal of the American Heart
Association, 2020. **9**(4): p. e013924. https://doi.org/10.1161/JAHA.119.013924
26.   Jin, Z., et al. *HeartToGo: a personalized medicine technology for cardiovascular disease
prevention and detection.* in *2009 IEEE/NIH Life Science Systems and Applications
Workshop.* 2009. IEEE. https://doi.org/10.1109/LISSA.2009.4906714
27.   Trayanova, N.A., D.M. Popescu, and J.K. Shade, *Machine Learning in Arrhythmia and
Electrophysiology.* Circulation Research, 2021. **128**(4): p. 544-566.
https://doi.org/10.1161/CIRCRESAHA.120.317872
28.   Hochreiter, S. and J. Schmidhuber, *Long short-term memory.* Neural computation, 1997.
9(8): p. 1735-1780. https://doi.org/10.1162/neco.1997.9.8.1735
29.   Guo, A., et al., *Predicting cardiovascular health trajectories in time-series electronic
health records with LSTM models.* BMC Medical Informatics and Decision Making,
2021. **21**(1): p. 1-10. https://doi.org/10.1186/s12911-020-01345-1
30.   Shi, K., et al., *Contactless analysis of heart rate variability during cold pressor test using
radar interferometry and bidirectional LSTM networks.* Scientific reports, 2021. **11**(1): p.
1-13. https://doi.org/10.1038/s41598-021-81101-1
31.   Picon, A., et al., *Mixed convolutional and long short-term memory network for the
detection of lethal ventricular arrhythmia.* PLoS one, 2019. **14**(5): p. e0216756.
https://doi.org/10.1371/journal.pone.0216756
32.   Ballinger, B., et al. *DeepHeart: semi-supervised sequence learning for cardiovascular
risk prediction.* in *Thirty-Second AAAI Conference on Artificial Intelligence.* 2018.
33.   He, R., et al., *Automatic cardiac arrhythmia classification using combination of deep
residual network and bidirectional LSTM.* IEEE Access, 2019. **7**: p. 102119-102135.
https://doi.org/10.1109/ACCESS.2019.2931500
34.   Hou, B., et al., *LSTM Based Auto-Encoder Model for ECG Arrhythmias Classification.*
IEEE Transactions on Instrumentation and Measurement, 2019.
https://doi.org/10.1109/TIM.2019.2910342
35.   Warrick, P. and M.N. Homsi. *Cardiac arrhythmia detection from ECG combining
convolutional and long short-term memory networks.* in *2017 Computing in Cardiology
(CinC).* 2017. IEEE. https://doi.org/10.22489/CinC.2017.161-460

36.   Oh, S.L., et al., *Automated diagnosis of arrhythmia using combination of CNN and LSTM*
techniques with variable length heart beats. Computers in biology and medicine, 2018.
102: p. 278-287. https://doi.org/10.1016/j.compbiomed.2018.06.002
37.   Chen, C., et al., *Automated arrhythmia classification based on a combination network of*
CNN and LSTM. Biomedical Signal Processing and Control, 2020. **57**: p. 101819.
https://doi.org/10.1016/j.bspc.2019.101819
38.   Wang, L. and X. Zhou, *Detection of congestive heart failure based on LSTM-based deep*
network via short-term RR intervals. Sensors, 2019. **19**(7): p. 1502.
https://doi.org/10.3390/s19071502
39.   Bian, M., et al. *An accurate lstm based video heart rate estimation method.* in *Chinese*
Conference on Pattern Recognition and Computer Vision (PRCV). 2019. Springer.
https://doi.org/10.1007/978-3-030-31726-3_35
40.   Maragatham, G. and S. Devi, *LSTM model for prediction of heart failure in big data.*
Journal of medical systems, 2019. **43**(5): p. 1-13. https://doi.org/10.1007/s10916-019-
1243-3
41.   Yildirim, O., et al., *A new approach for arrhythmia classification using deep coded*
features and LSTM networks. Computer methods and programs in biomedicine, 2019.
176: p. 121-133. https://doi.org/10.1016/j.cmpb.2019.05.004
42.   Wang, E.K., X. Zhang, and L. Pan, *Automatic classification of CAD ECG signals with*
SDAE and bidirectional long short-term network. IEEE Access, 2019. **7**: p. 182873-
182880. https://doi.org/10.1109/ACCESS.2019.2936525
43.   Martis, R.J., et al., *Application of higher order cumulant features for cardiac health*
diagnosis using ECG signals. International journal of neural systems, 2013. **23**(04): p.
1350014. https://doi.org/10.1142/S0129065713500147
44.   Liu, F., et al. *A LSTM and CNN based assemble neural network framework for*
arrhythmias classification. in *ICASSP 2019-2019 IEEE International Conference on*
Acoustics, Speech and Signal Processing (ICASSP). 2019. IEEE.
https://doi.org/10.1109/ICASSP.2019.8682299
45.   Yildirim, Ö., *A novel wavelet sequence based on deep bidirectional LSTM network model*
for ECG signal classification. Computers in biology and medicine, 2018. **96**: p. 189-202.
https://doi.org/10.1016/j.compbiomed.2018.03.016
46.   Yang, P.-C., et al., *A computational pipeline to predict cardiotoxicity: From the atom to*
the rhythm. Circulation research, 2020. **126**(8): p. 947-964.
https://doi.org/10.1161/CIRCRESAHA.119.316404
47.   Cai, C., et al., *Deep learning-based prediction of drug-induced cardiotoxicity.* Journal of
chemical information and modeling, 2019. **59**(3): p. 1073-1084.
https://doi.org/10.1021/acs.jcim.8b00769
48.   Zhang, Y., et al., *Prediction of hERG K+ channel blockage using deep neural networks.*
Chemical Biology & Drug Design, 2019. **94**(5): p. 1973-1985.
https://doi.org/10.1111/cbdd.13600
49.   Dickson, C.J., C. Velez-Vega, and J.S. Duca, *Revealing molecular determinants of hERG*
blocker and activator binding. Journal of chemical information and modeling, 2019.
60(1): p. 192-203. https://doi.org/10.1021/acs.jcim.9b00773
50.   Ryu, J.Y., et al., *DeepHIT: a deep learning framework for prediction of hERG-induced*
cardiotoxicity. Bioinformatics, 2020. **36**(10): p. 3049-3055.
https://doi.org/10.1093/bioinformatics/btaa075

51.   Li, Z., et al., *General principles for the validation of proarrhythmia risk prediction*
models: an extension of the CiPA in silico strategy. Clinical Pharmacology &
Therapeutics, 2020. **107**(1): p. 102-111. https://doi.org/10.1002/cpt.1647
52.   Kernik, D.C., et al., *A computational model of induced pluripotent stem-cell derived*
cardiomyocytes incorporating experimental variability from multiple data sources. The
Journal of physiology, 2019. https://doi.org/10.1113/JP277724
53.   O'Hara, T., et al., *Simulation of the undiseased human cardiac ventricular action*
potential: model formulation and experimental validation. PLoS computational biology,
2011. **7**(5): p. e1002061. https://doi.org/10.1371/journal.pcbi.1002061
54.   Goodfellow, I., Y. Bengio, and A. Courville, *Deep learning.* 2016: MIT press.
https://doi.org/10.4258/hir.2016.22.4.351
55.   Tanskanen, A.J. and L.H. Alvarez, *Voltage noise influences action potential duration in*
cardiac myocytes. Mathematical biosciences, 2007. **208**(1): p. 125-146.
https://doi.org/10.1016/j.mbs.2006.09.023
56.   Gustafsson, F., *Determining the initial states in forward-backward filtering.* IEEE
Transactions on signal processing, 1996. **44**(4): p. 988-992.
https://doi.org/10.1109/78.492552
57.   Devore, J.L., *Probability and Statistics for Engineering and the Sciences.* 2011: Cengage
learning.
58.   Fawcett, T., *An introduction to ROC analysis.* Pattern recognition letters, 2006. **27**(8): p.
861-874. https://doi.org/10.1016/j.patrec.2005.10.010
59.   Powers, D.M., *Evaluation: from precision, recall and F-measure to ROC, informedness,*
markedness and correlation. 2011.
60.   LeCun, Y., J. Denker, and S. Solla, *Optimal brain damage.* Advances in neural
information processing systems, 1989. **2**: p. 598-605.
61.   Reale, R.A., J.F. Brugge, and J.C. Chan, *Maps of auditory cortex in cats reared after*
unilateral cochlear ablation in the neonatal period. Developmental Brain Research,
1987. **34**(2): p. 281-290. https://doi.org/10.1016/0165-3806(87)90215-X
62.   Yang, P.C., et al., *A computational modelling approach combined with cellular*
electrophysiology data provides insights into the therapeutic benefit of targeting the late
Na+ current. The Journal of physiology, 2015. **593**(6): p. 1429-1442.
https://doi.org/10.1113/jphysiol.2014.279554
63.   Fabbri, A., et al., *Required GK1 to suppress automaticity of iPSC-CMs depends strongly*
on IK1 model structure. Biophysical Journal, 2019. **117**(12): p. 2303-2315.
https://doi.org/10.1016/j.bpj.2019.08.040
64.   Casini, S., A.O. Verkerk, and C.A. Remme, *Human iPSC-derived cardiomyocytes for*
investigation of disease mechanisms and therapeutic strategies in inherited arrhythmia
syndromes: strengths and limitations. Cardiovascular drugs and therapy, 2017. **31**(3): p.
325-344. https://doi.org/10.1007/s10557-017-6735-0
65.   Goversen, B., et al., *The immature electrophysiological phenotype of iPSC-CMs still*
hampers in vitro drug screening: Special focus on IK1. Pharmacology & therapeutics,
2018. **183**: p. 127-136. https://doi.org/10.1016/j.pharmthera.2017.10.001
66.   Knollmann, B.C., *Induced pluripotent stem cell–derived cardiomyocytes: Boutique*
science or valuable arrhythmia model? Circulation research, 2013. **112**(6): p. 969-976.
https://doi.org/10.1161/CIRCRESAHA.112.300567

67.   Sinnecker, D., et al., *Induced pluripotent stem cell-derived cardiomyocytes: a versatile*
842   *tool for arrhythmia research.* Circulation Research, 2013. **112**(6): p. 961-968.
843   https://doi.org/10.1161/CIRCRESAHA.112.268623

844   68.   Blinova, K., et al., *Comprehensive translational assessment of human-induced*
845   *pluripotent stem cell derived cardiomyocytes for evaluating drug-induced arrhythmias.*
846   Toxicological Sciences, 2017. **155**(1): p. 234-247. https://doi.org/10.1093/toxsci/kfw200

847   69.   Kernik, D.C., et al., *A computational model of induced pluripotent stem-cell derived*
848   *cardiomyocytes for high throughput risk stratification of KCNQ1 genetic variants.* PLOS
849   Computational Biology, 2020. **16**(8): p. e1008109.
850   https://doi.org/10.1371/journal.pcbi.1008109

851   70.   Yoshinaga, D., et al., *Phenotype-based high-throughput classification of long QT*
852   *syndrome subtypes using human induced pluripotent stem cells.* Stem cell reports, 2019.
853   **13**(2): p. 394-404. https://doi.org/10.1016/j.stemcr.2019.06.007

854   71.   Atkinson, K.E., *An introduction to numerical analysis*. 2008: John wiley & sons.

855   72.   Yang, P.C., et al., *A Computational Pipeline to Predict Cardiotoxicity: From the Atom to*
856   *the Rhythm.* Circ Res, 2020. **126**(8): p. 947-964.
857   https://doi.org/10.1161/CIRCRESAHA.119.316404

858   73.   Li, M., et al., *Overexpression of KCNJ2 in induced pluripotent stem cell-derived*
859   *cardiomyocytes for the assessment of QT-prolonging drugs.* Journal of Pharmacological
860   Sciences, 2017. **134**(2): p. 75-85. https://doi.org/10.1016/j.jphs.2017.05.004

861   74.   Cheng, J., L. Dong, and M. Lapata, *Long short-term memory-networks for machine*
862   *reading.* arXiv preprint arXiv:1601.06733, 2016.

863   75.   Olah, C., *Understanding LSTM Networks. Aug. 2015.* URL https://colah. github.
864   io/posts/2015-08-Understanding-LSTMs, 2017.

865   76.   Krogh, A., *What are artificial neural networks?* Nature biotechnology, 2008. **26**(2): p.
866   195-197. https://doi.org/10.1038/nbt1386

867   77.   Carugo, O., F. Eisenhaber, and Carugo, *Data mining techniques for the life sciences*. Vol.
868   609. 2010: Springer. https://doi.org/10.1007/978-1-4939-3572-7

869   78.   Murphy, K.P., *Machine learning: a probabilistic perspective*. 2012: MIT press.

870   79.   Kingma, D.P. and J. Ba, *Adam: A method for stochastic optimization.* arXiv preprint
871   arXiv:1412.6980, 2014.

872   80.   Glorot, X., A. Bordes, and Y. Bengio. *Deep sparse rectifier neural networks*. in
873   *Proceedings of the fourteenth international conference on artificial intelligence and*
874   *statistics*. 2011. JMLR Workshop and Conference Proceedings.

875   81.   Zaremba, W., I. Sutskever, and O. Vinyals, *Recurrent neural network regularization.*
876   arXiv preprint arXiv:1409.2329, 2014.

877   82.   Ketkar, N., *Introduction to pytorch*, in *Deep learning with python*. 2017, Springer. p.
878   195-208. https://doi.org/10.1007/978-1-4842-2766-4_12