AutoCoEv – a high-throughput *in silico* pipeline for predicting novel protein-protein interactions

Petar B. Petrov[1,2]*, Luqman O. Awoniyi[1,2], Vid Šuštar[1], Martti Tolvanen[3], and Pieta K. Mattila[1,2]*
[1]Institute of Biomedicine and MediCity Research Laboratories, University of Turku, Turku, Finland
[2]Turku Bioscience, University of Turku and Åbo Akademi University, Turku, Finland
[3]Department of Future Technologies, University of Turku, Turku, Finland
*Correspondence should be addressed to: PP (petar.petrov@utu.fi) or PM (pieta.mattila@utu.fi)

Keywords: coevolution, correlation, protein, interaction, automation

Protein-protein interactions govern the cellular decision-making and various functions. Thus, identifying new interactions between proteins can significantly facilitate our understanding on the mechanistic principles of protein functions. Coevolution between proteins is a sign of functional communication and as such provides a powerful approach to search for novel molecular partners. However, evolutionary analyses of large arrays of proteins, in silico, is a highly time-consuming effort, which has prevented the usage of this method beyond protein pairs or narrow protein families, for example. Here, we developed AutoCoEv, a user-friendly computational pipeline for the search of coevolution between hundreds and even thousands of proteins. Driving over 10 individual programs, with CAPS2 as a key software for coevolution detection, AutoCoEv achieves seamless automation and parallelization of the workflow. In addition, we provide a patch to CAPS2 source code to improve its statistical output, allowing for multiple comparisons correction. We apply the method to inspect coevolution among 346 individual proteins identified to be in close proximity to the B cell receptor (BCR) before and after receptor activation. We successfully detected coevolutionary relations between the proteins, predicting novel partners and clusters of interacting molecules. We conclude that AutoCoEv can be used to predict protein interaction from large datasets of hundreds, and with aid of super-computing recourses even thousands of proteins in a time and cost-efficient manner.

Introduction

The biological function of proteins is carried out through associations with various molecules, the majority of which being, in fact, other proteins. The specific interplay between their amino acids, reflects the underlying molecular mechanisms of protein association, activity and regulation. Investigating interactions not only elucidates the functional role of proteins, but can reveal the existence of yet unknown protein partners. Screening for novel interactions is of high importance for deciphering the complexity of protein networks, determinant for the functional organization of cells. It has been suggested that relations between proteins can be extrapolated from the evolutionary history of their genes, in silico [1,2]. Such computational approaches, however, would demand a high degree of automation when used with large datasets, an issue that we successfully addressed in this work.

Evolution of proteins is influenced by structural and functional constraints between amino acids, enforcing their changes in a concerted manner. Detecting intra- or inter- molecular coevolution is regarded as a sign for correlation between residues within the same protein, or between sites belonging to different partners, respectively [3]. Various computational methods for prediction have been described, among which are BIS2 [4], ContactMap [5], DCA [6], Evcouplings [7], MISTIC [8] and CAPS2 [9]. Many searches for inter-protein coevolution have been confined to a relatively small number of partners, where an existing correlation has been essentially anticipated [10–14]. With no automation, extending the work to even tens of proteins presents a challenge, and becomes virtually impossible for larger numbers of proteins.

Here, we developed an automated and user-friendly computational pipeline, called AutoCoEv, for the large-scale screening for protein interactions. In the center of the workflow is CAPS2 (Coevolution Analysis using Protein Sequences 2) software, that compares the evolutionary rates at two sites in the form of their correlated variance [9]. By driving over 10 additional programs, AutoCoEv achieves high level of automation, flexibility and processes parallelization, enabling the analysis of hundreds and even thousands or proteins.

Implementation

The preparation pipeline for most coevolutionary analyses has a relatively simple concept. Typically, for each protein of interest, a multiple sequence alignment (MSA) of its orthologues needs to be produced, optionally combined with a phylogenetic tree. The process requires the correct identification of orthologues, retrieval of the sequences, filtering, and various format conversions.

Command line interface, configuration and input

AutoCoEv is written in BASH, and offers a simple menu-driven command line interface (CLI), where the individual steps are enumerated (Figure 1). Options for the programs that AutoCoEv drives, as well as different filtering are configured in a single file, which is well commented and described in details in the manual distributed with the script. Once configuration options have been set, a user can simply go through the consecutive steps and conduct the analysis automatically.

A

B

Figure 1. AutoCoEv offers a simple and intuitive menu. By carrying out sequentially the steps, the user can complete the whole pipeline. **(A)** Preparation menu. Steps 1-3 retrieve the needed databases from OrthoDB. Steps 4-7 check the md5sum of the databases and extract the archives. Steps 8-10 index and "trim" databases to speed up searches. Once these have been set, step 11 brings the Main menu; **(B)** Main menu.. Steps 1-3 deal with homologous sequences retrieval; steps 4-6 carry the identification of correct orthologues; steps 7-9 create the MSA and phylogenetic trees; steps 10 and 11 run parallelized CAPS for each unique protein pair combination; steps 12-13 process the results and generate XML; step 15 exits the script.

As an input, the script requires a list of proteins with their UniProt identifiers [15] and a list of species with taxonomic codes. Optionally, a phylogenetic tree may be provided from an external source, such as TimeTree [16], to be used as a guide (see later). Upon start, AutoCoEv offers to download its required databases from OrthoDB [17] and run initial preparations, such as FASTA database indexing (Figure 1A). Once databases are in place and input files are loaded, the pipeline proceeds to the main menu (Figure 1B).

Identification of orthologues
For each protein of interest, AutoCoEv consults OrthoDB searching for orthologues in the species from the user-provided list. The script matches the UniProt ID of each protein to its OrthoDB ID, then extracts its unique orthologues group (OG) ID at a certain level of organisms (e.g. Eukaryota, Metazoa, Vertebrata, Tetrapoda, Mammalia). This level, or node, is specified by the user and would depend on the species for which orthologues are searched (next step). The script will report proteins with missing or duplicated entries at OrthoDB, as well as species where orthologues of a protein are not found. The script will also report proteins with the same OG ID at the specified level, that are a result of gene duplication (see Manual for details).

Once these searches are done, AutoCoEv prepares a list of homologues for each protein, found in the species of interest (Figure 2 A). Due to alternative splicing or gene duplication, there may be several homologues identifiers per species for the same protein. Therefore, the script determines the correct orthologue by a reciprocal BLAST [18] run as follows. The amino acid sequence (from the reference organism, e.g. mouse) of each protein is downloaded from UniProt and prepared as a local BLAST database. Homologous sequences from each species are then retrieved and blasted against the UniProt sequence from the reference organism (e.g. mouse). For each species, the hit with best score is considered as the closest to the correct orthologues.

Their sequences are collected, with the option to omit the ones that do not pass a certain identity and coverage (gaps) threshold, specified by the user. Now, each protein has a collection of automatically curated orthologous sequences, ready for alignment in the next step.

Multiple sequence alignment and quality filtering
AutoCoEv offers a choice of three widely-used and accurate programs for the creation of multiple sequence alignments (MSA): MAFFT [19], MUSCLE [20] and PRANK [21] (Figure 2B). Different MAFFT aliases are supported, while for PRANK an external phylogenetic tree (e.g. obtained from TimeTree) can be specified as a guide. The script then runs Gblocks [22] on the generated MSA, to filter out regions that are poorly aligned, too divergent or otherwise unreliable. Eliminating columns of low quality aims to improve the accuracy of results, while the shorter MSA may significantly speed up the consequent analyses. Using the Gblocks-filtered MSA for the subsequent steps is optional and left to the user to decide.

Phylogenetic trees
CAPS2 will generate trees automatically at runtime from the MSAs of the analysis, if no trees were specified. We have patched the program, so the generated trees are exported in the output (see Materials and Methods, "Patch for verbose CAPS output"), enabling inspection and assessment.

Trees can also be calculated by another program (Figure 2B), an approach that may be desirable in order to improve the sensitivity of the analysis. For the purpose, AutoCoEv drives PhyML (Phylogenetic estimation using Maximum Likelihood) [23] to calculate trees from each MSA (using either the full-length alignments or the ones processed by Gblocks). An external tree (e.g. obtained from TimeTree) can be specified as a guide, and users are provided with the option to automatically root the produced trees. In our experience, CAPS2 runs are more stable when rooted trees are used. Conversion between sequence formats is done by Squizz, while trees processing, such as trimming of branches, as well as, rooting are done by TreeBeST [24].

Detection of inter-protein coevolution by CAPS
Before the actual CAPS2 run, AutoCoEv takes several preparation steps of the orthologues MSA and (optionally) trees, created for each protein. The script determines all unique pairwise combinations between the proteins, creating an individual folder dedicated to each pair. As an example, 10 proteins will produce 45 combinations, while the 346 proteins of our dataset yield 59,685 pairs. For each combination, before being placed in the respective folder, the MSA (and trees) of the two proteins are compared to determine the species they have in common (Figure 2C). The sequences of the "not shared" species are removed from the MSA by SeqKit [25] and the trees (if used) are trimmed by TreeBeST, accordingly. In our experience, the presence of too many species not shared by the two proteins deteriorates the stability of CAPS2. The number of species affects the specificity of the coevolution detection [9], therefore users can specify a minimum threshold "shared species" for a protein pair. When all is set, AutoCoEv runs CAPS2 via GNU/Parallel (see next), spawning multiple individual instance of the program, each operating in a separate protein pair folder (Figure 2D).

Figure 2. AutoCoEv seamlessly connects the numerous steps of the pipeline. (A) Orthologues identification. Reading the user-provided lists of proteins of interest and species to be searched, the script communicates between databases to extract genes (ODB ID) and orthologous groups (OG ID) identifiers. Homologous sequences are then blasted against the UniProt sequences from the reference organism (e.g. mouse) in order to prepare a FASTA list of correct orthologues; **(B)** Alignments and phylogenetic trees. Orthologues are then aligned by selected method (mafft, muscle or prank) and optionally processed by Gblocks, excluding regions of low quality. PhyML calculates trees from the MSA generated in the previous step, optionally using the external tree as a guide; **(C)** Create all unique protein pairs. In preparation for the CAPS2 run, the script calls SeqKit and TreeBeST to ensure that only species that both paired proteins have in common are present in their MSA and trees. Since number of species affects the specificity of CAPS, the user can specify a threshold of the minimum permitted number of common species (e.g. 20). Each pair folder has two subfolders: for MSA and trees. **(D)** Running CAPS for each protein pair. The script executes CAPS in each protein pair folder in a parallelized fashion via GNU/Parallel. **(E)** Results processing. The output in each pairs folder is inspected and processed, followed by Bonferroni correction of p-values. Finally, the results are prepared as a table, exported as an interactive web-page by R Shiny, or parsed into an XML file ready for the network analysis by Cytoskape.

Parallelization

The computational time required for the analysis presents a major bottleneck, as many programs lack CPU multi-threading. Utilization of multiple processor cores is a necessity at several steps through this workflow, the most critical one being CAPS2 run itself. For CAPS2, and other software, we overcome these shortcomings by executing the program via GNU/Parallel [26]. We achieve the simultaneous run of multiple, single-core jobs, dramatically speeding up the time of computation.

Results processing and assessment

After CAPS runs are complete in all protein pair folders, AutoCoEv processes the results in several steps of filtering, sorting and assessment (for details see Manual). Before running CAPS2, users can specify an alpha-value threshold for the results, however, the program does not output the actual p-values for the detected correlation. Instead, CAPS2 calculates a correlation threshold, specific for each individual protein pair, based on a number of simulated sequences, that serve as null data. Due to the protein pair-specific thresholds, we would not directly compare the correlation values from one protein pair to those from another. For a large-scale analysis, as the one presented here, ranking the results and performing multiple testing corrections are desired. Therefore, we prepared a patch for CAPS source code (see Materials and Methods, "Patch for verbose CAPS output"), which makes the program report the p-value of each correlation (closest upper-bound p-value, see Supplementary Materials).

The script calls R [27] to produce Bonferroni-corrected p-values of the co-evolving residues from each protein pair (Figure 2E). Co-evolving residues with significant corrected p-values are further inspected in regards of their MSA columns and those with alignment gaps above a certain threshold (e.g. more than 20% gaps) are omitted. In the final step, the script writes a XML (Extensible Markup Language) file of the resulting network, ready for visualization and additional analyses by Cytoskape [28].

Application

We tested AutoCoEv on a set of 346 mouse proteins identified by APEX2 proximity biotinylation proteomics to be located at the lipid raft membrane domains in B cells [29] (bioRxiv). A list of 37 tetrapod species was prepared and an external phylogenetic tree was obtained from TimeTree knowledge-base. For each protein, orthologues sequences with homology greater than 35% to mouse, having less than 25% gaps in the BLAST alignment were considered. MSA were created by MAFFT with alias "mafft-linsi" and processed by Gblocks to eliminate low quality regions. Trees were then calculated by PhyML from the filtered MSA, using the TimeTree tree as a guide and produced trees were rooted by TreeBeST. Before running CAPS2, a total of 59,685 unique pairs were produced, with minimum overlapping species set to 20. AutoCoEv successfully completed the CAPS2 jobs in the individual protein pairs folders. After the run was complete, the script processed the results, excluding results with Bonferroni corrected p-values > 0.05 and MSA columns with more than 20% gaps.

Using Cytoskape, we limited the results to those with Bonferroni-corrected p-values < 0.005, and bootstrap > 0.9, producing a complicated network with numerous connections

between nodes, having several distinct proteins as interactions "hubs" (Supplementary Figure S1). Detailed network analysis can be performed following several strategies. A simple filtering method would be selecting a more stringent p-values and bootstrap cutoffs, resulting in a network of higher confidence (Figure 3A). Nodes can be scored by their multiple edges partners (proteins with more than one coevolving amino acid pairs), yielding a network of proteins with highest number of coevolving residues (Figure 3B). Our reasoning behind this is that two interacting proteins are likely to have more than a single co-evolving amino acid pair. Applying a combination of those, with even more stringent cutoff yields a concise list of proteins (Figure 3C), that are suitable targets for future investigation (Table 1).

Protein 1	Protein 1 ID	Protein 2	Protein 2 ID
Capzb	P47757	Actg1	P63260
Prdx4	O08807	Actg1	P63260
Msn	P26041	Actr2	P61161
Cdv3	Q4VAA2	Cltc	Q68FD5
Psmc5	P62196	Cltc	Q68FD5
Vcp	Q01853	Cltc	Q68FD5
Cltc	Q68FD5	Gnai3	Q9DC51
Psmc5	P62196	Gnai3	Q9DC51
Rps6	P62754	Gnai3	Q9DC51
Actr2	P61161	Gphn	Q8BUV3
Psmc5	P62196	Gphn	Q8BUV3
Actr2	P61161	Psmc6	P62334
Prdx4	O08807	Psmc6	P62334
Psmc5	P62196	Psmc6	P62334
Cd72	P21855	Rhoa	Q9QUI0
Ywhab	Q9CQV8	Rhoa	Q9QUI0
Rps6	P62754	Rps27	Q6ZWU9
Capzb	P47757	Rps27l	Q6ZWY3
Actg1	P63260	Smc3	Q9CW03
Gphn	Q8BUV3	Smc3	Q9CW03
Actg1	P63260	Vcp	Q01853
Cd72	P21855	Vcp	Q01853
Psmc5	P62196	Vcp	Q01853

Table 1. Protein pairs, candidates for further investigation

Discussion

In this paper, we present AutoCoEv: an interactive script, aimed at the large-scale prediction of inter-protein coevolution. The variety of options that can be easily set in the configuration file, allow for numerous adjustments, providing a great level of flexibility in the workflow.

The automated batch identification of orthologues, grants the seamless processing of even thousands of proteins, when high computing power is available. The choice of MSA software largely depends on the sequences being aligned, therefore our script drives three of the most widely used MSA programs [30], and we do not exclude incorporation of additional methods. At the moment, AutoCoEv drives PhyML, offering a reliable means for trees calculation, and we are planning to implement wrappers for at least RAxML [31] and MrBayes [32].

By default, inter-molecular analysis in CAPS2 was designed for just a handful of proteins, or only a pair, as illustrated by the web interface (http://caps.tcd.ie/caps/). Lack of multi-threading is a major obstacle in the analysis of large

Figure 3. Filtering strategies. (A) Stringent filter. Edges were filtered by corrected p-value < 0.001 and bootstrap > 0.95. **(B)** Partners. Node were filtered by number of multi-edges partners (>10), p-value < 0.001 and bootstrap > 0.95. **(C)** Combined. Nodes were filtered by by number of multi-edges partners (>10), p-value < 0.001 and bootstrap > 0.99.

datasets and here we have successfully overcome this issue. By creating in advance all possible pairwise combinations, then running multiple instances of the program simultaneously, we take full advantage of modern multi-core processor architecture. With the increasing numbers of processor cores in the recent years, it is possible to analyse hundreds of proteins even on a common modern PC. For example, the CAPS processing of our 346 proteins dataset took around two days on a workstation with an Intel Xeon W-2135 (6 cores and 12 threads). For protein numbers reaching thousand or more, access to super-computing resources is required to keep the analysis run times low.

Since correlation values derived by CAPS cannot be directly compared between the protein pairs, we opted to extract the actual p-value for each correlation. Comparable p-values allow the usage of additional statistical tests, and we believe the statistical power of the analyses got improved by this addition.

Materials and methods

The script is under open liencese and is freely available for download from the GitHub repository of our group together with the data used

in this work (https://github.com/mattilalab/autocoev). For details, please see Manual on GitHub.

Script environment and required software

AutoCoEv is written in BASH and its development was done on a Slackware (http://www.slackware.com/) GNU/ Linux
system. Software tools and their dependencies, not included in the base system, were installed from the scripts available at SlackBuilds.org (https://slackbuilds.org/). These are: BLAST+ (2.10.1), CAPS (2.0), Datamash (1.7), Exonerate (2.4.0), Gblocks (0.91b), MAFFT (7.471), MUSCLE (3.8.1551), PRANK (170427), Parallel (20200522), PhyML (3.3.20200621), R (4.0), SeqKit (0.13.2), squizz (0.99d) and TreeBeST with Ensembl modifications (1.9.2_git347fa82). Compiling CAPS requires Bio++ release 1.9 libraries (http://biopp.univ-montp2.fr/): bpp-utils (1.5.0), bpp-seq (1.7.0), bpp-numcalc (1.8.0) and bpp-phyl (1.9.0, patched).

A virtual machine image with all requirements pre-installed is also available upon request. See Supplementary Materials for details and dependencies.

Databases

When searching for orthologues, AutoCoEv takes advantage of the data from OrthoDB (https://www.orthodb.org/). The following databases are used (10.1): odb10v1_all_fasta.tab.gz, odb10v1_gene_xrefs.tab.gz, odb10v1_OG2genes.tab.gz. The script

also communicates with UniProt (https://www.uniprot.org/) to download the latest sequence of each protein of interest from its reference organism. In case an external (i.e. not calculated from MSA) phylogenetic tree was needed, the TimeTree knowledgebase was used (http://www.timetree.org/).

Patch for verbose CAPS output

Our patch introduces two modifications to CAPS, making the program produce more verbose output. First, the program will use TreeTemplateTools from bpp-phyl to export CAPS generated trees by treeToParenthesis, if none were supplied by the user at run-time. Second, after coevolution between sites has been determined, CAPS searches back within totaltemp vector of null simulated data, for the p-value corresponding closest to the estimated correlation value. See Supplementary Materials for detailed explanation with excerpts of code.

Proximity biotinylation

For details, see Awoniyi et al bioRxiv [29], a preceding study from our group, published in parallel with this work. Briefly, lysates of B cells stimulated with 10μg/mL antibody against BCR were collected after 0 min, 5 min, 10 min and 15 min time points. The APEX2 system was used to induce biotinylation of proteins within 20 nm range in close proximity to the BCR. Samples were subjected to streptavidin affinity purification followed by mass spectrometry analysis. MaxQuant (1.6.17.0) was used for database search and after differential enrichment analysis with NormalyzerDE (1.6.0), a list of 346 proteins identified with high confidence was prepared.

Acknowledgements

We thank the members of the Lymphocyte Cytoskeleton lab for their critical comments on our manuscript. This work was supported by the Academy of Finland (grant ID: 25700, 296684, 307313, and 327378 to PM; 286712 to VŠ), as well as Sigrid Juselius and Jane and Aatos Erkko foundations. The authors would like to thank Akseli Mantila for help with the C++ code of CAPS2.

Author contributions

PP developed the script and wrote the manuscript. LA provided the data for analyses, generated the network analysis of the results and developed a statistical evaluation of the results. VŠ conceived the original idea of the automated pipeline and contributed to trouble-shooting. MT contributed to trouble-shooting and brought expertise in the theoretical basis. PM contributed to the study design, trouble-shooting, and manuscript preparation.

Competing interest statement

The authors declare no competing interests.

References

1. Baussand J, Carbone A. A Combinatorial Approach to Detect Coevolved Amino Acid Networks in Protein Families of Variable Divergence. PLoS Comput Biol 2009; 5:
2. Kuriyan J. Allostery and coupled sequence variation in nuclear hormone receptors. Cell 2004; 116:354–356
3. Fares MA, McNally D. CAPS: coevolution analysis using protein sequences. Bioinformatics 2006; 22:2821–2822
4. Oteri F, Nadalin F, Champeimont R, et al. BIS2Analyzer: a server for co-evolution analysis of conserved protein families. Nucleic Acids Research 2017; 45:W307–W314
5. Wang S, Sun S, Li Z, et al. Accurate De Novo Prediction of Protein Contact Map by Ultra-Deep Learning Model. PLOS Computational Biology 2017; 13:e1005324
6. Morcos F, Pagnani A, Lunt B, et al. Direct-coupling analysis of residue coevolution captures native contacts across many protein families. Proc. Natl. Acad. Sci. U.S.A. 2011; 108:E1293-1301

7. Hopf TA, Green AG, Schubert B, et al. The EVcouplings Python framework for coevolutionary sequence analysis. Bioinformatics 2019; 35:1582–1584
8. Simonetti FL, Teppa E, Chernomoretz A, et al. MISTIC: Mutual information server to infer coevolution. Nucleic Acids Res. 2013; 41:W8-14
9. Fares MA, Travers SAA. A Novel Method for Detecting Intramolecular Coevolution: Adding a Further Dimension to Selective Constraints Analyses. Genetics 2006; 173:9–23
10. Travers SAA, Fares MA. Functional Coevolutionary Networks of the Hsp70–Hop–Hsp90 System Revealed through Computational Analyses. Molecular Biology and Evolution 2007; 24:1032–1044
11. Huang Y, Temperley ND, Ren L, et al. Molecular evolution of the vertebrate TLR1 gene family - a complex history of gene duplication, gene conversion, positive selection and co-evolution. BMC Evol Biol 2011; 11:149
12. Ruiz-González MX, Fares MA. Coevolution analyses illuminate the dependencies between amino acid sites in the chaperonin system GroES-L. BMC Evol Biol 2013; 13:156
13. Petrov P, Syrjänen R, Smith J, et al. Characterization of the Avian Trojan Gene Family Reveals Contrasting Evolutionary Constraints. PLoS ONE 2015; 10:e0121672
14. Champeimont R, Laine E, Hu S-W, et al. Coevolution analysis of Hepatitis C virus genome to identify the structural and functional dependency network of viral proteins. Sci Rep 2016; 6:26401
15. Consortium TU. UniProt: a worldwide hub of protein knowledge. Nucleic Acids Res 2019; 47:D506–D515
16. Kumar S, Stecher G, Suleski M, et al. TimeTree: A Resource for Timelines, Timetrees, and Divergence Times. Mol. Biol. Evol. 2017; 34:1812–1819
17. Kriventseva EV, Kuznetsov D, Tegenfeldt F, et al. OrthoDB v10: sampling the diversity of animal, plant, fungal, protist, bacterial and viral genomes for evolutionary and functional annotations of orthologs. Nucleic Acids Res 2019; 47:D807–D811
18. Camacho C, Coulouris G, Avagyan V, et al. BLAST+: architecture and applications. BMC Bioinformatics 2009; 10:421
19. Katoh K, Standley DM. MAFFT Multiple Sequence Alignment Software Version 7: Improvements in Performance and Usability. Mol Biol Evol 2013; 30:772–780
20. Edgar RC. MUSCLE: multiple sequence alignment with high accuracy and high throughput. Nucleic Acids Res. 2004; 32:1792–1797
21. Löytynoja A. Phylogeny-aware alignment with PRANK. Methods Mol. Biol. 2014; 1079:155–170
22. Castresana J. Selection of conserved blocks from multiple alignments for their use in phylogenetic analysis. Mol. Biol. Evol. 2000; 17:540–552
23. Guindon S, Dufayard J-F, Lefort V, et al. New Algorithms and Methods to Estimate Maximum-Likelihood Phylogenies: Assessing the Performance of PhyML 3.0. Syst Biol 2010; 59:307–321
24. Vilella AJ, Severin J, Ureta-Vidal A, et al. EnsemblCompara GeneTrees: Complete, duplication-aware phylogenetic trees in vertebrates. Genome Res 2009; 19:327–335
25. Shen W, Le S, Li Y, et al. SeqKit: A Cross-Platform and Ultrafast Toolkit for FASTA/Q File Manipulation. PLOS ONE 2016; 11:e0163962
26. Tange (2018) GNU Parallel March 2018, https://doi.org/10.5281/zenodo.1146014.
27. R Core Team (2013). R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL http://www.R-project.org/
28. Shannon P, Markiel A, Ozier O, et al. Cytoscape: A Software Environment for Integrated Models of Biomolecular Interaction Networks. Genome Res 2003; 13:2498–2504
29. Awoniyi LO, Šuštar V, Hernández-Pérez S, et al. APEX2 proximity biotinylation reveals protein dynamics triggered by B cell receptor activation. bioRxiv 2020; 2020.09.29.318766
30. Thompson JD, Linard B, Lecompte O, et al. A Comprehensive Benchmark Study of Multiple Sequence Alignment Methods: Current Challenges and Future Perspectives. PLOS ONE 2011; 6:e18093
31. Stamatakis A. RAxML version 8: a tool for phylogenetic analysis and post-analysis of large phylogenies. Bioinformatics 2014; 30:1312–1313
32. Ronquist F, Teslenko M, van der Mark P, et al. MrBayes 3.2: efficient Bayesian phylogenetic inference and model choice across a large model space. Syst. Biol. 2012; 61:539–542

Supplementary Materials

Manual

For details on AutoCoEv and instructions, please consult the Manual distributed with the script tarball. Also, check our GitHub page: https://github.com/mattilalab/autocoev for any updates.

Prerequisites

AutoCoEv was developed on Slackware 14.2 (http://www.slackware.com/) x86_64. Software, not included in the distribution, was installed from the scripts available at the SlackBuilds.org (SBo) project (https://slackbuilds.org/). The following programs should be installed, as well as their own dependencies, all available at SBo:

```
vCAPS       https://slackbuilds.org/repository/14.2/academic/vCAPS_coevolution/
PhyML       https://slackbuilds.org/repository/14.2/academic/PhyML/
Gblocks     https://slackbuilds.org/repository/14.2/academic/Gblocks/
MAFFT       https://slackbuilds.org/repository/14.2/academic/mafft/
MUSCLE      https://slackbuilds.org/repository/14.2/academic/muscle/
PRANK       https://slackbuilds.org/repository/14.2/academic/prank-msa/
BLAST+      https://slackbuilds.org/repository/14.2/academic/ncbi-blast+/
Datamash    https://slackbuilds.org/repository/14.2/academic/datamash/
SeqKit      https://slackbuilds.org/repository/14.2/academic/seqkit/
Squizz      https://slackbuilds.org/repository/14.2/academic/squizz/
TreeBeST    https://slackbuilds.org/repository/14.2/academic/treebest-ensembl/
Parallel    https://slackbuilds.org/repository/14.2/system/parallel/
R           https://slackbuilds.org/repository/14.2/system/R/
```

Detailed instructions on how to install software from SBo, can be found in website's the HOWTO section (https://slackbuilds.org/howto/). Send a request to pebope@utu.fi if you want a VM image with all dependencies preinstalled.

Compiling CAPS from source

CAPS requires Bio++ suite (release v1.9) libraries, compiled in this order: bpp-utils (1.5.0), bpp-numcalc (1.8.0), bpp-seq (1.7.0) and bpp-phyl (1.9.0). Sources can be obtained from the suite webpage (http://biopp.univ-montp2.fr/repos/sources/). TreeTemplateTools.h from bpp-phyl needs to be slightly modified, in order to work with CAPS, therefore a patch (caps_TreeTemplateTools.patch) is provided.

The libraries (and patch) are available at SBo, as part of the bpp1.9 "legacy" Bio++ suite, which can be safely installed along the new version of the suite:

```
bpp1.9-utils     https://slackbuilds.org/repository/14.2/academic/bpp1.9-utils/
bpp1.9-numcalc   https://slackbuilds.org/repository/14.2/academic/bpp1.9-numcalc/
bpp1.9-seq       https://slackbuilds.org/repository/14.2/academic/bpp1.9-seq/
bpp1.9-phyl      https://slackbuilds.org/repository/14.2/academic/bpp1.9-phyl/
```

Verbose CAPS (vCAPS)

A SlackBuild script for vCAPS is also available at SBo, which automatically applies the caps_verbose.patch (see next) and compiles the program with -O2 -fPIC flags. In our experience, setting flags to -O3 did not yield a significant speed improvement.

Hardware

Test runs of AutoCoEv were done on Intel Xeon W-2135 (6 cores / 12 threads) or i7-9700KF (8 cores / 8 threads) CPU with 32GB RAM.

Patch for verbose CAPS output

We provide a patch (caps_verbose.patch) to CAPS source code (caps.cpp), that makes the program output its generated trees, as well as the p-value for each correlated amino acid pair. For the moment, the patch introduces these changes only for inter-protein analyses.

Trees output

When phylogenetic trees are not supplied by the user, CAPS generates its own trees automatically:

```
tree1 = create_input_tree(vec1.names, vec1.sequences);
tree2 = create_input_tree(vec2.names, vec2.sequences);
```

Our patch simply outputs the trees by *treeToParenthesis*:

```
string temptre1 = TreeTemplateTools::treeToParenthesis(*tree1, true);
string temptre2 = TreeTemplateTools::treeToParenthesis(*tree2, true);
```

P-values output

CAPS simulates number (-r) of random MSA, where each simulated alignment has the same number of columns (length) as the real data and is tested by the same method. This ensures that the data are compared to a *null* distribution without coevolution pressures. Correlation information from the simulated data is stored and sorted into vector *totaltemp*:

The correlation *threshold* for each protein pair is based on the simulated data in *totaltemp*, found at a certain index, *value*. It is determined by the alpha (-a) run-time option, referred here as *threshval*:

```
[1] int value = floor(((totaltemp.size())*(1-(threshval))))+1;

threshold = totaltemp[value];
```

Correlation between residues R1 and R2 is determined as the mean of correlation R1→R2 and correlation R2→R1. Each must be higher than the *threshold*, whereas *thresholdR* is always 0.01:

```
if((fabs(Correl1[cor])>=threshold && fabs(Correl1[cor])>=thresholdR)
&& (fabs(Correl2[cor])>=threshold && fabs(Correl2[cor])>=thresholdR))
```

We seek to calculate the p-value of each correlation using the formula from **[1]**, where *value* is the correlation closest *index* within the *totaltemp* vector. We introduce a new function *getIndex*, which ranks a value *K* within a vector *v*, defines its lower bound value as *it*, then determines the *index* of *it* within the vector.

Here, *v* = *totaltemp* and *K* = Correl_[cor] and the p-value of Correl_[cor] is returned as *alphathresh*:

```
double getIndex(std::vector<double> const& v, double K) {
    auto const it = std::lower_bound(v.begin(), v.end(), fabs(K));
      if (it != v.end()) {
        int index = distance(v.begin(), it);
       alphathresh = (((int)1+(double)v.size()-(int)index)/(double)v.size());
       return alphathresh;
      }
      else {
        cerr << "ELEMENT NOT FOUND!" << endl;
      }
}
```

We use the *index* of lower bound *it*, since an exact match of the correlation value Correl_[cor] is unlikely to be found within *totaltemp*:

```
double Pvalue1 = getIndex(totaltemp, Correl1[cor]);
double Pvalue2 = getIndex(totaltemp, Correl2[cor]);
```

The patched executable of CAPS is installed as "**vCAPS**", so it can be installed along the the official binary "caps" provided by upstream.

Supplementary Figures

Figure S1. Coevolutionary network. A total of 346 proteins were screened for coevolution and a subnetwork of those correlations with corrected p-values < 0.005 and bootstrap > 0.9 was selected.