Topological Augmentation of Latent Information Streams in Feed-Forward Neural Networks

James M. Shine[1,2], Mike Li[1,2,6], Oluwasanmi Koyejo[3,4], Ben Fulcher[1,5] and Joseph T. Lizier[1,6]

Affiliations

Centre for Complex Systems, The University of Sydney, Sydney, NSW, Australia

Brain and Mind Centre, The University of Sydney, Sydney, NSW, Australia

Beckman Institute for Advanced Science and Technology, University of Illinois Champaign

Department of Computer Science, , University of Illinois at Urbana-Champaign

School of Physics, The University of Sydney, Sydney, NSW, Australia

Complex Systems Research Group, Faculty of Engineering, The University of Sydney, Sydney, NSW, Australia

Corresponding author:

* James M. Shine – mac.shine@sydney.edu.au

Abstract

The algorithmic rules that define deep neural networks are clearly defined, however the principles that define their performance remain poorly understood. Here, we use systems neuroscience and information theoretic approaches to analyse a feedforward neural network as it is trained to classify handwritten digits. By tracking the topology of the network as it learns, we identify three distinct phases of topological reconfiguration. Each phase brings the connections of the neural network into alignment with patterns of information contained in the input dataset, as well as the preceding layers. Performing dimensionality reduction on the data reveals a process of low-dimensional category separation as a function of learning. Our results enable a systems-level understanding of how deep neural networks function, and provide evidence of how neural networks reorganize edge weights and activity patterns so as to most effectively exploit the information theoretic content of input data during edge-weight training.

Summary

Trained neural networks are capable of remarkable performance on complex categorization tasks, however the precise rules according to which the network reconfigures during training remain poorly understood. We used a combination of systems neuroscience and information theoretic analyses to interrogate the network topology of a simple, feed-forward network as it was trained on a digit-classification task. Over the course of training, the hidden layers of the network reconfigured in characteristic ways that were reminiscent of key results in network neuroscience studies of human brain imaging. In addition, we observed a strong correspondence between the topological changes at different learning phases and information theoretic signatures of the data that were entered into the network. In this way, we show how neural networks learn.

Over the last few decades, neural networks[1] have been trained to outperform world experts at complex strategy games, such as Chess and Go[2]. One of the more remarkable aspects of this feat is that neural networks are comprised of relatively simple building blocks that facilitate the effective categorization of input data, applied at scale. Although the algorithms that are used to train neural network weights are well understood, the manner in which neural networks reconfigure in order to facilitate high levels of classification accuracy remain relatively opaque[1,3,4]. Based on their many-to-many connectivity, the functional capacities of neural networks are presumed to be distributed across the different nodes and connections that define their architecture. For this reason, the systems-level perspective is likely to improve our understanding of the principles through which the local rules that define neural networks emerge as coherent algorithmic processes[5–8].

Issues with defining the appropriate scale at which to analyse data have also occurred in the field of neuroscience[3]. In the human brain, capacities such as cognition, attention, and awareness emerge from the coordinated activity of billions of neurons. Although some of the implementation details differ[9], the two fields share some remarkable similarities. For example, the original neural-network algorithms were in part inspired by the anatomy of the cerebral cortex[1,4,9], and in the case of deep, layered neural networks, both systems share a common property of distributed computation facilitated by complex topological wiring between large numbers of (relatively) simple computational units. Despite ready access to high-quality neuroimaging datasets[10–12], it remains relatively challenging to infer precisely which aspects of neuroimaging data are integral for facilitating behaviour using traditional approaches[13], which are often based on relatively

localized interrogations of function that are difficult to extrapolate to the whole brain.

A potential solution to this challenge is to analyze neuroimaging data from a systems-level perspective[14–16]. By treating neuroimaging datasets as if the data arise from networks of interacting parts, systems neuroscientists are able to characterize high-dimensional datasets in intuitive ways that help to understand how brain networks process information[17,18]. Across multiple spatial[19] and temporal[20] scales, these approaches have revealed systems-level principles of brain function. A salient example is the measurement of network modularity, which quantifies the extent to which a network is comprised of a relatively weakly inter-connected set of tight-knit sub-modules. This organization has demonstrable computational advantages[21,22] and has been shown to map onto higher-level cognitive functions[23,24]. For instance, macroscopic brain networks constructed from multi-region interactions in neuroimaging data demonstrate substantial reconfiguration as a function of task performance: early in the course of learning, the brain is relatively inter-connected and integrated, but this pattern typically gives way to a more refined, segregated architecture as a simple motor skill becomes second-nature[16,25]. In this study, we asked whether similar network-based analyses could be used to better understand the mechanisms underlying the architectures of feed-forward neural networks.

Here, we applied systems neuroscience and information theoretic methods to analyze the structure of a feedforward neural network as it was trained (across 100,000 epochs with stochastic gradient descent) to rapidly classify a set of ten hand-written digits (Modified National Institute of Standards and Technology

[MNIST] dataset[26]). We analyzed the MNIST dataset due to its simplicity, as our purpose here was to use a systems-level approach to better understand the mechanisms through which artificial neural networks learn on an appropriately benchmarked dataset. Although a neural network with a single hidden layer is theoretically sufficient for high performance on MNIST[26], neural networks with more hidden layers provide benefits of both computational and parameter efficiency[27]. A feedforward network was constructed with two hidden layers – a 100-node hidden layer (HL1) that received the 28 x 28 input (pixel intensities from the MNIST dataset), and a 100-node hidden layer (HL2) that received input from HL1 – and a 10-node output layer (Figure 1A).

Figure 1. A feed-forward neural network exhibits three topologically distinct phases of reconfiguration throughout learning the MNIST dataset. A) A large (60,000 item) corpus of hand-drawn digits (28 x 28 pixel array with 256 intensity values per pixel) were vectorized and entered

into a generic feed-forward neural network with two hidden layers – a 100-node layer (HL1) that received the 28 x 28 input and a 100-node layer (HL2) that received the input from HL1 – and a 10-node output layer (argmax); B) the edges connecting the input → HL1 (dark blue; α), HL1 → HL2 (orange; β) and HL2 → output (dark green; γ) were embedded within an asymmetric weighted and signed connectivity matrix; C) the three subnetworks (α, β, γ) were associated with unique patterns of layer-specific modularity (Q): the α edges (dark blue) rose after an initial plateau (Early phase: light blue), before falling in later epochs (Middle phase: light green; and Late phase: purple); the β edges (orange) shows a more sustained elevation across learning; and the γ edges (dark green) settled into a relatively stable pattern after the initial learning phase; D) classification accuracy showed a non-linear relationship with Q (calculated across the whole network): there is an initial learning phase that was independent of network modularity (light blue), after which there is a positive linear relationship between accuracy and Q (Pearson's r = 0.981; light green), and finally a sustained drop in Q, as accuracy saturates in the later stages of learning (light purple).

Results

Inspired by results from systems neuroscience[16,25] and complex systems[6,8] literatures that link learning to network-level topology, we hypothesized that the network structure of the neural network should reconfigure so as to maximally extract the relevant information from the input dataset. To test this prediction, we created a weighted connectivity matrix (for all α, β and γ edge connections between all pairs of nodes) at each learning epoch (see Figure 1B). Given the widely varying number of nodes within each network layer, we first embedded the connections between each layer of the network in the upper triangle of a sparse network.

We tracked the modularity (Q) of the directed network over the course of training. Q quantifies the extent with which the network can be clustered into tight-knit communities with relatively sparse connections between them. We calculated Q twice: once for the whole connectivity matrix (which clustered nodes across layers

according to their edge-weight similarity), and again for each pair of connected layers ($\alpha, \beta \, \& \, \gamma$ subnetworks), with the lower triangle of the adjacency matrix network set to zero. Using this approach, both the α and γ edge sub-networks showed inverse-U shaped relationships with Q over time (Figure 1C), whereas the β sub-network showed a more consistent increase in Q as a function of training (Figure 1C). At the whole-network level, we observed a nonlinear relationship between network modularity, Q, and classification accuracy (Figure 1D).

From the shape of this curve, we identified three phases of topological adjustment through the training process (labelled as 'Early', 'Middle', and 'Late' in Figure 1D; retro-actively applied to Figure 1C). Early in the course of training, there was a substantial improvement in accuracy without a noticeable change in Q (light blue in Figure 1D). In the Middle phase, we observed an abrupt increase in Q (light green in Figure 1D) that tracked linearly with performance accuracy ($r = 0.981$, p-value following non-parametric permutation testing (i.e., p_{PERM}) < 0.0001), mirroring results from the network analysis of empirical neuroimaging datasets[22]. Finally, the level of Q began to drop in the Late training stage (Figure 1D; light purple). These results demonstrate that the modularity of the neural network varies over the course of learning in a way that is tightly associated with the classification performance of the network.

To better understand how the network reconfigures its edge-weights in the Early phase in a manner that promoted accuracy (independent of global topological reorganization – i.e., stable Q), we calculated the variance of changes in edge strength across all edges (σ Edge Δ) in the first sub-network (blue in Figure 1A/B) over the course of the Early phase. The α edge weights that changed the most over this phase were located along the main stroke lines in the middle of the image (e.g.,

the outside circle and a diagonal line; Figure 2A). Similar to the manner in which an eye saccades to a salient target[29], the network appeared to reconfigure to align with the most informative regions of the input space. To test this hypothesis, we binarized the pixel activity across the 60,000 items from the training set, with a threshold that varied across each pixel so as to maximize the mutual information (MI) that the binarized pixel provides about the class (digit), and then calculated the information held by each pixel (I_P: MI(pixel,class); Figure 2B). There was a clear, linear correspondence between I_P and the edges that reconfigured the most during the Early phase (Figure 2C; $r = 0.965$, $p_{PERM} < 0.0001$), supporting our hypothesis that the initial increments in performance were due to the network more strongly reconfiguring edge weights relating to the most class-discriminative areas of the input space.

Figure 2. Complex network signatures of neural network training. A) the standard deviation of changes in edge strength, σ Edge Δ, in the first hidden layer of the network over the course of the

Early training phase (first 10 epochs; cf. Fig. 1C); B) Pixel information, $I_P = MI(pixel,class)$; C) strong positive correlation between σ Edge Δ and MI(pixel,class): $r = 0.965$; D) $I_D = MI(pixel=active,class)$, where 'active' reflects an activity > 0.8; E) participation coefficient (PC) of α edges at training epoch 30; F) module degree z-score (MZ) of first layer at training epoch 30; G) Pearson's correlation, r, between I_D and PC (red) and MZ (blue) across first 30 training epochs. Black lines represent the upper and lower bounds (95th and 5th percentiles) of a permuted null dataset (10,000 iterations) and coloured bars represent learning phases; H) $I_H = MI(node,class)$ for α (blue) and β (orange) edges – note that both subnetworks increase I_H during the Middle phase, but that the Late phase dissociates the two subnetworks.

To better understand node-level network reconfiguration during the Middle phase, we decomposed the network into regional topological signatures – module-degree z-score (MZ) and participation coefficient (PC)[30]. In quantifying within-module and between-module connectivity respectively (see Methods), MZ and PC together characterize the cartographic profile of each node over the course of learning (Figures 2E and 2F). These measures have been previously used in combination with whole-brain human fMRI data to demonstrate a relationship between heightened network integration and cognitive function[24,31], however the algorithmic utility of integrative topological organization is less well understood. Here, we first note the correlation between I_P and MZ at the end of the Middle phase (c.f. Figure 2F). The pixels which hold the most information about the digit class become, on average, more segregated within modules during the Middle phase (Figure 2G). In neuroscience, nodes within the same module are typically presumed to process similar patterns of information[22], suggesting that the topology of the neural network studied here may be aligning to low-dimensional features within the input space.

In order to more precisely relate changes in MZ and PC to the manner in which each pixel held information about the digit class, we calculated the partial information (i.e., I_D: MI(pixel$_{On}$,class); as well as its inverse, MI(pixel$_{Off}$,class)) carried by each pixel about the class. In contrast to I_P, I_D for example quantifies how informative each pixel is for tracking multiple different digit classes, but only when the pixel is active (pixel$_{On}$). High values of I_D imply that the recruitment of the particular pixel is associated with a reduction in uncertainty (i.e., an increase in information) about the digit. As detailed in the Methods, I_P is inversely correlated to I_D and dominated by samples when the pixel is inactive; hence we focus on information carried when the pixel is active I_D (Figure 2D). We observed a double dissociation that emerged over the course of learning in the input layer (Figure 2G), wherein during the Middle phase I_D was positively correlated with nodal participation coefficient (max $r = 0.396$, $p_{PERM} < 0.0001$), but inversely correlated with mean module degree z-score (max $r = -0.352$, $p_{PERM} < 0.0001$). In other words, the topology of the neural network reconfigured so as to align highly informative active pixels with topologically integrated hubs (nodes with higher PC). By contrast, more segregated hubs (nodes with higher MZ) were likely to be informative of digit class. This may indicate that the network is reconfiguring so as to organize sets of informative nodes into modules in a way that supports the creation of higher order 'features' in the next layer.

Given that the same gradient descent algorithms used to train the network was applied consistently across all layers of the network, we predicted that the same principles identified in the input layer should propagate through the network, albeit to the abstracted 'features' captures by each previous layer. Similar to the manner in which a locksmith sequentially opens a bank vault, we hypothesized that each layer of the neural network should align with the most informative

dimensions of its input in turn, such that the information could only be extracted from an insulated layer once a more superficial layer was appropriately aligned with the most informative aspects of its input stream. To test this hypothesis, we investigated how the mutual information MI(node,class) in each node about the digit class evolved across training epochs. As shown in Fig. 2H, mean MI within both hidden layers 1 (MI_{HL1}) and 2 (MI_{HL2}) increased during the first two epochs, but then diverged at the point in learning coinciding with the global decrease in modularity, Q (cf. Fig. 1D). Crucially, the decrease in MI_{HL1} still afforded an increase in MI_{HL2}, suggesting that the Layer 2 nodes must somehow synergistically combine information available in individual Layer 1 nodes to become more informative about the class. This suggests that Layer 1 nodes specialise (and therefore hold less information overall, lower MI_{HL1}) in order to support the synergistic integration of information in later layers of the neural network (increased MI_{HL2}).

In summary, we observed that neural network edges reconfigured in three distinct phases to augment the relationship between input and hidden layer nodes and the information theoretic content of the data being fed into the network. To determine whether these training principles identified on the MNIST dataset were generalizable to other datasets, we trained a new feed-forward neural network (identical in architecture to the original network) on the eMNIST dataset[52], which is similar to MNIST, but uses hand-written letters, as opposed to numbers. Although learning was more protracted in the eMNIST dataset (likely due to the increased complexity of the alphabet, relative to the set of digits), we were able to replicate the changes in network structure across training the MNIST dataset: (i) the network shifted from integration to segregation; layers reconfigured in serial; and nodal roles (with respect to inferred network modules) were similarly related

to class-relevant information in individual pixels (Figure S1). These results suggest that the insights obtained from the MNIST analysis may represent general learning principles of multilayered neural networks.

Next, we investigated whether the manner in which the extent to which the topology of the networks trained on the two datasets differed (i.e., whether different regions of the input space had higher/lower PC/MZ) was proportional to the most informative locations of the inputs space in each dataset (ΔI_D). Specifically, the difference in the pattern of a node's edges across inferred network modules between the eMNIST and MNIST datasets (ΔPC) was correlated with the difference in image input characteristics between the two datasets (ΔI$_D$ vs. ΔPC: r = 0.301, p_{PERM} < 0.0001; ΔI$_D$ vs. ΔMZ: r = -0.247, p_{PERM} < 0.0001). This result provides further confirmation that neural networks learn by reorganizing their nodal topology into a set of phases that act so as to align network edges and activity patterns with the most informative pixels within the training set.

We found that pixels demonstrated unique roles across learning with respect to the emerging modular architecture of the training neural network, and that these roles were shaped by their class-relevant information. As the edge weights were reconfigured across training, we observed that nodal strength increases for highly informative inputs. As these weights change, they alter the activity of each of the nodes in the hidden layers, which ultimately pool their activity to affect the class predictions, which are read out based on the activity of the final output layer. So how do the changes in edge weight translate into nodal activity? Based on recent empirical electrophysiological[32] and fMRI[33] studies, we hypothesized that the activity patterns would be distributed across the neural network in a low-dimensional fashion. Specifically, by way of analogy to the notion of manifold

untangling in the ventral visual system[34], we predicted that across training, the high-dimensional initial state of the system (i.e., the random weights) would become more low-dimensional as pixel-pixel redundancies were discovered through the learning process.

To test this hypothesis, we used a dimensionality-reduction approach[35] to analyze the activity of all of the nodes within the neural network, across the different training epochs. The primary intuition behind these approaches is that, given the highly inter-connected nature of biological systems, reducing the dimensionality of data using statistical techniques, such as principal component analysis (PCA), can allow investigators to essentially ignore small details in order to track the representative activity of the system over time, often revealing key features of its organization[36]. We applied PCA to the nodal activity spread across all four layers of the feedforward network – i.e., the Input, HL1, HL2 and Output nodes – which were first standardized and then either concatenated (to calculate the dimensionality of the entire process) or analyzed on an epoch-to-epoch basis (to calculate the effect of training; see Methods for details). The concatenated state-space embedding was low-dimensional (120/994 components [12.2%] explained ~80% of the variance) and the pixel-wise loading of each of the top eigenvalues for the Input layer (Figure 3A) was correlated with both information theoretic measures used in the prior analyses (I_P – EV_1: $r = 0.218$, $p < 0.0001$; EV_2: $r = 0.189$, $p < 0.0001$; $EV_3 = 0.158$, $p < 0.0001$; and I_D – E_1: $r = 0.338$, $p < 0.0001$; EV_2: $r = 0.123$, $p < 0.0001$; EV_3: $r = 0.062$, $p = 0.080$), suggesting a direct correspondence between information theoretic signatures of the input space and the low-dimensional embedding. Crucially, test trials that were incorrectly classified (Epoch 10,000, though results were consistent for other Epochs) were associated with lower absolute loadings on the ten most explanatory EVs (EV_{1-10}; Figure S3; FDR $p < 0.05$).

This suggests that alignment with the low-dimensional space was related to accurate performance. These results are tangentially related to recent empirical neuroscientific studies that employed dimensionality reduction on electrophysiological[32] and fMRI data[33] to show that learning and cognitive task performance are typically more effective when constrained to a low-dimensional embedding space.

Figure 3 – Unravelling the manifold: low-dimensional projections of neural network activity during MNIST training reveal category-specific untangling. A) The first three principal components (EV_1/EV_2/EV_3) of the Input nodes; B) The percentage of variance explained by EV_1, when the PCA was fit on data from each training epoch separately; C) 3D scatter plot of the items from the training set during three different stages: during the Early phase (Epochs 1–10), the topological embedding of the different digits showed substantial overlap, which is reflected in the low between-category distance (i.e., distance between mean of each digit); in the Middle phase (Epochs 11–300), the embedding showed a relative expansion in the low-dimensional space; and

during the Late phase (Epochs 300+), the distance within each category dropped dramatically; D) 3D scatter plot of between-category and within-category distance, along with training accuracy – note that maximal accuracy is associated with increases in both within- and between-category distance.

By conducting a PCA on each epoch in turn, we were able to show that training was associated with a nonlinear alteration in network dimensionality that aligned with the topologically identified phases (Figure 3B and Movie S1). The network began in a relatively high-dimensional configuration, consistent with the random initiation of nodal activity. During the Early phase (light blue in Figure 3B), as the edge weights reconfigured to align with I_P (Figure 2C), the dimensionality of the system remained relatively high dimensional. During the Middle phase (light green in Figure 3B), there was a sharp reduction in dimensionality, however the dimensionality collapse flattened mid-way through the phase. The Late phase (purple in Figure 3B) was associated with a final, albeit mild, reduction in dimensionality. Interestingly, heightened levels of training led to a tighter correspondence between network topology (PC/MZ, calculated at each epoch) and the principal component loadings of nodes in the Input layer (Figure S2), suggesting that the topology of the neural network reconfigured over training to better map onto the low-dimensional manifold spanned by the information inherent within the training dataset.

Previous theoretical work in systems neuroscience has argued that a primary computational benefit of the nervous system may be to 'untangle' low-dimensional relationships between different information streams[34]. Interestingly, the same concept has been used to explain the function of both the visual system[34] and effective decision making[37], suggesting that the capacity may reflect a

relatively domain general property of nervous system organization. There is also evidence to suggest that the same concept may underpin the functionality of convolutional neural networks trained on naturalistic images[5]. Based on these results, we interrogated our data for the presence of manifold untangling, and found that the increase in topologically rich, low-dimensionality was associated with a relative 'untangling' of the low-dimensional manifold (Figure 3C): the Middle phase was associated with a general expansion in the low-dimensional embedding distance Within categories (light green in Figure 3D), which then allowed the system to both expand Between categories and contract within Categories during the Late phases of learning (purple in Figure 3D). This ultimately had the effect of augmenting classification accuracy. Indeed, the contraction of the within category embedding distance – which takes place first – co-occurs with the drop of MI_{HL1}, with the following expansion of Between category distance co-occurring with the increase in MI_{HL2}. At the sub-network level, the activity on nodes in HL2 was substantially more low-dimensional than HL1 (Figure S4), further expanding on the notion that different computational constraints are imposed on neural networks, depending on the depth of network layers.

Discussion

Overall, the results of this range of analyses demonstrates the benefit that can be obtained by translating neural networks into the language of systems neuroscience. These approaches have been honed to interpret the inner workings of the "black box" of the brain, which is a similar issue to that recognised today in seeking explanations for the inner workings of deep neural networks[4]. An important open question is whether other distinct network architectures, such as recurrent[38], convolutional[39], echo state[40] or generative adversarial networks[41], will

share similar or distinct mechanisms[1,3,4]. It is also well known that the brain contains numerous non-linear mechanisms, including gain modulation[42] and circuit-based mechanisms[43], that may in turn form the basis of distinct topological motifs. Regardless, our work provides evidence that network science can provide intuitive explanations for the computational benefits of neural network learning, and helps to highlight the growing intersection between artificial and biological network analyses[44]. Taking inspiration from biology, other authors have previously suggested that the concept of modularity may be explicitly employed to improve the design of deep neural network architecture in various ways[45,46]. Our findings add to this perspective by demonstrating that the training of such networks may be implicitly interpretable using these same concepts.

What can network neuroscience learn from the results of this experiment? For one, our observations provide evidence that the tools of systems neuroscience and engineering can indeed be used to understand the function of a complex, high-dimensional system[15,35,36]. In addition, there are a number of benefits to analysing neural networks that are not readily apparent in neurobiological analyses. For instance, in the case of feed-forward neural networks, we know the direct mapping between inputs and nodes, whereas in neuroscience, this mapping is challenging (e.g., the location of the animal's gaze can alter the information entering the brain). In addition, standard network approaches in neuroscience require a noisy estimation of network edges, whereas the process here allows us to observe the edge weights directly. It is our hope that these benefits can be used to improve our understanding of the computational benefits of particular systems-level organizing principles, which in turn can be brought back to neuroscience to accelerate progress in our understanding of the systems-level mechanisms that comprise effective neurological function.

In conclusion, we used a systems-level perspective to demonstrate a series of three serial phases over the course of network training that relate to manner in which the topological configuration of the neural network is aligned with the information content provided by the data fed into the network.

Methods

Feedforward Neural Network

A prototypical, four-layer, feed-forward neural network with no non-linearities was created with randomized weights (edge strengths: -1 to 1). The input layer was designed to take 784 inputs, which themselves were flattened from a 28x28 greyscale pixel array from the MNIST dataset[47]. The input layer was fully connected to a hidden layer of 100 nodes (HL1), which in turn was fully connected to a second hidden layer of 100 nodes (HL2). The second hidden layer was then fully connected to a 10-node output layer. The activation function was a standard sigmoid for the incoming connections at each hidden layer (exponent = 1), and a soft max at the output layer. The maximum value across the nodes of the output layer was taken to reflect the 'response' of the network. Each result in our study was also replicated in a separate eMNIST dataset, which was identical to MNIST, but had 26 hand-written letters, as opposed to 10 hand-written digits[48].

Training Approach

The network was trained with backpropagation using a Stochastic Gradient Descent optimiser. To aid interpretation, the learnt bias at each neuron was kept to zero and no regularisation was used. The weights and activities were saved as training progressed over the course of a number of epochs (SGD: 100,000). Accuracy was defined as the percentage of trials in a held-out, 10,000 trial testing set in which the maximum value of the output layer was matched with the test category.

Network Construction

The weighted and signed edges from each asymmetric layer of the neural network were concatenated together to create an asymmetric connectivity matrix. Each connectivity profile was placed in the upper triangle of the matrix (see Figure 2). To ensure that this step did not adversely affect the topological estimates, each experiment was conducted separately on: a) each layer in turn; b) only the upper triangle of the connectivity matrix. Similar patterns were observed when we re-ran each network separately, suggesting that the embedding did not adversely affect topological interpretation.

Modularity Maximization

The Louvain modularity algorithm from the Brain Connectivity Toolbox (BCT[73]) was used on the neural network edge weights to estimate community structure. The Louvain algorithm iteratively maximizes the modularity statistic, Q, for different community assignments until the maximum possible score of Q has been obtained (see Equation 1). The modularity of a given network is therefore a quantification of the extent to which the network may be subdivided into communities with stronger within-module than between-module connections.

$$Q_T = \frac{1}{v^+}\sum_{ij}\left(w_{ij}^+ - e_{ij}^+\right)\delta_{M_iM_j} - \frac{1}{v^+ + v^-}\sum_{ij}\left(w_{ij}^- - e_{ij}^-\right)\delta_{M_iM_j} \qquad [1]$$

where v is the total weight of the network (sum of all negative and positive connections), w_{ij} is the weighted and signed connection between nodes i and j, e_{ij} is the strength of a connection divided by the total weight of the network, and $\delta_{M_iM_j}$ is set to 1 when nodes are in the same community and 0 otherwise. '+' and '−' superscripts denote all positive and negative connections, respectively.

For each epoch, we assessed the community assignment for each region 500 times and a consensus partition was identified using a fine-tuning algorithm from the BCT. We calculated all graph theoretical measures on un-thresholded, weighted and signed undirected, asymmetric connectivity matrices[73]. The stability of the γ parameter (which defines the resolution of the community detection algorithm) was estimated by iteratively calculating the modularity across a range of γ values (0.5-2.5; mean Pearson's r = 0.859 +- 0.01) on the time-averaged connectivity matrix for each subject – across iterations and subjects, a γ value of 1.0 was found to be the least variable, and hence was used for the resultant topological analyses. A consensus clustering partition was defined across all epochs using *consensus_und.m* from the BCT. The resultant solution contained 10 clusters that each contained nodes that were distributed across multiple layers (i.e., Input, HL_1, HL_2 and Output).

Cartographic Profiling

Based on time-resolved community assignments, we estimated within-module connectivity by calculating the time-resolved module-degree Z-score (MZ; within module strength) for each region in our analysis (Equation 2)[74], where κ_{iT} is the strength of the connections of node *i* to other nodes in its module s_i at time *T*, $\bar{\kappa}_{s_{iT}}$ is the average of κ over all the regions in s_i at time *T*, and $\sigma_{\kappa_{s_{iT}}}$ is the standard deviation of κ in s_i at time *T*.

$$\text{MZ} = \frac{\kappa_{iT} - \bar{\kappa}_{s_{iT}}}{\sigma_{\kappa_{s_{iT}}}} \tag{2}$$

The participation coefficient, *PC*, quantifies the extent to which a node connects across all modules (i.e. between-module strength) and has previously been used

to successfully characterize hubs within brain networks (e.g. see [75]). The PC for each node was calculated within each temporal window using Equation 3, where κ_{isT} is the strength of the positive connections of node i to nodes in module s at time T, and κ_{iT} is the sum of strengths of all positive connections of nodes i at time T. Consistent with previous approaches in neuroscience[24,49], negative connections were removed prior to calculation. The participation coefficient of a region is therefore close to 1 if its connections are uniformly distributed among all the modules and 0 if all of its links are within its own module.

$$PC = 1 - \sum_{s=1}^{n_M} \left(\frac{\kappa_{isT}}{\kappa_{iT}}\right)^2 \qquad [3]$$

Mutual Information

We calculated three separate Information measures. To calculate the Information content within each pixel (I_P), we binarized the pixel activity across the 60,000 items from the training set, with a threshold that varied across each pixel so as to maximize the mutual information (MI) that the binarized pixel provides about the class, and then calculated the information within each pixel: MI(pixel,class). To calculate the Information content within each pixel when the pixel was active (after thresholding), we averaged the pointwise MI for each training item, $I_D = \log_2 \frac{p(\text{digit}|\text{pixel})}{p(\text{digit})}$, only over the items where the pixel was on (pixel$_{on}$). Note that I_P and I_D were inversely correlated across the 28x28 input dimension (r = -0.560, p_{PERM} < 0.0001), suggesting that the total information from the pixel is dominated by samples when the pixel is inactive. To calculate the Information content within each hidden layer node (I_H), we calculated the mutual information for each node

(binarized at activity = 0.5) with the digit class. All MI values were computed using the open source JIDT software[50].

Principal Components Analysis

Activity values from the test trials from the input, HL1 and HL2 layers from each epoch were concatenated to form a multi-epoch time series. The data were normalized and then a spatial PCA was performed on the resultant data[35]. The top 3 eigenvectors were used to track the data within a low-dimensional embedding space (Figure 3), and the percentage explained variance was tracked across all learning epochs. The eigenvectors from the concatenated data were then used to estimate the leading eigenvalues across all training epochs. The analysis was also re-run with activity patterns in HL1 and HL2 separately (i.e., independent of the input layer; Figure S4). The average value for each exemplar was then used to create two distance measures: Between-category distance, which was defined as the average between-category Euclidean distance at each epoch; and Within-category distance, which was defined as the average within-category Euclidean distance within each epoch.

Permutation Testing

We used non-parametric testing to determine statistical significance of the relationships identified across our study[51]. A distribution of 10,000 Pearson's correlations was calculated for each comparison, against which the original correlation was compared. Using this approach, the p-value was calculated as the proportion of the null distribution that was less extreme than the original correlation value. In many instances, the effects we observed were more extreme than the null distribution, in which case the p-value was designated as $p_{PERM} < 0.0001$.

References

1. Sejnowski, T. J. The unreasonable effectiveness of deep learning in artificial intelligence. *Proc Natl Acad Sci USA* 201907373 (2020) doi:10.1073/pnas.1907373117.

2. Silver, D. *et al.* Mastering the game of Go with deep neural networks and tree search. *Nature* **529**, 484–489 (2016).

3. Hasson, U., Nastase, S. A. & Goldstein, A. Direct Fit to Nature: An Evolutionary Perspective on Biological and Artificial Neural Networks. *Neuron* **105**, 416–434 (2020).

4. Richards, B. A. *et al.* A deep learning framework for neuroscience. *Nat Neurosci* **22**, 1761–1770 (2019).

5. Cohen, U., Chung, S., Lee, D. D. & Sompolinsky, H. Separability and geometry of object manifolds in deep neural networks. *Nat Commun* **11**, 746 (2020).

6. Shwartz-Ziv, R. & Tishby, N. Opening the Black Box of Deep Neural Networks via Information. *arXiv:1703.00810 [cs]* (2017).

7. Flesch, T., Balaguer, J., Dekker, R., Nili, H. & Summerfield, C. Comparing continual task learning in minds and machines. *Proc Natl Acad Sci USA* **115**, E10313–E10322 (2018).

8. Sussillo, D. Neural circuits as computational dynamical systems. *Current Opinion in Neurobiology* **25**, 156–163 (2014).

9. Lillicrap, T. P., Santoro, A., Marris, L., Akerman, C. J. & Hinton, G. Backpropagation and the brain. *Nat Rev Neurosci* (2020) doi:10.1038/s41583-020-0277-3.

10. Hawrylycz, M. J. *et al.* An anatomically comprehensive atlas of the adult human brain transcriptome. *Nature* **489**, 391–399 (2012).

11. Markram, H. *et al.* Reconstruction and Simulation of Neocortical Microcircuitry. *Cell* **163**, 456–492 (2015).

12. Phillips, J. W. *et al.* A repeated molecular architecture across thalamic pathways. *Nature Neuroscience* **22**, 1925–1935 (2019).

13. Jonas, E. & Kording, K. P. Could a Neuroscientist Understand a Microprocessor? *PLoS Comput Biol* **13**, e1005268 (2017).

14. Margulies, D. S. *et al.* Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proceedings of the National Academy of Sciences of the United States of America* **113**, 12574–12579 (2016).

15. Shine, J. M. *et al.* Human cognition involves the dynamic integration of neural activity and neuromodulatory systems. *Nature Neuroscience* (2019).

16. Bassett, D. S., Yang, M., Wymbs, N. F. & Grafton, S. T. Learning-induced autonomy of sensorimotor systems. *Nature Neuroscience* **18**, 744–751 (2015).

17. Wibral, M., Lizier, J. T. & Priesemann, V. Bits from brains for biologically inspired computing. *Frontiers in Robotics and AI* **2**, 5 (2015).

18. Hamrick, J. & Mohamed, S. Levels of Analysis for Machine Learning. *arXiv:2004.05107 [cs, stat]* (2020).

19. Favre-Bulle, I. A., Vanwalleghem, G., Taylor, M. A., Rubinsztein-Dunlop, H. & Scott, E. K. Cellular-Resolution Imaging of Vestibular Processing across the Larval Zebrafish Brain. *Current biology : CB* **28**, 3711–3722.e3 (2018).

20. Kitzbichler, M. G., Smith, M. L., Christensen, S. R. & Bullmore, E. Broadband Criticality of Human Brain Network Synchronization. *PLoS Comput Biol* **5**, e1000314 (2009).

21. Ellefsen, K. O., Mouret, J.-B. & Clune, J. Neural Modularity Helps Organisms Evolve to Learn New Skills without Forgetting Old Skills. *PLoS Comput Biol* **11**, e1004128 (2015).

22. Sporns, O. & Betzel, R. F. Modular Brain Networks. *Annual review of psychology* **67**, annurev–psych–122414–033634 (2015).

23. Betzel, R. F., Fukushima, M., He, Y., Zuo, X. N. & Sporns, O. Dynamic fluctuations coincide with periods of high and low modularity in resting-state functional brain networks. *NeuroImage* **127**, 287–297 (2016).

24. Shine, J. M. *et al.* The Dynamics of Functional Brain Networks: Integrated Network States during Cognitive Task Performance. *Neuron* **92**, 544–554 (2016).

25. Mohr, H. *et al.* Integration and segregation of large-scale brain networks during short-term task automatization. *Nature communications* **7**, 13217 (2016).

26. Leshno, M., Lin, V. Ya., Pinkus, A. & Schocken, S. Multilayer feedforward networks with a nonpolynomial activation function can approximate any function. *Neural Networks* **6**, 861–867 (1993).

27. Mhaskar, H., Liao, Q. & Poggio, T. Learning Functions: When Is Deep Better Than Shallow. *arXiv:1603.00988 [cs]* (2016).

28. Newman, M. E. J. Modularity and community structure in networks. *Proceedings of the National Academy of Sciences* **103**, 8577–8582 (2006).

29. Friston, K., Adams, R. A., Perrinet, L. & Breakspear, M. Perceptions as Hypotheses: Saccades as Experiments. *Front. Psychology* **3**, (2012).

30. Guimerà, R. & Nunes Amaral, L. A. Functional cartography of complex metabolic networks. *Nature* **433**, 895–900 (2005).

31. Bertolero, M. A., Yeo, B. T. T. & D'Esposito, M. The modular and integrative functional architecture of the human brain. *Proceedings of the National Academy of Sciences of the United States of America* 201510619 (2015).

32. Sadtler, P. T. *et al.* Neural constraints on learning. *Nature* **512**, 423–426 (2014).

33. Shine, J. M. *et al.* The Low-Dimensional Neural Architecture of Cognitive Complexity Is Related to Activity in Medial Thalamic Nuclei. *Neuron* **104**, 849-855.e3 (2019).

34. DiCarlo, J. J. & Cox, D. D. Untangling invariant object recognition. *Trends in Cognitive Sciences* **11**, 333–341 (2007).

35. Cunningham, J. P. & Yu, B. M. Dimensionality reduction for large-scale neural recordings. *Nature Neuroscience* **17**, 1500–1509 (2014).

36. Kato, S. *et al.* Global brain dynamics embed the motor command sequence of Caenorhabditis elegans. *Cell* **163**, 656–669 (2015).

37. Yoo, S. B. M. & Hayden, B. Y. Economic Choice as an Untangling of Options into Actions. *Neuron* **99**, 434–447 (2018).

38. Mastrogiuseppe, F. & Ostojic, S. Linking Connectivity, Dynamics, and Computations in Low-Rank Recurrent Neural Networks. *Neuron* **99**, 609–623.e29 (2018).

39. Yamins, D. L. K. *et al.* Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences of the United States of America* **111**, 8619–8624 (2014).

40. Gallicchio, C. & Scardapane, S. Deep Randomized Neural Networks. *arXiv:2002.12287 [cs, stat]* (2020).

41. Goodfellow, I. J. *et al.* Generative Adversarial Networks. *arXiv:1406.2661 [cs, stat]* (2014).

42. Salinas, E. & Sejnowski, T. J. Book Review: Gain Modulation in the Central Nervous System: Where Behavior, Neurophysiology, and Computation Meet. *Neuroscientist* **7**, 430–440 (2001).

43. Freeman, W. J. Nonlinear gain mediating cortical stimulus-response relations. *Biological cybernetics* **33**, 237–247 (1979).

44. Zador, A. M. A critique of pure learning and what artificial neural networks can learn from animal brains. *Nat Commun* **10**, 3770 (2019).

45. Jo, J., Verma, V. & Bengio, Y. Modularity Matters: Learning Invariant Relational Reasoning Tasks. *arXiv:1806.06765 [cs, q-bio, stat]* (2018).

46. Kirsch, L., Kunze, J. & Barber, D. Modular Networks: Learning to Decompose Neural Computation. *arXiv:1811.05249 [cs, stat]* (2018).

47. Lecun, Y., Bottou, L., Bengio, Y. & Haffner, P. Gradient-based learning applied to document recognition. *Proc. IEEE* **86**, 2278–2324 (1998).

48. Cohen, G., Afshar, S., Tapson, J. & van Schaik, A. EMNIST: an extension of MNIST to handwritten letters. *arXiv:1702.05373 [cs]* (2017).

49. Bertolero, M. A., Yeo, B. T. T. & D'Esposito, M. The diverse club. *Nature communications* **8**, 1277 (2017).

50. Lizier, J. T. JIDT: An Information-Theoretic Toolkit for Studying the Dynamics of Complex Systems. *Front. Robot. AI* **1**, (2014).

51. Nichols, T. E. & Holmes, A. P. Nonparametric permutation tests for functional neuroimaging: a primer with examples. *Human brain mapping* **15**, 1–25 (2002).

52. https://www.nist.gov/itl/products-and-services/emnist-dataset