2
3
4 **History-driven modulations of population codes in early visual cortex**
5 **during visual search**
6

7 Kirsten C.S. Adam[1,2] & John T. Serences[1,2,3]
8
9 [1] Department of Psychology, *University of California San Diego*
10 [2] Institute for Neural Computation*, University of California San Diego*
11 [3] Neurosciences Graduate Program, *University of California San Diego*

12
13 **Word count (abstract):** 149
14 **Word count (less abstract, methods, references, figure legends):** 4,007
15 **Word count (methods):** 2,215
16 **Tables:** 0
17 **Figures:** 7
18
19 **Keywords:** visual search; fMRI; priority maps; attentional selection; salience
20

21 **Contributions:** K.A. collected data, performed analyses, and drafted the manuscript.
22 Both authors designed the study and revised the manuscript.

24 **Funding:** Research was supported by National Eye Institute grant R01 EY025872
25 (J.S.). and National Institute of Mental Health grant 5T32-MH020002 (K.A.).

26
27 **Data availability:** Data will be made freely available online on the Open Science
28 Framework at https://osf.io/wrdvz/ upon acceptance for publication.
29

30 **Acknowledgements:** We thank Rosanne Rademaker for scanning assistance and for
31 sharing custom analysis code. We thank Nicole Rangan and Matteo d'Amico for
32 assistance with behavioral data collection, and we thank Ed Awh for helpful comments
33 on the manuscript.

34
35 **Conflicts of interest:** none
36

Correspondence to:
Kirsten C. S. Adam
University of California San Diego
9500 Gilman Drive, Mail Code: 0109
La Jolla, CA 92093-0109
kadam@ucsd.edu

Abstract

To find important objects, we must focus on our goals, ignore distractions, and take our changing environment into account. This is formalized in models of visual search whereby goal-driven, stimulus-driven and history-driven factors are integrated into a priority map that guides attention. History is invoked to explain behavioral effects that are neither wholly goal-driven nor stimulus-driven, but whether history likewise alters goal-driven and/or stimulus-driven signatures of neural priority is unknown. We measured fMRI responses in human visual cortex during a visual search task where trial history was manipulated (colors switched unpredictably or repeated). History had a near-constant impact on responses to singleton distractors, but not targets, from V1 through parietal cortex. In contrast, history-independent target enhancement was absent in V1 but increased across regions. Our data suggest that history does not alter goal-driven search templates, but rather modulates canonically stimulus-driven sensory responses to create a temporally-integrated representation of priority.

59   **Introduction**

At any moment we can selectively attend only a small fraction of available

perceptual inputs due to a limited processing capacity, and the world around us is

constantly changing. When performing visual search, we thus need to enhance relevant

information, discard irrelevant information, and keep track of our changing surroundings.

For example, when searching for sea glass at the beach, irrelevant but salient information

(e.g., a red plastic bottle-cap) may grab our attention. But, if we repeatedly encounter the

same irrelevant information (e.g., the beach is littered with red bottle-caps), then we can

learn to ignore initially salient distractors.

Models of visual search hypothesize that we integrate information about what is

relevant (*goal-driven* or *'top-down' factors*), what is salient given local image statistics

(*stimulus-driven* or *'bottom-up' factors*), and what has occurred in the past (*history-driven*

factors) via an integrated, topographically organized "priority map"[1–6]. Note, some work

uses the terms 'saliency' and 'priority' interchangeably, whereas other work uses these

terms to refer to distinct concepts. Here, we use 'priority' to refer to the integration of goal-

driven and stimulus-driven task factors, and 'saliency' to refer to strictly to image-

computable, stimulus-driven task factors[4].

Although both stimulus-driven and goal-driven information is represented to some

extent in many cortical regions[4,7–11], areas of parietal cortex (e.g., LIP, IPS) are

hypothesized to be ideal candidates for integrating information about stimulus-driven

sensory inputs from occipital cortex and information about goals from pre-frontal cortex[12–

15]. In contrast to goal-driven and stimulus-driven effects, history-driven effects have only

recently been added to models of visual search, in part because these effects do not

wholly fit within a 'goal-driven' versus 'stimulus-driven' dichotomous framework[1,16–18].

Rather, history-driven effects apparently rely upon the relationship between the current

sensory input and knowledge of prior experiences. Much work has demonstrated how

canonically 'goal-driven' and 'stimulus-driven' task manipulations alter neural activity in

occipital and parietal cortex (i.e., selective attention[7,10,11,19–25] and stimulus-driven

salience maps[3,26,27], respectively), but an open question is whether stimulus history

influences attentional priority by co-opting elements of these computations.

Some accounts of history-driven effects predict that we exploit existing goal-driven

selection mechanisms to incorporate information about history-driven task factors into

priority maps. For example, when looking for a particular target, one may form a

"template" of that feature and use this template to voluntarily up-regulate relevant portions

of the visual field by co-opting goal-driven selective attention[28–33]. Thus, one possibility is

that history-driven effects (e.g., repetition of target color) may strengthen the target

template, and this increased goal-driven guidance would result in greater activation of the

target position in a priority map. Likewise, if a particular distractor feature is repeated, one

may form an analogous "negative template" for ignoring this feature[34–37] (but see[38,39]).

However, not all evidence supports the notion that history-driven effects can be

implemented via goal-driven selective attention[40–44]. Rather, integrating history into

priority may exploit canonically 'stimulus-driven' mechanisms that are encapsulated

within local sensory circuits (e.g., modulation of stimulus-driven saliency maps via

adaptation[45,46], habituation[42–44] and/or repetition suppression[47,48]). Of course, these

possibilities are not mutually exclusive. For example, distractor and target processing

seem to be differentially affected by history[49–52]. Therefore, it may be that history-driven

changes to priority are reflected in a combination of traditionally 'goal-driven' and

'stimulus-driven' neural signatures of priority. Alternatively, history-driven effects may also

be coded via another pathway, such as via implicit and/or explicit learning of regularities

within the medial-temporal lobe[13,53,54].

To test how stimulus history modulates priority, we measured neural activity via

fMRI in human subjects performing a visual search task. If stimulus history influences

search by altering the specificity of the goal-driven target template, then we would expect

to see an enhanced representation of the target item's position, and this effect should be

most pronounced in regions that are also most influenced by goal-driven selective

attention such as IPS0. However, if stimulus history influences search by influencing

canonically stimulus-driven sensory activity, then we would expect to see a decreased

representation of the salient distractor's position, and this effect should be pronounced in

areas most influenced by stimulus-driven salience such as V1. We thus estimated the

strength of target and distractor representations in a 4-item search array across

retinotopically-defined visual cortical regions. Critically, we manipulated trial history such

that we could compare neural responses to physically identical displays (e.g., green

target, red singleton distractor) as a function of trial history (i.e., whether the colors of

preceding displays repeated or varied).

To preview the results, we found that trial history modulated model-based

estimates of distractor suppression, but not target enhancement, in retinotopically-defined

visual areas. Furthermore, we found that visual regions were differentially modulated by

goal-driven target enhancement and by history-driven distractor suppression. Whereas

goal-driven modulations to population codes (i.e., target enhancement) were absent in

V1 and were amplified across the visual hierarchy, history-driven effects were robust in

V1 and across all other examined ROIs. Overall, the data suggest a dissociation between

canonical 'goal-driven' mechanisms of attentional priority and 'history-driven' effects on

distractor processing. We discuss our findings in the context of 'stimulus-driven' saliency

models of V1, whereby history-driven task factors may directly modify priority within

canonically stimulus-driven saliency maps, which integrate neural activity across trials as

well as within a given trial, without the need for a 'goal-driven' template of the incidentally

repeated information.

136   **Results**

Behavior

Subjects performed a variant of the additional singleton search task[55] (Figure 1A)

in which they searched for a target (diamond) among non-targets (circles). On each trial,

the participant reported via button-press the orientation of the line inside the diamond

target (vertical or horizontal). On 66.67% of trials, one of the non-targets was uniquely

colored ("singleton distractor present", e.g., one red distractor, two green non-targets, and

one green target item). Behavioral capture was quantified as slowed response times

(RTs) when the distractor was present versus absent. In addition to examining the basic

capture effect, a key goal of this work was to examine modulation of capture by trial

history[56–58]. Prior work has shown that participants can learn to suppress a distractor (i.e.,

no RT difference for singleton distractor present versus absent trials) when the same

distractor color or distractor location is repeated over many trials[56–58]. Building on this

work, we included two key task conditions in a counterbalanced, block-wise fashion to

manipulate trial history and behavioral capture while using identical stimulus arrays (e.g.,

green target, red distractor). In the color constant condition (Figure 1A), the array colors

stayed constant throughout the block (e.g., green target, green non-target items, red

distractor). In the color variable condition (Figure 1B), the array colors randomly varied

from trial to trial. Based on prior work, we expected robust capture in the color variable

condition, and little or no capture in the color constant condition[56–58].

Figure 1. Visual search task stimuli. On each trial, participants viewed a 4-item array
and reported the orientation of the line inside the diamond-shaped target (horizontal or
vertical). **(A)** In the color constant condition, colors of targets and singleton distractors
were fixed throughout the run. **(B)** In the color variable condition, colors of targets and
singleton distractors swapped randomly from trial to trial.

Replicating prior work, we found significant behavioral capture that was modulated

by trial history[40,41,50,56–59]. In our MRI sample (Exp 1a), we observed significant behavioral

capture in the color variable condition, with longer RT's for distractor present versus

distractor absent trials ($M = 32.8$ ms, $SD = 25.5$ ms, $p = .001$, $d = 1.28$), but capture was

not significant in the color constant condition ($M = 10.8$ ms, $SD = 18.5$ ms, $p = .07$, $d =$

.59). Importantly, capture was significantly larger for color variable vs. color constant runs

($p = .009$, $d = .91$). We replicated this pattern of findings in the behavior-only experiment

(Exp. 1b), with robust capture for 'color variable' ($p < 1 \times 10^{-5}$, $d = 1.31$), no significant

capture for 'color constant' ($p = .1$, $d = .32$), and larger capture for color variable vs.

constant ($p = .002$, $d = .71$). Participants in both experiments were accurate overall

(>90%), and there was no evidence of a speed-accuracy trade-off (Analysis S1).

In addition to the key modulation of capture as a function of stimulus history, we
also replicated prior findings that the degree of capture is significantly modulated by the
physical distance between the target and the distractor[41,49,60,61], with larger capture for
distractors nearer the target (Figure 2E-F). We ran a repeated measures ANOVA
including both experiments (n=36). Including Experiment as a factor revealed no
experiment main effects or interactions (p > .2), so the two experiments were combined
for further analyses of the behavioral data (although Figure 2 shows data from the two
experiments separately). There was a significant effect of Condition (larger capture for
color variable than color constant), $p < 1 \times 10^{-4}$, a main effect of Distance (larger capture
for 90° than 180°), $p = .037$, $\eta^2_p = .12$, and an interaction between Condition and Distance
(greater distance effect in the color variable condition), $p = .014$, $\eta^2_p = .16$.

Figure 2. Behavioral capture during the visual search task. (A) In the main MRI
Experiment (Exp 1a), participants were significantly captured by the salient singleton
distractor in the color variable condition, but not in the color constant condition. **(B)** This
pattern replicated in the behavior-only experiment (Exp 1b). **(C-D)** Capture costs (RT
Difference for distractor present – absent trials) were significantly larger in the color
variable than in the color constant condition in Exp 1a **(C)** and Exp 1b **(D)**. **(E-F)** Capture

costs (RT Difference for distractor present – absent trials) were significantly modulated
by the distance between the target and distractor in the color variable condition both in
Exp 1a **(E)** and Exp 1b **(F)**. Violin plot shading shows range and distribution of the data;
dots represent single subjects; black error bars indicate ±1 SEM.
198

fMRI results: Model estimates of spatial position in the independent mapping task

We opted for a multivariate model-based approach to estimate the amount of

information encoded in voxel activation patterns about each of the 4 stimuli in the search

array, as such multivariate approaches are more sensitive than just computing the

univariate mean response across all voxels[62–67]. For example, item-specific information

has been observed using multivariate methods even in the absence of univariate

changes[68,69] (but for univariate analyses of the present data, see Figure S1). We opted

for an inverted encoding model (IEM) approach[70,71], as opposed to Bayesian or other

decoders[72,73], because this approach allowed us to easily derive a separate estimate of

the information encoded about each of the 4 simultaneously presented items from the

search array in the main analysis[70].

In our key analyses of the fMRI data, we used an independent mapping task to

train a model of spatial position from which we estimated the relative priority of all item

positions within the visual search array. During the independent mapping task, observers

viewed a flickering checkerboard wedge that was presented at 1 of 24 positions on an

imaginary circle around fixation (Figure 3A). We first checked that we observed robust

estimates of spatial position when training and testing within the independent mapping

task (leave 1 run out, see section 'Inverted Encoding Model'). We observed robust model-

based estimates of spatial position for all ROIs (Figure 3B). Parameters from the best-

fitting von Mises distribution to each region-of-interest (ROI) are depicted in Figure 3C

(model fits are shown in Figure S2). There was an effect of ROI on precision such that

spatial position was represented less precisely in later visual areas ($p < 1 \times 10^{-5}$, where

precision is the concentration parameter κ of the best fitting von Mises, with higher values

indicating a more precise function). There was also an effect of ROI on the amplitude and

baseline measures of the model-based estimates of spatial position ($p < 1 \times 10^{-5}$), and all

3 parameters significantly differed from zero across all ROIs ($p < 1 \times 10^{-5}$). These results,

particularly the observation of amplitudes greater than 0, confirmed that activation

patterns in all examined regions encode information about spatial position.

Figure 3. Single-item model estimates training and testing within the independent
mapping task. (A) Independent mapping task used to train the model to estimate spatial
position of 4 search array items. Participants viewed a flickering checkerboard which
could appear at one of 24 positions around an imaginary circle. **(B)** Blue lines: Model
estimates of viewed spatial position training and testing within the independent mapping
task. Single-trial model estimates for each subject are aligned to 0 degrees and averaged.
Black lines: Model estimates for shuffled training labels. Opaque lines = group average;
semi-transparent lines = individual subjects. **(C)** Descriptive statistics for best fit von Mises
parameters (precision [κ], amplitude, baseline) to model estimates in panel B. Error bars
indicate ±1 SEM; the opaque line shows the group average; semi-transparent lines show
individual subjects.

Unlike the single item model estimates that were derived based on the

independent mapping task (Figure 3), we could not fit a simple, uni-modal Gaussian

function to model-based estimates derived from the search task data because 4 peaks in

the model output were expected – one for each item in the search array. As such, we first

conducted simulations to ensure that we would be able to measure putative changes to

individual item representations (e.g. target enhancement, distractor suppression), despite

multiple item representations contributing to the aggregate 4-item model estimates. To

do so, we used data from the independent mapping task to generate predictions for

observed model responses in a 4-item array. For each ROI, we took the 1-item model

response derived from the independent mapping task, replicated this model response

four times (once at each of the four search array positions), and took the average of all 4

shifted 1-item model response lines to generate a single 4-item model prediction. In

addition, we systematically varied the strength of the simulated response to each item to

ensure that we were able to recover a corresponding change in the item-specific

responses estimated from the aggregate 4-item model estimate (Figure 4; Figure S3).

256   These simulations revealed clearly separable peaks for all four items in early areas

like V1, where spatial precision is high (Figure 4A-B, left panel). In contrast, identifying

clear peaks in later areas like IPS0 was difficult when the response to all items was

equivalent (Figure 4A-B, right panel). However, if one item evoked a larger or smaller

response than the other items, as would be expected with target enhancement or

distractor suppression, then clear and measurable changes to the aggregate 4-item

model estimates emerged (Figure 4C). Further simulations showed that we could detect

smaller changes to one item (e.g., distractor suppression) in the presence of larger

changes to another item (e.g., target) by measuring the response amplitude at each

expected item's peak. In V1, this is clearly seen in the peak response to each item; in

later areas such as IPS0, such changes manifest as a large central peak that is skewed

by the neighboring items' smaller changes (Figure 4D).

268   We also used a general linear model (GLM) to estimate best-fitting gain factors for

each of the 4 hypothesized item representations by fitting an aggregate function and

allowing one parameter in the GLM to scale the response associated with each item. This

is essentially the inverse of the simulations described above: For a given aggregate

response (i.e., the response of each of the 24 spatial channels when shown a given 4-

item search array), we used a non-negative least squares solution[74] to estimate the

contribution of each of the 4 item positions (calculated from the 1-item localizer task) to

the observed 4-item search array response (Figure 4E). This analysis yielded similar

results to the simple approach of comparing the height at each expected item peak (e.g.,

Analysis S2-4). Thus, using either the raw amplitude at expected peaks or a GLM-based

approach, we determined that we should be able to accurately characterize situations in

which there was no modulation of target and distractor responses as well as situations in

which there was a significant modulation of target and/or distractor responses.

Figure 4. Generating predictions for 4-item model estimates by averaging single-
item model estimates from the independent mapping task. (A) Average from the
independent mapping task plotted at 4 hypothetical item locations. Here, these 4 "items"
are represented with equal priority. (B) Hypothetical observed response when measuring
a single trial containing the 4 items presented simultaneously. This line is the average of
all lines in Panel A. (C) The same as panels A and B, but with the item at position 0
assigned a higher response amplitude than the other three items. (D) The same panels
as A and B, but with both an enhanced item at position 0 and a suppressed item at position
-90. (E) Actual IEM model output for 4-item search arrays in V2 (Target plotted at 0,
distractor plotted at -90). To estimate the strength of each of the 4 underlying item
representations, one can simply measure the height (a.u.) at expected item peaks (i.e., -
180, -90, 0, and 90). Alternatively, one may use a non-negative least squares solution to
estimate weights for a regressor for each of the 4 item positions. Each regressor is the 1-
item IEM output from the independent mapping task within the same region (e.g., V2),
shifted to the appropriate item location. (F) Example IEM output and best-fitting non-
negative least squares solution with 4 item regressors.
299

Analysis of search array locations in V1, V2, V3, V3AB, hV4, and IPS0.

Given that we can assess differential responses associated with each of the 4

items in the search array (Figure 4), we next tested whether goal- and history-driven

modulations were differentially represented across the visual stream by performing an

analysis of history-driven effects on target and distractor processing across visual ROIs

(Figure 5). These six ROIs (V1, V2, V3, V3AB, hV4 and IPS0) were chosen for each
participant having at least 90 spatially selective voxels as determined by the localizer
data. Here, we focus on history-driven effects on target processing and distractor
processing for the arrays where behavioral and neural distractor competition effects were
greatest (target-distractor separation +/-90°, see Figure 2E,F). Full ANOVA results and
additional plots are shown for individuals ROIs with both array 90° and 180°
configurations in Figure S7-8 and Analysis S5.

**Figure 5. Dissociable effects of stimulus history on target enhancement and
distractor suppression.** (A) Model responses for individual ROIs as a function of task
condition (Arrays with target-distractor distance +/-90). Purple and green lines (Shaded
error bars = 1 SEM) show the output of the inverted encoding model in the color constant
and color variable conditions, respectively. Target enhancement can be seen as the
greater height at position 0; history-driven distractor suppression can be seen as the lower
height at position -90 for the purple vs. green line. Background panels at -180°, -90°, 0°
and +90° show the positions of the 4 search array items (blue = target (T), pink = distractor
(D), green = non-target 1(N1), orange = non-target 2 (N2), (B) Target amplitude as a
function of ROI and task condition. There was no effect of task condition on target
amplitude, but a significant increase in target amplitude across ROIs. Violin plot shading
shows range and distribution of the data; dots represent single subjects; black error bars
indicate ±1 SEM. (C) Distractor amplitude as a function of ROI and task condition. There
was a significant effect of task condition on distractor amplitude, and this history-driven
effect did not interact with ROI.

330   We found evidence for within-display target enhancement (i.e., enhancement of

331 the target over other positions), but we did not find evidence for history-driven

332 modulations of target enhancement. Overall target enhancement was significant in all

333 ROIs (all p's < .001) except for V1 (p's > .12), and target enhancement significantly

334 increased across ROIs (p < .001) as shown in Figure 6A-B. There was, however, no

335 meaningful effect of history on target amplitude as revealed by a repeated-measures

336 ANOVA testing the main effect of history and the interaction between history and ROI on

337 target processing (p = .35, η^2_p = .08; p = .64, η^2_p = .04 for main effect and interaction

338 respectively). This pattern was the same whether we used raw amplitude values or we

339 used values from the GLM (no effect of history, p = .28, no interaction of history and ROI,

340 p = .51).

341   In contrast, history had a significant effect on distractor amplitude such that

342 distractor amplitudes were significantly attenuated in the color constant condition relative

343 to the color variable condition. A repeated-measures ANOVA revealed a main effect of

344 history (p = .007, η^2_p = .50) and no interaction between history and ROI (p = .44, η^2_p =

345 .08), indicating that the effect of history on distractor processing was similar throughout

346 the examined ROIs. Though the ANOVA suggests that history effects were of a similar

347 magnitude across all examined ROIs, a post-hoc simple main effects analysis showed

348 that the effect was individually significant only in V1 (p < .001) and V3 (p < .01). This

349 general pattern was the same whether we used raw amplitude values or else used values

350 from the GLM approach (main effect of history, p = .01, η^2_p = .47, no interaction of history

351 and ROI, p = .87, η^2_p = .03).

352   Finally, we examined changes in non-target responses. For "non-target 1" (the item

353 neighboring the target on the side opposite the distractor), there was an overall history

354 related modulation (color constant > color variable, p = .016, η^2_p = .42) that did not interact

355 with ROI (p = .76, η^2_p = .03). Similar general effects on non-target processing have been

356 observed recently[51] and may reflect a bias of attention away from the distractor such that

357 attention may 'overshoot' the target because of the reduction in signal at the distractor

358 location. The effect of history on "non-target 1" responses likewise was similar though of

borderline significance in the GLM analysis (color constant > color variable, p = .049, η^2_p

= .31). We found no effect of history on the other non-target ("non-target 2") which

occupied the spatial position 180 degrees from the target item (p >= .61).

Finally, additional analyses on larger, aggregate ROIs (V1-V3, IPS0-3) yield

convergent results and also demonstrate how distractor suppression effects were absent

for arrays where the target and distractor did not compete with each other (target-

distractor separation +/- 180°), consistent with our separate analysis of each ROI (Figure

6) and prior behavioral and neural findings[41,49,51,60] (Analysis S2-4, Figures S4-6).

368   **Discussion**

To find what we are looking for, we must integrate information about stimulus

relevance, salience, and history. While the impact of stimulus relevance and salience on

topographically organized population codes have been thoroughly investigated, stimulus

history is not thought to be a wholly goal-driven or stimulus-driven process as history

effects depend on interactions between the current stimulus drive ('bottom-up' factor) and

the current internal state of the visual system ('top-down' factor). To address this

ambiguity and to better understand how history impacts visual processing, we tested

whether history-driven changes to attentional priority operate in a manner akin to

canonically goal-driven and/or to stimulus-driven signatures of priority. To do so, we

estimated population-level neural responses evoked by 4-item search arrays across

retinotopically-defined areas of occipital and parietal cortex. We found that stimulus

history did not modulate the specificity of goal-driven target templates, as goal-driven

target enhancement was unaffected by stimulus history. Instead, we found that stimulus

history attenuated responses related to distractors throughout the visual hierarchy. These

results suggest that stimulus history may influence visual search performance via local

competitive interactions within early sensory cortex (i.e., V1).

Traditional models of image-computable salience propose that local image

statistics determine competitive interactions that give rise to 2D spatial salience maps

within V1[26,27], and these models do not typically account for the effects of stimulus history.

However, recent work suggests that neural adaptation – which is linked to the history of

prior stimuli – in a subset of tuned neurons may alter stimulus-driven competitive
dynamics (e.g., divisive normalization[75]) within early visual cortex[76]. Thus, to
accommodate our observation of history-driven distractor suppression within existing
saliency models, we propose that stimulus-driven evoked responses may be integrated
over a longer, multi-trial duration (as opposed to just within a single image; Figure 6)[77–79].
In the context of models of visual search, this might be comprised of a series of 2D spatial
maps that together form a temporally integrated 3D salience map (i.e., salience is
computed based on current and prior physical stimulus properties). Consistent with the
notion of a 3D salience map, recent behavioral and neural evidence suggests a role for
priming and habituation in visual search behaviors[42–44,50,80] (also see[81]).

Figure 6. Simplified cartoon illustration of local-image versus temporal-integration
salience for a simple image with one feature and location. (A) In 2-D salience
computations, stimulus-driven stimulus drive is determined locally within a given image
without respect to prior images. Sequence 1 is 4 different trials, and on each trial the
same stimulus is shown (Blue-Blue-Blue-Blue). Sequence 2 is 4 different trials, but the
final trial is a different color from the preceding trials (Green-Green-Green-Blue). The final
trial (Blue) is physically identical for the two sequences. So, the final stimuli (trial n in each
sequence) have identical 2-D salience. Assuming that we chose equiluminant green and
blue values, then each "frame" in the sequence likewise has approximately the same
image-computable salience, as shown by the uniform-sized square pulses in the cartoon.
(B) Alternatively, stimulus-driven salience maps may better be conceived of as reflecting
a temporally-integrated 3-D salience map, as early sensory neurons adapt to ongoing
stimulus features. In Sequence 1 (Blue-Blue-Blue-Blue), the activity of neurons that are
maximally responsive to blue wanes due to adaptation. In Sequence 2 the activity of
neurons maximally responsive to green wanes over the first 3 trials, but the final stimulus
elicits a robust response from the non-adapted blue-preferring neurons. Thus, temporally-
integrated salience for the trial *n* in each sequence differs across the two sequences even
though the stimuli are physically identical.

Consistent with a temporally-integrated salience account of history-driven
distractor suppression, we observed history-driven modulations only with sufficient
competition (i.e., targets and distractors were closer together) and we observed robust
history-driven modulations in V1 in the absence of goal-driven modulations. In line with
our findings, prior behavioral work has shown that incidental repetitions of distractor, but
not target, features and locations modulate search performance[49,50]. Likewise, prior work
has shown a rapid suppression of distractor-evoked neural responses[56,57,82–86] and that
the likelihood of distraction results in anticipatory changes to distractor, but not target,
locations[51,87,88]. However, the proposed temporally-integrated salience account does not
capture all history-driven effects. In our task, the repeated distractor features were purely
visual in nature, and thus history effects might be mediated entirely via local circuit
dynamics (i.e., the adaptation account described above). In contrast, other studies have
examined history-driven effects for more abstract features like reward[10,19,89–95] (but also
see[96,97]), which may require an intermediary pathway such as the medial-temporal lobe[13]
or dopaminergic midbrain structures[89,98].

In addition to implicating early visual cortex in representing history-driven task
factors during visual search, we also replicated prior findings that the locations of attended
items (here, search targets) are prioritized relative to other item locations in both visual
and parietal cortex[7,8,10]. These target-related modulations are consistent with the broad
involvement of visually-responsive regions in representing goal-driven priority during
visual search[19,25]. For example, recent studies manipulated the salience (contrast) and
relevance (attended or unattended) of items and found that salience and relevance were
both represented, to varying degrees, across the visual hierarchy[8,20]. Notably, however,
here we found that target prioritization was absent in V1, whereas prior work has found
robust effects of attention in V1[7,10,11,21–24,99,100]. This difference may reflect task
differences — much prior work found attention-related gains in V1 when spatial attention
was cued in advance or a single target was shown, whereas visual search arrays provide
visual drive at many competing locations and spatial attention is deployed only after array
onset. In addition, our work suggests that further work may be needed to unconfound
history effects and attention effects in the study of spatial attention, as much early work

on univariate attention effects has employed blocked designs where the same location is

attended for many trials in a row[21,22,24,99,100].

Although our work suggests that stimulus history modulates representations of

distractor but not target processing in visual cortex, there are some potential limitations

to the current design that suggest avenues for future work. First, because we measured

only location, we could not directly measure suppression of the distractor color[40].

However, as the spatial position of the distractor was completely unpredictable, our

results do strongly imply that the distractor color was suppressed. Likewise, most theories

of visual search hypothesize that space is the critical binding medium through which

feature and goal maps are integrated[3,5,6], and recent work suggests that location is

spontaneously encoded even when only non-spatial features such as color are task-

relevant[101]. Second, it is possible that history may modulate both distractor- and target-

processing in other circumstances not tested here. That is, perhaps the target template

'diamond' in our task was sufficiently useful such that adding feature information to this

template (e.g., 'red diamond' rather than 'diamond') did not confer a behavioral advantage

(but see[102]). Finally, the time-course of MRI (sampling every 800 ms) is slower than shifts

of spatial attention to the search target (< 500 ms)[103]. Although the history-driven effects

that we observed in visual cortex are consistent with the rapid distractor suppression

effects observed in EEG[82,83], we cannot definitively say on the basis of these data that

the observed history-driven effects occurred rapidly and directly within visual cortex

versus via recurrent feedback from later visual areas. Nonetheless, the present work is

consistent with and provides critical initial evidence for such a model.

471   **Methods**

Participants

Experiment 1a: MRI experiment. Healthy volunteers ($n = 12$; 9 female; mean age

= 25.3 years [SD = 2.5, min = 21, max = 30]; all right-handed; normal or corrected-to-

normal visual acuity; normal color vision) participated in three ~2 hour sessions at the

Keck Center for fMRI on the University of California San Diego (UCSD) campus, and were

compensated $20/hr. Procedures were approved by the UCSD Institutional Review

Board, and participants provided written informed consent. Sample size was determined

by a power analysis on data from Sprague et al.[8] where achieved power (1-ß) to detect a

within-subjects attention modulation using an inverted encoding model was 83% (across

10 ROIs) with n=8. We planned for n =11 to achieve estimated 90% power (rounded up

to n = 12 to satisfy our counter-balancing criteria).

Experiment 1b: Behavior only. Healthy volunteers ($n = 24$; 21 female; mean age

= 19.8 years [SD = 1.5, min = 18, max = 24]; normal or corrected-to-normal visual acuity;

normal color vision; handedness not recorded) participated in one 1.5-hour experimental

session in the Department of Psychology on the UCSD campus, and were compensated

with course credit. Procedures were approved by the UCSD IRB, and all participants

provided written informed consent. A sample size of 24 was chosen *a priori* based on

published papers[56].

Session procedures

Exp 1a, Retinotopy session. Participants completed one retinotopic mapping

session prior to participation in the experimental sessions, following standard

procedures[104,105]. Some participants had already completed a retinotopy session as part

of prior studies in the lab; this session was used if available. Retinotopy data were used

to identify retinotopic ROIs (V1-V3, V3AB, hV4, VO1, VO2, LO1, LO2, TO1, TO2, IPS0-

4). During each session, participants viewed flickering checkerboards. On meridian

mapping runs, a "bowtie" checkerboard alternated between the horizontal and vertical

meridians. On polar angle mapping runs, a checkerboard wedge slowly rotated in a

clockwise or counterclockwise direction. On eccentricity mapping runs, a "donut"

checkerboard began near fixation and its radius slowly expanded outward. A high-

resolution anatomical scan was collected for functional alignment. Anatomical and

functional retinotopy analyses were performed using custom code caling existing

FreeSurfer and FSL functions. Functional retinotopy data were used to draw ROIs, but

only voxels that were also visually responsive to experimental localizers (below) were

analyzed further.

Exp 1a, Main MRI session. Participants completed two experimental sessions. In

each session, they completed 2 runs of the item position localizer, 4 runs of the spatial

location localizer, and 8 runs of the search task (4 runs "color variable", 4 runs "color

constant"). When time allowed, extra localizer runs were collected. Some participants also

took part in an unrelated study in which additional localizers were collected.

Exp 1b. Participants completed 12 blocks of the search task (6 blocks "color

variable", 6 blocks "color constant").

Stimuli and task procedures

Experiment 1a: MRI

Stimuli were projected on a 21.5 x 16 cm screen mounted inside the scanner bore.

The screen was viewed from a distance of ~47 cm through a mirror. Stimuli were

generated in MATLAB (2017b, The MathWorks, Natick, MA) with the Psychophysics

toolbox [106,107] on a laptop running Ubuntu. Responses were collected with a 4-button

button box. Stimuli for each task are shown in Figure 1.

Item position localizer. Participants viewed reversing checkerboards (4 Hz

flicker) which occupied the locations of the items in the search task (each item radius =

2.5^o placed on an imaginary circle 7^o from fixation, with one item in each of the 4

quadrants on the circle). Participants were shown items on 2 alternating diagonals (i.e.,

items in Quadrants 1 and 3 and then Quadrants 2 and 4) for 3 sec each. There were 88

stimulus presentations within each run. Participants were instructed to attend to both

items, and to press a button if either item briefly dimmed. A brief (250 ms) dimming

occurred on 1 of the 2 items for 25% of stimulus presentations.

Spatial location localizer. Participants viewed a reversing checkerboard wedge

(flicker = 4 Hz; white & black checkerboards) at one of 24 positions. Checkerboard

positions were equally spaced along a circle with radius = 7^o, and wedges were non-

overlapping (i.e., each wedge's width along the circle filled a 15^o arc and was ~5^o of visual

angle in height). The wedge stayed at one position for 3 sec, then moved to a different

position (with the constraint that back-to-back positions must be in different quadrants).

There were 96 wedge presentations within each run. Participants were instructed to

attend to the fixation point; if the fixation point's color changed (increase or decrease in

brightness), they pressed a button on the button box. A total of 20 fixation point color

changes occurred throughout each run; changes to the fixation cross happened at

random times with respect to wedge stimulus onsets.

Search task. Participants performed a variant of the additional singleton search

task (Theeuwes, 1992). On each trial, participants saw a search array containing 4 items

(item colors were red, RGB = 255,0,0, or green, RGB = 0,255,0, and presented on a black

background, RGB = 0,0,0). The items (2.4º radius) were placed on an imaginary circle 7º

from fixation with 1 item in each visual quadrant (i.e., 45º, 135º, 225º & 315º). Participants

fixated a small, gray dot (.2º) throughout each run. Participants searched for a "target"

(the diamond-shaped item) among distractor items and reported the orientation of the

small line inside (line size = .08º x .94º; orientation = horizontal or vertical) by pressing

one of two buttons. Non-singleton distractors, 'non-targets', had the same color as the

shape-defined target (e.g., green circles). A "singleton distractor" was present on 66.67%

of trials, and was a color singleton (e.g., red circle). Stimuli are illustrated in Figure 1.

Target location (quadrant 1-4), distractor location relative to the target (-90º, +90º, or

+180º), distractor presence (66.67% present), and the orientation of the line inside the

target (horizontal or vertical) were fully counterbalanced within each run, for a total of 72

trials per run. Search set size was held constant at 4 items. The search array was

presented for 2 sec followed by a blank inter-trial interval (equal probability of 2, 3.2, 5, or

8 sec).

We manipulated the degree to which participants were behaviorally captured by

the distractor by changing trial history. In "color variable" runs, the colors of targets and

distractors swapped unpredictably. In "color constant" runs, the colors of targets and

distractors were fixed throughout the run (e.g., the targets and non-singleton distractors

were always green and the singleton distractor was always red). Based on prior work [57,58],

we expected to observe robust behavioral capture by the singleton distractor in the color

variable runs and no behavioral capture in the color constant runs.

Run types were blocked and partially counterbalanced within and across sessions,

such that the order of the 2 conditions would be balanced across the 2 sessions for each

participant. For example, if in Session 1 a participant first received 4 color variable runs

followed by 4 color constant runs (red), then in Session 2 they would first receive 4 color

constant runs (green) followed by 4 color variable runs.

Experiment 1b: Behavior

572   Participants performed the same additional singleton search task described above.

Participants viewed the stimuli on CRT monitors (39 x 29.5 cm) from a distance of ~52

cm. Stimulus parameters (size, color) and trial timing were matched to the fMRI

experiment. Each experimental block contained a total of 48 search trials. Participants

performed a total of 12 blocks of trials (6 color variable, 3 color constant with red targets,

3 color constant with green targets). The color constant and color variable conditions were

blocked and counterbalanced across participants (half of participants received the color

variable condition first).

Magnetic resonance imaging acquisition parameters

582   Scans were performed on a General Electric Discovery MR750 3.0T scanner at

the Keck Center for Functional Magnetic Resonance Imaging on the UCSD campus.

High-resolution ($1mm^3$ isotropic) anatomical images were collected as part of the

retinotopy session. Most participants' (10 of 12) anatomical images were collected with

an Invivo 8-channel head coil; 2 participants' anatomical images were collected with a

Nova Medical 32-channel head coil (NMSC075-32-3GE-MR750). GE's "Phased array

Uniformity Enhancement" (PURE) method was applied to anatomical data acquired using

the 32-channel coil in an attempt to correct inhomogeneities in the signal intensity.

Functional echo-planar imaging (EPI) data were collected with the Nova 32 channel coil

using the GE multiband EPI sequence, using nine axial slices per band and a multiband

factor of eight (total slices = 72; $2 mm^3$ isotropic; 0 mm gap; matrix = 104×104; field of

view = 20.8 cm; repetition time/echo time (TR/ TE) = 800/35 ms, flip angle = 52°; in-plane

acceleration = 1). The initial 16 TRs in each run served as reference images for the

transformation from *k*-space to image space. Un-aliasing and image reconstruction

procedures were performed on local servers and on Amazon Web Service servers using

code adapted from the Stanford Center for Cognitive and Neurobiological Imaging (CNI).

Forward and reverse phase-encoding directions were used during the acquisition of two

short (17 sec) "top-up" datasets. From these images, susceptibility-induced off-resonance

fields were estimated [108] and used to correct signal distortion inherent in EPI sequences,

using FSL top-up [109,110].

Pre-processing

Pre-processing of imaging data closely followed published lab procedures[111] using

FreeSurfer and FSL. We performed cortical surface gray-white matter volumetric

segmentation of the high-resolution anatomical volume from the retinotopy session using

FreeSurfer's "recon-all" procedures[112]. The first volume of the first functional run from

each scanning session was coregistered to this common T1-weighted anatomical image.

To align data from all sessions to the same functional space, we created transformation

matrices with FreeSurfer's registration tools[113], and used these matrices to transform

each four-dimensional functional volume using FSL's FLIRT[114,115]. After cross-session

alignment, motion correction was performed using FSL's McFLIRT (no spatial smoothing,

12 degrees of freedom). Voxelwise signal time-series were normalized via Z-scoring on

a run-by-run basis. Analyses after preprocessing were performed using custom scripts in

MATLAB 2018A.

fMRI analyses: Inverted encoding model

Voxel selection for Decoding ROIs. We defined visual ROI's using data from

the retinotopy session following published lab procedures[7,111]. From these retinotopically-

derived ROI's, we chose the subset of voxels that were spatially selective for the stimuli

used in this task. We thresholded voxels using the independent mapping task data. We

ran a one-way ANOVA with factor Quadrant on each voxel; significant voxels ($p < .05$

uncorrected) were retained for analysis. For the aggregate analyses, we *a priori* created

an early visual cortex ROI (all spatially selective voxels from V1-V3) and a parietal cortex

ROI (all spatially selective voxels from IPS0-3). For individual ROI analyses, we used all

individual retinotopic ROIs for which there were a minimum of 90 spatially selective voxels

per participant: V1, V2, V3, V3AB, hV4, and IPS0.

628   **Inverted Encoding Model.** Following prior work[7,116], we used an inverted

encoding model to estimate spatially-selective tuning functions from multivariate, voxel-

wise activity within each ROI. We assumed that each voxel's activity reflects the weighted

sum of 24 spatially selective channels, each tuned for a different angular location. These

information channels are assumed to reflect the activity of underlying neuronal

populations tuned to each location. We modeled the response profile of each spatial

channel as a half sinusoid raised to the 24th power:

635                             $R = \sin(0.5\theta)^{24}$,

636   where θ is angular location (0–359°, centered on each of the 24 bins from the mapping

637   task), and R is the response of the spatial channel in arbitrary units.

638   Independent training data B_1 were used to estimate weights that approximate the

relative contribution of the 24 spatial channels to the observed response at each voxel.

Let B_1 (m voxels × n_1 observations) be the activity at each voxel for each measurement

in the training set, C_1 (k channels × n_1 observations) be the predicted response of each

spatial channel (determined by the basis functions) for each measurement, and W (m

voxels × k channels) be a weight matrix that characterizes a linear mapping from "channel

space" to "voxel space". The relationship between B_1, C_1, and W can be described by a

general linear model:

646                             $B_1 = WC_1$

647   We obtained the weight matrix through least-squares estimation:

648                     $\widehat{W} = B_1 C_1{}^{T}\left(C_1 C_1{}^{T}\right)^{-1}$

649   In the test stage, we inverted the model to transform the observed test data B_2 (m voxels

650   × n_2 observations) into estimated channel responses, C_2 (k channels × n_2 observations),

651   using the estimated weight matrix, $\widehat{W}$, that we obtained in the training phase:

652                     $\widehat{C_2} = \left(\widehat{W}^{T}\widehat{W}\right)^{-1}\widehat{W}^{T}B_2$

Each estimated channel response function was then circularly shifted to a common center

by aligning the estimated channel responses to the channel tuned for target location.

Model training and testing. We trained the IEM using independent mapping task

data and tested the model using single trial search-task data (average of 4 to 10 TR's

after search array onset). We then shifted and averaged the search task data so that like

trials were aligned (e.g., rotate and average all trials with target-distractor distance of 90).

To reduce idiosyncrasies of only having 1 test set, we iterated the analysis by leaving out

1 block of training data and 1 block of test data, looping through all possible combinations

(e.g., for each 1 block of left out training data, we left out each possible block of test data

on different runs of the loop).

663   **References**

1.   Awh, E., Belopolsky, A. V. & Theeuwes, J. Top-down versus bottom-up attentional control: a failed
theoretical dichotomy. *Trends in Cognitive Sciences* **16**, 437–443 (2012).
2.   Fecteau, J. & Munoz, D. Salience, relevance, and firing: a priority map for target selection. *Trends in*
Cognitive Sciences **10**, 382–390 (2006).
3.   Itti, L. & Koch, C. A saliency-based search mechanism for overt and covert shifts of visual attention.
Vision Research **40**, 1489–1506 (2000).
4.   Serences, J. T. & Yantis, S. Selective visual attention and perceptual coherence. *Trends in Cognitive*
Sciences **10**, 38–45 (2006).
5.   Treisman, A. M. & Gelade, G. A feature-integration theory of attention. *Cognitive Psychology* **12**, 97–
136 (1980).
6.   Wolfe, J. M. Guided Search 2.0 A revised model of visual search. *Psychonomic Bulletin & Review* **1**,
202–238 (1994).
7.   Sprague, T. C. & Serences, J. T. Attention modulates spatial priority maps in the human occipital,
parietal and frontal cortices. *Nature Neuroscience* **16**, 1879–1887 (2013).
8.   Sprague, T. C., Itthipuripat, S., Vo, V. A. & Serences, J. T. Dissociable signatures of visual salience
and behavioral relevance across attentional priority maps in human cortex. *Journal of*
Neurophysiology (2018) doi:10.1152/jn.00059.2018.
9.   Bogler, C., Bode, S. & Haynes, J.-D. Decoding Successive Computational Stages of Saliency
Processing. *Current Biology* **21**, 1667–1671 (2011).
10. Saproo, S. & Serences, J. T. Spatial Attention Improves the Quality of Population Codes in Human
Visual Cortex. *Journal of Neurophysiology* **104**, 885–895 (2010).
11. Serences, J. T. & Yantis, S. Spatially Selective Representations of Voluntary and Stimulus-Driven
Attentional Priority in Human Occipital, Parietal, and Frontal Cortex. *Cerebral Cortex* **17**, 284–293
(2007).
12. Bisley, J. W. & Mirpour, K. The neural instantiation of a priority map. *Current Opinion in Psychology*
29, 108–112 (2019).
13. Theeuwes, J. Goal-driven, stimulus-driven, and history-driven selection. *Current Opinion in*
Psychology **29**, 97–101 (2019).
14. Ipata, A. E., Gee, A. L., Gottlieb, J., Bisley, J. W. & Goldberg, M. E. LIP responses to a popout
stimulus are reduced if it is overtly ignored. *Nature Neuroscience* **9**, 1071–1076 (2006).
15. Ipata, A. E., Gee, A. L., Bisley, J. W. & Goldberg, M. E. Neurons in the lateral intraparietal area
create a priority map by the combination of disparate signals. *Experimental Brain Research* **192**,
479–488 (2009).
16. Geng, J. J., Won, B.-Y. & Carlisle, N. B. Distractor Ignoring: Strategies, Learning, and Passive
Filtering. *Curr Dir Psychol Sci* **28**, 600–606 (2019).
17. Le Pelley, M. E., Mitchell, C. J., Beesley, T., George, D. N. & Wills, A. J. Attention and associative
learning in humans: An integrative review. *Psychological Bulletin* **142**, 1111–1140 (2016).

18. Van Moorselaar, D. & Slagter, H. A. Inhibition in selective attention. *Annals of the New York Academy of Sciences* **1464**, 204–221 (2020).

19. Mazer, J. A. & Gallant, J. L. Goal-Related Activity in V4 during Free Viewing Visual Search. *Neuron* **40**, 1241–1250 (2003).

20. Poltoratski, S., Ling, S., McCormack, D. & Tong, F. Characterizing the effects of feature salience and top-down attention in the early visual system. *Journal of Neurophysiology* **118**, 564–573 (2017).

21. Gandhi, S. P., Heeger, D. J. & Boynton, G. M. Spatial attention affects brain activity in human primary visual cortex. *Proceedings of the National Academy of Sciences* **96**, 3314–3319 (1999).

22. Somers, D. C., Dale, A. M., Seiffert, A. E. & Tootell, R. B. H. Functional MRI reveals spatially specific attentional modulation in human primary visual cortex. *Proceedings of the National Academy of Sciences* **96**, 1663–1668 (1999).

23. Motter, B. C. Focal attention produces spatially selective processing in visual cortical areas V1, V2, and V4 in the presence of competing stimuli. *Journal of Neurophysiology* **70**, 909–919 (1993).

24. Tootell, R. B. H. *et al.* The Retinotopy of Visual Spatial Attention. *Neuron* **21**, 1409–1422 (1998).

25. Ogawa, T. & Komatsu, H. Neuronal dynamics of bottom-up and top-down processes in area V4 of macaque monkeys performing a visual search. *Exp Brain Res* **173**, 1–13 (2006).

26. Zhang, X., Zhaoping, L., Zhou, T. & Fang, F. Neural Activities in V1 Create a Bottom-Up Saliency Map. *Neuron* **73**, 183–192 (2012).

27. Li, Z. A saliency map in primary visual cortex. *Trends in Cognitive Sciences* **6**, 9–16 (2002).

28. Beck, V. M., Hollingworth, A. & Luck, S. J. Simultaneous Control of Attention by Multiple Working Memory Representations. *Psychol Sci* **23**, 887–898 (2012).

29. Olivers, C. N. L., Meijer, F. & Theeuwes, J. Feature-based memory-driven attentional capture: Visual working memory content affects visual attention. *Journal of Experimental Psychology: Human Perception and Performance* **32**, 1243–1265 (2006).

30. Carlisle, N. B., Arita, J. T., Pardo, D. & Woodman, G. F. Attentional Templates in Visual Working Memory. *Journal of Neuroscience* **31**, 9315–9322 (2011).

31. Pashler, H. & Shiu, L. Do images involuntarily trigger search? A test of Pillsbury's hypothesis. *Psychonomic Bulletin & Review* **6**, 445–448 (1999).

32. Downing, P. E. Interactions Between Visual Working Memory and Selective Attention. *Psychol Sci* **11**, 467–473 (2000).

33. Soto, D., Heinke, D., Humphreys, G. W. & Blanco, M. J. Early, Involuntary Top-Down Guidance of Attention From Working Memory. *Journal of Experimental Psychology: Human Perception and Performance* **31**, 248–261 (2005).

34. Arita, J. T., Carlisle, N. B. & Woodman, G. F. Templates for rejection: Configuring attention to ignore task-irrelevant features. *Journal of Experimental Psychology: Human Perception and Performance* **38**, 580–584 (2012).

35. Conci, M., Deichsel, C., Müller, H. J. & Töllner, T. Feature guidance by negative attentional templates depends on search difficulty. *Visual Cognition* **27**, 317–326 (2019).

36. Moher, J. & Egeth, H. E. The ignoring paradox: Cueing distractor features leads first to selection, then to inhibition of to-be-ignored items. *Attention, Perception, & Psychophysics* **74**, 1590–1605 (2012).

37. Reeder, R. R., Olivers, C. N. L. & Pollmann, S. Cortical evidence for negative search templates. *Visual Cognition* **25**, 278–290 (2017).

38. Beck, V. M. & Hollingworth, A. Evidence for negative feature guidance in visual search is explained by spatial recoding. *Journal of Experimental Psychology: Human Perception and Performance* **41**, 1190–1196 (2015).

39. Becker, M. W., Hemsteger, S. & Peltier, C. No templates for rejection: a failure to configure attention to ignore task-irrelevant features. *Visual Cognition* **23**, 1150–1167 (2015).

40. Failing, M., Feldmann-Wüstefeld, T., Wang, B., Olivers, C. & Theeuwes, J. Statistical regularities induce spatial as well as feature-specific suppression. *Journal of Experimental Psychology: Human Perception and Performance* **45**, 1291–1303 (2019).

41. Wang, B. & Theeuwes, J. Statistical regularities modulate attentional capture. *Journal of Experimental Psychology: Human Perception and Performance* **44**, 13–17 (2018).

42. Won, B.-Y. & Geng, J. J. Passive exposure attenuates distraction during visual search. *Journal of Experimental Psychology: General* (2020) doi:10.1037/xge0000760.

43. Turatto, M. & Pascucci, D. Short-term and long-term plasticity in the visual-attention system: Evidence from habituation of attentional capture. *Neurobiology of Learning and Memory* **130**, 159–169 (2016).

44. Turatto, M., Bonetti, F., Pascucci, D. & Chelazzi, L. Desensitizing the attention system to distraction while idling: A new latent learning phenomenon in the visual attention domain. *Journal of Experimental Psychology: General* **147**, 1827–1850 (2018).

45. Engel, S. A. & Furmanski, C. S. Selective Adaptation to Color Contrast in Human Primary Visual Cortex. *J. Neurosci.* **21**, 3949–3954 (2001).

46. Gardner, J. L. *et al.* Contrast Adaptation and Representation in Human Early Visual Cortex. *Neuron* **47**, 607–620 (2005).

47. Kristjansson, A., Vuilleumier, P., Schwartz, S., Macaluso, E. & Driver, J. Neural Basis for Priming of Pop-Out during Visual Search Revealed with fMRI. *Cerebral Cortex* **17**, 1612–1624 (2007).

48. Grill-Spector, K. & Malach, R. fMR-adaptation: a tool for studying the functional properties of human cortical neurons. *Acta Psychologica* **107**, 293–321 (2001).

49. Failing, M., Wang, B. & Theeuwes, J. Spatial suppression due to statistical regularities is driven by distractor suppression not by target activation. *Atten Percept Psychophys* **81**, 1405–1414 (2019).

50. Geyer, T., Müller, H. J. & Krummenacher, J. Cross-trial priming in visual search for singleton conjunction targets: Role of repeated target and distractor features. *Perception & Psychophysics* **68**, 736–749 (2006).

51. Won, B.-Y., Forloines, M., Zhou, Z. & Geng, J. J. Changes in visual cortical processing attenuate singleton distraction during visual search. *Cortex* (in press).

52. van Moorselaar, D. & Slagter, H. A. Learning What Is Irrelevant or Relevant: Expectations Facilitate Distractor Inhibition and Target Facilitation through Distinct Neural Mechanisms. *J. Neurosci.* **39**, 6953–6967 (2019).

53. Turk-Browne, N. B., Scholl, B. J., Chun, M. M. & Johnson, M. K. Neural Evidence of Statistical Learning: Efficient Detection of Visual Regularities Without Awareness. *Journal of Cognitive Neuroscience* **21**, 1934–1945 (2009).

54. Schapiro, A. C., Gregory, E., Landau, B., McCloskey, M. & Turk-Browne, N. B. The Necessity of the Medial Temporal Lobe for Statistical Learning. *Journal of Cognitive Neuroscience* **26**, 1736–1747 (2014).

55. Theeuwes, J. Perceptual selectivity for color and form. *Perception & Psychophysics* **51**, 599–606 (1992).

56. Gaspelin, N., Leonard, C. J. & Luck, S. J. Direct Evidence for Active Suppression of Salient-but-Irrelevant Sensory Inputs. *Psychol Sci* **26**, 1740–1750 (2015).

57. Gaspelin, N., Leonard, C. J. & Luck, S. J. Suppression of overt attentional capture by salient-but-irrelevant color singletons. *Attention, Perception, & Psychophysics* **79**, 45–62 (2017).

58. Vatterott, D. B. & Vecera, S. P. Experience-dependent attentional tuning of distractor rejection. *Psychon Bull Rev* **19**, 871–878 (2012).

59. Goschy, H., Bakos, S., Müller, H. J. & Zehetleitner, M. Probability cueing of distractor locations: both intertrial facilitation and statistical learning mediate interference reduction. *Front. Psychol.* **5**, (2014).

60. Turatto, M. & Galfano, G. Attentional capture by color without any relevant attentional set. *Perception & Psychophysics* **63**, 286–297 (2001).

61. Mounts, J. R. W. Evidence for suppressive mechanisms in attentional selection: Feature singletons produce inhibitory surrounds. *Perception & Psychophysics* **62**, 969–983 (2000).

62. Kamitani, Y. & Tong, F. Decoding the visual and subjective contents of the human brain. *Nat Neurosci* **8**, 679–685 (2005).

63. Serences, J. T. & Saproo, S. Computational advances towards linking BOLD and behavior. *Neuropsychologia* **50**, 435–446 (2012).

64. Norman, K. A., Polyn, S. M., Detre, G. J. & Haxby, J. V. Beyond mind-reading: multi-voxel pattern analysis of fMRI data. *Trends in Cognitive Sciences* **10**, 424–430 (2006).

65. Tong, F. & Pratte, M. S. Decoding Patterns of Human Brain Activity. *Annu. Rev. Psychol.* **63**, 483–
509 (2012).
66. Cox, D. D. & Savoy, R. L. Functional magnetic resonance imaging (fMRI) "brain reading": detecting
and classifying distributed patterns of fMRI activity in human visual cortex. *NeuroImage* **19**, 261–270
(2003).
67. Haynes, J.-D. & Rees, G. Predicting the orientation of invisible stimuli from activity in human primary
visual cortex. *Nat Neurosci* **8**, 686–691 (2005).
68. Emrich, S. M., Riggall, A. C., LaRocque, J. J. & Postle, B. R. Distributed Patterns of Activity in
Sensory Cortex Reflect the Precision of Multiple Items Maintained in Visual Short-Term Memory.
Journal of Neuroscience **33**, 6516–6523 (2013).
69. Lewis-Peacock, J. A. & Postle, B. R. Decoding the internal focus of attention. *Neuropsychologia* **50**,
470–478 (2012).
70. Sprague, T. C., Boynton, G. M. & Serences, J. T. The Importance of Considering Model Choices
When Interpreting Results in Computational Neuroimaging. *eNeuro* **6**, ENEURO.0196-19.2019
(2019).
71. Sprague, T. C. *et al.* Inverted Encoding Models Assay Population-Level Stimulus Representations,
Not Single-Unit Neural Tuning. *eNeuro* **5**, ENEURO.0098-18.2018 (2018).
72. van Bergen, R. S., Ji Ma, W., Pratte, M. S. & Jehee, J. F. M. Sensory uncertainty decoded from
visual cortex predicts behavior. *Nat Neurosci* **18**, 1728–1730 (2015).
73. van Bergen, R. S. & Jehee, J. F. M. Probabilistic Representation in Human Visual Cortex Reflects
Uncertainty in Serial Decisions. *J. Neurosci.* **39**, 8164–8176 (2019).
74. Lawson, C. L. & Hanson, R. J. Chapter 23. in *Solving Least-Squares Problems* (Prentice-Hall, 1974).
75. Carandini, M. & Heeger, D. J. Normalization as a canonical neural computation. *Nat Rev Neurosci*
13, 51–62 (2012).
76. Solomon, S. G. & Kohn, A. Moving Sensory Adaptation beyond Suppressive Effects in Single
Neurons. *Current Biology* **24**, R1012–R1022 (2014).
77. Karni, A. & Sagi, D. Where practice makes perfect in texture discrimination: evidence for primary
visual cortex plasticity. *Proceedings of the National Academy of Sciences* **88**, 4966–4970 (1991).
78. Schwartz, S., Maquet, P. & Frith, C. Neural correlates of perceptual learning: A functional MRI study
of visual texture discrimination. *Proceedings of the National Academy of Sciences* **99**, 17137–17142
(2002).
79. Jehee, J. F. M., Ling, S., Swisher, J. D., van Bergen, R. S. & Tong, F. Perceptual Learning
Selectively Refines Orientation Representations in Early Visual Cortex. *Journal of Neuroscience* **32**,
16747–16753 (2012).
80. Feldmann-Wüstefeld, T. & Schubö, A. Intertrial priming due to distractor repetition is eliminated in
homogeneous contexts. *Atten Percept Psychophys* **78**, 1935–1947 (2016).
81. Reavis, E. A., Frank, S. M., Greenlee, M. W. & Tse, P. U. Neural correlates of context-dependent
feature conjunction learning in visual search tasks. *Hum Brain Mapp* **37**, 2319–2330 (2016).
82. Sawaki, R. & Luck, S. J. Capture versus suppression of attention by salient singletons:
Electrophysiological evidence for an automatic attend-to-me signal. *Attention, Perception, &*
Psychophysics **72**, 1455–1470 (2010).
83. Gaspar, J. M. & McDonald, J. J. Suppression of Salient Objects Prevents Distraction in Visual
Search. *Journal of Neuroscience* **34**, 5658–5666 (2014).
84. Hickey, C., Di Lollo, V. & McDonald, J. J. Electrophysiological Indices of Target and Distractor
Processing in Visual Search. *Journal of Cognitive Neuroscience* **21**, 760–775 (2009).
85. Moher, J., Lakshmanan, B. M., Egeth, H. E. & Ewen, J. B. Inhibition Drives Early Feature-Based
Attention. *Psychological Science* **25**, 315–324 (2014).
86. Zhang, W. & Luck, S. J. Feature-based attention modulates feedforward visual processing. *Nat*
Neurosci **12**, 24–25 (2009).
87. Serences, J. T., Yantis, S., Culberson, A. & Awh, E. Preparatory Activity in Visual Cortex Indexes
Distractor Suppression During Covert Spatial Orienting. *Journal of Neurophysiology* **92**, 3538–3545
(2004).

88. Heuer, A. & Schubö, A. Cueing distraction: electrophysiological evidence for anticipatory active
suppression of distractor location. *Psychological Research* (2019) doi:10.1007/s00426-019-01211-4.
89. Hickey, C. & Peelen, M. V. Neural Mechanisms of Incentive Salience in Naturalistic Human Vision.
Neuron **85**, 512–518 (2015).
90. Itthipuripat, S., Vo, V. A., Sprague, T. C. & Serences, J. T. Value-driven attentional capture enhances
distractor representations in early visual cortex. *PLoS Biol* **17**, e3000186 (2019).
91. Kim, H. & Anderson, B. A. Dissociable neural mechanisms underlie value-driven and selection-driven
attentional capture. *Brain Research* **1708**, 109–115 (2019).
92. Serences, J. T. Value-Based Modulations in Human Visual Cortex. *Neuron* **60**, 1169–1181 (2008).
93. MacLean, M. H. & Giesbrecht, B. Neural evidence reveals the rapid effects of reward history on
selective attention. *Brain Research* **1606**, 86–94 (2015).
94. Stanisor, L., van der Togt, C., Pennartz, C. M. A. & Roelfsema, P. R. A unified selection signal for
attention and reward in primary visual cortex. *Proceedings of the National Academy of Sciences* **110**,
9136–9141 (2013).
95. Chelazzi, L. *et al.* Altering Spatial Priority Maps via Reward-Based Learning. *Journal of Neuroscience*
34, 8594–8604 (2014).
96. Anderson, B. A. & Kim, H. On the relationship between value-driven and stimulus-driven attentional
capture. *Atten Percept Psychophys* **81**, 607–613 (2019).
97. Maunsell, J. H. R. Neuronal representations of cognitive state: reward or attention? *Trends in
Cognitive Sciences* **8**, 261–265 (2004).
98. Hickey, C. & Peelen, M. V. Reward Selectively Modulates the Lingering Neural Representation of
Recently Attended Objects in Natural Scenes. *J. Neurosci.* **37**, 7297–7304 (2017).
99. Kastner, S., Pinsk, M. A., De Weerd, P., Desimone, R. & Ungerleider, L. G. Increased Activity in
Human Visual Cortex during Directed Attention in the Absence of Visual Stimulation. *Neuron* **22**,
751–761 (1999).
100.   Kastner, S. Mechanisms of Directed Attention in the Human Extrastriate Cortex as Revealed by
Functional MRI. *Science* **282**, 108–111 (1998).
101.   Foster, J. J., Bsales, E. M., Jaffe, R. J. & Awh, E. Alpha-Band Activity Reveals Spontaneous
Representations of Spatial Position in Visual Working Memory. *Current Biology* **27**, 3216-3223.e6
(2017).
102.   Maljkovic, V. & Nakayama, K. Priming of pop-out: I. Role of features. *Memory & Cognition* **22**,
657–672 (1994).
103.   Foster, J. J., Sutterer, D. W., Serences, J. T., Vogel, E. K. & Awh, E. Alpha-Band Oscillations
Enable Spatially and Temporally Resolved Tracking of Covert Spatial Attention. *Psychological
Science* **28**, 929–941 (2017).
104.   Engel, S. A. *et al.* fMRI of human visual cortex. *Nature* **369**, 525–525 (1994).
105.   Swisher, J. D., Halko, M. A., Merabet, L. B., McMains, S. A. & Somers, D. C. Visual Topography
of Human Intraparietal Sulcus. *Journal of Neuroscience* **27**, 5326–5337 (2007).
106.   Brainard, D. H. The Psychophysics Toolbox. *Spat Vis* **10**, 433–436 (1997).
107.   Pelli, D. G. The VideoToolbox software for visual psychophysics: transforming numbers into
movies. *Spatial Vision* **10**, 437–442 (1997).
108.   Andersson, J. L. R., Skare, S. & Ashburner, J. How to correct susceptibility distortions in spin-
echo echo-planar images: application to diffusion tensor imaging. *NeuroImage* **20**, 870–888 (2003).
109.   Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W. & Smith, S. M. FSL.
NeuroImage **62**, 782–790 (2012).
110.   Smith, S. M. *et al.* Advances in functional and structural MR image analysis and implementation
as FSL. *NeuroImage* **23**, S208–S219 (2004).
111.   Rademaker, R. L., Chunharas, C. & Serences, J. T. Coexisting representations of sensory and
mnemonic information in human visual cortex. *Nat Neurosci* **22**, 1336–1344 (2019).
112.   Dale, A. M., Fischl, B. & Sereno, M. I. Cortical Surface-Based Analysis. *NeuroImage* **9**, 179–194
(1999).
113.   Greve, D. N. & Fischl, B. Accurate and robust brain image alignment using boundary-based
registration. *NeuroImage* **48**, 63–72 (2009).

114.   Jenkinson, M. & Smith, S. A global optimisation method for robust affine registration of brain
913   images. *Medical Image Analysis* **5**, 143–156 (2001).
914   115.   Jenkinson, M., Bannister, P., Brady, M. & Smith, S. Improved Optimization for the Robust and
915   Accurate Linear Registration and Motion Correction of Brain Images. *NeuroImage* **17**, 825–841
916   (2002).
917   116.   Brouwer, G. J. & Heeger, D. J. Decoding and Reconstructing Color from Responses in Human
918   Visual Cortex. *Journal of Neuroscience* **29**, 13992–14003 (2009).
919
920