1 **Abbreviated title:** HISTORY MODULATES DISTRACTORS
2
3
4
5 **History modulates early sensory processing of salient distractors**
6

7 Kirsten C.S. Adam[1] & John T. Serences[1,2,3]
8
9 [1] Department of Psychology, *University of California San Diego*
10 [2] Institute for Neural Computation*, University of California San Diego*
11 [3] Neurosciences Graduate Program, *University of California San Diego*

12
13 **Word count (abstract):** 237
14 **Word count (not including abstract, methods, references, figure legends):** 5,471
15 **Word count (methods):** 2,463
16 **Tables:** 0
17 **Figures:** 6
18
19 **Keywords:** visual search; fMRI; priority maps; attentional selection; salience
20

21 **Contributions:** K.A. collected data, performed analyses, and drafted the manuscript.
22 Both authors designed the study and revised the manuscript.
23
24 **Funding:** Research was supported by National Eye Institute grant R01 EY025872
25 (J.S.), National Institute of Mental Health grant T32-MH020002 (K.A.), and National Eye
26 Institute grant T32-EY020503 (K.A.).
27
28 **Data availability:** Data will be made freely available online on the Open Science
29 Framework at https://osf.io/wrdvz/ upon acceptance for publication.
30
31 **Acknowledgements:** We thank Rosanne Rademaker for scanning assistance and for
32 sharing custom analysis code. We thank Nicole Rangan and Matteo d'Amico for
33 assistance with behavioral data collection, and we thank Ed Awh for helpful comments
34 on earlier drafts of the manuscript.
35
Conflicts of interest: none

Correspondence to:
Kirsten C. S. Adam
University of California San Diego
9500 Gilman Drive, Mail Code: 0109
La Jolla, CA 92093-0109
kadam@ucsd.edu

Abstract

To find important objects, we must focus on our goals, ignore distractions, and take our changing environment into account. This is formalized in models of visual search whereby goal-driven, stimulus-driven and history-driven factors are integrated into a priority map that guides attention. Stimulus history robustly influences where attention is allocated even when the physical stimulus is the same: when a salient distractor is repeated over time, it captures attention less effectively. A key open question is how we come to ignore salient distractors when they are repeated. Goal-driven accounts propose that we use an active, expectation-driven mechanism to attenuate the distractor signal (e.g., predictive coding), whereas stimulus-driven accounts propose that the distractor signal is attenuated due to passive changes to neural activity and inter-item competition (e.g., adaptation). To test these competing accounts, we measured item-specific fMRI responses in human visual cortex during a visual search task where trial history was manipulated (colors unpredictably switched or were repeated). Consistent with a stimulus-driven account of history-based distractor suppression, we found that repeated distractors were suppressed starting in V1, and distractor suppression did not increase in later visual areas. In contrast, we observed signatures of goal-driven target enhancement that were absent in V1, increased across visual areas, and were not modulated by stimulus history. Our data suggest that stimulus history does not alter goal-driven expectations, but rather modulates canonically stimulus-driven sensory responses to contribute to a temporally-integrated representation of priority.

75   **Significance Statement**

Visual search refers to our ability to find what we are looking for in a cluttered visual world

(e.g., finding your keys). To perform visual search, we must integrate information about

our goals (e.g., 'find the red key-chain'), the environment (e.g., salient items capture your

attention), and changes to the environment (i.e., stimulus history). Although stimulus

history impacts behavior, the neural mechanisms that mediate history-driven effects

remain debated. Here, we leveraged fMRI and multivariate analysis techniques to

measure history-driven changes to the neural representation of items during visual

search. We found that stimulus history influenced the representation of a salient 'pop-out'

distractor starting in V1, suggesting that stimulus history operates via modulations in early

sensory processing rather than goal-driven expectations.

<div style="text-align:center">

Introduction

</div>

At any moment we can selectively attend only a small fraction of available perceptual inputs, so we need to select a subset of information and discard irrelevant information. This capacity limit poses a significant computational challenge, particularly given that perceptual inputs constantly change as we move through the world. Given our constantly changing surroundings, one particularly useful computational strategy is to discard information that stays the same over time. For example, when searching for sea glass at the beach, irrelevant but salient information (e.g., a red plastic bottle-cap) may grab our attention. But, if we repeatedly encounter the same irrelevant information (e.g., the beach is littered with red bottle-caps), then we can come to ignore initially salient distractors. Extensive evidence suggests that stimulus history robustly modulates behavior: An initially salient color distractor no longer captures our attention after we have seen it many times (Geyer et al., 2006; Vatterott and Vecera, 2012; Geng, 2014; Gaspelin et al., 2015, 2017; Wang and Theeuwes, 2018a; Failing et al., 2019a; Geng et al., 2019; Van Moorselaar and Slagter, 2020). Yet, debate persists as to how this history-driven behavioral modulation is achieved: Do we use an active, expectation-based mechanism to suppress the salient distractor signal when it is repeated (e.g., predictive coding), or, is the distractor signal passively attenuated because of changes to neural activity with repetition (e.g., adaptation)? Here, we leverage item-specific, neural estimates of priority, to test competing hypotheses of how stimulus history alters attentional priority.

Models of visual search hypothesize that we integrate information about what is relevant *(goal-driven* or *'top-down' factors)*, what is salient given local image statistics *(stimulus-driven* or *'bottom-up' factors)*, and what has occurred in the past (*history-driven factors*) via an integrated, topographically organized "priority map" (Treisman and Gelade, 1980; Wolfe, 1994; Itti and Koch, 2000; Fecteau and Munoz, 2006; Serences and Yantis, 2006; Awh et al., 2012). Note, some work uses the terms 'saliency' and 'priority' interchangeably, whereas other work uses these terms to refer to distinct concepts. Here, we use 'priority' to refer to the integration of goal-driven and stimulus-driven task factors, and 'saliency' to refer to strictly image-computable, stimulus-driven task factors (Serences and Yantis, 2006). Although both stimulus-driven and goal-driven information is

represented to some extent in many cortical regions (Silver et al., 2005; Serences and

Yantis, 2006, 2007; Saproo and Serences, 2010; Bogler et al., 2011; Sprague and

Serences, 2013; Sprague et al., 2018b), areas of parietal cortex (e.g., LIP, IPS) are

hypothesized to be ideal candidates for integrating information about stimulus-driven

sensory inputs from occipital cortex and information about goals from pre-frontal cortex

(Ipata et al., 2006, 2009; Bisley and Mirpour, 2019; Theeuwes, 2019).

History-driven effects have only recently been added to models of visual search,

in part because these effects do not wholly fit within a 'goal-driven' versus 'stimulus-

driven' dichotomous framework (Awh et al., 2012; Geng, 2014; Le Pelley et al., 2016;

Geng et al., 2019; Van Moorselaar and Slagter, 2020). Rather, history-driven effects rely

on both current sensory input and prior experiences. Thus, debate persists about whether

stimulus history influences attentional priority by co-opting elements of stimulus-driven

computations, goal-driven computations, or another pathway altogether (Gaspelin et al.,

2015; Gaspelin and Luck, 2018; Wang and Theeuwes, 2018b; Geng et al., 2019;

Theeuwes, 2019; Van Moorselaar and Slagter, 2020).

Goal-driven accounts propose that we exploit voluntary selection mechanisms to

incorporate information about history-driven task factors into priority maps. Earlier work

has shown how voluntary attention may be used to enhance the target item relative to the

other distractor items: when looking for a particular target, one may form a "template" of

that feature and use this template to voluntarily up-regulate relevant portions of the visual

field (Pashler and Shiu, 1999; Downing, 2000; Soto et al., 2005; Olivers et al., 2006;

Carlisle et al., 2011; Beck et al., 2012). Similar voluntary selection mechanisms might

likewise be used to suppress a distractor signal when it is repeated, either directly or

indirectly. First, distractor suppression could arise *indirectly* because of predictive coding

and biased competition (Desimone and Duncan, 1995; Spratling, 2008; Summerfield and

de Lange, 2014). In this account of history-driven distractor suppression, participants

could use their expectations about the upcoming, repeated stimulus futures to more

strongly enhance the target and, consequently, the competing distractor would be

automatically suppressed due to inter-item competition (Spratling, 2008). Second,

distractor suppression could arise *directly*, via a top-down suppression signal for a

specific feature. This direct suppression signal is sometimes referred to as a "negative

search template" (Arita et al., 2012; Moher and Egeth, 2012; Reeder et al., 2017; Conci

et al., 2019, but see: Beck and Hollingworth, 2015; Becker et al., 2015). Critically, in either

the direct or indirect case, we would expect to observe a similar neural signature at the

level of population codes measured with fMRI for both of these goal-driven accounts.

Specifically, we should observe that distractor suppression effects are greater in later

visual areas (e.g., IPS0) than in earlier visual areas (e.g., V1), consistent with a goal-

driven signal (e.g., Silver et al., 2005; Sprague et al., 2018b). In the case of the predictive

coding / biased competition model (Spratling, 2008), we would further predict that target

enhancement and distractor suppression should be yoked, whereby greater distractor

suppression will be accompanied by greater target enhancement as arrays are repeated.

In contrast, stimulus-driven accounts instead suggest that history-driven distractor

suppression can arise from passive changes to neural activity as stimuli are presented

over time (Turatto and Pascucci, 2016; Turatto et al., 2018; Wang and Theeuwes, 2018a;

Failing et al., 2019a; Won and Geng, 2020). For example, some work suggests that even

passive, task-irrelevant exposure to a particular feature may be sufficient to alter

attentional guidance and search behaviors (Engel and Furmanski, 2001; Grill-Spector and

Malach, 2001; Gardner et al., 2005; Kristjansson et al., 2007; Turatto and Pascucci, 2016;

Turatto et al., 2018; Won and Geng, 2020). Although the effects of adaptation for single

stimuli are well understood, how adaptation affects saliency in multi-item displays has

only recently been considered. Yet, emerging evidence suggests that altered firing rates

from simple sensory adaptation effects could alter inter-item competition (Solomon and

Kohn, 2014) which, in turn, could alter stimulus saliency and behavior (Treisman and

Gelade, 1980; Wolfe, 1994; Itti and Koch, 2000; Li, 2002; Zhang et al., 2012).

Here, we tackle the debate about history-driven distractor suppression from a new

angle: we measured neural activity via fMRI in human subjects performing a visual search

task in order to estimate item-specific changes to neural priority across the visual stream.

Critically, we manipulated trial history so that we could compare neural responses to

physically identical displays (e.g., green target, red singleton distractor) as a function of

trial history (i.e., whether the colors of preceding displays repeated or varied).

195   **Materials and Methods**

Participants

Experiment 1a: MRI experiment. Healthy volunteers (n = 12; 9 female; mean age

= 25.3 years [SD = 2.5, min = 21, max = 30]; all right-handed; normal or corrected-to-

normal visual acuity; normal color vision) participated in three ~2 hour sessions at the

Keck Center for fMRI on the University of California San Diego (UCSD) campus, and were

compensated $20/hr. Procedures were approved by the UCSD Institutional Review

Board, and participants provided written informed consent. Sample size was determined

by a power analysis on data from Sprague et al.(Sprague et al., 2018b) where achieved

power (1-ß) to detect a within-subjects attention modulation using an inverted encoding

model was 83% (across 10 ROIs) with n=8. We planned for n =11 to achieve estimated

90% power (rounded up to n = 12 to satisfy our counter-balancing criteria).

Experiment 1b: Behavior only. Healthy volunteers (n = 24; 21 female; mean age

= 19.8 years [SD = 1.5, min = 18, max = 24]; normal or corrected-to-normal visual acuity;

normal color vision; handedness not recorded) participated in one 1.5-hour experimental

session in the Department of Psychology on the UCSD campus, and were compensated

with course credit. There were no duplicate participants across experiments. Procedures

were approved by the UCSD IRB, and all participants provided written informed consent.

A sample size of 24 was chosen *a priori* based on published papers(Gaspelin et al., 2015).

Session procedures

Exp 1a, Retinotopy session. Participants completed one retinotopic mapping

session prior to participation in the experimental sessions, following standard

procedures(Engel et al., 1994; Swisher et al., 2007). Some participants had already

completed a retinotopy session as part of prior studies in the lab; this session was used

if available. Retinotopy data were used to identify retinotopic ROIs (V1-V3, V3AB, hV4,

VO1, VO2, LO1, LO2, TO1, TO2, IPS0-4). During each session, participants viewed

flickering checkerboards. On meridian mapping runs, a "bowtie" checkerboard alternated

between the horizontal and vertical meridians. On polar angle mapping runs, a

checkerboard wedge slowly rotated in a clockwise or counterclockwise direction. On

eccentricity mapping runs, a "donut" checkerboard began near fixation and its radius

slowly expanded outward. A high-resolution anatomical scan was collected for functional

alignment. Anatomical and functional retinotopy analyses were performed using custom

code calling existing FreeSurfer and FSL functions. Functional retinotopy data were used

to draw ROIs, but only voxels that were also visually responsive to experimental localizers

(below) were analyzed further.

Exp 1a, Main MRI session. Participants completed two experimental sessions. In

each session, they completed 2 runs of the item position localizer, 4 runs of the spatial

location localizer, and 8 runs of the search task (4 runs "color variable", 4 runs "color

constant"). When time allowed, extra localizer runs were collected. Some participants also

took part in an unrelated study in which additional localizers were collected. Across the

two sessions, participants completed 16 runs of visual search (M = 1,1152 trials, SD = 0),

an average of 11.2 runs of the spatial location localizer (M = 1,072 trials, SD = 298, min

= 768, max = 1,536), and an average of 4.3 item position localizer runs (M = 381 trials,

SD = 43, min = 352, max = 440).

Exp 1b. Participants completed 12 blocks of the search task (6 blocks "color

variable", 6 blocks "color constant").

Stimuli and task procedures

Experiment 1a: MRI

Stimuli were projected on a 21.5 x 16 cm screen mounted inside the scanner bore.

The screen was viewed from a distance of ~47 cm through a mirror. Stimuli were

generated in MATLAB (2017b, The MathWorks, Natick, MA) with the Psychophysics

toolbox (Brainard, 1997; Pelli, 1997) on a laptop running Ubuntu. Responses were

collected with a 4-button button box. Stimuli for each task are shown in Figure 1.

Item position localizer. Participants viewed reversing checkerboards (4 Hz

flicker) which occupied the locations of the items in the search task (each item radius =

2.5º placed on an imaginary circle 7º from fixation, with one item in each of the 4

quadrants on the circle). Participants were shown items on 2 alternating diagonals (i.e.,

items in Quadrants 1 and 3 and then Quadrants 2 and 4) for 3 sec each. There were 88

stimulus presentations within each run. Participants were instructed to attend to both

items, and to press a button if either item briefly dimmed. A brief (250 ms) dimming

occurred on 1 of the 2 items for 25% of stimulus presentations.

Spatial location localizer. Participants viewed a reversing checkerboard wedge

(flicker = 4 Hz; white & black checkerboards) at one of 24 positions. Checkerboard

positions were equally spaced along a circle with radius = 7º, and wedges were non-

overlapping (i.e., each wedge's width along the circle filled a 15º arc and was ~5º of visual

angle in height). The wedge stayed at one position for 3 sec, then moved to a different

position (with the constraint that back-to-back positions must be in different quadrants).

There were 96 wedge presentations within each run. Participants were instructed to

attend to the fixation point; if the fixation point's color changed (increase or decrease in

brightness), they pressed a button on the button box. A total of 20 fixation point color

changes occurred throughout each run; changes to the fixation cross happened at

random times with respect to wedge stimulus onsets. We chose to have participants

attend fixation, rather than the stimulus position, during the localizer task to reduce

contamination of eye movements on any observed decoding effects (Mostert et al., 2018).

Generally, systematic eye movement biases are absent or greatly attenuated when

participants attend fixation and ignore the peripheral stimulus. With this cross-task training

and testing scheme, we would expect that decoding should impaired for all 4 items if

participants moved their eyes in the visual search task. Thus, this training-testing scheme

protects against the possibility that item-specific target enhancement or distractor

suppression effects could be driven by eye movements to a particular item in the display.

Search task. Participants performed a variant of the additional singleton search

task (Theeuwes, 1992). On each trial, participants saw a search array containing 4 items

(item colors were red, RGB = 255,0,0, or green, RGB = 0,255,0, and presented on a black

background, RGB = 0,0,0). The items (2.4º radius) were placed on an imaginary circle 7º

from fixation with 1 item in each visual quadrant (i.e., 45º, 135º, 225º & 315º). Participants

fixated a small, gray dot (.2º) throughout each run. Participants searched for a "target"

(the diamond-shaped item) among distractor items and reported the orientation of the

small line inside (line size = .08º x .94º; orientation = horizontal or vertical) by pressing

one of two buttons. Non-singleton distractors, 'non-targets', had the same color as the

shape-defined target (e.g., green circles). A "singleton distractor" was present on 66.67%

of trials, and was a color singleton (e.g., red circle). Stimuli are illustrated in Figure 1.

Target location (quadrant 1-4), distractor location relative to the target (-90º, +90º, or

+180º), distractor presence (66.67% present), and the orientation of the line inside the

target (horizontal or vertical) were fully counterbalanced within each run, for a total of 72

trials per run. Search set size was held constant at 4 items. The search array was

presented for 2 sec followed by a blank inter-trial interval (equal probability of 2, 3.2, 5, or

8 sec).

We manipulated the degree to which participants were behaviorally captured by

the distractor by changing trial history. In "color variable" runs, the colors of targets and

distractors swapped unpredictably. In "color constant" runs, the colors of targets and

distractors were fixed throughout the run (e.g., the targets and non-singleton distractors

were always green and the singleton distractor was always red). Based on prior work

(Vatterott and Vecera, 2012; Gaspelin et al., 2017), we expected to observe robust

behavioral capture by the singleton distractor in the color variable runs and no behavioral

capture in the color constant runs.

Run types were blocked and partially counterbalanced within and across sessions,

such that the order of the 2 conditions would be balanced across the 2 sessions for each

participant. For example, if in Session 1 a participant first received 4 color variable runs

followed by 4 color constant runs (red), then in Session 2 they would first receive 4 color

constant runs (green) followed by 4 color variable runs.

Experiment 1b: Behavior

Participants performed the same additional singleton search task described above.

Participants viewed the stimuli on CRT monitors (39 x 29.5 cm) from a distance of ~52

cm. Stimulus parameters (size, color) and trial timing were matched to the fMRI

experiment. Each experimental block contained a total of 48 search trials. Participants

performed a total of 12 blocks of trials (6 color variable, 3 color constant with red targets,

3 color constant with green targets). The color constant and color variable conditions were

blocked and counterbalanced across participants (half of participants received the color

variable condition first).

Magnetic resonance imaging acquisition parameters

319   Scans were performed on a General Electric Discovery MR750 3.0T scanner at

the Keck Center for Functional Magnetic Resonance Imaging on the UCSD campus.

High-resolution (1mm^3 isotropic) anatomical images were collected as part of the

retinotopy session. Most participants' (10 of 12) anatomical images were collected with

an Invivo 8-channel head coil; 2 participants' anatomical images were collected with a

Nova Medical 32-channel head coil (NMSC075-32-3GE-MR750). GE's "Phased array

Uniformity Enhancement" (PURE) method was applied to anatomical data acquired using

the 32-channel coil in an attempt to correct inhomogeneities in the signal intensity.

Functional echo-planar imaging (EPI) data were collected with the Nova 32 channel coil

using the GE multiband EPI sequence, using nine axial slices per band and a multiband

factor of eight (total slices = 72; 2 mm^3 isotropic; 0 mm gap; matrix = 104 × 104; field of

view = 20.8 cm; repetition time/echo time (TR/ TE) = 800/35 ms, flip angle = 52°; in-plane

acceleration = 1). The initial 16 TRs in each run served as reference images for the

transformation from *k*-space to image space. Un-aliasing and image reconstruction

procedures were performed on local servers and on Amazon Web Service servers using

code adapted from the Stanford Center for Cognitive and Neurobiological Imaging (CNI).

Forward and reverse phase-encoding directions were used during the acquisition of two

short (17 sec) "top-up" datasets. From these images, susceptibility-induced off-resonance

fields were estimated (Andersson et al., 2003) and used to correct signal distortion

inherent in EPI sequences, using FSL top-up (Smith et al., 2004; Jenkinson et al., 2012).

Pre-processing

341   Pre-processing of imaging data closely followed published lab procedures

(Rademaker et al., 2019) using FreeSurfer and FSL. We performed cortical surface gray-

white matter volumetric segmentation of the high-resolution anatomical volume from the

retinotopy session using FreeSurfer's "recon-all" procedures (Dale et al., 1999). The first

volume of the first functional run from each scanning session was coregistered to this

common T1-weighted anatomical image. To align data from all sessions to the same

functional space, we created transformation matrices with FreeSurfer's registration tools

(Greve and Fischl, 2009), and used these matrices to transform each four-dimensional

functional volume using FSL's FLIRT (Jenkinson and Smith, 2001; Jenkinson et al.,

2002). After cross-session alignment, motion correction was performed using FSL's

McFLIRT (no spatial smoothing, 12 degrees of freedom). Voxelwise signal time-series

were normalized via Z-scoring on a run-by-run basis. Analyses after preprocessing were

performed using custom scripts in MATLAB 2018A.

fMRI analyses: Inverted encoding model

Voxel selection for Decoding ROIs. We defined visual ROI's using data from

the retinotopy session following published lab procedures (Sprague and Serences, 2013;

Rademaker et al., 2019). From these retinotopically-derived ROI's, we chose the subset

of voxels that were spatially selective for the stimuli used in this task. We thresholded

voxels using the independent mapping task data. We ran a one-way ANOVA with factor

Quadrant on each voxel; significant voxels ($p < .05$ uncorrected) were retained for

analysis. For the aggregate analyses, we *a priori* created an early visual cortex ROI (all

spatially selective voxels from V1-V3) and a parietal cortex ROI (all spatially selective

voxels from IPS0-3). For individual ROI analyses, we used all individual retinotopic ROIs

for which there were a minimum of 90 spatially selective voxels per participant: V1, V2,

V3, V3AB, hV4, and IPS0.

Inverted Encoding Model. Following prior work (Brouwer and Heeger, 2009;

Sprague and Serences, 2013), we used an inverted encoding model to estimate spatially-

selective tuning functions from multivariate, voxel-wise activity within each ROI. We

assumed that each voxel's activity reflects the weighted sum of 24 spatially selective

channels, each tuned for a different angular location. These information channels are

assumed to reflect the activity of underlying neuronal populations tuned to each location.

We modeled the response profile of each spatial channel as a half sinusoid raised to the

24th power:

$$R = \sin(0.5\theta)^{24},$$

where θ is angular location (0–359°, centered on each of the 24 bins from the mapping

task), and R is the response of the spatial channel in arbitrary units.

Independent training data B_1 were used to estimate weights that approximate the

relative contribution of the 24 spatial channels to the observed response at each voxel.

Let B_1 (m voxels × n_1 observations) be the activity at each voxel for each measurement

in the training set, C_1 (k channels × n_1 observations) be the predicted response of each

spatial channel (determined by the basis functions) for each measurement, and W (m

voxels × k channels) be a weight matrix that characterizes a linear mapping from "channel

space" to "voxel space". The relationship between B_1, C_1, and W can be described by a

general linear model:

$$B_1 = WC_1$$

We obtained the weight matrix through least-squares estimation:

$$\widehat{W} = B_1 C_1{}^{\mathrm{T}} (C_1 C_1{}^{\mathrm{T}})^{-1}$$

In the test stage, we inverted the model to transform the observed test data B_2 (m voxels

× n_2 observations) into estimated channel responses, C_2 (k channels × n_2 observations),

using the estimated weight matrix, $\widehat{W}$, that we obtained in the training phase:

$$\widehat{C_2} = (\widehat{W}^{\mathrm{T}}\widehat{W})^{-1}\widehat{W}^{\mathrm{T}}B_2$$

Each estimated channel response function was then circularly shifted to a common center

by aligning the estimated channel responses to the channel tuned for target location.

Model training and testing. We trained the IEM using independent mapping task

data and tested the model using single trial search-task data (average of 4 to 10 TR's

after search array onset). We then shifted and averaged the search task data so that like

trials were aligned (e.g., rotate and average all trials with target-distractor distance of 90).

To reduce idiosyncrasies of only having 1 test set, we iterated the analysis by leaving out

1 block of training data and 1 block of test data, looping through all possible combinations

(e.g., for each 1 block of left out training data, we left out each possible block of test data

on different runs of the loop).

404   **Results**

405   **Behavior**

406   Subjects performed a variant of the additional singleton search task (Theeuwes,

1992) (Figure 1A) in which they searched for a target (diamond) among non-targets

(circles). On each trial, the participant reported via button-press the orientation of the line

inside the diamond target (vertical or horizontal). On 66.67% of trials, one of the non-

targets was uniquely colored ("singleton distractor present", e.g., one red distractor, two

green non-targets, and one green target item). Behavioral capture was quantified as

slowed response times (RTs) when the distractor was present versus absent. In addition

to examining the basic capture effect, a key goal of this work was to examine modulation

of capture by trial history (Vatterott and Vecera, 2012; Gaspelin et al., 2015, 2017). Prior

work has shown that participants can learn to suppress a distractor (i.e., no RT difference

for singleton distractor present versus absent trials) when the same distractor color or

distractor location is repeated over many trials (Vatterott and Vecera, 2012; Gaspelin et

al., 2015, 2017). Building on this work, we included two key task conditions in a

counterbalanced, block-wise fashion to manipulate trial history and behavioral capture

while using identical stimulus arrays (e.g., green target, red distractor). In the color

constant condition (Figure 1A), the array colors stayed constant throughout the block

(e.g., green target, green non-target items, red distractor). In the color variable condition

(Figure 1B), the array colors randomly varied from trial to trial. Based on prior work, we

expected robust capture in the color variable condition, and little or no capture in the color

constant condition (Vatterott and Vecera, 2012; Gaspelin et al., 2015, 2017).

sec		2-8 sec

Figure 1. Visual search task stimuli. On each trial, participants viewed a 4-item array and reported the orientation of the line inside the diamond-shaped target (horizontal or vertical). **(A)** In the color constant condition, colors of targets and singleton distractors were fixed throughout the run. **(B)** In the color variable condition, colors of targets and singleton distractors swapped randomly from trial to trial. **(C)** An example trial with labels for the target, singleton distractor, and non-target items.

Replicating prior work, we found significant behavioral capture that was modulated by trial history (Geyer et al., 2006; Vatterott and Vecera, 2012; Goschy et al., 2014; Gaspelin et al., 2015, 2017; Wang and Theeuwes, 2018a; Failing et al., 2019a). In our MRI sample (Exp 1a, Figure 2A & 2C), we observed significant behavioral capture in the color variable condition, with longer RT's for distractor present versus distractor absent trials ($M = 32.8$ ms, $SD = 25.5$ ms, $p = .001$, $d = 1.28$), but capture was not significant in the color constant condition ($M = 10.8$ ms, $SD = 18.5$ ms, $p = .07$, $d = .59$). Importantly, capture was significantly larger for color variable vs. color constant runs ($p = .009$, $d = .91$). We replicated this pattern of findings in the behavior-only experiment (Exp. 1b, Figure 2B & 2D), with robust capture for 'color variable' ($p < 1 \times 10^{-5}$, $d = 1.31$), no significant capture for 'color constant' ($p = .1$, $d = .32$), and larger capture for color variable vs. constant ($p = .002$, $d = .71$). Participants in both experiments were accurate overall (>90%), and there was no evidence of a speed-accuracy trade-off (Figure 2-1).

In addition to the key modulation of capture as a function of stimulus history, we also replicated prior findings that the degree of capture is significantly modulated by the physical distance between the target and the distractor (Mounts, 2000; Turatto and Galfano, 2001; Wang and Theeuwes, 2018a; Failing et al., 2019b), with larger capture for distractors nearer the target (Figure 2E-F). We ran a repeated measures ANOVA

including both experiments (n=36). Including Experiment as a factor revealed no

experiment main effects or interactions (p > .2), so the two experiments were combined

for further analyses of the behavioral data (although Figure 2 shows data from the two

experiments separately). There was a significant effect of Condition (larger capture for

color variable than color constant), $p < 1\times10^{-4}$, a main effect of Distance (larger capture

for 90° than 180°), $p = .037$, $\eta^2_p = .12$, and an interaction between Condition and Distance

(greater distance effect in the color variable condition), $p = .014$, $\eta^2_p = .16$.

Figure 2. Behavioral capture during the visual search task. (A) In the main MRI

Experiment (Exp 1a), participants were significantly captured by the salient singleton

distractor in the color variable condition, but not in the color constant condition. **(B)** This

pattern replicated in the behavior-only experiment (Exp 1b). **(C-D)** Capture costs (RT

Difference for distractor present – absent trials) were significantly larger in the color

variable than in the color constant condition in Exp 1a **(C)** and Exp 1b **(D)**. **(E-F)** Capture

costs (RT Difference for distractor present – absent trials) were significantly modulated

by the distance between the target and distractor in the color variable condition both in

Exp 1a **(E)** and Exp 1b **(F)**. Violin plot shading shows range and distribution of the data;

dots represent single subjects; black error bars indicate ±1 SEM. Asterisks depict

significance for uncorrected post-hoc comparisons between adjacent bars within each

experiment, * $p < .05$, ** $p < .01$, *** $p < .001$.

fMRI results: Model estimates of spatial position in the independent mapping task

We opted for a multivariate model-based approach to estimate the amount of

information encoded in voxel activation patterns about each of the 4 stimuli in the search

array, as such multivariate approaches are more sensitive than just computing the

univariate mean response across all voxels (Cox and Savoy, 2003; Haynes and Rees,

2005; Kamitani and Tong, 2005; Norman et al., 2006; Serences and Saproo, 2012; Tong

and Pratte, 2012). For example, item-specific information has been observed using

multivariate methods even in the absence of univariate changes (Lewis-Peacock and

Postle, 2012; Emrich et al., 2013) (but for univariate analyses of the present data, see

extended data Figure 3-1). We opted for an inverted encoding model (IEM) approach

(Sprague et al., 2018a, 2019), as opposed to Bayesian or other decoders (van Bergen et

al., 2015; van Bergen and Jehee, 2019), because this approach allowed us to easily

derive a separate estimate of the information encoded about each of the 4 simultaneously

presented items from the search array in the main analysis (Sprague et al., 2019). For

further discussion of IEM model assumptions and best practices, see: (Sprague et al.,

2018a, 2019).

In our key analyses of the fMRI data, we used an independent mapping task to

train a model of spatial position from which we estimated the relative priority of all item

positions within the visual search array. During the independent mapping task, observers

viewed a flickering checkerboard wedge that was presented at 1 of 24 positions on an

imaginary circle around fixation (Figure 3A). We first checked that we observed robust

estimates of spatial position when training and testing within the independent mapping

task (leave 1 run out, see section 'Inverted Encoding Model'). We observed robust model-

based estimates of spatial position for all ROIs (Figure 3B). Parameters from the best-

fitting von Mises distribution to each region-of-interest (ROI) are depicted in Figure 3C

(model fits, linear classifier results, and von Mises parameters for shuffled data are shown

in extended data Figure 3-2). There was an effect of ROI on precision such that spatial

position was represented less precisely in later visual areas ($p < 1 \times 10^{-5}$, where precision

is the concentration parameter κ of the best fitting von Mises, with higher values indicating

a more precise function). There was also an effect of ROI on the amplitude and baseline

measures of the model-based estimates of spatial position ($p < 1\times10^{-5}$), and all 3 parameters significantly differed from zero across all ROIs ($p < 1\times10^{-5}$). These results, particularly the observation of amplitudes greater than 0, confirmed that activation patterns in all examined regions encode information about spatial position.

Figure 3. Single-item model estimates training and testing within the independent mapping task. (A) Independent mapping task used to train the model to estimate spatial position of 4 search array items. Participants viewed a flickering checkerboard which could appear at one of 24 positions around an imaginary circle. **(B)** Blue lines: Model estimates of viewed spatial position training and testing within the independent mapping task. Single-trial model estimates for each subject are aligned to 0 degrees and averaged. Black lines: Model estimates for shuffled training labels. Opaque lines = group average; semi-transparent lines = individual subjects. **(C)** Descriptive statistics for best fit von Mises parameters (precision [κ], amplitude, baseline) to model estimates in panel B. Error bars indicate ±1 SEM; the opaque line shows the group average; semi-transparent lines show individual subjects.

Unlike the single item model estimates that were derived based on the independent mapping task (Figure 3), we could not fit a simple, uni-modal Gaussian function to model-based estimates derived from the search task data because 4 peaks in the model output were expected – one for each item in the search array. As such, we first conducted simulations to ensure that we would be able to measure putative changes to individual item representations (e.g. target enhancement, distractor suppression), despite multiple item representations contributing to the aggregate 4-item model estimates. To

do so, we used data from the independent mapping task to generate predictions for

observed model responses in a 4-item array. For each ROI, we took the 1-item model

response derived from the independent mapping task, replicated this model response

four times (once at each of the four search array positions), and took the average of all 4

shifted 1-item model response lines to generate a single 4-item model prediction. In

addition, we systematically varied the strength of the simulated response to each item to

ensure that we were able to recover a corresponding change in the item-specific

responses estimated from the aggregate 4-item model estimate (Figure 4; extended data

Figure 4-1).

These simulations revealed clearly separable peaks for all four items in early areas

like V1, where spatial precision is high (Figure 4A-B, left panel). In contrast, identifying

clear peaks in later areas like IPS0 was difficult when the response to all items was

equivalent (Figure 4A-B, right panel). However, if one item evoked a larger or smaller

response than the other items, as would be expected with target enhancement or

distractor suppression, then clear and measurable changes to the aggregate 4-item

model estimates emerged (Figure 4C). Further simulations showed that we could detect

smaller changes to one item (e.g., distractor suppression) in the presence of larger

changes to another item (e.g., target) by measuring the response amplitude at each

expected item's peak. In V1, this is clearly seen in the peak response to each item; in

later areas such as IPS0, such changes manifest as a large central peak that is skewed

by the neighboring items' smaller changes (Figure 4D).

We also used a general linear model (GLM) to estimate best-fitting gain factors for

each of the 4 hypothesized item representations by fitting an aggregate function and

allowing one parameter in the GLM to scale the response associated with each item. This

is essentially the inverse of the simulations described above: For a given aggregate

response (i.e., the response of each of the 24 spatial channels when shown a given 4-

item search array), we used a non-negative least squares solution(Lawson and Hanson,

1974) to estimate the contribution of each of the 4 item positions (calculated from the 1-

item localizer task) to the observed 4-item search array response (Figure 4E). This

analysis yielded similar results to the simple approach of comparing the height at each

expected item peak (extended data Figure 5-4). Thus, using either the raw amplitude at expected peaks or a GLM-based approach, we determined that we should be able to accurately characterize situations in which there was no modulation of target and distractor responses as well as situations in which there was a significant modulation of target and/or distractor responses.

Figure 4. Generating predictions for 4-item model estimates by averaging single-item model estimates from the independent mapping task. (A) Average from the independent mapping task plotted at 4 hypothetical item locations. Here, these 4 "items" are represented with equal priority. (B) Hypothetical observed response when measuring a single trial containing the 4 items presented simultaneously. This line is the average of all lines in Panel A. (C) The same as panels A and B, but with the item at position 0 assigned a higher response amplitude than the other three items. (D) The same panels as A and B, but with both an enhanced item at position 0 and a suppressed item at position -90. (E) Actual IEM model output for 4-item search arrays in V2 (Target plotted at 0, distractor plotted at -90). To estimate the strength of each of the 4 underlying item representations, one can simply measure the height (a.u.) at expected item peaks (i.e., -180, -90, 0, and 90). Alternatively, one may use a non-negative least squares solution to estimate weights for a regressor for each of the 4 item positions. Each regressor is the 1-item IEM output from the independent mapping task within the same region (e.g., V2), shifted to the appropriate item location. (F) Example IEM output and best-fitting non-negative least squares solution with 4 item regressors.

Analysis of search array locations in V1, V2, V3, V3AB, hV4, and IPS0.

Given that we can assess differential responses associated with each of the 4

items in the search array (Figure 4), we next tested whether goal- and history-driven

modulations were differentially represented across the visual stream by performing an

analysis of history-driven effects on target and distractor processing across visual ROIs

(Figure 5). These six ROIs (V1, V2, V3, V3AB, hV4 and IPS0) were chosen for each

participant having at least 90 spatially selective voxels as determined by the localizer

data. Here, we focus on history-driven effects on target processing and distractor

processing for the arrays where behavioral and neural distractor competition effects were

greatest (target-distractor separation +/-90°, see Figure 2E,F). Full ANOVA results and

additional plots are shown for individuals ROIs with both array 90° and 180°

configurations in extended data Figures 5-4 and 5-5.

Figure 5. Dissociable effects of stimulus history on target enhancement and distractor suppression. (A) Model responses for individual ROIs as a function of task condition (Arrays with target-distractor distance +/-90). Purple and green lines (Shaded error bars = 1 SEM) show the output of the inverted encoding model in the color constant and color variable conditions, respectively. Background panels at -180°, -90°, 0° and +90° show the positions of the 4 search array items (blue = target (T), pink = distractor (D), green = non-target 1(N1), orange = non-target 2 (N2). Target enhancement can be seen as the greater height at position 0: The IEM peak at the blue bar is higher than the IEM peak at the orange, pink, and green bars. History-driven distractor suppression can be seen as the lower height at position -90 for the color constant vs. color variable conditions: The IEM peak at the pink bar is higher for the green line than for the purple line. (B) Target amplitude as a function of ROI and task condition. There was no effect of task condition on target amplitude, but a significant increase in target amplitude across ROIs. Violin plot shading shows range and distribution of the data; dots represent single subjects; black error bars indicate ±1 SEM. (C) Distractor amplitude as a function of ROI and task condition. There was a significant effect of task condition on distractor amplitude, and this history-driven effect did not interact with ROI.

We found evidence for within-display target enhancement (i.e., enhancement of the target over other positions), but we did not find evidence for history-driven modulations of target enhancement. Overall target enhancement was significant in all ROIs (all p's < .001) except for V1 (p's > .12), and target enhancement significantly increased across ROIs (p < .001) as shown in Figure 5A-B. There was, however, no meaningful effect of history on target amplitude as revealed by a repeated-measures

ANOVA testing the main effect of history and the interaction between history and ROI on

target processing (p = .35, η^2_p = .08; p = .64, η^2_p = .04 for main effect and interaction

respectively). This pattern was the same whether we used raw amplitude values or we

used values from the GLM (no effect of history, p = .28, no interaction of history and ROI,

p = .51).

In contrast, history had a significant effect on distractor amplitude such that

distractor amplitudes were significantly attenuated in the color constant condition relative

to the color variable condition. A repeated-measures ANOVA revealed a main effect of

history (p = .007, η^2_p = .50) and no interaction between history and ROI (p = .44, η^2_p =

.08), indicating that the effect of history on distractor processing was similar throughout

the examined ROIs. Though the ANOVA suggests that history effects were of a similar

magnitude across all examined ROIs, a post-hoc simple main effects analysis showed

that the effect was individually significant only in V1 (p < .001) and V3 (p < .01). This

general pattern was the same whether we used raw amplitude values or else used values

from the GLM approach (main effect of history, p = .01, η^2_p = .47, no interaction of history

and ROI, p = .87, η^2_p = .03).

Finally, we examined changes in non-target responses. For "non-target 1" (the item

neighboring the target on the side opposite the distractor), there was an overall history

related modulation (color constant > color variable, p = .016, η^2_p = .42) that did not interact

with ROI (p = .76, η^2_p = .03). Similar general effects on non-target processing have been

observed recently (Won et al., 2020) and may reflect a bias of attention away from the

distractor such that attention may 'overshoot' the target because of the reduction in signal

at the distractor location. The effect of history on "non-target 1" responses likewise was

similar though of borderline significance in the GLM analysis (color constant > color

variable, p = .049, η^2_p = .31). We found no effect of history on the other non-target ("non-

target 2") which occupied the spatial position 180 degrees from the target item (p >= .61).

Finally, additional analyses on larger, aggregate ROIs (V1-V3, IPS0-3) yield

convergent results and also demonstrate how distractor suppression effects were absent

for arrays where the target and distractor did not compete with each other (target-

distractor separation +/- 180°), consistent with our separate analysis of each ROI (Figure

6) and prior behavioral and neural findings (Turatto and Galfano, 2001; Wang and

Theeuwes, 2018a; Failing et al., 2019b; Won et al., 2020) (extended data Figures 5-1, 5-

2, and 5-3).

681   **Discussion**

682   To find what we are looking for, we must integrate information about stimulus

relevance, salience, and history. While the impact of stimulus relevance and salience on

topographically organized population codes have been thoroughly investigated, stimulus

history is not thought to be a wholly goal-driven or stimulus-driven process. Rather, history

effects may depend on interactions between the current stimulus drive ('bottom-up' factor)

and the current internal state of the visual system ('top-down' factor). To address this

ambiguity and to better understand how history impacts visual processing, we tested

whether history-driven changes to attentional priority operate in a manner akin to

canonically goal-driven and/or to stimulus-driven signatures of priority. To do so, we

estimated population-level neural responses evoked by 4-item search arrays across

retinotopically-defined areas of occipital and parietal cortex. We found that stimulus

history did not modulate the specificity of goal-driven target templates, as goal-driven

target enhancement was unaffected by stimulus history. Instead, we found that stimulus

history attenuated responses related to distractors throughout the visual hierarchy. These

results suggest that stimulus history may influence visual search performance via local

competitive interactions within early sensory cortex (i.e., V1), consistent with the V1

salience map hypothesis. Further, we argue that these early competitive interactions

cannot be explained by traditional predictive coding models.

Proposed model: Adaptation alters a stimulus-driven salience map in V1

702   Models of image-computable salience propose that local image statistics

determine competitive interactions that give rise to 2D spatial salience maps within V1

(Li, 2002; Zhang et al., 2012) or after integrating feature maps at a later stage of

processing (e.g., Treisman and Gelade, 1980; Wolfe, 1994; Itti and Koch, 2000; Carmi

and Itti, 2006), and these models do not typically account for the long-term effects of

stimulus history. Note, many existing saliency models do account for *short -term* changes

to stimuli by coding for dynamic image factors such as motion velocity and flicker (i.e.,

luminance onset or offset) across movie frames (~30 ms per frame), (Itti and Koch, 2000;

Carmi and Itti, 2006). However, these dynamic feature maps cannot explain history

effects that build up over the course of many trials and persist across blank inter-trial

intervals. Rather, an additional mechanism is needed to integrate stimulus information

over a longer duration. Recent work suggests that neural adaptation – which is linked to

the history of prior stimuli – in a subset of tuned neurons may alter stimulus-driven

competitive dynamics (e.g., divisive normalization, Carandini and Heeger, 2012) within

early visual cortex (Solomon and Kohn, 2014). Thus, to accommodate our observation of

history-driven distractor suppression within existing saliency models, we propose that

stimulus-driven evoked responses in V1 may be integrated over a longer, multi-trial

duration (as opposed to just within a single image; Figure 6) (Karni and Sagi, 1991;

Schwartz et al., 2002; Jehee et al., 2012). In the context of models of visual search, this

might be comprised of a series of 2D spatial maps that together form a temporally

integrated 3D salience map (i.e., salience is computed based on current and prior

physical stimulus properties). Consistent with the notion of a 3D salience map, recent

behavioral and neural evidence suggests a role for priming and habituation in visual

search behaviors (Geyer et al., 2006; Feldmann-Wüstefeld and Schubö, 2016; Turatto

and Pascucci, 2016; Turatto et al., 2018; Won and Geng, 2020, also see: Reavis et al.,

2016), even when the adapting stimuli are task-irrelevant.

730
Figure 6. Simplified cartoon illustration of local-image versus temporal-integration
salience for a simple image with one feature and location. (A) In 2-D salience
computations, stimulus-driven stimulus drive is determined locally within a given image
without respect to prior images. Sequence 1 is 4 different trials, and on each trial the
same stimulus is shown (Blue-Blue-Blue-Blue). Sequence 2 is 4 different trials, but the
final trial is a different color from the preceding trials (Green-Green-Green-Blue). The final
trial (Blue) is physically identical for the two sequences. So, the final stimuli (trial n in each
sequence) have identical 2-D salience. Assuming that we chose equiluminant green and
blue values, then each "frame" in the sequence likewise has approximately the same
image-computable salience, as shown by the uniform-sized square pulses in the cartoon.
Alternatively, stimulus-driven salience maps may better be conceived of as reflecting a
temporally-integrated 3-D salience map, as early sensory neurons adapt to ongoing
stimulus features. In Sequence 1 (Blue-Blue-Blue-Blue), the activity of neurons that are
maximally responsive to blue wanes due to adaptation. In Sequence 2 the activity of
neurons maximally responsive to green wanes over the first 3 trials, but the final stimulus
elicits a robust response from the non-adapted blue-preferring neurons. Thus, temporally-
integrated salience for the trial *n* in each sequence differs across the two sequences even
though the stimuli are physically identical. (B) Most studies of predictive coding and
adaptation consider changes to neural activity for a single item. Here, we illustrate how
adaptation can have consequences for stimulus-driven saliency that arises from inter-
item competition within multi-item arrays (e.g., Itti and Koch, 2000). Top: For the first
presentation of the array, all neurons respond strongly, leading to classic inter-item
competition effects that yield high distractor saliency. Bottom: With repeated
presentations and adaptation, overall activity and inter-item competition is weakened,
yielding a relative attenuation of the distractor.
756
Consistent with a temporally-integrated V1 saliency account of history-driven
distractor suppression, we observed history-driven modulations only with sufficient
competition (i.e., targets and distractors were closer together) and we observed robust
history-driven modulations in V1 in the absence of goal-driven modulations. In line with
our findings, prior behavioral work has shown that incidental repetitions of distractor, but

not target, features and locations modulate search performance (Geyer et al., 2006;

Failing et al., 2019b). Likewise, prior work has shown a rapid suppression of distractor-

evoked neural responses (Hickey et al., 2009; Zhang and Luck, 2009; Sawaki and Luck,

2010; Gaspar and McDonald, 2014; Moher et al., 2014; Gaspelin et al., 2015, 2017) and

that the likelihood of distraction results in anticipatory changes to distractor, but not target,

locations (Serences et al., 2004; Heuer and Schubö, 2019; Won et al., 2020). However,

the proposed temporally-integrated salience account does not capture all history-driven

effects. In our task, the repeated distractor features were purely visual in nature, and thus

history effects might be mediated entirely via local circuit dynamics (i.e., the adaptation

account described above). In contrast, other studies have examined history-driven effects

for more abstract features like reward (Mazer and Gallant, 2003; Serences, 2008; Saproo

and Serences, 2010; Stanisor et al., 2013; Chelazzi et al., 2014; Hickey and Peelen, 2015;

MacLean and Giesbrecht, 2015; Itthipuripat et al., 2019; Kim and Anderson, 2019) (but

also see: Maunsell, 2004; Anderson and Kim, 2019), which may require an intermediary

pathway such as the medial-temporal lobe (Theeuwes, 2019) or dopaminergic midbrain

structures (Hickey and Peelen, 2015, 2017).

Implications for predictive coding theories of visual processing

780   Much of the debate about history-driven changes to visual search has been

separated from the predictive coding literature, but these two ideas are highly intertwined.

Predictive coding theories propose that incoming visual information is compared to

expected visual information at later stages of processing (Rao and Ballard, 1999; Friston,

2005; Summerfield and de Lange, 2014; Spratling, 2017). Efficient, predictive coding is

achieved via an iterative updating process whereby error units detect deviations from

what is expected and inhibit expected information in the prediction units at an earlier stage

of processing. Thus, at first glance, it appears that predictive coding may explain the

results observed here: our core finding is that salient distractors are attenuated when they

are repeated. However, our findings deviate from the core predictions of extant predictive

coding models.

A fundamental tension has long been noted in the literature: Predictive coding

models primarily explain how expected information becomes *attenuated,* and thus have

difficulty explaining signal enhancement related to attention (e.g., Luck et al., 1997; Hupé

et al., 1998; Kastner and Ungerleider, 2000). Many predictive coding models implement

error-driven feedback as inhibitory signaling from the next adjacent visual area (e.g., V3

to V2). To explain top-down attentional prioritization effects, predictive coding models

must be modified, as has been done in the Predictive Coding/ Biased Competition

(PC/BC) model (Spratling, 2008). In this model, an additional top-down attention

component is added, and the error and prediction units are shifted such that error-driven

feedback is excitatory. These changes to the model allow for biased competition effects

to arise within a predictive coding framework.

Although the PC/BC model variants can predict biased competition effects in

attention, such models critically predict that target enhancement and distractor

suppression effects will be yoked, as both effects arise from feedback from the next higher

level of visual processing. Thus, for existing predictive coding models to explain our

results, we should have observed that the emergence of history-driven distractor

suppression paralleled top-down target enhancement. In contrast, we found diverging

target enhancement and history-driven distractor suppression effects: whereas target

enhancement was absent in V1 and increased across the visual stream, history-driven

distractor suppression emerged in V1. Thus, we propose that history-driven distractor

suppression is best explained by 'bottom-up' inter-trial priming arising from adaptation

within V1 (Westerberg et al., 2019).

Furthermore, we argue that it is important to differentiate between "bottom-up" and

"top-down" expectational effects, analogous to recent arguments that it is critical to

differentiate between potential confounds of attention and expectation (Summerfield and

de Lange, 2014; Rungratsameetaweemana and Serences, 2019). We define 'top-down'

expectations as those that can be updated flexibly and on a rapid time scale (e.g., over

the course of a few trials). In contrast, we define 'bottom-up' expectations as those that

are ingrained over a very long time-scale and tied to particular stimuli. For example, early

ideas about predictive coding emerged from studies of the retina: By exploiting long-term

'expectations' that naturalistic stimuli are correlated in space and time, coding can be

highly efficient (Srinivasan et al., 1982; Rao and Ballard, 1999).

Making a distinction between 'bottom-up' and top-down' expectations can explain

prior results that run counter to some predictive coding models. Specifically, Maljkovic

and Nakayama's (1994) priming of pop-out experiments demonstrated that RT costs are

incurred by switching stimuli even when the stimulus switch is expected. When a stimulus

is predictable and repeated (e.g., 0% probability of a color switch), participants are faster

than when a stimulus is unpredictable and switches color (e.g., 50% probability of a color

switch. If expectations can attenuate the cost of switching colors, then participants should

likewise be faster in a predictable, 100% switch condition than in the unpredictable 50%

switch condition. In contrast to this prediction, Maljkovic & Nakayama found that

participants were *slower* in the 100% switch condition: Participants apparently were

unable to use their expectations to overcome bottom-up stimulus-driven priming effects.

Goal-driven attention effects

In addition to implicating early visual cortex in representing history-driven task

factors during visual search, we also replicated prior findings that the locations of attended

items (here, search targets) are prioritized relative to other item locations in both visual

and parietal cortex (Saproo and Serences, 2010; Sprague and Serences, 2013; Sprague

et al., 2018b). These target-related modulations are consistent with the broad involvement

of visually-responsive regions in representing goal-driven priority during visual search

(Mazer and Gallant, 2003; Ogawa and Komatsu, 2006). For example, recent studies

manipulated the salience (contrast) and relevance (attended or unattended) of items and

found that salience and relevance were both represented, to varying degrees, across the

visual hierarchy (Poltoratski et al., 2017; Sprague et al., 2018b). Notably, however, here

we found that target prioritization was absent in V1, whereas prior work has found robust

effects of attention in V1 (Motter, 1993; Kastner, 1998; Tootell et al., 1998; Gandhi et al.,

1999; Kastner et al., 1999; Somers et al., 1999; Serences and Yantis, 2007; Saproo and

Serences, 2010; Sprague and Serences, 2013). This difference may reflect task

differences — much prior work found attention-related gains in V1 when spatial attention

was cued in advance or a single target was shown, whereas visual search arrays provide

visual drive at many competing locations and spatial attention is deployed only after array

onset. As such, further work may be needed to unconfound history effects and attention

effects in the study of spatial attention, as much early work on univariate attention effects

has employed blocked designs where the same location is attended for many trials in a

row (Kastner, 1998; Tootell et al., 1998; Gandhi et al., 1999; Kastner et al., 1999; Somers

et al., 1999).

Future directions

Although our work suggests that stimulus history modulates representations of

distractor but not target processing in visual cortex, there are some potential limitations

to the current design that suggest avenues for future work. First, because we measured

only location, we could not directly measure suppression of the distractor color (Failing et

al., 2019a). However, as the spatial position of the distractor was completely

unpredictable, our results do strongly imply that the distractor color was suppressed.

Likewise, most theories of visual search hypothesize that space is the critical binding

medium through which feature and goal maps are integrated (Treisman and Gelade,

1980; Wolfe, 1994; Itti and Koch, 2000), and recent work suggests that location is

spontaneously encoded even when only non-spatial features such as color are task-

relevant (Foster et al., 2017a). Second, it is possible that history may modulate both

distractor- and target-processing in other circumstances not tested here. That is, perhaps

the target template 'diamond' in our task was sufficiently useful such that adding feature

information to this template (e.g., 'red diamond' rather than 'diamond') did not confer a

behavioral advantage (but see: Maljkovic and Nakayama, 1994). Finally, the time-course

of MRI (sampling every 800 ms) is slower than shifts of spatial attention to the search

target (< 500 ms) (Foster et al., 2017b). Although the history-driven effects that we

observed in visual cortex are consistent with the rapid distractor suppression effects

observed in EEG (Sawaki and Luck, 2010; Gaspar and McDonald, 2014), we cannot

definitively say on the basis of these data that the observed history-driven effects

occurred rapidly and directly within visual cortex versus via recurrent feedback from later

visual areas. Nonetheless, the present work is consistent with and provides critical initial

evidence for such a model.

883   **References**

884   Anderson BA, Kim H (2019) On the relationship between value-driven and stimulus-driven attentional
885   capture. Atten Percept Psychophys 81:607–613.

886   Andersson JLR, Skare S, Ashburner J (2003) How to correct susceptibility distortions in spin-echo echo-
887   planar images: application to diffusion tensor imaging. NeuroImage 20:870–888.

888   Arita JT, Carlisle NB, Woodman GF (2012) Templates for rejection: Configuring attention to ignore task-
889   irrelevant features. Journal of Experimental Psychology: Human Perception and Performance
890   38:580–584.

891   Awh E, Belopolsky AV, Theeuwes J (2012) Top-down versus bottom-up attentional control: a failed
892   theoretical dichotomy. Trends in Cognitive Sciences 16:437–443.

893   Beck VM, Hollingworth A (2015) Evidence for negative feature guidance in visual search is explained by
894   spatial recoding. Journal of Experimental Psychology: Human Perception and Performance
895   41:1190–1196.

896   Beck VM, Hollingworth A, Luck SJ (2012) Simultaneous Control of Attention by Multiple Working Memory
897   Representations. Psychol Sci 23:887–898.

898   Becker MW, Hemsteger S, Peltier C (2015) No templates for rejection: a failure to configure attention to
899   ignore task-irrelevant features. Visual Cognition 23:1150–1167.

900   Bisley JW, Mirpour K (2019) The neural instantiation of a priority map. Current Opinion in Psychology
901   29:108–112.

902   Bogler C, Bode S, Haynes J-D (2011) Decoding Successive Computational Stages of Saliency
903   Processing. Current Biology 21:1667–1671.

904   Brainard DH (1997) The Psychophysics Toolbox. Spat Vis 10:433–436.

905   Brouwer GJ, Heeger DJ (2009) Decoding and Reconstructing Color from Responses in Human Visual
906   Cortex. Journal of Neuroscience 29:13992–14003.

907   Carandini M, Heeger DJ (2012) Normalization as a canonical neural computation. Nat Rev Neurosci
908   13:51–62.

909   Carlisle NB, Arita JT, Pardo D, Woodman GF (2011) Attentional Templates in Visual Working Memory.
910   Journal of Neuroscience 31:9315–9322.

911   Carmi R, Itti L (2006) Visual causes versus correlates of attentional selection in dynamic scenes. Vision
912   Research 46:4333–4345.

913   Chelazzi L, Eštočinová J, Calletti R, Lo Gerfo E, Sani I, Della Libera C (2014) Altering Spatial Priority
914   Maps via Reward-Based Learning. Journal of Neuroscience 34:8594–8604.

915   Conci M, Deichsel C, Müller HJ, Töllner T (2019) Feature guidance by negative attentional templates
916   depends on search difficulty. Visual Cognition 27:317–326.

Cox DD, Savoy RL (2003) Functional magnetic resonance imaging (fMRI) "brain reading": detecting and
classifying distributed patterns of fMRI activity in human visual cortex. NeuroImage 19:261–270.

Dale AM, Fischl B, Sereno MI (1999) Cortical Surface-Based Analysis. NeuroImage 9:179–194.

Desimone R, Duncan J (1995) Neural Mechanisms of Selective Visual Attention. Annu Rev Neurosci
18:193–222.

Downing PE (2000) Interactions Between Visual Working Memory and Selective Attention. Psychol Sci
11:467–473.

Emrich SM, Riggall AC, LaRocque JJ, Postle BR (2013) Distributed Patterns of Activity in Sensory Cortex
Reflect the Precision of Multiple Items Maintained in Visual Short-Term Memory. Journal of
Neuroscience 33:6516–6523.

Engel SA, Furmanski CS (2001) Selective Adaptation to Color Contrast in Human Primary Visual Cortex.
J Neurosci 21:3949–3954.

Engel SA, Rumelhart DE, Wandell BA, Lee AT, Glover GH, Chichilnisky E-J, Shadlen MN (1994) fMRI of
human visual cortex. Nature 369:525–525.

Failing M, Feldmann-Wüstefeld T, Wang B, Olivers C, Theeuwes J (2019a) Statistical regularities induce
spatial as well as feature-specific suppression. Journal of Experimental Psychology: Human
Perception and Performance 45:1291–1303.

Failing M, Wang B, Theeuwes J (2019b) Spatial suppression due to statistical regularities is driven by
distractor suppression not by target activation. Atten Percept Psychophys 81:1405–1414.

Fecteau J, Munoz D (2006) Salience, relevance, and firing: a priority map for target selection. Trends in
Cognitive Sciences 10:382–390.

Feldmann-Wüstefeld T, Schubö A (2016) Intertrial priming due to distractor repetition is eliminated in
homogeneous contexts. Atten Percept Psychophys 78:1935–1947.

Foster JJ, Bsales EM, Jaffe RJ, Awh E (2017a) Alpha-Band Activity Reveals Spontaneous
Representations of Spatial Position in Visual Working Memory. Current Biology 27:3216-3223.e6.

Foster JJ, Sutterer DW, Serences JT, Vogel EK, Awh E (2017b) Alpha-Band Oscillations Enable Spatially
and Temporally Resolved Tracking of Covert Spatial Attention. Psychological Science 28:929–
941.

Friston K (2005) A theory of cortical responses. Phil Trans R Soc B 360:815–836.

Gandhi SP, Heeger DJ, Boynton GM (1999) Spatial attention affects brain activity in human primary
visual cortex. Proceedings of the National Academy of Sciences 96:3314–3319.

Gardner JL, Sun P, Waggoner RA, Ueno K, Tanaka K, Cheng K (2005) Contrast Adaptation and
Representation in Human Early Visual Cortex. Neuron 47:607–620.

Gaspar JM, McDonald JJ (2014) Suppression of Salient Objects Prevents Distraction in Visual Search.
Journal of Neuroscience 34:5658–5666.

Gaspelin N, Leonard CJ, Luck SJ (2015) Direct Evidence for Active Suppression of Salient-but-Irrelevant
Sensory Inputs. Psychol Sci 26:1740–1750.

Gaspelin N, Leonard CJ, Luck SJ (2017) Suppression of overt attentional capture by salient-but-irrelevant
color singletons. Attention, Perception, & Psychophysics 79:45–62.

Gaspelin N, Luck SJ (2018) Distinguishing among potential mechanisms of singleton suppression.
Journal of Experimental Psychology: Human Perception and Performance 44:626–644.

Geng JJ (2014) Attentional Mechanisms of Distractor Suppression. Curr Dir Psychol Sci 23:147–153.

Geng JJ, Won B-Y, Carlisle NB (2019) Distractor Ignoring: Strategies, Learning, and Passive Filtering.
Curr Dir Psychol Sci 28:600–606.

Geyer T, Müller HJ, Krummenacher J (2006) Cross-trial priming in visual search for singleton conjunction
targets: Role of repeated target and distractor features. Perception & Psychophysics 68:736–749.

Goschy H, Bakos S, Müller HJ, Zehetleitner M (2014) Probability cueing of distractor locations: both
intertrial facilitation and statistical learning mediate interference reduction. Front Psychol 5
Available at: http://journal.frontiersin.org/article/10.3389/fpsyg.2014.01195/abstract [Accessed
September 8, 2020].

Greve DN, Fischl B (2009) Accurate and robust brain image alignment using boundary-based registration.
NeuroImage 48:63–72.

Grill-Spector K, Malach R (2001) fMR-adaptation: a tool for studying the functional properties of human
cortical neurons. Acta Psychologica 107:293–321.

Haynes J-D, Rees G (2005) Predicting the orientation of invisible stimuli from activity in human primary
visual cortex. Nat Neurosci 8:686–691.

Heuer A, Schubö A (2019) Cueing distraction: electrophysiological evidence for anticipatory active
suppression of distractor location. Psychological Research Available at:
http://link.springer.com/10.1007/s00426-019-01211-4 [Accessed September 8, 2020].

Hickey C, Di Lollo V, McDonald JJ (2009) Electrophysiological Indices of Target and Distractor
Processing in Visual Search. Journal of Cognitive Neuroscience 21:760–775.

Hickey C, Peelen MV (2015) Neural Mechanisms of Incentive Salience in Naturalistic Human Vision.
Neuron 85:512–518.

Hickey C, Peelen MV (2017) Reward Selectively Modulates the Lingering Neural Representation of
Recently Attended Objects in Natural Scenes. J Neurosci 37:7297–7304.

Hupé JM, James AC, Payne BR, Lomber SG, Girard P, Bullier J (1998) Cortical feedback improves
discrimination between figure and background by V1, V2 and V3 neurons. Nature 394:784–787.

Ipata AE, Gee AL, Bisley JW, Goldberg ME (2009) Neurons in the lateral intraparietal area create a
priority map by the combination of disparate signals. Experimental Brain Research 192:479–488.

Ipata AE, Gee AL, Gottlieb J, Bisley JW, Goldberg ME (2006) LIP responses to a popout stimulus are
reduced if it is overtly ignored. Nature Neuroscience 9:1071–1076.

Itthipuripat S, Vo VA, Sprague TC, Serences JT (2019) Value-driven attentional capture enhances
989   distractor representations in early visual cortex Tong F, ed. PLoS Biol 17:e3000186.

990   Itti L, Koch C (2000) A saliency-based search mechanism for overt and covert shifts of visual attention.
991   Vision Research 40:1489–1506.

992   Jehee JFM, Ling S, Swisher JD, van Bergen RS, Tong F (2012) Perceptual Learning Selectively Refines
993   Orientation Representations in Early Visual Cortex. Journal of Neuroscience 32:16747–16753.

994   Jenkinson M, Bannister P, Brady M, Smith S (2002) Improved Optimization for the Robust and Accurate
995   Linear Registration and Motion Correction of Brain Images. NeuroImage 17:825–841.

996   Jenkinson M, Beckmann CF, Behrens TEJ, Woolrich MW, Smith SM (2012) FSL. NeuroImage 62:782–
997   790.

998   Jenkinson M, Smith S (2001) A global optimisation method for robust affine registration of brain images.
999   Medical Image Analysis 5:143–156.

Kamitani Y, Tong F (2005) Decoding the visual and subjective contents of the human brain. Nat Neurosci
8:679–685.

Karni A, Sagi D (1991) Where practice makes perfect in texture discrimination: evidence for primary visual
cortex plasticity. Proceedings of the National Academy of Sciences 88:4966–4970.

Kastner S (1998) Mechanisms of Directed Attention in the Human Extrastriate Cortex as Revealed by
Functional MRI. Science 282:108–111.

Kastner S, Pinsk MA, De Weerd P, Desimone R, Ungerleider LG (1999) Increased Activity in Human
Visual Cortex during Directed Attention in the Absence of Visual Stimulation. Neuron 22:751–761.

Kastner S, Ungerleider LG (2000) Mechanisms of Visual Attention in the Human Cortex. Annu Rev
Neurosci 23:315–341.

Kim H, Anderson BA (2019) Dissociable neural mechanisms underlie value-driven and selection-driven
attentional capture. Brain Research 1708:109–115.

Kristjansson A, Vuilleumier P, Schwartz S, Macaluso E, Driver J (2007) Neural Basis for Priming of Pop-
Out during Visual Search Revealed with fMRI. Cerebral Cortex 17:1612–1624.

Lawson CL, Hanson RJ (1974) Chapter 23. In: Solving Least-Squares Problems. Upper Saddle River,
New Jersey: Prentice-Hall.

Le Pelley ME, Mitchell CJ, Beesley T, George DN, Wills AJ (2016) Attention and associative learning in
humans: An integrative review. Psychological Bulletin 142:1111–1140.

Lewis-Peacock JA, Postle BR (2012) Decoding the internal focus of attention. Neuropsychologia 50:470–
478.

Li Z (2002) A saliency map in primary visual cortex. Trends in Cognitive Sciences 6:9–16.

Luck SJ, Chelazzi L, Hillyard SA, Desimone R (1997) Neural Mechanisms of Spatial Selective Attention in
Areas V1, V2, and V4 of Macaque Visual Cortex. Journal of Neurophysiology 77:24–42.

MacLean MH, Giesbrecht B (2015) Neural evidence reveals the rapid effects of reward history on
selective attention. Brain Research 1606:86–94.

Maljkovic V, Nakayama K (1994) Priming of pop-out: I. Role of features. Memory & Cognition 22:657–
672.

Maunsell JHR (2004) Neuronal representations of cognitive state: reward or attention? Trends in
Cognitive Sciences 8:261–265.

Mazer JA, Gallant JL (2003) Goal-Related Activity in V4 during Free Viewing Visual Search. Neuron
40:1241–1250.

Moher J, Egeth HE (2012) The ignoring paradox: Cueing distractor features leads first to selection, then
to inhibition of to-be-ignored items. Attention, Perception, & Psychophysics 74:1590–1605.

Moher J, Lakshmanan BM, Egeth HE, Ewen JB (2014) Inhibition Drives Early Feature-Based Attention.
Psychological Science 25:315–324.

Mostert P, Albers AM, Brinkman L, Todorova L, Kok P, de Lange FP (2018) Eye Movement-Related
Confounds in Neural Decoding of Visual Working Memory Representations. eNeuro
5:ENEURO.0401-17.2018.

Motter BC (1993) Focal attention produces spatially selective processing in visual cortical areas V1, V2,
and V4 in the presence of competing stimuli. Journal of Neurophysiology 70:909–919.

Mounts JRW (2000) Evidence for suppressive mechanisms in attentional selection: Feature singletons
produce inhibitory surrounds. Perception & Psychophysics 62:969–983.

Norman KA, Polyn SM, Detre GJ, Haxby JV (2006) Beyond mind-reading: multi-voxel pattern analysis of
fMRI data. Trends in Cognitive Sciences 10:424–430.

Ogawa T, Komatsu H (2006) Neuronal dynamics of bottom-up and top-down processes in area V4 of
macaque monkeys performing a visual search. Exp Brain Res 173:1–13.

Olivers CNL, Meijer F, Theeuwes J (2006) Feature-based memory-driven attentional capture: Visual
working memory content affects visual attention. Journal of Experimental Psychology: Human
Perception and Performance 32:1243–1265.

Pashler H, Shiu L (1999) Do images involuntarily trigger search? A test of Pillsbury's hypothesis.
Psychonomic Bulletin & Review 6:445–448.

Pelli DG (1997) The VideoToolbox software for visual psychophysics: transforming numbers into movies.
Spatial Vision 10:437–442.

Poltoratski S, Ling S, McCormack D, Tong F (2017) Characterizing the effects of feature salience and top-
down attention in the early visual system. Journal of Neurophysiology 118:564–573.

Rademaker RL, Chunharas C, Serences JT (2019) Coexisting representations of sensory and mnemonic
information in human visual cortex. Nat Neurosci 22:1336–1344.

Rao RPN, Ballard DH (1999) Predictive coding in the visual cortex: a functional interpretation of some
extra-classical receptive-field effects. Nat Neurosci 2:79–87.

Reavis EA, Frank SM, Greenlee MW, Tse PU (2016) Neural correlates of context-dependent feature
conjunction learning in visual search tasks. Hum Brain Mapp 37:2319–2330.

Reeder RR, Olivers CNL, Pollmann S (2017) Cortical evidence for negative search templates. Visual
Cognition 25:278–290.

Rungratsameetaweemana N, Serences JT (2019) Dissociating the impact of attention and expectation on
early sensory processing. Current Opinion in Psychology 29:181–186.

Saproo S, Serences JT (2010) Spatial Attention Improves the Quality of Population Codes in Human
Visual Cortex. Journal of Neurophysiology 104:885–895.

Sawaki R, Luck SJ (2010) Capture versus suppression of attention by salient singletons:
Electrophysiological evidence for an automatic attend-to-me signal. Attention, Perception, &
Psychophysics 72:1455–1470.

Schwartz S, Maquet P, Frith C (2002) Neural correlates of perceptual learning: A functional MRI study of
visual texture discrimination. Proceedings of the National Academy of Sciences 99:17137–17142.

Serences JT (2008) Value-Based Modulations in Human Visual Cortex. Neuron 60:1169–1181.

Serences JT, Saproo S (2012) Computational advances towards linking BOLD and behavior.
Neuropsychologia 50:435–446.

Serences JT, Yantis S (2006) Selective visual attention and perceptual coherence. Trends in Cognitive
Sciences 10:38–45.

Serences JT, Yantis S (2007) Spatially Selective Representations of Voluntary and Stimulus-Driven
Attentional Priority in Human Occipital, Parietal, and Frontal Cortex. Cerebral Cortex 17:284–293.

Serences JT, Yantis S, Culberson A, Awh E (2004) Preparatory Activity in Visual Cortex Indexes
Distractor Suppression During Covert Spatial Orienting. Journal of Neurophysiology 92:3538–
3545.

Silver MA, Ress D, Heeger DJ (2005) Topographic Maps of Visual Spatial Attention in Human Parietal
Cortex. Journal of Neurophysiology 94:1358–1371.

Smith SM, Jenkinson M, Woolrich MW, Beckmann CF, Behrens TEJ, Johansen-Berg H, Bannister PR,
De Luca M, Drobnjak I, Flitney DE, Niazy RK, Saunders J, Vickers J, Zhang Y, De Stefano N,
Brady JM, Matthews PM (2004) Advances in functional and structural MR image analysis and
implementation as FSL. NeuroImage 23:S208–S219.

Solomon SG, Kohn A (2014) Moving Sensory Adaptation beyond Suppressive Effects in Single Neurons.
Current Biology 24:R1012–R1022.

Somers DC, Dale AM, Seiffert AE, Tootell RBH (1999) Functional MRI reveals spatially specific
attentional modulation in human primary visual cortex. Proceedings of the National Academy of
Sciences 96:1663–1668.

Soto D, Heinke D, Humphreys GW, Blanco MJ (2005) Early, Involuntary Top-Down Guidance of Attention
From Working Memory. Journal of Experimental Psychology: Human Perception and
Performance 31:248–261.

Sprague TC, Adam KCS, Foster JJ, Rahmati M, Sutterer DW, Vo VA (2018a) Inverted Encoding Models
1097   Assay Population-Level Stimulus Representations, Not Single-Unit Neural Tuning. eNeuro
1098   5:ENEURO.0098-18.2018.

1099   Sprague TC, Boynton GM, Serences JT (2019) The Importance of Considering Model Choices When
1100   Interpreting Results in Computational Neuroimaging. eNeuro 6:ENEURO.0196-19.2019.

1101   Sprague TC, Itthipuripat S, Vo VA, Serences JT (2018b) Dissociable signatures of visual salience and
1102   behavioral relevance across attentional priority maps in human cortex. Journal of
1103   Neurophysiology Available at: http://www.physiology.org/doi/10.1152/jn.00059.2018 [Accessed
1104   March 20, 2018].

1105   Sprague TC, Serences JT (2013) Attention modulates spatial priority maps in the human occipital,
1106   parietal and frontal cortices. Nature Neuroscience 16:1879–1887.

1107   Spratling MW (2008) Predictive coding as a model of biased competition in visual attention. Vision
1108   Research 48:1391–1408.

1109   Spratling MW (2017) A review of predictive coding algorithms. Brain and Cognition 112:92–97.

1110   Srinivasan MV, Laughlin SB, Dubs A (1982) Predictive coding: a fresh view of inhibition in the retina. Proc
1111   R Soc Lond B 216:427–459.

1112   Stanisor L, van der Togt C, Pennartz CMA, Roelfsema PR (2013) A unified selection signal for attention
1113   and reward in primary visual cortex. Proceedings of the National Academy of Sciences
1114   110:9136–9141.

1115   Summerfield C, de Lange FP (2014) Expectation in perceptual decision making: neural and
1116   computational mechanisms. Nat Rev Neurosci 15:745–756.

1117   Swisher JD, Halko MA, Merabet LB, McMains SA, Somers DC (2007) Visual Topography of Human
1118   Intraparietal Sulcus. Journal of Neuroscience 27:5326–5337.

1119   Theeuwes J (1992) Perceptual selectivity for color and form. Perception & Psychophysics 51:599–606.

1120   Theeuwes J (2019) Goal-driven, stimulus-driven, and history-driven selection. Current Opinion in
1121   Psychology 29:97–101.

1122   Tong F, Pratte MS (2012) Decoding Patterns of Human Brain Activity. Annu Rev Psychol 63:483–509.

1123   Tootell RBH, Hadjikhani N, Hall EK, Marrett S, Vanduffel W, Vaughan JT, Dale AM (1998) The Retinotopy
1124   of Visual Spatial Attention. Neuron 21:1409–1422.

1125   Treisman AM, Gelade G (1980) A feature-integration theory of attention. Cognitive Psychology 12:97–
1126   136.

1127   Turatto M, Bonetti F, Pascucci D, Chelazzi L (2018) Desensitizing the attention system to distraction while
1128   idling: A new latent learning phenomenon in the visual attention domain. Journal of Experimental
1129   Psychology: General 147:1827–1850.

1130   Turatto M, Galfano G (2001) Attentional capture by color without any relevant attentional set. Perception
1131   & Psychophysics 63:286–297.

1132   Turatto M, Pascucci D (2016) Short-term and long-term plasticity in the visual-attention system: Evidence
1133   from habituation of attentional capture. Neurobiology of Learning and Memory 130:159–169.

1134   van Bergen RS, Jehee JFM (2019) Probabilistic Representation in Human Visual Cortex Reflects
1135   Uncertainty in Serial Decisions. J Neurosci 39:8164–8176.

1136   van Bergen RS, Ji Ma W, Pratte MS, Jehee JFM (2015) Sensory uncertainty decoded from visual cortex
1137   predicts behavior. Nat Neurosci 18:1728–1730.

1138   Van Moorselaar D, Slagter HA (2020) Inhibition in selective attention. Annals of the New York Academy
1139   of Sciences 1464:204–221.

1140   Vatterott DB, Vecera SP (2012) Experience-dependent attentional tuning of distractor rejection. Psychon
1141   Bull Rev 19:871–878.

1142   Wang B, Theeuwes J (2018a) Statistical regularities modulate attentional capture. Journal of
1143   Experimental Psychology: Human Perception and Performance 44:13–17.

1144   Wang B, Theeuwes J (2018b) How to inhibit a distractor location? Statistical learning versus active, top-
1145   down suppression. Attention, Perception, & Psychophysics Available at:
1146   http://link.springer.com/10.3758/s13414-018-1493-z [Accessed March 20, 2018].

1147   Westerberg JA, Cox MA, Dougherty K, Maier A (2019) V1 microcircuit dynamics: altered signal
1148   propagation suggests intracortical origins for adaptation in response to visual repetition. Journal
1149   of Neurophysiology 121:1938–1952.

1150   Wolfe JM (1994) Guided Search 2.0 A revised model of visual search. Psychonomic Bulletin & Review
1151   1:202–238.

1152   Won B-Y, Forloines M, Zhou Z, Geng JJ (2020) Changes in visual cortical processing attenuate singleton
1153   distraction during visual search. Cortex 132:309–321.

1154   Won B-Y, Geng JJ (2020) Passive exposure attenuates distraction during visual search. Journal of
1155   Experimental Psychology: General Available at:
1156   http://doi.apa.org/getdoi.cfm?doi=10.1037/xge0000760 [Accessed June 15, 2020].

1157   Zhang W, Luck SJ (2009) Feature-based attention modulates feedforward visual processing. Nat
1158   Neurosci 12:24–25.

1159   Zhang X, Zhaoping L, Zhou T, Fang F (2012) Neural Activities in V1 Create a Bottom-Up Saliency Map.
1160   Neuron 73:183–192.

1161