Reference ontology and database annotation of the COVID-19 Open Research Dataset (CORD-19)

Oliver Giles[1*], Rachael Huntley[1], Anneli Karlsson[1], Jane Lomax[1], and James Malone[1*]

[1]SciBite, Biodata Innovation Centre, Wellcome Genome Campus, Hinxton, CB10 1SD, UK
[*]Corresponding authors

Oliver Giles:
oliver.giles@scibite.com
James Malone:
james@scibite.com

Abstract The COVID-19 Open Research Dataset (CORD-19) was released in March 2020 to allow the machine learning and wider research community to develop techniques to answer scientific questions on COVID-19. The data set consists of a large collection of scientific literature, including over 100,000 full text papers. Annotating training data to normalise variability in biological entities can improve the performance of downstream analysis and interpretation. To facilitate and enhance the use of the CORD-19 data in these applications, in late March 2020 we performed a comprehensive annotation process using named entity recognition tool, TERMite, along with a number of large reference ontologies and vocabularies including domains of genes, proteins, drugs and virus strains. The additional annotation has identified and tagged over 45 million entities within the corpus made up of 62,746 unique biomedical entities. The latest updated version of the annotated data, as well as older versions, is made openly available under GPL-2.0 License for the community to use at: https://github.com/SciBiteLabs/CORD19

Keywords
CORD-19, COVID-19, ontology annotation, sentence co-occurrence

Introduction

In March 2020 in response to the COVID-19 pandemic, a consortium including The White House, AI2, CZI, MSR, Georgetown and NIH released an open research dataset along with a call for action [1] from the science and technology community. They called on artificial intelligence experts to develop new text and data mining techniques that can help the science community answer high-priority scientific questions related to COVID-19. The original dataset can be accessed at Kaggle: https://www.kaggle.com/allen-institute-for-ai/CORD-19-research-challenge

Data normalisation is an important step in the data preparation phase of many machine learning approaches [2]. The use of ontologies to normalise this data has shown improvements in various machine learning applications [3, 4]. Using ontologies to standardise descriptions of data also offers benefits in post-analysis. Using the same ontology identifiers in annotations can enable the integration of results across multiple disparate but similarly annotated data sets. The value of sharing well-annotated data has never been made clearer with the emergence of COVID-19 [5, 6] and it is this challenge we are addressing here.

To contribute to this call for action, in March 2020, and for the months following, we developed updated COVID-19 focused vocabularies replete with rich synonyms to identify relevant virus strain names, proteins and genes often studied with these viruses, and related entities such as gene functions and processes. These vocabularies use public identifiers where available from the likes of NCBI Taxon, Uniprot and the Gene Ontology. Using these vocabularies along with others describing indications, phenotypes, species, countries, genes, proteins and drugs, we applied our named entity recognition tool, TERMite, to annotate the entire CORD-19 data set. This has produced a richly annotated dataset with over ten million annotations, using 42,307 unique biomedically relevant entities. In order to facilitate the discovery of connections between entities in the corpus, we have produced a set of entity co-occurrences. This includes sentences which mention at least two entities, for instance a drug and gene. Because the vocabularies for identifying COVID-19 related terms are available, this can be used to filter for COVID-19 specific co-occurrences.

Method

The CORD-19 data set is described as "the most extensive machine-readable coronavirus literature collection available for data mining" [7]. As of September 2020, the data set contains over 200,000 scientific articles, including over 100,000 with full text, focusing on COVID-19, SARS-CoV-2, and other relevant or related coronaviruses. The data set is made available as a set of JSON documents, each document includes the title, authors, abstract, body text and detailed references (where appropriate).

To identify relevant concepts, a focused set of vocabularies was required with enrichments specific to concepts pertinent to COVID-19 research. The new COVID-19 specific vocabularies, and a set of existing vocabularies, mostly aligned to public ontologies (Table 1).

Table 1. Summary of the vocabularies used to annotate the CORD-19 data in this work.

Vocabulary	Origin reference	Description
SPECIES	NCBI Taxon	A curated classification and nomenclature for all of the organisms in the public sequence databases, currently representing about 10% of the described species of life on the planet.
GOONTOL	Gene Ontology	Concepts for describing the functions of gene products from all organisms.
INDICATION	MeSH	Hierarchically-organized vocabulary for indexing, cataloging, and searching of biomedical and health-related information.
SARSCOV	Gene Ontology, NCBI Taxon, Custom	Coronavirus strains and viral processes.
COUNTRY	ISO 3166-1	Standard country codes.
HPO	Human Phenotype Ontology	phenotypic abnormalities and clinical features encountered in human disease.
GENE	HGNC	Reference, approved human gene nomenclature.
CORONAPROT	Protein Ontology, Uniprot, Custom	COVID-19 strains and their human targets.
DRUG	ChEMBL	Curated database of bioactive molecules with drug-like properties.

To create the annotations for each document, was used a commercial named entity recognition engine (NER), TERMite (ref), using these vocabularies. For each section of text in the CORD19 JSON (titles, abstract parts and body parts), we injected a new block containing entities identified. The JSON block for each entity consisted of:

- a preferred name

- a unique identifier which in most cases was a URL for the relevant entity in its respective ontology

- a count of the number of times the entity was found in the section of text

- a list of the sentences in which the entity was found in the section of text

- a list of exact string locations for the sentences in which the entity was found in the section of text

By injecting these results back into the original JSON as an additional set of objects, we aimed to prevent any compatibility issues that would have arisen for individuals and groups who had already begun work with the initial release of this data.

To enable a more focused analysis, we also tabulated and transposed the annotated data (i.e. only sentences with annotations). In this case, we pivoted the data around the sentence, making the sentence the primary key, with attendant lists of entities identified in said sentence.

Results

TERMite identified over 45 million entities within the initial CORD19 release, consisting of 62,746 unique identifiers. It should be noted that some terms are represented in multiple ontologies. This is particularly common with, for example, phenotypes from the Human Phenotype Ontology and indications from MeSH. (Table 6) summarises the annotations as a result of the NER process for each of the different vocabularies used. (Figure 1) gives an example of a sentence in which three annotations were found from three vocabularies.

Table 2. Summary of the NER annotations across each vocab used.

Vocabulary	Total hits	Unique hits
SPECIES	9958967	3502
GOONTOL	6975073	10702
INDICATION	12998639	6360
SARSCOV	2629924	302
COUNTRY	2078689	228
HPO	3997204	5737
GENE	4018135	15714
CORONAPROT	795869	67
DRUG	2513491	20134

The number of unique hits for each vocabulary type was many orders of magnitude less than the number of total hits found. This is very common in large, focused areas of research - in this case anything COVID-19 relevant - as the target virus will be mentioned many times in a single article.

Table 3. Most frequent annotations found for each vocabulary.

Vocabulary	Most frequent hits
DRUG	Hydroxychloroquine
	Ribavirin
	Chloroquine
	Remdesivir
	Benzylpenicillin
	Oseltamivir
	Oseltamivir Carboxylic Acid
	Lopinavir
	Penicillin V
	Angiotensin
GENE	ACE2
	IL6
	IFNG
	TNF
	CD4
	CRP
	IL10
	IL1B
	IFNB1
	IFNA2

The data has now seen use in, for example, generating entity graphs using sentence co-occurrences as edges (Knowledge Graph Hub, 2020) or for combining evidence from multiple publication sources (Pub Annotation, 2020).

Conclusions

The value of well-annotated and accessible data on a global scale has never been more acutely apparent. The CORD-19 dataset and call to action channeled this need for rapid and innovative action from the community to help research and development into tackling this global challenge. Within weeks of this call in March 2020, we have released to the community annotated sentences which mention entities of biomedical relevance to COVID-

Figure 1. Example of a sentence containing three annotations. In this example, the virus name *COVID-19* is found, the GO term *transmission of virus*, and the MeSH indication *Coronavirus infection*.

Table 4. Most frequent annotations found for gene and drug vocabularies.

Vocabulary	Most frequent hits
SARSCOV	Severe acute respiratory syndrome coronavirus 2
	transmission of virus
	SARS Coronavirus
	viral life cycle
	incubation period
	viral genome
	viral release from host cell
	viral nucleocapsid
	SARS coronavirus NS-1
	viral strain
CORONAPROT	Angiotensin-converting enzyme 2
	spike glycoprotein (SARS-CoV-2)
	Spike glycoprotein
	Replicase polyprotein 1ab
	Replicase polyprotein 1a
	nucleoprotein (SARS-CoV-2)
	Nucleoprotein
	3C-like proteinase (SARS-CoV-2)
	Interleukin-6
	RNA-directed RNA polymerase (SARS-CoV-2)

Table 5. Most frequent annotations found for COVID-19 specific vocabularies.

Vocabulary	Most frequent hits
GOONTOL	binding
	pathogenesis
	behavior
	growth
	gene expression
	signal transduction
	cell death
	immune response
	learning
	female pregnancy
HPO	pneumonia
	fever
	neoplasm
	diarrhea
	asthma
	cough
	sepsis
	anxiety
	depressivity
	respiratory tract infection

19 and coronaviruses broadly, along with co-occurrences within sentences. The use of this data has already helped in developing knowledge graphs and data integration portals and it is our hope it will be put to further use in the data driven approaches used in 2020 and beyond.

Competing interests

All authors are employees of SciBite at time of writing. No other competing interests are declared.

Grant information

The authors declared that no grants were involved in supporting this work.

Acknowledgements

We would like to thank Chris Mungall for his suggestions on using the Protein Ontology and Lee Harland for his support on this work. We would also like to thank the Biohackathon community for their feedback on the data which has led to improvements in later versions.

References

[1] The White House. Call to action to the tech community on new machine readable covid-19 dataset, 2020. URL `https://www.whitehouse.gov/briefings-statements/call-action-tech-community-new-machine-readable-covid`. Accessed: 2020-03-30.

[2] M. Arora and V. Kansal. Character level embedding with deep convolutional neural network for text normalization of unstructured data for twitter sentiment analysis. *Social Network Analysis and Mining*, 9(12), 2019.

[3] O. Giles, A. Karlsson, S. Masiala, S. White, G. Cesareni, L. Perfetto, J. Mullen, M. Hughes, L. Harland, and J. Malone. Optimising biomedical relationship extraction with biobert: Best practices for data creation. *bioRxiv*, 2020. doi: https://doi.org/10.1101/2020.09.01.277277.

[4] Smaili F. Z., Gao X., and R. Hoehndorf. Self-normalizing learning on biomedical ontologies using a deep siamese neural network. *bioRxiv*, 2020. doi: https://doi.org/10.1101/2020.04.23.057117.

[5] E. M. Hechenbleikner, D. V. Samarov, and E. Lin. A call for collaboration with the tech industry data scrutiny. *EClinicalMedicine*, 23, 2020. doi: https://doi.org/10.1016/j.eclinm.2020.100377.

[6] B. Mons. The vodan in: support of a fair-based infrastructure for covid-19. *European Journal of Human Genetics*, 28:724–727, 2020. doi: https://doi.org/10.1038/s41431-020-0635-7.

[7] Kaggle. Covid-19 open research dataset challenge (cord-19), 2020. URL `https://www.kaggle.com/allen-institute-for-ai/`

Table 6. Example sentence level annotation.

Document ID	Sentence ID	Ontology URIs for annotation	TERMite short ID	Sentence location
PMC7091850.xml	title_1	http://purl.obolibrary.org/obo/NCBITaxon_2697049| https://id.nlm.nih.gov/mesh/D018352	SARSCOV#NCBITaxon_2697049| INDICATION#D018352	0-110
PMC7091850.xml	body_0_1	https://id.nlm.nih.gov/mesh/D018380	INDICATION#D018380	0-239
PMC7194468.xml	body_0_1	https://id.nlm.nih.gov/mesh/D009975| https://id.nlm.nih.gov/mesh/D007251| https://id.nlm.nih.gov/mesh/D007251	SPECIES#D009975 | INDICATION#D007251 | INDICATION#D007251	0-191

```
CORD-19-research-challenge.    Accessed:    2020-
09-24.
```