Scene wheels: Measuring perception and memory of real-world scenes with a continuous stimulus space

Gaeun Son, Dirk B. Walther, Michael L. Mack

Department of Psychology, University of Toronto, Toronto, ON, Canada

Author Note

This research was supported by Natural Sciences and Engineering Research Council (NSERC) Discovery Grants (RGPIN-2017-06753 to MLM and RGPIN-2020-04097 to DBW) and Canada Foundation for Innovation and Ontario Research Fund (36601 to MLM).

The datasets generated during and/or analyzed during the current study are available in the Open Science Framework repository (https://osf.io/h5wpk/) and none of the experiments was preregistered.

The authors declare no conflict of interest.

Correspondence concerning this article should be addressed to Michael L. Mack, Department of Psychology, University of Toronto, Sidney Smith Hall, 100 St George St, Toronto, ON M5S 3G3, Canada. E-mail: michael.mack@utoronto.ca

Abstract

Precisely characterizing mental representations of visual experiences requires careful

control of experimental stimuli. Recent work leveraging such stimulus control has led to

important insights; however, these findings are constrained to simple visual properties like

colour and line orientation. There remains a critical methodological barrier to characterizing

perceptual and mnemonic representations of realistic visual experiences. Here, we introduce a

novel method to systematically control visual properties of natural scene stimuli. Using

generative adversarial networks (GAN), a state-of-art deep learning technique for creating highly

realistic synthetic images, we generated scene wheels in which continuously changing visual

properties smoothly transition between meaningful realistic scenes. To validate the efficacy of

scene wheels, we conducted two behavioral experiments that assess perceptual and mnemonic

representations attained from the scene wheels. In the perceptual validation experiment, we

tested whether the continuous transition of scene images along the wheel is reflected in human

perceptual similarity judgment. The perceived similarity of the scene images correspondingly

decreased as distances between the images increase on the wheel. In the memory experiment,

participants reconstructed to-be-remembered scenes from the scene wheels. Reconstruction

errors for these scenes resemble error distributions observed in prior studies using simple

stimulus properties. Importantly, perceptual similarity judgment and memory precision varied

systematically with scene wheel radius. These findings suggest our novel approach offers a

window into the mental representations of naturalistic visual experiences.

Keywords: scene perception, generative adversarial network, continuous report paradigm, visual

working memory

Scene wheels: Measuring perception and memory of real-world scenes with a continuous

45   **stimulus space**

The ultimate goal for visual cognition research is understanding how people encode the

complexities of everyday visual experience into memory traces that can be retrieved moments to

hours to days later. A guiding principle of this research is the use of simple stimuli (e.g., spatial

frequency, orientation, or colour) to investigate various aspects of visual representation including

the capacity of iconic memory (Bradley & Pearson, 2012; Sperling, 1960), the storage structure

of visual working memory (VWM; Bays et al., 2009; Brady & Alvarez, 2011; Luck & Vogel,

1997; Zhang & Luck, 2008), and decay or bias of visual long-term memory (Magnussen et al.,

2003; Ester et al., 2020). Although decades of this research have characterized many facets of the

visual memory and perception system, it remains an important open question how these findings

based on simple visual stimuli generalize to memory for realistic visual environments. The key

limitation preventing such advances is the methodological hurdle of proper empirical control of

realistic scene stimuli.

The careful control of the physical properties of stimuli is a critical element for many

domains of cognitive psychology. By systematically manipulating physical properties of stimuli,

corresponding changes in task performance can be identified and leveraged to characterize

changes in cognitive ability. One prominent example is the change detection paradigm in VWM

studies in which participants have to detect any differences between two visual arrays presented

sequentially. By manipulating the physical properties of stimuli composing the visual arrays,

researchers can identify those features that are successfully encoded and remembered (Harrison

& Tong, 2009; Kiyonaga & Egner, 2016; Johnson et al., 2009; Lin & Luck, 2009; Luck &

Vogel, 1997; Wilken & Ma, 2004). For example, Lin & Luck (2009) manipulated the similarity

of target and foil object colours by measuring coordinate distance between the stimuli in CIE

(Commission Internationale de l'Elcairage) colour space (Smith & Guild, 1931). Based on this

deliberate manipulation, they demonstrated that visual working memory (VWM) performance

increases when target and foil colours are similar, a finding that speaks to a fundamental

relationship between a pervasive visual feature and how the visual memory system encodes it.

The level of stimulus control available for a feature like colour is, however, very difficult

to achieve in the real-world scene domain. Whereas colour spaces like CIE offer well-established

links between physical and perceptual similarity, the amount of information and complexity in

realistic scenes makes it difficult to define the similarity between any two scenes in a manner

that reflects human perception. One recent study (Konkle et al., 2010) took an indirect approach

to overcoming this challenge by manipulating the semantic similarity of target and foil scenes as

a proxy for visual similarity. The underlying assumption was that scene exemplars would share

similar visual properties to some extent if they are in the same semantic category (e.g., two

kitchens are more visually similar than a kitchen and bedroom). Certainly, many natural

categories exhibit family resemblance with shared visual properties; however, such semantic

manipulations are a noticeable departure from the deliberate manipulation of visual properties

like colour or orientation (Harrison & Tong, 2009).

The fine control of stimulus properties is essential for adapting new experimental

paradigms. Continuous report is a recently developed paradigm that makes it possible to more

directly observe a representational structure of the visual system (Bays & Husain, 2008; Wilken

& Ma, 2004; Zhang & Luck, 2008). In this paradigm, participants select the stimulus they

experienced using a highly controlled response scale that contains all possible stimulus options

used in the study and is organized such that visually similar items are adjacent in a continuous

visual feature space (e.g., a colour space). The advantage of this paradigm is that researchers can

quantify the representational error that a cognitive system makes when processing the inputs by

calculating the distance between the responded value and the actual target in the scale.

Specifically, when a substantial number of errors are accumulated by repeating trials, they can

typically observe a Gaussian shaped error distribution around the target, which is conceptually

well-matched with internal noise assumed to arise during the representation process. That is,

with an appropriate response scale, the error distribution can be interpreted as a reconstruction of

our mental representation.

Since it provides direct reconstructions of visual representation, the continuous report

paradigm has broadened our understanding of visual perception and memory. For example,

researchers have quantified more detailed aspects of visual representations like memory

precision or bias by quantifying how densely errors are distributed near the target or how the

central tendency of a response distribution is systematically shifted (Oh et al., 2019; Son et al.,

2020; Wilken & Ma, 2004). The VWM literature has leveraged a mixture model approach that

teases apart different components of the error distribution that are theorized to reflect

fundamental retention mechanism of VWM (Bays et al., 2009; Fournie et al., 2010; van den

Berg et al., 2012; Zhang & Luck, 2008; but see also Schurgin et al., 2020). Specifically, despite

some variations, the basic structure of the mixture model consists of a von-Mises distribution

that reflects the correct memory for the target with internal noise and a uniform distribution that

accounts for pure guessing. By fitting this mixture model to the data, mechanistically relevant

properties of error distributions can be identified, such as how often participants forget the

stimuli or how precisely they can remember the target.

Despite the apparent advantages of the experimental paradigm based on highly controlled

stimuli, to our knowledge no studies have attempted to use this approach to characterize

perceptual and memory representations for realistic scene environments. The key challenge

stems from the difficulty in stimulus control for real world scenes. To create a continuous

stimulus space, it is necessary to parametrically manipulate the targeted properties of the stimuli

(e.g., hue in colour wheel) such that changes occur without any abrupt transitions at a fine scale

with constant increments. Since this level of control is very hard to achieve in real-world scenes,

several studies have instead embraced continuous spaces of simple features in real-world stimuli

(Brady et al., 2013; Miner et al., 2020; Chanales et al. 2020; Sun et al. 2017). For example, Sun

et al. (2017) systematically manipulated colours of real-world objects and asked participants to

remember and report the colour of the target object under a continuous report paradigm. Based

on the mixture model, they are able to distinguish behaviour driven by complete forgetting of

stimulus information (guessing) from less precisely remembered information (decrement in

precision). They found that colour memory for a target object can experience both modes of

failure depending on colour similarity between target and distractor objects. However, since

colour is only one attribute of the object stimuli, findings from this approach are more likely to

reflect colour memory itself rather than reflecting the integrative nature of object memory.

Moreover, although this work represents a departure from typical VWM paradigms based on

arrays of coloured squares or circles, it is unclear how continuous colour space manipulations

can be extended to real-world scenes. Not only are real-world scenes composed of multiple

objects, each with their own primary colour, but much of rapid scene perception and

categorization has little to do with colour information and these processes can even be hampered

when a scene's major color scheme is abonormal (Castelhano et al., 2008; Delorme et al., 2000;

Goffaux et al., 2004).

Conceptually, a continuous stimulus space for real world scenes should depend on the

complex features critical for distinguishing between scene categories (Walther & Shen, 2014;

Wilder et al., 2019). Characterizing such features has been a key question in scene perception for

decades (Davenport & Potter, 2004; Greene & Oliva, 2009; Kauffmann et al., 2015; Oliva &

Schyns, 2000; Oliva & Torralba, 2001; Schyns & Oliva, 1994; Walther et al., 2011); however,

the recent revolution in deep learning approaches from machine learning and computer vision

have provided novel insights into the nature of features underlying visual categorization (Cichy

et al., 2017; Eberhardt et al., 2016; Krizhevsky et al., 2012; Rezanejad et al., 2019; Zhou et al.,

2017; for review, Serre, 2019). In particular, generative adversarial networks (GAN; Brock et al.,

2018; Goodfellow et al., 2014; Karras et al., 2019; Shocher et al., 2020; Yang et al., 2019) offer a

data-driven method for uncovering the complex features spaces necessary for generating

artificial but highly realistic images. GANs are composed of two deep neural networks, a

generative network and a discriminative network, which perform antagonistic tasks. The

generative network produces artificial images from random inputs while the discriminative

network distinguishes real photographs from the artificial images synthesized by the generative

network. These networks are placed in opposition with the generative network aiming to

generate synthesized images that fool the discriminative network, and the discriminative network

adapting to correctly categorize real from synthetic. Thus, the GAN is set to train the generative

network so as to minimize the performance of the discriminative network. After successful

learning, the synthesized images created by the generative network are highly realistic even to

human observers. Recent studies of scene specific GANs (Shocher et al., 2020; Yang et al.,

2019) have demonstrated that latent spaces from trained generative networks show a meaningful

organization such that adjacent vectors in latent space are highly similar to each other and their

associated synthetic images represent continuously changing realistic scenes. These advances

offer a unique possibility – a continuous space of natural scene images may be constructed by

deliberately traversing the latent space of a GAN trained to synthesize scene images.

In the current study, we test whether a scene space synthesized from a GAN can be used

to generate continuous scene stimulus sets for the investigation of human perception and

memory. To do this, we leveraged a GAN trained on natural scene images (Yang et al., 2019)

and designed the way we select latent vectors such that the synthesized output results in a

continuously changing scene space. Specifically, we sought to generate circular scene spaces,

which we call scene wheels, akin to colour or orientation wheels that continuously traverse a

stimulus space with no specified start and end points. To do this, we selected a set of latent

vectors located on an imaginary circle in latent space and generated the associated synthetic

scene images. In particular, we parametrically manipulated the radius of the circles in latent

space to explore how the generated scenes vary depending on distances between their latent

vectors, and how this variation affects human perception and memory performance. To assess

and validate the continuous nature of changes throughout the scene wheels, we conducted a

perceptual similarity judgment task with the scene images and compared it with pixel-wise

correlations of the images. We anticipated that if our approach to generating scene wheels

actually reflected the latent scene spaces fundamental to human scene perception, scene wheels

with larger radii should be perceived as less similar. We found clear evidence of this pattern and

also confirmed that this pattern is reflected in pixel-wise correlations of the scene images. In

addition, we hypothesized that images on the larger wheel should be remembered with higher

precision, because other images neighboring the to-be-remembered scene would interfere less

with participants' memories. To test this hypothesis, we conducted a VWM experiment using a

delayed estimation task based on the continuous report paradigm. Participants successfully

remembered and reconstructed scene images from the scene wheels in their WM, and the

observed error pattens are consistent with typical error distributions observed from similar

experiments with simple stimuli (Bays & Husain, 2008; Wilken & Ma, 2004; Zhang & Luck,

2008). Critically, the radius of the scene wheels was associated with memory precision. Our

work provides a novel method to measure memory performance of realistic scene stimuli as well

as a new class of highly controllable scene stimuli for a range of experiments on scene

perception and memory.

Methods

Participants

Perceptual similarity judgment. One hundred and twenty eight participants (25 females,

101 males, 1 other, 1 missing, mean age = 34.88) were recruited online through Amazon

Mechanical Turk. We excluded 28 of the participants from the main analysis based on the

criterion explained in the *Analysis* section (screening rate = 21.87 %). This sample size was

determined for the purpose of collecting a sufficient amount of data to validate all 25 wheels. All

participants reported normal or corrected-to-normal vision and received monetary compensation

for their participating.

Delayed estimation. 20 participants (16 females, 4 males, 0 other, mean age = 23.31) with

normal or corrected-to-normal vision were recruited from University of Toronto. The experiment

was conducted online and all participants were compensated with monetary rewards. The

targeted sample size was pre-determined based on a power analysis from a pilot experiment

(N=17). The power analysis focused on the fixed effect of scene wheel radius as defined in a

mixed effect regression model (see details in Analysis) and was conducted using the SIMR

package (Green & MacLeod, 2015) in R 3.6.1 (R Core Team, 2019). A power curve was

estimated by simulating 100 datasets and refitting the regression model to each simulated dataset

for each of a range of sample sizes from 4 to 19 participants. The results showed that with a

sample size of only 4, the estimated power reached 95% (CI [88.72, 98.36]). Thus, we decided to

collect 20 participants for the main experiment, a similar number with the pilot experiment. The

study protocol was approved by University of Toronto Research Ethics Board.

Stimuli

The continuous scene space, or the scene wheel, was generated using the StyleGAN

model trained with a mixed image pool of three indoor scene categories – bedrooms, living

rooms, and dining rooms (Yang et al., 2019). The training image set included 500,000 scenes per

scene category all of which were selected from the LSUN dataset (Yu et al., 2015). Generating

scene wheels from this GAN required a systematic approach to sampling the latent vectors of the

generative model. First, we randomly sampled three latent vectors and defined a plane by

calculating the vector cross products of the three vectors. On that plane, an imaginary circle was

drawn around the center point of the three seed vectors. We then selected 360 points equally

spaced by 1-degree unit on the imaginary circle (Figure 1). The extracted points were fed into the

generative network as input and synthesized into natural-looking scene images. Figure 2 shows

the images synthesized by this procedure, including images representing 5 different center points

and the images generated from one of those center points (see Supplementary video for all

images at https://osf.io/h5wpk/).

Figure 1. A simple scheme of wheel generation procedure. The selected points on the imaginary
circles (third stage) were used as input to the generator.

228
229

230
We also examined how composite images of a scene wheel are affected by differences in

radii of the wheel in the latent space. To do this, we created separate imaginary circles by

repeatedly doubling the radius while maintaining the center of the circle. Scene wheels with

smaller radii resulted in scenes with few changes in their visual properties (Figure 2B) whereas

circles with larger radii contain less similar images with larger changes (Figure 2C). This pattern

was highly consistent across scene wheels generated from different origins. We chose 5 different

radii (2, 4, 8, 16, and 32 a.u.) to test whether perception and memory performance systematically

changes with radius. Since we generated different types of wheels from 5 different origins, a

total of 25 wheels were created.

Figure 2. A) Images corresponding to the center points of the five wheels. B & C) Example images of two scene wheels that share the same centre point but vary in radius. The images in these panels are equally spaced by 20 degrees from 0 to 340 degrees. B) 18 example images from Wheel05 with radius of 8. The top-left and bottom-right scenes are located at neighboring locations on the wheel (0 and 350 degrees) thus are very similar. C) 18 examples from Wheel05 with radius 32. Compared to B, the changes between images are larger.

The wheels generated through this process were validated with behavioral experiments

for perception and memory. For the perceptual validation, we sampled 12 scene images at 30-

degree intervals and created 66 unique pairs in each wheel for the pair-wise similarity judgment

task. We generated 360 images from each wheel in one-degree intervals for the working memory

experiment using the continuous report paradigm. To test the full range of each scene wheel, we

divided each wheel into 20-degree bins and randomly selected three scene images from each bin

as targets for each participant. Due to the web-based nature of the study, the image stimuli were

displayed at different sizes depending on the individual participant's monitor settings. The

images occupied 20% of the monitor width and were presented with a square aspect ratio. Note

that the experiment was set to be run only on laptop or desktop computers, but not on

smartphones or tablets.

Procedure & Design

Perceptual similarity judgment. In each trial, a pair of scene images was shown side by

side along with a 6-point Likert scale (Figure 3A). Participants were asked to click a score on the

scale according to how similar they think the two images are (see the demo version of the

experiment: https://macklab.github.io/sceneWheel_similarityJudgment/demo.html). Before

starting the main session, participants completed a set of 10 practice trials using scene pairs from

a wheel not used in the main session. Those scene pairs were selected to represent the full range

of physical similarity (pixelwise correlation coefficients) so that participants could calibrate to

the potential range of pair similarity. The full experimental design was 5 (between-subject

variable: different center points) x 5 (within-subject variable: wheel radii) x 66 (image pairs per

wheel, combination of 2 in 12 images with no replacement). 20 participants were recruited for

each center point condition. Each participant completed 340 trials, which consisted of 330 main

trials (66 image pairs x 5 radii condition) and 10 catch trials that showed identical images. The

catch trials were used for screening participants who showed bad performance and were thus

excluded from main analysis.

Delayed estimation. The procedure followed the conventional delayed estimation task in

visual working memory (Wilken & Ma, 2004) with a small variation on display durations. Each

trial began with a memory display with a target scene image (1 sec) and followed by a short

retention interval for approximately 1 second. After the retention interval, a response display

with a gray box and indicator wheel was presented. Once participants moved their computer

mouse, the gray box was replaced with a random scene within the scene wheel. Thereafter, the

scene shown changed according to the mouse position. By moving the mouse cursor along the

indicator wheel, participants were asked to find a scene that closely matched the target scene

presented in the memory display. Participants responded with their best matching scene

candidate by clicking the left mouse button. To avoid effects of location memory, the probe

scene wheel was randomly rotated in each trial. An example trial sequence is depicted in Figure

3B (demo experiment: https://macklab.github.io/sceneWheel_main/demo.html).

We used a mixed design with 5 (between-subject variable: 5 different center points) x 5

(within-subject variable: wheel radius) conditions. 4 participants were recruited for each scene

wheel and each participant performed 270 trials (54 trials for all 5 radius levels of a single scene

wheel). Before starting the main experiment, participants completed 5 practice trials. During the

main experiment, short breaks were given every 54 trials.

Figure 3. A. Example trial of perceptual similarity judgment task. B. Example trial sequence of delayed estimation.

Analysis

Perceptual similarity judgment. We quantified the perceptual similarity of the scene

images on wheels to confirm the continuous nature of scene images along their position on the

wheel. Before the analysis, we excluded 28 participants who showed poor performances on the

task based on a two-step exclusion process. First, we analyzed the performance in the 10 catch

trials, in which identical images were shown side by side. Participants who rated more than 70%

of the catch trials below the score of 4 were excluded in this step. Second, we excluded data if

the distribution of rating responses showed extremely large kurtosis over 5. These participants

rated most of the trials with a single score. We excluded 28 participants in total, 14 in step 1 and

14 in step 2. The similarity scores of the final 100 participants were normalized to the range

between 0 and 1 and averaged across the respective set of 20 participants who viewed the wheels

with the same center point (Figure 4). For a direct illustration of the continuous similarity

pattern, we sorted the mean similarity scores of all pairs according to their angular distance on

the scene wheel (Figure 6A).

Pixel-wise correlation. For practical reasons, we obtained perceptual similarity ratings

only for 12 images per scene wheel, spaced 30 degrees apart. Assessing physical similarity

between the images, however, poses no such constraints. We quantified physical similarity

between all 360 images in each wheel by computing their pixel-wise correlation (Figure 5). For

better illustration, we again sorted the correlation coefficients of the pairs according to their

angular distance on the scene wheel, by averaging all Fisher-z transformed correlation

coefficients with the same pair distance (Figure 6B). We compared the physical and perceptual

similarity scores by conducting Spearman's rank correlation between the lower triangle of the

perceptual similarity matrices and the corresponding values from the pixel-wise correlation

matrices.

Delayed estimation. To examine whether memory performance corresponds to

perceptual similarity changes among different radii, we measured memory response errors and

calculated circular standard deviation (SD) of errors in each radius condition. First, response

errors for each trial were calculated by subtracting the target angle from the angle of the response

that participants made in each trial. After sorting the response errors into 5 radius conditions and

5 center point conditions, we calculated circular SDs from the response error distributions using

the circular package (Agostinelli & Lund, 2017) in R 3.6.1 (R Core Team, 2019). Then, we

applied a linear mixed-effects model that predicts circular SDs with a fixed effect of the wheel

radii and the random effect of participants using the LME4 package (Bates et al., 2015).

Results

Perceived similarity pattern. To evaluate the perceptual similarity pattern of scene

wheels, we collected similarity rating scores of all pairs of 12 composite scenes (66 pairs) in

each wheel (Figure 4). Diagonal burgundy lines indicate image identity – these were not assessed

in the experiment, except in 10 catch trials. Across all center point conditions, we consistently

observed that images on the wheels with smaller radii were perceived as more similar, depicted

by warmer colors. This result supports our anticipation that wheels with smaller radii contain

more similar images because the corresponding latent vectors are located closer to each other.

For each wheel, we also observed a graded color transition: cells closer to the diagonal line show

higher similarity rating scores (warm colours), whereas farther cells show lower scores (cool

colours). To further examine this pattern, we averaged the similarity scores of image pairs whose

angular differences are the same on the wheel (Figure 6A). Across all center points with all radii,

mean similarity rating scores of image pairs continuously decrease as their angular distances on

the wheel increase, indicating that pairs of scenes become less similar the further apart they are

located on the scene wheel. Moreover, the drop-off gets steeper for larger radii, again showing

that similarity of scenes systematically varies with the wheel radius.

Figure 4. Perceptual similarity matrices. Each row indicates wheels with a different center point. Each column corresponds to a different radius. Across center points, smaller radii show higher correlation depicted by warmer color.

Pixel-wise correlation. Figure 5 shows the pixel-wise correlation matrices of all scene

wheels. Similar to the perceptual similarity matrices, we again observed that images on the

wheels with smaller radii and closers to the diagonal show higher correlation coefficients. Figure

6B shows the mean coefficient values sorted by the angular differences. We could observe the

gradual decrease of correlation coefficients, comparable to the pattern of perceived similarity

scores in the upper panel. This comparability between the physical and perceptual similarity of

the scene wheels was confirmed by a high correlation between the lower triangles of the

similarity matrices of the two measurements, averaged across all wheels (mean Spearman's $\rho =$

0.63; mean computed under Fisher's-z transformation).

Figure 5. Pixel-wise correlation matrices. Each row shows the correlation results of wheels with different center points. Each column corresponds to a different radius. Across center points, smaller radii show higher correlation depicted by warmer color.

Figure 6. A. Mean perceptual similarity rating scores aligned by the angular differences on each scene wheel. Values at 0 degrees (identical pairs) are set to one. B. Mean correlation coefficients aligned by the angular difference within each scene wheel. In both A and B, similarity values drop off as the angular differences get larger across all wheels. The steepness of the drop-off depends on the wheel radius.

Working memory performance. We tested if the changes in physical and perceptual

properties of scene wheels confirmed in the previous section are reflected in human memory.

Specifically, we conducted the VWM experiment using the continuous report paradigm to test if

scene wheels with larger radii where composite scenes look less similar are remembered more

precisely. The error distributions of each radius condition are provided in Figure 7A. The

observed error distributions resemble Gaussian distributions, as reported in previous studies

using the continuous report paradigm and simple stimuli (Husain & Bays, 2009; Wilken & Ma,

2004; Zhang & Luck, 2008; see *Direct comparison to previous studies* section for details). We

then applied a linear mixed-effects model to the data to predict memory precision represented by

circular SDs of errors with radii of the wheels, since we hypothesized that memory precision

would increase with larger radius. As expected, we observed that a strong effect of the radius on

circular SDs ($F(1, 79) = 205.32$, $p < .001$), suggesting that memory precision increases with the

increment of wheel radius (note that smaller circular SD indicates higher memory precision).

Then, we further explored the effect of the center points to see if it affects the memory precision

in addition to the radius by estimating a linear mixed model that included the interaction between

the wheel type and radius. Relative to the first model with only the radius factor, we found that

the interaction model explained the data better ($\chi^2(8) = 21.48$, $p = .006$). The interaction of the

wheel type and radius was significant ($F(4, 75) = 4.22$, $p = .004$), which is reflected in slightly

different slopes of the wheel types (Figure 6B). Despite these slight differences in the magnitude

of the effect across wheel types, we found that participants' memory for the realistic scenes was

more precise with larger radii, and this increasing pattern of memory precision along the

increment of radius is not limited to specific wheels but a common effect that can be applied to

all wheels.

A

B

Figure 7. A. Histograms of response errors in each radius condition. All participants' data and corresponding wheel type conditions are aggregated. Density of the histograms decreased with increasing radii (from left to right panel). Bin width is 5 degrees. Individual participant data are available in the Supplementary Figures. B. Decreasing pattern of circular SDs of the response errors with increasing radius, indicating that memory precision increases with increasing radius. Error bars: 95% confidence intervals.

387
388
389

Direct comparison to previous studies. We further examined the resemblance of the

changes in circular SDs between our study and previous studies conducted with simple stimulus

domains (Bays & Husain, 2008; Wilken & Ma, 2004; Zhang & Luck, 2008). These studies

reported gradual changes in the circular SDs of error distributions with increasing set size (the

number of items held in VWM), a factor commonly utilized to control the difficulty of memory

experiments. In our study, we also found a gradual change of circular SDs with increasing radii

of the scene wheels, which served as a similar control of task difficulty. Thus, we checked how

the circular SDs of our error distributions relate to the circular SDs observed in the previous

studies. We found that the range of circular SDs in our study spans the range of the previously

reported SDs (Figure 8). We conclude that the error distributions obtained using scene wheels

resemble the error distributions from other, simpler stimulus domains.

Figure 8. Illustration of observed error SD ranges. The range of the current study (top row,
scene wheel) spans the ranges of error SDs observed by the other studies.

404
Discussion

We demonstrated that continuous scene spaces generated with a GAN provide a novel

tool to measure visual perception and memory performance for complex realistic scenes.

Specifically, we confirmed that by carefully selecting latent vectors from a pretrained GAN, the

similarity among scene images can be well controlled, allowing for a continuously changing

traversal of meaningful scene space. With the generated scene wheels, we validated the

perceived similarity of the generated scene images using pairwise similarity judgment. We

observed that participants' similarity judgments corresponded to the images' distance on a

wheel. Also, this perceived similarity pattern was highly correlated with pixel-wise correlation,

suggesting that pixel-wise correlation provides a proxy to examine the continuous nature of

newly generated wheels according to perceptual similarity without further empirical validation.

For mnemonic validation, we conducted a visual working memory experiment using the

continuous report paradigm. We observed that the error distribution from the participant's

responses was comparable with the typical error distribution that previous studies observed from

simple stimuli like colours. Critically, we additionally manipulated the radii of the wheels in the

latent space to parametrically control the similarity among the scenes in the wheels. We found

clear evidence that participants' memory systematically varied with this manipulation of scene

similarity as predicted. Therefore, we suggest that this novel method to generate scene stimuli

using a GAN not only allows for an unprecedented level of stimulus control for complex scene

stimuli, but also that the latent spaces generating our scene wheels reflect fundamental

representational spaces important for human scene perception and memory.

As is evident in the perceptual similarity measures, pixelwise correlation, and memory

validation study, the latent GAN space is complex with regions of inhomogeneity. This means

that scene wheels generated from different center points will likely include distinctive scene

properties that uniquely impact perceptual and mnemonic similarity. It is important to consider

this limitation if the empirical goal is targeting perfect generalization of specific effects across

different scene wheels. However, despite these small scene wheel-specific variations, we

observed a reliable and consistent pattern of perceptual and mnemonic performance on different

scene wheels. We anticipate that the level of control achieved with the stimuli generated from the

GANs will be valid for the majority of experiments investigating perception and memory of real-

world scenes.

Based on this level of control over the scene stimulus space, we expect that findings from

using simple stimuli, such as colour wheels, can be generalized to photo-realistic scenes. First

and foremost, our approach can be leveraged to measure memory performance for scenes at a

fine level of granularity that was not available previously for realistic scenes. In the recognition

paradigm, for example, our methods could be utilized to parametrically control the perceptual

similarity between target and foil scenes to systematically test how scene similarity affects

memory interference or confusion (Konkle et al., 2010; Lin & Luck, 2009). In using a

continuous report paradigm with the GAN-based scene wheels, as we did here, one can measure

specific components of scene memory, such as precision or bias, on a continuous scale. Coupling

the current approach with cognitive models like the mixture model allows for quantitative

estimates of memory capacity and errors for scenes in the same way conventionally done for

simpler stimuli (Bays et al., 2009; Brady & Alvarez, 2011; Fournie et al., 2010; Son et al., 2020;

Sun et al., 2017; van den Berg et al., 2012; Wilken & Ma, 2004; Zhang & Luck, 2008).

Additionally, the continuous scene space can be utilized in any paradigm that requires carefully

controlled stimuli. Given that simple stimuli and realistic scenes have notable differences in their

complexity and the amount of information, comparing the results from those levels of stimuli

will contribute to elaborating how memory processes change along the visual hierarchy and

provide testable predictions for neural function and representation.

The scene space from the GAN has the potential to achieve even more deliberate control

over particular scene properties. Recent studies showed that different layers of the generative

network in GANs represent different properties of the scenes (Karras et al., 2019; Schocher et

al., 2020; Yang et al., 2019). By manipulating the latent vectors in a layer-wise manner, one can

exclusively control specific properties of the scenes that the targeted layer addresses, while the

other properties remain the same. For example, Yang et al. (2019) suggested that a visual

hierarchy emerges in layers of the generative network such that low-level scene properties like

layout are processed in lower layers while higher-level properties like detailed attributes of the

scene (e.g. composite objects, materials of the objects, lighting condition of the scenes, etc.) are

processed in higher layers. By manipulating the latent vector in certain layers, GANs are able to

synthesize a set of scenes with parametrically different attributes (e.g. lighting, amount of clutter)

but with limited changes in the other properties (e.g. layout and category). Based on this layer-

wise manipulation, future studies may investigate various level of information embedded in

realistic scenes, while minimizing effects from uncontrolled properties.

468   Our study is not the first attempt to generate realistic stimuli on a continuous scale.

Previous studies took an approach to morph stimuli with assigning different weights to each

reference stimulus in the various stimulus domains such as animal species (Freedman et al.,

2001; 2003), real-life objects (Newell & Bülthoff, 2002), cars (Folstein et al., 2012; Jiang et al.,

2007), or faces (Beale & Keil, 1995; Goldstone & Steyvers, 2001; Haberman & Whitney, 2007;

Steyvers, 1999). This approach allowed participants to respond on a continuous scale similar to

our study. However, to get a continuous interpolation between morphing references, the

reference images need to be similar and well matched in terms of their physical status. For

example, to continuously manipulate the emotion of faces, reference faces should be closely

matched in properties like identity, gender, and spatial configuration of the facial components

(e.g. eyes, nose, and lips), which requires time-consuming preprocessing by researchers to utilize

the morphing algorithm per se. For this reason, the morphing approach was restricted to stimulus

domains with little physical variance among the exemplars (e.g. faces have fewer physical

variances than scenes). Our approach using a GAN, however, can be applied to highly complex

naturalistic scenes since it utilizes neural networks trained on a large set of photographs and thus

creates a large latent space of possible images. That is, each GAN's latent space itself can be

considered as a huge geometrically structured image database with high controllability.

Synthesizing realistic images using the GANs, therefore, will expand the range of stimulus

domains that can be successfully adapted in visual cognition studies.

Some recent studies in the visual memory field have adapted a different measurement

paradigm, free recall, to target memory precision (Bainbridge et al., 2019; Bainbridge & Baker,

2019). In this paradigm, as conveyed by its name, participants are asked to freely recall whatever

they can remember after seeing the scene images by drawing the scenes. Since this paradigm

does not require foil images to be compared to the target representation in memory, it measures

memory representations more directly and provides insights into the details of the nature of scene

memory, such as what information is remembered from the scene, and how much detail survived

during retention. Nevertheless, this paradigm has practical challenges. Drawing is a qualitative

measurement that needs to be scored using intrinsically subjective judgments for use as a

quantitative measurement. This means that the measurement procedure in this paradigm requires

at least two steps, drawing and assessment of drawing by a third person. Considering that the

assessment is usually conducted by at least hundreds of participants, this is a labor-intensive

paradigm. The other issue is that the drawing behavior itself could confound accurate

measurement of memory performance. For many people, drawing is cognitive demanding

requiring cognitive resources other than visual memory such as active hand movement or visual

attention to the elements currently drawn, which could affect the retrieval process. Also, since

drawing a complex scene often requires a substantial amount of time, the memory representation

could suffer from memory decay. We believe that the technique proposed here can be another

option for a fine-grained measurement of scene representation with more practical benefits.

Scenes generated from the GANs, however, can have a drawback in terms of synthesis

quality. Depending on the pretrained GAN's performance, synthetic scenes can sometimes

include artifacts or "nonsense" regions (although in our experience, such scenes remain highly

realistic and interpretable). Thus, it is key to first select well-trained GAN models and manually

evaluate the generated scenes in preparation for conducting an experiment. We provide our scene

wheel sets that are already tested with human participants in the current experiment

(https://osf.io/h5wpk/) to help researchers to skip this procedure.

In conclusion, we anticipate that the continuous scene space approach proposed here will

quickly be adopted as a fundamental tool for measuring scene representations. Going beyond the

working memory experiment demonstrated here, we foresee that the scene wheels can be utilized

in any domain that needs fine measurement and adjustment methods for realistic scenes. In

leveraging this approach, we anticipate that future work will provide key insights into how we

perceive and remember the real-world naturalistic environments that serves as the backdrop to

our everyday experiences.

References

Agostinelli, C., & Lund, U. (2017). R package circular: Circular Statistics (version 0.4–93), CA:

Department of Environmental Sciences, Informatics and Statistics, Ca'Foscari

University, Venice, Italy. *UL: Department of Statistics, California Polytechnic State*

University, San Luis Obispo, California, USA.

Bainbridge, W. A., & Baker, C. I. (2020). Boundaries Extend and Contract in Scene Memory

Depending on Image Properties. *Current Biology*, *30*(3), 537-543.

Bainbridge, W. A., Hall, E. H., & Baker, C. I. (2019). Drawings of real-world scenes during free

recall reveal detailed object and spatial information in memory. *Nature*

communications, *10*(1), 1-13.

Bates D, Mächler M, Bolker B, Walker S (2015). "Fitting Linear Mixed-Effects Models Using

lme4." *Journal of Statistical Software*, **67**(1), 1–48. doi: 10.18637/jss.v067.i01.

Bays, P. M., Catalao, R. F., & Husain, M. (2009). The precision of visual working memory is set

by allocation of a shared resource. *Journal of vision*, *9*(10), 7-7.

Bays, P. M., & Husain, M. (2008). Dynamic shifts of limited working memory resources in

human vision. *Science*, *321*(5890), 851-854.

Beale, J. M., & Keil, F. C. (1995). Categorical effects in the perception of

faces. *Cognition*, *57*(3), 217-239.

Bradley, C., & Pearson, J. (2012). The sensory components of high-capacity iconic memory and

visual working memory. *Frontiers in psychology*, 3, 355.

Brady, T. F., & Alvarez, G. A. (2011). Hierarchical encoding in visual working memory:

Ensemble statistics bias memory for individual items. *Psychological science*, *22*(3), 384-

392.

Brady, T. F., Konkle, T., Gill, J., Oliva, A., & Alvarez, G. A. (2013). Visual long-term memory

has the same limit on fidelity as visual working memory. *Psychological science*, *24*(6),

981-990.

Brock, A., Donahue, J., & Simonyan, K. (2018). Large scale gan training for high fidelity natural

image synthesis. *arXiv preprint arXiv:1809.11096*.

Castelhano, M. S., & Henderson, J. M. (2008). The influence of color on the perception of scene

gist. *Journal of Experimental Psychology: Human perception and performance*, *34*(3),

660.

Chanales, A. J., Tremblay-McGaw, A. G., & Kuhl, B. A. (2020). Adaptive repulsion of long-

term memory representations is triggered by event similarity. *bioRxiv*.

Cichy, R. M., Khosla, A., Pantazis, D., & Oliva, A. (2017). Dynamics of scene representations in

the human brain revealed by magnetoencephalography and deep neural

networks. *NeuroImage*, *153*, 346-358.

Davenport, J. L., & Potter, M. C. (2004). Scene consistency in object and background

perception. *Psychological science*, *15*(8), 559-564.

Delorme, A., Richard, G., & Fabre-Thorpe, M. (2000). Ultra-rapid categorisation of natural

scenes does not rely on colour cues: a study in monkeys and humans. *Vision*

research, *40*(16), 2187-2200.

Eberhardt, S., Cader, J. G., & Serre, T. (2016). How deep is the feature analysis underlying rapid

visual categorization?. In *Advances in neural information processing systems* (pp. 1100-

1108).

Ester, E. F., Sprague, T. C., & Serences, J. T. (2020). Categorical biases in human

occipitoparietal cortex. *Journal of Neuroscience*, *40*(4), 917-931.

Folstein, J. R., Gauthier, I., & Palmeri, T. J. (2012). How category learning affects object

representations: Not all morphspaces stretch alike. *Journal of Experimental Psychology:*

Learning, Memory, and Cognition, *38*(4), 807.

Fougnie, D., Asplund, C. L., & Marois, R. (2010). What are the units of storage in visual

working memory?. *Journal of vision*, *10*(12), 27-27.

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2001). Categorical representation

of visual stimuli in the primate prefrontal cortex. *Science*, *291*(5502), 312-316.

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2003). A comparison of primate

prefrontal and inferior temporal cortices during visual categorization. *Journal of*

Neuroscience, *23*(12), 5235-5246.

Goffaux, V., Jacques, C., Mouraux, A., Oliva, A., Schyns, P. G., & Rossion, B. (2004).

Diagnostic colors contribute to the early stages of scene categorization: Behavioral and

neurophysiological evidence. *Journal of Vision,* 4(8), 873-873.

Goldstone, R. L., & Steyvers, M. (2001). The sensitization and differentiation of dimensions

during category learning. *Journal of experimental psychology: General*, *130*(1), 116.

Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., ... & Bengio,

Y. (2014). Generative adversarial nets. In *Advances in neural information processing*

systems (pp. 2672-2680).

Green, P., & MacLeod, C. J. (2016). SIMR: an R package for power analysis of generalized

linear mixed models by simulation. Methods in Ecology and Evolution, 7(4), 493-498.

Greene, M. R., & Oliva, A. (2009). Recognition of natural scenes from global properties: Seeing

the forest without representing the trees. *Cognitive psychology*, *58*(2), 137-176.

Haberman, J., & Whitney, D. (2007). Rapid extraction of mean emotion and gender from sets of

faces. *Current biology*, *17*(17), R751-R753.

Harrison, S. A., & Tong, F. (2009). Decoding reveals the contents of visual working memory in

early visual areas. *Nature*, *458*(7238), 632-635.

Karras, T., Laine, S., & Aila, T. (2019). A style-based generator architecture for generative

adversarial networks. In *Proceedings of the IEEE conference on computer vision and*

pattern recognition (pp. 4401-4410).

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). Imagenet classification with deep

convolutional neural networks. In *Advances in neural information processing*

systems (pp. 1097-1105).

Jiang, X., Bradley, E., Rini, R. A., Zeffiro, T., Vanmeter, J., & Riesenhuber, M. (2007).

Categorization training results in shape- and categoryselective human neural plasticity.

Neuron, 53, 891–903. doi:10.1016/j.neuron.2007.02.015

Johnson, J. S., Spencer, J. P., Luck, S. J., & Schöner, G. (2009). A dynamic neural field model of

visual working memory and change detection. *Psychological science*, *20*(5), 568-577.

Kauffmann, L., Ramanoël, S., Guyader, N., Chauvin, A., & Peyrin, C. (2015). Spatial frequency

processing in scene-selective cortical regions. *NeuroImage*, *112*, 86-95.

Kiyonaga, A., & Egner, T. (2016). Center-surround inhibition in working memory. *Current*

Biology, *26*(1), 64-68.

Konkle, T., Brady, T. F., Alvarez, G. A., & Oliva, A. (2010). Scene memory is more detailed

than you think: The role of categories in visual long-term memory. *Psychological*

science, *21*(11), 1551-1556.

Lin, P. H., & Luck, S. J. (2009). The influence of similarity on visual working memory

representations. *Visual Cognition*, *17*(3), 356-372.

Luck, S. J., & Vogel, E. K. (1997). The capacity of visual working memory for features and

conjunctions. *Nature*, *390*(6657), 279-281.

Magnussen, S., Greenlee, M. W., Aslaksen, P. M., & Kildebo, O. Ø. (2003). High-fidelity

perceptual long-term memory revisited—and confirmed. *Psychological Science*, *14*(1),

74-76.

Markov, Y. A., Tiurina, N. A., & Utochkin, I. S. (2019). Different features are stored

independently in visual working memory but mediated by object-based

representations. *Acta psychologica*, *197*, 52-63.

Miner, A. E., Schurgin, M. W., & Brady, T. F. (2020). Is working memory inherently more

"precise" than long-term memory? Extremely high fidelity visual long-term memories for

frequently encountered objects. *Journal of Experimental Psychology: Human Perception*

and Performance, *46*(8), 813.

Newell, F. N., & Bülthoff, H. H. (2002). Categorical perception of familiar

objects. *Cognition*, *85*(2), 113-143.

Oh, B. I., Kim, Y. J., & Kang, M. S. (2019). Ensemble representations reveal distinct neural

coding of visual working memory. *Nature communications*, *10*(1), 1-12.

Oliva, A., & Schyns, P. G. (2000). Diagnostic colors mediate scene recognition. *Cognitive*

psychology, *41*(2), 176-210.

Oliva, A., & Torralba, A. (2001). Modeling the shape of the scene: A holistic representation of

the spatial envelope. *International journal of computer vision*, *42*(3), 145-175.

R Core Team (2019). R: A language and environment for statistical computing. R Foundation for

Statistical Computing, Vienna, Austria. URL https://www.R-project.org/.

Rezanejad, M., Downs, G., Wilder, J., Walther, D. B., Jepson, A., Dickinson, S., & Siddiqi, K.

(2019). Scene categorization from contours: Medial axis based salience measures.

In *Proceedings of the IEEE Conference on Computer Vision and Pattern*

Recognition (pp. 4116-4124).

Serre, T. (2019). Deep learning: the good, the bad, and the ugly. *Annual Review of Vision*

Science, *5*, 399-426.

Schurgin, M. W., Wixted, J. T., & Brady, T. F. (2020). Psychophysical scaling reveals a unified

theory of visual memory strength. *Nature Human Behaviour*, 1-17.

Schyns, P. G., & Oliva, A. (1994). From blobs to boundary edges: Evidence for time-and spatial-

scale-dependent scene recognition. *Psychological science*, *5*(4), 195-200.

Shocher, A., Gandelsman, Y., Mosseri, I., Yarom, M., Irani, M., Freeman, W. T., & Dekel, T.

(2020). Semantic Pyramid for Image Generation. In *Proceedings of the IEEE/CVF*

Conference on Computer Vision and Pattern Recognition (pp. 7457-7466).

Smith, T., & Guild, J. (1931). The CIE colorimetric standards and their use. *Transactions of the*

Optical Society, *33*(3), 73.

Son, G., Oh, B. I., Kang, M. S., & Chong, S. C. (2020). Similarity-based clusters are

representational units of visual working memory. *Journal of Experimental Psychology:*

Learning, Memory, and Cognition, *46*(1), 46.

Sperling, G. (1960). The information available in brief visual presentations. *Psychological*

monographs: General and applied, 74(11), 1.

Steyvers, M. (1999). Morphing techniques for manipulating face images. *Behavior Research*

655   *Methods, Instruments, & Computers*, *31*(2), 359-369.

656   Sun, S. Z., Fidalgo, C., Barense, M. D., Lee, A. C., Cant, J. S., & Ferber, S. (2017). Erasing and

657   blurring memories: The differential impact of interference on separate aspects of

658   forgetting. *Journal of Experimental Psychology: General*, *146*(11), 1606.

659   Van den Berg, R., Shin, H., Chou, W. C., George, R., & Ma, W. J. (2012). Variability in

660   encoding precision accounts for visual short-term memory limitations. *Proceedings of the*

661   *National Academy of Sciences*, *109*(22), 8780-8785.

662   Walther, D. B., & Shen, D. (2014). Nonaccidental properties underlie human categorization of

663   complex natural scenes. *Psychological science*, *25*(4), 851-860.

664   Walther, D. B., Chai, B., Caddigan, E., Beck, D. M., & Fei-Fei, L. (2011). Simple line drawings

665   suffice for functional MRI decoding of natural scene categories. *Proceedings of the*

666   *National Academy of Sciences*, *108*(23), 9661-9666.

667   Wilder, J., Rezanejad, M., Dickinson, S., Siddiqi, K., Jepson, A., & Walther, D. B. (2019). Local

668   contour symmetry facilitates scene categorization. *Cognition*, *182*, 307-317.

669   Wilken, P., & Ma, W. J. (2004). A detection theory account of visual short-term memory for

670   color. *Journal of Vision*, *4*(8), 150-150.

671   Yang, C., Shen, Y., & Zhou, B. (2019). Semantic hierarchy emerges in deep generative

672   representations for scene synthesis. *arXiv preprint arXiv:1911.09267*.

673   Yu, F., Seff, A., Zhang, Y., Song, S., Funkhouser, T., & Xiao, J. (2015). Lsun: Construction of a

674   large-scale image dataset using deep learning with humans in the loop. *arXiv preprint*

675   *arXiv:1506.03365*.

676   Zhang, W., & Luck, S. J. (2008). Discrete fixed-resolution representations in visual working

677   memory. *Nature*, *453*(7192), 233-235.

678   Zhou, B., Lapedriza, A., Khosla, A., Oliva, A., & Torralba, A. (2017). Places: A 10 million

679   image database for scene recognition. *IEEE transactions on pattern analysis and machine*

680   *intelligence*, *40*(6), 1452-1464.

682   **Supplementary Figures**

Wheel 1

Wheel 2

Wheel 3

Wheel 4

Wheel 5

684   *FS 1. Error distributions of individual participant. Each panel containing five histograms*
685   *indicates individual participant data. Across all wheel types and all participants, error*
686   *distributions are highly similar, suggesting very consistent effects of radius condition. Bin width*
687   *is 5 degrees.*