Scene wheels: Measuring perception and memory of real-world

scenes with a continuous stimulus space

Gaeun Son, Dirk B. Walther, Michael L. Mack

Department of Psychology, University of Toronto, Toronto, ON, Canada

Author Note

This research was supported by Natural Sciences and Engineering Research Council (NSERC)

Discovery Grants (RGPIN-2017-06753 to MLM and RGPIN-2020-04097 to DBW) and Canada

Foundation for Innovation and Ontario Research Fund (36601 to MLM).

The datasets generated during and/or analyzed during the current study are available in the Open

Science Framework repository: https://osf.io/h5wpk/

The authors declare no conflict of interest.

Correspondence concerning this article should be addressed to Michael L. Mack, Department of

Psychology, University of Toronto, Sidney Smith Hall, 100 St George St, Toronto, ON M5S

3G3, Canada. E-mail: mack.michael@gmail.com

Abstract

Precisely characterizing mental representations of visual experiences requires careful

control of experimental stimuli. Recent work leveraging such stimulus control in continuous

report paradigms have led to important insights; however, these findings are constrained to

simple visual properties like colour and line orientation. There remains a critical methodological

barrier to characterizing perceptual and mnemonic representations of realistic visual experiences.

Here, we introduce a novel method to systematically control visual properties of natural scene

stimuli. Using generative adversarial networks (GAN), a state-of-art deep learning technique for

creating highly realistic synthetic images, we generated scene wheels in which continuously

changing visual properties smoothly transition between meaningful realistic scenes. To validate

the efficacy of scene wheels, we conducted a memory experiment in which participants

reconstructed to-be-remembered scenes from the scene wheels. Reconstruction errors for these

scenes resemble error distributions observed in prior studies using simple stimulus properties.

Importantly, memory precision varied systematically with scene wheel radius. These findings

suggest our novel approach offers a window into the mental representations of naturalistic visual

experiences.

Keywords: scene perception, generative adversarial network, continuous report paradigm, visual

working memory

Scene wheels: Measuring perception and memory of real-world scenes with a continuous

40   **stimulus space**

The ultimate goal for visual memory research is understanding how people encode the

complexities of everyday visual experience into memory traces that can be retrieved moments to

hours to days later. A guiding principle of this research is the use of simple stimuli (e.g. spatial

frequency, orientation, or colour) to investigate various aspects of visual memory including the

capacity of iconic memory (Bradley & Pearson, 2012; Sperling, 1960), the storage structure of

visual working memory (VWM; Bays et al. , 2009; Brady & Alvarez, 2011; Luck & Vogel,

1997; Zhang & Luck, 2008), and decay or bias of visual long-term memory (Magnussen et al.,

2003; Ester et al., 2020). Although decades of this research have characterized many facets of the

visual memory system, it remains an important open question how these findings based on

simple visual stimuli generalize to memory for realistic visual environments. The key limitation

preventing such advances is the methodological hurdle of proper empirical control of realistic

scene stimuli.

The careful control of the physical properties of stimuli is a critical element for many

domains of cognitive psychology. By systematically manipulating physical properties of stimuli,

corresponding changes in task performance can be identified and leveraged to characterize

changes in cognitive ability. One prominent example is the change detection paradigm in VWM

studies in which participants have to detect any differences between two visual arrays presented

sequentially. By manipulating the physical properties of stimuli composing the visual arrays,

researchers can identify those features that are successfully encoded and remembered (Harrison

& Tong, 2009; Kiyonaga & Egner, 2016; Johnson et al., 2009; Lin & Luck, 2009; Luck &

Vogel, 1997; Wilken & Ma, 2004). For example, Lin & Luck (2009) manipulated the similarity

of target and foil object colours by measuring coordinate distance between the stimuli in CIE

colour space. Based on this deliberate manipulation, they demonstrated that visual working

memory (VWM) performance increases when target and foil colours are similar, a finding that

speaks to a fundamental relationship between a pervasive visual feature and how the visual

memory system encodes it.

The level of stimulus control available for a feature like colour is, however, very difficult

to achieve in the real-world scene domain. Whereas colour spaces like CIE offer well-established

links between physical and perceptual similarity, the amount of information and complexity in

realistic scenes makes it difficult to define the similarity between any two scenes in a manner

that reflects human perception. One recent study (Konkle et al., 2010) took an indirect approach

to overcoming this challenge by manipulating the semantic similarity of target and foil scenes as

a proxy for visual similarity. The underlying assumption was that scene exemplars would share

similar visual properties to some extent if they are in the same semantic category (e.g., two

kitchens are more visually similar than a kitchen and bedroom). Certainly, many natural

categories exhibit family resemblance with shared visual properties; however, such semantic

manipulations are a noticeable departure from the deliberate manipulation of visual properties

like colour or orientation (Harrison & Tong, 2009).

The fine control of stimulus properties is essential for adapting new experimental

paradigms. Continuous report is one of the recent paradigms that makes it possible to more

directly observe a representational structure of the visual memory system (Bays & Husain, 2008;

Wilken & Ma, 2004; Zhang & Luck, 2008). In this paradigm, participants select the stimulus

they experienced using a highly controlled response scale that contains all possible stimulus

options used in the study and is organized such that visually similar items are adjacent in a

continuous visual feature space (e.g., a colour space). The advantage of this paradigm is that

researchers can quantify the representational error that a memory system makes when processing

the inputs by calculating the distance between the responded value and the actual target in the

scale. Specifically, when a substantial number of errors are accumulated by repeating trials, they

can typically observe a Gaussian shaped error distribution around the target, which is

conceptually well-matched with internal noise assumed to arise during the representation

process. That is, with an appropriate response scale, the error distribution can be interpreted as a

reconstruction of our mental representation.

Since it provides direct reconstructions of visual representation, the continuous report

paradigm has broadened our understanding of visual memory. For example, researchers have

quantified more detailed aspects of visual memory like memory precision or bias by quantifying

how densely errors are distributed near the target or how the central tendency of a response

distribution is systematically shifted (Oh et al., 2019; Son et al., 2020; Wilken & Ma, 2004). The

VWM literature has leveraged a mixture model approach that teases apart different components

of the error distribution that are theorized to reflect fundamental retention mechanism of VWM

(Bays et al., 2009; Fougnie et al., 2010; van den Berg et al., 2012; Zhang & Luck, 2008; but see

also Schurgin et al., 2020). Specifically, despite some variations, the basic structure of the

mixture model consists of a von-Mises distribution that reflects the correct memory for the target

with internal noise and a uniform distribution that accounts for pure guessing. By fitting this

mixture model to the data, mechanistically relevant properties of error distributions can be

identified, such as how often participants forget the stimuli or how precisely they can remember

the target.

Despite the apparent advantages of the continuous report paradigm and mixture

modeling, to our knowledge no studies have attempted to use this approach to characterize

memory for realistic scene environments. The key challenge stems from the difficulty in stimulus

control for real world scenes. To create a continuous stimulus space, it is necessary to

parametrically manipulate the targeted properties of the stimuli (e.g. hue in colour wheel) such

that changes occur without any abrupt transitions at a fine scale with constant increments. Since

this level of control is very hard to achieve in real-world scenes, several studies have instead

embraced continuous spaces of simple features in real-world stimuli (Brady et al., 2013; Miner et

al., 2020; Chanales et al. 2020; Sun et al. 2017). For example, Sun et al. (2017) systematically

manipulated colours of real-world objects and asked participants to remember and report the

colour of the target object under a continuous report paradigm. Based on the mixture model, they

are able to distinguish behaviour driven by complete forgetting of stimulus information

(guessing) from less precisely remembered information (decrement in precision). They found

that colour memory for a target object can experience both modes of failure depending on colour

similarity between target and distractor objects. However, since colour is only one attribute of

the object stimuli, findings from this approach are more likely to reflect colour memory itself

rather than reflecting the integrative nature of object memory. Moreover, although this work

represents a departure from typical VWM paradigms based on arrays of coloured squares or

circles, it is unclear how continuous colour space manipulations can be extended to real-world

scenes. Not only are real-world scenes composed of multiple objects, each with their own

primary colour, but much of rapid scene perception and categorization has little to do with colour

information and these processes can even be hampered when a scene's major color scheme is

abonormal (Castelhano et al., 2008; Delorme et al., 2000; Goffaux et al., 2004).

Conceptually, a continuous stimulus space for real world scenes should depend on the

complex features critical for distinguishing between scene categories (Walther & Shen, 2014;

Wilder et al., 2019). Characterizing such features has been a key question in scene perception for

decades (Davenport & Potter, 2004; Greene & Oliva, 2009; Kauffmann et al., 2015; Oliva &

Schyns, 2000; Oliva & Torralba, 2001; Schyns & Oliva, 1994; Walther et al., 2011); however,

the recent revolution in deep learning approaches from machine learning and computer vision

have provided novel insights into the nature of features underlying visual categorization (Cichy

et al., 2017; Eberhardt et al., 2016; Krizhevsky et al., 2012; Rezanejad et al., 2019; Zhou et al.,

2017; for review, Serre, 2019). In particular, generative adversarial networks (GAN; Brock et al.,

2018; Goodfellow et al., 2014; Karras et al., 2019; Shocher et al., 2020; Yang et al., 2019) offer a

data-driven method for uncovering the complex features spaces necessary for generating

artificial but highly realistic images. GANs are composed of two deep neural networks, a

generative network and a discriminative network, which perform antagonistic tasks. The

generative network produces artificial images from random inputs while the discriminative

network distinguishes real photographs from the artificial images synthesized by the generative

network. These networks are placed in opposition with the generative network aiming to

generate synthesized images that fool the discriminative network, and the discriminative network

adapting to correctly categorize real from synthetic. Thus, the GAN is set to train the generative

network so as to minimize the performance of the discriminative network. After successful

learning, the synthesized images created by the generative network are highly realistic even to

human observers. Recent studies of scene specific GANs (Shocher et al., 2020; Yang et al.,

2019) have demonstrated that latent spaces from trained generative networks show a meaningful

organization such that adjacent vectors in latent space are highly similar to each other and their

associated synthetic images represent continuously changing realistic scenes. These advances

offer a unique possibility – a continuous space of natural scene images may be constructed by

deliberately traversing the latent space of a GAN trained to synthesize scene images.

In the current study, we test whether a scene space synthesized from a GAN can be used

to generate stimuli for the continuous report paradigm. To do this, we leveraged a GAN trained

on natural scene images (Yang et al., 2019) and designed the way we select latent vectors such

that the synthesized output results in a continuously changing scene space. Specifically, we

sought to generate circular scene spaces, which we call scene wheels, akin to colour or

orientation wheels that continuously traverse a stimulus space with no specified start and end

points. To do this, we selected a set of latent vectors located on an imaginary circle in latent

space and generated the associated synthetic scene images. To assess and validate the continuous

nature of changes throughout the scene wheels, we calculated pixel-wise correlations of the

scene images. Also, we parametrically manipulated the radius of the circles in latent space to

explore how the generated scenes vary depending on distances between their latent vectors, and

how this variation affects human memory performance. We hypothesized that if our approach to

generating scene wheels actually reflected the latent scenes spaces fundamental to human scene

perception and memory, scene wheels with larger radii should be remembered with higher

precision. To test this hypothesis, we conducted a VWM experiment using the continuous report

paradigm. Participants successfully remembered and reconstructed scene images from the scene

wheels in their WM, and the observed error pattens are consistent with typical error distributions

observed from similar experiments with simple stimuli. Critically, the radius of the scene wheels

was associated with memory precision. Our work provides a novel method to measure memory

performance of realistic scene stimuli as well as a new class of highly controllable scene stimuli

for a range of experiments on scene perception and memory.

Methods

Participants

20 participants (16 females, 4 males, 0 other, mean age = 23.31) with normal or

corrected-to-normal vision completed the experiment. The experiment was conducted online and

all participants were compensated with monetary rewards. The targeted sample size was pre-

determined based on a power analysis from a pilot experiment (N=17). The power analysis

focused on the fixed effect of scene wheel radius as defined in a mixed effect regression model

(see details in Analysis) and was conducted using the SIMR package (Green & MacLeod, 2015)

in R 3.6.1 (R Core Team, 2019). A power curve was estimated by simulating 100 datasets and

refitting the regression model to each simulated dataset for each of a range of sample sizes from

4 to 19 participants. The results showed that with a sample size of only 4, the estimated power

reached 95% (CI [88.72, 98.36]). Thus, we decided to collect 20 participants for the main

experiment, a similar number with the pilot experiment. The study protocol was approved by

University of Toronto Research Ethics Board.

Stimuli

The continuous scene space, or the scene wheel, was generated using the StyleGAN

model trained with a mixed image pool of three indoor scene categories – bedrooms, living

rooms, and dining rooms (Yang et al., 2019). The training image set included 500,000 scenes per

scene category all of which were selected from the LSUN dataset (Yu et al., 2015). Generating

scene wheels from this GAN required a systematic approach to sampling the latent vectors of the

generative model. First, we randomly sampled three latent vectors and defined a plane by

calculating the vector cross products of the three vectors. On that plane, an imaginary circle was

drawn around the center point of the three seed vectors. We then selected 360 points equally

spaced by 1-degree unit on the imaginary circle (Figure 1). The extracted points were fed into the

generative network as input and synthesized into natural-looking scene images. Figure 2 shows

examples of output images generated by this procedure (see Supplementary video to check entire

images within a wheel).

Figure 1. A simple scheme of wheel generation procedure. The selected points on the imaginary
circles (third stage) were used as input to the generator.

209
We also examined how composite images of a scene wheel are affected by differences in

radii of the wheel in the latent space. To do this, we created separate imaginary circles by

increasing the radius by 1 unit in exponents of 2 but maintaining the center of the circle. Scene

wheels with smaller radii resulted in scenes with few changes in their visual properties (Figure

2A) while circles with larger radii contain less similar images with larger changes (Figure 2B).

This pattern was highly consistent across scene wheels generated from different origins. We

chose 5 different radii (2, 4, 8, 16, and 32 a.u.) to test whether memory performance

systematically changes with radius. We generated different types of wheels from 5 different

origins, and thus 25 wheels were created in total.

Figure 2. Example images of two scene wheels that share the same centre point but vary in radius. The images in this figure are equally spaced by 10 degrees from 0 to 350 degrees. A) 36 example images from a wheel with radius of 8 (arbitrary unit). The top-left and bottom-right scenes are closely located on the wheel (0 and 350 degrees) thus are very similar. B) 36 examples from a wheel with radius 32. Compared to A, the changes between images are larger.

The wheels generated through this process were used for the working memory

experiment using the continuous report paradigm. To test a full range of each scene wheel, we

divided each wheel into 20-degree bins and randomly selected three scene images from each bin

as targets for each participant. Due to the web-based nature of the study, the image stimuli were

displayed at different sizes depending on the individual participant's monitor settings. The

images occupied 20% of the monitor width and were presented with a square aspect ratio. Note

that the experiment was set to be run only on laptop or desktop computers, but not on

smartphones or tablets.

Procedure & Design

The procedure followed the conventional delayed estimation task in visual working

memory (Wilken & Ma, 2004) with a small variation on display durations. Each trial began with

a memory display with a target scene image (1 sec) and followed by a short retention interval for

approximately 1 second. After the retention interval, a response display with a gray box and

indicator wheel was presented. Once participants moved their computer mouse, the gray box was

replaced with a random scene within the scene wheel. Thereafter, the scene shown changed

according to the mouse position. By moving the mouse cursor along the indicator wheel,

participants were asked to find a scene that closely matched the target scene presented in the

memory display. Participants responded with their best matching scene candidate by clicking the

left mouse button. To avoid effects of location memory, the probe scene wheel was randomly

rotated in each trial. An example trial sequence is depicted in Figure 3 (see the demo version of

the experiment: https://macklab.github.io/sceneWheel_main/demo.html).

We used a mixed design with 5 (between-subject variable: 5 different wheel types) x 5

(within-subject variable: wheel radius) conditions. 4 participants were recruited for each scene

wheel and each participant performed 270 trials (54 trials for all 5 radius levels of a single scene

wheel). Before starting the main experiment, participants completed 5 practice trials. During the

main experiment, short breaks were given every 54 trials.

Figure 3. Example trial sequence.

Analysis

Before examining participants' performance in the working memory experiment, we first

quantified the image similarity of the scene wheels to confirm the continuous nature of

transitions between scenes and that visual similarity of the scene wheels changes according to the

radius manipulation. We calculated pixel-wise correlations from all possible pairs of 360 scene

images of each wheel using Pearson correlation. In addition to plotting the correlations in

correlation matrices (Figure 4), we also sorted the correlation values of all pairs of images

according to their angular distance on the scene wheel, averaging all Fisher-z transformed

correlation coefficients with the same pair distance (Figure 5).

Then, to compare memory performance among different radii, we measured memory

response error and calculated circular SDs of errors in each radius condition. First, response

errors of each trial were calculated by subtracting the target angle from the response angle that

participants made in each trial. After sorting the response errors into 5 radius conditions and 5

wheel conditions, we calculated circular SDs from the response error distributions using the

circular package (Agostinelli & Lund, 2017) in R 3.6.1 (R Core Team, 2019). Then, we applied a

linear mixed model that predicts circular SDs with a fixed effect of the wheel radii and the

random effect of participants using the LME4 package (Bates et al., 2015).

Results

Pixel-wise correlation of composite scenes. To generate the scene wheels, we sampled latent

vectors in a circular shape by drawing imaginary circles in the GAN's input latent space. The

GAN used in this study was pre-trained with the mixed indoor scene image pool of bedrooms,

living rooms, and dining rooms (Yang et al., 2019). Specifically, we generated 5 different wheel

types, which were determined by different center points of imaginary circles and manipulated

each circle's radius in 5 levels (2, 4, 8, 16, 32 a.u.), ended up with 25 wheels in total (See details

in Method section). The distances between adjacent latent vectors of a scene wheel depended on

the circle's radius such that vectors in smaller scene wheels were closer to each other. To

validate the continuous nature of scenes in these scene wheels, we calculated pixel-wise

correlations of all possible pairs of the composite scenes in each wheel (Figure 4). Diagonal red

lines indicate perfect correlations of an image with itself (angular difference of 0). Across all the

wheel types, we consistently observed that wheels with smaller radii consist of scenes with

higher correlation depicted by warmer colors. This result supports our anticipation that wheels

with smaller radii contain more similar images for the reason that the latent vectors are located

closer to each other. From each wheel, we also observed some extent of gradient color transition:

cells closer to the diagonal line show higher correlations while farther cells show lower

correlations. To quantify this pattern, we averaged correlation coefficients of pairs of images

whose angular differences are the same on the wheel (Figure 5). Across all wheel types with all

radii, mean correlation coefficients of image pairs continuously decrease as their angular

differences on the wheel get bigger, indicating that pairs of scenes become less similar the father

apart they are located on the scene wheel. Moreover, the drop-off gets steeper for larger radii,

again showing that similarity of scenes systematically varies with the wheel radius.

Figure 4. Pixel-wise correlation matrices. Each row shows the correlation results of different wheel types. Each column corresponds to a different radius. Across wheel types, smaller radii show higher correlation depicted by warmer color.

Figure 5. Mean correlation coefficients aligned by the angular difference on each scene wheel.
Across all the wheels, coefficients have strong peaks at the angular difference of 0 and drop off
as the angular differences get larger with the steepness of the drop-off depends on the wheel
radius.

Working memory performance. We tested if the changes in physical properties of scene wheels

confirmed in the previous section are reflected in human behavior. Especially, we conducted the

VWM experiment using the continuous report paradigm to test if scene wheels with larger radii

where composite scenes look less similar are remembered more precisely. A total of 20

participants (16 females, mean age = 23.31) were recruited for the experiment. Groups of four

participants were assigned to each wheel type. The task followed the typical procedure of

delayed estimation task (Figure 3). In each trial, a target scene that was pseudo-randomly

selected from the scene wheels were presented (1 sec), followed by a retention interval (1 sec).

Then, participants were asked to find the target scene from the given scene wheel by moving the

mouse cursor while the probe scene images changed depending on the angle of the mouse

position. Each participant repeated this trial until they complete 54 trials for each of 5 radius

conditions. The error distributions of each radius condition are provided in Figure 6A. The

observed error distributions resemble typical error distributions in studies using continuous

report paradigm and simple stimuli. We then applied a linear mixed model to the data to predict

memory precision represented by circular SDs of errors with radii of the wheels, since we

hypothesized that memory precision would increase with larger radius. As expected, we

observed that a strong effect of the radius on circular SDs ($F(1, 79) = 205.32, p < .001$),

suggesting that memory precision increases with the increment of wheel radius (note that smaller

circular SD indicates higher memory precision). Then, we further explored the effect of the

wheel type to see if it affects the memory precision in addition to the radius by estimating a

linear mixed model that included the interaction between the wheel type and radius. Relative to

the first model with only the radius factor, we found that the interaction model explained the data

better ($\chi^2(8) = 21.48, p = .006$). The interaction of the wheel type and radius was significant

($F(4, 75) = 4.22, p = .004$), which is reflected in slightly different slopes of the wheel types

(Figure 6B). Thus, despite these slight differences in the magnitude of the effect across wheel

types, we found that participants' memory for the realistic scenes was more precise with larger

radii, and this increasing pattern of memory precision along the increment of radius is not limited

to specific wheels but a common effect that can be applied to all wheels.

Figure 6. A. Histograms of response errors in each radius condition. All participants data and corresponding wheel type conditions are aggregated. Density of the histograms decreased with increment of radii (from left to right panel). Bin width is 5 degrees. Individual participant data are also available in Supplementary Figures. B. Decreasing pattern of circular SDs of the response errors along the increment of radius. This suggests that memory precision increased with the increment of the radius. Error bars: CI 95%.

329
330
Discussion

We demonstrate that continuous scene spaces generated from a GAN provide a novel tool

to measure visual memory performance for complex realistic scenes. Specifically, we confirm

that by carefully selecting latent vectors from a pretrained GAN, the similarity among scene

images can be well controlled and provide a continuously changing traversal of meaningful

scene space. With the generated scene wheels, we conducted a visual working memory

experiment using the continuous report paradigm. We observed that the error distribution from

the participant's responses was comparable with the typical error distribution that previous

studies observed from simple stimuli like colours. Critically, we additionally manipulated the

radii of the wheels in the latent space to parametrically control the similarity among the scenes in

the wheels. We found clear evidence that participants' memory performance systematically

varied with this manipulation of scene similarity as predicted. Therefore, we suggest that this

novel method to generate scene stimuli using a GAN not only allows for an unprecedented level

of stimulus control for complex scene stimuli, but also that the latent spaces generating our scene

wheels reflect fundamental representational spaces important for human scene perception and

memory.

Based on this level of control over the scene stimulus space, we expect that findings from

using simple stimuli, such as colour wheels, can be generalized to photo-realistic scenes. First

and foremost, our approach can be leveraged to measure memory performance for scenes at a

fine level of granularity that was not available previously for realistic scenes. In the recognition

paradigm, for example, our methods could be utilized to parametrically control the perceptual

similarity between target and foil scenes to systematically test how scene similarity affects

memory interference or confusion (Konkle et al., 2010; Lin & Luck, 2009). In using a

continuous report paradigm with the GAN-based scene wheels, as we did here, one can measure

specific components of scene memory, such as precision or bias, on a continuous scale. By

coupling the current approach with prominent cognitive models like the mixture model can be

applied to the scene domain, allowing for quantitative estimates of memory capacity and errors

in the same way conventionally done for simpler stimuli (Bays et al., 2009; Brady & Alvarez,

2011; Fougnie et al., 2010; Son et al., 2020; Sun et al., 2017; van den Berg et al., 2012; Wilken

& Ma, 2004; Zhang & Luck, 2008). Additionally, the continuous scene space can be utilized in

any paradigm that requires carefully controlled stimuli. Given that simple stimuli and realistic

scenes have notable differences in their complexity and the amount of information, comparing

the results from those levels of stimuli will contribute to elaborating how memory processes

change along the visual hierarchy and provide testable predictions for neural function and

representation.

The scene space from the GAN has the potential to achieve even more deliberate control

over particular scene properties. Recent studies showed that different layers of the generative

network in GANs represent different properties of the scenes (Karras et al., 2019; Schocher et

al., 2020; Yang et al., 2019). By manipulating the latent vectors in a layer-wise manner, one can

exclusively control specific properties of the scenes that the targeted layer addresses, while the

other properties remain the same. For example, Yang et al. (2019) suggested that a visual

hierarchy emerges in layers of the generative network such that low-level scene properties like

layout are processed in lower layers while higher-level properties like detailed attributes of the

scene (e.g. composite objects, materials of the objects, lighting condition of the scenes, etc.) are

processed in higher layers. They showed that by manipulating the latent vector in certain layers,

GANs synthesized a set of scenes with parametrically different attributes (e.g. lighting, amount

of clutter) but with limited changes in the other properties (e.g. layout and category). Based on

this layer-wise manipulation, future studies may investigate various level of information

embedded in realistic scenes, while minimizing unexpected effects from uncontrolled properties.

Our study is not the first attempt to generate realistic stimuli on a continuous scale.

Previous studies took an approach to morph stimuli with assigning different weights to each

reference stimulus in the various stimulus domains such as animal species (Freedman et al.,

2001; 2003), real-life objects (Newell & Bülthoff, 2002), cars (Folstein et al., 2012; Jiang et al.,

2007), or faces (Beale & Keil, 1995; Goldstone & Steyvers, 2001; Haberman & Whitney, 2007;

Steyvers, 1999). This approach let participants be able to respond for a specific task on a

continuous scale similar to what we showed in our experiment. However, to get a continuous

interpolation between morphing references, the reference images need to be similar and well

matched in terms of their physical status. For example, to continuously manipulate the emotion

of faces, reference faces should be closely matched in properties like identity, gender, and spatial

configuration of the facial components (e.g. eyes, nose, and lips), which requires time-

consuming preprocessing by researchers to utilize the morphing algorithm per se. For this

reason, the morphing approach was restricted to stimulus domains with little physical variance

among the exemplars (e.g. faces have fewer physical variances than scenes). Our approach using

the GAN, however, can be applied to highly complex naturalistic scenes since it utilized neural

networks trained on a large set of photographs and thus creates a large latent space of possible

images. That is, each GAN's latent space itself can be considered as a huge geometrically

structured image database with high controllability. Synthesizing realistic images using the

GANs, therefore, will expand the range of stimulus domains that can be successfully adapted in

visual cognition studies.

Some recent studies in the visual memory field have adapted a different measurement

paradigm, free recall, to target memory precision (Bainbridge et al., 2019; Bainbridge & Baker,

2019). In this paradigm, as conveyed by its name, participants are asked to freely recall whatever

they can remember after seeing the scene images by drawing the scenes. Since this paradigm

does not require foil images to be compared to the target representation in memory, it measures

memory representations more directly and provides insights into the details about the nature of

scene memory, such as what information is remembered from the scene, and how much detail

survived during retention. Nevertheless, this paradigm has practical challenges. Drawing is a

qualitative measurement that needs to be scored using intrinsically subjective judgments for use

as a quantitative measurement. This means that the measurement procedure in this paradigm

requires at least two steps, drawing and assessment of drawing by a third person. Considering

that the assessment is usually conducted by at least hundreds of participants, this is a labor-

intensive paradigm. The other issue is that the drawing behavior itself could confound accurate

measurement of memory performance. For many people, drawing is cognitive demanding

requiring cognitive resources other than visual memory such as active hand movement or visual

attention to the elements currently drawn, which could affect the retrieval process. Also, since

drawing a complex scene often requires a substantial amount of time, the memory representation

could suffer from memory decay. We believe that the technique proposed here can be another

option for a fine-grained measurement of scene representation with more practical benefits.

Scenes generated from the GANs, however, can have a drawback in terms of synthesis

quality. Depending on the pretrained GAN's performance, synthetic scenes can sometimes

include artifacts or "nonsense" regions (although in our experience, such scenes remain highly

realistic and interpretable). Thus, it is key to first select well-trained GAN models and manually

evaluate the generated scenes in preparation for conducting an experiment. We provide our scene

wheel sets that are already tested with human participants in the current experiment

(https://osf.io/h5wpk/) to help researchers to skip this procedure.

In conclusion, we anticipate that the continuous scene space approach proposed here will

quickly be adopted as a fundamental tool for measuring scene representations. Going beyond the

working memory experiment demonstrated here, we foresee that the scene wheels can be utilized

in any domain that needs fine measurement and adjustment methods for realistic scenes. In

leveraging this approach, we anticipate that future work will provide key insights into how we

perceive and remember the real-world naturalistic environments that serves as the backdrop to

our everyday experiences.

References

Agostinelli, C., & Lund, U. (2017). R package circular: Circular Statistics (version 0.4–93), CA:

Department of Environmental Sciences, Informatics and Statistics, Ca'Foscari

University, Venice, Italy. *UL: Department of Statistics, California Polytechnic State*

University, San Luis Obispo, California, USA.

Bainbridge, W. A., & Baker, C. I. (2020). Boundaries Extend and Contract in Scene Memory

Depending on Image Properties. *Current Biology*, *30*(3), 537-543.

Bainbridge, W. A., Hall, E. H., & Baker, C. I. (2019). Drawings of real-world scenes during free

recall reveal detailed object and spatial information in memory. *Nature*

communications, *10*(1), 1-13.

Bates D, Mächler M, Bolker B, Walker S (2015). "Fitting Linear Mixed-Effects Models Using

lme4." *Journal of Statistical Software*, **67**(1), 1–48. doi: [10.18637/jss.v067.i01](10.18637/jss.v067.i01).

Bays, P. M., Catalao, R. F., & Husain, M. (2009). The precision of visual working memory is set

by allocation of a shared resource. *Journal of vision*, *9*(10), 7-7.

Bays, P. M., & Husain, M. (2008). Dynamic shifts of limited working memory resources in

human vision. *Science*, *321*(5890), 851-854.

Beale, J. M., & Keil, F. C. (1995). Categorical effects in the perception of

faces. *Cognition*, *57*(3), 217-239.

Bradley, C., & Pearson, J. (2012). The sensory components of high-capacity iconic memory and

visual working memory. *Frontiers in psychology*, 3, 355.

Brady, T. F., & Alvarez, G. A. (2011). Hierarchical encoding in visual working memory:

Ensemble statistics bias memory for individual items. *Psychological science*, *22*(3), 384-

392.

Brady, T. F., Konkle, T., Gill, J., Oliva, A., & Alvarez, G. A. (2013). Visual long-term memory

has the same limit on fidelity as visual working memory. *Psychological science*, *24*(6),

981-990.

Brock, A., Donahue, J., & Simonyan, K. (2018). Large scale gan training for high fidelity natural

image synthesis. *arXiv preprint arXiv:1809.11096.*

Castelhano, M. S., & Henderson, J. M. (2008). The influence of color on the perception of scene

gist. *Journal of Experimental Psychology: Human perception and performance*, *34*(3),

660.

Chanales, A. J., Tremblay-McGaw, A. G., & Kuhl, B. A. (2020). Adaptive repulsion of long-

term memory representations is triggered by event similarity. *bioRxiv*.

Cichy, R. M., Khosla, A., Pantazis, D., & Oliva, A. (2017). Dynamics of scene representations in

the human brain revealed by magnetoencephalography and deep neural

networks. *NeuroImage*, *153*, 346-358.

Davenport, J. L., & Potter, M. C. (2004). Scene consistency in object and background

perception. *Psychological science*, *15*(8), 559-564.

Delorme, A., Richard, G., & Fabre-Thorpe, M. (2000). Ultra-rapid categorisation of natural

scenes does not rely on colour cues: a study in monkeys and humans. *Vision*

research, *40*(16), 2187-2200.

Eberhardt, S., Cader, J. G., & Serre, T. (2016). How deep is the feature analysis underlying rapid

visual categorization?. In *Advances in neural information processing systems* (pp. 1100-

1108).

Ester, E. F., Sprague, T. C., & Serences, J. T. (2020). Categorical biases in human

occipitoparietal cortex. *Journal of Neuroscience*, *40*(4), 917-931.

Folstein, J. R., Gauthier, I., & Palmeri, T. J. (2012). How category learning affects object

representations: Not all morphspaces stretch alike. *Journal of Experimental Psychology:*

Learning, Memory, and Cognition, *38*(4), 807.

Fougnie, D., Asplund, C. L., & Marois, R. (2010). What are the units of storage in visual

working memory?. *Journal of vision*, *10*(12), 27-27.

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2001). Categorical representation

of visual stimuli in the primate prefrontal cortex. *Science*, *291*(5502), 312-316.

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2003). A comparison of primate

prefrontal and inferior temporal cortices during visual categorization. *Journal of*

Neuroscience, *23*(12), 5235-5246.

Goffaux, V., Jacques, C., Mouraux, A., Oliva, A., Schyns, P. G., & Rossion, B. (2004).

Diagnostic colors contribute to the early stages of scene categorization: Behavioral and

neurophysiological evidence. *Journal of Vision,* 4(8), 873-873.

Goldstone, R. L., & Steyvers, M. (2001). The sensitization and differentiation of dimensions

during category learning. *Journal of experimental psychology: General*, *130*(1), 116.

Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., ... & Bengio,

Y. (2014). Generative adversarial nets. In *Advances in neural information processing*

systems (pp. 2672-2680).

Green, P., & MacLeod, C. J. (2016). SIMR: an R package for power analysis of generalized

linear mixed models by simulation. Methods in Ecology and Evolution, 7(4), 493-498.

Greene, M. R., & Oliva, A. (2009). Recognition of natural scenes from global properties: Seeing

the forest without representing the trees. *Cognitive psychology*, *58*(2), 137-176.

Haberman, J., & Whitney, D. (2007). Rapid extraction of mean emotion and gender from sets of

faces. *Current biology*, *17*(17), R751-R753.

Harrison, S. A., & Tong, F. (2009). Decoding reveals the contents of visual working memory in

early visual areas. *Nature*, *458*(7238), 632-635.

Karras, T., Laine, S., & Aila, T. (2019). A style-based generator architecture for generative

adversarial networks. In *Proceedings of the IEEE conference on computer vision and*

pattern recognition (pp. 4401-4410).

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). Imagenet classification with deep

convolutional neural networks. In *Advances in neural information processing*

systems (pp. 1097-1105).

Jiang, X., Bradley, E., Rini, R. A., Zeffiro, T., Vanmeter, J., & Riesenhuber, M. (2007).

Categorization training results in shape- and categoryselective human neural plasticity.

Neuron, 53, 891–903. doi:10.1016/j.neuron.2007.02.015

Johnson, J. S., Spencer, J. P., Luck, S. J., & Schöner, G. (2009). A dynamic neural field model of

visual working memory and change detection. *Psychological science*, *20*(5), 568-577.

Kauffmann, L., Ramanoël, S., Guyader, N., Chauvin, A., & Peyrin, C. (2015). Spatial frequency

processing in scene-selective cortical regions. *NeuroImage*, *112*, 86-95.

Kiyonaga, A., & Egner, T. (2016). Center-surround inhibition in working memory. *Current*

Biology, *26*(1), 64-68.

Konkle, T., Brady, T. F., Alvarez, G. A., & Oliva, A. (2010). Scene memory is more detailed

than you think: The role of categories in visual long-term memory. *Psychological*

science, *21*(11), 1551-1556.

Lin, P. H., & Luck, S. J. (2009). The influence of similarity on visual working memory

representations. *Visual Cognition*, *17*(3), 356-372.

Luck, S. J., & Vogel, E. K. (1997). The capacity of visual working memory for features and

conjunctions. *Nature*, *390*(6657), 279-281.

Magnussen, S., Greenlee, M. W., Aslaksen, P. M., & Kildebo, O. Ø. (2003). High-fidelity

perceptual long-term memory revisited—and confirmed. *Psychological Science*, *14*(1),

74-76.

Markov, Y. A., Tiurina, N. A., & Utochkin, I. S. (2019). Different features are stored

independently in visual working memory but mediated by object-based

representations. *Acta psychologica*, *197*, 52-63.

Miner, A. E., Schurgin, M. W., & Brady, T. F. (2020). Is working memory inherently more

"precise" than long-term memory? Extremely high fidelity visual long-term memories for

frequently encountered objects. *Journal of Experimental Psychology: Human Perception*

and Performance, *46*(8), 813.

Newell, F. N., & Bülthoff, H. H. (2002). Categorical perception of familiar

objects. *Cognition*, *85*(2), 113-143.

Oh, B. I., Kim, Y. J., & Kang, M. S. (2019). Ensemble representations reveal distinct neural

coding of visual working memory. *Nature communications*, *10*(1), 1-12.

Oliva, A., & Schyns, P. G. (2000). Diagnostic colors mediate scene recognition. *Cognitive*

psychology, *41*(2), 176-210.

Oliva, A., & Torralba, A. (2001). Modeling the shape of the scene: A holistic representation of

the spatial envelope. *International journal of computer vision*, *42*(3), 145-175.

R Core Team (2019). R: A language and environment for statistical computing. R Foundation for

546   Statistical Computing, Vienna, Austria. URL https://www.R-project.org/.

547   Rezanejad, M., Downs, G., Wilder, J., Walther, D. B., Jepson, A., Dickinson, S., & Siddiqi, K.

548   (2019). Scene categorization from contours: Medial axis based salience measures.

549   In *Proceedings of the IEEE Conference on Computer Vision and Pattern*

550   *Recognition* (pp. 4116-4124).

551   Serre, T. (2019). Deep learning: the good, the bad, and the ugly. *Annual Review of Vision*

552   *Science*, *5*, 399-426.

553   Schurgin, M. W., Wixted, J. T., & Brady, T. F. (2020). Psychophysical scaling reveals a unified

554   theory of visual memory strength. *Nature Human Behaviour*, 1-17.

555   Schyns, P. G., & Oliva, A. (1994). From blobs to boundary edges: Evidence for time-and spatial-

556   scale-dependent scene recognition. *Psychological science*, *5*(4), 195-200.

557   Shocher, A., Gandelsman, Y., Mosseri, I., Yarom, M., Irani, M., Freeman, W. T., & Dekel, T.

558   (2020). Semantic Pyramid for Image Generation. In *Proceedings of the IEEE/CVF*

559   *Conference on Computer Vision and Pattern Recognition* (pp. 7457-7466).

560   Son, G., Oh, B. I., Kang, M. S., & Chong, S. C. (2020). Similarity-based clusters are

561   representational units of visual working memory. *Journal of Experimental Psychology:*

562   *Learning, Memory, and Cognition*, *46*(1), 46.

563   Sperling, G. (1960). The information available in brief visual presentations. *Psychological*

564   *monographs: General and applied,* 74(11), 1.

565   Steyvers, M. (1999). Morphing techniques for manipulating face images. *Behavior Research*

566   *Methods, Instruments, & Computers*, *31*(2), 359-369.

Sun, S. Z., Fidalgo, C., Barense, M. D., Lee, A. C., Cant, J. S., & Ferber, S. (2017). Erasing and

blurring memories: The differential impact of interference on separate aspects of

forgetting. *Journal of Experimental Psychology: General*, *146*(11), 1606.

Van den Berg, R., Shin, H., Chou, W. C., George, R., & Ma, W. J. (2012). Variability in

encoding precision accounts for visual short-term memory limitations. *Proceedings of the*

National Academy of Sciences, *109*(22), 8780-8785.

Walther, D. B., & Shen, D. (2014). Nonaccidental properties underlie human categorization of

complex natural scenes. *Psychological science*, *25*(4), 851-860.

Walther, D. B., Chai, B., Caddigan, E., Beck, D. M., & Fei-Fei, L. (2011). Simple line drawings

suffice for functional MRI decoding of natural scene categories. *Proceedings of the*

National Academy of Sciences, *108*(23), 9661-9666.

Wilder, J., Rezanejad, M., Dickinson, S., Siddiqi, K., Jepson, A., & Walther, D. B. (2019). Local

contour symmetry facilitates scene categorization. *Cognition*, *182*, 307-317.

Wilken, P., & Ma, W. J. (2004). A detection theory account of visual short-term memory for

color. *Journal of Vision*, *4*(8), 150-150.

Yang, C., Shen, Y., & Zhou, B. (2019). Semantic hierarchy emerges in deep generative

representations for scene synthesis. *arXiv preprint arXiv:1911.09267*.

Yu, F., Seff, A., Zhang, Y., Song, S., Funkhouser, T., & Xiao, J. (2015). Lsun: Construction of a

large-scale image dataset using deep learning with humans in the loop. *arXiv preprint*

arXiv:1506.03365.

Zhang, W., & Luck, S. J. (2008). Discrete fixed-resolution representations in visual working

memory. *Nature*, *453*(7192), 233-235.

Zhou, B., Lapedriza, A., Khosla, A., Oliva, A., & Torralba, A. (2017). Places: A 10 million

590   image database for scene recognition. *IEEE transactions on pattern analysis and machine*

591   *intelligence*, *40*(6), 1452-1464.

Supplementary Figures

595   *FS 1. Error distributions of individual participant. Each panel containing five histograms*
596   *indicates individual participant data. Across all wheel types and all participants, error*
597   *distributions are highly similar, suggesting very consistent effects of radius condition. Binwidth*
598   *is 5 degrees.*