Removing independent noise in systems neuroscience data using DeepInterpolation

Jérôme Lecoq[1], Michael Oliver[1], Joshua H. Siegle[1], Natalia Orlova[1], Christof Koch[1]

[1]Allen Institute for Brain Science, Seattle, WA, USA.

Progress in nearly every scientific discipline is hindered by the presence of independent noise in spatiotemporally structured datasets. Three widespread technologies for measuring neural activity—calcium imaging, extracellular electrophysiology, and fMRI—all operate in domains in which shot noise and/or thermal noise deteriorate the quality of measured physiological signals. Current denoising approaches sacrifice spatial and/or temporal resolution to increase the Signal-to-Noise Ratio of weak neuronal events, leading to missed opportunities for scientific discovery.

Here, we introduce *DeepInterpolation*, a general-purpose denoising algorithm that trains a spatio-temporal nonlinear interpolation model using only noisy samples from the original raw data. Applying DeepInterpolation to *in vivo* two-photon Ca^{2+} imaging yields up to 6 times more segmented neuronal segments with a 15 fold increase in single pixel SNR, uncovering network dynamics at the single-trial level. In extracellular electrophysiology recordings, DeepInterpolation recovered 25% more high-quality spiking units compared to a standard data analysis pipeline. On fMRI datasets, DeepInterpolation increased the SNR of individual voxels 1.6-fold. All these improvements were attained without sacrificing spatial or temporal resolution.

DeepInterpolation could well have a similar impact in other domains for which independent noise is present in experimental data.

22   Introduction

Independent noise is a major impediment to any data acquisition effort. Experimental systems neuroscience

is acutely impacted given the weakness of neuronal signals. For example, *in vivo* imaging of fluorescent

reporters of cellular activity (voltage and calcium) are typically operating in low-photon-count regimes

where shot noise largely dominates the recorded signal. Similarly, thermal and shot noise present in

electronic circuits independently drown out *in vivo* electrophysiological recordings causing lower

sensitivity, impairing the detection of individual spikes. Functional Magnetic Resonance Imaging (fMRI)

also suffers from thermal noise present in recording circuits, as relevant changes in Blood-Oxygen-Level

Dependent (BOLD) signal are typically just a few percent. The presence of independent noise in all these

techniques hampers our ability to measure authentic biological signals, causing irreproducible research or

inducing biases related to particular choices of denoising filters[1] or statistical thresholds[2].

Often, nearby spatio-temporal samples share signals but are independently affected by noise. This

relationship allows the creation of filters to remove noise when applied to the data. Indeed, it is common

practice to apply median or Gaussian filters as a first pre-processing step. Sometimes these averaging filters

are designed in the Fourier domain to efficiently separate noise from the signal. Although this approach has

been successful for many applications, optimal denoising filters can be complicated to build when these

data relationships span multiple dimensions (e.g., time and space) or are intrinsically non-linear.

Importantly, most of these approaches also impact the signal, causing reductions in spatial or temporal

resolution.

The use of machine learning with large datasets permits very complex hierarchical relationships between

data points to be learned[3]. In this framework, learned statistical relationships between samples are exploited

to reconstruct a noiseless version of the signal, rather than applying filters to remove noise from the signal.

This approach has been particularly successful for learning denoising filters or upsampling filters, including

for fluorescence imaging[4,5] but was limited until recently to cases where ground truth is readily available.

For example, pre-acquired structural data at various spatial resolutions made it possible to train neural

network models to upsample datasets and limit the amount of data necessary to reconstruct a full resolution

image[4]. However, when dealing with the types of dynamic signals at the heart of systems neuroscience,

denoised datasets or ground truth data are not readily available or may be impossible to obtain.

A recent approach called Noise2Noise[6] demonstrated that deep neural networks can be trained to perform

image restoration without access to any clean 'ground-truth' data, with performance comparable or

exceeding training using cleaned data. Theoretical work extended this framework to remove pixel-wise

independent noise[7,8]. Here, we adapted these recent developments in machine learning to the problem of

denoising dynamical signals at the heart of systems neuroscience, thereby building a general-purpose

denoising algorithm we call *DeepInterpolation*. Here, we describe and demonstrate the use of

DeepInterpolation for two-photon *in vivo* Ca^{2+} imaging data, *in vivo* electrophysiological recordings, and

whole brain fMRI data. Importantly, our approach is applicable to many experimental fields with minimal

modifications.

Results

The Noise2Noise[6] study demonstrated that deep neural networks can be trained to perform image

restoration without access to any clean 'ground-truth' data. At the heart of this approach is the insight that

gradients derived from a loss function calculated on noisy samples are still partially aligned toward the

correct solution. Provided enough noisy samples are available to train—and the noisy loss is an unbiased

estimate of the true loss—the correct denoising filters are still learned[6]. However, unlike the data used in

the Noise2Noise publication[6], systems neuroscience data does not contain pairs of samples with identical

signals but different noise.

To address this limitation, we followed a similar approach proposed recently in the Noise2Self[7] and

Noise2Void[8] frameworks. In the absence of training pairs, we sought to solve an interpolation problem in

order to learn the spatio-temporal relationships present in the data. That is, we do not seek to denoise an

image but rather to learn the underlying relationship between an entire frame and spatio-temporally nearby

samples by optimizing the reconstruction loss calculated on noisy instances of the center frame. Second,

the noise present in the target (center) samples needs to be independent from the input (adjacent) samples;

otherwise our relationship model would overfit the noise we seek to remove. We eliminated any chance of

overfitting by (1) omitting the target center frame from the input, and (2) presenting training samples only

once during training. While this noisy center frame is the most informative about its own value, it serves

the key function of the target during training. During inference, the dataset is simply streamed through the

trained network to reconstruct a noiseless version of the signal. The quality of the reconstruction depends

on whether enough information about the center frame was present in spatio-temporally nearby samples

and if it was appropriately learned by the training procedure. Given the extensive leverage of complex

relationships present in the data, spanning multiple spatio-temporal dimensions, we will refer to this general

framework as ***DeepInterpolation***.

Application of DeepInterpolation to *in vivo* two-photon Ca^{2+} imaging

For two-photon imaging, we constructed our denoising network following simple principles: First, given

the presence of neuropil signals distributed throughout the background, a single pixel can share information

with other pixels throughout the entire field of view. Second, the decay dynamics of calcium-dependent

fluorescent indicators (GCaMP6f τ_{peak} = 80 +/- 35 ms; $\tau_{1/2}$ = 400 +/- 41 ms[9]) suggest frames as far as 1

second away can carry meaningful information. Therefore, we chose to train a neuronal network to

reconstruct a center frame from the data present in N_{pre} prior frames and N_{post} subsequent frames. The center

frame was omitted from the input so as to not provide any information about the independent pixel-wise

noise due to shot noise (**Fig. 1A**). The final value of the meta-parameter N_{pre} and N_{post} were selected by

comparing the validation loss during training (**Fig. 1B**, see **Methods** and **Appendix I** for details on loss

calculation). Our denoising network utilized a UNet inspired encoder-decoder architecture with 2D

convolutional layers[1011].

The Allen Brain Observatory datasets (http://observatory.brain-map.org/visualcoding) offered a unique

opportunity to train these denoising networks as we had collected more than 1,300 hours of highly

standardized and curated datasets[12]. For each Gcamp6 reporter line (Ai93, Ai148), we had access to more

than 100 million frames carefully curated with standard Quality Control (QC) metrics. We leveraged this

database by presenting each training sample only once during the entire training process, completely

eliminating any chance of noise overfitting.

Within the limits of our computational infrastructure, we showed that using a larger number of both prior

and subsequent frames as input yielded smaller final validation reconstruction losses (see **Fig. 1B**). Training

required 225,000 samples pulled randomly from 1144 separate one hour long experiments to stop improving

(see **Fig. 1B**). Since the loss is dominated by the independent noise present in the target image, the

reconstruction loss could not converge to zero. This was supported by simulation of ideal reconstruction

losses with known ground truth (**Supp. Fig. 1**). In fact, even small improvement in the loss related to visible

improvements in the reconstruction quality of the signal (**Fig. 1B**).

Applying this trained network to denoise held-out datasets (**Supp. Video 1, 2**) yielded remarkable

improvements in imaging quality. The same trained network generalized well to many movie examples (see

4 examples on **Supp. Video 2**). Shot noise was visibly eliminated from the reconstruction (see single frames

in **Fig. 1C** and associated calcium trace) while calcium dynamics were preserved, yielding a 15 fold increase

in SNR (mean raw pixel SNR = 2.4 +/- 0.01, mean pixel SNR after DeepInterpolation = 37.2 +/- 0.2,

N=9966 pixels). While the movies we used during training were motion corrected, a small amount of

motion remained and close inspection of the reconstructions showed that the algorithm also corrected these

remaining motion artifacts (**Supp. Video 1, 2**).

We compared our denoising approach with a recent algorithm called Penalized Matrix Decomposition

(PMD)[13]. While PMD properly reconstructed somatic activities, it rejected most of the variance present in

background pixels, contrary to DeepInterpolation (see **Supp. Video 3**). A key underlying assumption of

PMD is that motion artifacts are absent from the data. Contrary to DeepInterpolation movies, we observed

clear artifacts in movies denoised with PMD due to small residual motion artifacts (see arrow in **Supp.**

Video 3).

To compare these two approaches given this limitation, we created entirely simulated datasets devoid of

motion artifacts, for which we had knowledge of the underlying ground truth. For this, we used a recent

approach called *in silico* Neural Anatomy and Optical Microscopy (NAOMi)[14]. NAOMi combines a

detailed anatomical model of a volume of tissue with models of light propagation and laser scanning so as

to generate realistic Ca^{2+} imaging datasets (see **Methods**). Both DeepInterpolation and PMD performed

well with datasets generated by NAOMi (see **Supp. Fig. 2 B,C** and **Supp. Video 4**). Because

DeepInterpolation used information from nearby frames, it provided visibly smoother calcium traces with

reconstruction losses 1.2 to 2 times smaller than with PMD (see **Supp. Fig. 2**).

Having established that DeepInterpolation compares favorably to the state of the art, we investigated how

removing shot noise impacts our ability to analyze the activity of neuronal compartments.

Segmentation of active compartments during Ca^{2+} imaging is transformed by DeepInterpolation.

We first sought to evaluate the impact of DeepInterpolation on the segmentation process itself. Existing

approaches to calcium imaging segmentation rely on the analysis of correlation between pixels to create

ROIs[15,16]. After denoising, single pixel pairwise correlations greatly increased from near zero (averaged

Pearson correlation = $9.0*10^{-4}$ +/- $2.3*10^{-6}$ s.e.m, $n = 4*10^8$ pairs of pixels across 4 experiments) to a

significant positive value (averaged Pearson correlation = 0.10 +/- $1.2 10^{-5}$ s.e.m, n = 4e8 pairs of pixels

across 4 experiments, KS test comparing raw with DeepInterpolation: $p = 9*10^{-71}$, n = 1,000 pixels

randomly sub-selected, **Supp. Fig 3**). We expected that this increase in averaged correlation would improve

the quality and the number of segmented regions. To that end, we leveraged the sparse mode algorithm

available in Suite2p[16].

The improvement in correlation structure benefited this algorithm considerably. Suite2p extracted a large

number of additional active compartments in the field of view, including small sets of pixels covered by

axons or dendrites perpendicular to the imaging plane (**Fig. 2A**). In the absence of shot noise and single

frame motion artifacts, cell filters were surprisingly well defined (**Fig. 2B**). Automatically extracted ROIs

showed precise details of each compartment, sometimes encompassing dendrites or axons connected to a

local soma. In some cases, active attached buttons were clearly visible in the extracted filter of an horizontal

dendrite (**Fig. 2B**). In many movies, a large number of smaller, punctated compartments - likely a mixture

of horizontal sections of apical dendrites or axons - were detected, each with clear calcium transients (**Fig.**

2C).

Although those numerous compartments were not detected in the original movie, we applied the weighted

masks to both denoised and raw movies to quantify the improvement in SNR of the associated temporal

trace. ROIs associated with somatic compartments typically yielded a mean SNR of 21.0 +/- 0.5 (s.e.m, n

= 240 in 3 experiment) in the original movie (**Fig. 2D**); after denoising, the majority of those ROIs had an

SNR above 40 (mean 73.8 +/- 0.5). Similarly, the mean SNR across all compartments, including the

smallest apical dendrites, went from a mean of 13.2 +/- 0.1 (n = 3385 in 3 experiments) to 73.8 +/- 0.5.

Assuming that a single spike causes a calcium rise of about 10%[9], an SNR above 20 is necessary for those

events to be twice as large as the noise. Although this is a necessary but not sufficient condition, this

suggests that removing shot noise will increase our capability to detect the presence of single spikes.

The average number of active detected ROIs with SNR above 20 went from 178 +/- 135 (s.e.m., in 3

experiments) to 1122 +/- 371 in a 400x400 um^2 field of view (**Fig. 2D**). That is, as much as six times more

neuronal compartments are now available from a single movie for analysis following DeepInterpolation,

thanks to a more reliable segmentation process.

DeepInterpolation improves the analysis of correlated Ca^{2+} imaging activity

To illustrate this new opportunity, we analyzed the response of all compartments to 10 repeats of a natural

movie stimulation. We found clear examples of large and smaller responses to natural movies in both

somatic and non-somatic compartments (**Supp. Fig. 4A**). The trial by trial response reliability (see

Methods) increased substantially from raw traces to traces after DeepInterpolation (see, **Fig. 2E**), both for

somatics ROIs (raw: mean 0.10 +/- 0.01, DeepInterpolation: mean 0.20 +/- 0.01; s.e.m, n = 240 ROIs in n

= 3 experiments) and across all ROIs (raw: mean 0.029 +/- 0.001, DeepInterpolation: mean 0.113 +/- 0.002;

s.e.m, n = 3385 ROIs in n = 3 experiments). When considering the distribution of these responses across a

single field of view, both somatic and non-somatic compartments had a similar distribution for their

preferred movie frame, the maximum DF/F response at this prefered stimulus, as well as the reliability of

their response to natural movies (see **Supp. Fig. 4B , C, D**).

Neuronal representations are inherently noisy even when sensory stimuli and the behavioral state are kept

constant. This key property of neuronal networks has fueled a large number of studies on the relationship

between the averaged signal representation in individual neurons and the trial by trial fluctuation of these

responses[17,18]. Experimental noise directly impacts the measure of neuronal relationships as it modulates

trial-by-trial responses.

For each pair of ROIs in a single experiment, we extracted their shared signal and noise correlation (see

Methods). As expected, we found that both signal as well as noise correlation increased after denoising

(signal: from 0.06725 ± 0.00006 to 0.25 ± 0.0001; noise from 0.02240 ± 0.00002 to 0.12351 ± 0.00008;

both for 2,329,554 pairs of ROIs from three experiments; **Fig. 2F**). This result was not just due to the

improved segmentation as it was preserved using ROIs only detected on raw noisy data (see **Supp. Fig. 5**).

To further illustrate how these improved measures of neuronal fluctuations impacted the analysis of

functional interactions, we compared the spatial distribution of pairwise correlations between neurons

during natural movie stimulation. DeepInterpolation largely increased the number of strong pairwise

interactions for both somatic and non somatic pairs (see **Fig. 2G**, all ROIs: 43 to 1721 pairs). These

correlated pairs of units were almost invisible in the original data, illustrating the improved biological

insight gained through denoising.

Application of DeepInterpolation to *in vivo* electrophysiological recordings

Electrophysiological recordings from high-density silicon probes have similar characteristics to two-photon

imaging movies: information is shared across nearby pixels (electrodes), as well as across time. We

therefore reasoned that a similar architecture should perform well for denoising electrophysiology data, in

particular for removing strictly independent thermal and shot noise present in the recordings. For training

data, we used Neuropixels data that were similarly standardized and curated as the two-photon recordings[19].

Because a single action potential lasts ~1 ms, we constructed our interpolating filter to predict the voltage

profile at any given moment from 30 preceding and 30 following time steps acquired at 30 kHz. Contrary

to two-photon imaging, we found that omitting one sample before and after the center sample better rejected

the background noise while keeping the signal reconstruction of the highest quality. The architecture of the

network was similar to the one used for two-photon imaging, except that the input layer was reshaped to

match the approximate layout of the Neuropixels recording sites (**Fig. 3A**). Because electrophysiological

recordings have a 1,000-fold higher sampling rate than two-photon imaging, we had access to essentially 3

orders of magnitude more training data per experiment and could train the network using only 3 experiments

in total.

After inference, a qualitative inspection of the recordings showcased excellent noise rejection (**Fig. 3B**).

We compared spike profiles before and after denoising and found that the spike waveforms were more

clearly visible in the denoised data, especially for units with lower amplitude spikes (**Fig. 3B**, inset; **Fig.**

3C). The residual of our reconstruction showed weak spike structure but spectral analysis revealed a mostly

flat frequency distribution (**Supp. Fig. 6A**). Importantly, the overall shape (amplitude and decay time) of

individual action potentials was preserved, while the median channel RMS noise was decreased 1.7-fold

(6.96 µV after denoising, see **Fig. 3D**). We ran a state-of-the-art spike sorting algorithm (Kilosort2, version

downloaded April 8, 2019) and removed any detected units with waveforms not likely to be associated with

action potentials. After denoising, we found $25.5 \pm 14.5\%$ more high-quality units per probe (ISI violations

score < 0.5, amplitude cutoff < 0.1, presence ratio > 0.95; see Methods for details). The number of detected

units was higher after DeepInterpolation regardless of the quality metric thresholds that were chosen (**Supp.**

Fig. 6B). The majority of additional units had low-amplitude waveforms, with the number of units with

waveform amplitudes above 75 µV remaining roughly the same (1532 before vs. 1511 after), while the

number with amplitudes below 75 µV increased dramatically (381 before vs. 910 after) (**Fig. 3E**). For units

that were clearly matched before and after denoising (at least 70% overlapping spikes), average SNR

(defined as the ratio of the waveform amplitude to the RMS noise on the peak channel) increased from 11.2

to 14.5 (**Fig. 3F**).

By searching for spatiotemporally overlapping spikes, we determined that $6.2 \pm 2.9\%$ of units in the original

recording were no longer detected after applying DeepInterpolation (<50% matching spikes). However,

this was counterbalanced by the addition of $20.2 \pm 4.8\%$ units that had fewer than 50% matching spikes in

the original data (example unit in **Supp. Fig. 6C**). This is less than the 25.5% increase cited above, because

it accounts for a minority of units that were detected but merged together in the original data. To validate

that these novel units were likely to correspond to actual neuronal compartments, we analyzed their

responses to natural movie stimulation, using the same movie as in the two-photon imaging study. We

found approximately 9% more reliably visually modulated units in the visual cortex after denoising (**Supp.**

Fig. 6D), and found clear examples of stimulus-modulated units that were previously undetected (**Supp.**

Fig. 6E).

Applying DeepInterpolation to extracellular electrophysiology data increased the unit yield across all brain

regions tested, including visual cortex, hippocampus, and thalamus (**Supp. Fig. 7A**). Additional units

tended to have firing rates in the middle of each region's average range and waveform amplitudes below

100 µV (**Supp. Fig. 7B**). In all regions except for dentate gyrus, DeepInterpolation preserved the original

waveform amplitude, while detecting more low-amplitude units. The downward shift in waveform

amplitude observed in dentate gyrus suggests that it may be necessary to provide additional training data

from this region in order to optimize performance of the denoising step. In the visual cortex, additional

units were primarily "regular-spiking" (waveform peak-to-trough duration > 0.4 ms), rather than "fast-

spiking." This suggests that these may be previously undetectable regular-spiking interneurons with small

cell bodies; however, applying DeepInterpolation to datasets with ground truth cell type labels obtained via

optotagging[20] will be required to confirm this hypothesis.

Application of DeepInterpolation to functional Magnetic Resonance Imaging *(fMRI)*

We sought to evaluate how DeepInterpolation could help the analysis of volumetric datasets like fMRI.

fMRI is very noisy as the BOLD response is typically just a 1-2 % change of the total signal amplitude[21].

Thermal noise is present in the electrical circuit used for receiving the MR signal. A typical fMRI processing

pipeline involves averaging nearby pixels and successive trials to increase the SNR[22,23]. We reasoned that

our approach could replace smoothing kernels with more optimal local interpolation functions without

sacrificing spatial or temporal resolution.

Because of the low sampling rate (0.3 to 0.5 Hz), a single fMRI recording session could only provide several

hundreds full brain volumes, while each volume typically contains up to 10 millions voxels. To augment

our training datasets, we decided to alter our approach: Instead of learning a full brain interpolation model,

we sought to train a more local interpolation function.

To reconstruct the value of a brain sub-volume, we fed a neural network with a consecutive temporal series

of a local volume of 7 x 7 x 7 voxels. The entire target volume was omitted from the input (**Fig. 4A**). To

allow our interpolation network to be robust to edge conditions, input volumes on the edge of the volume

were fed with zeros for missing values. For inference, we convolved the denoising network through all

voxels of the volume, across both space and time, using only the center pixel of the output reconstructed

volume to avoid any potential volume boundaries artifacts.

We trained a single denoising network using 140 fMRI datasets acquired across 5 subjects or 1.2 billion

samples. Each training sample was presented only once to avoid any chance of overfitting. After training,

we applied the network to held-out test data, showing excellent denoising performance (**Fig. 4C**).

We extracted the temporal traces from individual voxels and found that tSNR (see **Methods**) increased

from 61.6 ± 20.6 to 100.40 ± 38.7 ($n = 100,001$ voxels). We noticed that the background noise around the

head was clearly excluded and only present in the residual image (**Fig. 4C and Supp. Video 5**). Surrounding

soft tissues became clearly visible after denoising (see **Fig. 4C,** Raw data: background voxel std = $7.59 \pm$

0.01 s.e.m; brain voxels std = 15.95 ± 0.08 s.em., $n = 10,000$ voxels; DeepInterpolation data: background

std = 2.24 ± 0.01 s.em., $n = 10,000$; brain voxels std = 9.72 ± 0.05 s.em., $n = 10,000$ voxels; Residual:

background std = 7.91 ± 0.01; brain voxels std = 15.79 ± 0.08, $n = 10,000$ voxels). The residual movie

showed no visible structure except for occasional blood vessels, corrected motion artifacts and head

mounting hardware (**Fig. 4C, Supp. Video 7**). We compared movies extracted with DeepInterpolation to

fully pre-processed movies that included a Gaussian denoising kernel (**Supp. Video 6**): the original 3D

resolution was fully maintained in DeepInterpolation while the processed data with Gaussian kernel clearly

diffused the voxel dynamic across all nearby voxels.

Discussion

Here, we demonstrated a methodology, *DeepInterpolation*, related to the approach outlined in the *Noise2Self*[7] and *Noise2Void*[8] framework to reconstruct noiseless versions of dynamic datasets, without any requirement for ground truth. While we share the key separation of noise and signal with these techniques, we developed our framework independently. As a result, several key differences are notable. First, instead of working with single fluorescence frames with pixel-wise omissions, we adapted our approach to complex multi-dimensional biological datasets at the heart of systems neuroscience. Second, we trained our models on large databases, demonstrating the impact of richer denoising models on existing neuroscience scientific data and data workflows like cell segmentations or unit detection. Third, we contributed practical solutions: network topology, training regimen and a validation process to extract complex multi-dimensional models.

When applied to two-photon Ca^{2+} imaging datasets, DeepInterpolation increased the SNR of single pixels 15-fold. On electrophysiological data, with little architectural change, DeepInterpolation uncovered 25% more high quality neuronal units. Similarly, applying DeepInterpolation led to a 1.6-fold increase in the SNR of fMRI voxels, effectively removing thermal noise from the recordings. The successful application of DeepInterpolation to these three experimental data modalities supports the general relevance of our method.

Given the increased leverage of the information present between samples, we anticipate DeepInterpolation to be instrumental for the development of large scale voltage-imaging of neuronal activity[24,25] as well as facilitate high-speed fMRI where thermal noise dominates the BOLD signal. Importantly, the pixel-wise framework we used for fMRI increased our training dataset, offering the opportunity to apply the same methodology to many different modalities, regardless of whether or not vast quantities of training data are available. Our approach should permit scientists in a variety of fields to re-analyze their existing datasets but now with independent noise removed.

Speeding up and/or parallelizing the inference step could facilitate real-time denoising of spatiotemporal

signals. This could enable a process whereby a short dataset would be acquired at the onset of any one

experiment, similar to a calibration routine. This dataset could then be used to fine-tune a pre-trained

denoiser that removes independent noise. Whether such training needs to be specific for each instrument,

each type of instrument, each brain area, each transgenic mouse line or even each subject remains a topic

for future research.

We here demonstrated a general purpose denoising methodology to reconstruct dynamic signals at the heart

of systems neuroscience without the contamination of independent noise. Applying DeepInterpolation to

Ca^{2+} imaging, electrophysiological recordings and fMRI showed its wide impacts on SNR and its ability to

uncover previous hidden neuronal dynamics. We anticipate that future work in all 3 modalities we presented

here will revise key subsequent processing steps to better leverage clearer correlation structures now

measured in the data.

Fig. 1 | Training DeepInterpolation networks for denoising two-photon Ca²⁺ imaging. (A) An encoder-

decoder deep network with skip connections was trained to denoise two-photon imaging data. The training

procedure minimized the L1 loss between the predicted frame and a raw frame contaminated with shot

noise. The encoder-decoder network utilized Npre and Npost frames, acquired at 30 Hz, respectively, before

and after the target frame (labelled in green) to predict the central, target frame. (which was omitted from

the input). **(B)** To validate training performance, the validation loss was monitored for convergence as well

as the quality of the image reconstruction throughout training (see inset). Y axis is the mean absolute

difference between a predicted frame and a noisy sample across 2500 samples. Individual data samples

were z-scored using a single estimate of mean and standard deviation per movie (see Methods). Different

combinations of (Npre, Npost) values were tested during training. Dashed vertical line indicates early

stopping (due to the extreme computational demands during training) to evaluate the best set of parameters.

We continued training the model with Npre=30 frames and Npost=30 frames and used this set of parameters

for the rest of this study. Right panels illustrate the denoising performance of this model compared to a

single raw frame (top). Notice the improved contrast between 25,000 and 450,000 samples training: the

smallest neuronal compartments are more clearly visible in the latter. Scale bar is 100 μm. Each red inset

is 100 μm. (**C**) Six example traces extracted from a held-out denoised movie before (black) and after (red)

denoising with DeepInterpolation. The top three traces are extracted from a somatic ROI, while the bottom

three traces are extracted from a single pixel. (**D**) Distribution of SNR (mean over standard deviation, see

Methods) for 10,000 voxels (randomly selected across N=19 denoised held-out test movies) before and

after DeepInterpolation.

Fig. 2 | Applying DeepInterpolation to Ca²⁺ imaging reveals many more ROIs and rich network physiology across small and large neuronal compartments. (A) Three examples showing overlaid colored segmentation masks on top of a maximum projection image of calcium imaging. Improved correlation structure (see **Supp. Fig 4**) allows the detection of a large number of ROIs using the "sparsity"

segmentation mode in Suite2p[16]. Red dashed boxes show zoomed-in view over smaller segmented

compartments. Apical and proximal dendrites are cleanly segmented, regardless of whether they were

imaged along their length or through a short vertical section. Scale bar is 100 μm. **(B)** Example individual

weighted segmented filters showcasing dendrites, isolated somas, somas with attached dendrites, and axons

and small sections of dendrites/axons. Scale bar is 50 μm **(C)** Manually sorted ROIs from one experiment

showcasing the calcium traces extracted from each individual type of neuronal compartments (from top to

bottom - cell body, horizontal processes, processes perpendicular to imaging plane). After

DeepInterpolation, calcium events are recorded with high SNR in all three compartment types, regardless

of their size. (**D, left**) Quantification of SNR for all detected ROIs (gray dots) and somatic ROIs (red dots)

with and without DeepInterpolation. The majority of ROIs have an SNR above 20 after DeepInterpolation.

Dashed line represents the identity line.   (**D, right**) Comparison of the number of ROIs with an SNR above

20 with and without DeepInterpolation. DeepInterpolation allows to reliably record the activity of more

than a thousand compartments in a small $(400 \ \mu m)^2$ field of view ($n = 3$ experiments). (**E**) Quantification

of the response reliability of individual ROIs across 10 trials of a natural movie visual stimulus. Both

somatic and non-somatic ROIs see increased response reliability to a visual stimulus. Dashed line represents

the identity line. **(F, left)** signal correlation (average correlation coefficient between the average temporal

response of a pair of neurons) for all pairs of ROI in (**D**) for both raw and denoised traces. **(F, right)** noise

correlation (average correlation coefficient at all time points of the mean-subtracted temporal response of

a pair of neurons) for all pairs of ROIs in (**D**). (**G**) For an example experiment, pairs of ROIs with high

noise correlation (>0.4) are connected with a straight line for both original two-photon data and after

DeepInterpolation. Scale bar is 100 μm.

Fig. 3 | Applying DeepInterpolation to electrophysiological recordings decreases background noise and yields more neuronal units. (**A**) Structure of the DeepInterpolation encoder-decoder network for electrophysiological data recorded from a Neuropixels silicon probe, with two rows of 192 electrodes each, spaced 20 µm apart. Data is acquired at 30 kHz. (**B**) Side-by-side comparison of original (left) and denoised (right) data, plotted as a 2D heatmap with time on the horizontal axis and channels along the vertical axis. Insets show a close-up of a single action potential across 22 contiguous channels (the box is 3.6 ms wide). (**C**) Denoised time series (red) overlaid on the original time series (gray) for three channels from panel B. (**D**) Histogram of RMS noise for all channels from 10 experiments, before and after applying DeepInterpolation. (**E**) Histogram of waveform amplitudes for all high-quality units from 10 experiments. (**F**) Histogram of waveform SNRs for all units that were matched before and after denoising.

Fig. 4 | Applying DeepInterpolation to fMRI removes thermal noise. (**A**) Structure of the

DeepInterpolation encoder-decoder network for fMRI data. Instead of predicting a whole brain volume at

once, the network reconstructs a local 7x7x7 cube of voxels. (**B**) tSNR (see Methods) for 10,000 voxels

randomly distributed in the brain volume in raw data and after DeepInterpolation.   (**C**) Exemplar

reconstruction of a single fMRI volume. First row is a coronal section while the second row is a sagittal

section through a human brain. Scale bar is 5 cm. In the second column, the temporal mean of 3D scan was

removed to better illustrate the presence of thermal noise in the raw data. The local denoising network was

processed throughout the whole 3D scan for denoising. The impact of DeepInterpolation on thermal noise

is illustrated in the 3rd column. The 4th column shows the residual of the denoising process. Notice how

the residual captured independent noise without any signal structure. Occasional large blood vessels are

visible in the residual (see bottom).

Bibliography

1.   Botvinik-Nezer, R. *et al.* Variability in the analysis of a single neuroimaging dataset by many teams. *Nature* **582**, 84–88 (2020).

2.   Mesa, N., Waters, J. & de Vries, S. E. J. The effect of inclusion criteria on the functional properties reported in mouse visual cortex. doi:10.1101/2020.05.12.091595.

3.   Hinton, G. E. & Salakhutdinov, R. R. Reducing the dimensionality of data with neural networks. *Science* **313**, 504–507 (2006).

4.   Weigert, M. *et al.* Content-aware image restoration: pushing the limits of fluorescence microscopy. *Nature Methods* **15,** 1090–1097 (2018).

5.   Belthangady, C. & Royer, L. A. Applications, promises, and pitfalls of deep learning for fluorescence image reconstruction. *Nat. Methods* **16**, 1215–1225 (2019).

6.   Lehtinen, J. *et al.* Noise2Noise: Learning Image Restoration without Clean Data. arXiv preprint arXiv:1803.04189 (2018).

7.   Batson, J. & Royer, L. Noise2Self: Blind Denoising by Self-Supervision. arXiv preprint arXiv:1901.11365. (2019).

8.   Krull, A., Buchholz, T.-O. & Jug, F. Noise2Void - Learning Denoising from Single Noisy Images. Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 2129-2137 (2018).

9.   Chen, T.-W. *et al.* Ultrasensitive fluorescent proteins for imaging neuronal activity. *Nature* **499**, 295–300 (2013).

10.   Badrinarayanan, V., Kendall, A. & Cipolla, R. SegNet: A Deep Convolutional Encoder-Decoder Architecture for Image Segmentation. *IEEE Trans. Pattern Anal. Mach. Intell.* **39**, 2481–2495 (2017).

11.   Huang, G., Liu, Z., Van Der Maaten, L. & Weinberger, K. Q. Densely Connected Convolutional

Networks. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)* (2017)

doi:10.1109/cvpr.2017.243.

12. de Vries, S. E. J. *et al.* A large-scale standardized physiological survey reveals functional

organization of the mouse visual cortex. *Nat. Neurosci.* **23**, 138–151 (2020).

13. Buchanan, E. K. *et al.* Penalized matrix decomposition for denoising, compression, and improved

demixing of functional imaging data. doi:10.1101/334706.

14. Charles, A. S., Song, A., Gauthier, J. L., Pillow, J. W. & Tank, D. W. Neural Anatomy and Optical

Microscopy (NAOMi) Simulation for evaluating calcium imaging methods. doi:10.1101/726174.

15. Mukamel, E. A., Nimmerjahn, A. & Schnitzer, M. J. Automated analysis of cellular signals from

large-scale calcium imaging data. *Neuron* **63**, 747–760 (2009).

16. Pachitariu, M. *et al.* Suite2p: beyond 10,000 neurons with standard two-photon microscopy.

doi:10.1101/061507.

17. Rumyantsev, O. I. *et al.* Fundamental bounds on the fidelity of sensory cortical coding. *Nature* **580**,

100–105 (2020).

18. Cohen, M. R. & Kohn, A. Measuring and interpreting neuronal correlations. *Nat. Neurosci.* **14**, 811–

819 (2011).

19. Siegle, J. H. *et al.* A survey of spiking activity reveals a functional hierarchy of mouse

corticothalamic visual areas. *Neuroscience* 889 (2019).

20. Lima, S. Q., Hromádka, T., Znamenskiy, P. & Zador, A. M. PINP: A New Method of Tagging

Neuronal Populations for Identification during In Vivo Electrophysiological Recording. *PLoS One* **4**,

e6099 (2009).

21. Caballero-Gaudes, C. & Reynolds, R. C. Methods for cleaning the BOLD fMRI signal. *NeuroImage*

vol. 154 128–149 (2017).

22. Park, B.-Y., Byeon, K. & Park, H. FuNP (Fusion of Neuroimaging Preprocessing) Pipelines: A Fully

Automated Preprocessing Software for Functional Magnetic Resonance Imaging. *Front.*

Neuroinform. **13**, 5 (2019).

23.   Esteban, O. *et al.* fMRIPrep: a robust preprocessing pipeline for functional MRI. *Nat. Methods* **16**,

111–116 (2019).

24.   Zhang, T. *et al.* Kilohertz two-photon brain imaging in awake mice. *Nat. Methods* **16**, 1119–1122

(2019).

25.   Wu, J. *et al.* Kilohertz two-photon fluorescence microscopy imaging of neural activity in vivo. *Nat.*

Methods **17**, 287–290 (2020).

26.   Madisen, L. *et al.* Transgenic mice for intersectional targeting of neural sensors and effectors with

high specificity and performance. *Neuron* **85**, 942–958 (2015).

27.   Daigle, T. L. *et al.* A Suite of Transgenic Driver and Reporter Mouse Lines with Enhanced Brain-

Cell-Type Targeting and Functionality. *Cell* **174**, 465–480.e22 (2018).

28.   Jun, J. J. *et al.* Fully integrated silicon probes for high-density recording of neural activity. *Nature*

551, 232–236 (2017).

29.   Horikawa, T. & Kamitani, Y. Generic decoding of seen and imagined objects using hierarchical

visual features. *Nat. Commun.* **8**, 15037 (2017).

30.   Siegle, J. H. *et al.* Open Ephys: an open-source, plugin-based platform for multichannel

electrophysiology. *J. Neural Eng.* **14**, 045003 (2017).

31.   Pachitariu, M., Steinmetz, N., Kadir, S., Carandini, M. & D., H. K. Kilosort: realtime spike-sorting

for extracellular electrophysiology with hundreds of channels. doi:10.1101/061481.

32.   Hill, D. N., Mehta, S. B. & Kleinfeld, D. Quality metrics to accompany spike sorting of extracellular

signals. *J. Neurosci.* **31**, 8699–8705 (2011).

33.   Magland, J. *et al.* SpikeForest, reproducible web-facing ground-truth validation of automated neural

spike sorters. *Elife* **9**, (2020).

Acknowledgement

We thank the Allen Institute founder, Paul G. Allen, for his vision, encouragement, and support. We thank

Alex Song from the Tank Laboratory for help with NAOMi and for providing early access to the codebase

that he created with Adam Charles. We thank Liam Paninski, Saveliy Yusufov, and Ian August Kinsella

for sharing code and support for applying PMD onto comparative datasets. We thank Daniel Kapner for

help with two-photon segmentation as well as for supportive discussions. We thank James Philip Thomson

from the Schnitzer laboratory for discussions related to denoising two-photon movies. We thank Anton

Arkhipov and Nathan Gouwens for fruitful discussions and for supporting early use of DeepInterpolation

toward analyzing two-photon datasets. We thank Mark Schnitzer and Biafra Ahanonu for continuous

support and evaluating early application of DeepInterpolation to one-photon datasets. We thank Todd

Peterson, Myra Imanaka, Steve Lawrenz, Sarah Naylor, Gabe Ocker, Michael Buice, Jack Waters, Peter

Ledochowitsch and Hongkui Zeng for encouragement and support. We thank Doug Ollerenshaw and

Nathan Gouwens for sharing code to standardize figure generation.

Funding

Funding for this project was provided by the Allen Institute, as well as by the National Institute Of

Neurological Disorders And Stroke of the National Institutes of Health under Award Number

UF1NS107610. The content is solely the responsibility of the authors and does not necessarily represent

the official views of the National Institutes of Health.

Author Contributions

J.L. initiated, conceptualized and directed the project. J.L. and M.O. conceptualized the DeepInterpolation

framework. J.L. wrote all training and inference code with guidance from M.O. J.L. performed all two-

photon and fMRI analysis and ran DeepInterpolation on electrophysiological data. J.H.S and J.L. iterated

the electrophysiological denoising process. J.H.S. performed all analysis on electrophysiological data. C.K.

guided the characterization of all denoising performance. N.O. ran the two-photon ground truth simulation.

J.L., M.O., J.H.S and C.K wrote the paper.

Correspondence and requests for materials should be addressed to J.L. (jeromel@alleninstitute.org).

Competing interests

The Allen Institute has applied for a patent related to the content of this manuscript.

485 **Supplementary Video Table**

Supp. Video 1	**Link:** https://www.dropbox.com/s/xrqn0x0o1z46c7d/Supplementary_video_1.mp4?dl=1 **Caption:** **Left:** Example two-photon movie before and after DeepInterpolation. **Right:** The average movie was subtracted to highlight uncovered fluorescence signals.
Supp. Video 2	**Link:** https://www.dropbox.com/s/58rh63zhepjf7cb/Supplementary_video_2.mp4?dl=1 **Caption:** 4 examples of two-photon movies before and after DeepInterpolation. The same DeepInterpolation model was used for all 4 examples.
Supp. Video 3	**Link:** https://www.dropbox.com/s/tx6me5gbf6trv23/Supplementary_video_3.mp4?dl=1 **Caption:** Example two-photon movie processed with Penalized-Matrix Decomposition (PMD) and DeepInterpolation. White arrow highlights the impact of motion artifacts on PMD.
Supp. Video 4	**Link:** https://www.dropbox.com/s/r0lh9si02dg7s9f/Supplementary_video_4.mp4?dl=1 **Caption:** Simulated two-photon data without motion artifacts with NAOMi. 1st column is ground truth data, in the absence of shot noise. The 2nd column is the same movie with shot noise. The 3rd column is the output of PMD after processing the movie in the 2nd column. 4th column is the output of DeepInterpolation after processing the movie in the 2nd column.
Supp. Video 5	**Link:** https://www.dropbox.com/s/o4v8tisrcy2ho7p/Supplementary_video_5.mp4?dl=1 **Caption:** Example fMRI data with and without DeepInterpolation. The 3 columns on the right are horizontal, sagittal and coronal sections of the same movie in the first column. The mean was subtracted to better highlight small changes in signal.
Supp. Video 6	**Link:** https://www.dropbox.com/s/m4uqr7vgfga8kgg/Supplementary_video_6.mp4?dl=1 **Caption:** Example fMRI data. Left column is the original raw data. Middle column is the same data through the original processing pipeline, containing a gaussian kernel. The right column is the same data through DeepInterpolation.
Supp. Video 7	**Link:** https://www.dropbox.com/s/7cttm3107xlxpp1/Supplementary_video_7.mp4?dl=1 **Caption:** Example fMRI data with and without DeepInterpolation. The residual was calculated to illustrate the type of signal that was removed by DeepInterpolation.

Methods

Description of experimental data collection of datasets used in this study

We trained 4 denoising neuronal networks in this study: one for two-photon imaging experiments using

the Ai93(TITL-GCaMP6f) reporter line, one for the Ai148(TIT2L-GCaMP6f-ICL-tTA2) reporter line[26,27],

one for Neuropixels recordings using "Phase 3a" probes[28], and one for fMRI imaging using datasets from

a study published on OpenNeuro.org[29]. All raw datasets used for training are available at the time of

publication through AWS S3 buckets (Amazon.com, Inc., see

https://openneuro.org/datasets/ds001246/versions/1.2.1 and https://registry.opendata.aws/allen-brain-

observatory/). Importantly, each denoising network is tightly coupled to the inherent properties of the

datasets they were trained on (acquisition parameters, sample characteristics,...).

Calcium imaging in mice was performed with two different two-photon imaging instruments[12] (either a

Scientifica Vivoscope or a Nikon A1R MP+). Laser excitation was provided by a Ti:Sapphire laser

(Chameleon Vision–Coherent) at 910 nm. 512x512 Movies were recorded at 30 Hz with resonant scanners

over a 400-μm field of view .

All extracellular electrophysiology recordings were carried out with Neuropixels probes[28] acutely inserted

into the brains of awake mice. Data at each recording site was acquired at 30 kHz (spike band) and 2.5 kHz

(LFP band). The spike band (which was used for denoising) had a hardware gain settings of 500x and a 500

Hz high pass filter. Each probe contained 960 recording sites, with the 374 sites closest to the tip configured

for recording. Neural signals were routed to an integrated base containing filtering, amplification,

multiplexing, and digitization circuitry, and were streamed via an Ethernet link to the Open Ephys GUI[30]

for online visualization and disk writing. Training data consisted of 1-hour of segments extracted from 10

different ~2.5 hour long recordings (see below for information on the specific sessions used).

All fMRI datasets were collected using 3.0-Tesla Siemens MAGNETOM Trio A Tim scanner located at

the ATR Brain Activity Imaging Center. Methodology was previously described[29]. Briefly, the functional

images covered the entire brain (TR, 3,000 ms; TE, 30 ms; flip angle, 80°; voxel size, 3 × 3 × 3 mm; FOV,

192 × 192 mm; number of slices, 50, slice gap, 0 mm). The dataset contained fMRI data from five subjects

with 3 types of scanning sessions: "ses-perceptionTraining", "ses-perceptionTest" and "ses-imageryTest".

We trained our denoiser on "ses-perceptionTraining" sessions and measured the denoising performance on

"ses-perceptionTest" sessions.

Visual stimulation.

Visual stimuli in mice were displayed on an ASUS PA248Q LCD monitor, with 1,920 × 1,200 pixels (see

original data publication for more details[12]). Stimuli were presented monocularly, and the monitor was

positioned 15 cm from the eye and spanned 120° × 95° of visual space. Each monitor was gamma corrected

and had a mean luminance of 50 cd/m^2. To account for the close viewing angle, spherical warping was

applied to all stimuli to ensure that the apparent size, speed, and spatial frequency were constant across the

monitor as seen from the mouse's perspective.

Pre-processing steps

Two-photon imaging movies were motion-corrected similarly to our previous publication[12]. The motion

correction algorithm relied on phase correlation and only corrected for rigid translational errors. We used

these motion corrected movies for denoising.

For Neuropixels recordings, the median across channels was subtracted to remove common-mode noise.

The median was calculated across channels that were sampled simultaneously, leaving out adjacent

(even/odd) channels that are likely measuring the same spike waveforms, as well as reference channels

that contain no signal. For each sample, the median value of channels N:24:384, where N = [1,2,3,...,24],

was calculated, and this value was subtracted from the same set of channels. Importantly, this step removes

noise that is *correlated* across channels, without affecting the independent noise targeted by

DeepInterpolation. We performed denoising on the spike band after the median subtraction and offline

filtering steps (150 Hz highpass) were applied.

For fMRI recordings, we used raw, unprocessed Nifti-1 volume data provided on OpenNeuro.org (see

https://openneuro.org/datasets/ds001246/versions/1.2.1).

Detection of ROIs in two-photon data

We used two different segmentation algorithms in this study. The first one was described in a previous

publication and leverages a succession of morphological filters to extract binary masks surrounding active

pixels[12]. These masks are publicly available through the AllenSDK (see

https://allensdk.readthedocs.io/en/latest/). In all analysis related to **Supp. Fig. 5**, we applied these binary

masks to both raw and DeepInterpolation movies to extract matching calcium traces.

In all analysis related to **Fig. 2**, we used the sparse mode in Suite2P[16] to extract all individual filters. We

used default parameter values of this mode except for threshold_scaling, which was set to 3. With the

increased SNR achieved with DeepInterpolation, this single change limited the proportion of false positives

in the final set of filters. Using Suite2p sorting GUI, we then manually sorted filters. We excluded filters

present at the edge of the image, filters created by motion artifacts as well as features that did not cover any

neuronal segment present in the max projection image. Somatic and non-somatic ROIs were also manually

sorted based on the presence of a soma-excluded region in the filter. Filters that included a blurred out of

plane soma were considered non-somatic. Once the final set of filters were extracted, we reapplied those

weighted masks either to the original raw movie or the movie after DeepInterpolation to extract individual

traces.

Detection of neuronal units in electrophysiological data

Kilosort2 was used to identify spike times and assign spikes to individual units[31]. Traditional spike sorting

techniques extract snippets of the original signal and perform a clustering operation after projecting these

snippets into a lower-dimensional feature space. In contrast, Kilosort2 attempts to model the complete

dataset as a sum of spike "templates." The shape and locations of each template is iteratively refined until

the data can be accurately reconstructed from a set of N templates at M spike times, with each individual

template scaled by an amplitude, a.

Kilosort2 was applied to the original and denoised datasets using identical parameters (all default

parameters, except for ops.Th, which was lowered from [10 4] to [7 3] to increase the probability of

detecting low-amplitude units). Because the spike detection threshold is relative to the overall noise level

per channel, the absolute value of the threshold was lower following DeepInterpolation.

The Kilosort2 algorithm will occasionally fit a template to the residual left behind after another template

has been subtracted from the original data, resulting in double-counted spikes. This can create the

appearance of an artificially high number of ISI violations for one unit or artificially high zero-time-lag

synchrony between nearby units. To eliminate the possibility that this artificial synchrony will contaminate

data analysis, the outputs of Kilosort2 are post-processed to remove spikes with peak times within 5 samples

(0.16 ms) and peak waveforms within 5 channels (~50 microns).

Kilosort2 generates templates of a fixed length (2 ms) that matches the time course of an extracellularly

detected spike waveform. However, there are no constraints on template shape, which means that the

algorithm often fits templates to voltage fluctuations with characteristics that could not physically result

from the current flow associated with an action potential. The units associated with these templates are

considered "noise," and are automatically filtered out based on 3 criteria: spread (single channel, or >25

channels), shape (no peak and trough, based on wavelet decomposition), or multiple spatial peaks

(waveforms are non-localized along the probe axis). A final manual inspection step was used to remove

any additional noise units that were not captured by the automated algorithm.

Quality control for electrophysiological units

Units with action-potential-like waveforms detected by Kilosort2 are not necessarily high quality. To ensure

that units met basic quality standards for further analysis, we filtered them using three different quality

metrics,   computing   with   the   ecephys_spike_sorting   Python   package

(github.com/AllenInstitute/ecephys_spike_sorting):

● **ISI violations score < 0.5**. This metric is based on refractory period violations that indicate a unit

contains spikes from multiple neurons. The ISI violations metric represents the relative firing rate

of contaminating spikes. It is calculated by counting the number of violations <1.5 ms, dividing by

the amount of time for potential violations surrounding each spike, and normalizing by the overall

spike rate. It is always positive (or 0), but has no upper bound. See[32] for more details.

● **Amplitude cutoff < 0.1**. This metric provides an approximation of a unit's false negative rate.

First, a histogram of spike amplitudes is created, and the height of the histogram at the minimum

amplitude is extracted. The percentage of spikes above the equivalent amplitude on the opposite

side of the histogram peak is then calculated. If the minimum amplitude is equivalent to the

histogram peak, the amplitude cutoff is set to 0.5 (indicating a high likelihood that >50% of spikes

are missing). This metric assumes a symmetrical distribution of amplitudes and no drift, so it will

not necessarily reflect the true false negative rate.

● **Presence ratio > 0.95**. The presence ratio is defined as the fraction of blocks within a session that

include 1 or more spikes from a particular unit. Units with a low presence ratio are likely to have

drifted out of the recording, or could not be tracked by Kilosort2 for the duration of the experiment.

Applying these quality metrics removed 54% of detected units in the original data, and 60% of units after

denoising. Spike sorting after DeepInterpolation found more units regardless of the threshold used for each

QC metric (**Supp. Fig. 6B**).

Procedure for finding matched vs. new units

Following spike sorting steps, we searched for overlapping spikes between pairs of units detected before

and after denoising. Spikes were considered to overlap if they had a peak occurring within ±5 channels and

0.5 ms of one another. The number of overlapping spikes was used to compute three metrics, using the

original spike trains as "ground truth"[33].

● **Precision.** The fraction of denoised spikes that were also found in the original data.

● **Recall.** The fraction of original spikes that were also found in the denoised data.

● **Accuracy.** $N_{match} / (N_{denoised} + N_{original} - N_{match})$

Units were considered matched if they had an accuracy exceeding 0.7. Units were considered novel after

denoising if they had a total precision (summed over all original units) less than 0.5. Units were considered

undetected after denoising if they had a total recall (summed over all denoised units) less than 0.5.

Training of denoising networks

We used 3 different sets of environments for training deep neural networks. Two-photon denoising

networks were trained using TensorFlow 1.9.0, keras 2.2.4 and CUDA 9.0. Electrophysiology denoising

networks were trained using TensorFlow 2.0 and CUDA 10.0 through their built-in Keras libraries. fMRI

denoising networks were trained using TensorFlow 2.2 and CUDA 10.1.

We utilized NVIDIA Titan X, Geforce GTX 1080, and Tesla V100-SXD2 GPUs available on the Allen

Institute internal computing clusters. The fMRI denoising network was trained on Amazon AWS using the

p2.8xlarge and p3.8xlarge instance type depending on availability.

We used an L1 loss during training for both two-photon imaging and fMRI datasets. Electrophysiological

datasets were trained with an L2 loss. All training was done with the RMSProp gradient descent algorithm

implemented in keras. Two-photon denoiser was trained with a batch size of 5 so as to fit on available GPU

memory. The learning rate was set to $5*10^{-4}$. The Neuropixels denoiser was trained with a batch size of

100, with the learning rate was set to 10^{-4}. The fMRI denoiser was trained with a batch size of 10,000. The

larger batch size was allowed by the smaller input-output size. The fMRI denoiser was trained with a

learning scheduler, initialized at 10^{-4}, dropping by half every 45 millions samples.

To facilitate training, all samples were mean-centered and normalized by a single shared value for each

experiment during training. For two-photon movies, the mean and standard deviation was pre-calculated

using the first 100 frames of the movie. For Neuropixels recordings, the mean and standard deviation was

pre-calculated using the 200,000 samples. For fMRI recordings, we extracted the centered volume of the

movie that was 1/4th of the total movie size and averaged all voxels.

A detailed step by step pseudocode description of this process is available in **Supp. Appendix 1**.

Inference of final datasets with trained networks

Once a DeepInterpolation network was learned, inference was performed by streaming entire experiments

through the same fixed network. To match the conditions in training, each dataset was mean-centered and

normalized following the same procedure used during training. Output denoised data were brought back to

their original scale after going through the DeepInterpolation model.

Quantification   of   SNR

In the two-photon data, SNR was defined as the ratio of the mean fluorescence value divided by the standard

deviation along the temporal dimension. In ideal photon shot-noise limited conditions, this SNR is

proportional to the square root of N, where N is the photon flux detected per pixel.

In the Neuropixels data, SNR for individual units was defined as the ratio of the maximum peak-to-peak

waveform   amplitude   to   the   RMS   noise   on   the   peak   channel.

In the fMRI data, tSNR of individual voxels was defined as the ratio of the mean BOLD signal value

divided by standard deviation along the temporal dimension.

Analysis of natural movie responses

<u>Noise and signal correlation analysis in two-photon data</u>

For each natural movie presentation, we extracted the corresponding ROI traces. The signal correlation was

computed by averaging all 10 presentations of the movie and calculating the Pearson pairwise correlation

of those averaged responses between pairs of ROIs.

The noise correlation was calculated by calculating the Pearson correlation of individual trial responses

between a pair of ROIs and then averaging all 10 presentations of the movie.

<u>Response reliability in two-photon data</u>

The response reliability was calculated by first calculating the pearson correlation matrix of an ROI

individual response to a single presentation of a natural movie with other trials. For each ROI, we then

excluded auto-correlation values and averaged out all pairwise combinations. This process yielded a single

reliability measure for each ROI.

<u>Significant responses in Neuropixels data</u>

When analyzing spike data, the trial-to-trial correlation of the natural movie response depends heavily on

the bin size chosen. To determine responsiveness for Neuropixels data, we instead compared each unit's

natural movie PSTH (averaged across 25 trials) to a version in which all bins were temporally shuffled. A

Kolmogorov–Smirnov test between the original and shuffled PSTHs was used to determine the probability

that the response could have occurred by chance ($p < 0.05$ for significantly responsive units; see **Supp. Fig.**

7B for an example).

Synthetic data generation

We created realistic synthetic calcium imaging datasets using a recent approach called in silico Neural

Anatomy and Optical Microscopy (NAOMi)[14]. The code repository was kindly made available to us by

Alex Song and Adam Charles. Given the computational load of the model, we generated a single dataset

made of 15,000 frames simulating a 400x400 μm^2 field of view. Except for the field of view size, all

parameters were set to default values. We did not use a pre-trained network to denoise this dataset and

trained our DeepInterpolation model directly on this simulated data.

Comparison with Penalized Matrix Factorisation

A PMD docker repository was kindly made available to us by the Paninski lab and we collaborated to run

the PMD algorithm in the best conditions[13]. PMD was run on an AWS instance (m5.8xlarge) under a pre-

packaged jupyterhub environment (https://hub.docker.com/r/paninski/trefide). All movies were pre-

centered and normalized using code available in the trefide package (psd_noise_estimate).

DeepInterpolation code availability

Code for DeepInterpolation and all other steps in our algorithm are available online through a GitHub

repository (https://github.com/AllenInstitute/deepinterpolation). Example training and inference tutorial

code are available on the repository. Several Docker inference containers are available on Docker Hub (see

list below for more details). They allow inference using the TensorFlow ModelServer framework.

Code and data to regenerate all figures presented in this manuscript is available online through a GitHub

repository (https://github.com/AllenInstitute/deepinterpolation_paper).

Two-photon Ai93 excitatory line DeepInterpolation network:

Key recording parameters:

● 30Hz sampling rate, 400x400 μm^2 field of view, 512x512 pixels.

● 0.8 NA objective.

● 910 nm excitation wavelength.

● Gcamp6f calcium indicator.

● Ai93 reporter line expressed in excitatory neurons.

Docker hub id : 245412653747/deep_interpolation:allen_400um_512pix_30hz_ai93

Two-photon Ai148 excitatory line DeepInterpolation network:

Key recording parameters:

● 30 Hz sampling rate, 400x400 μm^2 field of view, 512x512 pixels.

● 0.8 NA objective.

● 910 nm excitation wavelength.

● Gcamp6f calcium indicator.

● Ai93 reporter line expressed in excitatory neurons.

Pre-processing: Individual movies were motion corrected. Each movie recording was mean-centered and

normalized with a single pair of value for all pixels

Docker hub id : 245412653747/deep_interpolation:allen_400um_512pix_30hz_ai148

<u>Neuropixels DeepInterpolation network:</u>

Key recording parameters:

●   Neuropixels Phase 3a probes

●   374 simultaneous recording sites across 3.84 mm, 10 reference channels

●   Four-column checkerboard site layout with 20 μm spacing between rows

●   30 kHz sampling rate

●   500x hardware gain setting

●   500 Hz high pass filter in hardware, 150 Hz high-pass filter applied offline

Pre-processing: Median subtraction was applied to individual probes to remove signals that were

common across all recording sites. Each probe recording was mean-centered and normalized with a single

pair of value for all nodes on the probe.

Docker hub id : 245412653747/deep_interpolation:allen_neuropixel

<u>fMRI DeepInterpolation network:</u>

Key recording parameters:

●   TR, 3,000 ms; TE, 30 ms; flip angle, 80°; voxel size, 3 × 3 × 3 mm; FOV, 192 × 192 mm;

724   number of slices, 50, slice gap, 0 mm

Pre-processing: N/A

Docker hub id : 245412653747/deep_interpolation:allen_3_3_3_tr_3000_fmri

Data availability

The two-photon imaging and Neuropixels raw data can be downloaded from the following S3 bucket:

arn:aws:s3:::allen-brain-observatory

Two-photon imaging files are accessed according to Experiment ID, using the following path:

visual-coding-2p/ophys_movies/ophys_experiment_<Experiment   ID>.h5

We used a random subset of 1144 experiments for training the denoising network for Ai93, and 397

experiments for training the denoising network for Ai148. The list of used experiments IDs is available in

json files (in deepinterpolation/examples/json_data/) on the DeepInterpolation GitHub repository. The

majority of these experiment IDs are available on the S3 bucket. Some experimental data has not been

released to S3 at the time of publication.

Neuropixels raw data is accessed by Experiment ID and Probe ID, using the following paths:

visual-coding-neuropixels/raw-data/<Experiment ID>/<Probe ID>/spike_band.dat

The dat files have the median subtraction post-processing applied, but do not include an offline highpass

filter. Prior to DeepInterpolation, we extracted 3600 seconds of data from each of the recordings listed in

Table 1.

Experiment ID	Probe ID	Start time	Brain Structures	Used for training
778998620	792626851	4665.8179 s	VISl (LM), CA1, CA3	No
787025148	792586842	4672.1967 s	VISp (V1), SUB, LP	No
768515987	773549856	4672.2224 s	VISrl (RL), CA1, DG, APN	Yes
794812542	810758787	4665.8332 s	VISrl (RL), CA1, DG, APN	No
778998620	792626853	4665.8179 s	VISal (AL), CA1, CA3, DG, LGv	No
767871931	773462997	4672.2352 s	VISal (AL), CA1, CA3, DG, LT	Yes
779839471	792645501	4672.3841 s	VIS, CA1, CA3, DG, LGd	No
771160300	773621948	4672.3791 s	VISal (AL), CA1, CA3, DG, LGd	Yes
781842082	792586881	4672.1312 s	VISp (V1), SUB, SGN	No
793224716	805124815	4675.2401 s	VISrl (RL), CA1, DG, LP, APN	No

745   **Table 1. Details of Neuropixels data used for DeepInterpolation training and inference.**

746   To train the fMRI denoiser, we used datasets that can be downloaded from an S3 bucket:

747   arn:aws:s3:::openneuro.org/ds001246

749   We trained our denoiser on all "ses-perceptionTraining" sessions, across 5 subjects (3 perception training

750   sessions, 10 runs each).