Noise correlations for faster and more robust learning

Matthew R. Nassar[1,2], Daniel Scott[1,3], Apoorva Bhandari[1,3]

1. Robert J. & Nancy D. Carney Institute for Brain Science, Brown University, Providence RI 02912-1821, USA
2. Department of Neuroscience, Brown University, Providence RI 02912-1821, USA
3. Department of Cognitive, Linguistic, and Psychological Sciences, Providence RI, 02912-1821

Acknowledgements:

We would like to thank Josh Gold, Rex Liu, Michael Frank, Drew Linsley, Chris Moore and Jan Drugowitsch for helpful discussion. This work was funded by NIH grants F32MH102009 and R00AG054732 (MRN), NINDS R21NS108380 (AB). The funders had no role in study design, data collection and analysis, decision to publish or preparation of the manuscript.

Competing interests:

The authors have no financial or non-financial conflicts of interest related to this work.

Abstract:

Distributed population codes are ubiquitous in the brain and pose a challenge to downstream neurons that must learn an appropriate readout. Here we explore the possibility that this learning problem is simplified through inductive biases implemented by stimulus-independent noise correlations that constrain learning to task-relevant dimensions. We test this idea in a set of neural networks that learn to perform a perceptual discrimination task. Correlations among similarly tuned units were manipulated independently of overall population signal-to-noise ratio in order to test how the format of stored information affects learning. Higher noise correlations among similarly tuned units led to faster and more robust learning, favoring homogenous weights assigned to neurons within a functionally similar pool, and could emerge through Hebbian learning. When multiple discriminations were learned simultaneously, noise correlations across relevant feature dimensions sped learning whereas those across irrelevant feature dimensions slowed it. Our results complement existing theory on noise correlations by demonstrating that when such correlations are produced without significant degradation of the signal-to-noise ratio, they can improve the speed of readout learning by constraining it to appropriate dimensions.

Significance statement:

Positive noise correlations between similarly tuned neurons theoretically reduce the representational capacity of the brain, yet they are commonly observed, emerge dynamically in complex tasks, and persist even in well-trained animals. Here we show that such correlations, when embedded in a neural population with a fixed signal to noise ratio, can improve the speed and robustness with which an appropriate readout is learned. In a simple discrimination task such correlations can emerge naturally through Hebbian learning. In more complex tasks that require multiple discriminations, correlations between neurons that similarly encode the task-relevant feature improve learning by constraining it to the appropriate task dimension.

Introduction:

The brain represents information using distributed population codes in which particular feature values are encoded by large numbers of neurons. One advantage of such codes is that a pooled readout across many neurons can effectively reduce the impact of stimulus-independent variability (noise) in the firing of individual neurons (Pouget et al., 2000). However, the extent to which this benefit can be employed in practice is constrained by noise correlations, or the degree to which stimulus-independent variability is shared across neurons in

the population (Averbeck et al., 2006). In particular, positive noise correlations
between neurons that share the same stimulus tuning can reduce the amount of
decodable information in the neural population (Averbeck et al, 2006; Moreno-
Bote et al., 2014; Hu et al., 2014). Despite their detrimental effect on encoding,
noise correlations of this type are reliably observed, even after years of training
on perceptual tasks (Cohen and Kohn, 2011). Furthermore, noise correlations
between neurons are dynamically enhanced under conditions where two neurons
provide evidence for the same response in a perceptual categorization task
(Cohen and Newsome, 2008), raising questions about whether they might serve
a function rather than simply reflecting a suboptimal encoding strategy.
100
At the same time, learning to effectively read out a distributed code also poses a
significant challenge. Learning the appropriate weights for potentially tens of
thousands of neurons in a low signal-to-noise regime is a difficult, high-
dimensional problem, requiring a very large number of learning trials and
entailing considerable risk of "over fitting" to specific patterns of noise
encountered during learning trials. Nonetheless, people and animals can rapidly
learn to perform perceptual discrimination tasks, albeit with performance that
does not approach theoretically achievable levels (Hawkey et al., 2004; Stringer
et al., 2019). In comparison, deep neural networks capable of achieving human
level performance typically require a far greater number of learning trials than
would be required by humans and other animals (Tsividis et al., 2017). This
raises the question of how brains might implement inductive biases to enable
efficient learning in high dimensional spaces.
114
Here we address open questions about noise correlations and learning by
considering the possibility that noise correlations facilitate faster learning.
Specifically, we propose that noise correlations aligned to task relevant
dimensions could reduce the effective dimensionality of learning problems,
thereby making them easier to solve. For example, perceptual stimuli often
contain a large number of features that may be irrelevant to a given
categorization. At the level of a neural population, individual neurons may differ in
the degree to which they encode task irrelevant information, thus making the
learning problem more difficult. In principle, noise correlations in the relevant
dimension could reduce the effects of this variability on learned readout. Such an
explanation would be consistent with computational analyses of Hebbian learning
rules (Oja, 1982), which can both facilitate faster and more robust learning
(Krotov and Hopfield, 2019), and in turn may induce noise correlations. We
propose that faster learning of an approximate readout is made possible through
low dimensional representations that share both signal and noise across a large
neural population. In particular, we hypothesize that representations
characterized by enhanced noise correlations among similarly tuned neurons can
improve learning by focusing adjustments of the readout onto task relevant
dimensions.

134
We explore this possibility using neural network models of a two-alternative
forced choice perceptual discrimination task in which the correlation among
similarly tuned neurons can be manipulated independently of the overall
population signal-to-noise ratio. Within this framework, noise correlations, which
can be learned through Hebbian mechanisms, speed learning by forcing learned
weights to be similar across pools of similarly tuned neurons, thereby ensuring
learning occurs over the most task relevant dimension. We extend our framework
to a cued multidimensional discrimination task and show that dynamic noise
correlations similar to those observed in vivo (Cohen and Newsome, 2008),
speed learning by constraining weight updates to the relevant feature space. Our
results demonstrate that when information is extrinsically limited, noise
correlations can make learning faster and more robust by controlling the
dimensions over which learning occurs.
148
149

Materials and Methods:

Our goal was to understand the computational principles through which
correlations in the activity of similarly tuned neurons affect the speed with which
downstream neurons could learn an effective readout. Previous work has
demonstrated that manipulating noise correlations while maintaining a fixed
variance in the firing rates of individual neurons leads to changes in the
theoretical encoding capacity of a neural population (Averbeck et al., 2006;
Moreno-Bote et al., 2014). To minimize the potential impact of such encoding
differences, we took a different approach; rather than setting the variance of
individual neurons in our population to a fixed value, we set the signal-to-noise
ratio of our population to a fixed value. Thus, our approach does not ask how
maximum information can be packed into a given neural population's activity, but
rather how the strategy for packing a *fixed* amount of information in a population
affects the speed with which an appropriate readout of that information can be
learned. We implement this approach in a set of neural networks described in
more detail below.

Learning readout in perceptual learning task

Simulations and analyses for a simple perceptual discrimination task were
performed with a simplified and statistically tractable two-layer feed-forward
neural network (figure 3A). The input layer consisted of two homogenous pools of
100 units that were each identically "tuned" to one of two motion directions (left,
right). On each trial normalized firing rates for the neural population were drawn
from a multivariate normal distribution that was specified by a vector of stimulus-
dependent mean firing rates (signal: +1 for preferred stimulus, -1 for non-
preferred stimulus) and a covariance matrix. All elements of the covariance
matrix corresponding to covariance between units that were "tuned" to different

stimuli were set to zero. The key manipulation was to systematically vary the
magnitude of diagonal covariance components (eg. noise in the firing of
individual units) and the "same pool" covariance elements (eg. shared noise
across identically tuned neurons) while maintaining a fixed level of variance in
the summed population response for each pool:

$$\sigma^2_{pool} = n\sigma^2_{unit} + n(n-1)Cov(within\ pool) \quad Eq.1$$

Where σ^2_{pool} is the variance on the sum of normalized firing rates from neurons
within a given pool, n is the number of units in the pool and the within pool
covariance ($Cov(within\ pool)$) specifies the covariance of pairs of units
belonging to the same pool. Signal-to-noise ratio (SNR) was defined as the
population signal (preferred-antipreferred) divided by the standard deviation of
the population response in the signal dimension. SNR was set to be 2 for each
individual pool of neurons, leading to a signal-to-noise ratio for the entire
population (both pools) equal to $2\sqrt{2}$. Given this constraint, the fraction of noise
that was shared across neurons within the same pool was manipulated as
follows:
192

$$\sigma^2_{unit} = \frac{\sigma^2_{pool}}{n + n(n-1)\phi} \quad Eq.2$$

$$Cov(within\ pool) = \phi\sigma^2_{unit} \quad Eq.3$$

Where ϕ reflects the fraction of noise that is correlated across units, which we
refer to in the text as noise correlations. Noise correlations (ϕ) were manipulated
across values ranging from 0 to 0.2 for simulations. Note that, since ϕ appears in
the denominator of equation 2, adding noise correlations while sustaining a fixed
population signal-to-noise ratio leads to lower variance in the firing rates of single
neurons, differing from previous theoretical assumptions (compare figure 2a&b).
201
202 The input layer of the neural network was fully connected to an output layer
203 composed of two output units representing left and right responses. Output units
204 were activated on a given trial according to a weighted function of their inputs:
205
206 $$\boldsymbol{F_{output}} = \boldsymbol{wF_{input}} \quad Eq.4$$
207
208 Where F_{output} is a vector of firing rates of output units, F_{input} is a vector of firing
209 rates of the input units, and w is the weight matrix. Firing of an individual output
210 unit can also be written as a weighted sum over input unit activity:
211

$$212 \qquad\qquad F_j \; = \; \sum_{i=1}^{200} w_{i,j}\, F_i \quad Eq.\,5$$

214 where F_j reflects the firing of the jᵗʰ output unit, F_i reflects the firing of the iᵗʰ input
215 unit, and $w_{i,j}$ reflects the weight of the connection between the iᵗʰ input unit and
216 the jᵗʰ output unit. Actions were selected as a softmax function of output firing
217 rates:

$$219 \qquad\qquad p(A_j) \; = \; \frac{e^{\beta F_j}}{\sum_k e^{\beta F_k}} \quad Eq.\,6$$

220 where β is an inverse temperature, which was set to a relatively deterministic
221 value (10000). Learning was implemented through reinforcement of weights to
222 the selected output neuron (subscripted j below):

$$224 \qquad\qquad \Delta w_{i,j} = \quad \alpha \delta F_i \quad Eq.\,7$$

Where F_i is the normalized firing rate of the iᵗʰ input neuron, δ is the reward
prediction error experienced on a given trial [+0.5 for correct trials and -0.5 for
error trials], and α is a learning rate (set to 0.0001 for simulations in figure 2). The
network was trained to correctly identify two stimuli (each of which was preferred
by a single pool of input neurons) over 100 trials (the last 20 trials of which were
considered testing). Simulations were repeated 1000 times for each level of ϕ
and performance measures were averaged across all repetitions. Mean accuracy
per trial across all simulations was convolved with a Gaussian kernel (standard
deviation = 0.5 trials) for plotting in figure 2b. Mean accuracy across the final 20
trials was used as a measure of final accuracy (figure 2e). Statistics on model
performance were computed as Pearson correlations between noise correlations
ϕ and performance measures across all simulations and repetitions.

Analytical learning trajectories

One advantage of our simple network architecture is its mathematical tractability.
To complement the simulations described above, we also explored learning in
the network analytically. Specifically, we decomposed weight updates into two
categories: weight updates in the signal dimension, and weight updates
perpendicular to the signal dimension. Weight updates in the signal dimension
improved performance through alignment with the signal itself, whereas weight
updates in the perpendicular dimension limited performance through chance

alignment with trial-to-trial noise. An intuition for our approach and derivation are
provided below.
247
The two-alternative discrimination task is a one dimensional signal detection
problem, because it depends only on the difference between two scalars. In
particular, if $y = [y_1, y_2]$ denotes the readout activity the pair of pools and r
denotes the response (e.g. r=-1 is "respond left" and r=1 is "respond right"), then
$r = r(y_1 - y_2) = r(\Delta y)$. In addition, $\Delta y = w_1 x - w_2 x \equiv \Delta w x$, where x reflects
the firing rates of the input units and w_1 reflects the vector of weights mapping
input activation onto output unit 1 (y_1). To determine how accuracy is impacted
by noise correlations, we ask how Mahalanobis distance (d'), mean separation
(d), and signal variance (σ_{s*}^2) diverge over training time for the different noise
correlation conditions. The effective variance, σ_{s*}^2, differs from the true noise
variance in the signal dimension due to the fact that out-of-signal-dimension
noise is transferred into the signal dimension by imperfect readout weights.
Intuitively, learning speed may be improved by noise correlations because less
out-of-dimension noise is "learned into" the weights, thereby reducing the transfer
out-of-dimension noise into the signal space on any given trial.
263
264 The logic of training is as follows: On a correct trial, the weights to the chosen
265 unit are incremented by a multiple of the input vector x. That is:
266
267 $$w_i \rightarrow w_i + \alpha \delta x \quad Eq. 8$$
268
269 Here α reflects a positive learning rate, x reflects the activity of the input units and
270 δ is the reward prediction error, which we use as the absolute reward prediction
271 error instead of the signed one in this section for convenience.
272
273 Now the input is a sum of signal and zero mean noise:
274
275 $$x = \mu + \xi \quad Eq. 9$$
276
277 The expectation of noise is zero ($E(\xi) = 0$) and the signal μ can take only two
278 values $\mu \in \{\pm\mu_0\}$. Therefore if the weights start from some value $\Delta w(0)$, we will
279 find that:
280
281 $$E[\Delta w(t)] = t\alpha\delta\mu_0 + \Delta w(0) \quad Eq\ 10$$
282
283 Where t reflects the current timestep of learning. In words, we expect the amount
284 of signal in the weights to increase linearly over time. This means that we expect
285 the response to a noise-free signal (μ_0) after t timesteps to be:
286
287 $$\Delta y(\mu_0, t) = \Delta w(t)\mu_0 + \Delta w_0\mu_0 = t\alpha\delta||\mu_0||^2 + \Delta w_0\mu_0 \quad Eq. 11$$
288

289 This is the measure d between the two Gaussian peaks in the one dimensional
290 signal detection problem described above. Below, we ignore the initial weight
291 term, since it does not change over time. To compute accuracy and d' over
292 training time we also need to compute the effective variance along the signal
293 dimension. First we note that the noise can be decomposed as:
294
$$\xi = \xi_s + \xi_\perp \quad Eq.\,12$$
296
297 where ξ_s and $\xi_\perp$ are orthogonal components of the noise in the signal dimension
298 (ξ_s) and perpendicular to the signal dimension ($\xi_\perp$). Here we consider cases
299 where the noise along the signal dimension (ξ_s) has constant variance, following
300 on the assumptions that SNR is set to a constant value and that the mean signal
301 is the same for all noise correlation conditions.
302
303 The difference Δy on any given trial decomposes into a sum of terms, one
304 reflecting weight-based transfer of signal and one reflecting the transfer of
305 orthogonal noise. This latter term arises because the weights are not, at any
306 finite time, a perfect matched filter for the signal. Letting subscripts s and $\perp$
307 continue to denote "signal" and "perpendicular" dimensions, we have:
308
$$\Delta y = \Delta w x \quad Eq.\,13$$
310
$$\Delta y = (\Delta w_s + \Delta w_\perp)(\mu + \xi_s + \xi_\perp) \quad Eq.\,14$$
312
$$\Delta y = \Delta w_s (\mu + \xi_s) + \Delta w_\perp \xi_\perp \quad Eq.\,15$$
314 where the final equation reflects the absence of terms that have zero products by
315 definition of the perpendicular subspaces. The variance of Δy can be computed
316 using independence and orthogonality properties:
317
$$Var(\Delta y) = Var(\Delta w_s (\mu + \xi_s) + \Delta w_\perp \xi_\perp) \quad Eq.\,16$$
319
$$Var(\Delta y) = \Delta w_s^2 E[\xi_s^2] + \Delta w_\perp^2 E[\xi_\perp^2] \quad Eq.\,17$$
321
322
For any given network, the term $\Delta w(t)_\perp^2$ is a mean-zero diffusion process arising
from the fact that noise is added to the weights at every time step. For the
Gaussian white noise case, $\Delta w(t)_\perp^2$ is equivalent to Brownian motion in the (n-1)
dimensions perpendicular to the signal. Because (n-1) is not small, the summed
empirical variance of these processes, operative on each component, is likely to
be close to the theoretical total variance. If we split the term $\Delta w(t)_\perp^2$ into the (n-1)
components and index them with i, this gives:
330

331
$$\Delta w_\perp^i = \alpha\delta\sqrt{\frac{t}{n-1}}\,\sigma_\perp \quad Eq.\,18$$

The denominator of (n-1) appears here because Brownian motion determines
growth in the variance of each of the (n-1) perpendicular noise directions among
which the total variance $\sigma_\perp$ is distributed. Technically, our manipulation of the
noise covariance fixes the variance in a second direction of the space as well, so
that noise variance is actually evenly distributed over only (n-2) of the (n-1)
perpendicular dimensions, but this inhomogeneity is inconsequential if n is not
small; In effect, we are ignoring an order 1 term relative to an order n term for
simplicity. In order to understand how perpendicular weights grow with time, we
need only to determine $\sigma_\perp(\phi)$, where ϕ is the parameter controlling the noise
covariance matrix in our simulations. Specifically, the first row of the covariance
matrix takes the form:

345
$$\Sigma(\xi)_1 = [b, \phi b, \phi b, \dots \phi b, 0, \dots, 0] \quad Eq.\,19$$

347 Using the additional fact that row-sums are set to σ_s^2 to control the signal
348 variance, we find that:

350
$$b + \left(\frac{n}{2} - 1\right)\phi b = \sigma_s^2 \quad Eq.\,20$$

352
$$b = \frac{2\sigma_s^2}{2 + (n-2)\phi} \quad Eq.\,21$$

354 Since the eigenvalues of $\Sigma(\xi)$ are the variances in different dimensions of the
355 space, we can find the total variance perpendicular to the signal by subtracting
356 the known signal variance from the trace of $\Sigma(\xi)$:

358
$$\sigma_\perp^2 = Var(\xi_\perp) = Tr\big(\Sigma(\xi)\big) - Var(\xi_s) \quad Eq.\,22$$

360
$$\sigma_\perp^2 = Var(\xi_\perp) = nb - \sigma_s^2 \quad Eq.\,23$$

362 Putting this together with previous results, we have:

364
$$Var(\Delta y) = (t\alpha\delta\mu\sigma_s)^2 + \frac{t(\alpha\delta)^2\sigma_\perp^4}{n-1} \quad EQ\ 24$$

366 This provides analytic prediction for the variance of our readout decision variable
367 Δy after learning for t trials, using a learning rate α to learn from from prediction
368 errors of magnitude δ. Note that σ_s was fixed in our simulations, but that $\sigma_\perp^4$
369 depends on ϕ through b, such that larger values of ϕ lead to smaller values of b,

and thus a smaller $\sigma_\perp^2$, reducing the second term in Eq 24. Furthermore, since the first term in Eq 24 scales with t^2 its contributions dominate as more trials are observed. This leads to identical asymptotic variance in the limit of large t, since the first term does not depend on ϕ.

By combining the mean and variance information in Equations 11 and 24 we computed accuracy as one minus the cumulative probability density of the Gaussian distribution $N(t\alpha\delta||\mu_0||^2, \ (t\alpha\delta\mu\sigma_s)^2 + \frac{t(\alpha\delta)^2\sigma_\perp^4}{n-1})$ evaluated from negative infinity to zero.

Noise correlations with fixed signal-to-noise ratio and single unit variance

Noise correlations produced by the simulations above lead to reductions in the overall variance of single unit firing rates. In order to validate that our results depend on maintaining signal-to-noise, rather than depending on single-unit variance, we also consider the case where noise correlations are introduced with a fixed level of single unit variance. In this case, signal-to-noise ratio was maintained by scaling the amount of signal according to the level of noise correlations (see https://github.com/NassarLab/NoiseCorrelation for full derivation):

$$S_{neuron} = \sqrt{\frac{\sigma_{unit}^2\,(1 + (n-1)\phi)}{n}} \quad Eq.\,25$$

where S_{neuron} reflects the amount of signal provided by each unit, σ_{unit}^2 reflects a fixed variance assigned to each unit, n reflects the number of units in the pool, and ϕ reflects the level of noise correlations. Thus, when we simulated correlated noise using this equation, neurons maintained the same variance (σ_{unit}^2), but increased their signal relative to the zero noise correlation condition ($\phi = 0$).

Noise correlations that are bounded to a maximum signal-to-noise ratio

In order to examine the importance of our assumption regarding fixed signal-to-noise ratio, we also considered a parameterized model where signal (S_{neuron}) was set according to a linear mixture:

$$S_{neuron} = m\sqrt{\frac{\sigma_{unit}^2\,(1 + (n-1)\phi)}{n}} + (1-m)\sqrt{\frac{\sigma_{unit}^2}{n}} \quad Eq.\,26$$

where m is a mixing parameter that combines the signal producing a fixed signal-to-noise ratio (first term) with a fixed signal that does not depend on the level of noise correlations (second term). When m is set to 1, this parameterized model

408 obeys our assumptions regarding fixed signal to noise ratio, but when m is set to
409 0, the model conforms to more standard assumptions regarding fixed single unit
410 variance and signal.
411

Hebbian learning of noise correlations in three-layer network

We extended the two-layer feed-forward architecture described above to include
a third hidden layer in order to test whether Hebbian learning could facilitate
production of noise correlations among similarly tuned neurons (figure 5A). The
input layer was fully connected to the hidden layer, and each layer contained 200
neurons. In the input layer, neurons were homogenously tuned (100 leftward,
100 rightward) as described above, with ϕ set to zero (eg. no noise correlations).
Weights to the hidden layer were initialized to favor one-to-one connections
between input layer units and hidden layer units by adding a small normal
random weight perturbation (mean=0, standard deviation = 0.01) to an identity
matrix (though an alternate initialization was used to produce figure 6-1). During
learning, weights between the input and hidden layer were adjusted according to
a normalized Hebbian learning rule:
425

$$\Delta W = \alpha_{hebb} \boldsymbol{F'_1} \boldsymbol{F_2} \quad Eq.\,27$$

426
427

Where $\boldsymbol{F'_1}$ is a normalized vector of firing rates corresponding to the input layer
and $\boldsymbol{F_2}$ is a normalized vector of firing rates corresponding to the hidden layer
units. The learning rate for Hebbian plasticity (α_{hebb}) was set to 0.00005 for
simulations in figure 4 and 0.0005 for simulations in figure extended data figure
6-1. Weights were normalized after Hebbian learning to ensure that the
Euclidean norm of the incoming weights to each unit in layer two was equal to
one. The model was "trained" over 100 trials in the same perceptual
discrimination task described above and an additional 100 trials of the task were
completed to measure emergent noise correlations in the hidden layer. Noise
correlations were measured by regressing out variance attributable to the
stimulus on each trial, and then computing the Pearson correlation of residual
firing rate across each pair of neurons for the 100 testing trials (figure 4B&C).
440

Learning readout in multiple discrimination task

In order to test the impact of contextual noise correlations on learning (Cohen
and Newsome, 2008), the perceptual discrimination task was extended to include
two dimensions and two interleaved trial types: one in which an up/down
discrimination was performed (vertical), and one in which a right/left
discrimination was performed (horizontal). Each trial contained motion on the
vertical axis (up or down) and on the horizontal axis (left or right), but only one of
these motion axes was relevant on each trial as indicated by a cue.

449
In order to model this task, we extended our two-layer feed-forward network to
include 4 pools of input units, 4 output units, and 2 task units (figure 5A). Each
homogenous pool of 100 input units encoded a conjunction of the movement
directions (up-right, up-left, down-right, down-left). On each trial, the mean firing
rate of each input unit population was determined according to their tuning
preferences:
456
457
458 $$\mu = V + H \quad Eq.\,28$$
459
where V was +1/-1 for trials with the preferred/anti-preferred vertical motion
direction H was +1/-1 for trials with the preferred/anti-preferred horizontal motion
direction. Firing rates for individual neurons were sampled from a multivariate
Gaussian distribution with mean μ and a covariance matrix that depended on trial
type (vertical versus horizontal) and the level of same pool, relevant pool, and
irrelevant pool correlations.
466
467   In order to create a covariance matrix, we stipulated a desired standard error of
468   the mean for summed population activity (SEM=20 for simulations in figure 5)
469   and determined the summed population variance that would correspond to that
470   value (σ^2_{pool}). We then determined the variance on individual neurons that would
471   yield this population response under a given noise correlation profile as follows:
472

473 $$\sigma^2_{unit} = \frac{\sigma^2_{pool}}{n + n(n-1)\phi_{same} + n^2\phi_{relevant} - n^2\phi_{irrelevant}} \quad Eq.\,29$$

474
where ϕ_{same} is the level of same pool correlations (range: 0-0.2 in our
simulations), $\phi_{relevant}$ is the level of relevant pool correlations (range: 0-0.2 in our
simulations), $\phi_{irrelevant}$ is the level of irrelevant pool correlations (range: 0-0.2 in
our simulations. Note that increasing the same pool or in pool correlations
reduces the overall variance in order to preserve the same level of variance on
the task relevant dimension in the population response, but that increasing
irrelevant pool correlations has the opposite effect. Covariance elements of the
covariance matrix were determined as follows:
483

484 $$Cov(same\ pool) = \phi_{same}\sigma^2_{unit} \quad Eq.\,30$$

485 $$Cov(relevant\ pool) = \phi_{relevant}\sigma^2_{unit} \quad Eq.\,31$$

486 $$Cov(irrelevant\ pool) = \phi_{irrelevant}\sigma^2_{unit} \quad Eq.\,32$$

487 Variance and covariance values above were used to construct a covariance
488 matrix for each trial type (vertical/horizontal) as depicted in figure 1.
489

Covariance matrix: vertical trials

490
Figure 1: Schematic of covariance matrix for two-dimensional motion discrimination task.
The covariance between units with different motion tuning (reflected by the arrows labeling
columns and rows) is schematically represented for a simplified input layer, where only two
identically tuned neurons are in each pool (in actual simulations there were 100 units per pool).
Same pool correlations are controlled by covariance elements between neurons with identical
tuning (orange boxes). Relevant pool correlations are controlled by covariance elements between
neurons that are similarly tuned to the task-relevant feature. Task irrelevant correlations are
controlled by covariance elements between neurons that are similarly tuned to the task-irrelevant
feature. The covariance matrix shown here is for a vertical trial – on a horizontal trial the irrelevant
pool and relevant pool locations would be reversed. Covariance elements for pairs of neurons
that differed in tuning on both dimensions were set to zero. Each input population has been
depicted as two units here for presentation purposes. Background color reflects the case where
same pool correlations = 0.2 and relevant pool correlations = 0.1.

504
505
Output units corresponded to the four possible task responses (up, down, left,
right) and were activated according to a weighted sum of their inputs as

described previously. Task units were modeled as containing perfect information
about the task cue (vertical versus horizontal) and each task unit projected with
strong fixed weights (1000) to both responses that were appropriate for that task.
Decisions were made on each trial by selecting the output unit with the highest
activity level. Weights to chosen output unit were updated using the same
reinforcement learning procedure described in the two alternative perceptual
learning task.
515
516
517
518   **Results:**
519
We examine how noise correlations affect learning in a simplified neural network
where the appropriate readout of hundreds of weakly tuned units is learned over
time through reinforcement. In order to isolate the effects of noise correlations on
learning, rather than their effects on other factors such as representational
capacity, we consider population encoding schemes at the input layer that can be
constrained to a fixed signal-to-noise ratio. This assumption differs from previous
work on noise correlations where the *variance* of the neural population is
assumed to be fixed and covariance is changed to produce noise correlations,
thereby affecting the representational capacity of the population (figure 2A;
(Averbeck et al., 2006; Moreno-Bote et al., 2014)). Under our assumptions, a
fixed signal-to-noise ratio can be achieved for any level of noise correlations by
scaling the variance (figure 2B; equations 1-3), or, alternately scaling the
magnitude of the signal (equation 25). While we do not discount the degree to
which noise correlations affect the encoding potential of neural populations, we
believe that in many cases the relevant information is limited by extrinsic factors
(eg. the stimulus itself, or upstream neural populations providing input (Ecker et
al., 2011; Beck et al., 2012; Kanitscheider et al., 2015)). Under such conditions,
reducing noise correlations can increase information only until it saturates
because all of the available incoming information is encoded. Beyond that,
increasing encoding potential is not possible as it would be tantamount to the
population "creating new information" that was not communicated by inputs to the
population. Therefore, our framework can be thought of as testing how best to
format limited available information in a neural population in order to ensure that
an acceptable readout can be rapidly and robustly learned.
544
We propose that within this framework, noise correlations of the form that have
previously been shown to limit encoding are beneficial because they constrain
learning to occur over the most relevant dimensions. In general, a linear readout
can be thought of as hyperplane serving as a classification boundary in an N
dimensional space, where N reflects the number of neurons in a population.
Learning in such a framework involves adjustments of the hyperplane to
minimize classification errors. The most useful adjustments are in the dimension

that best discriminates signal from noise (central arrows in figure 2C&D), but
adjustments may also occur in dimensions orthogonal to the relevant one (such
as "twisting" of the hyperplane depicted by curved arrows in figure 2C&D) that
could potentially impair performance, or slow down learning. Our motivating
hypothesis is that by focusing population activity into the task relevant dimension,
noise correlations can increase the fraction of hyperplane adjustments that occur
in the task relevant dimension (figure 2D), thus reducing the effective
dimensionality of readout learning.
560

561
562
563
Figure 2: Modeling noise correlations with extrinsic constraint on signal-to-noise ratio. A)
Previous work has modeled noise correlations by assuming that population variance is fixed and
that covariance is manipulated to produce noise correlations. Under such assumptions, the firing
rate of two similarly tuned neurons is plotted in the absence (solid) or presence (dotted) of
information-limiting noise correlations. **B)** Here we assume that the signal-to-noise ratio of the
neural population is limited to a fixed value such that noise correlations between similarly tuned

neurons do not affect theoretical performance. Thus, the percent overlap of blue (target) and red
(non-target) activity profiles does not differ in the presence (dotted) or absence (solid) of noise
correlations. **C&D)** Under this assumption, noise correlations among similarly tuned neurons
could compress the population activity to a plane orthogonal to the optimal decision boundary,
thereby minimizing boundary adjustments in irrelevant dimensions (**C**) and maximizing boundary
adjustments on relevant ones (**D**).
576
577
578   *Noise correlations enable faster learning in a fixed signal-to-noise regime*
579
In order to test our overarching hypothesis, we constructed a fully connected two-
layer feed-forward neural network in which input layer units responded to one of
two stimulus categories (pool 1 & pool 2) and each output unit produced a
response consistent with a category perception (left/right units in figure 3A). On
each trial, the network was presented with one stimulus at random, and input
firing for each pool was drawn from a multivariate Gaussian with a covariance
that was manipulated while preserving the population signal-to-noise ratio.
Output units were activated according to a weighted average of inputs and a
response was selected according to output unit activations. On each trial,
weights to the selected action were adjusted according to a reinforcement
learning rule that strengthened connections that facilitated a rewarded action and
weakened connections that facilitated an unrewarded action (Law and Gold,
2009).
593
Noise correlations led to faster and more robust learning of the appropriate
stimulus-response mapping. All neural networks learned to perform the requisite
discrimination, but neural networks that employed correlations among similarly
tuned neurons learned more rapidly (figure 3B). After learning, networks that
employed such noise correlations assigned more homogenous weights to input
units of a given pool than did networks that lacked noise correlations (compare
figure 3C&D). This led to better trained-task performance (figure 3E; Pearson
correlation between noise correlations and test performance: $R = 0.29$, $p < 10e-$
50) and greater robustness to adversarial noise profiles (figure 3F; $R = 0.81$, $p <$
$10e-50$) in the networks that employed noise correlations. Critically, these
learning advantages emerged despite the fact that optimal readout of all
networks achieved similar levels of performance and robustness (figure 3E&F,
compare optimal readout across conditions).
607
608
609

610
611
612
Figure 3: Correlated noise within similarly tuned populations leads to faster and more robust learning of a perceptual discrimination. A) A two-layer feed-forward neural network was designed to solve a two alternative forced choice motion discrimination task at or near

perceptual threshold. Input layer contains two homogenous pools of identically tuned neurons
that provide evidence for alternate percepts (eg. leftward motion versus rightward motion) and
output neurons encode alternate courses of actions (eg. saccade left versus saccade right).
Layers are fully connected with weights randomized to small values and adjusted after each trial
according to rewards (see methods). **B)** Average learning curves for neural network models in
which population signal-to-noise ratio in pools 1 and 2 were fixed, but noise correlations
(grayscale) were allowed to vary from small (dark) to large (light) values. **C&D)** Weight
differences (left output – right output) for each input unit (color coded according to pool) after 100
timesteps of learning for low (**C**) and high (**D**) noise correlations. **E**) Accuracy in the last 20
training trials is plotted as a function of noise correlations for learned readouts (orange) and
optimal readout (red). Lines/shading reflect Mean/SEM. F) The shortest distance, in terms of
neural activation, required to take the mean input for a given category (eg. left or right) to the
boundary that would result in misclassification is plotted for the final learned (orange) and optimal
(red) weights for each noise correlation condition (abscissa). Lines/shading reflect Mean/SEM.
630
631
632 *Learning benefits from noise correlations are greatest for large, low SNR populations.*
633
In order to better understand how noise correlations promoted faster learning we
developed an analytical method for describing learning trajectories (see
methods). Our method considered the impacts of two influences on weight
updates over time: 1) weight updates in the signal dimension that tend to align
with the signal and improve performance and 2) weight updates perpendicular to
the signal dimension, which through chance alignment with trial-to-trial firing rate
variability allow noise to impact decisions and therefore and hinder performance
(fig 4a). Noise correlations implemented using our methods decreased the latter
form of weight updates (fig 4b), leading updates in the signal dimension to more
quickly dominate performance (fig 4c), thereby speeding analytical predictions for
learning (fig 4d&e). The analytically derived learning advantage for fixed-SNR
noise correlations was greatest for situations in which SNR was relatively low
and neural populations were large (fig 4f).
647

Figure 4: Analytic learning trajectories demonstrate advantage for noise correlations when pools are large and signal-to-noise ratio is low. A) Our analytical approach decomposed weight updates Δw into two components: updates in the signal dimension (Δw_s) and updates perpendicular to the signal dimension ($\Delta w_\perp$). **B)** Standard deviation of the variability in the dimension perpendicular to the signal (ordinate) decreased as a function of noise correlation (abscissa) as derived with our analytic approach (blue line, see methods), and for the empirical simulations. **C)** For a given noise correlation (0.02 in this example) learning yielded weight changes in the signal dimension (blue circles) as well in the perpendicular dimension (red circles) that could be described analytically (blue and red lines). Circles represent average values from twenty empirical simulations. **D&E)** Theoretical accuracy derived from the analytical weights reproduces learning advantages observed in our simulations for higher levels of noise correlations (compare yellow to blue curves) and demonstrates convergence with sufficient observations (**E**; note abscissa in log units). **F)** Improvement in average accuracy over first 100 trials, derived analytically by taking the mean difference between yellow and blue curves in (**D**), is indicated in color across a range of signal-to-noise ratios (ordinate) and neural population sizes (abscissa). The largest learning advantages for noise correlations were observed in large neural populations that contained limited stimulus information (moderately low SNR). Red X depicts parameters used for our simulations.

The advantage of noise correlations for learning speed did not depend on specific assumptions about whether SNR was balanced by adjusting signal or noise. We employed an alternate method for creating fixed-SNR noise correlations that amplified signal, rather than reducing variance, in order to maintain SNR for higher levels of noise correlation (equation 25). Such noise correlations could be thought of as reflecting amplification of both signal and shared noise that would result from top down recurrent feedback (Haefner et al., 2016). Under such assumptions, noise correlations sped learning and led to more robust weight profiles, similarly to in our previous simulations (Extended data Fig 3-1).

Noise correlations that do not maintain signal-to-noise ratio can introduce a tradeoff between learning speed and asymptotic performance.

In contrast, our learning speed results depended critically on the assumption that signal-to-noise ratio is maintained across different levels of noise correlation. In order to test this dependency, we examined performance of a family of models that contained a single parameter allowing them to range in assumptions from fixed SNR (m=1) to fixed signal and single unit variance, analogous to assumptions of Averbeck and colleagues (Averbeck et al., 2006) (m=0). Consistent with our previous results, noise correlations improve learning in the m=1 case, and consistent with Averbeck 2006, asymptotic performance is reduced by noise correlations in the m=0 case (Fig 5). Interestingly, for intermediate assumptions between these two extremes, noise correlations promote faster learning improving performance in the short run, but at the cost of lower asymptotic accuracy. Thus, under such assumptions, adjusting noise correlations between similarly tuned neurons could potentially optimize a tradeoff between short-term gains from rapid learning and long term gains from higher asymptotic performance.

**Figure 5: Impact of noise correlations on learning depends on the assumption that signal-
to-noise ratio is fixed.** Accuracy (ordinate) as a function of trials (abscissa) for a model without
noise correlations (red) and for several models that generate noise correlations (0.2) under
different assumptions. The lightest color reflects a case where signal-to-noise ratio of the
population is completely preserved, analogous to our previous simulations. The darkest color

reflects a case where the variance and signal of individual neurons is fixed, leading to a
population signal-to-noise ratio that varies as a function of noise correlations. Intermediate colors
indicate parametric mixtures of these assumptions created using equation 26. Note that learning
advantages depend critically on assumptions about signal-to-noise ratio, and that noise
correlations implemented using intermediate assumptions introduce a tradeoff between faster
learning (gray lines above red line for early trials) and lower asymptotic performance (gray lines
below red line for later trials).
713
714
715 *Hebbian learning can produce useful noise correlation structure.*
716
Given that noise correlations implemented in our previous simulations, like those
observed in the brain, depended on the tuning of individual units, we tested
whether such noise correlations might be produced via Hebbian plasticity.
Specifically, we considered an extension of our neural network in which an
additional intermediate layer is included between input and output neurons
(figure 6a). Input units were again divided into two pools that differed in their
encoding, but variability was uncorrelated across neurons within a given pool.
Connections between the input layer and intermediate layer were initialized such
that each input unit strongly activated one intermediate layer unit, and shaped
over time using a Hebbian learning rule that strengthened connections between
co-activated neuron pairs. Despite the lack of noise correlations in the input layer
of this network (figure 6b; mean[std] in pool residual correlation = 0.0015[0.10]),
neurons in the intermediate layer developed tuning-specific noise correlations of
the form that were beneficial for learning in the previous simulations (figure 6c;
mean[std] in pool residual correlation = 0.55[0.07]; t-test on difference from input
layer correlations $t = 443$, $dof = 19800$, $p < 10e\text{-}50$). Hebbian learning produced
analogous noise correlation structure when initialized with random weights
(Extended data figure 6-1). The ability of Hebbian learning to reduce the
dimensionality of the input units is consistent with previous theoretical work
showing that it extracts the first principal component of the input vector, which in
this case, is the signal (Oja, 1982)

Figure 6: Hebbian learning produces correlations within similarly tuned populations in a perceptual discrimination task. A) Three-layer neural network architecture. Input layer feeds forward to hidden layer, which is fully connected to an output layer. Input layer provides uncorrelated inputs to hidden layer through projection weights that are adjusted according to a Hebbian learning rule. **B&C)** Noise correlations observed in hidden layer units at the beginning (**B**) and end (**C**) of training.

Dynamic, task-dependent noise correlations speed learning by constraining it to relevant
feature dimensions.

In order to understand how noise correlations might impact learning in mixed
encoding populations, we extended our perceptual discrimination task to include
two directions of motion discrimination (eg. up/down and left/right). On each trial,
a cue indicated which of two possible motion discriminations should be
performed (figure 7A, left; (Cohen and Newsome, 2008)). We extended our
neural network to include four populations of one hundred input units, each
population encoding a conjunction of motion directions (up-right, up-left, down-
right, down-left; figure 7A; input layer). Two additional inputs provided a perfectly
reliable "cue" regarding the relevant feature for the trial (figure 7A; task units).
Four output neurons encoded the four possible responses (up, left, down, right)
and were fully connected to the input layer (figure 7A; output layer). Task units
were hard wired to eliminate irrelevant task responses, but weights of input units
were learned over time as in our previous simulations.

Learning performance in the two-feature discrimination task depended not only
on the level of noise correlations, but also on the type. As in the previous
simulation, adding noise correlations to each individual population of identically
tuned units led to faster learning of the appropriate readout (Figure 7B&C,
compare blue and yellow; Figure 7D&E, vertical axis; mean[std] accuracy across
training: 0.54[0.05] and 0.70[0.05] for minimum (0) and maximum (0.2) in pool
correlations, t-test for difference in accuracy: $t = 226$, *dof* $= 19998$, $p < 10e-50$).

However, the more complex task design also allowed us to test whether dynamic
trial-to-trial correlations might further facilitate learning. Specifically, correlations
that increase shared variability among units that contribute evidence to the same
response have been observed previously (Cohen and Newsome, 2008), and
could in principle focus learning on relevant dimensions (figure 2C&D) even
when those dimensions change from trial to trial. Indeed, adding correlations
among separate pools that share the same encoding of the relevant feature (eg.
UP on a vertical trial) led to faster learning (figure 7B; mean[std] training
accuracy for model with relevant pool correlations: 0.73[0.05], *t*-test for difference
from in pool correlation only model: $t = 34$, *dof* $=19998$, $p < 10e-50$) and weights
that more closely approached the optimal readout (figure 7E, horizontal axis). In
contrast, when positive noise correlations were introduced across separate
encoding pools that shared the same tuning for the irrelevant dimension on each
trial (eg. UP on a horizontal trial) learning was impaired dramatically (figure 7C;
mean[std] training accuracy for model with irrelevant pool correlations:
0.51[0.05], *t*-test for difference from in pool correlation only model: $t = -278$, *dof*
$=19998$, $p < 10e-50$) and learned weights diverged from the optimal readout
(figure 7F, horizontal axis). Model performance differences were completely

attributable to learning the readout, as all models performed similarly when using
the optimal readout (extended data figure 7-1).
804
In order to test the idea that noise correlations might focus learning onto relevant
dimensions, we extracted weight updates from each trial and projected these
updates into a two-dimensional space where the first dimension captured the
relative sensitivity to leftward versus rightward motion and the second dimension
captured relative sensitivity to upward versus downward motion. In the model
where input units were only correlated within their identically tuned pool, weight
updates projected in all directions more or less uniformly (figure 7G), and did not
differ systematically across trial types (vertical versus horizontal). However,
dynamic noise correlations that shared variability across the relevant dimension
tended to push weight updates onto the appropriate dimension for a given trial
(figure 4F; *t*-test for difference in the magnitude of updating in up/down and
left/right dimensions across conditions [up/down – left/right]: $t = 3.4$, *dof*=98, $p =$
0.001). In contrast, dynamic noise correlations that shared variability across the
irrelevant dimension tended to push weight updates onto the wrong dimension
(figure 4H; t-test for difference in the magnitude of updating in up/down and
left/right dimensions across conditions [up/down – left/right]: $t = -9.5$, *dof*=98, $p =$
10e-14). Both of these trends were consistent across simulations, providing an
explanation for the performance improvements achieved by relevant noise
correlations (projection of learning onto an appropriate dimension) and
performance impairments produced by irrelevant noise correlations (projection of
learning onto an inappropriate dimension).

Figure 7: Task dependent noise correlations affect learning speed by projecting learning onto specific feature dimensions. **A)** A neural network was trained to perform two interleaved motion discrimination tasks (left; (Cohen and Newsome, 2008)). Network schematic (right) depicts two-layer feed-forward network in which each homogenous pool of input units represents two dimensions of motion (up versus down, and left versus right), and output units produce

responses in favor of alternative actions (up, down, left, right). Each homogenous pool of input
units is identically tuned to one of four conjunctions of movement directions: up-left, down-left, up-
right, down-right. Two additional input units provide cue information that biases output units to
produce an output corresponding to the discrimination appropriate on this trial (eg. horizontal or
vertical). Noise correlations were manipulated among 1) identically tuned neurons (blue
rectangle; same pool), 2) neurons that have similar encoding of the task relevant feature (green
rectangle pair in vertical trials; relevant pool), and 3) neurons that have similar encoding of the
task irrelevant feature (green rectangle pair in horizontal trials; irrelevant pool). **B&C**) Learning
curves showing accuracy (ordinate) over trials (abscissa) for models 1) lacking noise correlations
(orange), 2) containing noise correlations that are limited to neurons that have same tuning for
both features (same pool; blue), 3) containing same pool noise correlations along with
correlations between neurons in different pools that have the same tuning for the task-relevant
feature (in pool+rel pool; green in **B**), and 4) containing in-pool noise correlations along with
correlations between neurons in different pools that have the same tuning for the task irrelevant
feature (in pool+irrel pool; green in **C**). **D&E**) Distance between learned weights and the optimal
readout (color) for models that differ in their level of "in pool" correlations (ordinate, both plots),
"relevant pool" correlations (abscissa, **D**), and "irrelevant pool" correlations (abscissa, **E**). **F,G,H**)
Weight updates for example learning sessions were projected into a two dimensional space in
which net updates to the relative contribution of vertical motion information (eg. up versus down)
is represented on the abscissa and updates to the relative contribution of horizontal motion
information (eg. left versus right) is represented on the ordinate. Arrows reflect single trial weight
updates and are colored according to the trial type (red = horizontal discrimination, blue = vertical
discrimination). Weight updates for a model with only "in pool" correlations look similar across trial
types (**G**), but weight updates for a model with "relevant pool" correlations indicate more weight
updating on the relevant feature (**F**), whereas the opposite was observed in the case of "irrelevant
pool" correlations (**H**).
868
869
870 **Discussion:**
871
Taken together, our results suggest that in settings where the population signal-
to-noise ratio is limited by external factors (eg. inputs) and relevant task
representations are low dimensional, noise correlations can make learning faster
and more robust by focusing learning on the most relevant dimensions. We
demonstrate this basic principle in a simple perceptual learning task (figure 3),
where beneficial noise correlations between similarly tuned units could be
produced through a simple Hebbian learning rule (figure 6). We extended our
framework to a contextual learning task to demonstrate that dynamic noise
correlations that bind task relevant feature representations facilitate faster
learning (figure 7b&d) by pushing learning onto task-relevant dimensions (figure
7f). Given the pervasiveness of noise correlations among similarly tuned sensory
neurons (Zohary et al., 1994; Maynard et al., 1999; Bair et al., 2001; Averbeck
and Lee, 2003; Cohen and Maunsell, 2009; Huang and Lisberger, 2009; Ecker et
al., 2010; Gu et al., 2011; Adibi et al., 2013), and that the noise correlations
dynamics beneficial for learning in our simulations are similar to those that have
been observed *in vivo* (Cohen and Newsome, 2008), we interpret our results as
suggesting that noise correlations between similarly tuned neurons are a feature
of neural coding architectures that ensures efficient readout learning, rather than
a bug that limits encoding potential.

This interpretation rests on several assumptions in our model. Of particular importance is the assumption that signal-to-noise ratio of our populations is fixed, meaning that our manipulation of noise correlations can focus variance on specific dimensions without gaining or losing information. This assumption reflects conditions in which information is limited at the level of the inputs to the population, for instance due to noisy peripheral sensors (Beck et al., 2012; Kanitscheider et al., 2015). In such conditions, even with optimal encoding, population information saturates at an upper bound determined by the information available in the inputs to the population. Therefore, fixing the signal-to-noise ratio enabled us to examine the effect of noise correlations on downstream processes that learn to read-out the population code in the absence of any influence of noise correlations on the quantity of information contained within that population code.

Previous theoretical work exploring the role of noise correlations in encoding has typically assumed that single neurons have a fixed variance, such that tilting the covariance of neural populations towards or away from the dimension of signal encoding would have a large impact on the amount of information that can be encoded by a population (figure 1a; (Averbeck et al., 2006; Moreno-Bote et al., 2014)). Such assumptions lead to the idea that positive noise correlations among similarly tuned neurons limit encoding potential, raising the question of why they are so common in the brain (Cohen and Kohn, 2011). In considering the implications of this framework, one important question is: if information encoded by the population can be increased by changing the correlation structure among neurons, where does this additional information come from? In some cases, the neural population in question may indeed receive sufficient task relevant information from upstream brain regions to reorganize its encoding in this way, but in other cases it is likely that information is limited by the inputs to a neural population (Kanitscheider et al., 2015; Kohn et al., 2016). In cases where incoming information is limited, further increasing representational capacity is not possible, and formatting information for efficient readout is essentially the best that the population code could do. Here we show that the noise correlations that have previously been described as "information limiting" are exactly the type of correlations that format information most efficiently for readout learning under such conditions.

Between these two bookends of a fixed signal-to-noise ratio and fixed single unit variance, we also simulated intermediate regimes which do not perfectly preserve the signal-to-noise ratio. In these intermediate regimes, a tradeoff emerges: noise correlations between similarly tuned neurons produce faster learning in the short term, at the cost of lower levels of asymptotic performance in the long run (Fig 5).

935
Jointly considering these perspectives on noise correlations provides a more
nuanced view of how neural representations are likely optimized for learning. In
order to optimize an objective function, a neural population can reduce correlated
noise in task relevant dimensions to increase its representational capacity up to
some level constrained by its inputs (Figure 8, left). But once the population is
fully representing all task relevant information that has been provided to it, it can
additionally optimize representations by pushing as much variance onto task
relevant dimensions as possible, thereby affording efficient learning in
downstream neural populations (Figure 8, right). In short, optimization of a neural
population code does not occur in a vacuum, and instead depends critically on
both upstream (eg. input constraints) and downstream (eg. readout) neural
populations (Figure 8). In this view, if a neural population is *not* fully representing
the decision relevant information made available to it, then learning could
improve the efficiency of representations by reducing rate limiting noise
correlations as has been observed in some paradigms (Gu et al., 2011; Ni et al.,
2018). In contrast, once available information is fully represented, readout
learning could be further optimized by reformatting population codes such that
variability is shared across neurons with similar tuning for the relevant task
feature, producing the sorts of dynamic noise correlations that have been
observed in well trained animals (Cohen and Newsome, 2008).
956
957

958
Figure 8: Information maximization and dimensionality reduction can be useful for
learning under different situations and have opposite effects on noise correlations among
similarly tuned units. A) A schematic representation of a three layer neural network in which
units provide evidence for one of two categorizations (blue/orange). In the left network, the hidden
layer initially has access to information from only one of two independent units in each pool, but
weights are subsequently adjusted to increase task-relevant information represented in the
hidden layer (pink). In the right network, the hidden layer initially has access to all task-relevant
information, but weights are subsequently adjusted to share signal and noise across similarly

tuned units to afford dimensionality reduction (purple). Note that the information maximizing weight adjustments (left, pink) increase signal-to-noise ratio in the hidden layer but preserve the variance in firing rate of individual neurons, whereas the dimensionality reducing weight adjustments (right, purple) maintain a fixed signal-to-noise ratio in hidden units, but decrease the variance of individual units by averaging across multiple similarly tuned inputs. Dashed lines to output units reflect weights that need to be learned based on feedback. **B)** Task relevant information (mutual information between unit activations and stimulus category; abscissa) is depicted for each layer (ordinate). Weight adjustments affording information maximization (left) increase task relevant information in the hidden layer (pink), whereas weight adjustments that afford dimensionality reduction (right) do not affect task-relevant information in the hidden layer itself but instead increase the rate of learning in the output layer, thereby leading to more task-relevant information in the output layer (purple). **C)** Weight adjustments for information maximization (pink in panel A) *decrease* correlations among hidden units A&B by removing shared input from a single input unit and instead providing independent sources of input to each unit (pink arrows). In contrast, weight adjustments for dimensionality reduction *increase* noise correlations among hidden units A&B by providing them with the same mixture of information from the two identically tuned input units. We propose that both of these processes play a critical role in learning and that changes in noise correlations across learning will depend critically on which process dominates. As shown in panel B, this will depend critically on whether the neural population in question has already fully represented information available from its inputs. In principle, these processes could occur serially, with early learning maximizing information available in intermediate layers (left) and later learning compressing that information into a format allowing rapid readout learning (right).

In addition to key assumptions about an external limitation on signal-to-noise, our modeling included a number of simplifying assumptions that are unlikely to hold up in real neural populations. For example, we consider pools of neurons identically tuned to discrete stimuli, rather than a continuous space of stimuli and the heterogeneous populations observed in sensory cortical regions of the brain. Previous work has shown that noise correlations do not necessarily limit encoding potential in heterogenous populations with diverse tuning (Shamir and Sompolinsky, 2004; 2006; Chelaru and Dragoi, 2008; Ecker et al., 2011). A primary goal of our work was to identify the computational principles that control the speed at which readout can be learned, and our simplified populations are considerably more tractable and transparent than realistic neural populations. The principles that we identify here are certainly at play in real neural populations, albeit with implications that are far less transparent. In particular, in a population with diverse tuning profiles, the degree to which individual neurons are informative about a task-relevant discrimination will vary. To benefit learning through coordinated weighted changes, the correlation structure in such populations should reflect this variability. Empirical studies in macaques suggest that such variability is indeed present in real populations (Cohen and Maunsell, 2009; Rabinowitz et al., 2015; Ruff and Cohen, 2016; Bondy et al., 2018). We hope that our simplified results pave the way for future work to assess nuances that can emerge in mixed heterogeneous populations, or in more realistic architectures that go beyond the simple feed forward flow of information considered here.

Model predictions

Our work shows that noise correlations can focus the gradient of learning onto the most appropriate dimensions. Thus, our model predicts that the degree to which similarly tuned neurons are correlated during a perceptual discrimination should be positively related to performance improvements experienced on subsequent discriminations. In contrast, our model predicts that the degree of correlation between neurons that are similarly tuned to a task irrelevant feature should control the degree of learning on irrelevant dimensions, and thus negatively relate to performance improvements on subsequent discriminations. These predictions are strongest for the earliest stages of learning where weight adjustments are critical for subsequent performance, but they may also hold for later stages of learning, when correlations on irrelevant dimensions, including independent noise channels, could potentially lead to systematic deviations from optimal readout (figure 2f, 4d&e). These predictions could be tested by recording neural responses to a stimulus set that differs across multiple features to characterize both signal-to-noise and correlated variability for each feature discrimination. A strong prediction of our model is that correlated variability within neurons tuned to a given feature should be a predictor of subsequent learning of responses to that feature – above and beyond feature value discriminability.

One interesting special case involves tasks where the relevant dimension changes in an unsignaled manner (Birrell and Brown, 2000). In such tasks, noise correlations on the previously relevant dimension would, after such an "extradimensional shift", force gradients into a task-irrelevant dimension and thus impair learning performance. Interestingly, learning after extra-dimensional shifts can be selectively improved by enhancing noradrenergic signaling (Devauges and Sara, 1990; Lapiz and Morilak, 2006), which leads to increased arousal (Joshi et al., 2016; Reimer et al., 2016) and decreased cortical pairwise noise correlations in sensory and higher order cortex (Vinck et al., 2015; Joshi and Gold, n.d.). While these observations have been made in different paradigms, our model suggests that the reduction of noise correlations resulting from increased sustained levels of norepinephrine after an extradimensional shift (Bouret and Sara, 2005) could mediate faster learning by expanding the dimensionality of the learning gradients (compare figure 7G to 7F) to consider features that have not been task-relevant in the past.

Relation to attentional effects on noise correlations

In broad strokes, our finding that manipulation of noise correlations can focus variance on specific dimensions is in line with specific models of attention. In particular, noise reduction in task irrelevant dimensions might be considered in the same light that is often cast on suppression of task irrelevant dimensions by attentional mechanisms (Zanto and Gazzaley, 2009), in particular for purposes of

accurate credit assignment (Akaishi et al., 2016; Leong et al., 2017). One possibility is that compressed low-dimensional task representations in higher-order decision regions (Mack et al., 2019) may pass accumulated decision related information back to sensory regions in order to approximate Bayesian inference (Haefner et al., 2016; Bondy et al., 2018; Lange et al., 2018). As task relevant features are learned, such a process would promote noise correlations between neurons coding those relevant features. In other words, noise correlations may reflect a chosen hypothesis about which feature is relevant for predicting outcomes. Such a signal would be beneficial if it could persist (and thus preserve correlations between neurons tuned to the same task relevant feature value) until the time of feedback or reinforcement. Recent work showing strengthened noise correlations between similarly tuned neurons during working memory maintenance suggests that this might very well be the case (Merrikhi et al., 2018).

One observation that seems at odds with this interpretation is that manipulations of attention that cue a particular location or feature tend to decrease noise correlations among neurons that encode that location or feature (Cohen and Maunsell, 2009; Mitchell et al., 2009; Cohen and Maunsell, 2011; Herrero et al., 2013; Doiron et al., 2016). The effects of attentional cuing on noise correlations are dynamic in that cues change from one trial to the next, and contextual, in that noise correlations are reduced most dramatically among neurons that contribute evidence toward the same response in a manner consistent with increasing the amount of task relevant information in the population code (Ruff and Cohen, 2014; Downer et al., 2015). These effects are generally observed in well-trained animals during task performance and may not result from the same processes as the longer timescale noise correlation structure. Indeed, there may be a tradeoff between learning and performance, particularly if the computations giving rise to noise correlations do so without perfectly preserving signal-to-noise ratio. Our model does not account for these attentional effects, as we intentionally constrained the signal-to-noise ratio of our neural populations, thereby eliminating any potential changes in information encoding potential. However, we hope that our work motivates future studies to jointly consider the impacts of noise correlations on both learning and immediate performance in order to better understand the potentially competing imperatives that the brain faces in dynamically controlling the correlation structure of its own representations (see (Haimerl et al., 2019) for one attempt to do so).

Origins of useful noise correlations

One important question stemming from our work is how noise correlations emerge in the brain. This question has been one of longstanding debate, largely because there are so many potential mechanisms through which correlations

could emerge (Kanitscheider et al., 2015; Kohn et al., 2016). Noise correlations
could emerge from convergent and divergent feed forward wiring (Shadlen and
Newsome, 1998), local connectivity patterns within a neural population (Hansen
et al., 2012; Smith et al., 2013), or top down inputs provided separately to
different neural populations (Haefner et al., 2016). Here we show that static noise
correlations that are useful for perceptual learning emerge naturally from
Hebbian learning in a feed-forward network. While this certainly suggests that
useful noise correlations could emerge through feed forward wiring, it is also
possible to consider our Hebbian learning as occurring in a one-step recurrence
of the input units, and thus the same data support the possibility of noise
correlations through local recurrence. The context dependent noise correlations
that speed learning (figure 7), however, would not arise through simple Hebbian
learning. Such correlations could potentially be produced through selective top-
down signals from the choice neurons, as has been previously proposed
(Wimmer et al., 2015; Haefner et al., 2016; Bondy et al., 2018; Lange et al.,
2018). Moreover, top-down input may selectively target neuronal ensembles
produced through Hebbian learning (Collins and Frank, 2013). While previous
work has suggested that such a mechanism could be adaptive for accumulating
information over the course of a decision (Haefner et al., 2016), our work
demonstrates that the same mechanism could effectively be used to tag relevant
neurons for weight updating between trials, making efficient use of top-down
circuitry. Haimerl et al. recently made a similar point, showing that stochastic
modulatory signals shared across task-informative neurons can serve to tag
them for a decoder (Haimerl et al., 2019).
1128
1129 *Noise correlations as inductive biases*
1130
Artificial intelligence has undergone a revolution over the past decade leading to
human level performance in a wide range of tasks (Mnih et al., 2015). However,
a major issue for modern artificial intelligence systems, which build heavily on
neural network architectures, is that they require far more training examples than
a biological system would (Hassabis et al., 2017). This biological advantage
occurs despite the fact that the total number of synapses in the human brain,
which could be thought of as the free parameters in our learning architecture, is
much greater than the number of weights in even the most parameter-heavy
deep learning architectures. Our work provides some insight into why this occurs;
correlated variability across neurons in the brain constrain learning to specific
dimensions, thereby limiting the effective complexity of the learning problem
(figures 4A, 7F-G). We show that, for simple tasks, this can be achieved using
Hebbian learning rules (figure 6), but that contextual noise correlations, of the
form that might be produced through top-down signals (Haefner et al., 2016), are
critical for appropriately focusing learning in more complex circumstances. In
principle, algorithms that effectively learn and implement noise correlations might
reduce the amount of data needed to train AI systems by limiting degrees of

freedom to those dimensions that are most relevant. Furthermore, our work
suggests that large scale neural recordings in early stages of learning complex
tasks might serve as indicators of the inductive biases that constrain learning in
biological systems.

In summary, we show that under external constraints of task-relevant
information, noise correlations that have previously been called "rate limiting" can
serve an important role in constraining learning to task-relevant dimensions. In
the context of previous theory focusing on representation, our work suggests that
neural populations are subject to competing forces when optimizing covariance
structures; on one hand reducing correlations between pairs of similarly tuned
neurons can be helpful to fully represent available information, but increasing
correlations among similarly tuned neurons can be helpful for assigning credit to
task relevant features. We believe that this view of the learning process not only
provides insight to understanding the role of noise correlations in the brain, but
opens up the door to better understand the inductive biases that guide learning in
biological systems.

References:

Adibi M, McDonald JS, Clifford CWG, Arabzadeh E (2013) Adaptation improves
        neural coding efficiency despite increasing correlations in variability. Journal
        of Neuroscience 33:2108–2120.

Akaishi R, Kolling N, Brown JW, Rushworth M (2016) Neural Mechanisms of
        Credit Assignment in a Multicue Environment. Journal of Neuroscience
        36:1096–1112.

Averbeck BB, Latham PE, Pouget A (2006) Neural correlations, population
        coding and computation. Nature Reviews Neuroscience 7:358–366.

Averbeck BB, Lee D (2003) Neural noise and movement-related codes in the
        macaque supplementary motor area. Journal of Neuroscience 23:7630–
        7641.

Bair W, Zohary E, Newsome WT (2001) Correlated firing in macaque visual area
        MT: time scales and relationship to behavior. Journal of Neuroscience
        21:1676–1697.

Beck JM, Ma WJ, Pitkow X, Latham PE, Pouget A (2012) Perspective. Neuron
        74:30–39.

Birrell JM, Brown VJ (2000) Medial frontal cortex mediates perceptual attentional

set shifting in the rat. Journal of Neuroscience 20:4320–4324.

Bondy AG, Haefner RM, Cumming BG (2018) Feedback determines the structure
of correlated variability in primary visual cortex. Nature Publishing Group:1–
15.

Bouret S, Sara SJ (2005) Network reset: a simplified overarching theory of locus
coeruleus noradrenaline function. Trends in Neurosciences 28:574–582.

Chelaru MI, Dragoi V (2008) Efficient coding in heterogeneous neuronal
populations. Proceedings of the National Academy of Sciences 105:16344–
16349.

Cohen MR, Kohn A (2011) Measuring and interpreting neuronal correlations.
Nature Publishing Group 14:811–819.

Cohen MR, Maunsell JHR (2009) Attention improves performance primarily by
reducing interneuronal correlations. Nature Publishing Group 12:1594–1600.

Cohen MR, Maunsell JHR (2011) Using neuronal populations to study the
mechanisms underlying spatial and feature attention. Neuron 70:1192–1204.

Cohen MR, Newsome WT (2008) Context-Dependent Changes in Functional
Circuitry in Visual Area MT. Neuron 60:162–173.

Collins AGE, Frank MJ (2013) Cognitive control over learning: creating,
clustering, and generalizing task-set structure. Psychological Review
120:190–229.

Devauges V, Sara SJ (1990) Activation of the noradrenergic system facilitates an
attentional shift in the rat. Behavioural Brain Research 39:19–28.

Doiron B, Litwin-Kumar A, Rosenbaum R, Ocker GK, Josić K (2016) The
mechanics of state-dependent neural correlations. Nature Publishing Group
19:383–393.

Downer JD, Niwa M, Sutter ML (2015) Task engagement selectively modulates
neural correlations in primary auditory cortex. Journal of Neuroscience
35:7565–7574.

Ecker AS, Berens P, Keliris GA, Bethge M, Logothetis NK, Tolias AS (2010)
Decorrelated neuronal firing in cortical microcircuits. Science 327:584–587.

Ecker AS, Berens P, Tolias AS, Bethge M (2011) The effect of noise correlations
in populations of diversely tuned neurons. Journal of Neuroscience
31:14272–14283.

Gu Y, Liu S, Fetsch CR, Yang Y, Fok S, Sunkara A, DeAngelis GC, Angelaki DE
(2011) Perceptual learning reduces interneuronal correlations in macaque
visual cortex. Neuron 71:750–761.

Haefner RM, Pietro Berkes, Fiser J (2016) Perceptual Decision-Making as
Probabilistic Inference by Neural Sampling. Neuron 90:649–660.

Haimerl C, Savin C, Simoncelli EP (2019) Flexible and accurate decoding of
neural populations through stochastic comodulation. Biorxiv 21:598.

Hansen BJ, Chelaru MI, Dragoi V (2012) Correlated variability in laminar cortical
circuits. Neuron 76:590–602.

Hassabis D, Kumaran D, Summerfield C, Botvinick M (2017) Neuroscience-
Inspired Artificial Intelligence. Neuron 95:245–258.

Hawkey DJC, Amitay S, Moore DR (2004) Early and rapid perceptual learning.
Nature Publishing Group 7:1055–1056.

Herrero JL, Gieselmann MA, Sanayei M, Thiele A (2013) Attention-induced
variance and noise correlation reduction in macaque V1 is mediated by
NMDA receptors. Neuron 78:729–739.

Hu, Y., Zylberberg, J., & Shea-Brown, E. (2014). The sign rule and beyond: boundary
effects, flexibility, and noise correlations in neural population codes. PLoS Comput
Biol, 10(2), e1003469.

Huang X, Lisberger SG (2009) Noise correlations in cortical area MT and their
potential impact on trial-by-trial variation in the direction and speed of
smooth-pursuit eye movements. Journal of Neurophysiology 101:3012–3030.

Joshi S, Gold JI (n.d.) Context-Dependent Relationships between Locus
Coeruleus Firing Patterns and Coordinated Neural Activity in the Anterior
Cingulate Cortex. Biorxiv.

Joshi S, Li Y, Kalwani RM, Gold JI (2016) Relationships between Pupil Diameter
and Neuronal Activity in the Locus Coeruleus, Colliculi, and Cingulate Cortex.
Neuron 89:221–234.

Kanitscheider I, Coen-Cagli R, Pouget A (2015) Origin of information-limiting
noise correlations. Proceedings of the National Academy of Sciences
112:E6973–E6982.

Kohn A, Coen-Cagli R, Kanitscheider I, Pouget A (2016) Correlations and
Neuronal Population Information. Annu Rev Neurosci 39:237–256.

Krotov D, Hopfield JJ (2019) Unsupervised learning by competing hidden units.

Proceedings of the National Academy of Sciences 116:7723–7731.

Lange RD, Chattoraj A, Beck JM, Yates JL, Haefner RM (2018) A confirmation
bias in perceptual decision-making due to hierarchical approximate inference.
Biorxiv.

Lapiz MDS, Morilak DA (2006) Noradrenergic modulation of cognitive function in
rat medial prefrontal cortex as measured by attentional set shifting capability.
Neuroscience 137:1039–1049.

Law C-T, Gold JI (2009) Reinforcement learning can account for associative and
perceptual learning on a visual-decision task. Nature Neuroscience 12:655–
663.

Leong YC, Radulescu A, Daniel R, DeWoskin V, Niv Y (2017) Dynamic
Interaction between Reinforcement Learning and Attention in
Multidimensional Environments. Neuron 93:451–463.

Mack ML, Preston AR, Love BC (2019) Ventromedial prefrontal cortex
compression during concept learning. Nature Communications:1–11.

Maynard EM, Hatsopoulos NG, Ojakangas CL, Acuna BD, Sanes JN, Normann
RA, Donoghue JP (1999) Neuronal interactions improve cortical population
coding of movement direction. Journal of Neuroscience 19:8083–8093.

Merrikhi Y, Clark K, Noudoost B (2018) Concurrent influence of top-down and
bottom-up inputs on correlated activity of Macaque extrastriate neurons.
Nature Communications 9:5393.

Mitchell JF, Sundberg KA, Reynolds JH (2009) Spatial attention decorrelates
intrinsic activity fluctuations in macaque area V4. Neuron 63:879–888.

Mnih V, Kavukcuoglu K, Silver D, Rusu AA, Veness J, Bellemare MG, Graves A,
Riedmiller M, Fidjeland AK, Ostrovski G, Petersen S, Beattie C, Sadik A,
Antonoglou I, King H, Kumaran D, Wierstra D, Legg S, Hassabis D (2015)
Human-level control through deep reinforcement learning. Nature 518:529–
533.

Moreno-Bote R, Beck J, Kanitscheider I, Pitkow X, Latham P, Pouget A (2014)
Information-limiting correlations. Nature Publishing Group 17:1410–1417.

Ni AM, Ruff DA, Alberts JJ, Symmonds J, Cohen MR (2018) Learning and
attention reveal a general relationship between population activity and
behavior. Science 359:463–465.

Oja E (1982) Simplified neuron model as a principal component analyzer. Journal

of Mathematical Biology:1–7.

Pouget A, Dayan P, Zemel R (2000) Information processing with population
codes. Nature Reviews Neuroscience 1:125–132.

Rabinowitz NC, Goris RL, Cohen M, Simoncelli EP (2015) Attention stabilizes the
shared gain of V4 populations. eLife 4:e08998.

Reimer J, McGinley MJ, Liu Y, Rodenkirch C, Wang Q, McCormick DA, Tolias
AS (2016) Pupil fluctuations track rapid changes in adrenergic and
cholinergic activity in cortex. Nature Communications 7:13289.

Ruff DA, Cohen MR (2014) Attention can either increase or decrease spike count
correlations in visual cortex. Nature Publishing Group 17:1591–1597.

Ruff DA, Cohen MR (2016) Stimulus Dependence of Correlated Variability across
Cortical Areas. Journal of Neuroscience 36:7546–7556.

Shadlen MN, Newsome WT (1998) The variable discharge of cortical neurons:
implications for connectivity, computation, and information coding. J Neurosci
18:3870–3896.

Shamir M, Sompolinsky H (2004) Nonlinear population codes. Neural Comput
16:1105–1136.

Shamir M, Sompolinsky H (2006) Implications of neuronal diversity on population
coding. Neural Comput 18:1951–1986.

Smith MA, Jia X, Zandvakili A, Kohn A (2013) Laminar dependence of neuronal
correlations in visual cortex. Journal of Neurophysiology 109:940–947.

Stringer C, Michaelos M, Pachitariu M (2019) High precision coding in mouse
visual cortex. Biorxiv.

Tsividis P, Pouncy T, Xu JL, Tenenbaum JB, Gershman SJ (2017) Human
Learning in Atari. 2017 AAAI Spring Symposium Series, Science of
Intelligence: Computational Principles of Natural and Artificial Intelligence:1–
4.

Vinck M, Batista-Brito R, Knoblich U, Cardin JA (2015) Arousal and Locomotion
Make Distinct Contributions to Cortical Activity Patterns and Visual Encoding.
Neuron 86:740–754.

Wimmer RD, Schmitt LI, Davidson TJ, Nakajima M, Deisseroth K, Halassa MM
(2015) Thalamic control of sensory selection in divided attention. Nature
526:705–709.

Zanto TP, Gazzaley A (2009) Neural Suppression of Irrelevant Information
Underlies Optimal Working Memory Performance. Journal of Neuroscience
29:3059–3066.

Zohary E, Shadlen MN, Newsome WT (1994) Correlated neuronal discharge rate
and its implications for psychophysical performance. Nature 370:140–143.

1326

1327
1328
1329
1330 Extended data:
1331
1332
1333

1334
**Extended data figure 3-1: Noise correlations that maintain signal-to-noise ratio by scaling
signal lead to faster and more robust learning of a perceptual discrimination.** This figure is
a replication of results reported in figure 3 of the main text, except that noise correlations are
produced using equation 25 such that each unit maintains the same fixed variance across noise
correlation conditions, and signal is scaled to maintain a fixed signal-to-noise ratio. **A)** A two-layer
feed-forward neural network was designed to solve a two alternative forced choice motion
discrimination task at or near perceptual threshold. Input layer contains two pools of neurons that
provide evidence for alternate percepts (eg. leftward motion versus rightward motion) and output

neurons encode alternate courses of actions (eg. saccade left versus saccade right). Layers are
fully connected with weights randomized to small values and adjusted after each trial according to
rewards (see methods). **B)** Average learning curves for neural network models in which
population signal-to-noise ratio in pools 1 and 2 were fixed, but noise correlations (grayscale)
were allowed to vary from small (dark) to large (light) values. **C&D)** Weight differences (left output
– right output) for each input unit (color coded according to pool) after 100 timesteps of learning
for low (**C**) and high (**D**) noise correlations. **E**) Accuracy in the last 20 training trials is plotted as a
function of noise correlations for learned readouts (orange) and optimal readout (red).
Lines/shading reflect Mean/SEM. F) The shortest distance, in terms of neural activation, required
to take the mean input for a given category (eg. left or right) to the boundary that would result in
misclassification is plotted for the final learned (orange) and optimal (red) weights for each noise
correlation condition (abscissa). Lines/shading reflect Mean/SEM.

1362
Extended data figure 6-1: **Emergence of noise correlations from Hebbian learning does not
depend on weight initialization**. In order to test whether beneficial noise correlations might have
emerged in our Hebbian learning simulations due to our initialization biasing one-to-one
connectivity between the input and hidden layers (see figure 4), we repeated these simulations
with in a network that was initialized with random normal weight projects from layer 1 to layer 2.
Simulations included performance of 200 trials with noise correlations measured in the final 100
trials of the simulation. Activity of layer 1 units was defined by a multivariate Gaussian with zero
covariance elements, and thus it is not surprising that pairwise noise correlations measured in the
activity of that layer were near zero (Left). Activity of layer 2 units was sculpted through Hebbian
learning that shaped connectivity between layer 1 and layer 2. This learning led many pairs of
neurons in layer 2 to become highly correlated and many other pairs to become anti-correlated
(middle, blue and yellow elements, respectively). In order to understand the structure defining
these correlations, we sorted the layer 2 units according to their relative projections to the two
output units (weight to output 1 – weight to output 2), and recomputed the pairwise correlations
(right). This sorting reveals that layer 2 units projecting to the same output unit are positively
correlated with one another, whereas they negatively correlate with the layer 2 units that project
to the opposing output neuron (note block diagonal structure).

Extended data figure 7-1: **Noise correlations affect speed of learning, but not performance using optimal readout in multiple discrimination task**. **A)** Mean test accuracy (color) of all models spanning the range of in pool correlations (abscissa) and relevant pool correlations (ordinate). **B)** Mean accuracy of same models using optimal readout, rather than the learned readout. **C)** Mean test accuracy (color) of all models spanning the range of in pool correlations (abscissa) and irrelevant pool correlations (ordinate). **D)** Mean accuracy of same models using optimal readout, rather than the learned readout. Note that performance of all models is identical when readout is optimal, rather than learned.