Noise correlations for faster and more robust learning

Matthew R. Nassar[1,2], Apoorva Bhandari[1,3]

1. Robert J. & Nancy D. Carney Institute for Brain Science, Brown University, Providence RI 02912-1821, USA
2. Department of Neuroscience, Brown University, Providence RI 02912-1821, USA
3. Department of Cognitive, Linguistic, and Psychological Sciences, Providence RI, 02912-1821

Acknowledgements:

We would like to thank Dan Scott, Josh Gold, Rex Liu, Michael Frank, Drew Linsley, Chris Moore and Jan Drugowitsch for helpful discussion. This work was funded by NIH grants F32MH102009 and R00AG054732 (MRN), NINDS R21NS108380 (AB). The funders had no role in study design, data collection and analysis, decision to publish or preparation of the manuscript.

Competing interests:

The authors have no financial or non-financial conflicts of interest related to this work.

Abstract:

Distributed population codes are ubiquitous in the brain and pose a challenge to downstream neurons that must learn an appropriate readout. Here we explore the possibility that this learning problem is simplified through inductive biases implemented by stimulus-independent noise correlations that constrain learning to task-relevant dimensions. We test this idea in a set of neural networks that learn to perform a perceptual discrimination task. Correlations among similarly tuned units were manipulated independently of overall population signal-to-noise ratio in order to test how the format of stored information affects learning. Higher noise correlations among similarly tuned units led to faster and more robust learning, favoring homogenous weights assigned to neurons within a functionally similar pool, and could emerge through Hebbian learning. When multiple discriminations were learned simultaneously, noise correlations across relevant feature dimensions sped learning whereas those across irrelevant feature dimensions slowed it. Our results complement existing theory on noise correlations by demonstrating that when such correlations are produced without degradation of signal-to-noise ratio, they can improve readout learning by constraining it to appropriate dimensions.

Introduction:

The brain represents information using distributed population codes in which particular feature values are encoded by large numbers of neurons. One advantage of such codes is that a pooled readout across many neurons can effectively reduce the impact of stimulus-independent variability (noise) in the firing of individual neurons (Pouget et al., 2000). However, the extent to which this benefit can be employed in practice is constrained by noise correlations, or the degree to which stimulus-independent variability is shared across neurons in the population (Averbeck et al., 2006). In particular, positive noise correlations between neurons that share the same stimulus tuning can reduce the amount of decodable information in the neural population (Averbeck et al, 2006; Moreno-Bote et al., 2014; Hu et al., 2014). Despite their detrimental effect on encoding, noise correlations of this type are reliably observed, even after years of training on perceptual tasks (Cohen and Kohn, 2011). Furthermore, noise correlations between neurons are dynamically enhanced under conditions where two neurons provide evidence for the same response in a perceptual categorization task (Cohen and Newsome, 2008), raising questions about whether they might serve a function rather than simply reflecting a suboptimal encoding strategy.

At the same time, learning to effectively read out a distributed code also poses a significant challenge. Learning the appropriate weights for potentially tens of

thousands of neurons in a low signal-to-noise regime is a difficult, high-
dimensional problem, requiring a very large number of learning trials and
entailing considerable risk of "over fitting" to specific patterns of noise across the
neural populations encountered during learning trials. Nonetheless, people and
animals can rapidly learn to perform perceptual discrimination tasks, albeit with
performance that does not approach theoretically achievable levels (Hawkey et
al., 2004; Stringer et al., 2019). In comparison, deep neural networks capable of
achieving human level performance typically require a far greater number of
learning trials than would be required by humans and other animals (Tsividis et
al., 2017). This raises the question of how brains might implement inductive
biases to enable efficient learning in high dimensional spaces.
101
Here we address open questions about noise correlations and learning by
considering the possibility that noise correlations facilitate faster learning.
Specifically, we propose that noise correlations aligned to task relevant
dimensions could reduce the effective dimensionality of learning problems,
thereby making them easier to solve. For example, perceptual stimuli often
contain a large number of features that may be irrelevant to a given
categorization. At the level of a neural population, individual neurons may differ in
the degree to which they encode task irrelevant information, thus making the
learning problem more difficult. In principle, noise correlations in the relevant
dimension could reduce the effects of this variability on learned readout. Such an
explanation would be consistent with computational analyses of Hebbian learning
rules (Oja, 1982), which can both facilitate faster and more robust learning
(Krotov and Hopfield, 2019), and in turn may induce noise correlations. We
propose that faster learning of an approximate readout is made possible through
low dimensional representations that share both signal and noise across a large
neural population. In particular, we hypothesize that representations
characterized by enhanced noise correlations among similarly tuned neurons can
improve learning by focusing adjustments of the readout onto task relevant
dimensions.
121
We explore this possibility using neural network models of a two-alternative
forced choice perceptual discrimination task in which the correlation among
similarly tuned neurons can be manipulated independently of the overall
population signal-to-noise ratio. Within this framework, noise correlations, which
can be learned through Hebbian mechanisms, speed learning by forcing learned
weights to be similar across pools of similarly tuned neurons, thereby ensuring
learning occurs over the most task relevant dimension. We extend our framework
to a cued multidimensional discrimination task and show that dynamic noise
correlations similar to those observed in vivo (Cohen and Newsome, 2008),
speed learning by constraining weight updates to the relevant feature space. Our
results demonstrate that when information is extrinsically limited, noise

correlations can make learning faster and more robust by controlling the
dimensions over which learning occurs.
135
136
Methods:

Our goal was to understand the computational principles through which
correlations in the activity of similarly tuned neurons affect the speed with which
downstream neurons could learn an effective readout. Previous work has
demonstrated that manipulating noise correlations while maintaining a fixed
variance in the firing rates of individual neurons leads to changes in the
theoretical encoding capacity of a neural population (Averbeck et al., 2006;
Moreno-Bote et al., 2014). To minimize the potential impact of such encoding
differences, we took a different approach; rather than setting the variance of
individual neurons in our population to a fixed value, we set the signal-to-noise
ratio of our population to a fixed value. Thus, our approach does not ask how
maximum information can be packed into a given neural population's activity, but
rather how the strategy for packing a *fixed* amount of information in a population
affects the speed with which an appropriate readout of that information can be
learned. We implement this approach in three neural networks described in more
detail below.

Learning readout in perceptual learning task

Simulations and analyses for a simple perceptual discrimination task were
performed with a simplified and statistically tractable two-layer feed-forward
neural network (figure 3A). The input layer consisted of two pools of 100 units
that were each "tuned" to one of two motion directions (left, right). On each trial
normalized firing rates for the neural population were drawn from a multivariate
normal distribution that was specified by a vector of stimulus-dependent mean
firing rates (signal: +1 for preferred stimulus, -1 for non-preferred stimulus) and a
covariance matrix. All elements of the covariance matrix corresponding to
covariance between units that were "tuned" to different stimuli were set to zero.
The key manipulation was to systematically vary the magnitude of diagonal
covariance components (eg. noise in the firing of individual units) and the "same
pool" covariance elements (eg. shared noise across identically tuned neurons)
while maintaining a fixed level of variance in the summed population response for
each pool:

$$\sigma^2_{pool} = n\sigma^2_{unit} + n(n-1)Cov(within\ pool) \quad Eq.1$$

Where σ^2_{pool} is the variance on the sum of normalized firing rates from neurons
within a given pool, n is the number of units in the pool and the within pool
covariance ($Cov(within\ pool)$) specifies the covariance of pairs of units

belonging to the same pool. The signal-to-noise ratio (signal/σ^2_{pool}) for each pool
was fixed to one. Given this constraint, the fraction of noise that was shared
across neurons within the same pool was manipulated as follows:

$$\sigma^2_{unit} = \frac{\sigma^2_{pool}}{n + n(n-1)\phi} \quad Eq.\, 2$$

$$Cov(within\,pool) = \phi\sigma^2_{unit} \quad Eq.\, 3$$

177
Where ϕ reflects the fraction of noise that is correlated across units, which we
refer to in the text as noise correlations. Noise correlations (ϕ) were manipulated
across values ranging from 0 to 0.2 for simulations. Note that, since ϕ appears in
the denominator of equation 2, adding noise correlations while sustaining a fixed
population signal-to-noise ratio leads to lower variance in the firing rates of single
neurons, differing from previous theoretical assumptions (compare figure 2a&b).
184
185 The input layer of the neural network was fully connected to an output layer
186 composed of two output units representing left and right responses. Output units
187 were activated on a given trial according to a weighted function of their inputs:
188
189

$$\boldsymbol{F_{output}} = \boldsymbol{wF_{input}} \quad Eq.\, 4$$

190
191 Where F_{output} is a vector of firing rates of output units, F_{input} is a vector of firing
192 rates of the input units, and w is the weight matrix. Firing of an individual output
193 unit can also be written as a weighted sum over input unit activity:
194

$$F_j = \sum_{i=1}^{200} w_{i,j} F_i \quad Eq.\, 5$$

195 where F_j reflects the firing of the j[th] output unit, F_i reflects the firing of the i[th] input
196 unit, and $w_{i,j}$ reflects the weight of the connection between the i[th] input unit and

197   the jth output unit. Actions were selected as a softmax function of output firing
198   rates:
199

$$p(A_j) \;=\; \frac{e^{\beta F_j}}{\sum_k e^{\beta F_k}} \quad Eq.\,6$$

200   where β is an inverse temperature, which was set to a relatively deterministic
201   value (10000). Learning was implemented through reinforcement learning of
202   weights to the selected output neuron (subscripted j below):
203

$$\Delta w_{i,j} \;=\; \alpha \delta F_i \quad Eq.\,7$$

Where F_i is the normalized firing rate of the ith input neuron, δ is the reward
prediction error experienced on a given trial [+0.5 for correct trials and -0.5 for
error trials], and α is a learning rate (set to 0.0001 for simulations in figure 2). The
network was trained to correctly identify two stimuli (each of which was preferred
by a single pool of input neurons) over 100 trials (the last 20 trials of which were
considered testing). Simulations were repeated 1000 times for each level of ϕ
and performance measures were averaged across all repetitions. Mean accuracy
per trial across all simulations was convolved with a Gaussian kernel (standard
deviation = 0.5 trials) for plotting in figure 2b. Mean accuracy across the final 20
trials was used as a measure of final accuracy (figure 2e). Statistics on model
performance were computed as Pearson correlations between noise correlations
ϕ and performance measures across all simulations and repetitions.
216

217   *Hebbian learning of noise correlations in three layer network*

218
We extended the two-layer feed-forward architecture described above to include
a third hidden layer in order to test whether Hebbian learning could facilitate
production of noise correlations among similarly tuned neurons (figure 4A). The
input layer was fully connected to the hidden layer, and each layer contained 200
neurons. In the input layer, neurons were tuned (100 leftward, 100 rightward) as
described above, with ϕ set to zero (eg. no noise correlations). Weights to the
hidden layer were initialized to favor one-to-one connections between input layer
units and hidden layer units by adding a small normal random weight perturbation
(mean=0, standard deviation = 0.01) to an identity matrix. During learning,
weights between the input and hidden layer were adjusted according to a
normalized Hebbian learning rule:
230

$$\Delta W = \alpha_{hebb} \mathbf{F'_1 F_2} \quad Eq.\,8$$

231
Where F_1' is a normalized vector of firing rates corresponding to the input layer
and F_2 is a normalized vector of firing rates corresponding to the hidden layer
units. The learning rate for Hebbian plasticity (α_{hebb}) was set to 0.00005 for
simulations in figure 4. The model was "trained" over 100 trials in the same
perceptual discrimination task described above and an additional 100 trials of the
task were completed to measure emergent noise correlations in the hidden layer.
Noise correlations were measured by regressing out variance attributable to the
stimulus on each trial, and then computing the Pearson correlation of residual
firing rate across each pair of neurons for the 100 testing trials (figure 4B&C).
241

Learning readout in multiple discrimination task

In order to test the impact of contextual noise correlations on learning (Cohen
and Newsome, 2008), the perceptual discrimination task was extended to include
two dimensions and two interleaved trial types: one in which an up/down
discrimination was performed (vertical), and one in which a right/left
discrimination was performed (horizontal). Each trial contained motion on the
vertical axis (up or down) and on the horizontal axis (left or right), but only one of
these motion axes was relevant on each trial as indicated by a cue.
250
In order to model this task we extended our two-layer feed-forward network to
include 4 populations of input units, 4 output units, and 2 task units (figure 5A).
Each population of 100 input units encoded a conjunction of the movement
directions (up-right, up-left, down-right, down-left). On each trial, the mean firing
rate of each input unit population was determined according to their tuning
preferences:
257
258

$$\mu = V + H \quad Eq.9$$

259
Where V was +1/-1 for trials with the preferred/anti-preferred vertical motion
direction H was +1/-1 for trials with the preferred/anti-preferred horizontal motion
direction. Firing rates for individual neurons were sampled from a multivariate
Gaussian distribution with mean μ and a covariance matrix that depended on trial
type (vertical versus horizontal) and the level of same pool, relevant pool, and
irrelevant pool correlations.
266
267 In order to create a covariance matrix, we stipulated a desired standard error of
268 the mean for summed population activity (SEM=20 for simulations in figure 5)
269 and determined the summed population variance that would correspond to that
270 value (σ_{pool}^2). We then determined the variance on individual neurons that would
271 yield this population response under a given noise correlation profile as follows:

$$\sigma^2_{unit} = \frac{\sigma^2_{pool}}{n + n(n-1)\phi_{same} + n^2\phi_{relevant} - n^2\phi_{irrelevant}} \quad Eq.\,10$$

273
Where ϕ_{same} is the level of same pool correlations (range: 0-0.2 in our
simulations), $\phi_{relevant}$ is the level of relevant pool correlations (range: 0-0.2 in our
simulations), $\phi_{irrelevant}$ is the level of irrelevant pool correlations (range: 0-0.2 in
our simulations. Note that increasing the same pool or in pool correlations
reduces the overall variance in order to preserve the same level of variance on
the task relevant dimension in the population response, but that increasing
irrelevant pool correlations has the opposite effect. Covariance elements of the
covariance matrix were determined as follows:
282

$$Cov(same\ pool) = \phi_{same}\sigma^2_{unit} \quad Eq.\,11$$

$$Cov(relevant\ pool) = \phi_{relevant}\sigma^2_{unit} \quad Eq.\,12$$

$$Cov(irrelevant\ pool) = \phi_{irrelevant}\sigma^2_{unit} \quad Eq.\,13$$

283 Variance and covariance values above were used to construct a covariance
284 matrix for each trial type (vertical/horizontal) as depicted in figure 1.

Covariance matrix: vertical trials

Figure 1: Schematic of covariance matrix for two-dimensional motion discrimination task. Same pool correlations are controlled by covariance elements between neurons with identical tuning (orange boxes). Relevant pool correlations are controlled by covariance elements between neurons that are similarly tuned to the task-relevant feature. Task irrelevant correlations are controlled by covariance elements between neurons that are similarly tuned to the task-irrelevant feature. The covariance matrix shown here is for a vertical trial – on a horizontal trial the irrelevant pool and relevant pool locations would be reversed. Covariance elements for pairs of neurons that differed in tuning on both dimensions were set to zero. Each input population has been depicted as two units here for presentation purposes. Background color reflects the case where same pool correlations = 0.2 and relevant pool correlations = 0.1.

Output units corresponded to the four possible task responses (up, down, left, right) and were activated according to a weighted sum of their inputs as described previously. Task units were modeled as containing perfect information about the task cue (vertical versus horizontal) and were modeled to completely inhibit the responses of the irrelevant output units. Decisions were made on each trial by selecting the output unit with the highest activity level. Weights to chosen output unit were updated using the same reinforcement learning procedure described in the two alternative perceptual learning task.

Results:

We examine how noise correlations affect learning in a simplified neural network where the appropriate readout of hundreds of weakly tuned units is learned over time through reinforcement. In order to isolate the effects of noise correlations on learning, rather than their effects on other factors such as representational capacity, we consider population encoding schemes at the input layer that can be constrained to a fixed signal-to-noise ratio. This assumption differs from previous work on noise correlations where the *variance* of the neural population is assumed to be fixed and covariance is changed to produce noise correlations, thereby affecting the representational capacity of the population (figure 2A; (Averbeck et al., 2006; Moreno-Bote et al., 2014)). Under our assumptions, a fixed signal-to-noise ratio can be achieved for any level of by scaling the variance (figure 2B; equations 1-3), or, alternately scaling the magnitude of the signal (not shown). While we do not discount the degree to which noise correlations affect the encoding potential of neural populations, we believe that in many cases the relevant information is limited by extrinsic factors (eg. the stimulus itself, or upstream neural populations providing input (Beck et al., 2012; Kanitscheider et al., 2015)). Under such conditions, reducing noise correlations can increase information only until it saturates because all of the available incoming information is encoded. Beyond that, increasing encoding potential is not possible as it would be tantamount to the population "creating new information" that was not communicated by inputs to the population. Therefore, our framework can be thought of as testing how best to format limited available information in a neural population in order to ensure that an acceptable readout can be rapidly and robustly learned.

We propose that within this framework, noise correlations of the form that have previously been shown to limit encoding are beneficial because they constrain learning to occur over the most relevant dimensions. In general, a linear readout can be thought of as hyperplane serving as a classification boundary in an N dimensional space, where N reflects the number of neurons in a population. Learning in such a framework involves adjustments of the hyperplane to minimize classification errors. The most useful adjustments are in the dimension that best discriminates signal from noise (central arrows in figure 2C&D), but adjustments may also occur in dimensions orthogonal to the relevant one (such as "twisting" of the hyperplane depicted by curved arrows in figure 2C&D) that could potentially impair performance, or slow down learning. Our motivating hypothesis is that by focusing population activity into the task relevant dimension, noise correlations can increase the fraction of hyperplane adjustments that occur in the task relevant dimension (figure 2D), thus reducing the effective dimensionality of readout learning.

A   **Fixed variance**

B   **Fixed Signal-to-Noise**

C   **Uncorrelated Noise**

D   **Correlated Noise**

Figure 2: Modeling noise correlations in under extrinsic constraint on signal-to-noise ratio. A) Previous work has modeled noise correlations by assuming that population variance is fixed and that covariance is manipulated to produce noise correlations. Under such assumptions, the firing rate of two similarly tuned neurons is plotted in the absence (solid) or presence (dotted) of information-limiting noise correlations. **B)** Here we assume that the signal-to-noise ratio of the neural population is limited to a fixed value such that noise correlations between similarly tuned neurons do not affect theoretical performance. Thus, the percent overlap of blue (target) and red (non-target) activity profiles does not differ in the presence (dotted) or absence (solid) of noise correlations. **C&D)** Under this assumption, noise correlations among similarly tuned neurons could compress the population activity to a plane orthogonal to the optimal decision boundary,

366 thereby minimizing boundary adjustments in irrelevant dimensions (**C**) and maximizing boundary
367 adjustments on relevant ones (**D**).
368
369
In order to test this hypothesis, we constructed a fully connected two-layer feed-
forward neural network in which input layer units responded to one of two
stimulus categories (pool 1 & pool 2) and each output unit produced a response
consistent with a category perception (left/right units in figure 3A). On each trial,
the network was presented with one stimulus at random, and input firing for each
pool was drawn from a multivariate Gaussian with a covariance that was
manipulated while preserving the population signal-to-noise ratio. Output units
were activated according to a weighted average of inputs and a response was
selected according to output unit activations. On each trial, weights to the
selected action were adjusted according to a reinforcement learning rule that
strengthened connections that facilitated a rewarded action and weakened
connections that facilitated an unrewarded action (Law and Gold, 2009).
382
Noise correlations led to faster and more robust learning of the appropriate
stimulus-response mapping. All neural networks learned to perform the requisite
discrimination, but neural networks that employed correlations among similarly
tuned neurons learned more rapidly (figure 3B). After learning, networks that
employed such noise correlations assigned more homogenous weights to input
units of a given pool than did networks that lacked noise correlations (compare
figure 3C&D). This led to better trained-task performance (figure 3E; Pearson
correlation between noise correlations and test performance: $R = 0.29$, $p < 10e$-
50) and greater robustness to adversarial noise profiles (figure 3F; $R = 0.81$, $p <$
10e-50) in the networks that employed noise correlations. Critically, these
learning advantages emerged despite the fact that optimal readout of all
networks achieved similar levels of performance and robustness (figure 3E&F,
compare optimal readout across conditions).
396
397
398

399
400
401
Figure 3: Correlated noise within similarly tuned populations leads to faster and more
robust learning of a perceptual discrimination. A) A two-layer feed-forward neural network
was designed to solve a two alternative forced choice motion discrimination task at or near

perceptual threshold. Input layer contains two pools of neurons that provide evidence for alternate
percepts (eg. leftward motion versus rightward motion) and output neurons encode alternate
courses of actions (eg. saccade left versus saccade right). Layers are fully connected with
weights randomized to small values and adjusted after each trial according to rewards (see
methods). **B)** Average learning curves for neural network models in which population signal-to-
noise ratio in pools 1 and 2 were fixed, but noise correlations (grayscale) were allowed to vary
from small (dark) to large (light) values. **C&D)** Weight differences (left output – right output) for
each input unit (color coded according to pool) after 100 timesteps of learning for low (**C**) and high
(**D**) noise correlations. **E)** Accuracy in the last 20 training trials is plotted as a function of noise
correlations for learned readouts (orange) and optimal readout (red). Lines/shading reflect
Mean/SEM. F) The shortest distance, in terms of neural activation, required to take the mean
input for a given category (eg. left or right) to the boundary that would result in misclassification is
plotted for the final learned (orange) and optimal (red) weights for each noise correlation condition
(abscissa). Lines/shading reflect Mean/SEM.
419
420
421
Given that noise correlations implemented in our previous simulation, like those
observed in the brain, depended on the tuning of individual units, we tested
whether such noise correlations might be produced via Hebbian plasticity.
Specifically, we considered an extension of our neural network in which an
additional intermediate layer is included between input and output neurons (figure
4a). Input units were again divided into two pools that differed in their encoding,
but variability was uncorrelated across neurons within a given pool. Connections
between the input layer and intermediate layer were initialized such that each
input unit strongly activated one intermediate layer unit, and shaped over time
using a Hebbian learning rule that strengthened connections between co-
activated neuron pairs. Despite the lack of noise correlations in the input layer of
this network (figure 4b; mean[std] in pool residual correlation = 0.0015[0.10]),
neurons in the intermediate layer developed tuning-specific noise correlations of
the form that were beneficial for learning in the previous simulations (figure 4c;
mean[std] in pool residual correlation = 0.55[0.07]; t-test on difference from input
layer correlations $t = 443$, $dof = 19800$, $p < 10e-50$).

**Figure 4: Hebbian learning produces correlations within similarly tuned populations in a
perceptual discrimination task. A**) Three-layer neural network architecture. Input layer feeds
forward to hidden layer, which is fully connected to an output layer. Input layer provides
uncorrelated inputs to hidden layer through projection weights that are adjusted according to a
Hebbian learning rule. **B&C**) Noise correlations observed in hidden layer units at the beginning
(**B**) and end (**C**) of training.

In order to understand how noise correlations might impact learning in mixed
encoding populations, we extended our perceptual discrimination task to include
two directions of motion discrimination (eg. up/down and left/right). On each trial,
a cue indicated which of two possible motion discriminations should be
performed (figure 5A, left; (Cohen and Newsome, 2008)). We extended our
neural network to include four populations of one hundred input units, each
population encoding a conjunction of motion directions (up-right, up-left, down-
right, down-left; figure 5A; input layer). Two additional inputs provided a perfectly
reliable "cue" regarding the relevant feature for the trial (figure 5A; task units).
Four output neurons encoded the four possible responses (up, left, down, right)
and were fully connected to the input layer (figure 5A; output layer). Task units
were hard wired to eliminate irrelevant task responses, but weights of input units
were learned over time as in our previous simulations.

Learning performance in the two-feature discrimination task depended not only
on the level of noise correlations, but also on the type. As in the previous
simulation, adding noise correlations to each individual population of identically
tuned units led to faster learning of the appropriate readout (Figure 5B&C,
compare blue and yellow; Figure 5D&E, vertical axis; mean[std] accuracy across
training: 0.53[0.05] and 0.614[0.08] for minimum (0) and maximum (0.2) in pool
correlations, t-test for difference in accuracy: $t = 95$, $dof = 19998$, $p < 10e-50$).

However, the more complex task design also allowed us to test whether dynamic
trial-to-trial correlations might further facilitate learning. Specifically, correlations
that increase shared variability among units that contribute evidence to the same
response have been observed previously (Cohen and Newsome, 2008), and
could in principle focus learning on relevant dimensions (figure 2C&D) even when
those dimensions change from trial to trial. Indeed, adding correlations among
separate pools that share the same encoding of the relevant feature (eg. UP on a
vertical trial) led to faster learning (figure 5B; mean[std] training accuracy for
model with relevant pool correlations: 0.64[0.09], t-test for difference from in pool
correlation only model: $t = 22$, $dof = 19998$, $p < 10e-50$) and weights that more
closely approached the optimal readout (figure 5E, horizontal axis). In contrast,
when positive noise correlations were introduced across separate encoding pools
that shared the same tuning for the irrelevant dimension on each trial (eg. UP on
a horizontal trial) learning was impaired dramatically (figure 5C; mean[std]
training accuracy for model with irrelevant pool correlations: 0.51[0.05], t-test for
difference from in pool correlation only model: $t = -112$, $dof = 19998$, $p < 10e-50$)
and learned weights diverged from the optimal readout (figure 5F, horizontal
axis). Model performance differences were completely attributable to learning the
readout, as all models performed similarly when using the optimal readout (figure
S1).

In order to test the idea that noise correlations might focus learning onto relevant
dimensions, we extracted weight updates from each trial and projected these
updates into a two-dimensional space where the first dimension captured the
relative sensitivity to leftward versus rightward motion and the second dimension
captured relative sensitivity to upward versus downward motion. In the model
where input units were only correlated within their identically tuned pool, weight
updates projected in all directions more or less uniformly (figure 5G), and did not
differ systematically across trial types (vertical versus horizontal). However,
dynamic noise correlations that shared variability across the relevant dimension
tended to push weight updates onto the appropriate dimension for a given trial
(figure 4F; t-test for difference in the magnitude of updating in up/down and
left/right dimensions across conditions [up/down – left/right]: $t = 3.4$, $dof=98$, $p = $
0.001). In contrast, dynamic noise correlations that shared variability across the
irrelevant dimension tended to push weight updates onto the wrong dimension
(figure 4H; t-test for difference in the magnitude of updating in up/down and
left/right dimensions across conditions [up/down – left/right]: $t = -9.5$, $dof=98$, $p = $
10e-14). Both of these trends were consistent across simulations, providing an
explanation for the performance improvements achieved by relevant noise
correlations (projection of learning onto an appropriate dimension) and
performance impairments produced by irrelevant noise correlations (projection of
learning onto an inappropriate dimension).

**Figure 5: Task dependent noise correlations affect learning speed by projecting learning
onto specific feature dimensions. A)** A neural network was trained to perform two interleaved
motion discrimination tasks (left; (Cohen and Newsome, 2008)). Network schematic (right)
depicts two-layer feed-forward network in which each population of input units represents two
dimensions of motion (up versus down, and left versus right), and output units produce responses
in favor of alternative actions (up, down, left, right). Two additional input units provide cue

information that biases output units to produce an output corresponding to the discrimination
appropriate on this trial (eg. horizontal or vertical). Noise correlations were manipulated among 1)
identically tuned neurons (blue rectangle; same pool), 2) neurons that have similar encoding of
the task relevant feature (green rectangle pair in vertical trials; relevant pool), and 3) neurons that
have similar encoding of the task irrelevant feature (green rectangle pair in horizontal trials;
irrelevant pool). **B&C**) Learning curves showing accuracy (ordinate) over trials (abscissa) for
models 1) lacking noise correlations (orange), 2) containing noise correlations that are limited to
neurons that have same tuning for both features (same pool; blue), 3) containing same pool noise
correlations along with correlations between neurons in different pools that have the same tuning
for the task-relevant feature (in pool+rel pool; green in **B**), and 4) containing in-pool noise
correlations along with correlations between neurons in different pools that have the same tuning
for the task irrelevant feature (in pool+irrel pool; green in **C**). **D&E**) Distance between learned
weights and the optimal readout (color) for models that differ in their level of "in pool" correlations
(ordinate, both plots), "relevant pool" correlations (abscissa, **D**), and "irrelevant pool" correlations
(abscissa, **E**). **F,G,H**) Weight updates for example learning sessions were projected into a two
dimensional space in which net updates to the relative contribution of vertical motion information
(eg. up versus down) is represented on the abscissa and updates to the relative contribution of
horizontal motion information (eg. left versus right) is represented on the ordinate. Arrows reflect
single trial weight updates and are colored according to the trial type (red = horizontal
discrimination, blue = vertical discrimination). Weight updates for a model with only "in pool"
correlations look similar across trial types (**G**), but weight updates for a model with "relevant pool"
correlations indicate more weight updating on the relevant feature (**F**), whereas the opposite was
observed in the case of "irrelevant pool" correlations (**H**).
563
564
565 **Discussion:**
566
Taken together, our results suggest that in settings where the population signal-
to-noise ratio is limited by external factors (eg. inputs) and relevant task
representations are low dimensional, noise correlations can make learning faster
and more robust by focusing learning on the most relevant dimensions. We
demonstrate this basic principle in a simple perceptual learning task (figure 3),
where beneficial noise correlations between similarly tuned units could be
produced through a simple Hebbian learning rule (figure 4). We extended our
framework to a contextual learning task to demonstrate that dynamic noise
correlations that bind task relevant feature representations facilitate faster
learning (figure 5b&d) by pushing learning onto task-relevant dimensions (figure
5f). Given the pervasiveness of noise correlations among similarly tuned sensory
neurons (Zohary et al., 1994; Maynard et al., 1999; Bair et al., 2001; Averbeck
and Lee, 2003; Cohen and Maunsell, 2009; Huang and Lisberger, 2009; Ecker et
al., 2010; Gu et al., 2011; Adibi et al., 2013), and that the noise correlations
dynamics beneficial for learning in our simulations are similar to those that have
been observed *in vivo* (Cohen and Newsome, 2008), we interpret our results as
suggesting that noise correlations between similarly tuned neurons are a feature
of neural coding architectures that ensures efficient readout learning, rather than
a bug that limits encoding potential.
586
587

This interpretation rests on several assumptions in our model. Of particular
importance is the assumption that signal-to-noise ratio of our populations is fixed,
meaning that our manipulation of noise correlations can focus variance on
specific dimensions without gaining or losing information. This assumption
reflects conditions in which information is limited at the level of the inputs to the
population, for instance due to noisy peripheral sensors (Beck et al., 2012;
Kanitscheider et al., 2015). In such conditions, even with optimal encoding,
population information saturates at an upper bound determined by the
information available in the inputs to the population. Therefore, fixing the signal-
to-noise ratio enabled us to examine the effect of noise correlations on
downstream processes that learn to read-out the population code in the absence
of any influence of noise correlations on the quantity of information contained
within that population code.
601
Previous theoretical work exploring the role of noise correlations in encoding has
typically assumed that single neurons have a fixed variance, such that tilting the
covariance of neural populations towards or away from the dimension of signal
encoding would have a large impact on the amount of information that can be
encoded by a population (figure 1a; (Averbeck et al., 2006; Moreno-Bote et al.,
2014)). Such assumptions lead to the idea that positive noise correlations among
similarly tuned neurons limit encoding potential, raising the question of why they
are so common in the brain (Cohen and Kohn, 2011). In considering the
implications of this framework, one important question is: if information encoded
by the population can be increased by changing the correlation structure among
neurons, where does this additional information come from? In some cases, the
neural population in question may indeed receive sufficient task relevant
information from upstream brain regions to reorganize its encoding in this way,
but in other cases it is likely that information is limited by the inputs to a neural
population (Kanitscheider et al., 2015; Kohn et al., 2016). In cases where
incoming information is limited, further increasing representational capacity is not
possible, and formatting information for efficient readout is essentially the best
that the population code could do. Here we show that the noise correlations that
have previously been described as "information limiting" are exactly the type of
correlations that format information most efficiently for readout learning under
such conditions.
623
Jointly considering these antagonistic perspectives on noise correlations provides
a more nuanced view of how neural representations are likely optimized for
learning. In order to optimize an objective function, a neural population can
reduce correlated noise in task relevant dimensions to increase its
representational capacity up to some level constrained by its inputs (Figure 6,
left). But once the population is fully representing all task relevant information that
has been provided to it, it can additionally optimize representations by pushing as
much variance onto task relevant dimensions as possible, thereby affording

efficient learning in downstream neural populations (Figure 6, right). In short,
optimization of a neural population code does not occur in a vacuum, and instead
depends critically on both upstream (eg. input constraints) and downstream (eg.
readout) neural populations (Figure 6). In this view, if a neural population is *not*
fully representing the decision relevant information made available to it, then
learning could improve the efficiency of representations by reducing rate limiting
noise correlations as has been observed in some paradigms (Figure 6, left; Gu et
al., 2011; Ni et al., 2018). In contrast, once available information is fully
represented, readout learning could be further optimized by reformatting
population codes such that variability is shared across neurons with similar
tuning for the relevant task feature, producing the sorts of dynamic noise
correlations that have been observed in well trained animals (Figure 6, right;
Cohen and Newsome, 2008).

645
Figure 6: Information maximization and dimensionality reduction can be useful for
learning under different situations and have opposite effects on noise correlations among
similarly tuned units. A) A schematic representation of a three layer neural network in which
units provide evidence for one of two categorizations (blue/orange). In the left network, the hidden
layer initially has access to information from only one of two independent units in each pool, but
weights are subsequently adjusted to increase task-relevant information represented in the
hidden layer (pink). In the right network, the hidden layer initially has access to all task-relevant

information, but weights are subsequently adjusted to share signal and noise across similarly
tuned units to afford dimensionality reduction (purple). Note that the information maximizing
weight adjustments (left, pink) increase signal-to-noise ratio in the hidden layer but preserve the
variance in firing rate of individual neurons, whereas the dimensionality reducing weight
adjustments (right, purple) maintain a fixed signal-to-noise ratio in hidden units, but decrease the
variance of individual units by averaging across multiple similarly tuned inputs. Dashed lines to
output units reflect weights that need to be learned based on feedback. **B)** Task relevant
information (mutual information between unit activations and stimulus category; abscissa) is
depicted for each layer (ordinate). Weight adjustments affording information maximization (left)
increase task relevant information in the hidden layer (pink), whereas weight adjustments that
afford dimensionality reduction (right) do not affect task-relevant information in the hidden layer
itself but instead increase the rate of learning in the output layer, thereby leading to more task-
relevant information in the output layer (purple). **C)** Weight adjustments for information
maximization (pink in panel A) *decrease* correlations among hidden units A&B by removing
shared input from a single input unit and instead providing independent sources of input to each
unit (pink arrows). In contrast, weight adjustments for dimensionality reduction *increase* noise
correlations among hidden units A&B by providing them with the same mixture of information from
the two identically tuned input units. We propose that both of these processes play a critical role
in learning and that changes in noise correlations across learning will depend critically on which
process dominates. As shown in panel B, this will depend critically on whether the neural
population in question has already fully represented information available from its inputs. In
principle, these processes could occur serially, with early learning maximizing information
available in intermediate layers (left) and later learning compressing that information into a format
allowing rapid readout learning (right).
677
678
In addition to key assumptions about an external limitation on signal-to-noise, our
modeling included a number of simplifying assumptions that are unlikely to hold
up in real neural populations. For example, we consider discrete pools of
identically tuned neurons, rather than the heterogeneous populations observed in
sensory cortical regions of the brain. A primary goal of our work was to identify
the computational principles that control the speed at which readout can be
learned, and our simplified populations are considerably more tractable and
transparent than realistic neural populations. The principles that we identify here
are certainly at play in real neural populations, albeit with implications that are far
less transparent. We hope that our simplified results pave the way for future work
to assess nuances that can emerge in mixed heterogeneous populations, or in
more realistic architectures that go beyond the simple feed forward flow of
information considered here.
692
693 *Model predictions*
694
Our work shows that noise correlations can focus the gradient of learning onto
the most appropriate dimensions. Thus, our model predicts that the degree to
which similarly tuned neurons are correlated during a perceptual discrimination
should be positively related to performance improvements experienced on
subsequent discriminations. In contrast, our model predicts that the degree of
correlation between neurons that are similarly tuned to a task irrelevant feature
should control the degree of learning on irrelevant dimensions, and thus

negatively relate to performance improvements on subsequent discriminations.
These predictions are strongest for the earliest stages of learning where weight
adjustments are critical for subsequent performance, but they may also hold for
later stages of learning, when correlations on irrelevant dimensions, including
independent noise channels, could potentially lead to systematic deviations from
optimal readout (figure 2f, 4d&e). These predictions could be tested by recording
neural responses to a stimulus set that differs across multiple features to
characterize both signal-to-noise and correlated variability for each feature
discrimination. A strong prediction of our model is that correlated variability within
neurons tuned to a given feature should be a predictor of subsequent learning of
responses to that feature – above and beyond feature value discriminability.
713
One interesting special case involves tasks where the relevant dimension
changes in an unsignaled manner (Birrell and Brown, 2000). In such tasks, noise
correlations on the previously relevant dimension would, after such an
"extradimensional shift", force gradients into a task-irrelevant dimension and thus
impair learning performance. Interestingly, learning after extra-dimensional shifts
can be selectively improved by enhancing noradrenergic signaling (Devauges
and Sara, 1990; Lapiz and Morilak, 2006), which leads to increased arousal
(Joshi et al., 2016; Reimer et al., 2016) and decreased cortical pairwise noise
correlations in sensory and higher order cortex (Vinck et al., 2015; Joshi and
Gold, n.d.). While these observations have been made in different paradigms, our
model suggests that the reduction of noise correlations resulting from increased
sustained levels of norepinephrine after an extradimensional shift (Bouret and
Sara, 2005) could mediate faster learning by expanding the dimensionality of the
learning gradients (compare figure 5G to 5F) to consider features that have not
been task-relevant in the past.
729
730 *Relation to attentional effects on noise correlations*
731
In broad strokes, our finding that manipulation of noise correlations can focus
variance on specific dimensions is in line with specific models of attention. In
particular, noise reduction in task irrelevant dimensions might be considered in
the same light that is often cast on suppression of task irrelevant dimensions by
attentional mechanisms (Zanto and Gazzaley, 2009), in particular for purposes of
accurate credit assignment (Akaishi et al., 2016; Leong et al., 2017). One
possibility is that compressed low-dimensional task representations in higher-
order decision regions (Mack et al., 2019) may pass accumulated decision
related information back to sensory regions in order to approximate Bayesian
inference (Haefner et al., 2016; Bondy et al., 2018; Lange et al., 2018). As task
relevant features are learned, such a process would promote noise correlations
between neurons coding those relevant features. In other words, noise
correlations may reflect a chosen hypothesis about which feature is relevant for
predicting outcomes. Such a signal would be beneficial if it could persist (and

thus preserve correlations between neurons tuned to the same task relevant
feature value) until the time of feedback or reinforcement. Recent work showing
strengthened noise correlations between similarly tuned neurons during working
memory maintenance suggests that this might very well be the case (Merrikhi et
al., 2018).
751
One observation that seems at odds with this interpretation is that manipulations
of attention that cue a particular location or feature tend to decrease noise
correlations among neurons that encode that location or feature (Cohen and
Maunsell, 2009; Mitchell et al., 2009; Cohen and Maunsell, 2011; Herrero et al.,
2013; Doiron et al., 2016). The effects of attentional cuing on noise correlations
are dynamic in that cues change from one trial to the next, and contextual, in that
noise correlations are reduced most dramatically among neurons that contribute
evidence toward the same response in a manner consistent with increasing the
amount of task relevant information in the population code (Ruff and Cohen,
2014; Downer et al., 2015). Our model does not account for these attentional
effects, as we intentionally constrained the signal-to-noise ratio of our neural
populations, thereby eliminating any potential changes in information encoding
potential. However, we hope that our work motivates future studies to jointly
consider the impacts of noise correlations on both learning and immediate
performance in order to better understand the potentially competing imperatives
that the brain faces in dynamically controlling the correlation structure of its own
representations (see (Haimerl et al., 2019) for one attempt to do so).
769
770
771 *Origins of useful noise correlations*
772
One important question stemming from our work is how noise correlations
emerge in the brain. This question has been one of longstanding debate, largely
because there are so many potential mechanisms through which correlations
could emerge (Kanitscheider et al., 2015; Kohn et al., 2016). Noise correlations
could emerge from convergent and divergent feed forward wiring (Shadlen and
Newsome, 1998), local connectivity patterns within a neural population (Hansen
et al., 2012; Smith et al., 2013), or top down inputs provided separately to
different neural populations (Haefner et al., 2016). Here we show that static noise
correlations that are useful for perceptual learning emerge naturally from Hebbian
learning in a feed-forward network. While this certainly suggests that useful noise
correlations could emerge through feed forward wiring, it is also possible to
consider our Hebbian learning as occurring in a one-step recurrence of the input
units, and thus the same data support the possibility of noise correlations through
local recurrence. The context dependent noise correlations that speed learning
(figure 4), however, would not arise through simple Hebbian learning. Such
correlations could potentially be produced through selective top-down signals
from the choice neurons, as has been previously proposed (Wimmer et al., 2015;

Haefner et al., 2016; Bondy et al., 2018; Lange et al., 2018). Moreover, top-down
input may selectively target neuronal ensembles produced through Hebbian
learning (Collins and Frank, 2013). While previous work has suggested that such
a mechanism could be adaptive for accumulating information over the course of a
decision (Haefner et al., 2016), our work demonstrates that the same mechanism
could effectively be used to tag relevant neurons for weight updating between
trials, making efficient use of top-down circuitry. Haimerl et al. recently made a
similar point, showing that stochastic modulatory signals shared across task-
informative neurons can serve to tag them for a decoder (Haimerl et al., 2019).
799
800 *Noise correlations as inductive biases*
801
Artificial intelligence has undergone a revolution over the past decade leading to
human level performance in a wide range of tasks (Mnih et al., 2015). However, a
major issue for modern artificial intelligence systems, which build heavily on
neural network architectures, is that they require far more training examples than
a biological system would (Hassabis et al., 2017). This biological advantage
occurs despite the fact that the total number of synapses in the human brain,
which could be thought of as the free parameters in our learning architecture, is
much greater than the number of weights in even the most parameter-heavy
deep learning architectures. Our work provides some insight into why this occurs;
correlated variability across neurons in the brain constrain learning to specific
dimensions, thereby limiting the effective complexity of the learning problem
(figure 5F-G). We show that, for simple tasks, this can be achieved using
Hebbian learning rules (figure 4), but that contextual noise correlations, of the
form that might be produced through top-down signals (Haefner et al., 2016), are
critical for appropriately focusing learning in more complex circumstances. In
principle, algorithms that effectively learn and implement noise correlations might
reduce the amount of data needed to train AI systems by limiting degrees of
freedom to those dimensions that are most relevant. Furthermore, our work
suggests that large scale neural recordings in early stages of learning complex
tasks might serve as indicators of the inductive biases that constrain learning in
biological systems.
823
In summary, we show that under external constraints of task-relevant information,
noise correlations that have previously been called "rate limiting" can serve an
important role in constraining learning to task-relevant dimensions. In the context
of previous theory focusing on representation, our work suggests that neural
populations are subject to competing forces when optimizing covariance
structures; on one hand reducing correlations between pairs of similarly tuned
neurons can be helpful to fully represent available information, but increasing
correlations among similarly tuned neurons can be helpful for assigning credit to
task relevant features. We believe that this view of the learning process not only
provides insight to understanding the role of noise correlations in the brain, but

opens up the door to better understand the inductive biases that guide learning in
biological systems.
836
837
838 Supplementary figures:
839
840
841

842
843
844
Figure S1: **Noise correlations affect speed of learning, but not performance using optimal**
readout in multiple discrimination task. **A)** Mean test accuracy (color) of all models spanning
the range of in pool correlations (abscissa) and relevant pool correlations (ordinate). **B)** Mean
accuracy of same models using optimal readout, rather than the learned readout. **C)** Mean test
accuracy (color) of all models spanning the range of in pool correlations (abscissa) and irrelevant
pool correlations (ordinate). **D)** Mean accuracy of same models using optimal readout, rather than
the learned readout. Note that performance of all models is identical when readout is optimal,
rather than learned.
853
854
855
856

Adibi M, McDonald JS, Clifford CWG, Arabzadeh E (2013) Adaptation improves
neural coding efficiency despite increasing correlations in variability. Journal
of Neuroscience 33:2108–2120.

Akaishi R, Kolling N, Brown JW, Rushworth M (2016) Neural Mechanisms of
Credit Assignment in a Multicue Environment. Journal of Neuroscience
36:1096–1112.

Averbeck BB, Latham PE, Pouget A (2006) Neural correlations, population
coding and computation. Nature Reviews Neuroscience 7:358–366.

Averbeck BB, Lee D (2003) Neural noise and movement-related codes in the
macaque supplementary motor area. Journal of Neuroscience 23:7630–7641.

Bair W, Zohary E, Newsome WT (2001) Correlated firing in macaque visual area
MT: time scales and relationship to behavior. Journal of Neuroscience
21:1676–1697.

Beck JM, Ma WJ, Pitkow X, Latham PE, Pouget A (2012) Perspective. Neuron
74:30–39.

Birrell JM, Brown VJ (2000) Medial frontal cortex mediates perceptual attentional
set shifting in the rat. Journal of Neuroscience 20:4320–4324.

Bondy AG, Haefner RM, Cumming BG (2018) Feedback determines the structure
of correlated variability in primary visual cortex. Nature Publishing Group:1–
15.

Bouret S, Sara SJ (2005) Network reset: a simplified overarching theory of locus
coeruleus noradrenaline function. Trends in Neurosciences 28:574–582.

Cohen MR, Kohn A (2011) Measuring and interpreting neuronal correlations.
Nature Publishing Group 14:811–819.

Cohen MR, Maunsell JHR (2009) Attention improves performance primarily by
reducing interneuronal correlations. Nature Publishing Group 12:1594–1600.

Cohen MR, Maunsell JHR (2011) Using neuronal populations to study the
mechanisms underlying spatial and feature attention. Neuron 70:1192–1204.

Cohen MR, Newsome WT (2008) Context-Dependent Changes in Functional
Circuitry in Visual Area MT. Neuron 60:162–173.

Collins AGE, Frank MJ (2013) Cognitive control over learning: creating,
clustering, and generalizing task-set structure. Psychological Review
120:190–229.

Devauges V, Sara SJ (1990) Activation of the noradrenergic system facilitates an
attentional shift in the rat. Behavioural Brain Research 39:19–28.

Doiron B, Litwin-Kumar A, Rosenbaum R, Ocker GK, Josić K (2016) The
mechanics of state-dependent neural correlations. Nature Publishing Group
19:383–393.

Downer JD, Niwa M, Sutter ML (2015) Task engagement selectively modulates
neural correlations in primary auditory cortex. Journal of Neuroscience
35:7565–7574.

Ecker AS, Berens P, Keliris GA, Bethge M, Logothetis NK, Tolias AS (2010)
Decorrelated neuronal firing in cortical microcircuits. Science 327:584–587.

Gu Y, Liu S, Fetsch CR, Yang Y, Fok S, Sunkara A, DeAngelis GC, Angelaki DE
(2011) Perceptual learning reduces interneuronal correlations in macaque
visual cortex. Neuron 71:750–761.

Haefner RM, Pietro Berkes, Fiser J (2016) Perceptual Decision-Making as
Probabilistic Inference by Neural Sampling. Neuron 90:649–660.

Haimerl C, Savin C, Simoncelli EP (2019) Flexible and accurate decoding of
neural populations through stochastic comodulation. Biorxiv 21:598.

Hansen BJ, Chelaru MI, Dragoi V (2012) Correlated variability in laminar cortical
circuits. Neuron 76:590–602.

Hassabis D, Kumaran D, Summerfield C, Botvinick M (2017) Neuroscience-
Inspired Artificial Intelligence. Neuron 95:245–258.

Hawkey DJC, Amitay S, Moore DR (2004) Early and rapid perceptual learning.
Nature Publishing Group 7:1055–1056.

Herrero JL, Gieselmann MA, Sanayei M, Thiele A (2013) Attention-induced
variance and noise correlation reduction in macaque V1 is mediated by
NMDA receptors. Neuron 78:729–739.

Huang X, Lisberger SG (2009) Noise correlations in cortical area MT and their
potential impact on trial-by-trial variation in the direction and speed of
smooth-pursuit eye movements. Journal of Neurophysiology 101:3012–3030.

Joshi S, Gold JI (n.d.) Context-Dependent Relationships between Locus
Coeruleus Firing Patterns and Coordinated Neural Activity in the Anterior
Cingulate Cortex. Biorxiv.

Joshi S, Li Y, Kalwani RM, Gold JI (2016) Relationships between Pupil Diameter
and Neuronal Activity in the Locus Coeruleus, Colliculi, and Cingulate Cortex.

Neuron 89:221–234.

Kanitscheider I, Coen-Cagli R, Pouget A (2015) Origin of information-limiting
noise correlations. Proceedings of the National Academy of Sciences
112:E6973–E6982.

Kohn A, Coen-Cagli R, Kanitscheider I, Pouget A (2016) Correlations and
Neuronal Population Information. Annu Rev Neurosci 39:237–256.

Krotov D, Hopfield JJ (2019) Unsupervised learning by competing hidden units.
Proceedings of the National Academy of Sciences 116:7723–7731.

Lange RD, Chattoraj A, Beck JM, Yates JL, Haefner RM (2018) A confirmation
bias in perceptual decision-making due to hierarchical approximate inference.
Biorxiv.

Lapiz MDS, Morilak DA (2006) Noradrenergic modulation of cognitive function in
rat medial prefrontal cortex as measured by attentional set shifting capability.
Neuroscience 137:1039–1049.

Law C-T, Gold JI (2009) Reinforcement learning can account for associative and
perceptual learning on a visual-decision task. Nature Neuroscience 12:655–
663.

Leong YC, Radulescu A, Daniel R, DeWoskin V, Niv Y (2017) Dynamic
Interaction between Reinforcement Learning and Attention in
Multidimensional Environments. Neuron 93:451–463.

Mack ML, Preston AR, Love BC (2019) Ventromedial prefrontal cortex
compression during concept learning. Nature Communications:1–11.

Maynard EM, Hatsopoulos NG, Ojakangas CL, Acuna BD, Sanes JN, Normann
RA, Donoghue JP (1999) Neuronal interactions improve cortical population
coding of movement direction. Journal of Neuroscience 19:8083–8093.

Merrikhi Y, Clark K, Noudoost B (2018) Concurrent influence of top-down and
bottom-up inputs on correlated activity of Macaque extrastriate neurons.
Nature Communications 9:5393.

Mitchell JF, Sundberg KA, Reynolds JH (2009) Spatial attention decorrelates
intrinsic activity fluctuations in macaque area V4. Neuron 63:879–888.

Mnih V, Kavukcuoglu K, Silver D, Rusu AA, Veness J, Bellemare MG, Graves A,
Riedmiller M, Fidjeland AK, Ostrovski G, Petersen S, Beattie C, Sadik A,
Antonoglou I, King H, Kumaran D, Wierstra D, Legg S, Hassabis D (2015)
Human-level control through deep reinforcement learning. Nature 518:529–

533.

Moreno-Bote R, Beck J, Kanitscheider I, Pitkow X, Latham P, Pouget A (2014)
Information-limiting correlations. Nature Publishing Group 17:1410–1417.

Ni AM, Ruff DA, Alberts JJ, Symmonds J, Cohen MR (2018) Learning and
attention reveal a general relationship between population activity and
behavior. Science 359:463–465.

Oja E (1982) Simplified neuron model as a principal component analyzer. Journal
of Mathematical Biology:1–7.

Pouget A, Dayan P, Zemel R (2000) Information processing with population
codes. Nature Reviews Neuroscience 1:125–132.

Reimer J, McGinley MJ, Liu Y, Rodenkirch C, Wang Q, McCormick DA, Tolias AS
(2016) Pupil fluctuations track rapid changes in adrenergic and cholinergic
activity in cortex. Nature Communications 7:13289.

Ruff DA, Cohen MR (2014) Attention can either increase or decrease spike count
correlations in visual cortex. Nature Publishing Group 17:1591–1597.

Shadlen MN, Newsome WT (1998) The variable discharge of cortical neurons:
implications for connectivity, computation, and information coding. J Neurosci
18:3870–3896.

Smith MA, Jia X, Zandvakili A, Kohn A (2013) Laminar dependence of neuronal
correlations in visual cortex. Journal of Neurophysiology 109:940–947.

Stringer C, Michaelos M, Pachitariu M (2019) High precision coding in mouse
visual cortex. Biorxiv.

Tsividis P, Pouncy T, Xu JL, Tenenbaum JB, Gershman SJ (2017) Human
Learning in Atari. 2017 AAAI Spring Symposium Series, Science of
Intelligence: Computational Principles of Natural and Artificial Intelligence:1–
4.

Vinck M, Batista-Brito R, Knoblich U, Cardin JA (2015) Arousal and Locomotion
Make Distinct Contributions to Cortical Activity Patterns and Visual Encoding.
Neuron 86:740–754.

Wimmer RD, Schmitt LI, Davidson TJ, Nakajima M, Deisseroth K, Halassa MM
(2015) Thalamic control of sensory selection in divided attention. Nature
526:705–709.

Zanto TP, Gazzaley A (2009) Neural Suppression of Irrelevant Information
Underlies Optimal Working Memory Performance. Journal of Neuroscience

29:3059–3066.

Zohary E, Shadlen MN, Newsome WT (1994) Correlated neuronal discharge rate
and its implications for psychophysical performance. Nature 370:140–143.