General auditory and speech-specific contributions to cortical envelope tracking revealed using auditory chimeras

Kevin D. Prinsloo[1], Edmund C. Lalor[1]

[1]Department of Biomedical Engineering, Department of Neuroscience, and Del Monte Institute for Neuroscience, University of Rochester, 201 Robert B. Goergen Hall, P.O. Box 270168, Rochester, NY 14627, USA.

Corresponding Author: Edmund C. Lalor PhD, Department of Biomedical Engineering, University of Rochester, 201 Robert B. Goergen Hall, P.O. Box 270168, Rochester, NY 14627, USA; Edmund_Lalor@urmc.rochester.edu

Abstract

In recent years research on natural speech processing has benefited from recognizing that low frequency cortical activity tracks the amplitude envelope of natural speech. However, it remains unclear to what extent this tracking reflects speech-specific processing beyond the analysis of the stimulus acoustics. In the present study, we aimed to disentangle contributions to cortical envelope tracking that reflect general acoustic processing from those that are functionally related to processing speech. To do so, we recorded EEG from subjects as they listened to "auditory chimeras" – stimuli comprised of the temporal fine structure (TFS) of one speech stimulus modulated by the amplitude envelope (ENV) of another speech stimulus. By varying the number of frequency bands used in making the chimeras, we obtained some control over which speech stimulus was recognized by the listener. No matter which stimulus was recognized, envelope tracking was always strongest for the ENV stimulus, indicating a dominant contribution from acoustic processing. However, there was also a positive relationship between intelligibility and the tracking of the perceived speech, indicating a contribution from speech specific processing. These findings were supported by a follow-up analysis that assessed envelope tracking as a function of the (estimated) output of the cochlea rather than the original stimuli used in creating the chimeras. Finally, we sought to isolate the speech-specific contribution to envelope tracking using forward encoding models and found that indices of phonetic feature processing tracked reliably with intelligibility. Together these results show that cortical speech tracking is dominated by acoustic processing, but also reflects speech-specific processing.

This work was supported by a Career Development Award from Science Foundation Ireland (CDA/15/3316) and a grant from the National Institute on Deafness and Other Communication Disorders (DC016297). The authors thank Dr. Aaron Nidiffer, Dr. Aisling O'Sullivan, Thomas Stoll and Lauren Szymula for assistance with data collection, and Dr. Nathaniel Zuk, Dr. Aaron Nidiffer, Dr. Aisling O'Sullivan for helpful comments on this manuscript.

Significance Statement

Activity in auditory cortex is known to dynamically track the energy fluctuations, or amplitude envelope, of speech. Measures of this tracking are now widely used in research on hearing and language and have had a substantial influence on theories of how auditory cortex parses and processes speech. But, how much of this speech tracking is actually driven by speech-specific processing rather than general acoustic processing is unclear, limiting its interpretability and its usefulness. Here, by merging two speech stimuli together to form so-called auditory chimeras, we show that EEG tracking of the speech envelope is dominated by acoustic processing, but also reflects linguistic analysis. This has important implications for theories of cortical speech tracking and for using measures of that tracking in applied research.

Introduction

Over the past few years research on natural speech processing has benefited from recognizing that low frequency cortical activity tracks the amplitude envelope of natural speech (Ahissar et al., 2001; Lalor & Foxe, 2010; Luo & Poeppel, 2007). This has been useful for investigating the mechanisms underlying speech processing (Peelle & Davis, 2012), how such processing is affected by attention (Ding & Simon, 2012; Power, Foxe, Forde, Reilly, & Lalor, 2012; Zion-Golumbic et al., 2013), and how audio and visual speech interact (Crosse, Butler, & Lalor, 2015; Crosse, Di Liberto, & Lalor, 2016; Luo, Liu, & Poeppel, 2010; Zion-Golumbic, Cogan, Schroeder, & Poeppel, 2013). However, it remains unclear to what extent these cortical measures reflect higher-level speech-specific processing versus lower-level processing of the spectrotemporal/acoustic stimulus dynamics.

There has been some evidence that speech intelligibility affects these envelope tracking measures (Peelle, Gross, & Davis, 2013), suggesting that they may indeed index speech-specific processing. But precisely what aspects of speech processing are reflected in envelope tracking measures, or even how specifically the measures reflect speech processing at all, is unclear. It has been suggested that different neural populations, having different functional roles in receptive speech processing, may simultaneously contribute to envelope tracking measures (Nai Ding & Simon, 2014). Furthermore, specific mechanistic theories have been proposed, suggesting that envelope tracking (or envelope "entrainment" more specifically) represents a more active process for parsing speech into discrete chunks for further processing (Giraud & Poeppel, 2012). However, drawing definitive inferences about the meaning of cortical speech tracking must contend with the likelihood that much of the speech-tracking signal will derive from general auditory processing of the stimulus acoustics by cortical regions that are agnostic to the special nature of speech. Indeed a wealth of evidence has amassed suggesting that speech is processed by a hierarchically organized network of cortical regions with responses in earlier stages (including primary auditory cortex) being well accounted for based on the spectrotemporal acoustics of the stimulus, and later stages being invariant to those acoustics and involved in more abstract linguistic processing (Davis & Johnsrude, 2003; de Heer, Huth, Griffiths, Gallant, & Theunissen, 2017; DeWitt & Rauschecker, 2012; Huth, de Heer, Griffiths, Theunissen, & Gallant, 2016; Kell, Yamins, Shook, Norman-Haignere, & McDermott, 2018; Norman-Haignere & McDermott, 2018). This is consistent with the idea

that speech sounds are perceived using mechanisms that evolved to process environmental sounds more generally (Diehl, Lotto, & Holt, 2004), with additional linguistic processing occurring in specialized downstream pathways (Hickok & Poeppel, 2007; Rauschecker & Scott, 2009).

Indeed, this notion that cortical tracking of speech might reflect (perhaps a lot of) general acoustic processing as well as (perhaps a more limited contribution from) linguistic processing helps to explain several other findings in the literature. For example, while cortical envelope tracking sometimes shows sensitivity to speech intelligibility as mentioned above (Peelle et al., 2013), this is definitely not always the case (Howard & Poeppel, 2010). Indeed robust cortical tracking has been observed for completely unintelligible speech, including vocoded and backward speech (Di Liberto, Crosse, & Lalor, 2018; Di Liberto, O'Sullivan, & Lalor, 2015; Howard & Poeppel, 2010), as well as very general auditory stimuli such as amplitude modulated broadband noise (Lalor, Power, Reilly, & Foxe, 2009). So acoustic processing definitely makes a substantial contribution. In the present study, we aim to explore this idea of dissociable contributions to envelope tracking using, so-called, auditory chimeras (Smith, Delgutte, & Oxenham, 2002). In particular, we record EEG from subjects as they listen to speech-speech chimeras – stimuli comprised of the temporal fine structure (TFS) of one speech stimulus modulated by the amplitude envelope (ENV) of another speech stimulus. By varying how these chimeras are constructed, we obtain some control over which stimulus is recognized by the listener, allowing us to decouple the processing of the acoustic envelope from the speech content. We hypothesize that envelope tracking will be dominated by the dynamic changes in the acoustic energy of the signal, with a smaller component reflecting speech-specific processing.

Materials and Methods

Subjects

Seventeen native English speakers (mean age 24.9; std 3.7; range 20-30; 8 males) participated in the experiment. Participants reported no neurological diseases, and self-reported normal hearing. Informed consent was obtained from all participants before the experiment and subjects received monetary compensation for their time. The study was conducted in accordance with protocols approved by the Research Subjects Review Board at the University of Rochester.

Stimuli

In our experiment, we wanted to decouple the acoustic amplitude fluctuations of the stimuli from their speech content. To do this, we used so-called auditory chimeras (Smith et al., 2002). These are stimuli in which the envelope of one sound is used to modulate the temporal fine structure of a second sound. Importantly, this can be done after first filtering the sounds into complementary frequency bands using a filter bank. Then, each filter output is Hilbert transformed to derive its analytic signal, and the envelope (calculated as the magnitude of the analytic signal) of the first sound is used to modulate the fine structure (calculated as the

cosine of the phase of the analytic signal) of the other sound within each band – giving a series of partial chimeras. Finally, the partial chimeras are summed over all frequency bands to produce the final chimera (Fig. 1). Critically for our experiment, the number of frequency bands used has a marked effect on which original sound source is actually perceived (Smith et al., 2002). If the original sounds are both speech and just one band is used, then listeners will partially recognize the speech content corresponding to the temporal fine structure. They will (obviously) fail to understand any of the speech content corresponding to the source of the broadband envelope. But, as the number of frequency bands grows, listeners will increasingly understand the speech content relating to the source of the envelope and will no longer perceive the speech content of the temporal fine structure source.

For our experiment, we generated auditory chimeras from two speech sources. These were audiobooks of two classic works of fiction (Env_Story and TFS_Story) which were read in English by two different male speakers and sampled at 48 kHz. Our study consisted of three experimental conditions each involving the presentation of a speech-speech chimera generated using a filterbank with a different number of frequency bands, specifically 1, 4, and 16. These filterbanks were comprised of FIR band-pass filters that were spectrally divided into logarithmically spaced filters along the cochlea frequency map from 80 to 8020 Hz (Greenwood, 1990). Each filter had a nearly rectangular response, and adjacent filters overlapped by 25% of the bandwidth of the narrower filter. All stimulus processing was performed using MATLAB 2016.b software (The MathWorks Inc.). And stimuli were presented to subjects using the Psychophysics toolbox (Brainard & Vision, 1997) within the MATLAB environment along with custom code.

Figure 1. Speech-speech chimera generation. Two audiobooks were passed through Gammatone filterbanks with different numbers of frequency bands (1, 4, 16) for our different experimental conditions. The outputs of these filterbanks were Hilbert transformed (*HT*) allowing us to calculate the envelope of story 1 and a temporal fine structure representation of story 2. The envelope of story 1 was used to modulate the temporal fine structure of story 2 within each frequency band, and the resulting partial chimeras were summed to produce a final multi-band chimera that was played to the subject.

Forty-five separate one-minute speech segments were randomly selected from each story and were used to generate the three types of chimera (1, 4, and 16 bands), resulting in 15 trials per chimeric condition. All of the chimera stimuli were made by using the envelope of the Env_Story segment to modulate the TFS of the TFS_Story segments. All stimuli were spatialized by convolution with a head-related transfer function (HRTF), simulating a scenario in which each stimulus appears to be spatially located directly in front of the subject (Algazi, Duda, Thompson, & Avendano, 2001). Incidentally, we selected an additional ten segments from Env_Story and five segments from TFS_Story, and we presented these – unmodified – to the subjects as a control condition. Ultimately, however, we did not include any analysis of these control data in our results below.

Experimental Procedure

Subjects were instructed to attend to the audio stimulus and maintain visual fixation for the duration of each trial on a crosshair centered on the screen, and to minimize eye blinking and all other motor activities. To quantify speech intelligibility, after each trial, subjects were required to answer four multiple-choice questions (MCQs) on both stories (i.e., 4 from the Env story and 4 from the TFS story). Each question had four possible answers. MCQs, answer choices and chimera condition order were all pseudorandomized across subjects. Stimulus presentation and data recording took place in an audiometric grade sound attenuated and electromagnetically shielded room (IAC Acoustics, North Aurora, IL. 120A-Series). The visual stimuli (crosshair, MCQs and answer choices) were presented on a 24-inch LCD monitor (ASUS Predator), operating at a refresh rate of 60 Hz, and participants were seated at a distance of 70 cm from the display. All audio stimuli were normalized to have the same root mean square intensity and were presented binaurally through Sennheiser HD650 headphones at a self-adjusted comfortable level.

EEG Acquisition

EEG was recorded from 130 channels at 512 Hz using a BioSemi ActiveTwo system. 128 cephalic electrodes were positioned according to the BioSemi Equiradial system, with another 2 electrodes located over the left and right mastoids. Triggers indicating the start of each trial were presented using Psychophysics toolbox in MATLAB for synchronous recording along with the EEG.

EEG Preprocessing

The EEG data were first resampled to 128 Hz using the *decimate* function in MATLAB. The *decimate* function incorporates an 8th order low-pass Chebyshev Type I infinite impulse response (IIR) anti-aliasing filter. Consistent with previous research suggesting that speech tracking is strongest in the δ-band (1-4 Hz) and θ-band (4-8 Hz), we focused our analysis on frequencies below 8 Hz. Specifically, we used a zero phase-shift Chebyshev type-2 bandpass filter with pass bands between 0.1 and 8 Hz. Subsequent preprocessing was performed using the Fieldtrip toolbox (Oostenveld, Fries, Maris, & Schoffelen, 2011) and custom code in MATLAB. After filtering, bad channels were defined as those whose variance was either less

than half or greater than twice that of the surrounding 3–7 channels (depending on location in the montage). These channels were then replaced through spherical spline interpolation (Fieldtrip). Next after removing bad channels we applied denoising using independent component analysis, usually only removing one or two components reflecting eye-movement-related artifacts, which were determined following definitions provided in (Debener, 2010).

Indexing Cortical Speech Tracking using the Temporal Response Function

The goal of this study was to examine how cortical activity tracks the envelope of speech and how that tracking might derive from acoustic vs speech-specific processing. To index cortical speech tracking, we used the temporal response function framework (Crosse, Di Liberto, Bednar, & Lalor, 2016). The general idea of this framework is to use linear regression to map between ongoing speech features (e.g., the envelope) and ongoing neural responses. This can be done either in the forward direction, by examining how well different speech features can explain variance in EEG responses on individual channels (a forward encoding model approach). Or it can be done in the backward direction by attempting to reconstruct an estimate of a speech feature using all of the EEG channels (a decoding approach). It provides a number of dependent measures: the accuracy of EEG predictions based on a forward encoding model, the accuracy of stimulus reconstructions based on a backward decoding model, or the weights that are applied to the stimulus features (forward) or EEG data (backward) on different channels and at different timelags between stimulus and response (see (Crosse et al., 2016) for more details). In the forward direction, the TRF can be described via the following equation:

$$r(t, n) = \sum_{\tau} w(\tau, n) s(t - \tau) + \varepsilon(t, n)$$

where $r(t, n)$ is the neural response at timepoint *t* on channel *n*, *s(t)* is the stimulus feature at time *t*, which can be a univariate (e.g., the envelope) or multivariate (e.g., the spectrogram) representation of the speech, τ indexes the relative time lag between the speech stimulus feature and the neural response in samples, and $\varepsilon(t, n)$ is an error term. In our analysis, *t* runs from 1 to the length of the trial (i.e., 60 s), $n = 1 \dots 128$ channels, and $\tau = -100$ to 500 ms indicating that we are exploring the impact of the stimulus on the EEG data at lags from –100 ms to +500 ms. We then estimated the unknown TRF, $w(\tau, n)$ using regularized (ridge) linear regression (Crosse et al., 2016). As mentioned above, this enabled us to use the weights of the TRF itself ($w(\tau, n)$) as dependent measures, and to test how well different speech features were represented in the EEG by seeing how well the TRF can predict EEG responses to held out trials (Crosse et al., 2016). We also conducted a backward decoding analysis described by the following equation:

$$\hat{s}(t) = \sum_{n-1}^{N} \sum_{\tau} R(t + \tau, n) g(\tau, n)$$

where the main difference is that the TRF, $g(\tau, n)$, is a multivariate function (often known as a decoder) that was fit on all EEG channels at the same time. In general, this approach is more sensitive as it makes more effective use of the available data, but it is also limited in terms of what speech features, $\hat{s}(t)$, can be reconstructed. In our case, we restricted ourselves to

decoding based on the univariate amplitude envelope of the speech stimuli (please see next section). Again, the weights of the decoder and the decoder's ability to reconstruct the stimulus were then available to us as dependent measures.

Speech stimulus representations

To use the TRF framework to examine how cortical activity tracks the amplitude envelope of our speech chimeras, we first needed to calculate the amplitude envelope of our stimuli. Moreover, we were specifically interested in how this cortical tracking might reflect contributions from acoustic and speech-specific processing. To do this, we also wished to use the TRF to explore how cortical activity reflects the processing of other acoustic and speech-specific features of our stimuli. Importantly, for other acoustic and speech-specific features to show up in measures of envelope tracking, their temporal dynamics would need to correlate with those of the envelope. This is true for the spectrogram and phonemes of speech (and less true for higher level representations of speech based on semantic content, e.g., Broderick et al., 2018). As such, to assess how contributions from spectrotemporal and phoneme processing might contribute to envelope tracking, we derived the following acoustic and phonemic feature representations of our speech stimuli:

1. *The Envelope (Env)*. We calculated the amplitude envelope for each the 45 one-minute speech segments from both Env_Story and TFS_Story. We did this by first bandpass filtering the segments into 128 logarithmically-spaced frequency bands spanning 80 and 8000 Hz using a cochlear filterbank (Greenwood, 1990). The envelope for each band was computed using the Hilbert transform, then the broadband envelope was obtained by averaging over the 128 narrowband envelopes. The output of this process was then logarithmically transformed in an effort to account for the nonlinear relationship between electrophysiological responses and stimulus amplitude (Aiken and Picton, 2008). Specifically, dB envelope representations were generated by taking $20\log_{10}$ of the broadband envelope (Aiken and Picton, 2008).

2. *Recovered-envelope (RE-Env)*. One important issue with modeling our EEG data as a function of the envelopes of the original stories used in creating the chimeras, is that the subjects were not actually presented with these original stories. So, when considering how our EEG might track the envelope of the stories in a chimera, we wanted to understand how the cortex might be able to recover the envelope of the TFS story (TFS_Story) from the output of the cochlea. To estimate this recovered envelope, we did the following. We first determined the TFS of the chimera stimuli for all three chimera conditions (1, 4, and 16 bands) by calculating the Hilbert transform of those chimera stimuli, and then determining the cosine of the phase of the resulting analytic signal. We then filtered the TFS signal into 128 bands using cochlear frequency map spanning a range of 80 to 8020 Hz (Greenwood, 1990) and we created analytical signals for each frequency band. Finally, the envelope of each of these narrow bands (calculated as the absolute values of its analytical signal) were summed to generate the broadband *RE-Env* (Smith et al., 2002; Zeng et al., 2004).

3. *Spectrogram (Sgram)*. The envelope is a very impoverished measure of a speech signal. To more fully explore the relationship between envelope tracking and the acoustic processing of speech we sought to more richly represent the speech acoustics. We did this by computing

the Log-Mel spectrogram of our speech stimuli (Chi, Ru, Shamma, & KWG, 2005; Schädler, Meyer, Kollmeier, & CYE, 2012; Verhulst, Altoè, & Vasilkov, 2018). This involved passing the speech signals through a bank of 64 filters that spanned from 124.1 to 7284.1 Hz and that were organized according to the Mel scale (i.e., the scale of pitches judged by listeners to be equal in distance one from another). The output of these filters was then scaled by a logarithmic compressive nonlinearity to convert it to the final Log-Mel spectrogram. The choice of Log-Mel spectrogram was used because it incorporates several properties of the auditory system, non-linear frequency scaling and compression of amplitude values.

4. *Phonemes (Ph)*. We were also interested to explore how envelope tracking might relate to speech-specific processing in the form of a sensitivity to phonemes within the speech. To derive a representation of phonemes, we used the Montreal Forced Aligner (McAuliffe et a., 2017), a python-based open source tool based the Kaldi ASR toolkit that relies on triphone-based Hidden Markov Models to create statistical models associating phonetic symbols to speech signals (http://kaldi-asr.org/). The aligner given an audio speech file and corresponding textual orthographical transcription, partitions each word into phonemes from the American English International Phonetic Alphabet (IPA) and performs forced-alignment (Yuan and Liberman, 2008), returning the starting and ending time-points for each phoneme. This information was then converted into a multivariate time-series composed of indicator variables, which are binary arrays (one for each phoneme). These are active for the time-points in which phonemes occurred. The phonemes are mutually exclusive, so that only one can be active at each sample point. We selected a subset of the IPA composed of the 35 most frequent phonemes in the presented speech stimuli (3 of 38 IPA phonemes were excluded as being outliers in terms of how rare they were). *Ph* is a language dependent representation of speech.

Using the mTRF to Assess the Sensitivity of EEG to Different Speech Features

In the results section that follows, we will be using the TRF framework to assess how well different speech features are represented in the EEG data. As discussed above, two of our dependent measures will be: 1) how well we can reconstruct a speech envelope from the EEG responses (i.e., backward modeling); and, 2) how well we can predict data on different EEG channels using different speech representations (i.e., forward modeling). Two key related considerations for using these dependent measures are: 1) how to train and test the mTRF models so as to trust in the generalizability of the findings, and 2) how to regularize the mTRF models so as to make them robust to EEG fluctuations that are unrelated to the speech, as well as to noise. In terms of the latter issue, we used ridge regression. In brief, this approach penalizes large values in the mTRF, meaning that we are reducing the variance of our mTRF weights, by adding a bias term. Ultimately, this makes for a more generalizable model (see Crosse et al., 2016 for extensive discussion). However, care must be taken not to over-regularize. In what follows we describe how we determined the ridge regression parameters (known as lambda values) that allowed us to best map between speech features and EEG.

Our general strategy for training, regularizing, and testing was to use the following cross-validation procedure. For each of our four stimulus representations, a separate TRF was fit to each of M trials for a range of lambda values. One trial was 'left out' to be used as a 'test set',

with the remaining M-1 trials to be used for the inner cross-validation. Next one of these inner M-1 trials was chosen to be 'left out' and used as a 'validation set'. The remaining M-2 trials were used as a 'training set'. An average model was obtained by averaging over the single-trial models in the 'training set'. This was done for each lambda value. Next, this average model was used to either reconstruct the speech envelope by convolving it with the EEG data (decoding) or predict the EEG responses by convolving it with the chosen speech representations (forward modeling) associated with the 'validation set'. The accuracy of this reconstruction or prediction (of selected EEG channels, please see below) was assessed by comparing it with the real speech envelope or EEG using Pearson's correlation coefficient. This procedure was repeated such that each of the M-1 trials was 'left out' of the 'training set' once. The lambda value that produced the highest average reconstruction or prediction accuracy across all of the validation sets was then chosen as the optimal lambda. Please note, this could mean different optimal values of lambda for reconstruction, for prediction, for each subject, and for each set of speech features.

Next, using the optimal lambda value chosen above, another average model was obtained by averaging over the single-trial models in both the 'validation' and 'training' sets and using that model on the data from the 'test set'. Model performance was assessed by quantifying how accurately the reconstructed envelope or predicted EEG correlated with the actual stimulus envelope or the actual recorded EEG response from the 'test set', again using Pearson's r. This entire procedure was repeated m-times times such that each trial was 'left out' of the inner-cross validation procedure once. As before the overall model performance was then finally assessed by averaging the overall individual model performances for each trial. Again, lambda parameter optimization was done separately for each stimulus representation and subject (i.e., each model was based on its respective optimal performance). Our modeling procedures were subjected to permutation testing to quantify a null distribution, 95% quartiles are demarcated by grey boxes are reported in the figures.

Statistics

As well as using frequentist probability-based statistics, we also used the Bayesian analog of an ANOVA (*anovanBF*) to allow us to explicitly determine the amount of evidence in favor of the null hypothesis (H_0: no interaction). We estimated the Bayes factors (BF_{10}) using Matlab code adapted from RStudio (R-Core-Team, 2016; the function *anovanBF* in the toolbox *Bayes factor* (Morey, Rouder, & Jamil, 2015)). We adopted the commonly used Jeffrey-Zellner-Siow (JZS) prior with a scaling factor of 0.707 (Rouder, Morey, Speckman, & Province, 2012; Rouder, Speckman, Sun, Morey, & Iverson, 2009; Schönbrodt, Wagenmakers, Zehetleitner, & Perugini, 2017). Monte-Carlo resampling with 10^6 iterations was used for the BF_{10} estimation. Subjects represented the random factor. Importantly, this estimation allows us to quantify evidence that our experimental factors and interactions explain variance in the data above the random between-subject variations. Standard convention stipulates that any BF_{10} exceeding 3 is evidence in favour of the alternative hypothesis (H_0), while below 1 is in support of the null hypothesis (H_0), and BF_{10} ranging between 1-3 is taken as weak evidence (Wagenmakers, Wetzels, Borsboom, & Van Der Maas, 2011).

Results

128-channel EEG was recorded from seventeen subjects as they listened to 60-s auditory chimeras composed of segments of narrative speech from two audiobooks. In particular, the envelope of Env_Story was used to modulate the temporal fine structure of TFS_Story. By varying the number of frequency bands used in making the chimeras (1, 4, or 16 bands), we aimed to manipulate which story was understood by the subjects. Following Smith et al. (2002), we expected subjects to (partially) recognize TFS_Story for the 1-band chimeras, to (partially) recognize Env_Story for the 4-band chimeras, and to clearly recognize Env_Story for the 16-band chimeras. We then aimed to explore how cortical tracking of the envelopes of Env_Story and TFS_Story might covary with this predicted behavior, and what that might tell us about the acoustic vs speech-specific processing underlying that cortical tracking.

Speech comprehension varies across speech-speech chimera conditions

Speech comprehension was assessed by asking multiple-choice questions at the end of each trial. There were four possible answers to each question setting the theoretical chance level at 25%. However, we determined that, at the group level, a score of 27.5% was significantly greater than chance ($p = 0.05$) based on a binomial distribution using all 840 trials (14 subjects x 60 questions) per condition. We then tested our distribution of subject scores against 27.5% using a one-sided Wilcoxon sign-rank test. The pattern of behavior was largely consistent with what we expected based on Smith et al., 2002 (Fig. 2A). In particular, performance on the questions for Env_Story in the 1-band condition was 29.43% ± 2.11 (% mean ± SEM) and was not significantly greater than chance (p = 0.28). However, as the number of chimera bands increased, so did performance with subjects achieving 33.43% ± 1.57 and 68.43% ± 2.09 for the 4-bands and 16-band conditions, respectively, both of which were significantly greater than chance ($z = 3.30$, $p = 4.56 \times 10^{-04}$, and $z = 3.60$, $p = 1.58 \times 10^{-04}$ Wilcoxon signed-rank test). Meanwhile, the performance on TFS_Story showed largely the opposite effect. Performance on the questions were 37.86% ± 1.41, 33.71% ± 1.16, and 22.79% ± 1.73 for the 1-band, 4-bands, and 16-bands conditions respectively. Importantly, these scores were significantly above chance for the 1-band ($z = 3.24$, $p = 6.04 \times 10^{-04}$) and 4-bands conditions ($z = 3.11$, $p = 9.37 \times 10^{-04}$). However, as expected, they were not significantly above chance for the 16-band condition ($z = -2.52$, $p = 0.99$).

We wanted to more explicitly test for the interaction effect between chimera condition and story that we expected from Smith et al., (2002). To do this we used a two-way repeated measures ANOVA (*rmANOVA, with factors of chimera condition: 1-, 4-, 16-band, and story: ENV Env_Story, TFS TFS_Story*). This analysis showed main effects of *chimera condition* ($F_{(1,2)} = 42.39, p < 0.001, \eta^2 = 0.15, BF_{10} = 3.259$), and *story* ($F_{(1,1)} = 189.42, p < 0.001, \eta^2 = 0.21, BF_{10} = 2.131$). Importantly, it also revealed a significant interaction between *chimera condition* and *story* ($F_{(1,1)} = 195.45, p < 0.001, \eta^2 = 0.51, BF_{10} = 2.128$). Post hoc analyses were carried out using Bonferroni-corrected pairwise *t*-tests which showed that Env_Story intelligibility scores in the 16-band condition were significantly higher than those in the 1-band condition ($t_{(16)} = 16.71, p < 0.001, BF_{10} = 1.4210 \times 10^{10}$), and TFS_Story scores in the 1-band were significantly higher than 16-bands ($t_{(16)} = 13.04, p < 0.001, BF_{10} = 1.5114 \times 10^{6}$). This pattern of results generally replicates the findings from

Smith et al. (2002), even though we assessed speech intelligibility by means of comprehension questions, while Smith et al. (2002) probed word recall.

Cortical tracking of the original story envelopes varies with understanding of speech-speech chimeras

In line with the overall goals of our study, we wished to explore how cortical tracking of speech envelopes might reflect acoustic and speech-specific processing. Importantly, all three of our stimulus conditions (1-, 4-, and 16-band chimeras) have envelopes that are derived from Env_Story. As such, their acoustic energy will be dominated by that of Env_Story. However, as shown in the previous section, for the 1-band condition, subjects are more likely to understand the speech content from TFS_Story. How might envelope tracking reflect these acoustic and behavioral inconsistencies? We investigated this by attempting to reconstruct estimates of the speech envelopes corresponding to Env_Story and TFS_Story from the EEG recorded during each of our chimera conditions. As discussed above, we did this for all 15 trials for each condition using a cross-validation training and testing procedure. Importantly, for this first analysis, we simply sought to reconstruct the envelopes of the original speech segments, not of the chimeras themselves. Then we compared these reconstructions to the two original envelopes using Pearson's correlation. We also determined a baseline level of reconstruction performance by generating a null distribution of Pearson's r values by shuffling the labels between trials 1000 times and attempting to reconstruct the envelopes using the same procedure (grey bars demarcate 95% confidence interval).

The general pattern of stimulus reconstruction measures mirrored that of the behavioral results. Specifically, as the number of frequency bands in the chimeras increased, envelope reconstructions for Env_Story tended to increase and reconstructions for TFS_Story decreased (Fig. 2B). We assessed this pattern of results using a two-way rmANOVA (with factors of *chimera condition* and *story*). As with the behavioral results, we found significant main effects for *chimera condition* ($F_{(1,2)} = 30.45, p < 0.001, \eta^2 = 0.007, BF_{10} = 16.042$) and *story* ($F_{(1,2)} = 34.44, p < 0.001, \eta^2 = 0.39, BF_{10} = 4.287$). And, mirroring our key behavioral result, we found a significant interaction between *chimera condition* and *story* ($F_{(1,1)} = 56.65, p < 0.001, \eta^2 = 0.15, BF_{10} = 19.307$). Again, we carried out post hoc analyses using Bonferroni-corrected pairwise *t*-tests. These also tracked with the behavioral results in that reconstructions for Env_Story were significantly higher for the 16-band condition than 1-band condition ($t_{(16)} = 16.0, p < 0.001, BF_{10} = 6.01 \times 10^8$), and TFS_Story reconstructions were significantly higher for the 1-band condition than the 16-band condition ($t_{(16)} = 5.04, p < 0.001, BF_{10} = 270.01$).

One important discrepancy between the behavioral and cortical tracking results is that there is robust cortical tracking of Env_Story for the 1-band condition (blue cloud, left, Fig. 2B), despite it being entirely unintelligible (blue cloud, left, Fig. 2A). Indeed, the cortical tracking of Env_Story in this condition is significantly stronger than that for TFS_Story ($t_{(16)} = 5.25, p < 0.001, BF_{10} = 3.49 \times 10^2$), despite TFS_Story being the one that is better understood. Of course, this is easily explained by reminding ourselves that the envelope of the chimera in this condition is determined by Env_Story. This highlights that fluctuations in the acoustic energy of an auditory stimulus will robustly drive cortical tracking, completely

independently of any speech-specific activity. That said, the similar pattern of interaction effects for behavior and envelope tracking also supports the notion that cortical envelope tracking does, at least to some extent, index speech-specific processing. Env_Story tracking improved across conditions as Env_Story understanding increased, and TFS_Story tracking decreased as TFS_Story understanding fell. On this issue, it is particularly interesting to consider the case of the cortical tracking of TFS_Story in the 1-band condition. Again, the envelope of the chimera stimulus in this condition is dominated by Env_Story, and, yet, we have significant cortical tracking of the envelope of TFS_Story. How might this come about? We examine this further in the next subsection below.

We also sought to explore the correspondence in the pattern of results between behavior and stimulus reconstruction more directly (Fig. 2E). Specifically, we used robust correlation analysis with bootstrap resampling (Pernet, Wilcox, & Rousselet, 2013) to check for correlations between these measures across subjects. We did so in one analysis that included all conditions and found a strong positive correlation between decoding accuracy and behavioral intelligibility scores as a function of *chimera condition*, for Env_Story ($r_s = 0.57, p < 0.001, 95\% \, CI \, [0.26 \, 0.74]$) and TFS_Story ($r_s = 0.35, p < 0.05, 95\% \, CI \, [0.06 \, 0.61]$. An important caveat with this result, is that, as mentioned, it was carried out across all stimulus conditions collapsed together. We tested this relationship further using a linear-mixed effect model (LME) with comprehension accuracy scores and envelope reconstruction values as dependent and predictor variables respectively. The LME models variability due to stimulus conditions and subjects simultaneously. We found a significant positive relationship between reconstruction accuracy and comprehension scores for Env_Story ($\beta = 223.21, SE = 30.27 \, p < 0.001$) and for TFS_Story ($\beta = 194.49, SE = 65.88 \, p < 0.01$). Even though EEG envelope tracking measures can vary greatly between subjects, presumably based on biophysics, we also tested for brain-behavior correlations across subjects within each chimera condition. Using permutation testing while controlling for multiple comparisons across conditions we found that there were no significant correlations within any one condition alone, in both the Env_Story ($p = 0.073; \, p = 0.65; p = 0.96$, for 1-bands, 4-bands, and 16 bands respectively) and the TFS_Story ($p = 1.0; \, p = 0.74; p = 0.75$, for 1-bands, 4-bands, and 16 bands respectively).

To visualize which EEG channels were contributing to the pattern of envelope reconstructions reported above, we transformed the backwards decoding model weights (Haufe et al., 2014) into a pattern of forward model weights (Fig. 2D). Visualizing these weights across the scalp is more analogous to exploring the topographical distribution of event-related potentials (Lalor et al., 2009). Using a cluster-based non-parametric permutation ($N = 2000$) analysis (Maris & Oostenveld, 2007) we identified model weights that were significantly different from zero across subjects and trials over a window of 80-120 ms time-lags. We chose these time-lags based on a prominent peak in the forward TRF model over these time-lags. For Env_Story there was an increase in the number of channels with significant model weights as intelligibility increased across conditions. These channels were largely over central and temporal scalp. For TFS_Story, significant model weights were found only for the 1-band condition, i.e., the condition for which TFS_Story was most intelligible. They were centered over central scalp regions.

Figure 2. Cortical tracking of speech envelopes reflects both acoustics and speech intelligibility across chimera conditions. A-C Box plots (mean ± SEM) and rain kernel density estimates of reconstruction decoding accuracy (Rho) values for Env_Story (turquoise) and TFS_Story (peach). Group- and individual statistics; black line in box plot indicates mean across subjects, asterisks indicate group statistical significance (permutation test, *p < 0.05) and grey box demarcates single subject-level statistical significance above chance (permutation test, *p < 0.05). Single dots represent single subject data. A. Behavioral intelligibility, B. original envelope reconstruction accuracies, and C. chimera envelope reconstruction accuracies across bands conditions and stories. D. Topographical plots show forward transformed decoder weights across all channels for Env_Story (C) and TFS_Story (D) over a

time-lag window of 80-120 ms. Red dot indicates significant effects at group level statistics (one-tailed cluster-based permutation test, N=2000, p < 0.05) across the three bands conditions. E. Env_Story and F. TFS_Story brain-behavior correlations collapsed across conditions. Robust Pearson's correlations (bootstrap permutation test p < 0.05, confidence interval 95%).

Cortical tracking of envelopes recovered from the chimeras also varies with understanding of speech-speech chimeras

In the previous section, we wondered about how we might see significant cortical tracking of the TFS_Story envelope to a 1-band chimera whose envelope is determined by Env_Story (Fig. 2B). The answer likely lies in the fact each subject's auditory cortex does not actually operate on the chimera stimuli that we present. Rather, each stimulus first undergoes extensive peripheral and subcortical processing. Indeed, the first stage of this processing is the fine-grained filtering by the cochlea. This produces a representation in the early auditory system that will be exquisitely sensitive to the temporal fine structure in the stimulus. It may be that some of the computations carried out by the cortex serve to synthesize a coherent TFS_Story speech object from these earlier representations – a process sometimes referred to as analysis-by-synthesis (Bever & Poeppel, 2010; N. Ding, Chatterjee, & Simon, 2013; Halle & Stevens, 1962; Halle, Stevens, Wathen-Dunn, & Woods, 1959; Poeppel & Monahan, 2011). This synthesis of an auditory object for TFS_Story from the temporal fine structure of the chimera is likely what our cortical envelope tracking measure is indexing, in this case.

To explore this more directly, we conducted an additional analysis aimed at examining how cortical activity might track with the envelopes of Env_Story and TFS_Story that we recovered from the actual chimera stimuli that were presented to the subjects. As detailed in the methods above, we determined the envelope of the chimera using standard methods. Next, we computed the recovered envelope (ReEnv) of the TFS component from the chimeras using an approach based on the Hilbert transform and cochlear scaled filtering (Apoux, Millman, Viemeister, Brown, & Bacon, 2011; Irino & Patterson, 1997; Roy D Patterson, 1987; Roy D. Patterson, Uppenkamp, Johnsrude, & Griffiths, 2002). The overall pattern of results for the chimera envelopes (which should be very similar to those for Env_Story) and Re-Env (which we expected to resemble the envelopes for TFS_Story) was very similar to that for the original envelopes. Specifically, a two-way rmANOVA (with factors *chimera condition* and *story*) showed main effects for *chimera condition* ($F_{(1,2)} = 29.05, p < 0.001, \eta^2 = 0.006, BF_{10} = 15.002$) and *story* ($F_{(1,1)} = 32.41, p < 0.001, \eta^2 = 0.32, BF_{10} = 4.024$). And there was a significant two-way interaction between *chimera condition* and *story* ($F_{(2,32)} = 55.45, p < 0.001, \eta^2 = 0.14, BF_{10} = 19.007$). Post hoc Bonferroni-corrected t-tests showed that Env_Story reconstruction accuracies for the 16-band condition were significantly higher than those for the 1-band condition ($t_{(16)} = 16.84, p < 0.001, BF_{10} = 5.87 \, x10^8$), and TFS_Story reconstruction accuracies for the 1-band condition were significantly higher than that for the 16-band condition ($t_{(16)} = 5.04, p < 0.001, BF_{10} = 280.21$).

For Env_Story, the fact that the pattern of stimulus reconstruction results was so similar for the original and recovered envelopes (compare turquoise raincloud plots in Fig. 2B and 2C) was entirely unsurprising. This is because the envelopes from the original Env_Story were used to create the chimeras in the first place. However, the similar pattern of stimulus reconstruction

results for the original and recovered envelopes for TFS_Story (compare peach raincloud plots in Fig. 2B and 2C), was more interesting. Indeed, it was not obvious in advance that this would be the result, given that the temporal fine structure of TFS_Story was so heavily modulated by the envelope of Env_Story for the chimeras. That said, the result supports that notion that cortex has been able to synthesize a coherent representation of the envelope of TFS_Story from its (partial) temporal fine structure. Indeed, the original and recovered envelopes for TFS_Story were significantly correlated for the 1-band condition ($r_s = 0.2, p < 0.001$, 95% CI [0.16-0.20]), and there was no significant correlation in the 4-band and 16-band conditions. A final note is the correspondence between the behavior and speech reconstructions for TFS_Story in the 16-band condition. At the group level, behavioral performance was not above chance, indicating a general lack of understanding of TFS_Story in this condition, consistent with previous research (Smith et al., 2002). This was mirrored in the failure to reconstruct the recovered envelope of TFS_Story in this condition (Fig. 2C).

Modeling speech responses in terms of both acoustics and phonetic features can disambiguate acoustic and speech-specific processing

The envelope reconstruction results above highlight one of the key limitations of using envelope tracking as a measure of speech processing. The general correspondence in the patterns of results for behavior and tracking indicate a sensitivity to speech-related processing. However, the robust tracking of speech that is either completely or almost completely unintelligible (i.e., Env_Story in the 1-band and 4-band conditions; Fig. 2B), highlight that much of the cortical tracking is simply driven by acoustic energy – consistent with previous work (Howard & Poeppel, 2010; Lalor et al., 2009). So how might we begin to disentangle the EEG activity that is driven by the stimulus acoustics from that which reflects speech-specific processing? One approach is to use forward encoding models to model EEG responses in terms of specific acoustic and linguistic features of the speech stimulus (Di Liberto et al., 2015). Here we explore this issue with a focus on acoustic and phonemic features whose dynamics likely correlate with those of the envelope. In particular, we aimed to model EEG responses in terms of both the spectrogram and phonemes of speech, and to try to identify unique variance in the EEG responses that can be explained by each. In doing so, we aim to disentangle the encoding of acoustic features from speech-specific processing that likely jointly contribute to the envelope reconstruction measures investigated above.

To explicitly quantify the unique contributions of acoustic and phonemic processing to the EEG, we computed the partial correlation coefficients (Pearson's *r*) between the EEG predicted by either the Phoneme (*Ph*) or Spectrogram (*Sgram*) model with the actual recorded EEG, after controlling for the effects of the other feature. In particular, we conducted two separate ANOVAs, one focused on *Ph* predictions (whilst controlling for *Sgram*) and one focused on *Sgram* (whilst controlling for *Ph*). Both ANOVAs (*rm*ANOVA) had factors of *chimera condition*; 1-, 4-, 16-bands, and *story:* Env_Story, TFS_Story). Both models showed a generally similar pattern to our envelope-based results above, with improvements in prediction with increasing chimera bands for Env_Story and decreases in prediction with increasing chimera bands for TFS_Story (Fig 3). Indeed, for both models, we found a significant main effect of *chimera condition* (*Ph*: ($F_{(1,2)} = 3.06, p < 0.05, \eta^2 = 0.18, BF_{10} =$

59.3); *Sgram*: $(F_{(1,2)} = 5.55, p = 0.006, \eta^2 = 0.09, BF_{10} = 3.2 \times 10^{17})$), and *Story* (*Ph*: $(F_{(1,1)} = 32.53, p < 0.001, \eta^2 = 0.41, BF_{10} = 1.61 \times 10^{08})$; *Sgram*: $(F_{(1,1)} = 62.89, p = 0.001, \eta^2 = 0.53, BF_{10} = 1.38 \times 10^{17})$), and a significant interaction of *chimera condition* and *story* (*Ph*: $(F_{(1,2)} = 16.1, p = 0.001, \eta^2 = 0.34, BF_{10} = 267.65)$; *Sgram*: $(F_{(1,2)} = 21.98, p < 0.001, \eta^2 = 0.07, BF_{10} = 2.9 \times 10^{16})$). Additionally, post-hoc Bonferroni-corrected pairwise *t*-tests revealed that Env_Story partial correlation coefficient scores in the 16-band condition were significantly higher than those scores in the 1-band condition for both models (*Ph*: $(t_{(16)} = 4.65, p < 0.001, BF_{10} = 120.12)$; *Sgram*: $(t_{(16)} = 5.44, p < 0.001, BF_{10} = 481.9)$), and TFS_Story scores in the 1-band were significantly higher than the 16-bands for both models (*Ph*: $(t_{(16)} = 2.79, p < 0.001, BF_{10} = 4.28)$; *Sgram*: $(t_{(16)} = 3.78, p < 0.05, BF_{10} = 23.68)$).

Figure 3. Partial correlations of EEG and stimulus feature representations. Box plots (mean ± SEM) and rain kernel density estimates of Partial correlation Rho (Pearson's r, two-tailed) values for Env_Story (turquoise) and TFS_Story (peach). Group- and individual statistics; black line in box plot indicates mean across subjects, asterisks indicate group statistical significance (permutation test, *p < 0.05) and grey box demarcates single subject-level statistical significance above chance (permutation test, *p < 0.05). Single dots represent single subject data. A, Partial correlation of predicted EEG and phoneme feature representation (Phon) while controlling for acoustics (Sgram). B, Partial correlation of predicted EEG and Sgram while controlling for Phon. C, D Topographical plots show partial correlation Rho across all channels for Env_Story (C) and TFS_Story (D). Red dot indicates significant effects at group level statistics (one-tailed cluster-based permutation test, *p < 0.05).

While these data show that both acoustic and phonemic features track with our original envelope findings, there are a couple of notable differences in the performances of the two models. First, in the 1-band condition, the Env_Story is completely unintelligible, so any prediction based on Env_Story must be driven by acoustic processing. This is reflected in the fact that the acoustic *Sgram* model (Fig 3B,D) predictions are significantly above zero ($z = 3.38$, $p = 7.13 \times 10^{-04}$). Meanwhile, the unique contribution of the *Ph* model (Fig 3A,C), is not significantly above zero for this condition ($z = -0.4$, $p = 0.71$), which again makes sense given that there is no phonemic information in this chimera for Env_Story as speech was degraded and unintelligible in this band. Conversely, for TFS_Story in the 1-band condition, the *Ph* model adds unique predictive power (Fig 3A,C), again, reflecting the fact that this chimera contains phonemic information for TFS_Story. The unique contribution of the *Ph* model disappears for the 4-band and 16-band conditions, again supporting the idea that it represents a measure of speech-specific processing, separable from more general acoustic processing. The differences between the *Ph* and *Sgram* models can also be seen when visualizing which EEG channels are significantly predicted by each model (Fig 3 C,D). While the performance of the *Sgram* model is qualitatively similar to the envelope, the unique contributions of the *Ph* model seem to track more specifically with speech intelligibility.

Figure 4. Envelope reconstructions based on delta and theta band EEG. (A) Box plots (mean ± SEM) and rain kernel density estimates of reconstruction decoding accuracy (Rho) values for Env_Story (turquoise) and TFS_Story (peach). Group- and individual statistics; black line in box plot indicates mean across subjects, asterisks indicate group statistical significance (permutation test, *p < 0.05) and grey box demarcates single subject-level statistical significance above chance (permutation test, *p < 0.05). Single dots represent single subject data.

Intelligibility of speech-speech chimeras reflected more strongly by cortical speech tracking in the delta-band than the theta-band

A substantial amount of previous research has sought to distinguish the roles of delta- and theta-band cortical activity in speech processing (Ding & Simon, 2013, 2014; Doelling, Arnal, Ghitza, & Poeppel, 2014; Etard & Reichenbach, 2019; Peelle, Gross, & Davis, 2013). With that in mind, we sought to explore the sensitivity of delta and theta band speech tracking measures across our different chimera conditions. We did this by attempting to reconstruct the envelopes of Env_Story and TFS_Story from EEG that had first been filtered into either the delta (0.05–4 Hz) or theta (4-8 Hz) bands (using zero phase-shift Chebyshev type-2 bandpass filters). We found that the pattern of reconstruction accuracies based on delta band EEG (Fig. 4A) corresponded to that seen for speech intelligibility (Fig. 2A). However, this was much less clear for reconstructions based on theta band activity (Fig. 4A). Indeed, for delta band reconstructions, as with both the broadband EEG decoding of the envelopes of the original speech (Fig. 2B) and the chimera speech (Fig. 2C), we found significant main effects for *chimera condition* ($F_{(1,2)} = 45.12, p < 0.001, \eta^2 = 0.58, BF_{10} = 6.01$) and *story* ($F_{(1,1)} = 34.44, p < 0.001, \eta^2 = 0.16, BF_{10} = 4.287$). And, we again saw a significant two-way interaction between *chimera condition* and *story* ($F_{(1,2)} = 132.42, p < 0.001, \eta^2 = 0.15, BF_{10} = 20.08$). Again, post-hoc Bonferroni-corrected pairwise *t*-tests revealed that reconstructions for Env_Story were significantly higher for the 16-band condition than 1-band condition ($t_{(16)} = 16.9, p < 0.001, BF_{10} = 8.88 \times 10^{8}$), and TFS_Story reconstructions were significantly higher for the 1-band condition than the 16-band condition ($t_{(16)} = 5.14, p < 0.001, BF_{10} = 283.93$), as we had found with broadband EEG. In contrast, theta-based reconstructions did not track significantly with speech intelligibility in the chimera stimuli. While there was a main effect for *story* ($F_{(1,1)} = 92.12, p < 0.001, \eta^2 = 0.5, BF_{10} = 4.84$), there was no main effect for *chimera condition* ($F_{(1,2)} = 0.04, p = 0.9, \eta^2 = 1.11 \times 10^{-15}, BF_{10} = 0.002$), and no interaction effect ($F_{(1,2)} = 1.89, p = 1.89, \eta^2 = 0.01, BF_{10} = 0.06$). Post-hoc Bonferroni-corrected *t*-tests showed that Env_Story reconstruction accuracies for the 16-band condition were not significantly different (or higher) than the 1-band condition ($t_{(16)} = 1.2, p = 0.24 \ (ns), BF_{10} = 0$). Similarly, there was no significant difference between 1-band and 16-bands conditions in TFS_Story reconstruction accuracies $t_{(16)} = 1.94, p = 0.07, BF_{10} = 1.1$).

Discussion

In this study, we have aimed to disentangle the contributions to cortical speech envelope tracking that derive from acoustic and speech-specific processing. Using speech-speech chimeras, we aimed to decouple the acoustic envelope fluctuations of a stimulus from its speech content. We found evidence of robust envelope tracking based on acoustic energy fluctuations. We also found that changes in the strength of envelope tracking correlate with speech intelligibility across conditions. Altogether, we conclude that the cortical tracking of speech envelopes contains a large contribution from general auditory processing, with additional contributions from neural populations that are specifically tuned to speech.

The notion of a substantial general acoustic contribution to cortical speech responses is in line with the idea that speech sounds are perceived using mechanisms that evolved to process environmental sounds more generally (Diehl et al., 2004), with additional linguistic processing occurring in specialized downstream pathways (Hickok & Poeppel, 2007; Rauschecker & Scott, 2009). Indeed, there is a wealth of evidence suggesting that speech is processed by a hierarchically organized network of cortical regions with responses in earlier stages (including primary auditory cortex) being well accounted for based on the spectrotemporal acoustics of the stimulus, and later stages being invariant to those acoustics and involved in more abstract linguistic processing (Davis & Johnsrude, 2003; de Heer et al., 2017; DeWitt & Rauschecker, 2012; Huth et al., 2016; Kell et al., 2018; Norman-Haignere & McDermott, 2018). Of course, to contribute to envelope tracking, any such linguistic processing must involve speech features whose dynamics correlate with the envelope. One candidate set of features would be phonemes, whose onsets and offsets will often coincide with fluctuations in the envelope. The superior temporal gyrus – an auditory association area whose activity is not especially well captured based on a spectrotemporal representation of speech (Davis & Johnsrude, 2003; Norman-Haignere & McDermott, 2018) has shown a high degree of tuning for phonetic features (Chang et al., 2010; Mesgarani, Cheung, Johnson, & Chang, 2014).

The idea that envelope tracking consists of general acoustic processing contributions from primary auditory areas, and temporally correlated speech-specific contributions from areas like STG explains many of the features of our results. For example, we see robust envelope tracking of Env_Story in the 1-band condition, when it is completely unintelligible. This must necessarily be due to simple auditory responses to changes in acoustic energy and fits with previous work showing robust envelope tracking to non-speech stimuli (e.g., Lalor et al., 2009). The tracking of the Env_Story envelope then increases in strength across the 4-band and 16-band conditions as subject increasingly understand the speech content of story 1, which likely reflects the increased contribution from speech-specific neuronal populations across these conditions. Conversely, we see significantly lower envelope tracking for TFS_Story, which makes sense as the energy fluctuations of the stimulus are dominated by Env_Story. Thus, the general acoustic processing contribution will be relatively insensitive to the dynamics of TFS_Story. However, in the 1-band (and 4-band) condition, subjects can partially understand the speech content of TFS_Story. And this leads to significant envelope tracking for TFS_Story in that condition, likely driven by contributions from STG and other speech-specific areas. That said, we also found that the EEG tracked the envelope that was recovered from the chimera stimuli (RE-Env), meaning that there could be tracking of lower-level

acoustic features that have been resynthesized from the chimera after it passes through the cochlea.

We attempted to parse the contributions of acoustic and phonemic processing using forward encoding models. In general, both sets of features contributed uniquely to predicting EEG responses, with both increasing across conditions for Env_Story and decreasing across conditions for TFS_Story. Notably, the unique contribution for the phoneme features (*Ph*) was only significant for individual EEG channels for Env_Story in the 4-band and 16-band conditions, i.e., where Env_Story could be partially understood, and TFS_Story in the 1-band condition, i.e., were TFS_Story could be partially understood. The phoneme model added no value in conditions where Env_Story (1-band) and TFS_Story (16-band) could not be understood. This suggests that modeling the responses to speech in this way has enabled us to tap into contributions from speech-specific areas, like STG.

The idea of general and speech-specific contributions to envelope tracking helps to explain why it can be quite difficult to link cortical envelope tracking measures with measures of speech understanding (Howard & Poeppel, 2010). For example, some studies have reported that cortical envelope tracking shows sensitivity to speech intelligibility (Peelle et al., 2013; Vanthornhout, Decruy, Wouters, Simon, & Francart, 2018), while others have failed to find it (Howard & Poeppel, 2010). It may be that the large general auditory processing contribution to envelope tracking that is common to both intelligible and unintelligible speech somewhat masks a smaller contribution from task-based speech-specific processing. Indeed, in studies that have tried to control or account for the acoustic contributions to speech perception, correlations with behavior have been reported for phoneme-level processing (Di Liberto et al., 2018), including in STG (Leonard et al., 2016).

It has been well established that cortical envelope tracking is strongly affected by selective attention (Ding & Simon, 2012; Kerlin, Shahin, & Miller, 2010; O'Sullivan et al., 2015; Power et al., 2012). However, correlations between envelope tracking and behavioral measures of cocktail party attention have been difficult to identify (O'Sullivan et al., 2015; Tune, Alavash, Fiedler, & Obleser, 2020). Again, if we consider envelope tracking as the combination of general acoustic and speech-specific processing, this makes sense. Using invasive recordings, it has recently been shown that cocktail party attention effects vary substantially in their strength across the cortical hierarchy, with weak effects in early auditory areas like Heschl's gyrus and much stronger effects in areas like STG (O'Sullivan et al., 2019). And EEG studies have suggested something similar on the basis of examining envelope tracking at different latencies (Power et al., 2012) or based on trying to isolate markers of acoustic and phonetic feature processing (Teoh & Lalor, 2020). Indeed, focusing specifically on cortical responses to higher-level linguistic speech features – including those at the lexical and semantic levels – researchers have often found strong correlations with attention (Brodbeck, Hong, & Simon, 2018; Broderick, Anderson, Di Liberto, Crosse, & Lalor, 2018), and speech understanding more generally (Broderick et al., 2018). Incidentally, it is worth reflecting on the possible role of attention in the pattern of results we see in the present study. For example, one might wonder if changes in the amount of attention being paid to Env_Story or TFS_Story across conditions is driving the changes in envelope reconstruction accuracy we see (Fig 2). We think this is unlikely. This is because, in our experiment, there was always just a single chimera stimulus being presented at any one time. Thus, any increase in attention to

the speech content is likely to enhance the response to the acoustic energy changes. Of course, this is not guaranteed. Feature-based attention has been shown to affect the processing of some features more than others within the same object (Maunsell & Treue, 2006). However, the limited literature exploring how different feature-based attention tasks within a cocktail party environment have shown no clear effects on envelope tracking (Lauteslager, O'Sullivan, Reilly, & Lalor, 2014).

The approach and results in this study have implications for theories of so-called speech entrainment (Giraud & Poeppel, 2012; Obleser & Kayser, 2019). One such prominent theory posits that intrinsic, ongoing oscillatory brain rhythms "entrain" to the rhythms of the speech signal by aligning their phase with the stimulus in an anticipatory, behaviourally effective manner. The core idea of this model is that salient points ('edges') in the speech signal cause "phase resetting" of ongoing oscillatory activity. The realignment of the phase of these oscillations, which has been linked to fluctuations in cortical excitability (Lakatos et al., 2005), then enables the parsing and chunking of the continuous speech signal into discrete linguistic units for further processing by faster oscillations (Ghitza, 2011; Giraud & Poeppel, 2012; Rimmele, Morillon, Poeppel, & Arnal, 2018). This theory links to fundamental electrophysiological observations in nonhuman studies (Lakatos, Karmos, Mehta, Ulbert, & Schroeder, 2008). However, when it comes to the specific case of speech processing in humans, it has largely been built from observations that cortical activity (often measured noninvasively) shows consistent phasic fluctuations in theta band activity across repeated presentations of a speech stimulus (Luo & Poeppel, 2007). The fact that theta band activity appears special in this regard has led to the suggestion that this entrainment facilitates the parsing of continuous speech into syllables, given that the timescale of syllables is in the range of 4-8 Hz. However, basing this theory on the idea of consistent fluctuations in noninvasively recorded brain responses to speech is problematic. As we have shown in the present study, much of the variance in these fluctuations is driven by amplitude modulations of the stimulus, again, in line with previous research (Lalor et al., 2009). If acoustic edges (perhaps corresponding to syllable boundaries) were driving this cortical tracking, we might expect to see stronger tracking for TFS_Story than Env_Story in our 1-band condition. Of course, it may be that different oscillators, each with a different specific role, are concurrently active in different cortical areas. And, indeed, recent research (also using auditory chimeras) has reported cortical entrainment in the theta range to temporal fine structure (Teng et al., 2019). However, in general, the entrainment theory has assumed cortical entrainment in primary auditory areas (Giraud & Poeppel, 2012) and has treated scalp-based measures of cortical speech tracking in the theta band as if they represent a monolithic thing. Our interpretation is that acoustic energy fluctuations drive evoked responses in early auditory areas, with speech-specific tuning leading to additional contributions from auditory association areas like STG – an interpretation that can also easily explain the recently reported cortical tracking of TFS (Teng et al., 2019).

Finally, the variation in speech intelligibility across chimera conditions was mirrored more strongly in delta band EEG frequencies than theta band. This runs counter to some previous literature that has suggested that theta-band activity encodes speech features critical for intelligibility while delta-band activity is more related to non-speech-specific acoustic fluctuations (Nai Ding & Simon, 2014). However, as discussed above, we contend that treating activity in each of these frequency bands as if it is a unitary signal is likely to mask the fact that

both general auditory and speech-specific activity are likely to be occurring within those frequency ranges. Continued future efforts to account for general acoustic contributions will be essential to honing in on neural signatures of speech-specific processing.

References

Ahissar, E., Nagarajan, S., Ahissar, M., Protopapas, A., Mahncke, H., & Merzenich, M. M. (2001). Speech comprehension is correlated with temporal response patterns recorded from auditory cortex. *Proceedings of the National Academy of Sciences, 98*(23), 13367–13372.

Algazi, V. R., Duda, R. O., Thompson, D. M., & Avendano, C. (2001). *The cipic hrtf database.* Paper presented at the Proceedings of the 2001 IEEE Workshop on the Applications of Signal Processing to Audio and Acoustics (Cat. No. 01TH8575).

Apoux, F., Millman, R. E., Viemeister, N. F., Brown, C. A., & Bacon, S. P. (2011). On the mechanisms involved in the recovery of envelope information from temporal fine structure. *The Journal of the Acoustical Society of America, 130*(1), 273-282.

Bever, T. G., & Poeppel, D. (2010). Analysis by synthesis: a (re-) emerging program of research for language and vision. *Biolinguistics, 4*(2-3), 174-200.

Brainard, D. H., & Vision, S. (1997). The psychophysics toolbox. *Spatial vision, 10*, 433-436.

Brodbeck, C., Hong, L. E., & Simon, J. Z. (2018). Rapid Transformation from Auditory to Linguistic Representations of Continuous Speech. *Current Biology*.

Broderick, M. P., Anderson, A. J., Di Liberto, G. M., Crosse, M. J., & Lalor, E. C. (2018). Electrophysiological correlates of semantic dissimilarity reflect the comprehension of natural, narrative speech. *Current Biology, 28*(5), 803-809.

Chang, E. F., Rieger, J. W., Johnson, K., Berger, M. S., Barbaro, N. M., & Knight, R. T. (2010). Categorical speech representation in human superior temporal gyrus. *Nature neuroscience, 13*(11), 1428-1432.

Chi, T., Ru, P., Shamma, S. A., & KWG. (2005). Multiresolution spectrotemporal analysis of complex sounds.

Crosse, M. J., Butler, J. S., & Lalor, E. C. (2015). Congruent Visual Speech Enhances Cortical Entrainment to Continuous Auditory Speech in Noise-Free Conditions. *J Neurosci, 35*(42), 14195-14204.

Crosse, M. J., Di Liberto, G. M., Bednar, A., & Lalor, E. C. (2016). The multivariate temporal response function (mTRF) toolbox: a MATLAB toolbox for relating neural signals to continuous stimuli. *Frontiers in Human Neuroscience, 10*.

Crosse, M. J., Di Liberto, G. M., & Lalor, E. C. (2016). Eye Can Hear Clearly Now: Inverse Effectiveness in Natural Audiovisual Speech Processing Relies on Long-Term Crossmodal Temporal Integration. *J Neurosci, 36*(38), 9888-9895.

Davis, M. H., & Johnsrude, I. S. (2003). Hierarchical processing in spoken language comprehension. *Journal of Neuroscience, 23*(8), 3423-3431.

de Heer, W. A., Huth, A. G., Griffiths, T. L., Gallant, J. L., & Theunissen, F. E. (2017). The hierarchical cortical organization of human speech processing. *Journal of Neuroscience*, 3267-3216.

Debener, T. J., Schneider TR, Viola FC. (2010). Using ICA for the Analysis of Multi-Channel EEG Data : Simultaneous EEG and fMRI - oi. *Oxford: OUP*, pp121–134.

DeWitt, I., & Rauschecker, J. P. (2012). Phoneme and word recognition in the auditory ventral stream. *Proceedings of the National Academy of Sciences of the United States of America, 109*(8), 505–514.

Di Liberto, G. M., Crosse, M. J., & Lalor, E. C. (2018). Cortical Measures of Phoneme-Level Speech Encoding Correlate with the Perceived Clarity of Natural Speech. *eNeuro*, ENEURO. 0084-0018.2018.

Di Liberto, G. M., O'Sullivan, J. A., & Lalor, E. C. (2015). Low-Frequency Cortical Entrainment to Speech Reflects Phoneme-Level Processing. *Current Biology, 25*(19), 2457-2465.

Diehl, R. L., Lotto, A. J., & Holt, L. L. (2004). Speech perception. *Annu. Rev. Psychol., 55*, 149-179.

Ding, N., Chatterjee, M., & Simon, J. Z. (2013). Robust cortical entrainment to the speech envelope relies on the spectro-temporal fine structure. *Neuroimage, 88c*, 41-46.

Ding, N., & Simon, J. Z. (2012). Emergence of neural encoding of auditory objects while listening to competing speakers. *Proceedings of the National Academy of Sciences, 109*(29), 11854-11859.

Ding, N., & Simon, J. Z. (2013). Adaptive temporal encoding leads to a background-insensitive cortical representation of speech. *Journal of Neuroscience, 33*(13), 5728-5735.

Ding, N., & Simon, J. Z. (2014). Cortical entrainment to continuous speech: functional roles and interpretations. *Frontiers in human neuroscience, 8*.

Doelling, K. B., Arnal, L. H., Ghitza, O., & Poeppel, D. (2014). Acoustic landmarks drive delta–theta oscillations to enable speech comprehension by facilitating perceptual parsing. *Neuroimage, 85*, 761-768.

Etard, O., & Reichenbach, T. (2019). Neural speech tracking in the theta and in the delta frequency band differentially encode clarity and comprehension of speech in noise. *Journal of Neuroscience, 39*(29), 5750-5759.

Ghitza, O. (2011). Linking speech perception and neurophysiology: speech decoding guided by cascaded oscillators locked to the input rhythm. *Frontiers in psychology, 2*.

Giraud, A.-L., & Poeppel, D. (2012). Cortical oscillations and speech processing: emerging computational principles and operations. *Nature neuroscience, 15*(4), 511–517.

Greenwood. (1990). A cochlear frequency-position function for several species--29 years later. *J Acoust Soc Am, 87*(6), 2592-2605.

Halle, M., & Stevens, K. (1962). Speech recognition: A model and a program for research. *IRE transactions on information theory, 8*(2), 155-159.

Halle, M., Stevens, K. N., Wathen-Dunn, W., & Woods, L. (1959). Proceedings of the Seminar on Speech Compression and Processing.

Hickok, G., & Poeppel, D. (2007). The cortical organization of speech processing. *Nature Reviews Neuroscience, 8*(5), 393-402.

Howard, M. F., & Poeppel, D. (2010). Discrimination of speech stimuli based on neuronal response phase patterns depends on acoustics but not comprehension. *Journal of neurophysiology, 104*(5), 2500-2511.

Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature, 532*(7600), 453-458.

Irino, T., & Patterson, R. D. (1997). A time-domain, level-dependent auditory filter: The gammachirp. *The Journal of the Acoustical Society of America, 101*(1), 412-419.

Kell, A. J., Yamins, D. L., Shook, E. N., Norman-Haignere, S. V., & McDermott, J. H. (2018). A task-optimized neural network replicates human auditory behavior, predicts brain responses, and reveals a cortical processing hierarchy. *Neuron, 98*(3), 630-644. e616.

Kerlin, J. R., Shahin, A. J., & Miller, L. M. (2010). Attentional gain control of ongoing cortical speech representations in a "cocktail party". *The Journal of Neuroscience, 30*(2), 620-628.

Lakatos, P., Karmos, G., Mehta, A. D., Ulbert, I., & Schroeder, C. E. (2008). Entrainment of neuronal oscillations as a mechanism of attentional selection. *science, 320*(5872), 110-113.

Lakatos, P., Shah, A. S., Knuth, K. H., Ulbert, I., Karmos, G., & Schroeder, C. E. (2005). An oscillatory hierarchy controlling neuronal excitability and stimulus processing in the auditory cortex. *Journal of neurophysiology, 94*(3), 1904-1911.

Lalor, E. C., & Foxe, J. J. (2010). Neural responses to uninterrupted natural speech can be extracted with precise temporal resolution. *European Journal of Neuroscience, 31*(1), 189–193.

Lalor, E. C., Power, A. J., Reilly, R. B., & Foxe, J. J. (2009). Resolving precise temporal processing properties of the auditory system using continuous stimuli. *Journal of Neurophysiology, 102*(1), 349–359.

Lauteslager, T., O'Sullivan, J. A., Reilly, R. B., & Lalor, E. C. (2014). *Decoding of attentional selection in a cocktail party environment from single-trial EEG is robust to task.* Paper presented at the 2014 36th Annual International Conference of the IEEE Engineering in Medicine and Biology Society.

Luo, H., Liu, Z. X., & Poeppel, D. (2010). Auditory Cortex Tracks Both Auditory and Visual Stimulus Dynamics Using Low-Frequency Neuronal Phase Modulation. *Plos Biology, 8*(8).

Luo, H., & Poeppel, D. (2007). Phase patterns of neuronal responses reliably discriminate speech in human auditory cortex. *Neuron, 54*(6), 1001-1010.

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG-and MEG-data.

Maunsell, J. H., & Treue, S. (2006). Feature-based attention in visual cortex. *Trends in neurosciences, 29*(6), 317-322.

McAuliffe, M., Socolof, M., Mihuc, S., & Wagner…, M. (2017). Montreal Forced Aligner: trainable text-speech alignment using Kaldi.

Mesgarani, N., Cheung, C., Johnson, K., & Chang, E. F. (2014). Phonetic feature encoding in human superior temporal gyrus. *Science, 343*(6174), 1006-1010.

Morey, R. D., Rouder, J. N., & Jamil, T. (2015). BayesFactor: Computation of Bayes factors for common designs. R package version 0.9. 12-2.

Norman-Haignere, S. V., & McDermott, J. H. (2018). Neural responses to natural and model-matched stimuli reveal distinct computations in primary and nonprimary auditory cortex. *PLoS biology, 16*(12), e2005127.

O'Sullivan, J. A., Power, A. J., Mesgarani, N., Rajaram, S., Foxe, J. J., Shinn-Cunningham, B. G., et al. (2015). Attentional selection in a cocktail party environment can be decoded from single-trial EEG. *Cerebral Cortex, 25*(7), 1697–1706.

O'Sullivan, J., Herrero, J., Smith, E., Schevon, C., McKhann, G. M., Sheth, S. A., et al. (2019). Hierarchical Encoding of Attended Auditory Objects in Multi-talker Speech Perception. *Neuron, 104*(6), 1195-1209. e1193.

Obleser, J., & Kayser, C. (2019). Neural entrainment and attentional selection in the listening brain. *Trends in cognitive sciences, 23*(11), 913-926.

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J. M. (2011). FieldTrip: Open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data. *Comput Intell Neurosci, 2011*, 156869.

Patterson, R. D. (1987). A pulse ribbon model of monaural phase perception. *The Journal of the Acoustical Society of America, 82*(5), 1560-1586.

Patterson, R. D., Uppenkamp, S., Johnsrude, I. S., & Griffiths, T. D. (2002). The Processing of Temporal Pitch and Melody Information in Auditory Cortex. *Neuron, 36*(4), 767-776.

Peelle, J. E., & Davis, M. H. (2012). Neural oscillations carry speech rhythm through to comprehension. *Frontiers in psychology, 3*.

Peelle, J. E., Gross, J., & Davis, M. H. (2013). Phase-locked responses to speech in human auditory cortex are enhanced during comprehension. *Cerebral cortex, 23*(6), 1378-1387.

Peelle, J. E., Gross, J., & Davis, M. H. (2013). Phase-locked responses to speech in human auditory cortex are enhanced during comprehension. *Cereb Cortex, 23*(6), 1378-1387.

Pernet, C. R., Wilcox, R. R., & Rousselet, G. A. (2013). Robust correlation analyses: false positive and power validation using a new open source matlab toolbox. *Frontiers in psychology, 3*, 606.

Poeppel, D., & Monahan, P. J. (2011). Feedforward and feedback in speech perception: Revisiting analysis by synthesis. *Language and Cognitive Processes, 26*(7), 935-951.

Power, A. J., Foxe, J. J., Forde, E. J., Reilly, R. B., & Lalor, E. C. (2012). At what time is the cocktail party? A late locus of selective attention to natural speech. *European Journal of Neuroscience, 35*(9), 1497–1503.

Rauschecker, J. P., & Scott, S. K. (2009). Maps and streams in the auditory cortex: nonhuman primates illuminate human speech processing. *Nature neuroscience, 12*(6), 718-724.

Rimmele, J. M., Morillon, B., Poeppel, D., & Arnal, L. H. (2018). Proactive sensing of periodic and aperiodic auditory patterns. *Trends in cognitive sciences, 22*(10), 870-882.

Rouder, J. N., Morey, R. D., Speckman, P. L., & Province, J. M. (2012). Default Bayes factors for ANOVA designs. *Journal of Mathematical Psychology, 56*(5), 356-374.

Rouder, J. N., Speckman, P. L., Sun, D., Morey, R. D., & Iverson, G. (2009). Bayesian t tests for accepting and rejecting the null hypothesis. *Psychonomic bulletin & review, 16*(2), 225-237.

Schädler, M. R., Meyer, B. T., Kollmeier, B., & CYE. (2012). Spectro-temporal modulation subspace-spanning filter bank features for robust automatic speech recognition.

Schönbrodt, F. D., Wagenmakers, E.-J., Zehetleitner, M., & Perugini, M. (2017). Sequential hypothesis testing with Bayes factors: Efficiently testing mean differences. *Psychological methods, 22*(2), 322.

Smith, Z. M., Delgutte, B., & Oxenham, A. J. (2002). Chimaeric sounds reveal dichotomies in auditory perception. *Nature, 416*(6876), 87-90.

Teoh, E. S., & Lalor, E. C. (2020). Attention differentially affects acoustic and phonetic feature encoding in a multispeaker environment. *bioRxiv*.

Tune, S., Alavash, M., Fiedler, L., & Obleser, J. (2020). Neural attention filters do not predict behavioral success in a large cohort of aging listeners. *bioRxiv*.

Vanthornhout, J., Decruy, L., Wouters, J., Simon, J. Z., & Francart, T. (2018). Speech intelligibility predicted from neural entrainment of the speech envelope. *Journal of the Association for Research in Otolaryngology, 19*(2), 181-191.

Verhulst, S., Altoè, A., & Vasilkov, V. (2018). Computational modeling of the human auditory periphery: Auditory-nerve responses, evoked potentials and hearing loss.

Wagenmakers, E.-J., Wetzels, R., Borsboom, D., & Van Der Maas, H. L. (2011). Why psychologists must change the way they analyze their data: the case of psi: comment on Bem (2011).

Zeng, F.-G., Nie, K., Liu, S., Stickney, G., Rio, E. D., Kong, Y.-Y., et al. (2004). On the dichotomy in auditory perception between temporal envelope and fine structure cues (L).

Zion-Golumbic, E. M., Cogan, G. B., Schroeder, C. E., & Poeppel, D. (2013). Visual Input Enhances Selective Speech Envelope Tracking in Auditory Cortex at a "Cocktail Party". *Journal of Neuroscience, 33*(4), 1417–1426.

Zion-Golumbic, E. M., Ding, N., Bickel, S., Lakatos, P., Schevon, C. A., McKhann, G. M., et al. (2013). Mechanisms Underlying Selective Neuronal Tracking of Attended Speech at a "Cocktail Party". *Neuron, 77*(5), 980–991.