Longitudinal Network Re-organization Across Learning and Development

Ethan M. McCormick*[1], Sabine Peters[2,3], Eveline A. Crone[2,3,4], & Eva H. Telzer[1]

[1]Department of Psychology and Neuroscience, University of North Carolina, Chapel Hill, North Carolina, 27599; [2]Department of Developmental and Educational Psychology, Leiden University, 2333AK Leiden, The Netherlands; [3]Leiden Institute for Brain and Cognition, 2333ZA Leiden, The Netherlands; [4]School of Social and Behavioural Sciences, Erasmus University Rotterdam, Rotterdam, The Netherlands.

*corresponding author
Ethan M. McCormick
235 E. Cameron Avenue
Chapel Hill, NC 27514
emccormick@unc.edu

Abstract

While it is well understood that the brain experiences changes across short-term

experience/learning and long-term development, it is unclear how these two mechanisms interact

to produce developmental outcomes. Here we test an interactive model of learning and

development where certain learning-related changes are constrained by developmental changes in

the brain against an alternative development-as-practice model where outcomes are determined

primarily by the accumulation of experience regardless of age. Participants (8-29 years)

participated in a three-wave, accelerated longitudinal study during which they completed a

feedback learning task during an fMRI scan. Adopting a novel longitudinal modeling approach,

we probed the unique and moderated effects of learning, experience, and development

simultaneously on behavioral performance and network modularity during the task. We found

nonlinear patterns of development for both behavior and brain, and that greater experience

supported increased learning and network modularity relative to naïve subjects. We also found

changing brain-behavior relationships across adolescent development, where heightened network

modularity predicted improved learning, but only following the transition from adolescence to

young adulthood. These results present compelling support for an interactive view of experience

and development, where changes in the brain impact behavior in context-specific fashion based on

developmental goals.

1. Introduction

65
The brain is a dynamic system capable of reshaping itself across time to adapt to its external
environment. For some developmental processes (e.g., cognitive control or risk-taking; Casey,
2015; or socioemotional development; Blakemore & Mills, 2014), these changes unfold across
long time horizons (e.g., months or years). However, functional development does not require
years, or even months, to show measurable changes. Indeed, a broad literature has demonstrated
that brain function rapidly adapts to task demands and feedback to support skill acquisition or goal-
directed behavior (e.g., Daw et al., 2006; Bassett et al., 2011; McCormick & Telzer, 2017a; 2017b;
2018; Telesford et al., 2017; Gerraty et al., 2018). However, it remains unclear to what extent these
short-term, learning-related changes in brain activation overlap with the long-term, maturational
plasticity seen across years and decades of development (Galván, 2010). Here, we test two
potential explanations for how experience and development interact across time to explain changes
in learning performance and the functional brain systems that support that performance across
time. To probe these interactions, we adopt a novel application of longitudinal modeling that
allows us to consider changes across minutes, years, and the course of development
simultaneously. This approach offers an integrated perspective of learning and development as co-
dependent processes of neural and behavior plasticity which interact across time.

While traditionally thought of as a period of vulnerability (Steinberg et al., 2008; Casey et
al., 2008; Shulman et al., 2016), adolescence is also a period associated with increases in flexible
behavior and the capacity to learn from feedback in the environment (Johnson & Wilbrecht, 2011;
Crone & Dahl, 2012; Casey, 2015; Vigilant et al., 2015), with neural changes associated with age
supporting increased learning (Van Duijvenvoorde et al., 2008; Peters et al., 2016; McCormick &
Telzer, 2017a; Peters & Crone, 2017). In general. the ability to learn and engage in other complex

cognitive tasks (Casey et al., 2005; Luna et al., 2010), improves with age through the first decades

of life. However, this co-occurrence does not by itself imply that maturation is necessary for the

age-related improvements in learning seen during development. With increased age also comes

more experience and practice at skills needed to support task performance. Under this view,

development involves the accumulation of practice or training of neural systems, and the neural

mechanisms for this process should closely resemble those involved in short-term learning. In

concrete terms, this would imply that developmentally younger individuals can be trained to

perform as well as older individuals given sufficient practice.

In contrast, an interactive view of learning and development would suggest that certain

kinds of neural changes in response to learning are constrained by developmental changes in the

brain. In other words, it should be practically impossible to train a child to perform at adult levels

because they have not experienced the maturational changes in the brain necessary to support that

performance. This would suggest that certain kinds of neural changes in response to learning will

be relatively unique to older individuals. These two alternative accounts are not mutually

exclusive, since training studies in younger individuals clearly demonstrate that there is some

capacity to improve cognitive performance and shift brain function even in the maturing brain

(Jolles & Crone, 2012). However, the first explanation of how learning and development interact

would predict that this capacity to train should be quite extensive, whereas the second explanation

would predict that biological maturation imposes stricter limitations on the ability to train young

individual to "adult" levels of performance. It is important to note, however, that these limitations

may not be maladaptive, but rather serve some other developmental function where "immature"

brain states or behavioral performance are important for flexible learning and adaptation (e.g.,

Johnson & Wilbrecht, 2011; Jolles & Crone, 2012; Crone & Steinbeis, 2017; McCormick &

Telzer, 2017a).

A major challenge in modeling experience and development simultaneously is that in real

data, they are often confounded (Bell, 1953; Jolles & Crone, 2012; Telzer et al., 2018) in

developmental models. In longitudinal studies which use a cohort-sequential (or panel) design,

where individuals are repeatedly assessed at the same ages, older participants are also more-

experienced participants (both in life and practice in the specific measures of interest). In

neuroimaging contexts, these experience effects can confound developmental effects in a number

of ways, including reducing anxiety about the scanner environment, changing baseline conditions

(the "task B" problem), or reduce errors on tasks through familiarity rather than change in

underlying ability (Jolles & Crone, 2012; Telzer et al., 2018). Fortunately, we can leverage an

alternative, the accelerated longitudinal design, to address these challenges. In accelerated

longitudinal studies, individuals vary in the age of first assessment and are followed longitudinally

thereafter. By adopting this design, we can de-couple experience from age (or other measure of

developmental stage) sufficiently to successfully model the accumulation of experience and

developmental maturation simultaneously (McCormick, *preprint*).

The current study tests the two competing hypotheses of how experience and development

interact to drive neural plasticity during learning. Participants across a wide age range (8-29 years)

participated in a three-wave, accelerated longitudinal neuroimaging study during which they

completed a feedback learning task. By leveraging the accelerated longitudinal design and a novel

extension of mixed-effects models (McCormick, *preprint*), we differentiate between three

temporal levels of neural plasticity: 1) short-term practice-related changes within a scan session

(within-individual) across blocks of feedback learning; 2) long-term changes within individuals,

across measurement occasions (i.e., waves); and 3) the mixed (i.e., within- and between-

individual) effect of changes associated with age. By considering these three levels in the same

model, we can partition effects at each level. (1) Within-session changes reflect how brain and

behavior adapt during learning the task structure, (2) between-session changes reflect changes due

to experience after repeated exposure to the task and testing environments, (3) while age reflects

the developmental effect. Importantly, including effects at the second level allows us to de-

confound age and experience, giving a more reliable estimate of the developmental effect. Because

learning is an integrative process, involving the interactions between many brain regions (Bassett

et al., 2011; Gerraty et al., 2014; Bassett et al., 2015; McCormick & Telzer, 2017a; Gerraty et al.,

2018; McCormick, Gates, & Telzer, 2019), we test this developmental model in the context of

brain networks. Specifically, we model the interaction of practice, experience, and development

effects on network modularity. Modularity is a measure of the degree of network segregation into

distinct functional units (Bullmore & Bassett, 2011). Higher levels of modularity in brain networks

predicts increased learning (Bassett et al., 2011; Ellefsen et al., 2015) and working memory (Braun

et al., 2015) performance in adults.

Our analytic approach to addressing these questions involved several steps. First, we fit

mixed-effects models with only linear and quadratic effects of age on behavioral performance and

network modularity during learning separately (Peters et al., 2016; Peters & Crone, 2017) for

comparison to more complex models. We then included predictors of within- and between-session

change as main effects to consider the unique effects of practice, experience, and development,

before fitting a model that included interaction terms between our predictors. This third model

allowed us to probe how the effects of the lower-level predictors change across development in a

continuous fashion. Finally, we estimated a brain-as-predictor model where we probed how brain

states (e.g., high versus low modularity) differentially predicted learning performance across

practice, experience, and development. This final model tests a core difference between the two

explanations of developmental improvement in learning performance. In the development-as-

practice view, network modularity should predict learning performance consistently regardless of

when in the developmental trajectory (i.e., there is no moderation by age). This is contrasted by

the interaction view of development and experience, where we would expect that modularity

would predict performance differentially depending on age.

2. Methods

2.1 Sample

A total of 299 participants (ages 8-29 years; 153 female) participated in a 3-wave,

accelerated longitudinal MRI study. Participants were scanned every 2 years, spanning a 5-year

period (Figure 1). At wave 1, 28 participants were excluded for a number of factors including not

completing the MRI session (N=4), excessive movement during the scan session (>3 mm relative

motion in any direction/rotation) (N=22), ADD diagnosis disclosure (N=1), and reported medicine

use (N=1), resulting in a final sample of 271 participants at the initial data collection (140 female;

M_{age}=14.17, SD=3.63, $range$=8.01–25.95 years). At wave 2 (2 years later), 254 participants were

scanned (33 could not be scanned due to braces; 11 declined to return). Of the scanned participants,

an additional 21 were excluded (12 for motion; 2 for preprocessing errors; 5 for T2 artifacts; 1 for

medicine use; 1 for ADD diagnosis), leaving a final sample of 233 participants (121 female;

M_{age}=16.15, SD=3.62, $range$=10.02–26.61 years). During the final wave (2 years later), 243

participants were scanned (11 could not be scanned due to braces; 45 declined to return). Of these,

11 were excluded (3 did not complete MRI session; 4 for motion; 2 for processing errors; 1 for

medicine use; 1 for ADD diagnosis), for a total final sample of 232 participants (121 female;

M_{age}=18.15, *SD*=3.68, *range*=11.94–28.72 years). Across the dataset, 183 participants had data at

all three waves, 78 participants had data at two waves, 31 participants had data at only one wave,

and 7 were excluded at all three waves. A total of 736 scans were included for final data analyses.

When considered at the trail level, these scans yielded 4799 observations for modeling.

IQ scores were measured at the first two waves of data collection, using the WISC-III (for

participants < 16 years; N_{W1} = 195; N_{W2} = 119) or WAIS-III (for participants ≥ 16 years; N_{W1} =

76; N_{W2} = 114). All participants were within the normal range at wave 1 (*M*=109.8, *SD*=10.34,

range=80-142.5) and wave 2 (*M*=108.3, *SD*=10.27, *range*=80-147.5). Further details and the

distributions of the descriptive variables are available in the supplemental material.

189
190   *Figure 1. Structure of repeated measures within the accelerated longitudinal design. Participants are ordered*
191   *in ascending order based on their age at wave 1. Sex is denoted by separate colors.*

192
193   **2.2 Feedback Learning Task**

194   Participants completed a feedback learning task during an fMRI session (Peters et al., 2014;

Peters et al., 2016). On each trial, participants saw a screen with three empty boxes and one (out

of a possible set of three) stimulus underneath (Figure 2). Participants were told that each stimulus

within a given set had a corresponding correct location among the empty boxes and that their goal

on the task was to appropriately sort each stimulus into its location. For each stimulus-location

choice, participants either received positive (a "+" sign) or negative (a "-" sign) feedback based on

their choice. Positive feedback indicated correct stimulus placement, while negative feedback

indicated incorrect placement. Each stimulus within a set associated with a unique,

deterministically correct location. Stimuli within a set were presented in pseudorandom order,

constrained such that no stimulus within a set was present more than twice in a row. After a

maximum of 12 trials per block, or after all three stimuli within a set were correctly placed twice

(indicating that all locations were successfully learned), stimulus sets were swapped out for a new

set with three new stimuli. Participants saw a total of 15 blocks of 3-stimuli sets (for a maximum

possible of 180 trials) at waves 1 and 2, and 10 blocks (maximum possible 120 trials) at wave 3.

Prior to the MRI session, participants practiced three example sets of stimuli. Each trial consisted

of the following: 1) a 500-ms fixation cross, 2) stimulus presentation for 2500 ms while

participants made location decisions, and 3) feedback presentation for 1000 ms. Trials were

separated by intervals jittered based on OptSeq (Dale, 1999), with durations that varied between 0

and 6 s.

Figure 2. During the Feedback Learning task, participants learned the correct placement of each stimuli (e.g., the elephant) through feedback. Participants received either positive or negative feedback on each trial.

2.3 Behavioral Analyses

2.3.1 Task Metrics of Behavior. Our primary metric of task performance was the learning rate participants displayed in forming correct stimulus-location associations. To calculate learning rate, we distinguished between two phases of task performance: the learning and the application phase (Peters et al., 2014; Peters et al., 2016). The learning phase was defined as trials where the correct location for a given stimulus was still unknown, and participants needed to rely on trial-and-error or hypothesis testing to correctly place the stimulus. Trials in the learning phase could result in either positive (indicating a future stay strategy) or negative (prompting a future shift strategy) feedback. In contrast, the application phase was defined as trials where the correct location for the presented stimulus is already known (as established by an earlier learning trial) and participants correctly place that stimulus again. Learning rate was calculated as the proportion of trials in the learning phase where feedback was correctly applied in the following trial involving the same stimulus (either as repeated placement following positive feedback or as altered placement following negative feedback) out of all the trials during the learning phase.

2.3.2 Linear Mixed-Effects Model. To test our developmental/experience interaction model, we fit a linear mixed-effects model to participants' learning rate data. We followed a model-building procedure similar to the one used in previous work in this sample (Peters et al., 2016; Peters & Crone, 2017). This procedure involved a build-up approach where we tested main

effects and then interactions of time to establish the optimal developmental form before bringing

in additional predictors. We fit a random effects ANOVA model with a random intercept which

served as a comparison for subsequent models. For descriptive purposes at the random effects

level, we fit a three level model where blocks were nested within wave and then within person,

however for comparison with future models, we also fit a two level model where wave and age

were included at level 1. To compare across levels of change, we constructed a model using the

lme4 software package through R (version 1.1-21; Bates et al., 2015), where stimulus blocks (N=1-

max 15) and wave (N=1-3) were nested within individual, and age was included as a time-varying

covariate. Because wave (i.e., repeated exposure to the task) was a predictor of interest, we did not

nest with respect to wave since that would result in a variable that acts as both a nesting factor and

linear effect of interest. We included interactions between wave, age, and blocks. To capture more

complex changes in behavior between blocks of the task, we utilized piece-wise regression at level

1 (Flora, 2008; Li et al., 2009), including predictors which model the linear effects across the first

and second half of the task separately. This model resulted in the following equation:

250
251   Reduced Form:
252   *Learning Rate*$_{ij}$

$$
\begin{aligned}
&= \gamma_{00} + \gamma_{10}First\ Half_{ij} + \gamma_{20}Second\ Half_{ij} + \gamma_{30}Wave_{ij} + \gamma_{40}Age_{ij} \\
&+ \gamma_{50}Age_j^2 + \gamma_{60}First\ Half_{ij} * Wave_{ij} + \gamma_{70}Second\ Half_{ij} * Wave_{ij} \\
&+ \gamma_{80}First\ Half_{ij} * Age_{ij} + \gamma_{90}Second\ Half_{ij} * Age_{ij} + \gamma_{100}First\ Half_{ij} \\
&* Age_{ij}^2 + \gamma_{110}Second\ Half_{ij} * Age_{ij}^2 + \gamma_{120}Wave_{ij} * Age_{ij} + \gamma_{130}Wave_{ij} \\
&* Age_{ij}^2 + u_{0j} + r_{ij}
\end{aligned}
$$

258
While previous work has discouraged using wave as a predictor in longitudinal models (instead

using precise age; see Mehta & West, 2000), here we draw a meaningful distinction between wave

and age. We would expect changes in behavior after each subsequent exposure the task

environment (Telzer, et al., 2018), which due to the sampling method in accelerated longitudinal

designs is disassociated with age to some degree because a large age range is represented at each

wave.

2.4 fMRI Data Acquisition and Processing

2.4.1 MRI data acquisition. Scans across all three waves were acquired using the same

Philips 3T MRI scanner, utilizing identical scan settings. The Feedback Learning Task included

T2*-weighted echoplanar images (EPI; slice thickness=2.75mm; 38 slices; sequential acquisition;

TR=2.2sec; TE=30ms; FOV=220 x 220 x 114.68mm). Additionally, structural images were

acquired, including a high-resolution 3D T1-FFE anatomical scan (TR=9.76ms; TE=4.59ms; 140

slices; voxel size=0.875 x 0.875 x 1.2mm; FOV=224 x 177 x 168mm; flip angle=8). Prior to

undergoing the scan procedure, participants were introduced to the scanner environment (e.g.,

space and noises) through a mock scan session.

2.4.2 fMRI data preprocessing and analysis. Preprocessing and analyses utilized a suite

of tools from FSL FMRIBs Software Library (FSL v6.0; https://fsl.fmrib.ox.ac.uk/fsl/), Steps

taken during preprocessing included skull stripping of all images using BET; and slice-to-slice

motion correction of EPI images using MCFLIRT; co-registration in a two-step sequence to the

high-resolution T2-weighted and T1-FFE anatomical images using FLIRT in order to warp them

into the standard stereotactic space defined by the Montreal Neurological Institute (MNI) and the

International Consortium for Brain Mapping; and the application of a 128s high-pass temporal

filter to remove low frequency drift within the time-series.

2.4.3 Nuisance Regressors. Prior to modeling the fMRI data further, we took several steps

to reduce the influence of motion. Motion, as measured by framewise displacement (Power et al.,

2012), was minimal across the sample (mean across participants = 0.12 mm FD; max = 0.77 mm;

average percentage of volumes with > 0.3 mm FD = 4.95%). We also controlled for 8 nuisance

regressors in the GLM and time-series analyses: 6 motion parameters generated during

realignment and the average signal from both the white matter and cerebrospinal fluid masks.

Previous work (see Ciric et al., 2017) has shown that these strategies reduce the influence of motion

on functional connectivity analyses.

2.4.4 Graph Construction. We then utilized a graph theoretical approach to investigate

how networks in the brain changed across levels of practice, experience, and development. Using

a subset of the BigBrain parcellation scheme (Sietzman et al., 2020), an atlas comprised of 300, 5-

mm sphere parcels from cortical and subcortical regions, we extracted functional timeseries data

for each block (15 in total) in order to model changes in network structure across time during the

task. We chose to examine network features between regions with theoretical relevance to task

performance during learning. This resulted in 147 regions including those in the cingulo-opercular

(14), default mode (55), fronto-parietal (27), salience (14), ventral (9) and dorsal (14) attention,

hippocampal (6), and reward (8) sub-networks (for the relevant ROI coordinates on a whole-brain

projection, see Figure S1). Selection of these networks were guided by those regions engaged in

the feedback learning task in previous research (Peters et al., 2016; Peters & Crone, 2016) or

classically engaged during learning and decision-making (Daw & Shohamy, 2008; Sadaghiani &

D'Esposito, 2014; McCormick & Telzer, 2018a; McCormick et al., 2019). This subset was chosen

to balance including enough regions of interest with the challenges of computing whole-brain

networks on relatively short timeseries. Regions were included or excluded as a group based on

their network label (e.g., all fronto-parietal regions were included while all visual regions were

excluded).

To extract, we constructed a task regressor made from the onset and duration of each block

of stimuli convolved with an HRF function. These regressors were multiplied with the entire

timeseries extracted from ROIs in order to give a set of time-series files for each individual at each

wave. Block durations (M = 45.32 s; SD = 3.26; $range$ = 37.27-60.23 s) were comparable to

approaches used in dynamic functional connectivity analyses (approximately 30s; Shirer et al.,

2012; Gonzalez-Castillo et al., 2015). Correlation matrices were constructed by computing the

zero-lag cross-correlation between each ROI. Graph metrics were calculated across a range of

costs (5-20% in 5% increments; Cohen & D'Esposito, 2016). We utilized the standard community

assignment for distinguishing within- versus between-network edges (Sietzman et al., 2020).

2.4.5 Graph Metric. For our measure of brain development, we calculated network

modularity, or the degree to which communities within the brain network are segregated.

Modularity is computed as the relative number of edges between nodes of the same community

compared to the number of total edges within the brain graph. We calculated modularity (Q^*)

using positive and negative weighted edges as:

322
$$Q^* = \frac{1}{2W^+} \sum_{ij} (w_{ij}^+ - e_{ij}^+)\delta(m_i, m_j) - \frac{1}{2W^+ + 2W^-} \sum_{ij} (w_{ij}^- - e_{ij}^-)\delta(m_i, m_j)$$

323
where w^+ is the number of positively weighted edges and w^- is the number of negatively weighted

edges. The e_{ij} term represents the expected number of edges between two nodes i and j, and the

$\delta(m_i, m_j)$ term is 1 if the nodes i and j are in the same module and 0 if they are not in the same

module. Notice that negatively weighted edges are given less influence than positively weighted

edges in computing modularity (Rubinov & Sporns, 2011).

2.5 Developmental Model

We then utilized the same multi-level modeling approach used for the behavior to model

change in brain networks across blocks, waves, and age:

$Modularity_{ij} = \gamma_{00} + \gamma_{10}First\ Half_{ij} + \gamma_{20}Second\ Half_{ij} + \gamma_{30}Wave_{ij} + \gamma_{40}Age_{ij}$

$+ \gamma_{50}Age_j^2 + \gamma_{60}First\ Half_{ij} * Wave_{ij} + \gamma_{70}Second\ Half_{ij} * Wave_{ij}$

$+ \gamma_{80}First\ Half_{ij} * Age_{ij} + \gamma_{90}Second\ Half_{ij} * Age_{ij} + \gamma_{100}First\ Half_{ij}$

$* Age_{ij}^2 + \gamma_{110}Second\ Half_{ij} * Age_{ij}^2 + \gamma_{120}Wave_{ij} * Age_{ij} + \gamma_{130}Wave_{ij}$

$* Age_{ij}^2 + u_{0j} + r_{ij}$

2.6 Probing Interactions.

To better understand potential interaction effects involving age in the models of behavior

and brain, we probed the effects at four distinct ages (Figure 3). Ages were chosen to be evenly

spaced (approximately standard deviation distances within the sample) and roughly correspond to

different developmental periods including early, middle, and late adolescences, as well as young

adulthood (e.g., Shulman et al., 2016). Interaction effects in the model are continuous across the

age range and therefore leverage information across the sample. However, due to lower coverage

of observations at later ages, the simple slope estimates when probing the interaction at these levels

have correspondingly larger standard errors.

349
350 *Figure 3. Probing Interactions with Age. Four distinct ages were chosen to probe interactions with age,*
351 *including during early adolescence (12, [~ -1SD]; red), middle adolescence (16, [~ mean age], green), late*
352 *adolescence (20, [+1SD]; blue), and young adulthood (25, [~ +2SD], purple). Bar height represents the*
353 *proportion of observations at that level. Rug plot hashes (below x-axis) represent individual observations.*
354

355   **3. Results**

3.1 Descriptives and Age-only Growth Models

Before formally fitting models to the data, we assessed descriptives of both learning rate

and network modularity as a function of wave and age (taking the mean of within-session data).

Connected data points represent the same individual across time and waves are labeled with

different colors (Figure 4A & B). As reported earlier (Peters & Crone, 2017), learning rate was

high overall with late adolescents performing near ceiling, and either leveling off or declining for

older participants. Although not constrained in the same way as learning performance at upper

values, neural network modularity appears to increase at earlier ages and declining at later ages

(see Supplemental for formal regions of significance analysis for all models). As our first model

building step, we fit a relatively simple model by including linear and quadratic effects of age to

both learning rate and network modularity. Predicted values of each measure were obtained from

the mixed-effects model (Figure 4C & D; see Table 1), confirming these trends. However, this

simple model neither captures within-session practice-related change, nor does it disaggregate

within-person changes due to experience (i.e., across waves) and between-person changes due to

maturation (i.e., across age). We next formally tested these effects using the developmental

model specified above.

373
Figure 4. Learning (A) and Network Modularity (B) Across Age and Wave. Means of within-session data were
plotted against age to visualize potential time-related trends. Wave number was indicated by color, and data
from the same individual were connected by a solid line. If individuals only contributed data at one timepoint,
data was indicated with a lone point. Linear mixed-effects models that only consider the mixed effect of age
suggest quadratic effects peaking in late adolescence for learning performance (C), and for network modularity
(D). These models fail to consider effects of experience (i.e., wave) and within-session practice effects.
380

3.2 Behavioral Improvements in Learning Performance

We began by fitting an unconditional random effects ANOVA model (i.e., a random

intercept at each level) to determine the distribution of variance across the three levels of the model

(level 1 = within-session; level 2 = waves; level 3 = individual). Results indicated that the majority

of variance in learning rate was between trials within the same scan session (68.7%), an additional

19.3% of the variance was between scan sessions within the same individual (i.e., change across

waves), and the remaining 11.9% variance was accounted for by between-individual differences

in overall learning performance (see Table 2 for full details). However, to establish a baseline for

future models, we also fit a two level random effects ANOVA model where level 1 and 2 are

collapsed (see Table 2).

3.2.1 Separating Effects of Age and Wave. Next, we fit a mixed effects model with fixed

predictors of learning rate at each level to assess the separable effects of age and wave on learning

rate. Importantly, wave and age were sufficiently decoupled in this model (r = .397, *variance*

inflation factor = 1.19, *SE inflation* = 1.08 times), and all predictors were centered. In this model

neither effect of the within-session practice predictors were significant. This suggests that there

was no total systematic change in learning rate within a scan session net the effects of wave and

age, nor was there a significant within-person effect of wave. In other words, neither within-session

practice or between-session experience related to increased performance when accounting for the

age-related change. However, individuals showed significant linear (β = .250, SE = .031, p < .001)

and quadratic (β = -.136, SE = .021, p < .001) effects of age on learning rate. All results are reported

as standardized effects (Table 3). A likelihood ratio test suggests that this model offers an

improvement over the unconditional model (Δ_{AIC} = -158.7; χ^2_{diff} = 168.71, df = 5, p < .001).

3.2.2 Learning Rate Improvements Show Interactions Across Levels of Time. Finally,

we tested the interactive model of learning and development for participants' learning rates. To do

so, we added two-way cross-level interaction terms to the previous model. Three-way interactions

were explored but were not found to be significant and so the model with two-way interactions

was retained. All predictors were centered to create interaction terms which were uncorrelated with

the main effects and to facilitate the interpretation of main effects in the presence of interaction

terms (Aiken & West, 1991). There was a significant positive interaction of wave and the quadratic

effect of age on learning rate (β = .083, *SE* = .021, *p* < .001) such that at each later waves, the

quadratic decreases lessen. To probe this interaction, we plotted mean within-session level

increases in learning rate across age for each wave (Figure 5). Results suggest that without repeated

exposure to the task (i.e., experience) there are predicted decreases in learning performance at

younger ages (red trajectory), but that practice helps compensate and cause performance to level

off instead (green and blue trajectories). The quadratic effect where wave is coded as zero (i.e.,

wave 2) reflects the effects seen in the age-only model and is consistent with prior research (Peters

et al., 2016; Peters & Crone, 2017), however, by including interactions with experience, we show

how that total effect is influenced by repeated exposure to the task (see Table 4 for full details). A

likelihood ratio test suggests that this model offers an improvement over the main-effects only

model (Δ_{AIC} = -22; χ^2_{diff} = 38.03, *df* = 8, *p* < .001). In a follow-up sensitivity analysis, we found

that this pattern of effects held when including IQ as a covariate.

Experience Moderates the Effects of Age on Learning Performance

Figure 5. Increased Experience Impacts Learning Trajectories. Compared with first exposure (red), accumulating experience (green and blue) between waves tended to predict better learning performance at later ages, compensating for expected declines in performance during young adulthood.

3.3 Changes in Network Modularity

Similar to the behavioral analysis, we first fit an unconditional random effects ANOVA model to participants' neural network modularity data. The majority of variance in network modularity was between trials within the same scan session (51.4%), relatively less (15.6%) of the variance was between scan sessions within the same individual (i.e., change across waves), with the remainder (33.0%) accounted for by between-individual differences in network modularity (Table 2).

3.3.1 Separating Effects of Age and Wave. Next, we fit a main-effects only model with predictors including task block, wave, and age. There were linear (β = .285, *SE* = .0.39, *p* < .001) and quadratic (β = -.136, *SE* = .021, *p* < .001) effects of age, such that network modularity tended to increase early in adolescence and level off and decrease across late adolescence and young

adulthood. Additionally, modularity increased across blocks within waves (i.e., practice) across

both halves of the task (first half : β = .088, SE = .013, p < .001; second half: β = .121, SE = .013,

p < .001). There was no independent effect of wave on network modularity. This suggests that

while modularity tends to increase within-session across the task and with older individuals, there

is no independent effect of repeated exposure to the same task environment (Table 3). As expected,

this model offered improvements over the random effects ANOVA model (Δ_{AIC} = -476.3; χ^2_{diff} =

486.3, df = 5, p < .001).

3.3.2 Network Modularity Shows Interactions Across Levels of Time. We next fit the

interactive model of development to the network modularity data. Similar to the model with

learning performance, there was a significant interaction of wave and the quadratic effect of age

on network modularity (β =.057, SE = .018, p = .001; Table 4). When probed (Figure 6A), there

was a similar compensatory pattern to the one seen in learning performance, such that experience

across waves (green and blue) predicted positive shifts in modularity at later ages compared with

the first exposure to the task (red). Interestingly, these differences appear to only emerge during

the transition from adolescence to young adulthood, whereas increased experience does not impact

modularity at younger ages. Furthermore, there was a significant positive interaction of age and

practice in the first half of the task (β = .068, SE = .019, p < .001), such that older individuals

showed more rapid gains in modularity across the first half of the task (Figure 6B). This model

offered continued improvements over the main effects only model (Δ_{AIC} = -18.18; χ^2_{diff} = 34.18,

df = 8, p < .001).

461
462 *Figure 6. Experience and Age Impact Brain Network Organization. A) Accumulating experience (green and*
463 *blue) across waves predicts increased network modularity compared with first exposure (red), however these*
464 *differences only emerge during the transition from adolescence to young adulthood. B) Increased age predicts*
465 *greater positive gains in network modularity across blocks in the first half of the task.*
466

3.3.3 Predicting Learning with Network Modularity. Finally, we tested whether

network modularity predicts learning performance above and beyond the effects of time. To do so,

we entered network modularity and interaction terms between modularity and the time predictors

into the model. In addition to similar effects of the time predictors, this model revealed a significant

positive interaction between network modularity and age (β = .062, *SE* = .023, *p* = .007; Table 5).

Probing this interaction (Figure 7), we plotted the model-implied trajectory of learning rate across

age for individuals who showed relatively low (-1 SD), mean, and relatively high (+1 SD) network

modularity. This showed that individuals who evinced relatively high network modularity (blue

trajectory) tended to show higher learning rates, but only after the transition from adolescence to

young adulthood (see region of significance analysis in Supplement for details). A likelihood ratio

test suggests that including the brain as a predictor increased model fit (Δ_{AIC} = -4.1; χ^2_{diff} = 20.10,

df = 8, *p* = .010).

479
480
481

482
483 *Figure 7. Differential Impacts of Network Modularity on Learning Rate By Age. At earlier ages, increased*
484 *modularity did not predict increased learning, but this relationship emerges following adolescence.*
485
4. Discussion

The contributions of experience versus development can be difficult to tease apart,

especially within a longitudinal sample (Jolles & Crone, 2012; Telzer et al., 2018) because age,

experience, and practice are confounded. To test an interaction model of experience and

development, we utilized a novel longitudinal approach to separate out variability in learning

performance and brain network modularity along different timescales: 1) within-session practice

across blocks of learning, 2) within-person, across-waves, and 3) across age. Briefly, we found

that learning performance tends to improve throughout adolescence and level off into adulthood.

In contrast, network modularity appears to peak around middle adolescence and then shows

declines across young adulthood. However, both of these effects are moderated by the amount of

experience individuals have accumulated across waves, with more experience relating to higher

performance and network modularity during learning. When considering the brain-behavior

relationships, relatively higher modularity predicts better learning performance but only at older

ages, suggesting that the importance of individual differences around developmental trends for

determining behavioral outcomes may depend on timing in development. We discuss each of these

findings in greater detail below.

4.1 Multi-Level Changes in Learning Rate and Brain Networks

Even without probing cross-level interactions, a major advantage of the models employed

here is the separation of variance in the outcome across levels of time. In the current study, we

found that behavioral improvements in learning occur across age, but do not change systematically

across waves or blocks within the task. In contrast, network modularity showed systematic within-

session increases as well as positive age effects, while showing no systematic changes across

waves. While these total effects should be interpreted with caution given the presence of higher-

order interaction effects, they nevertheless highlight an advantage of the growth model employed

here (McCormick, *preprint*). Controlling for the effects of repeated exposure to the task

environment allow us to be more confident that the effects of age are due to maturational forces

rather than comfort or familiarity with the task or scanner environment (Bell, 1953; Jolles & Crone,

2012). Even if these effects are not significant, as is the case here, these models allow us to check

our assumptions about the processes underlying longitudinal change.

4.2 Cross-Level Interactions between Growth at Different Scales

More interestingly, there were significant cross-level interactions between time predictors

in the models for both behavior and brain trajectories. For both outcomes of interest, results

supported the idea of an interactive model of development, where the impacts of experience change

across age. For learning rate, the model recapitulated previous findings in this task (Peters &

Crone, 2017) showing that learning rate reaches peak levels around late adolescence, and is

consistent with other findings showing improvements in learning across adolescence (van

Duijvenvoorde et al., 2008; Peters et al., 2016; McCormick & Telzer, 2017a). This highlights that

the model with growth at multiple levels accommodates the same inferences made with the age-

only models. In this way, adopting the current approach offers advantages without limiting the

inferences made about developmental trajectories. Indeed, the interaction of wave and the

quadratic effect of age on learning performance reveals that changes in behavior are driven by

complex interplays between development and experience, with experience appearing to play

different roles in supporting overall performance across adolescence and young adulthood.

Specifically, probing the interaction shows that increased experience compensates for the main

effect of age, boosting behavioral performance gains further into to young adulthood. Extensive

experience (blue trajectory in Figure 5) blunts otherwise predicted declines and stabilizes

performance at the peak achieved during middle to late adolescence. However, this experience-

related improvement is not universal across the developmental period considered, as mid-

adolescent performance is heightened even at first wave. This might suggest that during

adolescence, learning is universally improved, and then individual differences become more

relevant as individuals transition out of this period (see Pattwell et al., 2011 for a similar idea in

the area of contextual fear during adolescence). None of the models tested showed within-session

effects on learning performance, although we may have been under-powered to detect such effects

given the restraints of the task (i.e., there was a maximum of 12 trials per block regardless of

learning). Overall, these results are a powerful validation of the model, converging with previous

findings on the same data while simultaneously allowing for the addition of more complex time-

dependent relationships.

Findings with the brain showed a distinct pattern of effects from growth in learning

performance. Previous work in this area has shown developmental changes during learning in

regional activation of the fronto-parietal (Peters et al., 2016) and striatal regions (Peters & Crone,

2017; McCormick & Telzer, 2017a), as well as seed-based connectivity with the orbitofrontal

cortex (McCormick & Telzer, 2017a). In the current study, we instead examine changes in brain

network organization during learning. Learning over short periods of time has been shown to alter

neural network organization (Bassett et al., 2011; Telesford et al., 2017; Gerraty et al., 2018), but

these processes have not been compared with long-term changes due to maturation previously. In

the current study, we show changes in network modularity both at the short-term within-session

and long-term developmental level. In the short term, playing repeated blocks within-session is

associated with heightened modularity between brain networks involved in learning, and this effect

across the first half of the task increases with age. This suggests that older individuals are able to

segregate (i.e., high within-network and low between-network connectivity) the relevant networks

of regions to a greater extent than younger participants. The quadratic total effect of age suggests

that rather than a linear increase in modularity across experience across waves and maturation,

network modularity instead decreases at later ages (Figure 6A), with late adolescents and young

adults showing decreasingly modular networks compared with middle-adolescents (also consistent

with the age-only model (Figure 4D). This pattern of network connectivity evolves similarly across

development to striatal activation during learning versus application (Peters & Crone, 2017).

However, the interaction of this age effect with wave shows an analogous effect as seen in learning

performance, where experience appears to blunt expected decreases in network modularity in

young adulthood. While this compensatory effect does not counteract the overall decreases as seen

in the behavioral results, it does serve to shift network organization toward a more adolescent-

typical phenotype. For both behavioral performance and network modularity, the pattern of results

seen here clearly support an interactive view of experience and development, where maturation

constrains the effect of experience rather than simply serving as a form of extended practice.

Regardless of the effects of experience (i.e., wave), there appear to be more substantial

decreases in modularity compared with behavioral performance. In the context of learning and

development, this pattern of long-term change in neural networks might have two potential

explanations. First, it might be that brain networks show the greatest capacity for modularity

during adolescence, and this capacity supports the heightened flexible learning (Johnson &

Wilbrecht, 2011; Casey, 2015) and feedback sensitivity (Peters et al., 2016; van Duijvenvoorde et

al., 2014; McCormick & Telzer, 2017a; b; 2018b) that characterize this developmental period

regardless of practice or exposure effects. Alternatively, these changes might reflect differences in

how the brain performs similar actions across development. For instance, high modularity might

be necessary for adolescents to achieve high performance, while adults might not require this to

the same degree. For instance, stabilizing learning performance with experience is still associated

with overall (albeit blunted) decreases in modularity during young adulthood. This might also be

consistent with an expansion-normalization theory of development and learning (Wenger et al.,

2017) where brains show initial changes in structure and function (e.g., increased synaptic

formation, increased activation) that then return to baseline without compromising behavioral

performance. These hypotheses are not mutually exclusive, and the effects probed here might

suggest both that adolescent brains support improved performance regardless of other influences

(e.g., experience) and that returns to network phenotypes seen in younger adolescents does not

lead to a complete collapse of behavioral performance.

4.3 Changing Brain-Behavior Relationships

While characterizing trajectories of brain and behavior separately is informative, we also

examined whether individual differences in network organization might predict learning

performance above and beyond developmental (Peters & Crone, 2017) and experiential effects, as

well as whether that relationship changed across time. Consistent with the interaction view of

development and experience, significant interactions between network modularity and time

predictors in the model revealed a significant moderation of brain-behavior relationships across

age. This means that in early adolescence, there is no effect of increased modularity on learning

performance, but that increased modularity predicts enhanced learning rates for older individuals.

These findings are consistent with previous work in young adults showing positive associations

between network modularity and successful learning (Bassett et al., 2011; Ellefsen et al., 2015)

and higher-order cognitive processing generally (Kitzbichler et al., 2011; Braun et al., 2015).

However, these positive associations at later ages are particularly interesting in the context of the

developmental trends detected, where older individuals on average show decreased modularity

across waves. Despite normative decreases in network modularity during late adolescence and

young adulthood, individuals with higher modularity show greater learning performance. This

might lend support to the first explanation of the interaction effect of age and wave – that

adolescent-typical neural phenotypes offer advantages in performance (e.g., Johnson & Wilbrecht,

2011; Jones et al., 2014; van Duijvenvoorde et al., 2016). If young adults simply did not need

highly modular networks to perform what is a relatively easy task for them (i.e., the expansion-

renormalization hypothesis), then we would expect that the relationship between modularity and

learning performance would decrease. However, the positive interaction effect (Figure 7) suggests

that older individuals show an even greater dependence on high modularity for successful learning

performance compared with younger participants. This pattern of results presents a compelling

case for adolescent-specific advantages in learning. For older individuals, retaining "immature,"

but apparently more-optimal, network configurations helps boost behavioral performance.

4.4 Conclusions

In summary, we took a novel modeling approach to disaggregate change in learning and

neural networks across different timescales. While we focus on learning here, these results

highlight the potential flexibility of mixed-effects models for probing complex developmental

trajectories in other domains. We found nonlinear patterns of development for both behavior and

brain, which were moderated by experience. Specifically, greater experience with the task across

waves supported increased learning and network modularity relative to comparatively naïve

subjects at later ages, highlighting that these effects can potentially bias age-related inferences

unless explicitly included in longitudinal models. Future research using accelerated longitudinal

designs (or see McCormick, *preprint* for alternatives) should take care to model practice/exposure-

related effects to remove this confound. Finally, we showed changing brain-behavior relationships

across adolescence, where higher network modularity predicts increased learning performance

only following the transition into young-adulthood. These results present compelling support for

an interactive view of experience and development, where changes in the brain impact behavior in

context-specific fashion based on developmental goals (Crone & Dahl, 2012; Romer et al., 2017).

Acknowledgements

Author Contributions: S.P. and E.A.C. designed research, and performed research; E.M.M.,

analyzed data; E.M.M., S.P., E.A.C. & E.H.T. wrote the paper.

This research was funded by a starting grant of the European Research Council (ERC-2010-StG-

263234 awarded to E.A.C.) and a grant from the Netherlands Organization for Scientific Research

(NWO-VICI 453-14-001 awarded to E.A.C.). We would like to thank Laura van der Aar, Sibel

Altikulaç, Neeltje Blankenstein, Barbara Braams, Suzanne van de Groep, Juliette Cassé, Dianne

van der Heide, Jorien van Hoorn, Cédric Koolschijn, Babette Langeveld, Kyra Lubbers, Batsheva

Mannheim, Mara van der Meulen, Rosa Meuwese, Sandy Overgaauw, Jiska Peper, Elisabeth

Schreuders, Merel Schrijver, Jochem Spaans, Marije Stolte, Erik de Water, and Bianca Westhoff

for their help with data collection, Ferdi van de Kamp for help with data analyses, and Anna Van

Duijvenvoorde and Berna Güroğlu for carefully reviewing the manuscript. Finally we would like

to thank all participants and their parents for their collaboration.

E.M.M. was supported in this research by grants from the National Institutes of Health

(R01DA039923, R01 EB022904 awarded to E.H.T.) and generous funds from the University of

North Carolina at Chapel Hill.

The authors declare no competing financial interests.

References

Aiken, L. S., & West, S. G. (1991). *Multiple regression: Testing and interpreting*

interactions. Sage Publications, Inc.

Bassett, D. S., Wymbsb, N. F., Porterc, M. A., Muchae, P. J., Carlsona, J. M., & Graftonb, S. T.

(2011). Dynamic reconfiguration of human brain networks during learning. *Proceedings of the*

National Academy of Sciences, *108*(18), 7641-7646.

Bassett, D. S., Yang, M., Wymbs, N. F., & Grafton, S. T. (2015). Learning-induced autonomy of

sensorimotor systems. *Nature Neuroscience*, *18*(5), 744-751.

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2014). Fitting linear mixed-effects models using

lme4. *Journal of Statistical Software, 67*(1), 1-48.

Bell, R. Q. (1953). Convergence: An accelerated longitudinal approach. *Child Development*, 145-

152.

Blakemore, S. J., & Mills, K. L. (2014). Is adolescence a sensitive period for sociocultural

processing?. *Annual Review of Psychology*, *65*, 187-207.

Braun, U., Schäfer, A., Walter, H., Erk, S., Romanczuk-Seiferth, N., Haddad, L., ... & Meyer-

Lindenberg, A. (2015). Dynamic reconfiguration of frontal brain networks during executive

cognition in humans. *Proceedings of the National Academy of Sciences*, *112*(37), 11678-

11683.

Casey, B. J., Jones, R. M., & Hare, T. A. (2008). The adolescent brain. *Annals of the New York*

Academy of Sciences, *1124*(1), 111-126.

Casey, B. J., Tottenham, N., Liston, C., & Durston, S. (2005). Imaging the developing brain: what

have we learned about cognitive development?. *Trends in Cognitive Sciences*, *9*(3), 104-110.

Ciric, R., Wolf, D. H., Power, J. D., Roalf, D. R., Baum, G. L., Ruparel, K., ... & Gur, R. C. (2017).

Benchmarking of participant-level confound regression strategies for the control of motion

artifact in studies of functional connectivity. *NeuroImage*, *154*, 174-187.

Crone, E. A., & Dahl, R. E. (2012). Understanding adolescence as a period of social–affective

engagement and goal flexibility. *Nature Reviews Neuroscience*, *13*(9), 636-650.

Dale, A. M. (1999). Optimal experimental design for event-related fMRI. *Human Brain*

Mapping, *8*(2-3), 109-114.

Daw, N. D., O'doherty, J. P., Dayan, P., Seymour, B., & Dolan, R. J. (2006). Cortical substrates

for exploratory decisions in humans. *Nature*, *441*(7095), 876-879.

Ellefsen, K. O., Mouret, J. B., & Clune, J. (2015). Neural modularity helps organisms evolve to

learn new skills without forgetting old skills. *PLoS Computational Biology*, *11*(4), e1004128.

Flora, D. B. (2008). Specifying piecewise latent trajectory models for longitudinal data. *Structural*

Equation Modeling, *15*(3), 513-533.

Galván, A. (2010). Neural plasticity of development and learning. *Human Brain Mapping*, *31*(6),

879-890.

Gates, K. M., Henry, T., Steinley, D., & Fair, D. A. (2016). A Monte Carlo evaluation of weighted

community detection algorithms. *Frontiers in Neuroinformatics*, *10*, 45.

Gerraty, R. T., Davidow, J. Y., Foerde, K., Galvan, A., Bassett, D. S., & Shohamy, D. (2018).

Dynamic flexibility in striatal-cortical circuits supports reinforcement learning. *Journal of*

Neuroscience, 2084-17.

Gerraty, R. T., Davidow, J. Y., Wimmer, G. E., Kahn, I., & Shohamy, D. (2014). Transfer of

learning relates to intrinsic connectivity between hippocampus, ventromedial prefrontal cortex,

and large-scale networks. *Journal of Neuroscience*, *34*(34), 11297-11303.

Gogtay, N., Giedd, J. N., Lusk, L., Hayashi, K. M., Greenstein, D., Vaituzis, A. C., ... & Rapoport,

J. L. (2004). Dynamic mapping of human cortical development during childhood through early

adulthood. *Proceedings of the National Academy of Sciences*, *101*(21), 8174-8179.

Gonzalez-Castillo, J., Hoy, C. W., Handwerker, D. A., Robinson, M. E., Buchanan, L. C., Saad,

Z. S., & Bandettini, P. A. (2015). Tracking ongoing cognition in individuals using brief, whole-

brain functional connectivity patterns. *Proceedings of the National Academy of*

Sciences, *112*(28), 8762-8767.

Guimerá, R., & Amaral, L. A. N. (2005a). Cartography of complex networks: modules and

universal roles. *Journal of Statistical Mechanics: Theory and Experiment*, *2005*(02), P02001.

Guimerá, R., & Amaral, L. A. N. (2005b). Functional cartography of complex metabolic

networks. *Nature*, *433*(7028), 895.

Huttenlocher, P. R. (2009). *Neural plasticity: The effects of environment on the development of the*

cerebral cortex. Harvard University Press. Cambridge, MA.

Johnson, C., & Wilbrecht, L. (2011). Juvenile mice show greater flexibility in multiple choice

reversal learning than adults. *Developmental Cognitive Neuroscience*, *1*(4), 540-551.

Karrer, B., Levina, E., & Newman, M. E. (2008). Robustness of community structure in

networks. *Physical Review E*, *77*(4), 046119.

Kitzbichler, M. G., Henson, R. N., Smith, M. L., Nathan, P. J., & Bullmore, E. T. (2011). Cognitive

effort drives workspace configuration of human brain functional networks. *Journal of*

Neuroscience, *31*(22), 8259-8270.

Kolb, B., & Gibb, R. (2011). Brain plasticity and behaviour in the developing brain. *Journal of the*

Canadian Academy of Child and Adolescent Psychiatry, *20*(4), 265.

Li, F., Duncan, T. E., Duncan, S. C., & Hops, H. (2001). Piecewise growth mixture modeling of

adolescent alcohol use data. *Structural Equation Modeling*, *8*(2), 175-204.

Luna, B., Padmanabhan, A., & O'Hearn, K. (2010). What has fMRI told us about the development

of cognitive control through adolescence?. *Brain and Cognition*, *72*(1), 101-113.

McCormick, E. M., & Telzer, E. H. (2017a). Adaptive adolescent flexibility: Neurodevelopmental

of decision-making and learning in a risky context. *Journal of Cognitive Neuroscience*, *29*,

413-423.

McCormick, E. M., & Telzer, E. H. (2017b). Failure to retreat: blunted sensitivity to negative

feedback supports risky behavior in adolescents. *NeuroImage, 147,* 381-389.

McCormick, E. M., & Telzer, E. H. (2018). Not Doomed to Repeat: Enhanced Medial Prefrontal

Cortex Tracking of Errors Promotes Adaptive Behavior during Adolescence. *Journal of*

Cognitive Neuroscience, *30*(3), 281-289.

McCormick, E. M. (*preprint*). Multi-Level Multi-Growth Models: New opportunities for

addressing developmental theory using longitudinal designs.

https://doi.org/10.1101/2020.10.21.349274

Mehta, P. D., & West, S. G. (2000). Putting the individual back into individual growth

curves. *Psychological Methods*, *5*(1), 23.

Mills, K. L., Goddings, A. L., Herting, M. M., Meuwese, R., Blakemore, S. J., Crone, E. A., ... &

Tamnes, C. K. (2016). Structural brain development between childhood and adulthood:

Convergence across four longitudinal samples. *NeuroImage*, *141*, 273-281.

Morrell, C. H., Brant, L. J., & Ferrucci, L. (2009). Model choice can obscure results in longitudinal

studies. *Journals of Gerontology Series A: Biomedical Sciences and Medical Sciences*, *64*(2),

215-222.

Paus, T. (2005). Mapping brain maturation and cognitive development during adolescence. *Trends*

in Cognitive Sciences, *9*(2), 60-68.

Peters, S., & Crone, E. A. (2017). Increased striatal activity in adolescence benefits

learning. *Nature Communications*, *8*(1), 1983.

Peters, S., Braams, B. R., Raijmakers, M. E., Koolschijn, P. C. M., & Crone, E. A. (2014). The

neural coding of feedback learning across child and adolescent development. *Journal of*

Cognitive Neuroscience, *26*(8), 1705-1720.

Peters, S., Van Duijvenvoorde, A. C., Koolschijn, P. C. M., & Crone, E. A. (2016). Longitudinal

development of frontoparietal activity during feedback learning: contributions of age,

performance, working memory and cortical thickness. *Developmental Cognitive*

Neuroscience, *19*, 211-222.

Piaget, J. (1954). The construction of reality in the child. New York: Basic Books.

Pons, P., & Latapy, M. (2006). Computing communities in large networks using random

walks. *Journal of Graph Algorithms and Applications*, *10*(2), 191-218.

Power, J. D., Cohen, A. L., Nelson, S. M., Wig, G. S., Barnes, K. A., Church, J. A., ... & Petersen,

S. E. (2011). Functional network organization of the human brain. *Neuron*, *72*(4), 665-678.

Rubinov, M., & Sporns, O. (2010). Complex network measures of brain connectivity: uses and

interpretations. *NeuroImage*, *52*(3), 1059-1069.

Shirer, W. R., Ryali, S., Rykhlevskaia, E., Menon, V., & Greicius, M. D. (2012). Decoding subject-

driven cognitive states with whole-brain connectivity patterns. *Cerebral Cortex*, *22*(1), 158-

165.

Shulman, E. P., Smith, A. R., Silva, K., Icenogle, G., Duell, N., Chein, J., & Steinberg, L. (2016).

The dual systems model: Review, reappraisal, and reaffirmation. *Developmental Cognitive*

Neuroscience, *17*, 103-117.

Steinberg, L., Albert, D., Cauffman, E., Banich, M., Graham, S., & Woolard, J. (2008). Age

differences in sensation seeking and impulsivity as indexed by behavior and self-report:

evidence for a dual systems model. *Developmental Psychology*, *44*(6), 1764.

Stiles, J., & Jernigan, T. L. (2010). The basics of brain development. *Neuropsychology*

Review, *20*(4), 327-348.

Telesford, Q. K., Ashourvan, A., Wymbs, N. F., Grafton, S. T., Vettel, J. M., & Bassett, D. S.

(2017). Cohesive network reconfiguration accompanies extended training. *Human Brain*

Mapping, *38*(9), 4744-4759.

Telzer, E. H., McCormick, E. M., Peters, S., Cosme, D., Pfeifer, J. H., & van Duijvenvoorde, A.

C. (2018). Methodological considerations for developmental longitudinal fMRI

research. *Developmental Cognitive Neuroscience*, *33*, 149-160.

Van Duijvenvoorde, A. C., Zanolie, K., Rombouts, S. A., Raijmakers, M. E., & Crone, E. A.

(2008). Evaluating the negative or valuing the positive? Neural mechanisms supporting

feedback-based learning across development. *Journal of Neuroscience*, *28*(38), 9495-9503.

Vigilant, L., Roy, J., Bradley, B. J., Stoneking, C. J., Robbins, M. M., & Stoinski, T. S. (2015).

Reproductive competition and inbreeding avoidance in a primate species with habitual female

dispersal. *Behavioral Ecology and Sociobiology*, *69*(7), 1163-1172.

Vygotsky, L. S. (1978). *Mind in society: The development of higher psychological processes* (M.

Cole, V. John-Steiner, S. Scribner & E. Souberman., Eds.) (A. R. Luria, M. Lopez-Morillas &

M. Cole [with J. V. Wertsch], Trans.) Cambridge, Mass.: Harvard University Press. (Original

manuscripts [ca. 1930-1934])

Ward, J. H. (1963). Hierarchical grouping to optimize an objective function. *Journal of the*

American Statistical Association, *58*(301), 236-244.

Wenger, E., Brozzoli, C., Lindenberger, U., & Lövdén, M. (2017). Expansion and renormalization

of human brain structure during skill acquisition. *Trends in Cognitive Sciences*, *21*(12), 930-

939.

Table 1. Model Output from Age-Only Models.

Predictors	Learning Rate				Network Modularity			
	Estimates	*SE*	*P-Value*	*df*	*Estimates*	*SE*	*P-Value*	*df*
Intercept	0.937	0.004	**<0.001**	359.604	0.994	0.011	**<0.001**	361.688
Age $_{std}$	0.277	0.023	**<0.001**	1003.133	0.275	0.023	**<0.001**	1992.711
Age^2 $_{std}$	-0.140	0.021	**<0.001**	1924.892	-0.209	0.020	**<0.001**	3523.698
Random Effects								
σ^2	0.010				0.055			
τ_{00}	0.002 $_{ID}$				0.030 $_{ID}$			
ICC	0.18				0.35			
N	297 $_{ID}$				297 $_{ID}$			
Observations	4799				4799			
Marginal R^2 / Conditional R^2	0.065 / 0.236				0.075 / 0.402			

799   *Note:* All effects rounded to the third decimal place for display purposes. std = standardized effects
800   reported. σ^2 = level 1 random effect. τ_{00} = higher level random effect (effect specified by subscript).
801   ICC = Intraclass correlation. N = number of units at each level.
802

803   Table 2. Model Output from Random Effects ANOVA Models.

3-Level Model	Learning Rate				Network Modularity			
Predictors	*Estimates*	*SE*	*P-Value*	*df*	*Estimates*	*SE*	*P-Value*	*df*
Intercept	0.927	0.003	**<0.001**	256.681	0.949	0.012	**<0.001**	284.150
Random Effects								
σ^2	0.009				0.048			
τ_{00}	0.002 ID:Wave				0.014 ID:Wave			
	0.002 ID				0.030 ID			
ICC	0.31				0.49			
N	297 ID				297 ID			
	3 Wave				3 Wave			
Observations	4799				4799			
Marginal R^2 / Conditional R^2	0.000 / 0.313				0.000 / 0.486			

2-Level Model	Learning Rate				Network Modularity			
Predictors	*Estimates*	*SE*	*P-Value*	*df*	*Estimates*	*SE*	*P-Value*	*df*
Intercept	0.925	0.003	**<0.001**	271.214	0.946	0.012	**<0.001**	289.668
Random Effects								
σ^2	0.010				0.056			
τ_{00}	0.003 ID				0.037 ID			
ICC	0.22				0.40			
N	297 ID				297 ID			
Observations	4799				4799			
Marginal R^2 / Conditional R^2	0.000 / 0.218				0.000 / 0.398			

804   *Note:* All effects rounded to the third decimal place for display purposes. σ^2 = level 1 random
805   effect. τ_{00} = higher level random effect (effect specified by subscript). ICC = Intraclass correlation.
806   N = number of units at each level.
807

808
809 Table 3. Model Output from Main Effects-Only Models.

Predictors	Learning Rate				Network Modularity			
	Estimates	SE	P-Value	df	Estimates	SE	P-Value	df
Intercept	0.927	0.004	**<0.001**	717.508	0.987	0.013	**<0.001**	520.937
First Half $_{std}$	0.025	0.016	0.113	4473.435	0.088	0.013	**<0.001**	4491.297
Second Half $_{std}$	0.022	0.016	0.151	4473.468	0.121	0.013	**<0.001**	4491.319
Wave $_{std}$	0.023	0.018	0.198	1205.547	-0.004	0.019	0.845	694.861
Age $_{std}$	0.250	0.31	**<0.001**	299.628	0.285	0.039	**<0.001**	311.080
Age^2 $_{std}$	-0.136	0.021	**<0.001**	1941.031	-0.209	0.020	**<0.001**	3747.423
Random Effects								
σ^2	0.010				0.051			
τ_{00}	0.002 $_{ID}$				0.030 $_{ID}$			
ICC	0.18				0.37			
N	297 $_{ID}$				297 $_{ID}$			
Observations	4799				4799			
Marginal R^2 / Conditional R^2	0.060 / 0.232				0.112 / 0.441			

810 *Note:* All effects rounded to the third decimal place for display purposes. std = standardized effects
811 reported. σ^2 = level 1 random effect. τ_{00} = higher level random effect (effect specified by subscript).
812 ICC = Intraclass correlation. N = number of units at each level.
813

814   Table 4. Model Output from Interactions Models.

Predictors	Learning Rate				Network Modularity			
	Estimates	SE	P-Value	df	Estimates	SE	P-Value	df
Intercept	0.935	0.005	**<0.001**	768.901	0.997	0.014	**<0.001**	513.739
First Half $_{std}$	-0.007	0.020	0.751	4473.838	0.094	0.017	**<0.001**	4495.715
Second Half $_{std}$	0.021	0.020	0.297	4473.787	0.115	0.017	**<0.001**	4495.776
Wave $_{std}$	0.011	0.031	0.722	3143.488	-0.044	0.029	0.131	1734.974
Age $_{std}$	0.160	0.044	**<0.001**	650.191	0.327	0.049	**<0.001**	471.938
Age^2 $_{std}$	-0.080	0.042	0.053	615.163	-0.261	0.047	**<0.001**	513.285
First Half * Wave $_{std}$	-0.016	0.022	0.469	4484.108	-0.036	0.019	0.058	4508.580
Second Half * Wave $_{std}$	-0.044	0.022	0.048	4484.488	-0.022	0.019	0.244	4508.591
First Half * Age $_{std}$	-0.049	0.022	0.027	4466.136	0.068	0.019	**<0.001**	4482.736
Second Half * Age $_{std}$	0.025	0.022	0.252	4466.143	-0.004	0.019	0.818	4482.736
Wave * Age $_{std}$	-0.038	0.024	0.111	870.145	0.002	0.026	0.947	648.001
First Half * Age^2 $_{std}$	0.047	0.024	0.048	4464.637	-0.027	0.020	0.182	4481.364
Second Half * Age^2 $_{std}$	-0.025	0.024	0.292	4464.630	-0.002	0.020	0.906	4481.360
Wave * Age^2 $_{std}$	0.083	0.021	**<0.001**	4746.733	0.057	0.018	**0.001**	4674.686
Random Effects								
σ^2	0.010				0.051			
τ_{00}	0.002 $_{ID}$				0.030 $_{ID}$			
ICC	0.19				0.37			
N	297 $_{ID}$				297 $_{ID}$			
Observations	4799				4799			
Marginal R^2 / Conditional R^2	0.066 / 0.239				0.126 / 0.449			

815
816   *Note:* All effects rounded to the third decimal place for display purposes. std = standardized effects
817   reported. σ^2 = level 1 random effect. τ_{00} = higher level random effect (effect specified by subscript).
818   ICC = Intraclass correlation. N = number of units at each level.
819

820   Table 5. Model Output from Brain as Predictor of Learning Performance Model.

Predictors	Learning Rate			
	Estimates	SE	P-Value	df
Intercept	0.935	0.005	**<0.001**	794.679
First Half	-0.003	0.021	0.886	4476.805
Second Half	0.006	0.021	0.775	4482.941
Wave	-0.056	0.067	0.401	4670.922
Age	0.174	0.045	**<0.001**	718.911
Age^2	-0.086	0.043	0.046	679.282
First Half * Wave	-0.018	0.022	0.415	4481.722
Second Half * Wave	-0.040	0.022	0.072	4485.072
First Half * Age	-0.054	0.023	0.018	4472.145
Second Half * Age	0.005	0.023	0.822	4502.070
Wave * Age	-0.034	0.025	0.172	987.428
First Half * Age^2	0.044	0.025	0.073	4469.835
Second Half * Age^2	-0.013	0.025	0.604	4483.426
Wave * Age^2	0.076	0.022	**0.001**	4754.347
Modularity	-0.014	0.029	0.627	4764.879
Modularity * First Half	0.006	0.021	0.786	4532.995
Modularity * Second Half	0.044	0.021	0.044	4545.020
Modularity * Wave	0.061	0.061	0.317	4774.206
Modularity * Age	0.062	0.023	**0.007**	4222.697
Modularity * Age^2	-0.004	0.025	0.888	4389.408
Modularity * Wave * Age	0.035	0.021	0.093	4776.952
Modularity * Wave * Age^2	-0.043	0.021	0.041	4724.872

Random Effects

σ^2	0.010
$\tau_{00\ ID}$	0.002
ICC	0.19
N_{ID}	297
Observations	4799
Marginal R^2 / Conditional R^2	0.071 / 0.243

822 *Note:* All effects rounded to the third decimal place for display purposes. std = standardized effects

823 reported. σ^2 = level 1 random effect. τ_{00} = higher level random effect (effect specified by subscript).

824 ICC = Intraclass correlation. N = number of units at each level.