Deep-learning based identification, pose estimation and end-to-end behavior classification for interacting primates and mice in complex environments

Markus Marks[1,3], Jin Qiuhan[1,3], Oliver Sturman[2,3,], Lukas von Ziegler[2,3,], Sepp Kollmorgen[1,3], Wolfger von der Behrens[1,3], Valerio Mante[1,3], Johannes Bohacek[2,3], Mehmet Fatih Yanik[1,3,*]

[1]Institute of Neuroinformatics ETH Zürich and University of Zürich, Switzerland
[2]Institute for Neuroscience, Department of Health Sciences and Technology, Lab of Molecular and Behavioral Neuroscience, ETH Zürich, Switzerland
[3]Neuroscience Center Zurich, ETH Zürich and University of Zürich, Switzerland
[*]correspondence to: yanik@ethz.ch

ABSTRACT

The quantification of behaviors of interest from video data is commonly used to study the effects of pharmacological interventions, genetic alterations, and the function of the brain. Existing approaches lack the capabilities to analyze the behavior of groups of animals in complex environments. We present a novel deep learning architecture for classifying individual and social animal behavior, even in complex environments from raw video frames, whilst requiring no intervention after minimal human supervision. Our behavioral classifier is embedded in a pipeline (SIPEC) to perform segmentation, identification, pose-estimation, and classification of complex behavior all automatically with state-of-the-art performance. SIPEC successfully recognizes multiple behaviors of freely moving individual mice as well as socially interacting non-human primates in 3D, using data only from simple mono-vision cameras in home-cage setups.

Introduction

While the analysis of animal behavior is crucial for systems neuroscience and preclinical assessment of therapies, it remains a highly laborious and error-prone process. Over the last few years, there has been a surge in machine learning tools for behavioral analysis, including segmentation, identification, and pose estimation[1–8]. Although this has been an impressive feat for the field, a key element, the direct recognition of behavior itself has been rarely addressed. Unsupervised analysis of behavior[9–11] can be a powerful tool to capture the diversity of the underlying behavioral patterns, but the results of these methods do not align with human annotations and therefore require subsequent inspection. There have been advances also in the supervised analysis of mouse behavior, using classifiers on top of pose-estimation generated features[12–15] or manually defined features such as ellipses[16]. Sturman et. al.[14] demonstrated that

the classification of mouse behaviors using features generated from pose-estimation algorithms can outperform the behavioral classification performance of commercial systems. Yet, such pose-estimation-based classification of behavior remains a labor-intensive and error-prone process as we show below.

Here, we demonstrate a complementary approach for researchers who seek to automatically identify particular behaviors of interest. Our approach relies on the initial annotation of exemplar behaviors, i.e. snippets of video footage. These video snippets are subsequently used to train a Deep Neural Network (DNN) to subsequently recognize such particular behaviors in arbitrarily long videos and complex environments. To achieve this, we designed a novel end-to-end DNN architecture, called SIPEC:BehaveNet which significantly outperforms a pose-estimation-based approach[14] tested on a well-annotated mouse dataset. In addition to this behavioral classification network, we developed the first all-inclusive pipeline, called SIPEC, with modules for segmentation (SIPEC:SegNet), identification (SIPEC:IdNet), behavioral classification (SIPEC:BehaveNet), and pose estimation (SIPEC:PoseNet) of multiple and interacting animals in complex environments. This pipeline utilizes four DNNs operating directly on videos, which are developed and optimized for analyzing animal behavior and provide state-of-the-art performance. We use this pipeline to classify, for the first time, social interactions in home-caged primates from raw video frames and without needing to use any pose estimation.

SIPEC:SegNet is a Mask R-CNN architecture[17], which is optimized to robustly segment animals despite occlusions, multiple scales, and rapid movement, and enables tracking of animal identities within a session. SIPEC:IdNet has a DenseNet[18] backbone, that yields visual features, that are integrated over time through a gated-recurrent-unit network (GRU[19,20]) to re-identify animals when temporal-continuity-based tracking does not work, for example when animals enter or exit a scene. This enables SIPEC to identify primates across weeks and to outperform the identification module of idtracker.ai[3] both within session and across sessions (see also Discussion). SIPEC:PoseNet performs top-down multi-animal pose estimation which we compared to DeepLabCut (DLC)[1]. SIPEC:BehaveNet uses an Xception[21] like network in combination with a temporal convolution network (TCN)[22,23] to classify behavioral events end-to-end. To rapidly train our modules, we use image augmentation[24] as well as transfer-learning[25], optimized specifically for each module. SIPEC enables researchers to identify behaviors of multiple animals in complex and changing environments over multiple days in 3D space, even from a single camera with relatively little labeling in contrast to other approaches that use heavily equipped environments and large amounts of labeled data[7].

To accelerate the reusability of SIPEC, we share the network weights among all four modules for mice and primates, which can be directly used for analyzing new animals in similar environments without further training, or serve as pre-trained networks to accelerate training of networks in different environments.

Results

Our algorithm performs segmentation (SIPEC:SegNet) followed by identification (SIPEC:IdNet), behavioral classification (SIPEC:BehaveNet) and finally pose estimation (SIPEC:PoseNet) from video frames (Fig. 1). These four artificial neural networks, trained for different purposes, can also be used individually or combined in different ways (Fig. 1a). To illustrate the utility of this feature, Fig. 1b shows the output of pipelining SIPEC:SegNet and SIPEC:IdNet to track the identity and location of 4 primates housed together (Fig. 1b). Similarly, Fig. 1c shows the output of pipelining SIPEC:SegNet and SIPEC:PoseNet to do multi-animal pose estimation in a group of 4 mice.

Segmentation module SIPEC:SegNet. SIPEC:SegNet (see Methods, Supp. Fig. 13) is based on the Mask-RCNN architecture[17], which we optimized for analyzing multiple animals and integrated into SIPEC. We further applied transfer learning[25] onto the weights of the Mask-RCNN ResNet-backbone[26] pretrained on the Microsoft Common Objects in Context (COCO dataset)[27] (see Methods for SIPEC:SegNet architecture and training). Moreover, we applied image augmentation[24] to increase generalizability and invariances, i.e. rotational invariance. For a given image, if we assume that N individuals (with N the total number of animals or less) are in the field of view (FOV), the output of SIPEC:SegNet are N segmentations or masks of the image. If the analysis is for multiple animals in a group, this step is mandatory, since subsequent parts of the pipeline are applied to the individual animals. Based on the masks, the center of masses (COMs) of the individual animals is calculated and serves as a proxy for the animals' 2D spatial positions. Next, we crop the original image around the COMs of each animal, thus reducing the original frame to N COMs and N square-masked cutouts of the individuals. This output can then be passed onto other modules.

Segmentation performance on individual mice and groups of 4. We first examined the performance of SIPEC:SegNet on top-view video recordings of individual mice (Supp. Fig. 2), behaving in an open-field test (OFT). 8 mice were freely behaving for 10 minutes in the TSE Multi Conditioning System's OFT arena, previously described in Sturman et al.[14]. We labeled the outlines of mice in a total of 23 frames using the VGG image annotator[28] from videos of randomly selected mice. To evaluate the performance, we used 5-fold cross-validation (CV). We assessed the segmentation performance on images of individual mice, where SIPEC:SegNet achieved a mean-Average Precision (mAP) of 1.0 ± 0 (mean $\pm$ s.e.m., see Methods for metric details). We performed a video-frame ablation study to find out how many labeled frames (outline of the animal, see Supp. Fig. 1) are needed for SIPEC:SegNet to reach peak performance (Supp. Fig. 2). While randomly selecting an increasing amount of training frames, we measured performance using CV. For single-mouse videos, we find that our model achieves 95% of mean peak performance (mAP of 0.95 ± 0.05) using as few as a total of 3 labeled frames for training. To the existing 23 labeled single-mouse frames, we added 57 labeled 4-plex frames, adding to a total of 80 labeled frames. Evaluated on a 5-fold CV, SIPEC:SegNet achieves an mAP of 0.97 ± 0.03 (Fig. 2b). For segmentation in groups of 4 mice, we performed an ablation study as well and found that SIPEC:SegNet achieves better than 95% of the mean peak performance (mAP of 0.94 ± 0.05) using as few as only 16 labeled frames. To assess the

overlap between prediction and ground truth, we report IoU and dice coefficient metrics as well (Fig. 2b).

Segmentation performance of groups of primates. To test SIPEC:SegNet for detecting instances of primates within a group, we annotated 191 frames from videos on different days (Day 1, Day 9, Day 16, Day 18). As exemplified in Fig. 2a, the network handles even difficult scenarios very well: representative illustrations include ground-truth as well as predictions of moments in which multiple primates are moving rapidly while strongly occluded at varying distances from the camera. SIPEC:SegNet achieved a mAP of 0.91 ± 0.03 (mean $\pm$ s.e.m.) using 5-fold CV. When we performed the previously described ablation study, SIPEC:SegNet achieved 95% of mean peak performance (mAP of 0.87 ± 0.03) with only 30 labeled frames (Fig. 2b). To assess the overlap between prediction and ground truth, we report IoU and dice coefficient metrics as well (Fig. 2c).

Pose estimation module SIPEC:PoseNet. We also added a pose estimation network, build on an encoder-decoder architecture[29] with an EfficientNet[41] backbone, to SIPEC for performing pose estimation (SIPEC:PoseNet) (see Methods, Supp. Fig. 12). SIPEC:PoseNet can be used to perform pose estimation on N animals (with N the total number of animals or less), yielding K different coordinates for previously defined landmarks on the body of each animal. The main advantage of SIPEC:PoseNet in comparison to previous approaches is that it receives its inputs from SIPEC:SegNet (top-down pose estimation): While bottom-up approaches such as DLC[1] require grouping of pose estimates to individuals, our top-down approach makes the assignment of pose estimates to individual animals trivial, as inference is performed on the masked image of an individual animal and pose estimates within that mask are assigned to that particular individual (Fig. 1c). We labeled frames with 13 standardized body parts of individual mice in an OFT similarly to Sturman et. al.[14] to train and test the performance of SIPEC:PoseNet against that of DLC[1]. SIPEC:PoseNet achieves a Root-Mean-Squared-Error (RMSE) (see Methods) of 2.9 pixels in mice (Fig. 2d) for a total of 96 labeled training frames, while DLC[1] achieves a 3.9 pixel RMSE[1]. Instead of our top-down pose estimation framework, previously published pose estimation methods for single animals, can also be easily substituted into our pipeline to perform multi-animal pose estimation in conjunction with SIPEC:SegNet.

Identification module SIPEC:IdNet. The identification network (SIPEC:IdNet) (see Methods, Supp. Fig. 11) allows the determination of the identity of individual animals. Given SIPEC:IdNet receives input as a series (T time points) of cropped images of N (with N the total number of animals or less) individuals from SIPEC:SegNet, the output of SIPEC:IdNet are N identities. The input images from SIPEC:SegNet are scaled to the same average size (see Methods) before being fed into SIPEC:IdNet. We designed a feedforward classification neural network, which utilizes a DenseNet[18]-backbone pretrained on ImageNet[30]. This network serves as a feature-recognition network on single frames. We then utilize past and future frames by dilating the mask around the animal with each timestep. The outputs of the feature-recognition network on these frames are then integrated over T timesteps using a GRU (see Methods for architecture and training details). Based on the accuracy and speed requirements of a particular application, SIPEC:IdNet can integrate information from none to many temporally-neighboring frames. We developed an annotation tool for a human to assign identities of individual animals,

in a multi-animal context, to segmentation masks in videoframes, which capture primates from different perspectives (Supp. Fig. 3). This tool was used for annotating identification data in the following sections. Below we compared SIPEC:IdNet's performance to that of the current state-of-the-art i.e. the identification module of idTracker.ai[3]. idTracker.ai[3] is an unsupervised algorithm for tracking the identity of individual animals within a single session. Particularly in complex or enriched home-cage environments, where animals are frequently obstructed as they move underneath/behind objects or enter/exit the scene, temporally based tracking as idtracker.ai performs it becomes impossible, which causes failure of identification of the animals for the rest of the session. We evaluated the identification performance of SIPEC:IdNet across sessions with the identification module of idTracker.ai, providing each network with identical training and testing data. While idtracker.ai behaves like unsupervised (until catastrophic errors occur: see Discussion), the identification module it uses to distinguish animals is trained with the labels generated by idTracker.ai's cascade algorithm in a supervised fashion. Apart from re-identifying animals across sessions using SIPEC:IdNet, SIPEC:SegNet segmentation masks can be used via greedy-mask matching (see Methods) to temporally track the identities of animals as well (Supp. Videos 2-3) or to smooth the outputs of SIPEC:IdNet as a secondary step, that can boost performance for continuous video sequences, but this advantage was not used in the following evaluations for mice and primates.

Identification of mice in an open-field test. We first evaluated the performance of SIPEC:IdNet in identifying 8 individual mice. We acquired 10-minute-long videos of these mice behaving in the previously mentioned OFT (see Methods for details). While for the human observer, these mice are difficult to distinguish (Supp. Fig. 4), our network copes rather well. We used 5-fold CV to evaluate the performance, i.e. splitting the 10-minute videos into 2-minute long ones, while using one fold for testing and the rest to train the network Since this data is balanced, we use the accuracy metric for evaluation. We find that SIPEC:IdNet achieves 99 ± 0.5 % (mean and s.e.m.) accuracy, while the current state of the art idTracker.ai[3] only achieves 87 ± 0.2 % accuracy (Fig. 2e). The ablation study shows that only 650 labeled frames (frame and identity of the animal) are sufficient for the SIPEC:IdNet to achieve 95% of its mean peak performance (Fig. 2f). We tested how this performance translates to identifying the same animals during the subsequent days (Supp. Fig. 5). We find that identification performance is similarly high on the second day 86 ± 2 %, using the network trained on day 1. Subsequently, we tested identification robustness with respect to the interventions on day 3. Following a forced swim test, the identification performance of SIPEC:IdNet, trained on data of day 1, dropped dramatically to 4 ± 2 %, indicating that features utilized by the network to identify the mice are not robust to this type of intervention.

Identification of individual primates in a group. To evaluate SIPEC:IdNet's performance on the identification of individual primates within a group, we used the SIPEC:SegNet-processed videos of the 4 macaques (see Section "Segmentation performance of groups of primates"). We annotated frames from 7 videos taken on different days, with each frame containing multiple individuals, yielding approximately 2200 labels. We used leave-one-out CV with respect to the videos in order to test SIPEC:IdNet generalization across days. Across sessions SIPEC:IdNet reaches an accuracy of 78 ± 3 % (mean ± s.e.m.) while idTracker.ai[3] achieves only 33 ± 3 % (Fig. 2e), where the human expert (i.e. ground truth) had the advantage of seeing all the video frames and the entire cage (i.e. the rest of the primates). We did a separate evaluation of the identification performance on "typical frames" i.e. where the human expert can also correctly identify the primates using single frames. In this case, SIPEC:IdNet achieved a performance of 86 ± 3 (Supp. Fig. 6). The identification labels can then be further enhanced by greedy mask-match based tracking (see Methods for details). Supp. Video 1 illustrates the resulting performance on a representative video snippet. We perform here an ablation study as well, which yields 95% of mean peak performance at 1504 annotated training samples (Fig. 2g).

Behavioral classification module SIPEC:BehaveNet. SIPEC:BehaveNet (see Methods, Supp. Fig. (see Methods, Supp. Fig. 14) offers researchers a powerful means to recognize specific animal behaviors in an end-to-end fashion within a single neuronal net framework. SIPEC:BehaveNet uses video frames of N individuals over T time steps to classify what actions the animals are performing. We use a recognition network to extract features from the analysis of single frames, that we base on the Xception[21] network architecture. We initialize parts of the network with ImageNet[4] weights. These features are then integrated over time by a TCN[22,23] to classify the behavior of the animal in each frame (see Methods for architecture and training details).

SIPEC end-to-end behavior recognition outperforms DLC-based approach. We compare our end-to-end approach to Sturman et al.[14], who recently demonstrated that they can classify behavior based on DLC[1] generated features. On top of a higher classification performance with fewer labels, SIPEC:BehaveNet does not require annotation and training for pose estimation, if the researcher is interested in behavioral classification alone. The increased performance with fewer labels comes at the cost of a higher computational demand since we increased the dimensionality of the input data by several orders of magnitude (12 pose estimates vs. 16384 pixels). To test our performance we used the data and labels from Sturman et al.[14] of 20 freely behaving mice in an OFT. The behavior of these mice was independently annotated by 3 different researchers on a frame-by-frame basis using the VGG video annotation tool[28]. Annotations included the following behaviors: supported rears, unsupported rears, grooming and none (unlabeled default class). While Sturman et al.[14] evaluated the performance of their behavioral event detection by averaging across chunks of time, evaluating the frame-by-frame performance is more suitable for testing the actual network performance since it was trained the same way. Doing such frame-by-frame analysis shows that SIPEC:BehaveNet has fewer false positives as well as false negatives with respect to the DLC-based approach of Sturman et al. We illustrate a representative example of the performance of both approaches for each of the behaviors with their respective ground truths (Fig. 3a). We further resolved spatially the

events that were misclassified by Sturman et al., that were correctly classified by SIPEC:BehaveNet and vice versa (Fig. 3b). We calculated the percentage of mismatches, that occurred in the center or the surrounding area. For grooming events mismatches of Sturman et al.[14] and SIPEC:BehaveNet occurs similarly often in the center 41 ± 12 % (mean and s.e.m.) and 42 ± 12 % respectively. For supported and unsupported rearing events Sturman et al.[14] find more mismatches occurring in the center compared to SIPEC:BehaveNet (supported rears: 40 ± 4 % and 37 ± 6 %, unsupported rears: 12 ± 2 % and 7 ± 2 %). This indicates that the misclassifications of the pose estimation based approach are more biased towards the center than the ones of SIPEC:BehavNet. To quantify the behavioral classification over the whole timecourse of all videos of 20 mice, we used leave-one-out CV (Fig. 3c). We used macro-averaged F1-score as a common metric to evaluate a multi-class classification task and Pearson correlation (see Methods for metrics) to indicate the linear relationship between the ground truth and the estimate over time. For the unsupported rears/grooming/supported rears behaviors SIPEC:BehaveNet achieves F1-Scores of $0.6 \pm 0.16 / 0.49 \pm 0.21 / 0.84 \pm 0.04$ (values reported as mean $\pm$ s.e.m.) respectively, while the performance of the manually intensive Sturman et al.[14]'s approach reaches only $0.49 \pm 0.11 / 0.37 \pm 0.2 / 0.84 \pm 0.03$, leading to a significantly higher performance of SIPEC:BehaveNet for the unsupported rearing (F1: $p=1.689 \times 10^{-7}$, Wilcoxon paired-test was used as recommended[31]) as well as the grooming (F1: $p=6.226 \times 10^{-4}$) behaviors. While we see a higher precision only in the classification of supported rears in the DLC-based approach, SIPEC:BehaveNet has an improved recall for the supported rears as well as improved precision and recall for the other behaviors (Supp. Fig. 7a). As expected, more stereotyped behaviors with many labels like supported rears yield higher F1, while less stereotypical behaviors like grooming with fewer labels have lower F1 for both SIPEC:BehaveNet and the DLC-based approach. Additionally, we computed the mentioned metrics on a dataset with shuffled labels to indicate chance performance for each metric as well as computed each metric when tested across human annotators to indicate an upper limit for frame-by-frame behavioral classification performance (Supp. Fig. 7b). While the overall human-to-human F1 is 0.79 ± 0.07 (mean $\pm$ s.e.m.), SIPEC:BehaveNet classifies with an F1 of 0.71 ± 0.07. As Sturman et al.[14] demonstrated for unsupported and supported rears, this frame-by-frame performance we achieved is sufficient to reach human-like performance, when behavioral classifications are temporally smoothed and grouped to single events rather than analyzed frame-by-frame. Such identification and counting of specific behaviors per video are indeed commonly used to compare the number of occurrences of behaviors across experimental groups. Using such analysis, Sturman et al. reach a correlation of 0.95 to human event-counts which outperforms commonly used commercial systems. Moreover, we also tested combining the outputs of pose estimation-based classification together with the end-to-end model (Combined Model in Methods, Supp. Fig. 7). Lastly, we performed a frame ablation study and showed that SIPEC:BehaveNet needs only 114 minutes, less than 2 hours, of labeled data to reach peak performance in behavior classification (Fig. 3d).

Socially interacting primate behavior classification. We used the combined outputs of SIPEC:SegNet and SIPEC:IdNet, smoothed by greedy match based tracking, to generate videos of individual primates over time (see Methods for details). To detect social events, we used SIPEC:SegNet to generate additional video events covering "***pairs***" of primates.

Whenever masks of individual primates came sufficiently close (see Methods), an interaction event was detected. We were able to rapidly annotate these videos again using the VGG video annotation tool[28] (overall 80 minutes of video are annotated from 3 videos, including the individual behaviors of object interaction, searching, **social grooming** and none (background class)). We then trained SIPEC:BehaveNet to classify frames of individuals as well as merged frames of pairs of primates socially interacting over time. We used grouped 5-fold stratified CV over all annotated video frames, with labeled videos being the groups. Overall SIPEC:BehaveNet achieved a macro-F1 of 0.72 ± 0.07 (mean $\pm$ s.e.m.) across all behaviors (Fig. 4a). This performance is similar to the earlier mentioned mouse behavioral classification performance. The increased variance compared to the classification of mouse behavior is expected as imaging conditions, as previously mentioned, are much more challenging and primate behaviors are much less stereotyped compared to mouse behaviors.

Tracking identity and position of individual primates among groups in 3D without stereovision. By performing SIPEC:SegNet and SIPEC:IdNet inference on a full one-hour video, we easily built a density map of positions of individuals within the husbandry (Fig. 1a). With a single camera without stereovision, one cannot optically acquire depth information. Instead, we used the output masks of SIPEC:SegNet and annotated the position of the primates in 300 frames using a 3D model (Supp. Fig. 9). Subsequently, we generated 6 features using Isomap[32] and trained a multivariate linear regression model to predict the 3D positions of the primates (Fig. 4b). Using 10-fold CV, our predicted positions using only single camera have an overall RMSE of only 0.43 ± 0.01 m (mean $\pm$ s.e.m.), that is of 0.27 ± 0.01 m in x-direction or 6% error w.r.t the room dimension in x-direction; 0.26 ± 0.01 m / 7% and 0.21 ± 0.01 m / 7% for the y and z coordinates respectively.

Discussion

We have presented SIPEC, a novel pipeline, using specialized deep neural networks to perform segmentation, identification, behavioral classification, and pose estimation on multiple animals. With SIPEC we address multiple key challenges in the domain of behavioral analysis. Our **SIPEC:SegNet** enables the segmentation of animals with minimal labeling. In combination with greedy-mask matching, SIPEC:SegNet can be used to track the identities of animals within one session similar to idtracker.ai. Although SIPEC is not unsupervised, SIPEC causes no catastrophic errors unlike idtracker.ai suffers from (see Supp. Videos 2-3). Subsequently, **SIPEC:BehaveNet** enables end-to-end animal behavior recognition directly from raw video data. End-to-end classification has the advantage of not requiring pre-processing adjustments or feature engineering to specific video conditions. Moreover, learning task-relevant features directly from the raw video can lead to better results than pose-estimation based approaches which train a classifier on top of the detected landmarks[11-14]. We demonstrate that our network outperforms such a state-of-the-art pose estimation approach[13] on a well-annotated mouse behavioral dataset. We thus propose to skip pose-estimation if researchers are solely interested in classifying behavior. We note that our end-to-end approach increases the input-dimensionality of the behavioral classification network and therefore uses more

computational resources and is slower than pose-estimation based approaches. **SIPEC:IdNet** identifies primates in complex environments across days with high accuracy, while also offering smoothing of labels in conjunction with SIPEC:SegNet. We demonstrate that identification accuracy is significantly higher than that of the identification module of idtracker.ai. Therefore, the better the coverage by the camera system the better is the overall identification performance. Finally, **SIPEC:PosNet** enables top-down pose estimation of multiple animals in complex environments, making it easy to assign pose estimates to individual animals. All approaches are optimized through augmentation and transfer learning, significantly speeding up learning and reducing labeling in comparison to the other approaches we tested on mouse as well as non-human primate datasets. We demonstrate how SIPEC can analyze social interactions of non-human primates such as mutual grooming over multiple days after annotating sequences of interest in videos. Finally, we show how SIPEC enables 3D vision from a single-camera view, yielding an off-the-shelf solution for home-cage monitoring of primates, without the need for setting stereo-vision setups.

SIPEC can be used to study the behavior of primates and their social interactions over longer periods of time in a naturalistic environment. After initial training of SIPEC modules, they could automatically output a specific behavioral profile of each individual in a group, potentially over days, weeks, or months and therefore also be used to quantify the changes in behavioral and social dynamics over time.

It would be interesting to integrate complementary unsupervised approaches[9,10] into SIPEC to cover behavioral sequences that are not classified by SIPEC:BehaveNet and give researchers the chance to explore the data of these not-specified behaviors in an unsupervised fashion. The output of other modules (SIPEC:SegNet, SIPEC:IdNet and SIPEC:PoseNet) could be used as inputs for these unsupervised approaches to assign results to individual animals.

SIPEC is easy to use for practitioners from the neuroscience community as well as very modular and hackable to encourage future improvements by researchers from the machine learning community. SIPEC can aid neuroscientific research by increasing throughput, reproducibility, and transferability of results of behavioral analysis.

Acknowledgments
This project was funded by the Swiss Federal Institute of Technology (ETH) Zurich and the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation program (grant agreement No 818179), SNSF (CRSII5_198739/1 to MFY; 310030_172889/1 to JB, PP00P3_157539 to VM) ETH Research Grant (ETH-20 19-1 to JB), 3RCC (OC-2019-009 to JB and MFY) , the Simons Foundation (awards 328189 and 543013 to VM) and the Botnar Foundation (to JB). We would like to thank Petra Tornmalm and Victoria de La Rochefoucauld for the annotation of primate data and feedback on primate behavior. We would like to thank Paul Johnson, Baran Yasar, Bifeng Wu, and Aagam Shah for helpful discussions and feedback."

Author contributions

M.M. developed, implemented, and evaluated the SIPEC modules and framework. J.Q. developed segmentation filtering, tracking, and 3D-estimation. M.M., W.B., and M.F.Y. wrote the manuscript. M.M., O.S., LvZ., S.K., W.B., V.M., J.B., and M.F.Y. conceptualized the study. All authors gave feedback on the manuscript.

Competing interests
The authors declare no competing interests.

Fig. 1 | Overview of the SIPEC workflow and modules. a) From a given video, instances of animals are segmented with the segmentation network (SIPEC:SegNet), indicated by masked outline as well as bounding boxes. Subsequently, individuals are identified using the identification network (SIPEC:IdNet). For each individual, the pose and behavior can be estimated/classified using the pose estimation network (SIPEC:PoseNet) and the behavioral identification network (SIPEC:BehaveNet), respectively. b) Outcome of SIPEC:SegNet, and SIPEC:IdNet modules are overlaid on a representative video-frame. Time-lapsed positions of individual primates (center of mass) are plotted as circles with respective colors. c) Outputs of

SIPEC:SegNet (boxes) and SIPEC:PoseNet (colored dots) on a representative videoframe of mouse open-field data.

Fig. 2 | Performance of the segmentation (SIPEC:SegNet), pose estimation (SIPEC:PoseNet), and identification (SIPEC:IdNet) modules under demanding video conditions and using few labels. a) Qualitative comparison of ground truth (top row) versus predicted segmentation masks (bottom row) under challenging conditions; multiple animals, at varying distances from the camera, under strong visual occlusions, and in rapid motions. b) For mice, SIPEC:SegNet performance in mAP (mean average precision), dice (dice coefficient), and IoU (intersection over union) as a function of the number of labels. The lines indicate the means for 5-fold CV while circles, squares, triangles indicate the mAP, dice, and IoU, respectively, for individual folds. c) For primates, SIPEC:SegNet performance in mAP, dice, and IoU as a function of the number of labels. The lines indicate the means for 5-fold CV while circles, squares, triangles indicate the mAP, dice, and IoU, respectively, for individual folds. d) The performance of SIPEC:PoseNet in comparison to DeepLabCut measured as RMSE in pixels on single mouse pose estimation data. e). Comparison of identification accuracy for SIPEC:IdNet module, idtracker.ai[3], and randomly shuffled labels (chance performance). 8 videos from 8 individual mice and 7 videos across 4 different days from 4 group-housed primates are used. All data is represented by mean, showing all points. f) For mice, the accuracy

of SIPEC:IdNet as a function of the number of training labels used. The black lines indicate the mean for 5-fold CV with individual folds displayed. g) For primates, the accuracy of SIPEC:IdNet as a function of the number of training labels used. The black lines indicate the mean for 5-fold CV with individual folds displayed.

Fig. 3 | SIPEC:BehaveNet outperforms pose-estimation (DeepLabCut) based approach (Sturman et al.[14]). a) Comparison of behavioral classification by human annotator (ground truth), SIPEC:BehaveNet, and Sturman et al.[14] b) Errors in the classification of mouse behavior in the open arena for SIPEC:BehaveNet versus Sturman et al. Each colored dot represents a behavioral event that is incorrectly classified by that method (while correctly classified by the other) with respect to the ground truth. none-classified (background class) positions of mice are indicated as grey dots. c) Frame-by-frame classification performance per video (n=20 mice) compared to ground truth. Wilcoxon paired test:* p <= 0.05; *** p <= 0.001; **** p <= 0.0001. d) SIPEC:BehaveNet classification performance as a function of labeled minutes. All data is represented by a Tukey box-and-whisker plot, showing all points.

Fig. 4 | SIPEC can recognize social interactions of multiple primates and infer their 3D positions using a single camera. a) Performance of SIPEC:BehaveNet for individual and social behaviors with respect to ground truth evaluated using grouped 5-fold CV. Behaviors include searching, object interaction and social grooming; while the performance is measured using F1. F1 on shuffled labels is included for comparison. All data is represented by a minimum to maximum box-and-whisker plot, showing all points. b) Evaluation of 3D position estimates of primates in home-cage. Annotated positions (n=300) are marked by black spots while predicted positions are marked as red-hued spots at the end of the solid arrows (color-coded using a red gradient with brighter red indicating higher RMSE of predicted to true position).

Methods

Animals. C57BL/6J (C57BL/6JRj) mice (male, 2.5 months of age) were obtained from Janvier (France). Mice were maintained in a temperature- and humidity-controlled facility on a 12-h reversed light-dark cycle (lights on at 08:15 am) with food and water ad libitum. Mice were housed in groups of 5 per cage and used for experiments when 2.5–4 months old. For each experiment, mice of the same age were used in all experimental groups to rule out confounding effects of age. All tests were conducted during the animals' active (dark) phase from 12–5 pm. Mice were single housed 24 h before behavioral testing in order to standardize their environment and avoid disturbing cage mates during testing. The animal procedures of these studies were approved by the local veterinary authorities of the Canton Zurich, Switzerland, and carried out in accordance with the guidelines published in the European Communities Council Directive of November 24, 1986 (86/609/EEC).

Acquisition of mouse data. For mouse behavioral data and annotation, we refer to Sturman et al.[14]. For each day, we randomized the recording chamber of mice used. On days 1-2, we recorded animals 1-8 individually. On day 3, for measuring the effect of interventions on performance, mice were forced-swim-tested in water for 5 minutes immediately before the recording sessions.

Acquisition of primate data. 4 male rhesus macaques were recorded with a 1080p camera within their home-cage. The large indoor room was about $15m^2$. Videos were acquired using a Bosch Autodome IP starlight 7000 HD camera with 1080p resolution at 50 Hz.

Annotation of segmentation data. To generate training data for segmentation training, we randomly extracted frames of mouse and primate videos using a standard video player. Next, we used the VIA video annotator[28] to draw outlines around the animals.

Generation and annotation of primate behavioral videos. For creating the dataset, 3 primate videos of 20-30 minutes were annotated using the VIA video annotator[28]. These videos were generated by previous outputs of SIPEC:SegNet and SIPEC:IdNet. Frames of primates, that were identified as the same over consecutive frames, were stitched together in order to generate individualized videos. To generate videos of social interactions, we dilated the frames of each primate in each frame and checked if their overlap crossed a threshold, in which case we recalculated the COM of those two masks and center-cropped the frames around them. Labeled behaviors included 'searching', 'object interacting', 'social grooming' and 'none' (background class).

Tracking by segmentation and greedy mask-matching. Based on the outputs of the segmentation masks, we implemented greedy-match-based tracking. For a given frame the bounding box of a given animal is assigned to the bounding box in the previous frame with the largest spatial overlap. The resulting track-identities can be optionally used to smooth the labels that were created by SIPEC:IdNet.

Identification labeling with the SIPEC toolbox. As part of SIPEC we release a GUI that allows to label for identification when multiple animals are present (Supp. Fig. 4). For that SIPEC:SegNet has to be trained and inference has to be performed on videos to be identity labeled. SIPEC:SegNet results can then be loaded from the GUI and overlaid with the original videos. Each box then marks an instance of the species that is to be labeled in green. For each animal, a number on the keyboard can be defined, which corresponds to the permanent ID of the animal. This keyboard number is then pressed and the mask-focus jumps to the next mask until all masks in that frame are annotated. Subsequently, the GUI jumps to the next frame in either regular intervals or randomly throughout the video, as predefined by the user. Once a predefined number of masks is reached, results are saved and the GUI is closed.

SIPEC:SegNet network architecture and training. SIPEC:SegNet was designed by optimizing the Mask R-CNN architecture. We utilized a ResNet101 and feature pyramid network (FPN)[33] as the basis of a convolutional backbone architecture. These features were fed to the region proposal network (RPN), which applies convolutions onto these feature maps and proposes regions of interest (ROIs). Subsequently, these are passed to a ROIAlign layer, which performs feature pooling, while preserving the pixel-correspondence in the original image. Per level of this pyramidal ROIAlign layer, we assign a ROI feature map from the different layers of the FPN feature maps. Now multiple outputs are generated from the FPN, one of which is classifying if an animal is identified. The regressor head of the FPN returns bounding-box regression offsets per ROI. Another fully convolutional layer, followed by a per-pixel sigmoid activation, performs the mask prediction, returning a binary mask for each animal ROI. The network is trained using stochastic gradient descent, minimizing a multi-task loss for each ROI:

$$L = L_{mask} + L_{regression} + L_{class}$$

where L_{mask} is the average binary cross-entropy between predicted and ground truth segmentation mask, applied to each ROI. $L_{regression}$ is a regression loss function applied to the coordinates of the bounding boxes, modified to be outlier robust as in the original Fast R-CNN paper[34]. L_{class} is calculated for each of the proposed ROIs (or anchors) as a logarithmic loss of non-animal vs animal. The learning rate was adapted by an animal specific schedule and training was done iteratively, by first training the output layers for some epochs and then incrementally including previous blocks in the training process. SIPEC:SegNet outputs segmentation masks and bounding boxes to create cutouts or masked cutouts of individual animals to be used by one of the downstream modules.

SIPEC:IdNet network architecture and training. SIPEC:IdNet was based on the DenseNet architecture[18] for frame-by-frame identification. It consists of 4 dense blocks, which consist of multiple sequences of a batch normalization layer, a ReLU activation, and a convolution. The resulting feature maps are concatenated to the outputs of the following sequences of layers (skip-connections). The resulting blocks are connected through transitions, that are convolutional followed by pooling layers. After the last dense block, there is an average pooling layer that we connect to a Dropout[35] layer with a dropout rate of 0.5 followed by the softmax classification layer. For the recurrent SIPEC:IdNet, we remove the softmax layer and feed the

output of the average pooling layers for each time point into a batch normalization layer[36] followed by 3 layers of bidirectional gated recurrent units[19,20] with leaky ReLU activation[37,38] (alpha=0.3) followed by a 0.2 Dropout[35] followed by the softmax layer. The input for SIPEC:IdNet is the output cutouts of individuals, generated by SIPEC:SegNet (for the single-animal case background-subtracted thresholding and centered-cropping would also work). For the recurrent case, the masks of past or future frames are dilated with a factor that increases with distance in time in order to increase the field of view. We pre-trained first the not-recurrent version of SIPEC:IdNet using Adam[39] with an lr=0.00025, a batch size of 16 and using a weighted cross-entropy loss. We used a learning rate scheduler in the following form:

$$L_{E+1} = \frac{L_E}{k^E} \quad (2)$$

where E stands for epoch, using a k=1.5. Subsequently, we removed the softmax layer and fixed the weights of the network. We then trained the recurrent SIPEC:IdNet again using Adam[39] and an lr=0.00005, k=1.25 and a batch size of 6.

SIPEC:BehaveNet network architecture and training. SIPEC:BehaveNet was constructed as an end-to-end action recognition network. It consists of a feature recognition network that operates on a single frame basis and a network, which integrates these features over time (Supp. Fig. 2). The feature recognition network (FRN) is based on the Xception[21] architecture, which consists of an entry flow, a middle flow, and an exit flow. The entry flow initially processes the input with convolution and ReLU blocks. Subsequently, we pass the feature maps through 3 blocks of separable convolution layers, followed by ReLU, separable convolution, and a max-pooling layer. The outputs of these 3 blocks are convolved and concatenated, and passed to the middle flow. The middle flow consists of 8 blocks of ReLU layers followed by a separable convolution layer. The Exit receives the feature maps from the middle flow and passes it one more entry-flow like block, followed by twice with separable convolution and ReLU units. Finally, these features are integrated by a global average pooling layer and then the softmax output. This FRN was first pre-trained on a frame-by-frame basis using an lr=0.00035, gradient clipping norm of 0.5, and batch size=36 using the Adam[39] optimizer. For mouse data, we reduced the original Xception architecture by the first 17 layers, in order to speed up the computation and reduce overfitting. After training the FRN, the outputting dense and softmax layers were removed and all weights were fixed for further training. The FRN-features were integrated over time by a non-cause Temporal Convolution Network[22]. It is non-causal because, for classification of behavior at timepoint *t,* it integrates features from [*t-n,t+n*] with *n* being the number of timesteps, therefore looking not only backward in time but also forward. In this study, we used an *n* of 10. The FRN features are transformed by multiple TCN blocks of the following form: 1D-Convolution followed by batch normalization, a ReLU activation and spatial dropout. The optimization was performed using Adam[39] as well with a learning rate of 0.0001 and a gradient clipping norm of 0.5, trained with a batch size of 16.

Loss adaptation. To overcome the problem of strong data imbalance (most frames are annotated as 'none', i.e. no labeled behavior), we used a multi-class adaptation technique Focal loss[40], commonly used for object detection, instead for action recognition, to discount the contribution of the background class to the overall loss:

$$L_{focal} = -\alpha(1 - p_t)^\gamma \log p_t$$

We used a gamma = 3.0 and an alpha = 0.5. For evaluation, we used the commonly used *F1* metric to assess multi-class classification performance, while using *Pearson Correlation* to assess temporal correlation.

SIPEC:PoseNet network architecture and training. In combination with SIPEC:SegNet we can perform top-down pose estimation with SIPEC:PoseNet. That means, instead of pose estimation network outputting for one landmark multiple possible outputs, corresponding to different animals, we can first segment different animals and then run SIPEC:PoseNet per animal on its cropped frame. In principle, every architecture can now be run on the cropped animal frame, including DLC[1]. The SIPEC:PoseNet architecture is based on an encoder-decoder design[29]. In particular, we used EfficientNet[41] as a feature detection network for a single frame. Subsequently, these feature maps are deconvolved into heatmaps that regress towards the target location of that landmark. Each deconvolutional layer is followed by a batch normalization layer and a ReLU activation function layer. For processing target images for pose-regression, we convolved pose landmark locations in the image with a 2D Gaussian kernel. Since there were many frames with an incomplete number of labels, we defined a custom cross-entropy-based loss function, which was 0 for non-existing labels.

$$L_{incomplete} = \begin{cases} CrossEntropy \\ 0, if\ labels\ does\ not\ exist \end{cases}$$

Combined Model. To test performance effects of doing a pose-estimation based classification in conjunction with SIPEC:BehaveNet, we pretrained SIPEC:PoseNet (with classification layer on top) as well as SIPEC:BehavNet individually. Subsequently removed the output layers and fixed the weights of the individual networks and trained a joint output model, which combined inputs of each stream followed by a batch normalization layer, a dense layer (64 units), and a ReLU activation layer. The resulting units were concatenated into a joint tensor followed by a batch normalization layer, a dense layer (32 units), and a ReLU activation layer. This layer was followed by a dense layer with 4 units for the 4 behavioral classes and softmax activation function. This combined model was trained using Adam[39] with an lr=0.00075 (See Supp. Fig. 7).

Implementation and Hardware. For all neural network implementations, we used Tensorflow[42] and Keras[43]. Computations were done on either NVIDIA RTX 2080 Ti or V100 GPUs.

3D location labeling. To annotate the 3D location of a primate, we firstly create a precise model of the physical room (Supp. Fig. 9). For a given mask-cutout of a primate, we place an artificial primate at an approximate location in the 3D-model. We can then directly readout the 3D-position of the primate. 300 samples are annotated which altogether cover the most frequent parts of the primate positions.

3D location estimation. To regress the animal positions in 3D, we trained a manifold embedding using Isomap[32] using the mask size (normalized sum of positively classified pixels), the x and y pixel positions and their pairwise multiplications as features. We used the resulting 6 Isomap features, together with the inverse square root of the mask size, mask size and x-y-position in pixel space to train an ordinary least squares regression model to predict the 3D position of the animal.

Metrics used. Abbreviations used: Pearson – Pearson Correlation, RMSE – Root mean squared error, IoU – intersection over union, mAP – mean average precision, dice – dice coefficient.

$$Pearson_{xy} = \frac{\sum_{i=1}^{n}(x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum_{i=1}^{n}(x_i - \bar{x})^2}\sqrt{\sum_{i=1}^{n}(y_i - \bar{y})^2}}$$

$$RMSE = \sqrt{\frac{\sum_{n=1}^{N}(\hat{y}_n - y_n)^2}{N}}$$

$$precision = \frac{TP}{TP + FP}$$

$$recall = \frac{TP}{TP + FN}$$

Where TP denotes True Positives, FP False Positives, TN True Negatives, and FN False Negatives.

$$F1 = 2 \cdot \frac{precision \cdot recall}{precision + recall}$$

$$IoU(M_{GT}, M_P) = \frac{M_{GT} \cap M_P}{M_{GT} \cup M_P}$$

Where M_{GT} denotes the ground truth mask and M_P the predicted one. We now calculate the mAP for detections with an IoU > 0.5 as follows:

$$mAP = \sum_{n=0}(r_{n+1} - r_n)\, \rho_{interp}(r_{n+1})$$

With

$$\rho_{interp}(r_{n+1}) = \max_{\tilde{r}:\tilde{r} \geq r_{n+1}} \rho(\tilde{r})$$

Where $\rho(r)$ denotes precision measure at a given recall value.

$$dice = \frac{2 * M_{GT} \cap M_P}{|M_{GT}| + |M_P|}$$

Data Availability

Data available upon reasonable request from authors. Exemplary data is available through our github repository.

Code Availability

We provide the code for SIPEC at: https://github.com/SIPEC-Animal-Data-Analysis/SIPEC and the GUI for the identification of animals https://github.com/SIPEC-Animal-Data-Analysis/idtracking_gui.

References

1. Mathis, A. *et al. DeepLabCut: markerless pose estimation of user-defined body parts with deep learning*. (2018).

2. Geuther, B. Q. *et al.* Robust mouse tracking in complex environments using neural networks. *Communications biology* **2**, 124 (2019).

3. Romero-Ferrero, F., Bergomi, M. G., Hinz, R. C., Heras, F. J. & de Polavieja, G. G. idtracker. ai: tracking all individuals in small or large collectives of unmarked animals. *Nature methods* **16**, 179 (2019).

4. Forys, B., Xiao, D., Gupta, P., Boyd, J. D. & Murphy, T. H. Real-time markerless video tracking of body parts in mice using deep neural networks. *bioRxiv* 482349 (2018).

5. Pereira, T. D. *et al.* Fast animal pose estimation using deep neural networks. *Nature methods* **16**, 117 (2019).

6. Graving, J. M. *et al.* DeepPoseKit, a software toolkit for fast and robust animal pose estimation using deep learning. *eLife* **8**, e47994 (2019).

7. Bala, P. C. *et al.* Automated markerless pose estimation in freely moving macaques with OpenMonkeyStudio. *Nature Communications* **11**, 4560 (2020).

8. Günel, S. *et al.* DeepFly3D, a deep learning-based approach for 3D limb and appendage tracking in tethered, adult Drosophila. *eLife* **8**, e48571 (2019).

9. Wiltschko, A. B. *et al.* Mapping sub-second structure in mouse behavior. *Neuron* **88**, 1121–1135 (2015).

10. Hsu, A. I. & Yttri, E. A. *B-SOiD: An Open Source Unsupervised Algorithm for Discovery of Spontaneous Behaviors*. http://biorxiv.org/lookup/doi/10.1101/770271 (2019) doi:10.1101/770271.

11. Berman, G. J., Choi, D. M., Bialek, W. & Shaevitz, J. W. Mapping the stereotyped behaviour of freely moving fruit flies. *Journal of The Royal Society Interface* **11**, 20140672 (2014).

12. Nilsson, S. R. *et al. Simple Behavioral Analysis (SimBA) – an open source toolkit for computer classification of complex social behaviors in experimental animals*. http://biorxiv.org/lookup/doi/10.1101/2020.04.19.049452 (2020) doi:10.1101/2020.04.19.049452.

13. Segalin, C. *et al. The Mouse Action Recognition System (MARS): a software pipeline for automated analysis of social behaviors in mice*. http://biorxiv.org/lookup/doi/10.1101/2020.07.26.222299 (2020) doi:10.1101/2020.07.26.222299.

14. Sturman, O. *et al.* Deep learning-based behavioral analysis reaches human accuracy and is capable of outperforming commercial solutions. *Neuropsychopharmacology* 1–13 (2020) doi:10.1038/s41386-020-0776-y.

15. Nourizonoz, A. *et al.* EthoLoop: automated closed-loop neuroethology in naturalistic environments. *Nature Methods* **17**, 1052–1059 (2020).

16. Kabra, M., Robie, A. A., Rivera-Alba, M., Branson, S. & Branson, K. JAABA: interactive machine learning for automatic annotation of animal behavior. *Nature methods* **10**, 64 (2013).

17. He, K., Gkioxari, G., Dollár, P. & Girshick, R. Mask r-cnn. in *Proceedings of the IEEE international conference on computer vision* 2961–2969 (2017).

18. Huang, G., Liu, Z., Van Der Maaten, L. & Weinberger, K. Q. Densely connected convolutional networks. in *Proceedings of the IEEE conference on computer vision and pattern recognition* 4700–4708 (2017).

19. Cho, K. *et al.* Learning Phrase Representations using RNN Encoder-Decoder for Statistical Machine Translation. *arXiv:1406.1078 [cs, stat]* (2014).

20. Chung, J., Gulcehre, C., Cho, K. & Bengio, Y. Empirical Evaluation of Gated Recurrent Neural Networks on Sequence Modeling. *arXiv:1412.3555 [cs]* (2014).

21. Chollet, F. Xception: Deep learning with depthwise separable convolutions. in *Proceedings of the IEEE conference on computer vision and pattern recognition* 1251–1258 (2017).

22. Oord, A. van den *et al.* Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499* (2016).

23. Bai, S., Kolter, J. Z. & Koltun, V. An empirical evaluation of generic convolutional and recurrent networks for sequence modeling. *arXiv preprint arXiv:1803.01271* (2018).

24. Jung, A. B. *et al. imgaug*. GitHub repository:https://github.com/aleju/imgaug (2020).

25. Yosinski, J., Clune, J., Bengio, Y. & Lipson, H. How transferable are features in deep neural networks? in *Advances in neural information processing systems* 3320–3328 (2014).

26. He, K., Zhang, X., Ren, S. & Sun, J. Deep residual learning for image recognition. in *Proceedings of the IEEE conference on computer vision and pattern recognition* 770–778 (2016).

27. Lin, T.-Y. *et al.* Microsoft coco: Common objects in context. in *European conference on computer vision* 740–755 (Springer, 2014).

28. Dutta, A. & Zisserman, A. The VIA Annotation Software for Images, Audio and Video. in *Proceedings of the 27th ACM International Conference on Multimedia* (ACM, 2019). doi:10.1145/3343031.3350535.

29. Xiao, B., Wu, H. & Wei, Y. Simple Baselines for Human Pose Estimation and Tracking. *arXiv:1804.06208 [cs]* (2018).

30. Krizhevsky, A., Sutskever, I. & Hinton, G. E. Imagenet classification with deep convolutional neural networks. in *Advances in neural information processing systems* 1097–1105 (2012).

31. Demšar, J. Statistical comparisons of classifiers over multiple data sets. *Journal of Machine learning research* **7**, 1–30 (2006).

32. Tenenbaum, J. B. A Global Geometric Framework for Nonlinear Dimensionality Reduction. *Science* **290**, 2319–2323 (2000).

33. Lin, T.-Y. *et al.* Feature Pyramid Networks for Object Detection. in *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)* 936–944 (IEEE, 2017). doi:10.1109/CVPR.2017.106.

34. Girshick, R. Fast R-CNN. in *2015 IEEE International Conference on Computer Vision (ICCV)* 1440–1448 (2015). doi:10.1109/ICCV.2015.169.

35. Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I. & Salakhutdinov, R. Dropout: A Simple Way to Prevent Neural Networks from Overfitting. 30.

36. Ioffe, S. & Szegedy, C. Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift. *arXiv:1502.03167 [cs]* (2015).

37. Maas, A. L., Hannun, A. Y. & Ng, A. Y. Rectifier Nonlinearities Improve Neural Network Acoustic Models. 6.

38. Xu, B., Wang, N., Chen, T. & Li, M. Empirical Evaluation of Rectified Activations in Convolutional Network. *arXiv:1505.00853 [cs, stat]* (2015).

39. Kingma, D. P. & Ba, J. Adam: A Method for Stochastic Optimization. *arXiv:1412.6980 [cs]* (2017).

40. Lin, T.-Y., Goyal, P., Girshick, R., He, K. & Dollár, P. Focal Loss for Dense Object Detection. *arXiv:1708.02002 [cs]* (2018).

41. Tan, M. & Le, Q. V. EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks. *arXiv:1905.11946 [cs, stat]* (2020).

42. Abadi, M. *et al.* TensorFlow: Large-Scale Machine Learning on Heterogeneous Distributed Systems. 19.

43. Chollet, F. *Keras*. GitHub repository:https://github.com/fchollet/keras (2015).

Supplementary

Supplementary Fig. 1 | Segmentation annotation illustration. Exemplary frame of mice in OFT with manually annotated outlines.

Supplementary Fig. 2 | Mouse single segmentation. For mice, SIPEC:SegNet performance in mAP, dice and IoU for single mouse as a function of the number of labels. The lines indicate the means for 5-fold CV while circles, squares, triangles indicate the mAP, dice, and IoU, respectively, for individual folds. All data is represented by mean, showing all points.

Mask: 92
Frame: 244

Charles : 1   p -- display previous mask   . -- change mask to focus on forward
Max : 2   b -- reset view to current mask   , -- change mask to focus on backward
Paul : 3   m -- trigger manual mode on current frame   = -- zoom in
Alan : 4   w -- wrong mask (not a primate)   - -- zoom out
    h -- difficult to annotate (hard to see from current frame)
    t -- too difficult to annotate

Supplementary Fig. 3 | Identification Graphical User Interface. Mask-box results from SIPEC:SegNet is overlaid over frames in blue and can be labeled one by one. The current box to be labeled is in green. A simple keyboard input scheme is provided within the GUI. Names of individuals and the number of masks to be labeled can be set by the user.

Supplementary Fig. 4 | Example frames of the 8 distinct mice.

Supplementary Fig. 5 | Identification performance of mice across days and interventions. Identification accuracy across days for models trained on day 1. While the performance for the day the model is trained on is very high it drops when tested on day 2, but is still significantly above chance level. When tested on day 3, after a forced swim test intervention, the performance drops significantly. All data is represented by mean, showing all points.

a

c

b

Supplementary Fig. 6 | Identification of typical vs difficult frames. a) Very difficult exemplary frames, which are also beyond human single-frame recognition, are excluded for the 'typical' frame evaluation. b) Exemplary frames used for the 'typical' frame analysis. c) Identification performance is significantly higher on 'typical' frames than on all frames. All data is represented by mean, showing all points.

Supplementary Fig. 7 | Additional behavioral evaluation. a) Overall increased F1 score is caused by an increased recall in case of grooming events and precision for unsupported rearing events. b) Comparison of F1 values as well as Pearson Correlation of SIPEC:BehaveNet to human-to-human performance as well as combined model. Using pose estimates in conjunction with end-to-end classification increases precision in comparison with solely end-to-end classification while suffering from a decrease in recall. All data is represented by a Tukey box-and-whisker plot, showing all points.

Supplementary Fig.9 | 3D model used for annotation of primate 3D-location data.

Supplementary Fig.10 | Comparison tracking and identification. a) <u>**Tracking** describes the process of following each individual animal in a group of animals within one session in a given field of view.</u> b) <u>**Identification** describes the ability to identify an individual from a single frame or a few consecutive frames across multiple sessions that could be apart hours, days, or</u>

months. This entails difficulties such as varying lighting conditions, occlusions, changes in the appearance of animals over time.

Supplementary Fig. 11 | SIPEC IdNet Architecture.

SIPEC:PoseNet architecture

EfficientNet backbone

Target probability maps

Deconvolution   BN   ReLU   Gaussian Noise

Supplementary Fig. 12 | SIPEC PoseNet Architecture.

SIPEC:SegNet architecture

Mask

L_{mask}

class

L_{class}

$L_{regression}$

input image   ResNet backbone   feature maps   ROIAlign   bounding box   output

Region Proposal Network

Dense

Sigmoid

Supplementary Fig. 13 | SIPEC SegNet Architecture.

Supplementary Fig. 14 | SIPEC BehaviorNet Architecture.

Supplementary Tab. 1 | Training and inference times
All measures are done with an NVIDIA RTX 2080 Ti and represent average values.

Species	Network	Training (seconds/epoch)	Epochs	Total training (min)	Inference (seconds/frame)
Primate	SegNet	133	100	222	0.4
Primate	IdNet(single frame)	134	10	22	0.35
Primate	IdNet(recurrent)	60	20	20	0.6
Primate	PoseNet	34	900	510	0.07
Primate	BehaveNet(single frame)	15	50	5	0.08
Primate	BehaveNet(recurrent)	190	10	31	0.6

Mouse	SegNet	40	100	67	0.14
Mouse(@100 0 frames)	IdNet(single frame)	432	10	72	0.1
Mouse(@100 0 frames)	IdNet(recurrent)	502	10	83	0.19
Mouse	PoseNet	20	2450	817	0.03
Mouse	BehaveNet(single frame)	547	10	91	0.05
Mouse	BehaveNet(recurrent)	1163	10	194	0.2

Supplementary Video 1 | Illustration of SIPEC:SegNet and SIPEC:IdNet in primate homecage environment.

Short exemplary video of behaving primates in their homecage environment. SIPEC:SegNet is used to mask different primates and SIPEC:IdNetis used to identify them. During obstructions, the identity of a primate can alter but SIPEC:IdNet quickly recovers the correct identity over the next frames, as it becomes more visible and therefore better identifiable.

Supplementary Video 2 | Comparison of SIPEC and idtracker.ai for mice.

Comparison for tracking 4 mice by idtracker.ai (Left) and by SIPEC(Right). We used publicly available data from idtracker.ai (https://drive.google.com/drive/folders/1Vua7zd6VuH6jc-NAd1U5iey4wU5bNrm4) as well as idtracker.ai's publicly available inference results (https://www.youtube.com/watch?v=ANsThSPgBFM) for a tracking comparison. **Left video**: The tracking of idtracker.ai exhibits catastrophic errors where the label of two or more animals get swapped and the error propagates through the rest of the video unless corrected by the user (i.e. thus supervision is required): Because idtracker.ai relies on continuity of animals in the field of view, when such continuity is lost or when the borders separating the animals are unclear (due to occlusions either by other animals or objects), catastrophic errors occur. These errors must be manually corrected, otherwise they propagate indefinitely. **Right Video**: Tracking is performed by SIPEC:SegNet in conjunction with greedy-mask matching to track the identities of animals. SIPEC does not experience catastrophic failures because it does not rely on the continuity of the animals within the field of view (see also Supp. Video 1).

Supplementary Video 3 | Tracking of 4 mice by SIPEC in an open-field test.

The masks generated by SIPEC:SegNet in conjunction with greedy-mask matching are used to robustly track identities of four mice in an open-field test (see Methods).