simplifyEnrichment: an R/Bioconductor package for Clustering and Visualizing Functional Enrichment Results

Zuguang Gu[1,2], Daniel Hübschmann[1,3,4,5]

[1]Computational Oncology, Molecular Diagnostics Program, National Center for Tumor Diseases (NCT) and German Cancer Research Center (DKFZ), Im Neuenheimer Feld 280, 69120 Heidelberg, Germany
[2]DKFZ-HIPO (Heidelberg Center for Personalized Oncology), 69120 Heidelberg, Germany
[3]Heidelberg Institute of Stem cell Technology and Experimental Medicine (HI-STEM), Im Neuenheimer Feld 280, 69120 Heidelberg, Germany
[4]German Cancer Consortium (DKTK), Im Neuenheimer Feld 280, 69120 Heidelberg, Germany
[5]Department of Pediatric Immunology, Hematology and Oncology, University Hospital Heidelberg, 69120 Heidelberg, Germany

Abstract

Motivation: Functional enrichment analysis or gene set enrichment analysis is a basic bioinformatics method that evaluates biological importance of a list of genes of interest. However, it may produce a long list of significant terms with highly redundant information that is difficult to summarize. Current tools to simplify enrichment results by clustering them into groups either still produce redundancy between clusters or do not retain consistent term similarities within clusters.
Results: We propose a new method named *binary cut* for clustering similarity matrices of functional terms. Through comprehensive benchmarks on both simulated and real-world datasets, we demonstrated that binary cut can efficiently cluster functional terms into groups where terms showed more consistent similarities within groups and were more mutually exclusive between groups. We compared binary cut clustering on the similarity matrices from different similarity measures and found that the semantic similarity worked well with binary cut while the similarity matrices based on gene overlap showed less consistent patterns and they were not recommended to work with binary cut. We implemented the binary cut algorithm in the R package *simplifyEnrichment* which additionally provides functionalities for visualizing, summarizing and comparing the clusterings.
Availability and implementation: The *simplifyEnrichment* package and the documentation are available at https://bioconductor.org/packages/simplifyEnrichment/. The reports for the analysis of all datasets benchmarked in the paper are available at https://simplifyenrichment.github.io/. The scripts coding the analysis are available at https://github.com/jokergoo/simplifyEnrichment_manuscript.

1. Introduction

Functional enrichment analysis or gene set enrichment analysis is a method widely used to evaluate whether genes of interest (GOI), *e.g.,* differentially expressed genes, are over-represented or depleted in certain biological processes represented by gene sets. It is performed by testing the list of GOI against these gene sets *e.g.*, through a hypergeometric test (Khatri and Drăghici, 2005), by analyzing whether the gene sets are enriched at the top of a ranked gene list (Subramanian *et al.*, 2005), or by evaluating the gene expression profile

in individual gene sets through univariate or multivariate approaches (Hung *et al.*, 2012). There are also methods to associate genomic regions of interest (ROI), *e.g.*, regulatory domains, to gene sets, *e.g.*, to identify which biological processes the ROIs might affect (McLean *et al.*, 2010). Functional enrichment analysis depends on *a priori* biological knowledge encoded in pre-defined gene sets, which are obtained from multiple sources. Among them, Gene Ontology (GO) (The Gene Ontology Consortium, 2019) is the most comprehensive source which organizes the biological terms in a hierarchical tree structure, in the form of a Directed Acyclic Graph (DAG). Other popular sources are, for example, KEGG pathways (Kanehisa *et al.*, 2017) and MsigDB catalogues (Liberzon *et al.*, 2015).

Enrichment results usually contain a long list of significantly enriched terms which have highly redundant information and are difficult to summarize, *e.g.*, an analysis on 671 EBI Expression Atlas differential expression datasets (Kapushesky *et al.*, 2010) using GO gene sets with Biological Process ontology showed that there were 543 (80.9%) datasets having more than 250 significantly enriched GO terms under FDR < 0.05. The enrichment results can be simplified by clustering functional terms into groups where in the same group the terms provide similar information. The similarities between terms are important for the clustering and the calculation varies for different sources of gene sets. In the simplest and most general form, the similarity between two gene sets is based on gene overlap and is calculated as Jaccard coefficient, Dice coefficient or overlap coefficient (Merico *et al.*, 2010). The Kappa coefficient is suggested to be more robust, and it is implemented in the widely used *DAVID* tool (Huang *et al.*, 2007). For GO gene sets, there are more advanced methods which integrate the DAG structure to measure the semantic similarity between terms, *e.g.* the methods proposed in (Wang *et al.*, 2007; Schlicker *et al.*, 2006) and implemented in the R package *GOSemSim* (Yu *et al.*, 2010). The semantic similarity can also be calculated on other ontologies with DAG structure such as the Disease Ontology (Yu *et al.*, 2015; Schriml *et al.*, 2012).

One way to simplify the enrichment results is to cluster the similarity matrix of gene sets. Various clustering methods that have already been implemented in current tools can be applied, for example, hierarchical clustering (Ayllon-Benitez *et al.*, 2020), affinity propagation clustering (Zhao and Wang, 2018) or density-based clustering (Huang *et al.*, 2007). The similarity matrix can also be treated as an adjacency matrix and converted to a graph where the gene sets are the nodes and the similarity values are the weights of edges. Later, algorithms for detecting graph communities or modules are applied for identifying the clusters. A popular tool is *Enrichment Map* (Merico *et al.*, 2010).

Nevertheless, there are some common issues for clustering the similarity matrix of gene sets. Taking GO gene sets as an example, we call the root nodes (*i.e.*, the three top terms Biological Process, Molecular Function and Cellular Component) *the root* of the GO tree. In the GO tree, there are branches with different depths, which causes two major problems for clustering. First, the size of GO clusters varies a lot, which means that there are large clusters which normally correspond to large branches inheriting from the root region of the GO tree, while at the same time, there are also many tiny clusters which correspond to the small branches in the very downstream of the GO tree. Due to the hierarchical relations in the tree, large clusters tend to have relatively low average similarities among terms while

small clusters generally have relatively high average similarities. Methods such as *k*-means clustering sometimes cannot preserve the large clusters and split them into smaller clusters, which might produce redundant information between clusters. Moreover, they are not able to separate tiny clusters while they prefer to merge them into one larger cluster. This over-segmentation and under-segmentation behaviour is mainly due to that *k*-means clustering expects clusters to have similar sizes. Second, large GO clusters contain large amounts of terms and it is possible that a small fraction of terms in cluster A also share similarities to terms in cluster B, *i.e.*, larger clusters are less mutually exclusive than smaller clusters, and this results in the fact that some graph community methods merge clusters A and B into one larger cluster due to the terms shared by the two clusters. This in turn increases the inconsistency among gene sets in that merged cluster. Thus, an effective method is needed to balance between these two scenarios, which are the generality and specificity of GO clustering.

In this paper, we propose a new method named *binary cut* that clusters functional terms based on their similarity matrix. It recursively applies partition around medoids (PAM) with two groups on the similarity matrix and in each iteration step, a score is assigned to the submatrices to decide whether the corresponding terms should be further split into smaller clusters or not. We compared binary cut to a wide range of other clustering methods with 100 simulated GO lists and 648 GO enrichment results from real-world datasets, and we demonstrate that, with the similarities calculated by semantic measurements, binary cut was more efficient to cluster GO terms such that inside clusters, terms shared more consistent similarity while at the same time the clusters had a higher degree of mutual exclusivity. Binary cut can also be applied to similarity matrices in general, *i.e.,* based on gene overlap between gene sets and on any type of ontologies. However, the performance of binary cut varied, depending on the sources of gene sets. Similarity matrices based on gene overlap generally showed less consistent patterns than semantic similarity matrices and were not suggested to be used with binary cut.

We implemented binary cut in an R/Bioconductor package named *simplifyEnrichment*. After the gene sets have been clustered, *simplifyEnrichment* visualizes the summaries of gene sets clusters by word clouds, which helps users to easily interpret the common biological functions shared in the clusters. Additionally, *simplifyEnrichment* provides a framework where user-defined clustering methods can be integrated and subsequently their results can be fed into the visualization functionality of *simplifyEnrichment*. Furthermore, *simplifyEnrichment* can compare multiple results from different clustering methods in a straightforward way.

2. Methods

2.1 Similarity measure

If functional terms can be clustered into groups, the similarity matrices of corresponding gene sets are expected to represent a pattern where blocks can be observed on the diagonal if visualized as heatmaps where hierarchical clustering is applied on both rows and columns. Thus, efficiently clustering gene sets is equivalent to the task of identifying the

diagonal blocks in the similarity heatmap. The similarity between gene sets can be calculated as gene overlap by, *e.g.*, the Jaccard coefficient, Dice coefficient or overlap coefficient. The three coefficients have similar forms. It is also suggested to calculate the gene overlap by kappa coefficient which takes into account the possibility of gene occurrence in two gene sets just by chance (Huang *et al.*, 2007). The formal definition of the four gene overlap coefficients can be found in Supplementary file 1. If the ontologies have DAG structure such as GO, the topology information can be used to calculate the similarities, to generate the so-called *semantic similarity*, *e.g.*, through information content-based approaches which measure the information each term provides from its offspring terms. There exist a broad amount of algorithms for calculating semantic similarities, see (Mazandu *et al.*, 2017) for a comprehensive overview.

As we observed from the benchmark datasets for GO terms, semantic similarities showed more clear diagonal block patterns than similarities based on gene overlap (see comparisons in Section 3.3). Additionally, the diagonal block pattern of the semantic matrix was common even for randomly sampled GO terms (Supplementary file 2 and 4). Thus, we mainly consider clustering GO terms with semantic similarities in this work. *simplifyEnrichment* uses the semantic measurements implemented in the R package *GOSemSim* (Yu *et al.*, 2010) and takes the relevance method (Schlicker *et al.*, 2006) as default (see comparisons of different semantic measurements in Supplementary file 3). Nevertheless, a similarity matrix by any other method and on any other ontology can be provided for an analysis with *simplifyEnrichment*.

2.2 Clustering process

Figure 1. Examples of similarity matrices for two sets of GO terms $\mathbf{M}_a$ and $\mathbf{M}_b$. Both matrices are split into two groups in the two dimensions. The values s_{11}, s_{12}, s_{21} and s_{22} are the medians of the entries in the corresponding submatrices. The values on the diagonal are excluded when calculating s_{11} and s_{22}.

Let $\mathbf{M}_a$ and $\mathbf{M}_b$ denote the similarity matrices of two lists of GO terms, as illustrated in Figure 1. Intuitively, in this example GO terms in $\mathbf{M}_a$ have overall high pairwise similarities, thus they should be treated as one single cluster (Figure 1A), while terms in $\mathbf{M}_b$ show a two-block pattern on the diagonal and should be split into two sub-clusters (Figure 1B). Therefore, a metric can be designed to decide whether a group of terms should be split or not. Based on this idea, we proposed a new method named *binary cut* to cluster the similarity matrix of functional terms, executed in two phases :

Phase 1: Applying divisive clustering and generating a dendrogram. This phase includes two steps:

Step 1. For the similarity matrix $\mathbf{M}$ of a given gene set, apply partitioning around medoids (PAM) with two-group classification on both rows and columns, which partitions $\mathbf{M}$ into four submatrices, denoted as $\mathbf{M}_{11}$, $\mathbf{M}_{12}$, $\mathbf{M}_{21}$, and $\mathbf{M}_{22}$ where the indices represent the groups in the two matrix dimensions. Next calculate the following scores s_{11}, s_{12}, s_{21} and s_{22} where s_{11} and s_{22} are the median values of all entries in $\mathbf{M}_{11}$ and $\mathbf{M}_{22}$ excluding the diagonals. s_{12} and s_{21} are the median values of all entries in $\mathbf{M}_{12}$ and $\mathbf{M}_{21}$. s_{11} or s_{22} is defined to be 1 if $\mathbf{M}_{11}$ or $\mathbf{M}_{22}$ have only one row. For the above terms derived from $\mathbf{M}$ we then define the score s as

$$s = \frac{s_{11} + s_{22}}{s_{11} + s_{12} + s_{21} + s_{22}}.$$

The diagonal blocks $\mathbf{M}_{11}$ and $\mathbf{M}_{22}$ correspond to similarity measures within sub-clusters, whereas the off-diagonal blocks $\mathbf{M}_{12}$ and $\mathbf{M}_{21}$ correspond to similarity measures between sub-clusters. In a successful clustering, similarity measures will be higher within clusters than between clusters, and this roughly translates to the median values s_{11}, s_{12}, s_{21} and s_{22}, which results in $s_{11} + s_{22} \geq s_{12} + s_{21}$. Thus, the values of s approximately range between 0.5 and 1. If the similarity matrix $\mathbf{M}$ shows overall similarities, s is close to 0.5 (Figure 1A) and it should not be split any more, while if the GO terms can still be split into more groups, s_{12} and s_{21} are close to 0, which results in s close to 1 (Figure 1B).

Step 2. Apply Step 1 to the two submatrices $\mathbf{M}_{11}$ and $\mathbf{M}_{22}$ respectively. The clusterings in Step 1 and 2 are executed recursively and the process is saved as a dendrogram where the score s is attached to every node in the dendrogram which corresponds to every submatrix in the iteration. The clustering stops when the number of terms in a group reaches 1; these are the leaves of the dendrogram.

Phase 2: Cutting the dendrogram and generating clusters. Since every node in the dendrogram has a score s computed in Phase 1, s is simply compared to a cutoff (0.85 as the default and it can be optimally selected by *simplifyEnrichment*). If s is larger than the cutoff, the two branches from the node are split, or else all the terms under the node are taken as a single cluster.

Nodes with large numbers of terms tend to have relatively smaller s, thus, it is possible that at a certain node, s does not exceed the cutoff but is very close to it, while its child nodes have values of s larger than the cutoff. In this case, we don't want to close the node so early and we still split this node into two subgroups so that its child nodes can be split furthermore. Thus, the rule in Phase 2 is modified as follows: if the score s of a given node does not exceed the cutoff but it is larger than 0.8*cutoff, the node is still split if at least one of its child nodes has a score which exceeds the cutoff.

Figure 2. A demonstration of the binary cut clustering with 500 random GO terms. A-C) The clusterings in the first three iterations; D) The complete dendrogram from binary cut clustering. The colors of the dendrogram segments correspond to the scores s assigned to the nodes. Nodes to split are marked with crosses.

In the iterations of binary cut clustering, there might exist more than two diagonal blocks in the submatrices. In the two-group partitioning on the submatrices, a proper method should be selected to ensure that each group contains complete diagonal blocks. As we have broadly tested on a large number of datasets, in most cases, PAM kept the completeness of diagonal blocks in the two-group classification. Of note, iterative application of bifurcations, *i.e.*, two-group partitioning, can resolve any number of underlying diagonal blocks or clusters.

An example of the process of binary cut clustering is demonstrated in Figure 2. Figure 2A-C illustrate the clusterings in the first three iterations. Figure 2D illustrates the final dendrogram where the nodes that are split are marked with crosses.

2.3 Software implementation

The binary cut algorithm is implemented in an R/Bioconductor package named *simplifyEnrichment*. The input of the package is a similarity matrix that is provided either directly by the user or by the functions implemented in *simplifyEnrichment*, such as the function `GO_similarity()` for calculating GO semantic similarity or the function

`term_similarity()` that measures general gene set similarity by Jaccard coefficient, Dice coefficient, overlap coefficient or kappa coefficient based on gene overlap.

Figure 3. An example of similarity heatmap from 500 random GO terms that have been clustered and annotated with word clouds. The bottom right cluster with no word cloud annotation contains all other small clusters with numbers of terms less than 5. The plot was made by the function *simplifyGO()*.

The function `simplifyGO()` performs clustering for GO terms as well as visualizing the results. Once the GO terms have been clustered, the biological descriptions for the terms are automatically extracted. The summaries of the biological functions in clusters are visualized as word clouds and are attached to the similarity heatmap, which gives a direct illustration of the common biological functions involved in each cluster (Figure 3). The function `simplifyEnrichment()` performs clustering on similarity matrices from any type of ontology.

simplifyEnrichment also allows to integrate other clustering methods. New clustering functions can be added by the function `register_clustering_methods()` and the function `compare_clustering_methods()` applies multiple clustering methods on the same similarity matrix and compares between them via heatmaps (see example in Figure 4).

3. Results

We compared the following 10 clustering methods to binary cut: *k*-means clustering (kmeans) where the optimized number of clusters was selected based on the distribution of within-cluster sum of squares (WSS), dynamicTreeCut (Langfelder *et al.*, 2008), mclust (Scrucca *et al.*, 2016), apcluster (Bodenhofer *et al.*, 2011), hdbscan (Hahsler *et al.*, 2019), the following graph community methods implemented in the R package *igraph* (Csardi and Nepusz, 2006): fast greedy, leading eigen, louvain and walktrap, as well as one additional community method MCL (Van Dongen, 2008) which was recently used in one

implementation for clustering GO terms (Wang *et al.*, 2020). These methods are by default supported in *simplifyEnrichment* for comparisons. GO semantic similarities were calculated by the relevance method (Schlicker *et al.*, 2006) with the R package *GOSemSim*.

3.1 On random GO lists

Figure 4. Comparison of different clustering methods. A-K) The clusterings from 11 different methods. L) Numbers of all clusters and numbers of large clusters with size ≥ 5. For some methods, the small clusters (size < 5) were put into one single cluster on the bottom right of the heatmap and were marked by green lines. All the methods were applied to the same GO semantic similarity matrix from 500 random GO terms from Biological Process ontology. The plots were made by the function *compare_clustering_methods()*.

500 random GO terms were uniformly sampled from the Biological Process (BP) ontology. Clusterings of 11 different methods are illustrated in Figure 4. dynamicTreeCut, mclust and apcluster generated huge numbers of small clusters (Figure 4C-E). kmeans and hdbscan generated intermediate numbers of clusters, but kmeans failed to preserve large clusters even if overall similarities within them were high (*e.g.*, the first three clusters in Figure 4B), while for hdbscan, the largest cluster did not show consistent similarities for all term pairs and it should be split further (the bottom right cluster in Figure 4F). fast greedy, leading eigen, louvain, walktrap and MCL identified both small and large clusters; however, some large clusters may still be split further (Figure 4G-K), as most strikingly visualized for MCL where only two large clusters were identified (Figure 4K). In comparison, binary cut generated clean clusters and it was able to identify large and small clusters at the same time (Figure 4A).

We then benchmarked the clustering methods quantitatively. To this end, the random GO lists of 500 BP terms were generated 100 times and the following metrics were used:

Difference score: It measures the difference of the similarity values of the terms within clusters and between clusters. For a similarity matrix denoted as $\mathbf{M}$, and for term i and j where $i \neq j$, the similarity value $x_{i,j}$ is saved to the vector $\mathbf{x}_1$ when term i and j are in the same cluster. $x_{i,j}$ is saved to the vector $\mathbf{x}_2$ when term i and j are in different clusters. The difference score measures the distribution difference between $\mathbf{x}_1$ and $\mathbf{x}_2$, calculated as the Kolmogorov-Smirnov statistic between the two distributions of $\mathbf{x}_1$ and $\mathbf{x}_2$.

Number of clusters: For each clustering, there are two numbers: the total number of clusters and the number of clusters with size ≥ 5 (*i.e.*, the large clusters). The two values can be used to test whether the clustering methods can identify small clusters.

Block mean: It is simply calculated as the mean similarity values of the diagonal blocks in the similarity heatmap. Using the same convention as for the difference score, the block mean is the mean value of $\mathbf{x}_1$.

Figure 5. Benchmarks of different clustering methods. A-C) Difference scores, numbers of clusters and the block mean values for the clusterings identified by 11 methods. The analysis was applied to 100 random GO lists of 500 BP terms. D-F) Similar as Figure A-C, but on the functional enrichment results from Expression Atlas datasets.

As shown in Figure 5A, binary cut had the highest difference score, reflecting that clusterings obtained with binary cut had the most distinct differences in similarity values within clusters and between clusters, therefore the clusters identified by binary cut were the most mutually

exclusive among all methods. dynamicTreeCut and apcluster generated a huge number of clusters (Figure 5B, examples in Figure 4C and 4E). These two methods can be considered too stringent for clustering GO terms, in addition there still are high levels of redundant information among different clusters. In comparison, graph community methods and binary cut generated moderate numbers of clusters, and especially the numbers of "large clusters" (size ≥ 5) dropped dramatically compared to the total numbers of clusters, indicating that these methods were able to identify small clusters. binary cut generated clusters with moderate block mean values (Figure 5C, examples in Figure 4G-H). In comparison, kmeans, dynamicTreeCut, mclust and apcluster generated high block mean values, reflecting that they were not able to preserve large clusters with intermediate similarities. Graph community methods generated low block mean values, mainly due to the fact that terms in the clusters were not necessary to have high similarities to all other terms (examples in Figure 4G-H). The method hdbscan generated intermediate numbers of clusters and had intermediate block mean values, but it had the lowest difference score in the comparisons, which implies that differences between similarities within clusters and between clusters were small (example in Figure 4F). In conclusion, these comparisons indicated that binary cut kept both generality and specificity of GO clusters. The analysis reports for all 100 random GO lists can be found in [Supplementary file 4](#).

3.2 On real-world datasets

To assess the performance of *simplifyEnrichment* also on actual biological data, we analyzed all datasets from the Expression Atlas (Kapushesky *et al.*, 2010) that have differential expression analysis results. We applied functional enrichment analysis with the R package *clusterProfiler* (Yu *et al.*, 2012) to the significantly expressed genes (FDR < 0.05) with the GO Biological Process ontology. We only took those datasets for which the number of significant genes was in the interval [500, 3000] and the number of significant GO terms (FDR < 0.05) was in [100, 1000]. This yielded 468 GO lists. Figure 5D-F illustrated the results for the comparisons among the 11 clustering methods. The conclusion was very similar to the benchmark with random GO datasets: binary cut outperformed other clustering methods. The analysis reports for 468 individual Expression Atlas datasets can be found in [Supplementary file 4](#).

3.3 General similarity by gene overlap

Many ontologies (*e.g.* MsigDB gene sets) are only represented as lists of genes for which the similarities are merely measured by gene overlap. While in the previous section, the benchmark was based on only one similarity measure, *i.e.*, semantic similarity, we thus performed a second benchmark and compared the performance of binary cut when applied to similarity matrices calculated by different similarity measures. In addition to semantic similarity, these included four gene overlap measures: Jaccard coefficient, Dice coefficient, overlap coefficient and kappa coefficient. For this second benchmark, we again used the 100 random GO lists with 500 BP terms as well as 468 significant GO lists from Expression Atlas datasets.

Figure 6. Comparison of clusterings on similarity matrices by different similarity measures. A) Numbers of clusters. B) Average numbers of terms per cluster. Y-axes in Figure A and B are in log10 scale. C) Mean concordance of the clusterings. The definition of concordance can be found in Supplementary file 10. The analysis was applied to 100 random GO lists with 500 BP terms. D-E) Examples of binary cut clustering on two similarity matrices from the list of random GO terms by semantic and kappa measurements. F-J) Analogous to Figure A-E, but on the functional enrichment results from Expression Atlas datasets. Figure I and J were based on the same dataset. K) Distributions of cluster sizes on similarity matrices from different similarity measures. L) Distributions of the fraction of the largest cluster. Figure K and L were based on Expression Atlas datasets.

When GO terms were randomly generated, with similarities measured by Jaccard coefficient, Dice coefficient and kappa coefficient, 500 terms were split into large numbers of clusters (on average 358 clusters, Figure 6A, red boxes), where on average, less than two terms were in a single cluster (Figure 6B, red boxes). The numbers of clusters dropped dramatically if only counting clusters with size ≥ 5 (on average 6 clusters for all five similarity measures, Figure 6A, blue boxes). For the clusters with size ≥ 5, the average numbers of GO terms per cluster were 20 with the Jaccard coefficient, 17 with the Dice coefficient and 12 with the kappa coefficient, while 53 were identified with semantic measurement (Figure

6B, blue boxes). For the clusters with size < 5 which we defined as "small clusters", the Jaccard coefficient generated on average 375 small clusters (covering 84.5% of all terms), the Dice coefficient generated 335 small clusters (81.4% of all terms) and the kappa coefficient generated 345 small clusters (84.9% of all terms), while in comparison, semantic measurement only generated 31 small clusters (7.8% of all terms) (see difference of red boxed and blue boxed in Figure 6A). This implies that binary cut generated many small clusters on the similarity matrices of Jaccard coefficient, Dice coefficient and kappa coefficient and that these three coefficients could not assign similarities for most of the term pairs, thus they were not efficient for clustering. Examples of the clusterings under different similarity measures can be found in Figure 6D-E and Supplementary file 5. The overlap coefficient performed differently from the other three gene overlap measures (32.3% agreement of the clusterings, Figure 6C). In 30% of all 100 random GO lists, the 500 GO terms could not even be separated and the numbers of clusters for them were only identified as one (Supplementary file 5: Figure S5.2-S5.4). The individual heatmaps of overlap similarities showed that in most cases only one major cluster was generated with a marginal pattern where a small amount of terms showed high similarities to most of the other terms and no diagonal block pattern was observable (Supplementary file 5: Table S5.1), thus binary cut had very weak performance on it. The marginal pattern is due to the definition of the overlap coefficient where the score was normalized by the size of the smaller gene set. For a term located at the downstream of the GO tree, it had the same overlap coefficients to all its ancestor terms because parent terms included all genes of their child terms. The heatmaps for individual datasets (Supplementary file 5: Table S5.1) showed that, for the randomly sampled GO lists, similarity values calculated by gene overlap were very weak and noisy, which led to the fact that in most cases, terms could not be clustered. In comparison, the semantic similarity matrices generated intermediate numbers of clusters and had clear diagonal block patterns (Figure 6D).

Analysis on the Expression Atlas datasets with GO BP ontology also showed that binary cut applied to similarity matrices obtained by semantic similarity generated very different clusterings from the four gene overlap similarity matrices (Figure 6F-J). The cluster sizes obtained from the matrices measured by Jaccard coefficient, Dice coefficient and kappa coefficient had very broad ranges where many datasets had more than 100 clusters (on average 16.7% of all datasets, Figure 6K, an example in Figure 6J). On the other hand, Jaccard coefficient, Dice coefficient and overlap coefficient also generated many small clusters (size < 5) for many datasets (on average 49.7% of all datasets, an example in Figure 6K). In comparison, semantic measurements generated numbers of clusters in a moderate range (14 to 40 for the 10th to the 90th percentile, Figure 6K). Moreover, this analysis showed that the largest cluster comprised more than 80% of all terms in 30.6% of the datasets when using the Jaccard coefficient, in 33.8% of the datasets when using the Dice coefficient and in 39.7% of the datasets when using the overlap coefficient (Figure 6L). This implies that these three coefficients cannot efficiently separate terms in many datasets. For the overlap coefficient, it showed almost no obvious marginal pattern as the random GO lists, because it is relatively difficult for a deeper GO term to be significant due to the small number of genes in the GO term (Supplementary file 6). Taken together, semantic similarity matrices worked better than gene overlap similarities on the real-world datasets.

3.4 Compare enrichment results from multiple lists of genes - a case study

It is a common task to integrate functional enrichment results from multiple lists of genes into one plot, *e.g.*, the enrichment results from up-regulated and down-regulated genes in a two-group differential expression analysis. One of the frequently used methods is to make barplot-like graphics where heights of bars correspond to -log10(p-value) or -log10(FDR) and the enrichment of the up-regulated and down-regulated genes are assigned with positive and negative signs respectively. This method is limited because users need to pre-select functional terms only to a small number either by selecting top n terms with the highest significance or by manually picking representative terms that have distinct biological meanings. The former way might lose important terms with less significance and the latter might be easily affected by subjectivity. Also this is limited only to two gene lists. Here, we used a public dataset to demonstrate a strategy to efficiently compare enrichment results from multiple gene lists without losing any information, which makes it easy to detect, *e.g.*, the biological functions that are uniquely enriched only in one gene list. It works for arbitrary numbers of gene lists.

Figure 7A illustrates a heatmap of signatures genes from a three-group classification of the Golub leukemia dataset (Golub, 2020; Golub *et al.*, 1999). The classification was applied by consensus partitioning with the R package *cola* (Gu *et al.*, 2020). The signatures genes were additionally clustered into three groups by *k*-means clustering and the groups were labelled as "km1", "km2" and "km3". GO enrichment analysis was applied to the three groups of genes separately with the R package *clusterProfiler* (Yu *et al.*, 2012). To compare the enrichment results from the three gene lists, the three significant GO term lists (FDR < 0.01) were merged and binary cut was applied to the union of the terms (Figure 7B). On the left of the GO similarity heatmap illustrates a heatmap of FDR which visualizes whether the GO term was significant in the corresponding gene list. This strategy keeps all significant GO terms without removing anyone. Also it allows more specific studies of how the enrichment varies between gene lists. For example, in Figure 7B, it is easy to inspect genes that were down-regulated in acute myeloid leukemia (AML) samples (km1 group) were more specifically enriched in cell cycle and metabolic processes (labelled with 1 in Figure 7B), genes that were up-regulated in AML (km2 group) were more specifically enriched in lymphocyte activation (labelled with 2 in Figure 7B), and genes that were down-regulated in a subset of acute lymphoblastic leukaemia (ALL) samples (km3 group) were more specifically enriched in cell differentiation (labelled with 3 in Figure 7B).

This strategy was also applied in a previous study (Gu *et al.*, 2020) where it compared biological functions of gene lists generated by four different feature selection methods for consensus partitioning to access which feature selection method generates more biological meaningful features.

Figure 7. Compare enrichment results from three gene lists. A) Heatmap of the expression of signature genes from a three-group classification of Golub leukemia dataset. The three gene lists were generated by applying *k*-means clustering on rows of the expression matrix. B) GO terms that were significant in any enrichment results of the three gene lists were clustered and their similarities were visualized as a heatmap. The left heatmap demonstrates whether the GO terms were significant in the corresponding gene list. The labels of "1, 2 and 3" on word clouds are explained in the main text.

4. Discussion

Simplifying functional enrichment results is necessary for easy interpretation without missing important biological terms. The essential step to simplify enrichment results is to cluster the functional terms, later *post hoc* analysis can be applied to summarize the major biological functions in each cluster, such as extracting the most significant terms in each cluster (Yu *et al.*, 2012) or looking for a minimal subset of terms that cover genes from all terms in that cluster (Liao *et al.*, 2019). A proper clustering method should identify groups of terms that provide more distinct information between clusters and reduce large numbers of terms into an amount easier to read and analyze. In this work, we developed the package *simplifyEnrichment*, which proposes a new method called binary cut to efficiently cluster functional terms and to summarize the general functions in clusters by word cloud visualizations.

Binary cut worked well when the diagonal block patterns were observable in the similarity matrix of functional terms. In the benchmark, the similarity matrices of GO terms by semantic measurement showed clear diagonal block patterns, even for a list of random GO terms. In [Supplementary 3](#), we compared the five semantic similarity measurements supported in the *GOSemSim* package and we found the methods of "Rel" (Schlicker *et al.*, 2006), "Resnik" (Resnik, 1999) and "Lin" (Lin, 1998) produced similar and clear diagonal block patterns, thus they are more suggested to work with binary cut clustering. These three semantic measurements are all information content (IC)-based methods with similar forms which rely on the IC of the most informative common ancestor of two terms in the GO tree. A GO term has higher IC if it has less offspring terms. Thus, in general, the deeper the ancestor of two terms is in the GO tree, the higher IC the ancestor will provide and the higher similarity the two terms will have. Uniformly sampling the GO terms selects more terms locating in the downstream of the GO tree due to its hierarchical structure, therefore, it is more probable for

two terms to reach an ancestor node relatively deeper in the GO tree to contribute a higher IC value, which makes that even random GO lists had clear diagonal block patterns in the benchmark. An analysis of the complete set of terms of GO BP ontology showed that with semantic similarity, globally they had diagonal block patterns where the clusters correspond to several top functional categories (Supplementary file 7).

In each iteration step of the recursive splitting on the similarity matrix, the current submatrix is partitioned into two groups using PAM as default. In Supplementary file 8, we compared binary cut clustering on 100 random GO BP lists with the following three partitioning methods: PAM, *k*-means++ and hierarchical clustering with "ward.D2" method. *k*-means++ is an optimized *k*-means clustering by pre-selecting proper initial centroids (Vassilvitskii, 2007; Leisch, 2006). The results showed the three partitioning methods performed very similarly, *i.e.*, with similar difference scores, numbers of clusters and block mean values among 100 random GO lists. The final clusterings of GO terms are highly agreed (on average 89% agreement, Supplementary file 8: Figure S8.1) between the three partitioning methods. The three methods are all supported in *simplifyEnrichment* and they can be selected specifically for individual datasets.

In the binary cut clustering process, a score is calculated based on the two-group partitioning on the current submatrix and it is compared against a cutoff to decide whether the corresponding terms are treated as a single group or should be further split. In most cases, the default cutoff is robust and works well if the diagonal pattern in the similarity heatmap is observable. Nevertheless, there are still cases where manual adjustment on the cutoff needs to be applied, such as a large cluster which is composed of several small and dense clusters. A typical example is the clustering on the semantic similarity matrices of Disease Ontology terms (Supplementary file 4). The cutoff can be fine-tuned according to what levels of similarities users want to keep. *simplifyEnrichment* provides a `select_cutoff()` function which tries a list of cutoffs and compares difference scores, numbers of clusters and block mean values for the clusterings to decide an optimized cutoff value. In Supplementary file 9, we demonstrated the use of `select_cutoff()` function and how it helps the selection for a proper cutoff.

We mainly benchmarked GO enrichment with BP ontology, which is the major ontology category (65.9%) in GO. In Supplementary file 4, we also applied binary cut to random GO lists from Cellular Component (CC) and Molecular Function (MF) ontologies. The results were very similar as BP terms where binary cut outperformed other clustering methods on the semantic similarity matrices. Besides GO gene sets, we also applied other ontologies to Express Atlas datastes, *i.e.*, gene sets from DO, KEGG, Reactome and MsigDB, only with gene overlap as the similarity measurements (Supplementary file 4). We only found the similarity matrices based on gene overlap coefficients of Reactome and MsigDB C4 gene sets can be used for binary cut clustering while the similarity matrices from other gene sets generally showed low consistency between terms and did not have clear diagonal block patterns, thus, they are not recommended to work with binary cut.

5. Conclusions

We described a new clustering algorithm, binary cut, for clustering similarity matrices of functional terms. Through comprehensive benchmarks on both simulated and real-world datasets, we demonstrated that binary cut can efficiently cluster functional terms where the terms showed more consistent similarities within clusters and were more mutually exclusive between clusters. We implemented the algorithm into an R package *simplifyEnrichment* which additionally provides functionalities for visualizing, summarizing and comparing the clusterings. We believe *simplifyEnrichment* will be a useful tool for researchers to fast explore their results and obtain key biological findings.

Bibliography

Ayllon-Benitez,A. *et al.* (2020) GSAn: an alternative to enrichment analysis for annotating gene sets. *NAR Genom. Bioinform.*, **2**.
Bodenhofer,U. *et al.* (2011) APCluster: an R package for affinity propagation clustering. *Bioinformatics*, **27**, 2463–2464.
Csardi,G. and Nepusz,T. (2006) The igraph software package for complex network research. *InterJournal*, **Complex Systems**, 1695.
Golub,T.R. *et al.* (1999) Molecular classification of cancer: class discovery and class prediction by gene expression monitoring. *Science*, **286**, 531–537.
Golub,T. (2020) golubEsets: exprSets for golub leukemia data Bioconductor.
Gu,Z. *et al.* (2020) cola: an R/Bioconductor package for consensus partitioning through a general framework. *Nucleic Acids Res.*
Hahsler,M. *et al.* (2019) dbscan : Fast Density-Based Clustering with *R. J. Stat. Softw.*, **91**.
Huang,D.W. *et al.* (2007) The DAVID Gene Functional Classification Tool: a novel biological module-centric algorithm to functionally analyze large gene lists. *Genome Biol.*, **8**, R183.
Hung,J.-H. *et al.* (2012) Gene set enrichment analysis: performance evaluation and usage guidelines. *Brief. Bioinformatics*, **13**, 281–291.
Kanehisa,M. *et al.* (2017) KEGG: new perspectives on genomes, pathways, diseases and drugs. *Nucleic Acids Res.*, **45**, D353–D361.
Kapushesky,M. *et al.* (2010) Gene expression atlas at the European bioinformatics institute. *Nucleic Acids Res.*, **38**, D690-8.
Khatri,P. and Drăghici,S. (2005) Ontological analysis of gene expression data: current tools, limitations, and open problems. *Bioinformatics*, **21**, 3587–3595.
Langfelder,P. *et al.* (2008) Defining clusters from a hierarchical cluster tree: the Dynamic Tree Cut package for R. *Bioinformatics*, **24**, 719–720.
Leisch,F. (2006) A toolbox for -centroids cluster analysis. *Comput. Stat. Data Anal.*, **51**, 526–544.
Liao,Y. *et al.* (2019) WebGestalt 2019: gene set analysis toolkit with revamped UIs and APIs. *Nucleic Acids Res.*, **47**, W199–W205.
Liberzon,A. *et al.* (2015) The Molecular Signatures Database (MSigDB) hallmark gene set collection. *Cell Syst.*, **1**, 417–425.
Lin,D. (1998) An Information-Theoretic Definition of Similarity. In, *Machine Learning Proceedings 1998*, ICML '98. Morgan Kaufmann, San Francisco, CA, USA, p. 592.

Mazandu,G.K. *et al.* (2017) Gene Ontology semantic similarity tools: survey on features and challenges for biological knowledge discovery. *Brief. Bioinformatics*, **18**, 886–901.

McLean,C.Y. *et al.* (2010) GREAT improves functional interpretation of cis-regulatory regions. *Nat. Biotechnol.*, **28**, 495–501.

Merico,D. *et al.* (2010) Enrichment map: a network-based method for gene-set enrichment visualization and interpretation. *PLoS ONE*, **5**, e13984.

Resnik,P. (1999) Semantic Similarity in a Taxonomy: An Information-Based Measure and Its Application to Problems of Ambiguity in Natural Language. *J. Artif. Int. Res.*, **11**, 95–130.

Schlicker,A. *et al.* (2006) A new measure for functional similarity of gene products based on Gene Ontology. *BMC Bioinformatics*, **7**, 302.

Schriml,L.M. *et al.* (2012) Disease Ontology: a backbone for disease semantic integration. *Nucleic Acids Res.*, **40**, D940-6.

Scrucca,L. *et al.* (2016) mclust 5: Clustering, Classification and Density Estimation Using Gaussian Finite Mixture Models. *R J.*, **8**, 289–317.

Subramanian,A. *et al.* (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci USA*, **102**, 15545–15550.

The Gene Ontology Consortium (2019) The Gene Ontology Resource: 20 years and still GOing strong. *Nucleic Acids Res.*, **47**, D330–D338.

Van Dongen,S. (2008) Graph clustering via a discrete uncoupling process. *SIAM. J. Matrix Anal. & Appl.*, **30**, 121–141.

Vassilvitskii,S. (2007) K-means : the advantages of careful seeding. *IN PROCEEDINGS OF THE 18TH ANNUAL ACM-SIAM SYMPOSIUM ON DISCRETE ALGORITHMS*.

Wang,G. *et al.* (2020) GOMCL: a toolkit to cluster, evaluate, and extract non-redundant associations of Gene Ontology-based functions. *BMC Bioinformatics*, **21**, 139.

Wang,J.Z. *et al.* (2007) A new method to measure the semantic similarity of GO terms. *Bioinformatics*, **23**, 1274–1281.

Yu,G. *et al.* (2012) clusterProfiler: an R package for comparing biological themes among gene clusters. *OMICS*, **16**, 284–287.

Yu,G. *et al.* (2015) DOSE: an R/Bioconductor package for disease ontology semantic and enrichment analysis. *Bioinformatics*, **31**, 608–609.

Yu,G. *et al.* (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products. *Bioinformatics*, **26**, 976–978.

Zhao,C. and Wang,Z. (2018) GOGO: An improved algorithm to measure the semantic similarity between gene ontology terms. *Sci. Rep.*, **8**, 15107.