Information-theory-based benchmarking and feature selection algorithm improve cell type

annotation and reproducibility of single cell RNA-seq data analysis pipelines

Ziyou Ren[1], Martin Gerlach[2], Hanyu Shi[2], Alexander V. Misharin[1], GR Scott Budinger[1], Luís A. Nunes Amaral[1,2,3,4, 5#]

[1]Department of Medicine, Division of Pulmonary and Critical Care Medicine, Northwestern University, Chicago, IL, 60611, USA.

[2]Department of Chemical and Biological Engineering, Northwestern University, Evanston, IL 60208, USA.

[3]Northwestern Institute on Complex Systems, Northwestern University, Evanston, IL 60208, USA

[4] Department of Physics and Astronomy, Northwestern University, Evanston, IL 60208, USA

[5] Department of Molecular Biosciences, Northwestern University, Evanston, IL 60208, USA

#Corresponding author:

Luís A. Nunes Amaral, PhD

Chemical & Biological Engineering

Northwestern University

2145 Sheridan Road (Room E136)

Evanston, IL 60208, US

Phone: (847) 491-7850

Email: amaral@northwestern.edu

Abstract:

Single cell RNA sequencing (scRNA-seq), which promises to enable the quantitative study of biological processes at the single cell level, are now a routine part of experimental practice. One key computational challenge in analyzing scRNA-seq data is cell type annotation. A source of concern, however, is that the data analysis protocols for clustering cells suffer from low reproducibility and poorly-quantified accuracy. Here, we propose a new benchmark for determining clustering accuracy that uses a dataset where independent reference annotations are generated from surface protein measurements. We then systematically investigate the impact on labelling accuracy of different approaches to feature selection, of different clustering algorithms, and of different sets of parameter values. We demonstrate quantitatively the impact of feature selection and the poor performance of a widely used approach. Additionally, we show that an approach grounded on information theory can provide a generalizable, reliable, and accurate process for discarding uninformative features.

1   **Introduction**

2   The application of single cell RNA sequencing (scRNA-seq) as a hypothesis generation

3   step is becoming increasingly popular in biology and medical research because of the promise to

4   (i) efficiently identify novel cell types from transcriptomic data (Patel et al. 2014; Villani et al.

5   2017); (ii) identify heterogeneity within defined cell populations during homeostasis and disease

6   (Reyfman et al. 2019; Lawson et al. 2015); (iii) follow cellular lineage trajectories(Treutlein et

7   al. 2014; Rizvi et al. 2017; Collin et al. 2019); or (iv) identify novel genetic markers for disease

8   (Miyamoto et al. 2015; Min et al. 2015; Lindström et al. 2019).

9   A key step in scRNA-seq analysis is cell type identification using computational

10 clustering algorithms. While supervised clustering approaches, i.e. identifying cell types based

11 on reference dataset, have been developed to use the data produced by large international efforts

12 such as the Human Primary Cell Atlas (HPCA) and the Encyclopedia of DNA Elements

13 (ENCODE) (Aran et al. 2019; Mabbott et al. 2013; Davis et al. 2018), many studies still rely on

14 unsupervised clustering approaches i.e. identifying cell types based on expression patterns.

15 Among all clustering algorithms, Louvain method (Blondel et al. 2008) is the most popular

16 method in scRNA-seq because of its high efficiency in analyzing high dimensional data. It is the

17 default clustering algorithm in one widely used analysis package, Seurat (Satija et al. 2015).

18 Besides Louvain methods, these integrated packages implement a number of normalizations,

19 feature selection and other cell clustering algorithms. Nevertheless, all unsupervised clustering

20 algorithms try to quantify the similarity of every pairwise cell expression profile in order to

21 identify "clusters" of cells of the same type. Clusters are then assigned to known cell types via

22 the manual identification of genes expressed by cells in the cluster based on *a priori* biological

23 knowledge. Visual inspection is then used to "validate" the quality of the clustering, or the

1   clustering produced by a new algorithm is compared to the clustering reported using a previously

2   published algorithm. Almost always, the algorithms will use the same scRNA-sq data for

3   producing their cluster assignments. Almost never, studies will report on a systematic evaluation

4   of the impact of feature selection or parameter values on the reliability of cluster assignment.

5   Therefore, the lack of independent ground-truth labels for cells against, in which

6   clustering algorithms can be rigorously evaluated, poses a challenge to the establishment of

7   standardized consensus approaches in single cell RNA-seq analysis. And, without standard

8   approaches, it becomes impossible to achieve even adequate reproducibility and replicability of

9   published research.

10   Information theory is a collection of tools and theories to evaluate information

communication and signal processing in complex networks (Amaral and Ottino 2004). It has

been widely used in fields such as literature classification to improve the algorithm performance

and reproducibility (Cheng et al. 2002; Aizawa 2003). We focus here first the development of a

benchmarking data set that <u>does not</u> rely on transcriptomic data for defining reference

annotations. We calculate the normalized mutual information to systemically evaluate the impact

of sparsity and genes on the accuracy and reproducibility of current clustering algorithms using

the independently-generated reference labels. Then we propose an entropy based, non-parametric

feature selection algorithm to evaluate the information content for genes in scRNA-seq data.

Using only the genes with high information content, both the clustering accuracy and

reproducibility were improved for several clustering algorithms.

Results

22   The traditional benchmarking approach for scRNA-seq clustering algorithms may induce

a circularity problem. The evaluation of new algorithm largely relies on the labels published in

literature that are generated by the previous clustering algorithms (Fig. 1A). Unlike those, we use

a publicly available peripheral blood mononuclear cells (PBMC) dataset compiled by 10x

Genomics. This dataset provides for every cell protein staining with TotalSeq-B antibodies and

single cell transcriptomic profiling using the 10x platform. Thus, independently-generated

reference labels are assigned based on the surface protein used traditionally for cell classification

in immunohistochemistry and flow cytometry (Fig. 1B). This benchmarking data set then enables

it to systematically evaluate the impact of different feature selection algorithms and different

clustering algorithms on cell labelling accuracy.

9   Following the traditional approach in cell classification using surface protein markers

with reproducible workflow, we produce a decision tree for cell type annotation (Fig. 1C). It is

visually apparent that the distribution of the surface protein levels is consistent in all cases with a

bimodal distribution. Therefore, we model the distribution using a Gaussian mixture model with

two peaks and determine a binary cutoff by identifying the value for which the likelihoods of a

cell belonging to each of the two groups are identical. We list the estimated parameters for the

decision tree in Supplementary Table 1. We use this approach to classify every one of the 713

cells in the dataset into one of ten cell types. These cell types cover all of the well-known cell

types in PBMC (Supplementary Table 2).

In order to test the robustness of our classification and to acknowledge uncertainty in a

cell's classification, we also consider the case in which we set cells with protein levels that yield

odds ratios smaller than 5:1 between estimated Gaussian functions for two peaks as "unclassified

cells". Using this procedure, we are still able to classify 696 of 713 cells (Fig. S1 and

Supplementary Table 3). Importantly, our results and conclusions do not change when

considering this alternative labelling approach.

Next, we investigate whether our benchmarking approach enables us to quantify the

impacts of data sparsity and potentially uninformative genes on the performance of clustering

algorithms. For concreteness, we focus first on the performance of build-in Louvain methods in

Seurat, which we will simply refer to as Seurat in the remainder of the manuscript. Seurat is one

of the most widely adopted tool in scRNA-seq analysis. To test the hypothesis that high sparsity

and overwhelming numbers of uninformative genes will induce poor classification accuracy, we

generate synthetic datasets that allow us to vary data sparsity and the number of potentially

uninformative genes.

As a first step, we apply Seurat to the surface protein level dataset in which sparsity is

negligible and all features are by construction meaningful. Using the full data for the seventeen

cell-surface proteins, we are able to classify cell types with very high precision (Fig. 2A-B and

Fig. S2). Indeed, the only misclassifications occur in separating cells types that are relatively

infrequent in the dataset. Thus, as one would expect, Seurat performs very well when applied to

data with negligible data sparsity.

To systemically investigate how data sparsity affects clustering accuracy without the

complications due to uninformative features, we model data sparsity by setting a model for the

probability that a specific surface protein's level is too low to be detected (refer to Methods for

details). Compared with an available method for producing sparsity where counts are drawn from

the negative binomial distribution (Zappia, Phipson, and Oshlack 2017), or a naïve model where

counts are randomly changed to 0, our method better captures the physical process occurring in

real experiments where the presence of a value of zero counts will be correlated with the

expression level.

We systematically change the value of the threshold level t, and quantify the clustering

accuracy using the normalized mutual information (NMI) between the independently-generated

reference labels and the labels generated by the clustering algorithm on the synthetic dataset.

NMI is a commonly used metric to quantify the overlap between different partition. An NMI

equal to 1 indicates perfect overlap, whereas a value of 0 indicates random overlap (Witten and

Frank 2002). Figure 2C shows that our benchmarking approach correctly reflects that steady

decrease in clustering accuracy as data sparsity increases, that is, as the detectability threshold

increases to higher levels.

Next, we examine how a large number of potentially uninformative features interacts

with data sparsity to affect the accuracy of clustering algorithm as another important part of

benchmarking. To this end, we add the data from 16,000 randomly selected genes from the

transcriptomics dataset to the synthetic data for protein levels with distinct detectability threshold

generated in the previous step (Fig. 2D). As expected, the large number of likely uninformative

features leads to a decrease in clustering accuracy. Surprisingly, this decrease is even more

dramatic than one would expect as it completely overshadows the impact of data sparsity.

In order to quantify the specific effect of uninformative features, we add to the full

surface proteins level data different numbers of randomly selected genes from the transcriptomic

dataset. It is remarkable that transcriptomic data for even as few as 1,000 randomly selected

genes reduces the algorithm's NMI by 25% (from 0.8 to 0.6, Fig. 2E). This decrease clearly

demonstrates that more data are not always helpful. In fact, an increase in the number of

uninformative features dramatically decreases performance.

These results demonstrate that in order to increase the accuracy of cell labelling using

transcriptomic data we must filter out features that are uninformative for the purpose of cell

labeling. This is particularly important because a recent review (Kiselev, Andrews, and Hemberg

2019) dedicates a single paragraph to this issue. Before proceeding, we must emphasize that

important genes for the functioning of a cell are not necessarily informative of cell type. Genes

such as *MALAT1* and *HLA-A*, which are highly conserved or constitutively expressed, are critical

for cells (Hutchinson et al. 2007; Kovats et al. 1990). However, because they will be expressed at

similar levels in all cells, they cannot provide useful information for detecting cell type. Due to

the importance of the degree to which a gene may provide *information* for cell classification, we

pursue an approach grounded on information theory that we have recently demonstrated can

dramatically improve the performance of algorithms for the classification of texts (Gerlach, Shi,

and Amaral 2019). Unlike other currently pursued approaches, such as filtering out genes with

low coefficient of variation, ours has a solid theoretical grounding and does not require any

assumptions about the distribution of counts of unique molecular identifiers (UMIs).

Concisely, conditional entropy $H(g|S)$ is calculated for each gene given the UMI

frequency. We also created null models by random distribution to calculate average conditional

entropy over different realizations, $\langle \tilde{H}(g|C) \rangle$ (details refer to method). The information content

$I(g)$ is calculated by the difference between $H(g|S)$ and $\langle \tilde{H}(g|C) \rangle$. Higher $I(g)$ indicates that

the gene has high expression in a subset of cells, which will be useful to determine cell types.

To test the robustness of our filtering approach, we calculate $H(g|S)$, $\langle \tilde{H}(g|C) \rangle$, and

$I(g)$ for three PBMC datasets publicly available on the 10x Genomics website. As predicted, we

observe a very strong dependency of $\langle \tilde{H}(g|C) \rangle$ on gene total expression level (Fig. 3A). We

also find that most genes have $I(g) \approx 0$, indicating that those genes cannot possibly provide

meaningful information concerning cell identities. Surprisingly, 15 out of 17 of the genes coding

the surface protein markers we use in generating labels are not informative for determining cell

type.

A few genes such as *GNLY*, which codes for a T-cell activation protein, and *PTGDS*,

which codes for a protein involved in platelet aggregation, are informative about cell type across

the three datasets (Fig. 3A, B). Importantly, we observe a large and consistent number of

overlaps for the set of top 5%, 10% and 20 % most informative genes for cell type classification

across the three datasets (Fig. 3D and Fig. S3B-D). We also observe a large overlap of

informative genes using the default filtering algorithm in Seurat and our information-based

filtering but not when we consider the coefficient of variation filtering approach (Fig. 3E). These

findings suggest that the genes informative of cell type will be generally conserved across

biological replicates. Importantly, because this approach requires no prior biological knowledge

and contains no fitted parameters, it can be <u>applied without adjustment to samples from different</u>

<u>tissues or from different organisms</u> (Fig. S3A).

We next compare the impact of using three feature filtering algorithms on the clustering

accuracy of Seurat: coefficient of variation, default filtering algorithm in Seurat, and our

information-based algorithm (Fig. 4A). Our analysis shows that using the coefficient of variation

for filtering features performs poorly at detecting uninformative features. In contrast, the default

Seurat filtering and our information-based filtering are truly able to select informative features. A

point of distinction between the filtering algorithm implemented with Seurat and our proposed

information-based filtering is their theoretical foundations. The filtering algorithm in Seurat

algorithm models the mean-variance relationship within the data, as such is limited by the scope

of its assumption and by the need to select parameter values. Information theory provides the

best-grounded non-parametric approach to the problem of selecting informative features.

Moreover, it requires the fewest assumptions and provides a roadmap for improvement and

generalization. To our best knowledge, it is unlikely that any *ad hoc* approach being proposed

now and not grounded on information theory would be superior to that provided by information

theory. For this reason, and even though the filtering algorithm in Seurat performs well for the

dataset considered here, there is not guarantee that it will work as well for other datasets.

We next evaluate the impact of using our filtering algorithm on clustering accuracy of

three algorithms: SC3 (Kiselev et al. 2017), Seurat (Satija et al. 2015), and Topic Mapping

(Lancichinetti et al. 2015). Topic Mapping is a highly reproducible high-accuracy algorithm for

clustering documents. We implement a straightforward analogy: words to genes and documents

to cells.

As the fraction of filtered genes increases, the classification accuracy of all three

algorithms also increases (Fig. 4B and Fig. S4A). Interestingly, the greatest gain in accuracy

occurs once we remove the 50% genes with the lowest $I(g)$, demonstrating that most genes

measured in scRNA-seq truly contain no useful information for cell classification. Indeed,

clustering accuracy increases up to the removal of the bottom 90% of genes by information

content.

Filtering out uninformative genes greatly improves classification stability (Fig. 4C-D and

Fig. S4B). Specifically, the number of clusters returned by Seurat and Topic Mapping become

more stable as the percentage of genes filtered increases. Additionally, the confidence with

which cluster assignment are made in Topic Mapping also increase with percentage of filtered

genes. Importantly, the genes that are most informative in our analysis are dissimilar to those

used for cellular classification based on protein measurements (Fig. 3A). This suggests that

classification schema based on genes coding for proteins targeted in flow cytometry,

immunohistochemistry or other protein-based measures (Bhattacharya et al. 2014), will not

necessarily extract the optimal amount of information from scRNA-seq data.

Our results also suggest that "noise" from uninformative genes leads to ambiguous

assignment of cells to clusters. After removing uninformative genes, the three algorithms largely

correctly assign major cell groups such as B cells or monocytes (Figs. 5A, C, E). Seurat and SC3,

but not by Topic Mapping, also correctly identify NK cells. However, all three have trouble

distinguishing between other cell types. CD4, CD8 and NKT cells are placed into the same

clusters by the three methods, but while SC3 and Seurat arbitrarily break the cells from those

types into two clusters, Topic Mapping puts them all in a single cluster. The confusion matrices

are similar when we compare the same clustering results against a supervised annotation

approach using SingleR and ENCDOE or HPCA as reference dataset (Figs. 5 B, D, F and Fig.

S5C). While the supervised annotation approach identifies broader cell groups, our protein-based

annotation significantly overlaps with their results (Figs. S5A, B).

Study Limitations

There are limitations in our study. Our benchmarking method is limited to CITE-seq

platform where both surface protein and mRNA are quantified at the same time. The number of

CITE-seq datasets is limited in current literature. However, CITE-seq analysis is becoming

increasing popular in medicine (Saigusa and Ley 2020; Bandyopadhyay et al. 2019; Kotliarov et

al. 2020) and our method can be readily applied to these new datasets. On the other side, our

filtering approach is not limited to CITE-seq platform and can be applied in any scRNA-seq data

without any prior biology knowledge. Secondly, we recognize that researchers perform some

filtering procedures to remove the undetected genes before clustering algorithms as best practice.

However, most of current filtering rely on parametric tests, there could be potential biases in

their assumptions. Our method, on the other hand, does not reply on parametric test and has

minimal assumptions. Lastly, there exist supervised cell annotation tools such as SingleR (Aran

et al. 2019). We demonstrate our annotation method largely overlaps with the results based on

ENCODE and HPCA reference but with more details. Furthermore, our labels can be used as a

reference dataset in those supervised approach.

Discussion

9   Our study demonstrates that without independent validation, current frameworks for

benchmarking scRNA-seq are plagued by circularity and lead to irreproducible research. The

entanglement of cell type assignment with assessment of clustering quality is deeply problematic

because it creates a serious risk for confirmation bias. This situation is made more concerning

due to the fact that the evaluation of clustering quality relies almost entirely on visual inspection.

As an example, take Figure 5 of Furlan *et al.* (Furlan et al. 2017). As in many other studies, the

authors attempt to persuade the reader of the quality of the clustering by showing how specific

genes are preferentially expressed in cells assigned to a certain cluster. No quantification of such

"preference" is provided and neither is a comparison with the outcomes that would be obtained

using alternative clustering approaches.

19   In contrast to the lack of attention to validation of cell clustering approaches, data

sparsity due to low RNA capture rates and uninformative genes are frequently acknowledged as

challenges in the analysis of scRNA-seq data (Kharchenko, Silberstein, and Scadden 2014).

Depending on the sequencing platform, experimental setup, and sample preparation, on the order

of 80% of the scRNA-seq measurements for each of the approximately 20,000 human genes

yield zero counts (Angerer et al. 2017). Remarkably, most publications still do not document

appropriately whether they used some approach for removing uninformative genes. Confirming

prior research, we find that high sparsity and the large number of uninformative genes

significantly reduces the performance of clustering algorithms. We show that this reduction in

clustering accuracy and reproducibility can be reversed through appropriate feature selection,

however, even in this there is no consensus. As we demonstrated, a recently recommend

approach (Kiselev, Andrews, and Hemberg 2019) for identifying uninformative genes – small

coefficient of variation – is widely used even though it produces poor labelling accuracy.

In contrast, we show that the information content for cell classification of a gene in a

specific dataset can be determined without the need for any prior biological knowledge. As we

demonstrate, cell-type classification can be greatly improved by identifying the relatively small

fraction of genes with high information content. However, much is still left to be done.

Hopefully, this study will prompt others to develop additional benchmark datasets and tools to

improve reproducibility and accuracy of scRNA-seq analysis.

Methods

Benchmarking CITE-seq protein data with bimodal modeling

We model the distribution using a Gaussian mixture model with two peaks and determine a

binary cutoff by identifying the value for which the likelihoods of a cell belonging to each of the

two groups are identical. We list the estimated parameters for the decision tree in the

supplementary information.

In order to test the robustness of our classification and to acknowledge uncertainty in a

cell's classification, we also consider the case in which we set cells with protein levels that yield

odds ratios smaller than 5:1 between estimated Gaussian functions for two peaks as "unclassified

cells".

Clustering PBMC scRNA-seq data

Seurat: We download version 3.2.1 of the Seurat package from CRAN R project and use default

defaults settings illustrated by the online tutorial (https://satijalab.org/seurat/vignettes.html).

Different parameters in resolution are sampled to reflect the change in clustering accuracy.

SC3: We download version 1.16.0 of the SC3 package from Bioconductor project and use

default settings except for the selection of the number of clusters. Several cluster numbers are

used to examine the clustering accuracy.

Topic Mapping: We obtained the Topic Mapping package from the authors. We implement a

straightforward analogy: words to genes and documents to cells. The TopicMapping algorithm

outputs two conditional probability vectors: p(gene|topic), which is used to identify marker

genes for each cluster, and p(topic|cell), which is used to identify cell clusters based on

probability distribution over topics. Each topic is treated as a cell type and the cells are assigned

to the topic with the highest probability. There are only two parameters in determining the

clustering results P, which specifies the statistical significance threshold for acceptance of new

clusters, and t, which specifies which required minimal manipulation. We use default values ($P =$

0.05 and $t = 10$) in our analyses.

Generating synthetic datasets to model sparsity and uninformative genes

We model data sparsity by setting a model for the probability that a specific surface protein's

level is too low to be detected. We use a sigmoidal function to generate the probability that

protein j is detected by the assay for an individual cell c:

$$p(x_{c,j}; x0) = \frac{1}{1+e^{\ln(x0/x_{c,j})/\sigma}}$$

where x is the actual protein level, ln is the natural logarithm function, $x0$ is the selected

detectability threshold, and σ controls the stochasticity of the detection process around the

threshold. For simplicity, we set $\sigma = 1$ for all simulations.

To model the impact of uninformative genes on clustering accuracy, we add the data

from 500, 1000, 2000, 8000, 16,000 randomly selected genes from the transcriptomics dataset to

the synthetic data for protein levels with distinct detectability threshold generated in the previous

step.

Calculating the information content of all genes for a sample

Our method is generalized from that reported by Gerlach, Shi, and Amaral (2019). Consider a

sample S comprised of L cells and denote by $n(g, c)$ the number of UMIs for gene g and cell c.

The total reading depth N can be expressed as the sum over all genes g and all cells c of $n(g, c)$.

The probability that a UMI for gene g occurs in cell $c \; \epsilon \; S$ is:

$$p(c|g) = \frac{p(g,c)}{p(g)} = \frac{n(g,c)}{n(g)}$$

2   Where $p(g) = N(g)/N$ is the relative frequency of UMIs for gene g across the entire sample.

3   We can use Shannon entropy to quantify the heterogeneity of this distribution:

$$H(g|S) = -\sum_{c\epsilon S} p(c|g) \ln [p(c|g)].$$

5   The entropy $H(g|S)$ thus describes the information we can hope to extract from the distribution

6   of number of UMIs for gene g. A gene specific to a certain cell type will have less uncertainty in

7   its expression pattern across the sample and thus will have a lower entropy than a 'house-

8   keeping' gene which will not be specific to a certain cell type. The maximum possible value of

9   the conditional entropy occurs for a uniform distribution of number of UMIs,

$$H_{max} = -\sum_{c \in S} \frac{1}{L} \ln \left(\frac{1}{L}\right) = \ln(L).$$

Due to high sparsity nature of scRNA-seq dataset, most genes will occur at very low frequencies

and the limit expressed by H_{max} will not be accurate. Therefore, we estimate a null model for the

$n(g)$ in order to calculate the expected value of the entropy under the null hypothesis. To this

end, we generate random distributions of UMI counts across genes and cells while preserving the

marginal counts $N(g)$ and $N(c) = \sum_g n(g,c)$. By calculating the expected entropy from many

realizations of this null model, we define the "true" information content of a gene, $I(g)$, as:

$$I(g) = \langle \tilde{H}(g|S) \rangle - H(g|S)$$

where $\langle \tilde{H}(g|C) \rangle$ denotes the average conditional entropy over different realizations of the null

model, and higher $I(g)$ indicates higher information-content. In contrast, genes with $I(g) \approx 0$

are uninformative and should be excluded from the list of features during the clustering analysis.

Comparison of protein-based cell type annotation with supervised methods.

We compare our protein-based cell type annotation with the supervised cell type annotation

method using SingleR with both Human Primary Cell Atlas (HPCA) and Encyclopedia of DNA

Elements (ENCODE) dataset. SingleR package is obtained through CRAN R project and default

parameters are used in cell type annotation for single cells.

Data and code availability

We use a publicly available peripheral blood mononuclear cells (PBMC) dataset compiled by

10x Genomics: PBMC dataset 1 (https://support.10xgenomics.com/single-cell-gene-

expression/datasets/3.0.0/pbmc_1k_protein_v3). PBMC dataset 2

(https://support.10xgenomics.com/single-cell-gene-

expression/datasets/3.0.0/pbmc_10k_protein_v3) and PBMC dataset 3

https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.1.0/pbmc3k). Human

and mouse pancreas cells data were downloaded on 04/03/2018 from https://hemberg-

lab.github.io/scRNA.seq.datasets/human/pancreas/.

The source code is publicly available at https://github.com/amarallab/Benchmark_scRNA_seq.

Statistical analysis

All statistical analyses are performed using R (Team 2014) and figures are produced using the

package ggplot2 (Wickham). The error bar and confident intervals are calculated using

bootstrapping. P-value is calculated using student's t-test with two side for figure 2 and

hypergeometric test for Venn diagram in figure 3 and figure S3 using build-in function in R.

23
Acknowledgements

Z.R. is supported from American Heart Association Postdoctoral Fellowship 20POST35180141.

LANA is supported by the Successful Clinical Response In Pneumonia Therapy (SCRIPT)

Systems Biology Center (U19AI135964); and the Northwestern University Quantitative Biology

Center (NUQuB) (NSF/Simons DMS-1764421);

Conflicts of interests

The authors declare no conflicts of interests.

Figure 1. Limitations of current framework for optimizing scRNA-seq cell type

classification algorithms and development of an externally validated dataset.

A. Current implicit frameworks for optimizing scRNA-seq classification algorithms assume that

some algorithm, typically Louvain method from Seurat, yields a ground-truth classification

against which the accuracy of other algorithms is then determined.

B. A reproducible, objective framework would make use of an independently-obtained, robust,

and reproducible independently-generated reference annotations against which the accuracy of

scRNA-seq classification algorithms can be objectively determined. We believe that in order to

avoid circularity reference annotations should be based on independent approaches such as

surface protein expression or immunostaining.

C. Creation of externally validated labelling for peripheral blood mononuclear cells (PBMCs)

from a healthy donor released by 10x Genomics (https://support.10xgenomics.com/single-cell-

gene-expression/datasets/3.0.0/pbmc_1k_protein_v3). The dataset includes simultaneous single

cell levels for 17 surface proteins measured using ToptalSeq-B antibodies, as well as

transcriptomic profiles for 713 cells. Surface protein level from the cells is consistent with a

bimodal distribution. We model empirical distribution as a mixture of two Gaussian peaks and

detect a threshold for binary classification of protein level, which can be used for classification

with a biologically-grounded decision tree enabling us to classify every cell into one of ten cell

types.

Figure S1. Creation of externally validated labelling for peripheral blood mononuclear cells

(PBMCs) with uncertainty thresholds. We model the empirical distribution as a mixture of two

Gaussian peaks, which can be used for classification with a biologically-grounded decision tree

enabling us to classify every cell into one of ten cell types.

Supplementary Table 1. The estimated parameters for each decision tree using Gaussian

mixture model. (Data shown in separated file)

Supplementary Table 2. Cell type classification based on binary cutoffs. (Data shown in

separated file)

Supplementary Table 3. Cell type classification based on uncertainty regions. (Data shown

in separated file)

Figure 2. Clustering accuracy of Seurat decreases dramatically with increasing levels of data

sparsity and increasing number of uninformative variables.

A. Sankey diagram of Seurat classification based solely on surface protein labels. The left side

shows the clusters identified by Seurat with the parameter set to the default value (0.8). The right

side shows the cell types we identify using surface protein data and a decision tree.

B. Confusion matrix between Seurat classification and surface protein label in A. The most likely

cell type is highlighted in red on the diagonal line.

C. Effect of data sparsity on accuracy of Seurat algorithm for four values of the parameter,

resolution, ranging from 0.3 to 3.0. We model data sparsity by setting a threshold level for the

detectability of the log protein counts (see text for details). As we increase data sparsity, by

moving the mid-point of sigmoidal function, we find a steady decrease in accuracy. Notably, this

decrease does not depend on the value of *resolution*. Sparsity measured by percentage of zero

counts (black line) with the increasing threshold of log protein counts. About 90% of the counts

become zero for $t \geq 8$.

D. Effect of number of possibly uninformative variables and data sparsity on accuracy. We

repeat the procedure described above for surface protein levels, but now include in the data the

measured levels of 16,000 randomly selected mRNAs. The large number of uninformative

variables included in the transcriptomic data decreases clustering accuracy by nearly 40% for

low levels of data sparsity. Interestingly, it yields best accuracy with *resolution* >1.6, not with

the default value.

E. Effect of number of possibly uninformative variables on accuracy. We generate 10 replicates

by adding to the protein-levels data randomly-selected sets with data from varying numbers of

mRNAs in order to estimate the confidence intervals for accuracy of classification. If none of the

possibly uninformative mRNA is included, then classification accuracy measured is very high.

As we include data from an increasing number of mRNAs, we find a steady decrease in accuracy

across all parameter settings.

Figure S2. Sankey diagram of classification based on surface protein levels using

uncertainty region.

For the first two panels, the right side shows the cell types we identify using binary cutoffs of

surface proteins. The left side shows the clusters identified by A. SC3 algorithm with the user

input of correct cluster number (10); B. Topic Mapping algorithm.

For the last three panels, the right side shows the cell types we identify using binary cutoffs of

surface proteins. The left side shows the clusters identified by C. Seurat algorithm at default

resolution (0.8); D. SC3 algorithm with the user input of correct cluster number (10);

Topic Mapping algorithm.

Figure 3. Context-specific identification of genes that are uninformative for cell type

classification. We consider 3 PMBC datasets published by 10x Genomics. PBMC dataset 1 is

the dataset we consider in the previously presented figures. PBMC dataset 2 and 3 comprise

2,700 and 7865 PBMCs from human blood samples (https://support.10xgenomics.com/single-

cell-gene-expression/datasets/3.0.0/pbmc_10k_protein_v3 and

https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.1.0/pbmc3k).

A. The conditional entropy across cells enables the identification of genes that cannot provide

information for a classification task. The red lines show the expected entropy for genes that are

randomly distributed across cells. The conditional entropies are normalized by H_{max}. Most genes

have distributions with entropies very close to the random expectation, implying that those genes

cannot provide any information concerning cell classification. Two such uninformative genes are

MALAT1 and *HLA-A*, which code for highly-conserved proteins and are constitutively expressed

in almost all cell types. In contrast, *GNLY*, which codes for a T-cell activation protein, and

PTGDS, which codes for a protein involved in platelet aggregation, are quite informative about

blood cell type. Most of the surface protein coding genes such as CD16 or CD19 are close to the

null expectation and thus provides no additional information for cell type assignment.

B. Distribution of information content for genes with different UMI frequency. Each dot

represents a gene from PBMC dataset 1 (left), dataset 2 (middle), dataset 3 (right). The

information content is calculated by the difference between randomly distributed null model and

actual conditional entropy.

C. Distribution of UMI counts for *GNLY* (orange) and *MALAT1* (purple) gene across cells in

PBMC dataset 1 (left), dataset 2 (middle), dataset 3 (right). *MALAT1* is highly expressed in most

cells and has a uniform distribution. *GNLY* is highly expressed in a small fraction of the cells and has a bimodal distribution.

D. Overlap of the most informative genes from three datasets of peripheral blood mononuclear cells. The expected overlap across the three sets if we had simply selected 630 mRNAs at random from 12,600 would have been only about 1.2 mRNA on average, whereas overlap between two sets would have been above for most informative genes. Suggesting the robustness of the approach, and its biological significance, we find for both most and least informative mRNAs a statistically significant excess in the number of mRNAs that overlap across the three sets (p-values were calculated using non-parametric test with10,000 iterations).

E. Overlap of most informative genes using Seurat default filtering approach, CV based filtering approach and our entropy-based approach using PBMC dataset 1. We select the same number of top informative genes from three filtering outputs.

Figure S3. Context-specific identification of genes that are uninformative for cell type

classification.

A. The conditional entropy across cells does not require *a priori* biological knowledge in

determining uninformative genes. We consider a published dataset of pancreas cells from either

human or mouse and calculate the information content for each gene. Genes such as INS that are

critical for pancreas cell types identification are with high information content. *MALAT1* or *HLA-*

A are uninformative in both human and mouse datasets like what we find in PBMC datasets.

Some genes such as *PTGDS* are informative for human cell types but not for mouse.

B-D: Overlap of most informative and least informative genes (B: 5%; C:10%; D: 20%) using

information contents from three datasets of peripheral blood mononuclear cells.

Figure 4. Filtering uninformative genes yields dramatic improvements in classification

accuracy.

A. Effect of filtering non-informative genes on accuracy using three different filtering

approaches. We filter the genes using Seurat default filtering, our info filtering and coefficient of

variance filtering and test the effects of classification accuracy on Seurat algorithm.

B. Effect of filtering non-informative genes on accuracy of two standard algorithms (Seurat,

SC3) and a new algorithm (Topic Mapping) for optimal parameter settings. We rank genes by

the information content of the distribution and filter out an increasing percentage of the least

informative genes. We generate 15 replicates using bootstrapping (sampling with replacement) in

order to estimate confidence intervals for the accuracy of the different classification algorithms.

We observe that there is no significant increase in accuracy until we remove at least 50%

mRNAs, indicating that most mRNA measured in scRNA-seq screens contain no useful

information for cell classification. As we then increase number of non-informative gene filtered

out, we reveal a steady increase in accuracy across all testing algorithms regardless of parameter

settings (see Fig. S4A). We also plot the results using Seurat default filtering algorithm. We also

plot the results using Seurat default filtering algorithm.

C. Filtering out non-informative genes does not alter the estimated number of detected clusters.

D. Filtering out non-informative genes reduces the percentage of unclassified cells in Topic

Mapping. The number of unclassified cells reduce significantly after we remove 50% of mRNAs

for Topic Mapping. For this dataset there are no unclassified cells in SC3. Seurat always

classifies every cell.

Figure S4. Filtering uninformative genes yields dramatic improvements in classification

accuracy.

A. Effect of filtering non-informative genes on accuracy of two standard (Seurat, SC3) and a

new (Topic Mapping) algorithms for different parameter settings.

B. Filtering out non-informative genes reduces the percentage of unclassified cells in Topic

Mapping for different parameter settings.

3 **Figure 5. Confusion matrices for Seurat, SC3 and Topic Mapping classification of mRNA**

4 **with 80% filtering against surface-protein based classification (A, C, E) and ENCODE**

5 **based annotation (B, D, F), respectively.** For Topic Mapping, unclassified cells are listed in a

6 separate row and excluded from NMI calculation.

2
3
4
Figure S5. Supervised annotation methods highly overlap with our protein-based

annotation.

A. Confusion matrix for supervised annotation method using ENCODE SingleR and our protein-

based annotation.

B. Confusion matrix for supervised annotation method using HPCA SingleR and our protein-

based annotation.

C. Confusion matrix for Seurat (top), SC3 (middle) and Topic Mapping (bottom) classification

of mRNA with 80% filtering against HPCA based annotation.

References:

Aizawa, Akiko. 2003. 'An information-theoretic perspective of tf–idf measures', *Information Processing & Management*, 39: 45-65.

Amaral, Luis AN, and Julio M Ottino. 2004. 'Complex networks', *The European Physical Journal B*, 38: 147-62.

Angerer, Philipp, Lukas Simon, Sophie Tritschler, F Alexander Wolf, David Fischer, and Fabian J Theis. 2017. 'Single cells make big data: New challenges and opportunities in transcriptomics', *Current Opinion in Systems Biology*, 4: 85-91.

Aran, D., A. P. Looney, L. Liu, E. Wu, V. Fong, A. Hsu, S. Chak, R. P. Naikawadi, P. J. Wolters, A. R. Abate, A. J. Butte, and M. Bhattacharya. 2019. 'Reference-based analysis of lung single-cell sequencing reveals a transitional profibrotic macrophage', *Nat Immunol*, 20: 163-72.

Bandyopadhyay, Gautam, Jacquelyn Lillis, Ravi S Misra, Jason R Myers, John M Ashton, Heidie L Huyck, Daria Krenitsky, Stephen T Romas, Cory J Poole, and Jeanne Holden-Wiltse. 2019. 'Identification and Characterization of Cellular Heterogeneity within Human Late Developmental Stage Dissociated Lung by CITE-Seq', *The FASEB Journal*, 33: 847.5-47.5.

Bhattacharya, Subarna, Paul W Burridge, Erin M Kropp, Sandra L Chuppa, Wai-Meng Kwok, Joseph C Wu, Kenneth R Boheler, and Rebekah L Gundry. 2014. 'High efficiency differentiation of human pluripotent stem cells to cardiomyocytes and characterization by flow cytometry', *JoVE (Journal of Visualized Experiments)*: e52010.

Blondel, Vincent D, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. 2008. 'Fast unfolding of communities in large networks', *Journal of statistical mechanics: theory and experiment*, 2008: P10008.

Cheng, Jie, Russell Greiner, Jonathan Kelly, David Bell, and Weiru Liu. 2002. 'Learning Bayesian networks from data: An information-theory based approach', *Artificial intelligence*, 137: 43-90.

Collin, J., R. Queen, D. Zerti, B. Dorgau, R. Hussain, J. Coxhead, S. Cockell, and M. Lako. 2019. 'Deconstructing Retinal Organoids: Single Cell RNA-Seq Reveals the Cellular Components of Human Pluripotent Stem Cell-Derived Retina', *Stem Cells*, 37: 593-98.

Davis, Carrie A, Benjamin C Hitz, Cricket A Sloan, Esther T Chan, Jean M Davidson, Idan Gabdank, Jason A Hilton, Kriti Jain, Ulugbek K Baymuradov, and Aditi K Narayanan. 2018. 'The Encyclopedia of DNA elements (ENCODE): data portal update', *Nucleic Acids Res*, 46: D794-D801.

Furlan, A., V. Dyachuk, M. E. Kastriti, L. Calvo-Enrique, H. Abdo, S. Hadjab, T. Chontorotzea, N. Akkuratova, D. Usoskin, D. Kamenev, J. Petersen, K. Sunadome, F. Memic, U. Marklund, K. Fried, P. Topilko, F. Lallemend, P. V. Kharchenko, P. Ernfors, and I. Adameyko. 2017. 'Multipotent peripheral glial cells generate neuroendocrine cells of the adrenal medulla', *Science*, 357.

Gerlach, Martin, Hanyu Shi, and Luís A Nunes Amaral. 2019. 'A universal information theoretic approach to the identification of stopwords', *Nature Machine Intelligence*, 1: 606-12.

Hutchinson, J. N., A. W. Ensminger, C. M. Clemson, C. R. Lynch, J. B. Lawrence, and A. Chess. 2007. 'A screen for nuclear transcripts identifies two linked noncoding RNAs associated with SC35 splicing domains', *BMC Genomics*, 8: 39.

Kharchenko, P. V., L. Silberstein, and D. T. Scadden. 2014. 'Bayesian approach to single-cell differential expression analysis', *Nat Methods*, 11: 740-2.

Kiselev, V. Y., T. S. Andrews, and M. Hemberg. 2019. 'Challenges in unsupervised clustering of single-cell RNA-seq data', *Nat Rev Genet*, 20: 273-82.

Kiselev, V. Y., K. Kirschner, M. T. Schaub, T. Andrews, A. Yiu, T. Chandra, K. N. Natarajan, W. Reik, M. Barahona, A. R. Green, and M. Hemberg. 2017. 'SC3: consensus clustering of single-cell RNA-seq data', *Nat Methods*, 14: 483-86.

Kotliarov, Yuri, Rachel Sparks, Andrew J Martins, Matthew P Mulè, Yong Lu, Meghali Goswami, Lela Kardava, Romain Banchereau, Virginia Pascual, and Angélique Biancotto. 2020. 'Broad immune activation underlies shared set point signatures for vaccine responsiveness in healthy individuals and disease activity in patients with lupus', *Nature Medicine*, 26: 618-29.

Kovats, S., E. K. Main, C. Librach, M. Stubblebine, S. J. Fisher, and R. DeMars. 1990. 'A class I antigen, HLA-G, expressed in human trophoblasts', *Science*, 248: 220-3.

Lancichinetti, Andrea, M Irmak Sirer, Jane X Wang, Daniel Acuna, Konrad Körding, and Luís A Nunes Amaral. 2015. 'High-reproducibility and high-accuracy method for automated topic classification', *Physical Review X*, 5: 011007.

Lawson, D. A., N. R. Bhakta, K. Kessenbrock, K. D. Prummel, Y. Yu, K. Takai, A. Zhou, H. Eyob, S. Balakrishnan, C. Y. Wang, P. Yaswen, A. Goga, and Z. Werb. 2015. 'Single-cell analysis reveals a stem-cell program in human metastatic breast cancer cells', *Nature*, 526: 131-5.

Lindström, N. O., G. De Sena Brandine, A. Ransick, and A. P. McMahon. 2019. 'Single-Cell RNA Sequencing of the Adult Mouse Kidney: From Molecular Cataloging of Cell Types to Disease-Associated Predictions', *Am J Kidney Dis*, 73: 140-42.

Mabbott, N. A., J. K. Baillie, H. Brown, T. C. Freeman, and D. A. Hume. 2013. 'An expression atlas of human primary cells: inference of gene function from coexpression networks', *BMC Genomics*, 14: 632.

Min, J. W., W. J. Kim, J. A. Han, Y. J. Jung, K. T. Kim, W. Y. Park, H. O. Lee, and S. S. Choi. 2015. 'Identification of Distinct Tumor Subpopulations in Lung Adenocarcinoma via Single-Cell RNA-seq', *PLoS One*, 10: e0135817.

Miyamoto, D. T., Y. Zheng, B. S. Wittner, R. J. Lee, H. Zhu, K. T. Broderick, R. Desai, D. B. Fox, B. W. Brannigan, J. Trautwein, K. S. Arora, N. Desai, D. M. Dahl, L. V. Sequist, M. R. Smith, R. Kapur, C. L. Wu, T. Shioda, S. Ramaswamy, D. T. Ting, M. Toner, S. Maheswaran, and D. A. Haber. 2015. 'RNA-Seq of single prostate CTCs implicates noncanonical Wnt signaling in antiandrogen resistance', *Science*, 349: 1351-6.

Patel, A. P., I. Tirosh, J. J. Trombetta, A. K. Shalek, S. M. Gillespie, H. Wakimoto, D. P. Cahill, B. V. Nahed, W. T. Curry, R. L. Martuza, D. N. Louis, O. Rozenblatt-Rosen, M. L. Suvà, A. Regev, and B. E. Bernstein. 2014. 'Single-cell RNA-seq highlights intratumoral heterogeneity in primary glioblastoma', *Science*, 344: 1396-401.

Reyfman, P. A., J. M. Walter, N. Joshi, K. R. Anekalla, A. C. McQuattie-Pimentel, S. Chiu, R. Fernandez, M. Akbarpour, C. I. Chen, Z. Ren, R. Verma, H. Abdala-Valencia, K. Nam, M. Chi, S. Han, F. J. Gonzalez-Gonzalez, S. Soberanes, S. Watanabe, K. J. N. Williams, A. S. Flozak, T. T. Nicholson, V. K. Morgan, D. R. Winter, M. Hinchcliff, C. L. Hrusch, R. D. Guzy, C. A. Bonham, A. I. Sperling, R. Bag, R. B. Hamanaka, G. M. Mutlu, A. V. Yeldandi, S. A. Marshall, A. Shilatifard, L. A. N. Amaral, H. Perlman, J. I. Sznajder, A. C. Argento, C. T. Gillespie, J. Dematte, M. Jain, B. D. Singer, K. M. Ridge, A. P. Lam,

A. Bharat, S. M. Bhorade, C. J. Gottardi, G. R. S. Budinger, and A. V. Misharin. 2019. 'Single-Cell Transcriptomic Analysis of Human Lung Provides Insights into the Pathobiology of Pulmonary Fibrosis', *Am J Respir Crit Care Med*, 199: 1517-36.

Rizvi, A. H., P. G. Camara, E. K. Kandror, T. J. Roberts, I. Schieren, T. Maniatis, and R. Rabadan. 2017. 'Single-cell topological RNA-seq analysis reveals insights into cellular differentiation and development', *Nat Biotechnol*, 35: 551-60.

Saigusa, Ryosuke, and Klaus Ley. 2020. 'CITE-Seq Hits Vascular Medicine', *Clinical Chemistry*, 66: 751-53.

Satija, R., J. A. Farrell, D. Gennert, A. F. Schier, and A. Regev. 2015. 'Spatial reconstruction of single-cell gene expression data', *Nat Biotechnol*, 33: 495-502.

Team, R Core. 2014. "R: a language and environment for statistical computing. Version 3.1. 2 [computer program]. R Foundation for Statistical Computing, Vienna, Austria." In.

Tian, L., X. Dong, S. Freytag, Lê Cao KA, S. Su, A. JalalAbadi, D. Amann-Zalcenstein, T. S. Weber, A. Seidi, J. S. Jabbari, S. H. Naik, and M. E. Ritchie. 2019. 'Benchmarking single cell RNA-sequencing analysis pipelines using mixture control experiments', *Nat Methods*, 16: 479-87.

Treutlein, B., D. G. Brownfield, A. R. Wu, N. F. Neff, G. L. Mantalas, F. H. Espinoza, T. J. Desai, M. A. Krasnow, and S. R. Quake. 2014. 'Reconstructing lineage hierarchies of the distal lung epithelium using single-cell RNA-seq', *Nature*, 509: 371-5.

Villani, A. C., R. Satija, G. Reynolds, S. Sarkizova, K. Shekhar, J. Fletcher, M. Griesbeck, A. Butler, S. Zheng, S. Lazo, L. Jardine, D. Dixon, E. Stephenson, E. Nilsson, I. Grundberg, D. McDonald, A. Filby, W. Li, P. L. De Jager, O. Rozenblatt-Rosen, A. A. Lane, M. Haniffa, A. Regev, and N. Hacohen. 2017. 'Single-cell RNA-seq reveals new types of human blood dendritic cells, monocytes, and progenitors', *Science*, 356.

Wickham, H. 'ggplot2: elegant graphics for data analysis Springer; New York; 2009', *URL http://had. co. nz/ggplot2/book.[Google Scholar]*.

Witten, Ian H, and Eibe Frank. 2002. 'Data mining: practical machine learning tools and techniques with Java implementations', *Acm Sigmod Record*, 31: 76-77.

Zappia, L., B. Phipson, and A. Oshlack. 2017. 'Splatter: simulation of single-cell RNA sequencing data', *Genome Biol*, 18: 174.