Distinct and Common Neural Coding of Semantic and Non-semantic Control Demands

Zhiyao Gao[1], Li Zheng[2], Rocco Chiou[3], André Gouws[1], Katya Krieger-Redwood[1], Xiuyi Wang[1], Dominika Varga[4], Matthew A. Lambon Ralph[3], Jonathan Smallwood[5], Elizabeth Jefferies[1]

[1] Department of Psychology, University of York, Heslington, York YO10 5DD, United Kingdom

[2] Department of Psychology, University of Arizona, Tucson, AZ 85719, USA

[3] MRC Cognition and Brain Sciences Unit, University of Cambridge, Cambridge CB2 1TN, United Kingdom

[4] School of Psychology, University of Sussex, Brighton, BN1 9RH, United Kingdom

[5] Department of Psychology, Queen's University, Kingston, ON K7L 3N6, Canada

Abbreviated title:

Neural coding of semantic and non-semantic control

Acknowledgements

This work was sponsored by the European Research Council (Project ID: 771863 - FLEXSEM Project).

Author contributions

Z.G. and E.J. designed the experiment. Z.G. performed the study. Z.G. and L.Z. analysed the data. Z.G., E.J. wrote the original manuscript, R.C. J.S. M.A.L.R. reviewed and edited the manuscript.

Competing financial interests

The authors declare no competing financial interests.

Corresponding author:

Elizabeth Jefferies: beth.jefferies@york.ac.uk

Abstract

The flexible retrieval of knowledge is critical in everyday situations involving problem solving, reasoning and social interaction. Current theories have emphasised the importance of a left-lateralised semantic control network (SCN) in supporting flexible semantic behaviour. Apart from the SCN, a bilateral multiple-demand network (MDN) is implicated in executive functions across domains. No study, however, has examined whether semantic and non-semantic demands are reflected in a common neural code within regions specifically implicated in semantic control. Using functional MRI and univariate parametric modulation analysis as well as multivariate pattern analysis, we found that semantic and non-semantic demands gave rise to both similar and distinct neural responses across control-related networks. Though activity patterns in SCN and MDN could decode the difficulty of both semantic and verbal working memory decisions, there was no shared common neural coding of cognitive demands in SCN regions. In contrast, regions in MDN showed common patterns across manipulations of semantic and working memory control demands, with successful cross-classification of difficulty across tasks. Therefore, SCN and MDN can be dissociated according to the information they maintain about cognitive demands.

Introduction

Our semantic knowledge encompasses disparate features and associations for any given concept (e.g., APPLE can go with PIE but also HORSE). While this allows us to understand the significance of diverse experiences, it raises the question of how we generate coherent patterns of semantic retrieval that diverge from strong associations in the semantic store. The controlled semantic cognition framework suggests that a distributed neural network manipulates activation within the semantic representational system to generate inferences and behaviours that are appropriate for the context in which they occur (Lambon Ralph et al. 2017). In well-practised contexts, in which the relevant information is robustly encoded, conceptual representations need little constraint from semantic control processes to produce the correct response. In contrast, situations requiring the retrieval of weakly-encoded information, the suppression of strong but currently-irrelevant patterns of retrieval or the emphasis of uncharacteristic features, depend more on control to shape semantic retrieval (Jefferies et al. 2020). Converging evidence from neuroimaging, patient and neuro-modulation studies suggests left inferolateral prefrontal cortex, posterior middle temporal gyrus, pre-supplementary motor area and intraparietal sulcus form a semantic control network (SCN); these sites all respond to diverse manipulations of semantic control demands (Jefferies and Lambon Ralph 2006; Hoffman et al. 2010; Jefferies 2013; Lambon Ralph 2014; Nozari and Thompson-Schill 2016; Lambon Ralph et al. 2017; Chiou et al. 2018).

An outstanding question concerns the degree to which the neural mechanisms underpinning semantic control are specialised for this domain. A bilateral "multiple demand" network (MDN), including frontal, parietal, cingulate and opercular brain regions (Duncan and Owen 2000; Duncan 2010; Fedorenko et al. 2013), supports a diverse range of

cognitively-demanding tasks, including selective attention, working memory (WM), task switching, response inhibition, conflict monitoring and problem-solving (Fedorenko et al. 2013; Fedorenko 2014; Crittenden et al. 2016; Assem et al. 2020; Diachek et al. 2020). Meta-analyses of neuroimaging studies identify a network for semantic control that partially overlaps with MDN (Figure 3; Noonan et al. 2013; Jackson 2020). However, there also appear to be anatomical differences between these networks: regions supporting semantic control extend into more anterior areas of left inferior frontal gyrus, and posterior middle temporal areas, which are not implicated in executive control more generally. Moreover, SCN shows strong left-lateralisation, in contrast to other aspects of control, which are bilateral or even right-lateralized (Gonzalez Alam et al. 2018; Gonzalez Alam et al. 2019; Jefferies et al. 2020).

Moreover, it is still poorly understood whether semantic control demands are analogous to domain-general control processes. Some studies have argued that there are important differences in the processes supported by MDN and SCN: for example, when semantic category is used as the basis of go-no go decisions, behavioural inhibition is still associated with right-lateralised MD regions, not activation within SCN (Gonzalez-Alam et al., 2018). This suggests that semantic control processes are only recruited when conceptual information itself must be controlled, and not whenever semantic tasks become hard. Semantic control might involve distinct neural processes not shared by the control of action or visual attention, since controlled semantic retrieval draws on heteromodal memory representations and information integration, supported by DMN (Price et al. 2015; Margulies et al. 2016; Price et al. 2016; Pylkkänen 2019; Lanzoni et al. 2020), along with control processes (Davey et al. 2016). The SCN sits at the intersection of DMN and MDN, showing structural and intrinsic functional connectivity to regions in both networks (Davey

et al., 2016) and falling between these networks on whole-brain connectivity and functional gradients (Wang et al. 2020): in this way, it might support functional coupling between DMN and MDN in the left-lateralised semantic network. While a few studies have manipulated both linguistic and non-linguistic demands, observing common modulation of the neural response in anterior insula and/or anterior cingulate cortex (Eckert et al. 2009; Erb et al. 2013; Fedorenko et al. 2013; Piai et al. 2013), prior studies failed to match the task structure and task difficulty across these domains. More importantly, we are still lacking knowledge about whether MDN and SCN regions share the same neural coding.

Here, we conducted a pair of fMRI studies to assess the nature of neural signals relating to semantic and domain-general control demands. First, we contrasted parametric manipulations of difficulty for semantic judgements (by varying the strength of association) and verbal working memory (by varying load), to identify sites specifically implicated in semantic and non-semantic control. We matched the task/trial structure and input modality across semantic and non-semantic domains. Next, using pattern classification analyses which examine the multivariate pattern of activation across voxels (Haynes and Rees 2006; Norman et al. 2006; Tong and Pratte 2012; Haynes 2015), we tested whether regions in each network could decode semantic demands and working memory load. Finally, we assessed whether SCN and MD regions could cross-classify difficulty across semantic and non-semantic judgements. In this way, the current study tests the extent to which a shared neural currency underlies both semantic control and working memory load.

Materials and Methods

Participants

A group of 32 young healthy participants aged 19~35 (mean age = 21.97 ±⬚3.47 years; 19 females) was recruited from the University of York. They were all right-handed, native English speakers, with normal or corrected-to-normal vision and no history of psychiatric or neurological illness. The study was approved by the Research Ethics Committee of the York Neuroimaging Centre. All volunteers provided informed written consent and received monetary compensation or course credit for their participation. The data from one task was excluded for four participants due to head motion, and one additional working memory dataset was excluded due to errors in recording the responses. The final sample included 28 participants for the semantic task and 27 participants for the working memory task, with 26 participants completing both tasks.

Design

Participants completed two experiments, presented in separate sessions. The first session included four functional scans while participants performed a semantic association task. The second session included three working memory functional scans and a structural scan (see Figure 1 for an example of each task). A slow event-related design was adopted for the two sessions in order to better characterise the activation pattern for each trial. Each trial lasted 9s and each run included 48 trials in the semantic task and 40 trials in the working memory task.

Semantic association task design

Participants were asked to decide if pairs of words were semantically associated or not. The stimuli were 192 English concrete noun word-pairs. We excluded any abstract nouns and items drawn from the same taxonomic category, so that only thematic links were evaluated in this task (i.e. forest – path or bath – duck; these items are related because they are found or used together). The strength of the thematic link between the items varied parametrically from no clear link to highly related; in this way, participants were free to decide based on their own experience if the words had a discernible semantic link. There were no 'correct' and 'incorrect' responses: instead, we expected slower response times and less convergence across participants for items judged to be 'related' when the associative strength between the items was weak, and for items judged to be 'unrelated' when the associative strength between the items was strong (see behavioural below). Overall, there were roughly equal numbers of 'related' and 'unrelated' responses across participants.

Each trial began with a visually presented word (WORD-1) which lasted 1.5s, followed by a fixation presented at the centre of the screen for 1.5s. Then, the second word (WORD-2) was presented for 1.5s, followed by a blank screen for 1.5s. Participants had 3s from the onset of WORD-2 to judge whether this word pair was semantically associated or not by pressing one of two buttons with their right hand (using their index and middle fingers). During the inter-trial interval (3s), a red fixation cross was presented until the next trial began. Both response time (RT) and response choice were recorded. Participants finished 4 runs of the semantic task, each lasting 7.3 min. Before the scan, they completed a practice session to familiarise themselves with the task and key responses (see Figure 1 for task schematic).

Semantic stimuli

To quantify the strength of semantic relationships in the association task, distributed representations of word meanings were obtained from the word2vec neural network, trained on the 100 billion-word Google News dataset (Mikolov et al. 2013). In common with other distributional models of word meaning, the word2vec model represents words as high-dimensional vectors with 300 dimensions, where the similarity of two words' vectors indicates that they appear in similar contexts, and thus are assumed to have related meanings. The word2vec vectors used here were found to outperform other available vector datasets in predicting human semantic judgements in a recent study (Pereira et al. 2016). We defined the strength of the semantic relationship between words using the cosine similarity method. This value was calculated for each word pair presented as a trial, allowing us to characterise the trials on a continuum from strongly related to unrelated.

While word2vec values were higher for trials judged to be semantically related overall (see below), there was considerable variation for both related and unrelated judgements. Since different numbers of items were judged to be thematically related and unrelated across participants, we split related and unrelated trials for each participant into five levels according to their word2vec value, each with the same number of word-pairs. In order to simplify the presentation of the results, the analysis was based on these five levels of word2vec unless otherwise stated. We reasoned that higher word2vec values would be associated with lower task demands for trials judged to be related, and with higher task demands for trials judged to be unrelated. This was confirmed by behavioural analyses (see below). Word2vec values did not correlate with psycholinguistic variables from N-Watch (Davis 2005), including word length (number of letters: Word1, $r = 0.099$, $p = 0.17$; Word2, r

= 0.113, p = 0.119), word frequency (Word1, r = 0.033, p = 0.657; Word2, r = 0.111, p =

0.127) or imageability (Word1, r = -0.004, p = 0.958; Word2, r = -0.010, p = 0.901). We also

computed a semantic decision consistency index for each word pair by calculating how

many participants judged it to be semantically associated (expressed as a proportion of the

total participants tested). Word2vec was significantly positively correlated with this

consistency value (r = 0.773, p < 0.0001), showing that people were more likely to judge

word pairs as related when they had high word2vec values.

Verbal working memory task

The working memory task had a similar structure to the semantic task (see Figure 1). Each

trial began with a letter string (3 to 7 letters) presented at the centre of the screen for 1.5s,

followed by a fixation presented for 1.5s. Participants were asked to remember these letters.

Next, two letters were shown on the screen for 1.5s. Participants judged whether both of

them had been presented in the letter string by pressing one of two buttons within 3s

(participants were told the order of the letters on the screen did not matter). Then a red

fixation cross was presented for 3s, until the start of the next trial. Participants completed 3

runs, each containing 40 trials and lasting for 6.1 minutes. The working memory load was

manipulated by varying the number of letters memorised in each trial; there were five levels

of load from 3 to 7 letters (to match the five levels of word2vec in the semantic task), with 8

trials at each level in each run, presented in a random order. Both response time (RT) and

accuracy were recorded, and participants were asked to respond as quickly and accurately

as possible.

Mixed-Effects Modelling of Behavioural Data

Since participants judged different numbers of items to be semantically related and
unrelated in the semantic task, mixed-effects modelling was used for the analysis of the
behavioural data. This approach is particularly suitable when the number of trials in each
condition differs across participants (Mumford and Poldrack 2007; Ward et al. 2013).
Semantic association strength (or working memory load) was used as a predictor of the
decision participants made (in the semantic task: judgements of whether the words were
related or unrelated; in the working memory task: whether the response was correct or
incorrect) and, in separate models, how long the reaction time this decision took (i.e., RT).
Participants were included as a random effect. The mixed-effects model was implemented
with lme4 in R (Bates et al. 2014). We used the likelihood ratio test (i.e., Chi-Square test) to
compare models with and without the effect of semantic association strength and working
memory load level, in order to determine whether the inclusion of the difficulty
manipulations significantly improved the model fit.

Neuroimaging data acquisition

Imaging data were acquired on a 3.0 T GE HDx Excite Magnetic Resonance Imaging (MRI)
scanner using an eight-channel phased array head coil at the York Neuroimaging Centre. A
single-shot T2*-weighted gradient-echo, EPI sequence was used for functional imaging
acquisition with the following parameters: TR/TE/θ = 1500 ms/15 ms/90°, FOV = 192 × 192
mm, matrix = 64 × 64, 3 x 3 x 4 mm voxel size, 32 axial slices without a gap. Slices were tilted
approximately 30° relative to the AC-PC line to improve the signal-to-noise ratio in the
anterior temporal lobe and orbitofrontal cortex (Deichmann et al. 2003; Wimmer and
Büchel 2019). Anatomical MRI was acquired using a T1-weighted, 3D, gradient-echo pulse-

sequence (MPRAGE). The parameters for this sequence were as follows: TR/TE/θ = 7.8s/2.3 ms/20°, FOV = 256 × 256 mm, matrix = 256 × 256, and slice thickness = 1 mm. A total of 176 sagittal slices were acquired to provide high-resolution structural images of the whole brain.

fMRI Data Pre-processing Analysis

Image pre-processing and statistical analysis were performed using FEAT (FMRI Expert Analysis Tool) version 6.00, part of FSL (FMRIB software library, version 5.0.11, www.fmrib.ox.ac.uk/fsl). The first 4 volumes before the task were discarded to allow for T1 equilibrium. The remaining images were then realigned to correct for head movements. Translational movement parameters never exceeded one voxel in any direction for any participant or session. Data were spatially smoothed using a 5 mm FWHM Gaussian kernel. The data were filtered in the temporal domain using a nonlinear high-pass filter with a 100 s cut-off. A two-step registration procedure was used whereby EPI images were first registered to the MPRAGE structural image (Jenkinson and Smith 2001). Registration from MPRAGE structural image to standard space was further refined using FNIRT nonlinear registration (Andersson et al. 2007).

Univariate Parametric Modulation Analysis

We examined the parametric effect of semantic control demands (i.e. the strength of association between WORD-1 and WORD-2) in the decision phase of the task, using general linear modelling within the FILM module of FSL. Trials judged to be semantically related (YES trials) and unrelated (NO trials) by participants were separately modelled, using their demeaned word2vec values as the weight, and the RT of each trial as the duration. In addition, we included unmodulated regressors for the trials judged to be related and unrelated, as well as regressors containing WORD-1 and the within-trial fixation between

the words. The second fixation interval between the trials was not coded and thus treated as an implicit baseline. Regressors of no interest were included to account for head motion. Three contrasts (related vs. baseline, unrelated vs. baseline, and related vs. unrelated) were defined to examine the effect of semantic control demands on trials judged to be related and unrelated.

The working memory task was analysed in a similar way. Correct and incorrect trials were separately modelled. For correct trials, the parametric effect of difficulty was modelled by including memory load as the weight, and reaction time as the duration of each trial; we also included unmodulated regressors for these trials. In addition, we included three unmodulated regressors: incorrect trials, the first word and the first within-trial fixation. The second fixation interval between the trials was not coded and thus treated as an implicit baseline. Regressors of no interest were included to account for head motion. Two contrasts (correct > baseline and the reverse) were defined to examine how memory load parametrically modulated neural activation in the brain.

For both semantic and WM models, a higher-level analysis was conducted to perform cross-run averaging using a fixed-effects model. These contrasts were then carried forward into the group-level analysis, using FMRIB's Local Analysis of Mixed Effects 1 + 2 with automatic outlier detection (Beckmann et al. 2003; Woolrich et al. 2004; Woolrich 2008). Unless otherwise noted, group images were thresholded using cluster detection statistics, with a height threshold of $z > 3.1$ and a cluster probability of $p < 0.05$, corrected for whole-brain multiple comparisons using Gaussian Random Field Theory. The same threshold was used for both univariate and MVPA analysis. Uncorrected statistical maps are available to view online: (https://neurovault.org/collections/8710/).

Multivoxel Pattern Analysis

Single-trial Response Estimation

We used the least square-single (LSS) approach to estimate the activation pattern for each trial during the decision phase in the two tasks. Each trial's decision was separately modelled in one regressor and all other trials were modelled together as a second regressor; we also included WORD-1 and the fixation as additional regressors. The same pre-processing procedure as in the univariate analysis was used except that no spatial smoothing was applied. This voxel-wise GLM was used to compute the activation associated with each trial in the two tasks. Classification was performed on t statistic maps, derived from beta weights associated with each regressor, to increase reliability by normalizing for noise (Walther et al., 2016).

Network Selection and Parcellation

We used two complementary multivariate approaches to assess representations of control demands; both network/ROI-based and whole-brain searchlight methods. We used two networks defined from previous studies: the semantic control network (SCN) and multiple-demand network (MDN) (Fedorenko et al. 2013; Jackson 2020) (Fig. 1D). We decomposed these networks into semantic control specific (SCN specific) areas, which did not overlap with MDN; multiple-demand specific (MDN specific) regions, which did not overlap with SCN; and shared control regions identified from the overlap between MDN and SCN. As a comparison, we also examined regions within the semantic network not implicated in control. To identify these regions, we downloaded a semantic meta-analysis from Neurosynth (search term 'semantic'; 1031 contributing studies; http://www.neurosynth.org/analyses/terms/). Then, we removed regions within this

semantic network which overlapped with the two control networks to identify semantic regions predominately associated with semantic representation or more automatic aspects of semantic retrieval, mostly within default-mode network (e.g. in lateral temporal cortex and angular gyrus). All of the voxels within the network maps defined above were included within network-based ROIs. In total, thirty ROIs were defined; four ROIs in semantic non-control areas, three ROIs in SCN areas, six ROIs in the overlap of MDN and SCN, and seventeen ROIs in MDN specific areas; see Figure 3A.

Support Vector Regression Analysis

Epsilon-insensitive support vector regression analysis (SVR) (Drucker et al. 1997) was conducted using a linear support vector machine (SVM) (Chang and Lin 2011) and custom code implemented in MATLAB (The MathWorks) (code is available at: https://osf.io/bau5c/). In contrast to conventional support vector machine classification (SVM), the SVR does not depend on categorical classification (i.e., predictions falling on the correct or incorrect side of a hyperplane); instead, it outputs estimations using a regression approach. This approach was used to estimate the difficulty level or cognitive demand for each trial. For each level of difficulty (based on inverse word2vec for semantic trials judged to be related, word2vec for semantic trials judged to be unrelated and memory load in the working memory task), the test and training data were normalized (i.e., mean subtracted and divided by the standard deviation) across voxels within each region of interest (i.e., searchlight, ROI) (Misaki et al. 2010). This allowed an evaluation of the pattern of activity across voxels without contamination from mean signal differences within the searchlight or ROI across the difficulty levels (i.e., the univariate effect) (Misaki et al. 2010; Jimura and Poldrack 2012; Coutanche 2013). The SVR cost parameter was set to 0.001. For each searchlight or ROI, the

accuracy of SVR prediction was then calculated within-participant, defined as the z-transformed Pearson's correlation coefficient between actual and predicted values of the difficulty parameter for the left-run-out data, with the actual difficulty levels ranging from 1 (easy) to 5 (hard) in both tasks. The epsilon parameter in the SVR model was set to epsilon = 0.01 (Jimura and Poldrack 2012).

For each participant, three separate SVR classifiers were trained to decode cognitive demands: these examined the difficulty of semantic trials judged to be related (difficulty maximised for low association trials), the difficulty of semantic trials judged to be unrelated (difficulty maximised for high association trials), and the difficulty of working memory trials (difficulty maximised for highest memory load). In order to test whether semantic control and executive control share a common neural code, we also performed a series of generalization (cross-classification) analyses, in which classifiers were trained on each task type (semantic related; semantic unrelated; working memory) and tested on the other task types (i.e. trained on semantic related, tested on working memory), resulting in 3-by-3 SVR decoding accuracy types (nine analyses in total). All classification analyses were performed using a leave-one-run-out cross-validation. The semantically-related and unrelated easy and harder decisions showed similar cross-classification effects when these semantic trials were compared with the working memory task (see Supplementary Figure S3). To simplify reporting of these results, we averaged the semantically-related and unrelated trials into one index (combining easy related/unrelated trials and comparing them to hard related/unrelated trials). We also examined generalization of difficulty effects within the semantic domain (i.e. between trials judged to be semantically-related and unrelated). SVR decoding was performed using searchlight and ROI approaches.

For searchlight-based analysis, for each voxel, signals were extracted from a cubic region containing 125 surrounding voxels. The searchlight analysis was conducted in standard space. A random-effects model was used for group analysis. Since no first-level variance was available, an ordinary least square (OLS) model was used.

For the network ROI-based analysis, because the number of voxels in the network ROIs varied and differences in ROI size are likely to influence classifier performance, classification analyses were performed by randomly subsampling 200 voxels from each ROI. This process was repeated for 100 iterations for each ROI and subject, with each iteration involving a different random sample of 200 voxels. To check our results were not influenced by this arbitrary number, in a supplementary analysis we also randomly sampled 300 voxels from each ROI and iterated 100 times for each participant, obtaining very similar results.

Results

Behavioural Results

Linear mixed effects models examined whether associative strength and working memory load were reliable predictors of behaviour. We found that both the strength of the semantic association (word2vec value) and working memory load successfully manipulated task difficulty. For the semantic task, the continuous word2vec value was positively associated with a higher probability that participants would identify a semantic relationship between the words ($\chi2(1) = 2505.4$, $p < 0.001$). When word pairs were grouped into 5 levels according to their word2vec value, the relationship was still significant ($\chi2(1) = 2644.7$, $p < 0.001$). Since we used a continuous manipulation of associative strength, and there is no categorical boundary of word2vec values which can capture the trials reliably judged to be related and unrelated, we were not able to compute a traditional error score for the semantic task.

Mean RT for each level is presented in Figure 1C, separately for related (YES) and unrelated

(NO) decisions. To examine how association strength level modulated RT for trials judged to

be related and unrelated, we performed linear mixed effects analyses with participant as a

between-subject variable and association level as a within-subject variable. This revealed a

significant effect of level of association strength for both related and unrelated decisions.

Association strength level was negatively associated with RT ($\chi2(1) = 146.6$, $p < 0.001$) for

related trials and positively associated with reaction time for unrelated trials ($\chi2(1) = 58.668$,

$p < 0.001$). It was more difficult for participants to retrieve a semantic connection between

two words when strength of association was lower; on the contrary, it was easier for them

to decide there was no semantic connection between word pairs with low word2vec values.

For the working memory task, higher working memory load was associated with lower

accuracy ($\chi2(1) = 108.46$, $p < 0.001$). A further linear mixed effects model with participant as

a between-subject variable and memory load as a within-subject variable revealed a

significant positive relationship between load level and RT for correct responses ($\chi2(1) =$

39.826, $p < 0.001$).

Figure 1. Experiment paradigm and behavioural results. A. Semantic association task; participants were asked to decide if word pairs were semantically related or not. B. Word pair examples for both related and unrelated decisions from one participant, with association strength increasing from Level 1 (L1; little semantic overlap) to Level 5 (L5; high semantic overlap). These trials were assigned to related and unrelated sets of trials on an individual basis for each participant, depending on their decisions, and then split into 5 levels, based on word2vec scores. C. RT for semantic decisions across 5 levels of word2vec for word pairs judged to be related and unrelated. D. Working memory task; participants were asked to decide if two probe letters were presented in a sequence, in any order. E. Working memory load ranged from 3 to 7 items. F. RT for working memory trials across 5 levels of load, for correct and incorrect decisions.

fMRI Results

The Parametric Effect of Word2vec on Brain Activation

We identified brain areas showing an increase or decrease in activation as a function of association strength (using the continuous word2vec scores). It was harder for participants to decide that items were semantically related when they were weakly associated; consequently, we would expect stronger responses in semantic control and multiple demand regions for these trials. It was also harder for participants to decide that items were semantically unrelated when they had greater word2vec values; therefore we would expect opposite effects of word2vec for related and unrelated trials in brain regions supporting demanding semantic decisions. The direct comparison of word2vec effects for semantically-related and unrelated decisions can identify brain areas responding to semantic similarity but not difficulty, while the combination of negative effects of word2vec for related decisions and positive effects of word2vec for unrelated decisions can identify brain regions that respond to the difficulty of semantic decisions, without a confound of semantic relatedness.

For related trials, weaker associations elicited greater activity in regions linked to semantic control in previous studies, including left inferior frontal gyrus (IFG), left middle frontal gyrus (MFG), superior frontal gyrus (SFG) and left posterior middle temporal gyrus (pMTG); see Figure 2A. Similarly, when participants decided that items were unrelated, there was stronger activation in left inferior frontal gyrus, middle frontal gyrus, superior frontal gyrus and frontal orbital cortex (FOC) when these items had higher word2vec scores; see Figure 2B.

We investigated common and distinct effects of semantic control demands across trials classified as related and unrelated. A conjunction analysis revealed that rejecting strongly associated word pairs and accepting weakly associated word pairs recruited common semantic control regions including left inferior frontal gyrus, middle frontal gyrus, superior frontal gyrus and frontal orbital cortex, see Figure 2D. There were no significant differences in the parametric effects of semantic control demands or semantic relatedness for trials judged to be related and unrelated in a direct contrast. There were also no common effects of semantic similarity (i.e. positive effects of word2vec that were shared across related and unrelated decisions).

In addition, although we could not compute task accuracy in our main analysis (since we manipulated strength of association in a continuous way, and participants were asked to split this distribution into related and unrelated trials), a supplementary control analysis removed trials with unexpected word2vec scores, given the decision that was made. An additional regressor was included to capture trials judged to be related even though they had particularly low word2vec values (bottom 25% of word2vec values), and trials judged to be unrelated that had particularly high word2vec values (top 25% of word2vec values). The results were very similar to the analysis above; see Supplementary Figure S1A.

The Parametric Effect of Working Memory Load on Brain Activation and the Comparison with Semantic Control

For correct working memory trials, a significant parametric effect of memory load was found in right middle frontal gyrus, frontal pole (FP) and superior frontal gyrus consistent with

previous studies in which higher working memory loads elicited greater activity in distributed bilateral areas within the multiple-demand network (MDN); see Figure 2C.[1]

We performed further analyses to establish the common and distinct parametric effects of semantic control demands and working memory load. We compared correct working memory trials and word pairs judged to be semantically-related, since participants made YES decisions in both situations. Since semantic relatedness was varied in a continuous fashion while working memory load was manipulated across five levels, we first divided the semantically related trials into five difficulty levels according to their word2vec values, with lower word2vec corresponding to harder trials (re-analysis of the univariate activation for the semantic task using these five levels replicated the findings above and obtained highly similar results, see Supplementary Figure S1B). To simplify the following univariate and multivariate results focussed on the comparison of the semantic and working memory tasks, we used five levels of difficulty or association strength for the thematically related and unrelated decisions, unless otherwise mentioned.

A conjunction analysis showed a significant overlap between semantic control demands and working memory load in superior frontal gyrus and pre-supplementary motor area (pre-SMA); see Figure 2F. Direct contrasts of these semantic and non-semantic difficulty effects revealed stronger effects of difficulty in the working memory than the semantic task in right-lateralized regions mainly within the multiple-demand network, including right middle frontal gyrus, frontal pole and supramarginal gyrus (SMG); Figure 2G. There was a greater effect of semantic control demands in distributed areas in the left hemisphere, including IFG,

---

[1] A supplementary analysis, thresholded at Z > 2.6, revealed a more distributed neural substrate for working memory load including bilateral middle frontal gyrus, precentral gyrus and occipital fusiform cortex; see Supplementary Figure S2A.

frontal orbital cortex, superior frontal gyrus, lateral occipital cortex (LOC), precuneus, hippocampus, parahippocampal gyrus and temporal fusiform, consistent with previous observations that semantic control is strongly left-lateralized; Figure 2E. A supplementary ROI-based analysis using percent signal change to directly compare the parametric effect of difficulty against implicit baseline in the two tasks showed that the task differences in most of the clusters in Figure 2E and Figure 2G were driven by increased responses to more difficult trials, and not solely by negative parametric effects of difficulty in the other task (see detailed information in Supplementary Figure S2B).

Figure 2. Univariate results with cluster thresholded at Z = 3.1, p = 0.05. A. Parametric modulation effect of associative strength for trials judged to be semantically related. B. Parametric modulation effect of associative strength for trials judged to be unrelated. C. Parametric modulation effect of working memory for correct trials. D. The conjunction of semantic control parametric effects across trials judged to be related and unrelated (i.e. negative word2vec for related trials and positive word2vec for unrelated trials). E. Areas showing a stronger parametric effect of control demands for

semantic judgements (negative effect of word2vec for related trials) compared to working memory (effect of memory load for correct trials). F. The conjunction of the parametric modulation effect for semantic control (from related trials) and working memory load (correct trials). G. A larger parametric modulation effect for working memory load (correct trials) compared with semantic control demands (negative effect of word2vec on semantically-related trials). There are no additional clusters within brain views not shown for each contrast.

Neural Coding of Semantic and Working Memory Demand in Large-scale Brain Networks

In order to test whether the same neural code supported semantic control demands and working memory load, we examined classification of control demands in each task, and cross-classification of difficulty across tasks, within MDN and SCN. We performed a series of SVR decoding analyses in ROIs selected to fall within the following networks: (i) sites within the semantic network but not implicated in control; (ii) SCN (defined as voxels within the semantic control network identified by Noonan et al. (2013) and updated by Jackson (2020), and yet outside the MDN); (iii) regions common to both SCN and MDN; (iv) MDN (defined as voxels within the multiple-demand network identified by Fedorenko et al. (2013), and not within the SCN. For the semantic task, word2vec (as a measure of relatedness) and difficulty (as assessed by behavioural performance) show an opposite relationship for trials judged to be related and unrelated. We therefore reasoned that a classifier sensitive to semantic control and/or executive demands would show a positive correlation between actual and predicted control demands when trained on related trials (which had low word2vec values for more difficult trials) and then tested on unrelated trials (which had high word2vec values for more difficult trials), or vice versa. In contrast, brain regions showing a negative correlation across these trial types would be sensitive to the associative strength of the presented items, irrespective of the subsequent judgement. Moreover, brain regions able to

cross-classify difficulty between semantic and working memory tasks are sensitive to domain-general control demands. In contrast, brain regions sensitive to difficulty in one or both tasks that do not show this task cross-classification may reflect task-specific control processes, and not domain-general control.

The within-task and between-task classification results are summarised in Figure 3. We found the difficulty of both tasks could be decoded across all four networks (compared to chance level, all p values < 0.001; all networks survived Bonferroni correction). There was also significant generalization of difficulty within the semantic domain (between semantically-related and unrelated trials) in all control networks (all p < 0.001), and also in non-control-semantic regions (p = 0.002). All p values were adjusted by Bonferroni correction.

However, this global sensitivity to difficulty across tasks and networks does not test whether the neural representation of difficulty was equivalent across tasks. Cross-classification between the semantic and working memory tasks was found only for the MDN-only regions and MDN+SCN regions for Semantic2WM (p = 0.018 and p = 0.012, respectively, which both with Bonferroni correction applied). The SCN-only and non-control-semantic regions were unable to cross-classify difficulty across these different language tasks (p = 0.594 and p = 0.891, respectively, with Bonferroni correction applied). These results indicate that semantic demand and working memory load did not share a common neural code in semantic-only networks, although they did in multiple-demand regions. This result demonstrates that semantic demand is not analogous to other types of control within the SCN.

A series of one-way repeated-measures ANOVA including the within-participant factors of brain network (with 4 levels) were used to examine the neural representation of cognitive

demands for each classification type. We found a significant main effect of brain network for the semantic difficulty decoding (SEM) ($F_{(2.242,56.044)}$ = 6.869, p = 0.001, Greenhouse-Geisser corrected). Post-hoc paired sample t-tests revealed significant better neural coding of semantic difficulty in SCN+MDN regions than non-control-semantic regions and MDN-only regions (p = 0.006 and p = 0.01 with Bonferroni correction applied, respectively), suggesting a more important role of SCN related regions than MDN regions in representing semantic control demands. There was no reliable difference of brain networks for the decoding accuracy of WM load ($F_{(2.302,57.553)}$ = 2.363, p = 0.096, Greenhouse-Geisser corrected). There was a significant main effect of brain network for cross-condition decoding accuracy within the semantic domain (between related and unrelated decisions; $F_{(2.305,57.623)}$ = 5.859, p = 0.003, Greenhouse-Geisser corrected): post-hoc t-tests revealed there were reliable differences between non-control-semantic regions compared with SCN+MDN regions and MDN-only regions (p = 0.001 and p = 0.023 after Bonferroni correction, respectively), with the control regions showing better decoding. For the cross-task classification, there was a significant main effect of brain networks ($F_{(2.462,61.551)}$ = 6.194, p = 0.002, Greenhouse-Geisser corrected), post-hoc t-tests revealed higher decoding accuracy in SCN+MDN and MDN-only than in non-control-semantic regions (p = 0.002 and p = 0.038 with Bonferroni correction applied, respectively). These results demonstrate the critical role of SCN regions in representing the unique neural coding of semantic control demands, alongside the roles of MDN-only and MDN+SCN regions in representing the neural coding of both semantic and non-semantic control demands.

To further check the robustness of our results, we performed a series of control analyses: 1) we randomly subsampled different numbers of voxels in each ROI in each network; 2) we examined a subsample of the voxels within whole networks, not restricted to specific ROIs

in each iteration; 3) we ran an additional whole brain searchlight analysis using the same

methods; 4) we assessed the prediction accuracy for semantically related and unrelated

trials separately, to validate the use of an averaged index 'SEM' for semantic domain

decoding in our analysis. All of these control analyses support our key conclusions; details

are provided in Supplementary Figures S3 to S6.

Figure 3. Decoding cognitive demand in large-scale brain networks; bars reflect average accuracy

which is different from the conventional SVM classification and instead measures correlation

(Fisher's z-transformed) between actual task demand (difficulty) and predicted task demand. A.

Brain regions for each network. B. SEM: The decoding accuracy for semantically related and

unrelated were averaged to produce a single semantic score (see also Supplementary Figures S3 to S6). WM: Decoding accuracy for WM correct trials. R2U: Cross-condition classification between semantic related and unrelated trials. Semantic2WM: Cross-task classification between semantic difficulty and WM load. Cross-task decoding was not significantly greater than chance level (0) in the 'semantic, not control' and SCN networks, and significantly higher than chance level in MDN+SCN regions and MDN ($p = 0.012$ and $p = 0.018$, respectively, with Bonferroni correction applied). All other decoding accuracy results are significantly higher than chance level in all networks ($P < 0.001$). Bonferroni correction was used, ***$p < 0.001/4$. **$p < 0.01/4$. *$p < 0.05/4$.

Discussion

This study parametrically manipulated the difficulty of semantic and verbal working memory judgements to delineate common and distinct neural mechanisms supporting control processes in these two domains. Across two experiments, we investigated the brain's univariate and multivariate responses to different manipulations of difficulty: in a semantic relatedness task, we varied the strength of association between probe and target words, while in a verbal working memory task, we manipulated the number of items to be maintained (working memory load). Retrieving semantic links between weakly associated words is known to elicit stronger activation within the "semantic control network" (SCN) (Noonan et al. 2013; Jackson 2020), while higher loads in working memory are associated with greater responses within the "multiple demand network" (MDN) (Fedorenko et al. 2013) – particularly, left-lateralised parts of this network for verbal working memory (Emch et al. 2019). This comparison is therefore ideal to establish similarities and differences in the neural basis of these forms of control, with any divergence unlikely to be accounted for by the use of language (as both tasks were verbal in nature). We obtained convergent evidence across analyses for both common and distinct neural responses to difficulty across networks.

Dorsolateral prefrontal cortex and pre-supplementary motor area (within MDN) showed a common response to difficulty across tasks; in decoding analyses, MDN showed common patterns of activation across manipulations of semantic and non-semantic demands, and cross-classification of difficulty across tasks. In contrast, left inferior frontal gyrus within SCN showed an effect of difficulty that was greater for the semantic task; moreover, there was no shared neural coding of cognitive demands in SCN regions, confirming that semantic control has a neural basis distinct from the effects of working memory load.

The semantic control network, encompassing left inferior frontal gyrus and posterior middle temporal gyrus, is known to activate across a wide range of manipulations of semantic control demands – including a stronger response for weak associations, ambiguous words, and multiple distractors (Noonan et al. 2013; Davey et al. 2016; Jackson 2020). Since these regions are implicated in semantic cognition, as well as in control processes, one point of contention is the extent to which semantic retrieval per se, which is potentially increased in more demanding conditions, can explain this pattern of results. A unique strength of this study is that we can distinguish the impacts of semantic control and semantic similarity through the comparison of difficulty in trials judged by participants to be related and unrelated. This is because semantic similarity has opposite effects of difficulty in these two sets of trials: when participants decide there is a semantic link between two words, more control is needed to make this link when the words are more weakly associated; in contrast, when participants decide there is no semantic link between two words, more control is needed for this decision when the words are more strongly associated. The univariate analyses found equivalent effects of difficulty in left inferior frontal gyrus for trials judged to be related and unrelated; consequently, we can conclude this site is sensitive to the difficulty of semantic decisions; moreover, it is not sensitive to the semantic overlap

between the items that are presented. This is exactly the pattern that we would expect for brain regions implicated in semantic control but not long-term conceptual similarity.

In addition to investigating the involvement of SCN and MDN in semantic and non-semantic tasks differing in difficulty, we examined the characteristics of cognitive control in multivariate analyses of activation patterns in large scale networks using SVR decoding for the first time. To avoid circularity, we performed this decoding within large, spatially discontinuous networks identified from independent studies examining semantic and domain general control demands (Fedorenko et al. 2013; Jackson 2020). Our results revealed significant information about semantic demands within both SCN and MDN; however, the decoding of semantic difficulty was more accurate in MDN regions that also lie within the SCN (i.e., IFG, pre-SMA, ITG) than within other MDN regions, pointing to functional heterogeneity within this network (Dixon et al. 2018). In addition, decoding generalization analysis provided strong evidence that semantically-related and unrelated judgements share the same neural code relating to difficulty in both of these networks (despite opposing effects of semantic similarity). We additionally demonstrated that working memory load is reflected in the activation patterns of SCN as well as MDN; both networks are sensitive to the difficulty of both semantic and non-semantic tasks. Importantly, we were not able to decode difficulty across tasks in SCN (when training on working memory load and testing on semantic association strength or vice versa), indicating that the multivariate neural codes relating to the difficulty of semantic and working memory judgements were distinct in SCN.

We examined the decoding of task demands within parts of the semantic network not implicated in control processes, primarily regions within default mode network (DMN;

including anterior lateral temporal cortex and angular gyrus). Decoding of task difficulty was less accurate in DMN than in control networks – yet semantic regions not implicated in control could still decode difficulty, consistent with literature showing that DMN increases its connectivity to executive cortex during control-demanding semantic retrieval (Krieger-Redwood et al. 2015). It may be these varying patterns of connectivity that are decodable (Cole et al. 2013). These results add to growing evidence that DMN contributes to controlled as well as more automatic aspects of cognition, even as it deactivates (Elton and Gao 2015; Raichle 2015; Vatansever et al. 2015; Vatansever et al. 2017).

The current study, to our knowledge, is the first to test whether semantic and non-semantic demands share a common neural currency in the brain via cross-classification analyses. Converging evidence from both ROI/Network and searchlight-based analyses revealed that only regions in MDN (including the overlap with SCN) could cross-classify task difficulty across domains. There was no such common currency in SCN-specific regions or non-control semantic areas. As proposed by Duncan (2010, 2013, 2016), MDN captures an abstract code relating to the difficulty of decisions across multiple domains. Frontal-parietal regions in MDN have been shown to flexibly represent goal-directed information, including visual, auditory, motor, and rule information, to support context-appropriate behaviour (Cole et al. 2013; Crittenden et al. 2016; Woolgar et al. 2016; Bhandari et al. 2018). Our results suggest that SCN diverges from this pattern in important ways. Semantic cognition is thought to emerge from heteromodal brain regions (Lambon Ralph et al. 2017); in line with this, a heteromodal control network which only partially overlaps with MDN has been shown to support the retrieval of both verbal and non-verbal information (Krieger-Redwood et al. 2015). Semantic control processes could regulate the activation of semantic features, thought to draw on unimodal systems supporting vision, audition and action etc. – for

example, when linking dog to beach, activation might be focussed on running, swimming and digging actions, as opposed to the physical features of a dog (such as its ears and tail). These features are thought to rely on interactions between the heteromodal 'hub' within anterolateral temporal cortex and 'spoke' systems in unimodal cortex; consequently, semantic control processes could bias activation towards relevant spoke systems, resulting in a more relevant response within the heteromodal hub when these features are distilled into a coherent meaning (Jackson et al. 2019; Zhang et al. 2020). This process could be largely analogous to the way that MDN regions are thought to bias processing towards task-relevant inputs or sensory features. However, our observation that there are semantic-specific control processes beyond MDN is consistent with the view that this mechanism is supplemented by separate semantic control representations that interface with the long-term conceptual store. This evidence allows us to reject the account that semantic control demands are exactly analogous to other types of cognitive demand.

Contemporary accounts of brain organization suggest that neural function is organized along a connectivity gradient from unimodal regions of sensorimotor cortex, through executive regions to transmodal default mode network (Margulies et al. 2016; Huntenburg et al. 2018). Wang et al. (2020) suggested this gradient can capture the orderly transitions between MDN, SCN and DMN in semantic processing. Given that SCN has greater proximity to DMN than MDN along this principal gradient of connectivity, this network might be able to more efficiently select, retrieve and act on semantic information stored in heteromodal DMN regions. Our results showed a clearly decreasing pattern in cross-task decoding and the representation of working memory load from MDN and shared MDN+SCN regions, through SCN to semantic regions not implicated in control – with this series of networks following the principal gradient (Wang et al. 2020). In a similar way, González-García et al.

(2018) found regions in DMN and MDN have similar representational formats relating to prior experience and occupy adjacent positions on the principle gradient.

In summary, univariate and multivariate pattern analyses provide strong evidence that semantic control demands and working memory load recruit both common and distinct processes in the multiple-demand and semantic control networks, respectively. Though semantic demand and domain general demand are represented in both control networks, there was a shared neural coding only in MDN but strikingly different neural coding of control demands in SCN. These findings indicate SCN and MDN can be dissociated according to the information that they maintain about cognitive demands.

References

Andersson JL, Jenkinson M, Smith S. 2007. Non-linear registration, aka spatial normalisation. FMRIB technial report TR07JA2. 22.

Anzellotti S, Coutanche MN. 2018. Beyond functional connectivity: investigating networks of multivariate representations. Trends in cognitive sciences. 22:258-269.

Assem M, Glasser MF, Van Essen DC, Duncan J. 2020. A Domain-General Cognitive Core Defined in Multimodally Parcellated Human Cortex. Cerebral Cortex.

Bates D, Mächler M, Bolker B, Walker S. 2014. Fitting linear mixed-effects models using lme4. arXiv preprint arXiv:14065823.

Beckmann CF, Jenkinson M, Smith SM. 2003. General multilevel linear modeling for group analysis in FMRI. Neuroimage. 20:1052-1063.

Bhandari A, Gagne C, Badre D. 2018. Just above chance: is it harder to decode information from prefrontal cortex hemodynamic activity patterns? Journal of cognitive neuroscience. 30:1473-1498.

Buckner RL, Andrews-Hanna JR, Schacter DL. 2008. The brain's default network: anatomy, function, and relevance to disease.

Camilleri J, Müller VI, Fox P, Laird AR, Hoffstaedter F, Kalenscher T, Eickhoff SB. 2018. Definition and characterization of an extended multiple-demand network. NeuroImage. 165:138-147.

Chang C-C, Lin C-J. 2011. LIBSVM: A library for support vector machines. ACM transactions on intelligent systems and technology (TIST). 2:1-27.

Chiou R, Humphreys GF, Jung J, Ralph MAL. 2018. Controlled semantic cognition relies upon dynamic and flexible interactions between the executive 'semantic control'and hub-and-spoke 'semantic representation'systems. cortex. 103:100-116.

Cole MW, Reynolds JR, Power JD, Repovs G, Anticevic A, Braver TS. 2013. Multi-task connectivity reveals flexible hubs for adaptive task control. Nat Neurosci. 16:1348-1355.

Cole MW, Reynolds JR, Power JD, Repovs G, Anticevic A, Braver TS. 2013. Multi-task connectivity reveals flexible hubs for adaptive task control. Nature neuroscience. 16:1348.

Coutanche MN. 2013. Distinguishing multi-voxel patterns and mean activation: why, how, and what does it tell us? Cognitive, Affective, & Behavioral Neuroscience. 13:667-673.

Crittenden BM, Mitchell DJ, Duncan J. 2016. Task Encoding across the Multiple Demand Cortex Is Consistent with a Frontoparietal and Cingulo-Opercular Dual Networks Distinction. The Journal of Neuroscience. 36:6147-6155.

Davey J, Thompson HE, Hallam G, Karapanagiotidis T, Murphy C, De Caso I, Krieger-Redwood K, Bernhardt BC, Smallwood J, Jefferies E. 2016. Exploring the role of the posterior middle temporal gyrus in semantic cognition: Integration of anterior temporal lobe with executive processes. Neuroimage. 137:165-177.

Davis CJ. 2005. N-watch: a program for deriving neighborhood size and other psycholinguistic statistics. Behav Res Methods. 37:65-70.

Deichmann R, Gottfried JA, Hutton C, Turner R. 2003. Optimized EPI for fMRI studies of the orbitofrontal cortex. Neuroimage. 19:430-441.

Diachek E, Blank I, Siegelman M, Affourtit J, Fedorenko E. 2020. The domain-general multiple demand (MD) network does not support core aspects of language comprehension: a large-scale fMRI investigation. Journal of Neuroscience. 40:4536-4550.

Dixon ML, De La Vega A, Mills C, Andrews-Hanna J, Spreng RN, Cole MW, Christoff K. 2018. Heterogeneity within the frontoparietal control network and its relationship to the default and dorsal attention networks. Proceedings of the National Academy of Sciences. 115:E1598-E1607.

Dosenbach NU, Fair DA, Miezin FM, Cohen AL, Wenger KK, Dosenbach RA, Fox MD, Snyder AZ, Vincent JL, Raichle ME. 2007. Distinct brain networks for adaptive and stable task control in humans. Proceedings of the National Academy of Sciences. 104:11073-11078.

Drucker H, Burges CJ, Kaufman L, Smola AJ, Vapnik V editors. Support vector regression machines, Advances in neural information processing systems; 1997. 155-161 p.

Duncan J. 2010. The multiple-demand (MD) system of the primate brain: mental programs for intelligent behaviour. Trends in cognitive sciences. 14:172-179.

Duncan J. 2013. The structure of cognition: attentional episodes in mind and brain. Neuron. 80:35-50.

Duncan J, Owen AM. 2000. Common regions of the human frontal lobe recruited by diverse cognitive demands. Trends in neurosciences. 23:475-483.

Eckert MA, Menon V, Walczak A, Ahlstrom J, Denslow S, Horwitz A, Dubno JR. 2009. At the heart of the ventral attention system: The right anterior insula. Human Brain Mapping. 30:2530-2541.

Elton A, Gao W. 2015. Task-positive functional connectivity of the default mode network transcends task domain. Journal of Cognitive Neuroscience. 27:2369-2381.

Emch M, von Bastian CC, Koch K. 2019. Neural Correlates of Verbal Working Memory: An fMRI Meta-Analysis. Frontiers in Human Neuroscience. 13.

Erb J, Henry MJ, Eisner F, Obleser J. 2013. The Brain Dynamics of Rapid Perceptual
Adaptation to Adverse Listening Conditions. The Journal of Neuroscience. 33:10688-
10697.

Fedorenko E. 2014. The role of domain-general cognitive control in language
comprehension. Frontiers in psychology. 5:335.

Fedorenko E, Duncan J, Kanwisher N. 2013. Broad domain generality in focal regions of
frontal and parietal cortex. Proceedings of the National Academy of Sciences.
110:16616-16621.

González-García C, Flounders MW, Chang R, Baria AT, He BJ. 2018. Content-specific
activity in frontoparietal and default-mode networks during prior-guided visual
perception. eLife. 7:e36068.

Gonzalez Alam T, Murphy C, Smallwood J, Jefferies E. 2018. Meaningful inhibition:
Exploring the role of meaning and modality in response inhibition. Neuroimage.
181:108-119.

Gonzalez Alam TRdJ, Karapanagiotidis T, Smallwood J, Jefferies E. 2019. Degrees of
lateralisation in semantic cognition: Evidence from intrinsic connectivity. NeuroImage.
202:116089.

Haynes J-D. 2015. A primer on pattern-based approaches to fMRI: principles, pitfalls, and
perspectives. Neuron. 87:257-270.

Haynes J-D, Rees G. 2006. Decoding mental states from brain activity in humans. Nature
Reviews Neuroscience. 7:523-534.

Hoffman P, Jefferies E, Ralph MAL. 2010. Ventrolateral prefrontal cortex plays an executive
regulation role in comprehension of abstract words: convergent neuropsychological
and repetitive TMS evidence. Journal of Neuroscience. 30:15450-15456.

Huntenburg JM, Bazin P-L, Margulies DS. 2018. Large-scale gradients in human cortical
organization. Trends in cognitive sciences. 22:21-31.

Jackson RL. 2020. The Neural Correlates of Semantic Control Revisited.
bioRxiv.2020.007.2015.204990.

Jackson RL, Rogers TT, Lambon Ralph MA. 2019. Reverse-Engineering the Cortical

    Architecture for Controlled Semantic Cognition. bioRxiv.860528.

Jefferies E. 2013. The neural basis of semantic cognition: converging evidence from

    neuropsychology, neuroimaging and TMS. Cortex. 49:611-625.

Jefferies E, Lambon Ralph MA. 2006. Semantic impairment in stroke aphasia versus

    semantic dementia: a case-series comparison. Brain. 129:2132-2147.

Jefferies E, Thompson H, Cornelissen P, Smallwood J. 2020. The neurocognitive basis of

    knowledge about object identity and events: dissociations reflect opposing effects of

    semantic coherence and control. Philosophical Transactions of the Royal Society B:

    Biological Sciences. 375:20190300.

Jenkinson M, Smith S. 2001. A global optimisation method for robust affine registration of

    brain images. Medical image analysis. 5:143-156.

Jimura K, Poldrack RA. 2012. Analyses of regional-average activation and multivoxel pattern

    information tell complementary stories. Neuropsychologia. 50:544-552.

Krieger-Redwood K, Teige C, Davey J, Hymers M, Jefferies E. 2015. Conceptual control

    across modalities: graded specialisation for pictures and words in inferior frontal and

    posterior temporal cortex. Neuropsychologia. 76:92-107.

Lambon Ralph MA. 2014. Neurocognitive insights on conceptual knowledge and its

    breakdown. Philosophical Transactions of the Royal Society B: Biological Sciences.

    369:20120392.

Lambon Ralph MAL, Jefferies E, Patterson K, Rogers TT. 2017. The neural and

    computational bases of semantic cognition. Nature Reviews Neuroscience. 18:42.

Lanzoni L, Ravasio D, Thompson H, Vatansever D, Margulies D, Smallwood J, Jefferies E.

    2020. The role of default mode network in semantic cue integration. NeuroImage.

    219:117019.

Long NM, Kuhl BA. 2018. Bottom-up and top-down factors differentially influence stimulus

    representations across large-scale attentional networks. Journal of Neuroscience.

    38:2495-2504.

Margulies DS, Ghosh SS, Goulas A, Falkiewicz M, Huntenburg JM, Langs G, Bezgin G, Eickhoff SB, Castellanos FX, Petrides M, Jefferies E, Smallwood J. 2016. Situating the default-mode network along a principal gradient of macroscale cortical organization. Proceedings of the National Academy of Sciences. 113:12574-12579.

Mikolov T, Sutskever I, Chen K, Corrado GS, Dean J editors. Distributed representations of words and phrases and their compositionality, Advances in neural information processing systems; 2013. 3111-3119 p.

Misaki M, Kim Y, Bandettini PA, Kriegeskorte N. 2010. Comparison of multivariate classifiers and response normalizations for pattern-information fMRI. Neuroimage. 53:103-118.

Mumford JA, Poldrack RA. 2007. Modeling group fMRI data. Social cognitive and affective neuroscience. 2:251-257.

Noonan KA, Jefferies E, Visser M, Lambon Ralph MA. 2013. Going beyond inferior prefrontal involvement in semantic control: evidence for the additional contribution of dorsal angular gyrus and posterior middle temporal cortex. Journal of cognitive neuroscience. 25:1824-1850.

Norman KA, Polyn SM, Detre GJ, Haxby JV. 2006. Beyond mind-reading: multi-voxel pattern analysis of fMRI data. Trends in cognitive sciences. 10:424-430.

Nozari N, Thompson-Schill SL. 2016. Left ventrolateral prefrontal cortex in processing of words and sentences. In. Neurobiology of language   Elsevier p 569-584.

Pereira F, Gershman S, Ritter S, Botvinick M. 2016. A comparative evaluation of off-the-shelf distributed semantic representations for modelling behavioural data. Cognitive neuropsychology. 33:175-190.

Piai V, Roelofs A, Acheson DJ, Takashima A. 2013. Attention for speaking: domain-general control from the anterior cingulate cortex in spoken word production. Frontiers in Human Neuroscience. 7.

Price AR, Bonner MF, Peelle JE, Grossman M. 2015. Converging evidence for the neuroanatomic basis of combinatorial semantics in the angular gyrus. Journal of Neuroscience. 35:3276-3284.

Price AR, Peelle JE, Bonner MF, Grossman M, Hamilton RH. 2016. Causal evidence for a

   mechanism of semantic integration in the angular gyrus as revealed by high-

   definition transcranial direct current stimulation. Journal of Neuroscience. 36:3829-

   3838.

Pylkkänen L. 2019. The neural basis of combinatory syntax and semantics. Science. 366:62-

   66.

Raichle ME. 2015. The brain's default mode network. Annual review of neuroscience.

   38:433-447.

Raichle ME, MacLeod AM, Snyder AZ, Powers WJ, Gusnard DA, Shulman GL. 2001. A

   default mode of brain function. Proceedings of the National Academy of Sciences.

   98:676-682.

Tong F, Pratte MS. 2012. Decoding patterns of human brain activity. Annual review of

   psychology. 63:483-509.

Vatansever D, Menon DK, Manktelow AE, Sahakian BJ, Stamatakis EA. 2015. Default mode

   dynamics for global functional integration. Journal of Neuroscience. 35:15254-15262.

Vatansever D, Menon DK, Stamatakis EA. 2017. Default mode contributions to automated

   information processing. Proceedings of the National Academy of Sciences.

   114:12821-12826.

Wang X, Margulies DS, Smallwood J, Jefferies E. 2020. A gradient from long-term memory

   to novel cognition: Transitions through default mode and executive cortex.

   NeuroImage. 220:117074.

Ward EJ, Chun MM, Kuhl BA. 2013. Repetition suppression and multi-voxel pattern similarity

   differentially track implicit and explicit visual memory. Journal of Neuroscience.

   33:14749-14757.

Wimmer EG, Büchel C. 2019. Learning of distant state predictions by the orbitofrontal cortex

   in humans. Nature Communications. 10:2554.

Woolgar A, Jackson J, Duncan J. 2016. Coding of visual, auditory, rule, and response

    information in the brain: 10 years of multivoxel pattern analysis. Journal of cognitive

    neuroscience. 28:1433-1454.

Woolrich M. 2008. Robust group analysis using outlier inference. Neuroimage. 41:286-301.

Woolrich MW, Behrens TE, Beckmann CF, Jenkinson M, Smith SM. 2004. Multilevel linear

    modelling for FMRI group analysis using Bayesian inference. Neuroimage. 21:1732-

    1747.

Zhang M, Wang X, Varga D, Krieger-Redwood K, Margulies DS, Smallwood J, Jefferies E.

    2020. Distinct default mode network subsystems show similarities and differences in

    the effect of task focus across reading and autobiographical memory.

    bioRxiv.2020.2010.2003.324947.