Efficient and precise single-cell reference atlas mapping with Symphony

Joyce B. Kang[1-5], Aparna Nathan[1-5], Fan Zhang[1-5], Nghia Millard[1-5], Laurie Rumker[1-5], D. Branch Moody[3], Ilya Korsunsky[1-5]**, Soumya Raychaudhuri[1-6]**

[1] Center for Data Sciences, Brigham and Women's Hospital, Boston, MA, USA

[2] Division of Genetics, Department of Medicine, Brigham and Women's Hospital and Harvard Medical School, Boston, MA, USA

[3] Division of Rheumatology, Inflammation, and Immunity, Department of Medicine, Brigham and Women's Hospital and Harvard Medical School, Boston, MA, USA

[4] Department of Biomedical Informatics, Harvard Medical School, Boston, MA, USA

[5] Program in Medical and Population Genetics, Broad Institute of MIT and Harvard, Cambridge, MA, USA

[6] Versus Arthritis Centre for Genetics and Genomics, Centre for Musculoskeletal Research, Manchester Academic Health Science Centre, The University of Manchester, Manchester, UK

** These authors jointly supervised this work.

Correspondence to:

Ilya Korsunsky

Harvard New Research Building

77 Avenue Louis Pasteur

Boston, MA 02115

ikorsunskiy@bwh.harvard.edu

Soumya Raychaudhuri

Harvard New Research Building

77 Avenue Louis Pasteur, Suite 250

Boston, MA 02115

soumya@broadinstitute.org

Ph: 617-525-4484 Fax: 617-525-4488

Abstract

Recent advances in single-cell technologies and integration algorithms make it possible to construct

comprehensive reference atlases encompassing many donors, studies, disease states, and sequencing

platforms. Much like mapping sequencing reads to a reference genome, it is essential to be able to map

query cells onto complex, multimillion-cell reference atlases to rapidly identify relevant cell states and

phenotypes. We present Symphony (https://github.com/immunogenomics/symphony), an algorithm for

building integrated reference atlases of millions of cells in a convenient, portable format that enables

efficient query mapping within seconds. Symphony localizes query cells within a stable low-dimensional

reference embedding, facilitating reproducible downstream transfer of reference-defined annotations to

the query. We demonstrate the power of Symphony by (1) mapping a multi-donor, multi-species query

to predict pancreatic cell types, (2) localizing query cells along a developmental trajectory of human

fetal liver hematopoiesis, and (3) inferring surface protein expression with a multimodal CITE-seq atlas

of memory T cells.

Keywords: single-cell genomics, scRNA-seq, reference mapping, annotation

Introduction

Advancements in single-cell RNA-sequencing (scRNA-seq) have launched an era in which individual studies can routinely profile 10^4-10^6 cells[1–3], and multimillion-cell datasets are already emerging[4,5]. Single-cell resolution enables the discovery and refinement of cell states across diverse clinical and biological contexts[6–11]. To date, most studies redefine cell states from scratch, making it difficult to compare results across studies and thus hampering reproducibility. Coordinated large-scale efforts, exemplified by the Human Cell Atlas (HCA)[12], aim to establish comprehensive and well-annotated reference datasets comprising millions of cells that capture the broad spectrum of cell states. Building these reference atlases requires integrating multiple datasets that may have been collected under different technical and biological conditions. Hence, reference construction requires application of one of many recently developed single-cell integration algorithms[13–19]. Our group previously developed Harmony[15], a fast, accurate, and well-reviewed method[20] that is able to explicitly model complex study design, a property that makes it suitable for integrating complex datasets into reference atlases[21–24]. The potential to define common cell states using reference maps has already been demonstrated[25,26]. For example, we built an integrated reference of ~80,000 single-cell profiles of fibroblasts from human lung, synovium, salivary gland, and intestine and successfully mapped fibroblasts from human skin and mouse synovium, lung, and intestine to analyze conserved states across tissues and species[25]. Once such reference atlases are painstakingly constructed, interpretation of new datasets requires the ability to quickly map single-cell profiles into these reference atlases. This enables interpretation of new datasets by transferring annotations and metadata of interest from nearby reference cells.

Fast mapping of query cells against a large, stable reference is a well-recognized open problem[27] and active area of research[28–30]. One inefficient but accurate approach to project reference and query cells into a joint embedding is to integrate both sets of cells together *de novo*, resulting in what might be considered a "gold standard" embedding. While this approach is reasonable for relatively small reference datasets, it is intractable for atlas-sized references with millions of cells. It requires users to "rebuild" the reference for each analysis, which may be computationally challenging and

require administratively cumbersome exchanges of large-scale datasets. Furthermore, *de novo*

integration may corrupt the reference embedding once a reference is carefully constructed and

annotated. It is instead preferable to freeze the reference when mapping new query cells onto it.

Here, we define reference mapping to mean placing query cells within the same embedding as

integrated reference cells without requiring access to the raw data on all individual reference cells.

Importantly, this embedding does not take advantage of any particular annotation, such as cell type

labels, which may be refined or updated over time. This is in contrast to automated cell type classifiers,

such as scmap[31], which assign rigid annotations based on reference datasets in a supervised manner.

Reference mapping approaches introduced so far include Seurat v4[30], which is compatible with Seurat

integration[18], and scArches, which is compatible with autoencoders such as scANVI[32] and trVAE[33].

These approaches separate reference building, which integrates datasets in the reference into a low-

dimensional embedding, from query mapping, which uses a compressed version of the reference to

efficiently map cells into the reference embedding. They further contrast with *de novo* integration

methods like BBKNN[34], Seurat v3[18], and Harmony[17], which enable reference building but are slow and

require access to the raw data and batch information on individual reference cells. High-quality

reference mapping requires both a framework to efficiently store an integrated reference, and a fast and

accurate procedure to map query datasets.

An ideal reference mapping algorithm must meet four key requirements. First, similar to *de novo*

integration algorithms, they must be able to remove confounding signals due to complex study design

in both the reference and query. In addition, they must be able to scale to large datasets, map with high

accuracy, and enable inference of diverse query cell annotations based on reference cells. We present

Symphony, a novel algorithm to compress a large, integrated reference and map query cells to a

precise location in the reference embedding within seconds. Through multiple real-world dataset

analyses, we show that Symphony can enable accurate downstream inference of cell type,

developmental trajectory position, and protein expression, even when the query itself contains complex

confounding technical and biological effects.

Results

Symphony compresses an integrated reference for efficient query mapping

Symphony comprises two main algorithms: reference compression and mapping (**Methods, Fig. S1a**). Symphony *reference compression* captures and structures information from multiple reference datasets into an integrated and concise format that can subsequently be used to map query cells (**Fig. 1a-b**). Symphony builds upon the linear mixture model framework first introduced by Harmony[17]. Briefly, in a low-dimensional embedding, such as principal component analysis (PCA), the model represents cell states as soft clusters, in which a cell's identity is defined by probabilistic assignments across one or more clusters. For *de novo* integration of the reference, cells are iteratively assigned soft cluster memberships, which are used as weights in a linear mixture model to remove unwanted covariate-dependent effects. To store the reference efficiently without saving information on individual reference cells, Symphony computes summary statistics learned in the low-dimensional space (**Fig. 1b, Methods**), returning computationally efficient data structures containing the "minimal reference elements" needed to map new cells. These include the means and standard deviations used to scale the genes, the gene loadings from PCA (or another low dimensional projection, e.g. canonical correlation analysis [CCA]) on the reference cells, soft-cluster centroids from the integrated reference, and two "compression terms" (a k x 1 vector and k x d matrix, where k is the number of clusters and d is the dimensionality of the embedding) (**Methods, Supplementary Equations, Fig. S1b**).

To map new query cells to the compressed reference, we apply Symphony *mapping*. The algorithm approximates integration of reference and query cells *de novo* (**Methods**), but uses only the minimal reference elements to compute the mapping (**Fig. S1c**). First, Symphony projects query gene expression profiles into the same uncorrected low-dimensional space as the reference cells (e.g. PCs), using the saved scaling parameters and reference gene loadings (**Fig. 1c**). Second, Symphony computes soft cluster assignments for the query cells based on proximity to the reference cluster centroids. Finally, to correct unwanted user-specified technical and biological effects in the query data, Symphony assumes the soft cluster assignments from the previous step and uses stored mixture model

Figure 1. Symphony Overview. Symphony comprises two algorithms: Symphony compression **(a-b)** and Symphony mapping **(c-d)**. **(a)** To construct a reference atlas, cells from multiple datasets are embedded in a lower-dimensional space (e.g. PCA), in which dataset integration (Harmony) is performed to remove dataset-specific effects. Shape indicates distinct cell types, and color indicates finer-grained cell states. **(b)** Symphony compression represents the information captured within the harmonized reference in a concise, portable format based on computing summary statistics for the reference-dependent components of the linear mixture model. Symphony returns the minimal reference elements needed to efficiently map new query cells to the reference. **(c)** Given an unseen query dataset and compressed reference, Symphony mapping precisely localizes the query cells to their appropriate locations within the integrated reference embedding **(d)**. Reference cell locations do not change during mapping. **(e)** The resulting joint embedding can be used for downstream transfer of reference-defined annotations to the query cells. See Fig. S1.

components to estimate and regress out the query batch effects (**Fig. 1d**). Importantly, the reference

cell embedding remains stable during mapping. Embedding the query within the reference coordinates

enables downstream transfer of annotations from reference cells to query cells, including discrete cell

type classifications, quantitative cell states (e.g. position along a trajectory), or expression of missing

genes or proteins (**Fig. 1e**).

Symphony approximates *de novo* integration of PBMCs without reintegration of

reference datasets

As we demonstrate in the **Methods**, Symphony is equivalent to running *de novo* Harmony integration if

three conditions are met: (I) all cell states represented in the query data set are captured by the

reference dataset, (II) the number of query cells is much smaller than the number of reference cells,

and (III) the query dataset has a design matrix that is independent of reference datasets (i.e. non-

overlapping batches in reference and query). As the scope of available single-cell atlases continues to

grow, it is reasonable to assume that reference datasets are large and all-inclusive, making conditions

(I) and (II) well-supported. Condition (III) is also typically met if the query data was generated in

separate experiments from the reference.

To demonstrate that Symphony mapping closely approximates running *de novo* integration on

all cells, we applied Symphony to 20,792 peripheral blood mononuclear cells (PBMCs) assayed with

three different 10x technologies: 3'v1, 3'v2, and 5'. We performed three mapping experiments. For

each, we built an integrated Symphony reference from two technologies, then mapped the third

technology as a query. The resulting Symphony embeddings were compared to a gold standard

embedding obtained by running Harmony on all three datasets together. Visually, we found that the

Symphony embedding for each mapping experiment (**Fig. 2a**) closely reproduced the overall structure

and cell type information of the gold standard embedding (**Fig. 2b**). To quantitatively assess the

degrees of dataset mixing we use the Local Inverse Simpson's Index (LISI)[17] metric. For a given

categorical label assigned to each cell (in this case, technology), LISI indicates the effective number of

categories represented in the local neighborhood of each cell; higher LISI scores correspond to better

Figure 2. Symphony approximates *de novo* integration without reintegration of the reference cells. Three PBMC datasets were sequenced with different 10x protocols: 5' (yellow, n=7,697 cells), 3'v2 (blue, n=8,380 cells), and 3'v1 (red, n=4,809 cells). We ran Symphony three times, each time mapping one dataset onto a reference built from integrating the other two. **(a)** Symphony embeddings generated across the three mapping experiments (columns). Top row: cells colored by query (yellow, blue, or red) or reference (gray), with query cells plotted in front. Bottom row: cells colored by cell type: B cell (B), dendritic cell (DC), hematopoietic stem cell (HSC), megakaryocyte (MK), monocyte (Mono), natural killer cell (NK), or T cell (T), with query cells plotted in front. **(b)** For comparison, gold standard *de novo* Harmony embedding colored by dataset (top) and cell type (bottom). **(c)** Distribution of technology LISI scores for query cell neighborhoods in the Symphony, gold standard, and a standard PCA embeddings on all cells. **(d)** Distribution of k-NN-corr (Spearman correlation between the similarities between the neighbor-pairs in the Harmony embedding and the similarities between the same neighbor-pairs in the Symphony embedding) across query cells for k=500, colored by query dataset. **(e)** Classification accuracy as measured by cell type F1 scores for query cell type annotation using 5-NN on the Symphony embedding. See Fig. S2.

mixing of cells across batches. LISI scores in Symphony embeddings (mean LISI 2.16, 95% CI [2.16,

2.17]) and *de novo* integration embeddings (mean LISI 2.14, 95% CI [2.13, 2.15]) were nearly identical

(**Fig. 2c**, **Methods**).

To directly assess similarity of the local neighborhood structures, we computed the correlation

between the local neighborhood adjacency graphs generated by Symphony and *de novo* integration.

We define a new metric called k-nearest-neighbor correlation (k-NN-corr), which quantifies how well the

local neighborhood structure in a given embedding is preserved in an alternative embedding by looking

at the correlation of neighbor cells sorted by distance (**Fig. S2a-e**). Anchoring on each query cell, we

calculate (1) the pairwise similarities to its k nearest reference neighbors in the gold standard

embedding and (2) the similarities between the same query-reference neighbor pairs in the alternate

embedding (**Methods**), then calculate the Spearman correlation between (1) and (2). k-NN-corr ranges

from -1 to +1, where +1 indicates a perfectly preserved sorted ordering of neighbors. We find that for

k=500, the Symphony embeddings produce a k-NN-corr >0.4 for 77.3% of cells (and positive k-NN-corr

for 99.9% of cells), demonstrating that Symphony not only maps query cells to the correct broad cluster

but also preserves the distance relationships between nearby cells in the same local region (**Fig. 2d**).

As a comparison, we calculated k-NN-corr for a simple PC projection of the query cells (with no

correction step) using the original reference gene loadings prior to integration and observed

significantly lower correlations (Wilcoxon signed-rank p<2.2e-16), with k-NN-corr >0.4 for 39.9% of cells

(**Fig. S2f**).

Symphony enables accurate cell type classification of PBMCs across technologies

If Symphony is effective, then cells should be mapped close to cells of the same cell type, enabling

accurate cell type classification. To test this, we performed post-mapping query cell type classification

in the 10x PBMCs example from above. We used a 5-NN classifier to annotate query cells across 7 cell

types based on the nearest reference cells in the harmonized embedding and compared the predictions

to the ground truth labels assigned *a priori* with lineage-specific marker genes (**Methods, Table S2**).

Across all three experiments, predictions using the Symphony embeddings achieved 99.5% accuracy

overall, with a median cell type F1-score (harmonic mean of precision and recall, ranging from 0 to 1) of

0.99 (**Fig. 2e, Table S3**). This indicates that Symphony appropriately localizes query cells in

harmonized space to enable the accurate transfer of cell type labels.

Automatic cell type classification represents an open area of research[31,35–38]. Existing

supervised classifiers assign a limited set of labels to new cells based on training data and/or marker

genes. To benchmark Symphony-powered downstream inference against existing classifiers, we

followed the same procedure as a benchmarking analysis in Abdelaal et al. (2019)[35]. The benchmark

compared 22 cell type classifiers on the PbmcBench dataset consisting of two PBMC samples

sequenced using 7 different protocols[39]. For each protocol train-test pair (42 experiments) and donor

train-test pair (additional 6 experiments) (**Methods**), we built a Symphony reference from the training

dataset then mapped the test dataset. We used the resulting harmonized feature embedding to predict

query cell types using three downstream models: 5-NN, SVM with radial kernel, and multinomial logistic

regression. The Symphony-based classifiers achieve consistently high cell type F1-scores (average

median F1 of 0.79-0.83) comparable to the top three supervised classifiers for this benchmark

(scmapcell, singleCellNet, and SCINA, average median F1 of 0.77-0.83) (**Fig. S3a**). Notably, as

discussed in Abdelaal et al., the median F1-score alone can be misleading given that some classifiers

(including SCINA) leave low-confidence cells as "unclassified", whereas we used Symphony to assign a

label to every cell. This benchmark is also arguably suboptimal in that the reference in each experiment

is comprised of a single dataset (no reference integration involved).

Symphony maps against a large reference within seconds

To demonstrate scalability to large reference atlases, we evaluated Symphony's computational speed.

We downsampled a large memory T cell dataset[40] to create benchmark reference datasets with 20,000,

50,000, 100,000, 250,000, and 500,000 cells (from 12, 30, 58, 156, and 259 donors, respectively).

Against each reference, we mapped three different-sized queries: 1,000, 10,000, and 100,000 cells

(from 1, 6, and 64 donors) and measured total elapsed runtime (**Fig. 3, Table S4**). The speed of the

reference building process is comparable to that of running *de novo* integration since they both start

Figure 3. Symphony scales mapping to large references within seconds. Total elapsed time (in secs) required to run Symphony reference building starting from gene expression (left), Symphony query mapping starting from query gene expression (middle), or *de novo* Harmony integration (right) for different-sized reference (x-axis) and query (colors) datasets downsampled from the memory T cell CITE-seq dataset. See Table S4.

with expression data and require a full pipeline of scaling, PCA, and Harmony integration. However, a

reference need only be built and saved once in order to map all subsequent query datasets onto it. For

instance, initially building a 500,000-cell reference with Symphony took 5,163 seconds (86.1 min) and

mapping a subsequent 10,000-cell query onto it took only 0.99 secs, compared to 4,806 secs (80.1

mins) for *de novo* integration on all cells. Symphony offers a 5000x speedup in this application. These

results show that Symphony scales efficiently to map against multimillion-cell references, enabling it to

power potential web-based queries within seconds.

Importantly, Symphony mapping time does not depend on the number of cells or batches in the

reference since the reference cells are modeled post-batch correction (**Methods**); however, it does

depend on the reference complexity (number of centroids k and dimensions d) and number of query

cells and batches (**Table S4**) since the query mapping algorithm solves for the query batch coefficients

for each of the reference-defined clusters.

Symphony maps multi-donor, multi-species study to reference of human pancreatic

islet cells

A query dataset might include data from multiple donors, species, and perturbations that create

confounding signals obscuring biological signal of interest. Integration algorithms remove these signals

in *de novo* analysis, and it is essential that reference mapping removes them too. Therefore, we

designed Symphony to simultaneously handle both tasks: mapping query to reference cells and

integration within the query. To test the ability of Symphony to integrate query datasets during mapping,

we analyzed reference and query datasets of pancreatic islet cells in which both the reference and

query have complex experimental structure (**Fig 4a**). The reference contained 5,887 pancreatic islet

cells from 32 human donors across four independent studies[41–44], each profiled with a different plate-

based scRNA-seq technology (CEL-seq, CEL-seq2, Smart-seq2, and Fluidigm C1). We manually

annotated cell types using cluster-specific marker genes within each reference dataset separately

(**Methods**). The query contained 8,569 pancreatic islet cells from 4 human donors and 1,866 cells from

2 mice, all profiled with inDrop, a droplet-based scRNA-seq technology absent in the reference[45] (**Fig**

Figure 4. Symphony maps multi-donor, multi-species study to human pancreatic islet cell reference. (a) Schematic of mapping experiment with reference (n=5,887 cells, 32 donors) built from four human pancreas datasets and query dataset (n=10,455 cells, from 4 human donors and 2 mouse donors) sequenced on a new technology (inDrop). **(b)** Bar plot shows relative proportions of cell types per query donor. We integrated the reference datasets *de novo* using Harmony, Seurat anchor-based integration, or trVAE, then mapped the query onto the corresponding reference using Symphony, Seurat v4, or scArches, respectively. UMAP plots of resulting joint embeddings showing **(c)** density of integrated reference cells colored by cell type and **(d)** query cells colored by cell type as defined by Baron et al. (left) or donor (right) with reference densities plotted in the back in gray. Degree of integration for each method was measured by LISI metric between reference and query labels **(e)** and LISI between query donors **(f)** for each query cell neighborhood. Distributions of LISI scores for each method faceted by species and normalized to equal height. See Fig. S4 and S5.

4b). PCA of the query dataset alone demonstrated the magnitude of the confounding species and

donor signals, emphasizing the need for within-query integration (**Fig. S4a**).

Symphony mapped the multi-species, multi-donor, droplet-based query into the reference by

effectively and simultaneously removing the effects of species, donor, and technology (**Fig. 4c-d**);

reference mapping obtained superior integration compared to PCA (mean donor LISI=2.72 compared

to 1.45). We predicted that integrating over three nested sources of variation would make it possible to

accurately predict query cell types. Using a simple 5-NN classifier in the harmonized embedding, we

observed accurate cell-type prediction. Using ground truth labels defined by the original publication[45],

we obtained a median cell type F1-score of 0.96 (overall accuracy 96%) for human and median cell

type F1 of 0.95 (overall accuracy 91%) for mouse cells (**Fig. S4c-d, Table S5**), By mapping against a

reference, Symphony is able to overcome strong species effects and simultaneously map analogous

cell types between mouse and human.

Next, we evaluated the ability of the other reference mapping algorithms, scArches and Seurat

v4, to integrate the same query dataset. For each mapping method, we built a reference using its

compatible *de novo* integration method (**Methods, Fig. 4c, S4b**). Symphony obtained higher levels of

integration than did Seurat and scArches, both between reference and query as well as donors within

the query (**Fig. 4e-f**). Symphony mapping achieves comparable donor mixing to that of Harmony *de*

novo integration of all five datasets (mean mapping LISI=2.67 vs *de novo* LISI=2.55 in human, 2.91 vs

2.7 in mouse). In contrast, the other mapping methods return less integrated embeddings, when

compared to their corresponding *de novo* methods (mean mapping LISI=2.09 vs *de novo* LISI=2.83 for

Seurat in human, 2.43 vs 2.67 in mouse; 1.12 vs 2.52 for scArches/trVAE in human, and 1.24 vs 3.05 in

mouse; **Table S6**). We then evaluated the accuracy of each mapping with 5-NN cell type classification

(**Methods**). We observed that Symphony and Seurat performed comparably well, and both

outperformed scArches on both human and mouse cell type prediction (**Fig. S4c-d, Table S5**).

Symphony was 1-2 orders of magnitude faster (1.4 s) than either Seurat (31.7 s) or scArches (381.5 s)

mapping on this example (**Table S6**).

Localizing query cells along a reference-defined trajectory of human fetal liver

hematopoiesis

A successful mapping method should position cells not only within cell type clusters but also along smooth transcriptional gradients, commonly used to model differentiation and activation processes over time (**Fig. 5a**). To test Symphony in a gradient mapping context, we built and mapped to a reference atlas profiling human fetal liver hematopoiesis, containing 113,063 liver cells from 14 donors spanning 7-17 post-conceptional weeks of age and 27 author-defined cell types, sequenced with 10x 3' chemistry (**Fig. 5b, Fig. S6a**)[46]. Trajectory analysis of immune populations with the force directed graph (FDG) algorithm[46] highlights relationships among progenitor and differentiated cell types (**Fig. 5c**). Notably, the hematopoietic stem cell and multipotent progenitor population branches into three major trajectories, representing the lymphoid, myeloid, and megakaryocyte-erythroid-mast (MEM) lineages. This reference contains two forms of annotation for downstream query inference: discrete cell types and positions along differentiation gradients.

We mapped a query consisting of 21,414 new cells from 5 of the original 14 donors, sequenced with 10x 5' chemistry. We first inferred query cell types with k-NN classification (**Methods**) and confirmed accurate cell type assignment based on the authors' independent query annotations[46] (median cell type F1=0.92 across 14 held-out donor experiments within 3' dataset only, median cell type F1=0.83 for the 5'-to-3' experiment; **Fig. S7, Table S7**). To evaluate query trajectory inference, we used the Symphony joint embedding to position query cells from the MEM lineage (n=5,141) in the reference-defined trajectory by averaging the 10 nearest reference cell FDG coordinates. The inferred query trajectory (**Fig. 5d**) recapitulated known branching from MEM progenitors (MEMPs, brown) into distinct megakaryocyte (green), erythroid (blue, pink), and mast cell (yellow) lineages. Moreover, transitions from MEMPs to differentiated types were marked by gradual changes in canonical marker genes (**Fig. 5e**): *PPBP* for megakaryocytes, *HBB* for erythrocytes, and *KIT* for mast cells. These gradual expression patterns are consistent with correct placement of query cells along differentiation gradients.

Figure 5. Localizing query cells along a trajectory of fetal liver hematopoiesis. (a) Symphony can precisely place query cells along a reference-defined trajectory. The reference (n=113,063 cells, 14 donors) was sequenced using 10x 3' chemistry, and the query (n=25,367 cells, 5 donors) was sequenced with 10x 5' chemistry. **(b)** Symphony reference colored by cell types as defined by Popescu et al. (2019). Contour fill represents density of cells. Black points represent soft-cluster centroids in the Symphony mixture model. **(c)** Reference developmental trajectory of 3'-sequenced immune cells (FDG coordinates obtained from original authors). Query cells in the MEM lineages (n=5,141 cells) were mapped against the reference and query coordinates along the trajectory were predicted with 10-NN **(d)**. The inferred query trajectory preserves branching within the MEM lineages, placing terminally differentiated states on the ends. **(e)** Expression of lineage marker genes (*PPBP* for megakaryocytes, *HBB* for erythroid cells, and *KIT* for mast cells). Cells colored by log-normalized expression of gene. See Fig. S6 and S7.

Inferring query surface protein marker expression by mapping to a reference assayed

with CITE-seq

Recent technological advances in multimodal single-cell technologies (e.g., CITE-seq) make it possible

to simultaneously measure mRNA and surface protein expression from the same cells using

oligonucleotide-tagged antibodies[47,48]. With Symphony, we can construct a reference from these data,

map query cells from experiments that measure only mRNA expression, and infer surface protein

expression for the query cells to expand possible analyses and interpretations (**Fig. 6a**).

To demonstrate this, we used a CITE-seq dataset that measures the expression of whole-

transcriptome mRNA and 30 surface proteins on 500,089 peripheral blood memory T cells from 271

samples[40]. We leveraged both mRNA and protein features to build a multimodal reference from 80% of

samples (n=217) and map the remaining 20% of samples (n=54). Instead of using PCA, which is best

for one modality[49], we used canonical correlation analysis (CCA) to embed reference cells into a space

that leverages both. Specifically, CCA constructs a pair of correlated low-dimensional embeddings, one

for mRNA and one for protein features, each with a linear projection function akin to gene loadings in

PCA. We corrected reference batch effects in CCA space with Harmony and built a Symphony

reference (**Fig. 6b**), saving the gene loadings for the CCA embedding from mRNA features. Then, we

mapped the held-out query using only mRNA expression to mimic a unimodal scRNA-seq experiment,

reserving the measured query protein expression as a ground truth for validation. We accurately

predicted the surface protein expression of each query cell using the 50-NN average from the reference

cells in the harmonized embedding. For all proteins, we found strong concordance between predicted

and (50-NN smoothed) measured expression (Pearson r: 0.88-0.99, **Fig. 6c-d**). For all but three

proteins, we achieved comparable results with as few as 5 or 10 nearest neighbors (**Fig. S8a**).

We note that it is also possible to conduct the same analysis with a unimodal PCA-based

reference built from the cells' mRNA expression only. This approach has slightly worse performance for

some proteins (Pearson r: 0.65-0.97, **Fig. S8b-d**), demonstrating that a reference built jointly on both

mRNA and protein permits better inference of protein expression than an mRNA-only reference, which

Figure 6. Mapping onto a multimodal reference to infer query surface protein expression in memory T cells. (a) Schematic of multimodal mapping experiment. The dataset was divided into training and test sets (80% and 20% of samples, respectively). The training set was used to build a Symphony reference, and the test set was mapped onto the reference to predict surface protein expression in query cells (pink) based on 50-NN reference cells (gray). **(b)** Symphony reference built from mRNA/protein CCA embedding. Contour fill represents density of reference cells. Black points represent soft-cluster centroids in the Symphony mixture model. **(c)** We measured the accuracy of protein expression prediction with the Pearson correlation between predicted and ground truth expression for each surface protein across query cells in each donor. Bar height represents the average per-donor correlation for each protein, and error bars represent standard deviation. **(d)** Ground truth and predicted expression of CD4, CCR6, and CD69 based on CCA reference. Ground truth is the 50-NN-smoothed expression measured in the CITE-seq experiment. Colors are scaled independently for each marker from minimum (blue) to maximum (yellow) expression. See Fig. S8.

305   is consistent with previous observations that mRNA expression is not fully representative of protein

306   expression[47,48]. This analysis highlights how users can start with a low-dimensional embedding other

307   than PCA, such as CCA, to better capture rich multimodal information in the reference.

Discussion

Mapping query cells into large, annotated references in real time and without the need to share

sensitive information from the reference datasets is becoming increasingly important for reproducible

single-cell analysis. We approached this inherently complex, big-data problem using well-established

mathematical methods from integration analysis. We framed reference mapping as a specialized case

of integration between one relatively small dataset and a second larger, more comprehensive, and

previously integrated dataset. Because the reference is already integrated, it is natural to use the same

mathematical framework from the integration to perform mapping. For instance, the scArches[28]

algorithm uses an autoencoder-based framework to map to references built with autoencoder-based

integration algorithms[32,33]. Similarly, Symphony uses the mixture modeling framework to map to

references built with Harmony mixture modeling integration. Symphony compresses the reference by

extracting relevant reference-derived parameters from the mixture model to map query cells in

seconds. With this compression, references can be distributed without the need to share raw

expression data or donor-level metadata, which enables data privacy[50]. Symphony compression greatly

reduces the size of a reference dataset: for the memory T cell dataset of 500,089 cells, the raw

expression matrix is 8.9 GB, whereas the Symphony minimal reference elements are 1.3 MB.

Useful reference atlases contain annotations absent in the query, such as cell type labels (**Fig.**

4), trajectory coordinates (**Fig. 5**), or multimodal measurements (**Fig. 6**). Transfer of these annotations

from reference to query is an open area of research that includes algorithms for automated cell type

classification[31,35–38]. We approach annotation transfer in two steps. We first learn a predictive model in

the reference embedding, and then map query cells and use their reference coordinates to predict

query annotations. In this two-step approach, Symphony mapping provides a feature space but is

otherwise independent from the choice of downstream inference model. In PBMC type prediction (**Fig.**

S3), we used Symphony embeddings to train multiple competitive classifiers: k-NN, SVM, and logistic

regression. In our analyses, we were encouraged to find that a simple k-NN classifier can achieve high

performance with only 5-10 neighbors. In practice, users can choose more complex inference models if

it is warranted for certain annotation types. Moreover, we expect prediction results to improve with more

accurate and reproducible annotation methods, such as consistent cell type taxonomies provided by

the Cell Ontology[51] project and better modeling of multimodal expression data[52].

Because mapping is a special case of integration, we expected Symphony mapping to

recapitulate the results of *de novo* Harmony integration. To this end, we defined three conditions under

which Symphony and *de novo* integration with Harmony yield equivalent results. In subsequent

examples, we showed that Symphony still performs well when the last two conditions are relaxed. The

pancreas query contains more cells than its reference (**condition II**), while the liver hematopoiesis

reference and query overlap in donors (**condition III**). Condition I, which requires comprehensive cell

type coverage in the reference, is less flexible. When the query contains a brand new cell type, it will be

aligned to its most transcriptionally similar reference cluster. Note that condition I only pertains to cell

types and not clinical and biological contexts. For instance, we successfully mapped mouse pancreas

query to an entirely human pancreas reference (**Fig. 4**), because the same pancreatic cell types are

shared in both species. Mapping novel cell types is a current limitation and important direction for future

work. For now, we advise users interested in novel cell type discovery to supplement a Symphony

analysis with *de novo* analyses of the query alone.

Instead of one monolithic reference for all cell types across all tissues and disease, we expect

the proliferation of multiple, well-annotated specialized references that focus on fine-grained modeling

of diverse biological systems. For instance, the memory T cell reference (**Fig. 6**) will be useful to

annotate fine-grained T cell states, while an unsorted PBMC reference (**Fig. 2**) would better suit

coarse-grained annotation of multiple immune populations. Similarly, a reference with only healthy

individuals is useful for annotation of cell types, while a reference with both healthy and diseased

individuals is useful for annotation of cell types and pathological cell states. We advise Symphony users

to carefully select the appropriate reference atlas for their study and potentially map to multiple

references, as needed. For instance, one may use a PBMC reference to identify and isolate T cells and

a memory T cell reference to assign fine-grained labels to query T cells.

As large-scale tissue and whole-organism single-cell reference atlases become available in the

near future, Symphony will enable investigators to leverage the rich information in these references to

perform integrative analyses and transfer reference coordinates and diverse annotations to new

datasets in a rapid and reproducible manner.

364 Acknowledgements

We thank members of the Raychaudhuri Lab for helpful feedback and comments. We thank members

of the Tuberculosis Research Unit (TBRU) LIMAA and Socios En Salud, in particular Megan Murray,

Jessica Beynor, Yuriy Baglaenko, Sara Suliman, Ildiko van Rhijn, and Leonid Lecca, for their

contributions to generating the memory T cell dataset. We would also like to thank Issac Goh, Muzlifah

Haniffa, and other members of the Haniffa Lab for graciously providing preprocessed datasets from

their fetal liver hematopoiesis study. This work is supported in part by funding from the National

Institutes of Health (1UH2AR067677, U19 AI111224, U01 HG009379, 1R01AR073833, and

R01AR063759). The project described was supported by award Number T32GM007753 from the

National Institute of General Medical Sciences (JBK). The content is solely the responsibility of the

authors and does not necessarily represent the official views of the National Institute of General

Medical Sciences or the National Institutes of Health.

376 Author contributions

377   I.K., J.B.K., and S.R. conceived the project. J.B.K. and I.K. developed the method and performed the

378   analyses under the guidance of S.R. F.Z. assisted with benchmarking. S.R., A.N., and D.B.M.

379   contributed to generating the memory T cell dataset. A.N. performed analysis of the memory T cell

380   dataset. All authors participated in interpretation and writing the manuscript.

Declaration of interests

Figure Legends

Figure 1. Symphony Overview. Symphony comprises two algorithms: Symphony compression **(a-b)** and Symphony mapping **(c-d)**. **(a)** To construct a reference atlas, cells from multiple datasets are embedded in a lower-dimensional space (e.g. PCA), in which dataset integration (Harmony) is performed to remove dataset-specific effects. Shape indicates distinct cell types, and color indicates finer-grained cell states. **(b)** Symphony compression represents the information captured within the harmonized reference in a concise, portable format based on computing summary statistics for the reference-dependent components of the linear mixture model. Symphony returns the minimal reference elements needed to efficiently map new query cells to the reference. **(c)** Given an unseen query dataset and compressed reference, Symphony mapping precisely localizes the query cells to their appropriate locations within the integrated reference embedding **(d)**. Reference cell locations do not change during mapping. **(e)** The resulting joint embedding can be used for downstream transfer of reference-defined annotations to the query cells. See Fig. S1.

Figure 2. Symphony approximates *de novo* integration without reintegration of the reference cells. Three PBMC datasets were sequenced with different 10x protocols: 5' (yellow, n=7,697 cells), 3'v2 (blue, n=8,380 cells), and 3'v1 (red, n=4,809 cells). We ran Symphony three times, each time mapping one dataset onto a reference built from integrating the other two. **(a)** Symphony embeddings generated across the three mapping experiments (columns). Top row: cells colored by query (yellow, blue, or red) or reference (gray), with query cells plotted in front. Bottom row: cells colored by cell type: B cell (B), dendritic cell (DC), hematopoietic stem cell (HSC), megakaryocyte (MK), monocyte (Mono), natural killer cell (NK), or T cell (T), with query cells plotted in front. **(b)** For comparison, gold standard *de novo* Harmony embedding colored by dataset (top) and cell type (bottom). **(c)** Distribution of

technology LISI scores for query cell neighborhoods in the Symphony, gold standard, and a standard

PCA embeddings on all cells. **(d)** Distribution of k-NN-corr (Spearman correlation between the

similarities between the neighbor-pairs in the Harmony embedding and the similarities between the

same neighbor-pairs in the Symphony embedding) across query cells for k=500, colored by query

dataset. **(e)** Classification accuracy as measured by cell type F1 scores for query cell type annotation

using 5-NN on the Symphony embedding. See Fig. S2.

Figure 3. Symphony scales mapping to large references within seconds. Total elapsed time (in

secs) required to run Symphony reference building starting from gene expression (left), Symphony

query mapping starting from query gene expression (middle), or *de novo* Harmony integration (right) for

different-sized reference (x-axis) and query (colors) datasets downsampled from the memory T cell

CITE-seq dataset. See Table S4.

Figure 4. Symphony maps multi-donor, multi-species study to human pancreatic islet cell

reference. (a) Schematic of mapping experiment with reference (n=5,887 cells, 32 donors) built from

four human pancreas datasets and query dataset (n=10,455 cells, from 4 human donors and 2 mouse

donors) sequenced on a new technology (inDrop). **(b)** Bar plot shows relative proportions of cell types

per query donor. We integrated the reference datasets *de novo* using Harmony, Seurat anchor-based

integration, or trVAE, then mapped the query onto the corresponding reference using Symphony,

Seurat v4, or scArches, respectively. UMAP plots of the resulting joint embeddings showing **(c)** density

of integrated reference cells colored by cell type and **(d)** query cells colored by cell type as defined by

Baron et al. (left) or donor identity (right) with reference densities plotted in the back in gray. Degree of

integration for each method was measured by LISI metric between reference and query labels **(e)** and

LISI between query donors **(f)** for each query cell neighborhood. Distributions of LISI scores for each

method faceted by species and normalized to equal height. See Fig. S4 and S5.

Figure 5. Localizing query cells along a trajectory of fetal liver hematopoiesis. (a) Symphony can

precisely place query cells along a reference-defined trajectory. The reference (n=113,063 cells, 14

donors) was sequenced using 10x 3' chemistry, and the query (n=25,367 cells, 5 donors) was

sequenced with 10x 5' chemistry. **(b)** Symphony reference colored by cell types as defined by Popescu

et al. (2019). Contour fill represents density of cells. Black points represent soft-cluster centroids in the

Symphony mixture model. **(c)** Reference developmental trajectory of 3'-sequenced immune cells (FDG

coordinates obtained from original authors). Query cells in the MEM lineages (n=5,141 cells) were

mapped against the reference and query coordinates along the trajectory were predicted with 10-NN

(d). The inferred query trajectory preserves branching within the MEM lineages, placing terminally

differentiated states on the ends. **(e)** Expression of lineage marker genes (*PPBP* for megakaryocytes,

HBB for erythroid cells, and *KIT* for mast cells). Cells colored by log-normalized expression of gene.

See Fig. S6 and S7.

Figure 6. Mapping onto a multimodal reference to infer query surface protein expression in

memory T cells. (a) Schematic of multimodal mapping experiment. The dataset was divided into

training and test sets (80% and 20% of samples, respectively). The training set was used to build a

Symphony reference, and the test set was mapped onto the reference to predict surface protein

expression in query cells (pink) based on 50-NN reference cells (gray). **(b)** Symphony reference built

from mRNA/protein CCA embedding. Contour fill represents density of reference cells. Black points

represent soft-cluster centroids in the Symphony mixture model. **(c)** We measured the accuracy of

protein expression prediction with the Pearson correlation between predicted and ground truth

expression for each surface protein across query cells in each donor. Bar height represents the

average per-donor correlation for each protein, and error bars represent standard deviation. **(d)** Ground

truth and predicted expression of CD4, CCR6, and CD69 based on CCA reference. Ground truth is the

50-NN-smoothed expression measured in the CITE-seq experiment. Colors are scaled independently

for each marker from minimum (blue) to maximum (yellow) expression. See Fig. S8.

Supplementary Figure 1. Overview of reference mapping pipeline and Symphony data

structures. (a) The overall analysis pipeline comprises various functions (orange boxes) that each

perform a transformation on the data. Symphony mapping takes in a query gene expression matrix and

a Symphony reference built from integrated reference datasets, and outputs the query cell locations in

the harmonized feature embedding. Models trained on the reference feature embedding (e.g. cell type

classifier) can transfer annotations to the query for various downstream tasks. **(b)** Steps of reference

building algorithm. Reference datasets spanning multiple batches are aggregated into a single

expression matrix on which PCA and Harmony integration is performed. The output of reference

compression is the Symphony minimal reference elements, consisting of data structures μ, σ, U, Y_{cos},

N_r, and C (red symbols). Z_{r_corr} (the harmonized reference embedding) is not used for the mapping

calculation but is saved for downstream annotation transfer. **(c)** Steps of query mapping algorithm,

indicating where each reference element is used. Query cells are projected into reference PCA space,

clustered to reference centroids, and corrected to harmonized space by removing query batch effects.

Supplementary Figure 2. Nearest neighbor correlation (k-NN-corr) metric. The k-NN-correlation

metric assesses how well an alternative embedding recapitulates the structure of a gold standard

embedding. k-NN-corr is asymmetric in that it matters which of the two embeddings is selected as the

gold standard. Consider a gold standard embedding **(a)** and two alternative embeddings **(b)** and **(c)**,

representing a good mapping and a bad mapping, respectively. For a given query cell q (red), we

identify its top k nearest reference (gray) neighbors in the gold standard embedding (k = 3 depicted)

and calculate the similarity between the query cell and each neighbor. The similarities between the

same query-reference neighbor pairs are then calculated in the alternate embedding. k-NN-corr is the

Spearman correlation between the similarities in the gold standard vs. alternative embedding, ranging

from -1 to +1. Example k-NN-corr for one query cell and k = 500 for the **(d)** Symphony embedding and

(e) PCA projection embedding. **(f)** k-NN-corr distribution across query cells for k=500 and a gold

standard Harmony embedding, for either the Symphony embeddings (blue) or a simple PCA projection

with no correction step (red), faceted by query dataset.

Supplementary Figure 3. Symphony performance against automatic cell type classifiers.

Following the cross-technology PBMC benchmarking experiment from Abdelaal et al. (2019), we ran a

total of 48 train-test experiments per Symphony-based classifier. Two different versions of the

Symphony feature embeddings were generated depending on variable gene selection method: top

2000 variable genes (vargenes) or top 20 differentially genes (DEGs) expressed per cell type.

Symphony embeddings were used to train 3 downstream classifiers: k-NN (k=5), SVM with radial

kernel, and multinomial logistic regression (glmnet) with ridge. **(a)** Symphony (orange) median cell-type

F1 score across 48 train-test experiments compared to supervised methods (green), demonstrating

noninferiority to the top supervised methods and stable performance regardless of downstream

classification method. Red dot indicates mean of median F1 scores across 48 experiments (used for

ordering the methods along the x-axis). **(b, c)** Median cell type F1 score across 48 experiments for the

5-NN classifier with variable gene selection **(b)** and DEG selection **(c)**. Non-diagonal values represent

train on one technology, test on another (42 experiments, all with donor 1). Values along the diagonal

indicate train on donor 1, test on donor 2 of the same technology (6 experiments; missing square

because donor 2 not sequenced with 10x v3).

Supplementary Figure 4. Comparison of Symphony to alternative reference mapping methods

on a cross-species pancreatic islet cell benchmark. (a) Standard PCA pipeline applied to the Baron

et al. query dataset exhibits strong species and donor effects, demonstrating the need for within-query

integration. We benchmarked Symphony mapping (on a Harmony-integrated reference), Seurat v4

mapping (on a Seurat anchor-based-integrated reference), and scArches mapping (on a trVAE-

integrated reference). For each approach, we built an integrated reference **(b)**, mapped the query, then

predicted query cell types using a 5-NN classifier to transfer annotations using the respective reference

embedding. **(c)** Query cell prediction accuracy by species for each method as measured by cell type F1

score, with author-defined ground truth labels. Mouse samples did not have acinar or epsilon cells. The

resulting joint cell embedding for each tool was visualized by UMAP **(b, d)**: **(b)** Reference cells colored

by dataset/technology. **(d)** Query cells colored by correct (green) or incorrect (red) cell type prediction.

Supplementary Figure 5. Comparison of *de novo* integration methods for harmonizing all five

pancreatic islet cell datasets. As a comparison to reference mapping (Fig 3), we integrated all five

pancreatic islet cell technologies (n=16,342 cells) using 3 *de novo* integration methods: Harmony,

Seurat anchor-based integration, and trVAE. UMAP visualizations for the integrated embedding colored

by batch **(a)** and cell types **(b)** for each method. Cell types for reference datasets (c1, celseq, celseq2,

smartseq) were defined within each dataset separately based on marker genes. Query cell types were

defined by Baron et al. Degree of mixing between reference and query datasets **(c)** and mixing

between query donors **(d)** was measured with LISI metric on query cell neighborhoods for each

method, demonstrating equivalent mixing among *de novo* integration methods (compare to Fig 3d-e).

Supplementary Figure 6. Mapping to a fetal liver hematopoiesis trajectory. (a) Size and cell type

composition of each donor sample in the 10x 3' dataset across 27 author-defined cell types from

Popescu et al. (2019). pcw = post-conception weeks. **(b)** Library complexity for each sample in 10x 3'

and 10x 5' datasets, showing low complexity for donor F2 and F5 5'-sequenced samples (removed

from further analysis). **(c)** UMAP projections of query cells into reference UMAP space after Symphony

mapping, faceted by query donor, colored by cell type. Reference UMAP embedding in bottom-right.

Supplementary Figure 7. Fetal liver hematopoiesis cell type classification confusion matrices.

We performed two versions of the reference mapping experiments to assess cell type classification

accuracy across 27 fine-grained cell types: (1) using exclusively 10x 3' data, we mapped one held-out

donor against a reference constructed from the remaining 13 donors (total 14 mapping experiments),

(2) mapping all 10x 5' cells against all 10x 3' cells. Cell type confusion matrices are shown for a 30-NN

cell type classifier **(a)** aggregated across the 14 held-out donor experiments using exclusively 3' data

and **(b)** the 5'-to-3' experiment mapping the full 5' query (n=21,414, n=5 donors) against the full 3'

reference (n=113,063 cells, 14 donors), colored by the proportion of the true cell type that was

classified correctly. True cell type is defined by the original authors (Popescu et al., 2019). Rows (true

query cell types) are sorted by hierarchical clustering on the average gene expression (all genes) for

the cell types to order similar types together. Bar graph (right) shows population size for each cell type.

Supplementary Figure 8. Inferring query surface protein expression in memory T cells. (a) Mean

Pearson correlation for CCA reference between k-NN predicted protein expression and ground truth for

different values of *k*. **(b)** Symphony reference built from a standard mRNA PCA embedding (reference

protein values were not used to build embedding but treated as annotations only). Contour fill

represents density of reference cells. Black points represent soft-cluster centroids in the Symphony

mixture model. **(c)** We measured the accuracy of protein expression prediction based on the PCA

reference with the Pearson correlation between predicted and ground truth expression for each surface

protein across query cells in each donor. Bar height represents the average per-donor correlation for

each protein, and error bars represent standard deviation. **(d)** Ground truth and predicted expression of

CD4, CCR6, and CD69 based on PCA reference. Ground truth is the 50-NN-smoothed expression

measured in the CITE-seq experiment. Colors are scaled independently for each marker from minimum

(blue) to maximum (yellow) expression.

Supplementary Table 1. Links to datasets used in the study.

Supplementary Table 2. Canonical lineage markers (Wilcoxon rank sum test and auROC statistic) and

top 10 differentially expressed genes per cluster used to assign cell types in 10x PBMCs.

Supplementary Table 3. Cell type classification confusion matrices for the three 10x PBMCs mapping

experiments.

Supplementary Table 4. Runtime scalability analysis results (downsampling memory T cell dataset),

showing effect of reference and query size, number of query cells or donors, and number of reference

centroids or embedding dimensions on elapsed time (in secs).

Supplementary Table 5. Cell type classification confusion matrix for multi-donor, multi-species

pancreatic islet cell benchmarking example (mapping Baron et al. 2016 as query) among the reference

mapping methods evaluated.

Supplementary Table 6. Degree of mixing between reference and query cells **(**ref_query LISI) and

between donors within the query (query donor LISI) as well as runtime comparison across different

reference mapping methods and corresponding *de novo* integration methods (Symphony/Harmony,

Seurat v4/Seurat, and trVAE/scArches) for multi-donor, multi-species pancreas benchmarking example.

560 **Supplementary Table 7.** Cell type classification confusion matrix for mapping 10x 5'-sequenced fetal

561 liver cells onto an atlas of 3'-sequenced fetal liver cells (Popescu et al. 2019). True labels provided by

562 the original authors, and predictions were made using a 30-NN classifier.

Methods

1. Symphony

1.1 Symphony overview

The goal of single-cell reference mapping is to embed newly assayed query cells into an existing comprehensive reference atlas, facilitating the automated transfer of annotations from the reference to the query. The optimal mapping method needs to be able to operate at various levels of resolution, capture continuous intermediate cell states, and scale to multimillion cells[27]. Consider a scenario in which we wish to map a query of m cells against reference datasets with n cells, where $m<<n$. Unsupervised integration of measurements across donors, studies, and technological platforms is the standard way to compare single cell datasets and identify cell types. Hence, a "gold standard" reference mapping strategy might be to run Harmony integration on all $m+n$ cells *de novo*. However, this approach is impractical because it is cumbersome and time-intensive to process all the cell-level data for the reference datasets every time a user wishes to reharmonize it with a query. Instead, we envision a pipeline where a reference atlas need only be carefully constructed and integrated once, and all subsequent queries can be rapidly mapped into the same stable reference embedding.

Symphony is a reference mapping method that efficiently places query cells in their precise location within an integrated low-dimensional embedding of reference cells, approximating *de novo* harmonization without the need to reintegrate the reference cells. Symphony is comprised of two algorithms: reference compression and mapping. Expanding upon the linear mixture model framework introduced in Harmony[17], Symphony compression takes in an integrated reference and faithfully compresses it by capturing the components of the model into efficient data structures. The output of reference compression is the minimal set of elements needed for mapping **(Fig. S1b)**. The Symphony mapping algorithm takes as input a new query dataset as well as minimal reference elements and returns the appropriate locations of the query cells within the integrated embedding **(Fig. S1c)**.

Once a harmonized reference is constructed and compressed using Symphony, subsequent mapping

of query cells executes within seconds (**Fig. 3**). Efficient implementations of Symphony are available as

part of an R package at https://github.com/immunogenomics/symphony, along with several

precomputed references constructed from public scRNA-seq datasets. The following sections introduce

the Symphony model, then describes Symphony compression and mapping in terms of the underlying

data structures and algorithms. We also provide **Supplementary Equations** containing more detailed

derivations for reference compression terms.

Glossary

We define all symbols for data structures used in the discussion of Symphony below, including their

dimensions and possible values. Dimensions are in terms of the following parameters:

- *n:* the number of reference cells

- *m:* the number of query cells

- *N:* the total number of cells ($n + m$)

- *g:* the number of genes in the reference after any gene selection

- *d:* the dimensionality of the embedding (e.g. PCs). *d* applies to both reference and query.

- *b:* the number of batches in the reference

- *c:* the number of batches in the query

- *k:* the number of clusters in the mixture model for reference integration (representing latent cell

states)

Reference-related symbols:

$G_r \in \mathbb{R}^{g \times n}$	Input reference gene expression matrix, prior to scaling.
$G_{rs} \in \mathbb{R}^{g \times n}$	Scaled reference gene expression matrix.
$X_r \in \{0,1\}^{b \times n}$	One-hot design matrix assigning reference cells (columns) to batches (rows).
$X_r' \in \{0\}^{c \times n}$	Zero matrix assigning reference cells (columns) to *query* batches (rows). All values are 0 because reference cells do not belong to query batches. This term is used in the derivation for the reference compression terms.

$\mu \in \mathbb{R}^{g \times 1}$	Reference gene means used to center each gene for PCA.
$\sigma \in \mathbb{R}^{g \times 1}$	Reference gene standard deviations used to scale each gene for PCA.
$U \in \mathbb{R}^{g \times d}$	Gene loadings from the original PCA (before Harmony integration).
$Z_r \in \mathbb{R}^{d \times n}$	Original (non-harmonized) PC embedding for reference cells.
$\hat{Z}_r \in \mathbb{R}^{d \times n}$	Integrated embedding for reference cells in harmonized PC (hPC) space, as output by Harmony.
$R_r \in [0,1]^{k \times n}$	Soft cluster assignment of reference cells (columns) to clusters (rows), as output by Harmony. Each column is a probability distribution that sums to 1.
$Y_{cos} \in \mathbb{R}^{d \times k}$	Cluster centroid locations in the harmonized embedding, L2 normalized.
$B_r \in \mathbb{R}^{k \times (1+b) \times d}$	3D tensor of the estimated parameters (betas and intercepts) of the linear mixture model for each of *k* clusters for the reference cells.
$N_r \in \mathbb{R}^{k \times 1}$	First reference compression term. Vector containing the size of each of the k clusters, effectively the number of reference cells contained within them.
$C \in \mathbb{R}^{k \times d}$	Second reference compression term.
$Ref = \{\mu, \sigma, U, Y_{cos}, N_r, C\}$	Symphony minimal reference elements comprising $\mu, \sigma, U, Y_{cos}, N_r, C$.

607 **Query-related symbols:**

$G_q \in \mathbb{R}^{g \times m}$	Input query gene expression matrix, prior to scaling.
$G_{qs} \in \mathbb{R}^{g \times m}$	Query gene expression matrix, scaled by *reference* gene means μ and standard deviations σ.
$X_q \in \{0,1\}^{c \times m}$	Design matrix assigning query cells (columns) to query batches (rows).
$Z_q \in \mathbb{R}^{d \times m}$	Query cell locations in original (non-harmonized) PC embedding.
$\hat{Z}_q \in \mathbb{R}^{d \times m}$	Approximate query cell locations in integrated embedding (hPC space). Output of Symphony reference mapping.
$R_q \in [0,1]^{k \times m}$	Soft cluster assignment of query cells (columns) to clusters (rows). Each column is a probability distribution that sums to 1.
$B_q \in \mathbb{R}^{k \times (1+c) \times d}$	3D tensor of the estimated parameters (betas and intercepts) of the linear mixture model for each of *k* clusters.

1.2 Symphony model and conditions for equivalence to Harmony integration

Symphony and Harmony both use a linear mixture model framework, but the two methods perform

different tasks: Harmony integrates a reference, whereas Symphony compresses the reference and

enables efficient query mapping. To motivate the Symphony model, it is helpful to first briefly review the

mixture model, which serves as the basis. Harmony integrates scRNA-seq datasets across batches

(e.g. multiple donors, technologies, studies) and projects the cells into a harmonized embedding where

cells cluster by cell type rather than batch-specific effects. Harmony takes as input a low-dimensional

embedding of cells (Z) and design matrix with assignments to batches (X) and outputs a harmonized

embedding ($\hat{Z}$) with batch effects removed. Briefly, Harmony works by iterating between two

subroutines—maximum diversity clustering and linear mixture model correction—until convergence. In

the clustering step, cells are probabilistically assigned to soft clusters with a variant of soft *k*-means with

a diversity penalty favoring clusters represented by multiple datasets rather than single datasets. In the

correction step, each cluster learns a cluster-specific linear model that explains cell locations in PC

space as a function of a cluster-specific intercept and batch membership. Then, cells are corrected by

cell-specific linear factors weighted by cluster membership to remove batch-dependent effects. The full

algorithm and implementation are detailed in Korsunsky et al. (2019)[17].

In the scenario of mapping *m* query cells against *n* reference cells, the *de novo* integration strategy

would model all cells as in (1), where the *H* subscript denotes the Harmony solution, in contrast to the

Symphony model which is presented in (2). Let $X_H \in \{0,1\}^{(c+b)\times(m+n)}$ represent the one-hot encoded

design matrix assigning all cells across batches. X_H^* denotes X_H augmented with a row of 1s for the

batch-independent intercept term: $X_H^* = 1||X_H$. The intercept terms represent cluster centroids (location

of "experts" in the mixture of experts model). Z_H represents the low-dimensional PCA embedding of all

cells. R_H represents the probabilistic assignment of cells across *k* clusters, and $diag(R_{Hk}) \in \mathbb{R}^{N \times N}$

denotes the diagonalized *k*th row of R_H. For each cluster *k*, the parameters of the linear mixture model

$B_k \in \mathbb{R}^{(1+c+b)\times d}$ can therefore be solved for as in (1), using ridge regression with ridge penalty

hyperparameter λ. Note that we do not penalize the batch-independent intercept term: $\lambda_0 = 0$,

$\forall_{a \in [1:(c+b)]} \lambda_a = 1$.

De novo Harmony model:

$$B_k = (X_H^* \, diag(R_{Hk}) X_H^{*T} + \lambda I)^{-1} X_H^* diag(R_{Hk}) \, Z_H^T \tag{1}$$

The goal of Symphony mapping is to add new query cells to the model in order to estimate and remove the query batch effects. Symphony mapping approximates *de novo* Harmony integration on all cells, except the reference cell positions in the harmonized embedding do not change. In order for Symphony mapping to be equivalent to *de novo* Harmony, several conditions must be met:

     I.   All cell states represented in the query dataset are captured by the reference datasets—i.e. there are no completely novel cell types in the query.

    II.   The number of reference cells is much larger than the query (*m<<n*).

    III.   The query dataset is obtained independent of the reference datasets—i.e. the reference batch design matrix (X_r) has no interaction with the query batch design matrix (X_q).

We consider these to be fair assumptions for large-scale reference atlases, allowing Symphony to make three key approximations:

    (1) With a large reference, the reference-only PCs approximate the PCs for the combined reference and query datasets. This allows us to project the query cells into the pre-harmonized reference PCA space using the reference gene loadings (U).

    (2) The cluster centroids (Y) for the integrated reference cells approximate the cluster centroids from harmonizing all cells.

    (3) The reference cell cluster assignments (R_r) remains approximately stable with the addition of query cells.

Given these approximations, we can thereby harmonize the reference cells *a priori* and save the reference-dependent portions of the Harmony mixture model (**Supplementary Equations**). In Symphony, we model the reference cells as already harmonized with batch effects removed, so we can thereafter ignore the reference design matrix structure. The Symphony design matrix $X \in [0, 1]^{c \times N}$ assigns all cells (reference and query) to *query* batches only. X^* denotes X augmented with a row of 1s

$(X^*_{[0,\cdot]})$ corresponding to the batch-independent intercepts (we model the intercepts for all cells). The

remaining c rows $(X^*_{[1:c,\cdot]})$ represent the one-hot batch assignment of the cells among the c query

batches. Note that for the reference cell columns, these values are all 0 since the reference cells do not

belong to any *query* batches. The parameters $(B_{qk} \in \mathbb{R}^{(1+c) \times d})$ of the model for each cluster k can

then be solved for as in (2). Similar to Harmony, we use ridge regression penalizing the non-intercept

terms, where $\lambda_0 = 0, \forall_{a \in [1:c]} \lambda_a = 1$.

Symphony model:

$$B_{qk} \approx (X^* \, diag(R_k) \, X^{*T} + \lambda I)^{-1} X^* \, diag(R_k) \, Z^T \tag{2}$$

The matrix $R \in \mathbb{R}^{k \times N}$ denotes the assignment of query and reference cells (columns) across the

reference clusters (rows). $Z \in \mathbb{R}^{d \times N}$ denotes the horizontal matrix concatenation of the uncorrected

query cells in original PC space (Z_q) and corrected reference cells in harmonized space ($\hat{Z}_r$). For each

cluster k, let matrix $B_{qk} \in \mathbb{R}^{(1+c) \times d}$ represent the query parameters to be estimated. The first row of

B_{qk} represents the batch-independent intercept terms, and the remaining c rows of B_{qk} represent the

query batch-dependent coefficients, which can be regressed out to harmonize the query cells with the

reference. Note that the intercept terms from Symphony mapping should equal the cluster centroid

locations from the integrated reference since the harmonized reference cells are modeled only by a

weighted average of the centroid locations for the clusters over which it belongs (and a cell-specific

residual). Hence, the reference cell positions should not change when removing query batch effects.

The matrices X^*, R_k, and Z in (2) can be partitioned into query and reference-dependent portions. In the

Supplementary Equations, we show in detail how the reference-dependent portions can be further

simplified into a k x 1 vector and k x d matrix (N_r and C), which we call "reference compression terms."

Intuitively, the vector N_r contains the size (in cells) of each reference cluster. The matrix $C = R_r \hat{Z}_r^T$ does

not have as intuitive an explanation but follows from the derivation (**Supplementary Equations**). These

terms can be computed at the time of reference building and saved as part of the minimal reference

elements to reduce the necessary computations during mapping.

1.3 Reference building and compression

Reference compression is the key idea that allows for the efficient mapping of new query cells onto the harmonized reference embedding without the need to reintegrate all cells. To construct a Symphony reference with minimal elements needed for mapping, reference cells are first harmonized in a low-dimensional space (e.g. PCs) to remove batch-dependent effects. Symphony then compresses the Harmony mixture model components to be saved for subsequent query mapping.

Data structures

Symphony takes as input a gene expression matrix for reference cells (G_r) and corresponding one-hot-encoded design matrix (X_r) containing metadata about assignment of cells to batches. It outputs a set of data structures, referred to as the Symphony minimal reference elements, that captures key information about the reference embedding that can be subsequently used to efficiently map previously unseen query cells (**Algorithm 1**). These components include the gene mean (μ) and standard deviation (σ) used to scale the genes, the PCA gene loadings (U), the final L2-normalized cluster centroid locations (Y_{cos}), and precomputed values which we call the "reference compression terms" (N_r and C) that expedite the correction step of query mapping (**Supplementary Equations**). These elements are a subset of the components available once Harmony integration is applied to the reference cells. Note that other input embeddings, such as canonical correlation analysis (CCA), may be used in place of PCA as long as the gene loadings to perform query projection into those coordinates are saved.

Table 1 lists the Symphony minimal reference elements required to perform mapping. **Table 2** shows additional components of a "full" Harmony reference that are not included in the Symphony reference elements. Importantly, the dimensions of the Symphony data structures do not require information on the *n* individual reference cells and hence do not scale with the raw number of reference cells. Rather the components scale with the biological complexity captured (i.e. number of clusters *k* and dimensionality of embedding *d*). Conversely, the Harmony data structures store information on a per-cell basis (*n*). Note that in practice the integrated embedding of reference cells ($\hat{Z}_r$) listed in **Table 2** is

709 needed to perform downstream transfer of annotations from reference to query cells (e.g. k-NN), but it

710 is not required during any computations of the mapping step.

711 **Table 1: Symphony minimal reference elements**

$\mu \in \mathbb{R}^{g \times 1}$	Reference gene means used to center each gene for PCA.
$\sigma \in \mathbb{R}^{g \times 1}$	Reference gene standard deviations used to scale each gene for PCA.
$U \in \mathbb{R}^{g \times d}$	Gene loadings to project from expression to PCA (or CCA) space
$Y_{cos} \in \mathbb{R}^{d \times k}$	Cluster centroid locations in harmonized PC space, L2 normalized.
$N_r \in \mathbb{R}^{k \times 1}$	First reference compression term. Vector containing the size of each of the k clusters, effectively the number of reference cells contained within them.
$C \in \mathbb{R}^{k \times d}$	Second reference compression term.

713 **Table 2: Additional components of Harmony reference**

$G_r \in \mathbb{R}^{g \times n}$	Input reference gene expression matrix, prior to scaling.
$X_r \in \{0,1\}^{b \times n}$	Design matrix assigning reference cells (columns) to reference batches (rows).
$B_r \in \mathbb{R}^{k \times (1+b) \times d}$	3D tensor of the estimated parameters (betas and intercepts) of the linear mixture model for each of *k* clusters for the reference cells.
$\hat{Z}_r \in \mathbb{R}^{d \times n}$	Integrated embedding for reference cells in harmonized PC ("hPC") space, as output by Harmony.
$R_r \in [0,1]^{k \times n}$	Soft cluster assignment of reference cells (columns) to clusters (rows), as output by Harmony. Each column is a probability distribution that sums to 1.

Algorithm

Starting from reference cell gene expression, we first perform within-cell library size normalization (if not

already done) and variable gene selection to obtain G_r, scaling of the genes to have mean 0 and

variance 1 (saving μ and σ for each gene), and PCA to embed the reference cells in a low-dimensional

space, saving the gene loadings (U) (**Implementation Details**). Then, the PCA embedding (Z_r) and

batch design matrix (X_r) are used as input to Harmony integration to harmonize over batch-dependent

sources of variation. Given the resulting harmonized embedding ($\hat{Z}_r$) and final soft assignment of

reference cells to clusters (R_r), the locations of the final reference cluster centroids $Y \in \mathbb{R}^{d \times k}$ can be

calculated as in (3) and saved.

$$Y = \hat{Z}_r R_r^T \tag{3}$$

724 Symphony then computes the reference compression terms N_r (intuitively, the number of cells per

725 cluster) and C, which does not have an intuitive explanation but can be directly computed as $C = R_r \hat{Z}_r^T$.

726 Refer to the **Supplementary Equations** for a complete mathematical derivation of the compression

727 terms. Symphony reference building ultimately returns the minimal reference elements: $\mu, \sigma, U, Y_{cos}, N_r$,

728 and C (**Fig. S1a**).

---

729 **Algorithm 1** Build Symphony reference

---

function BUILDREFERENCE(G_r, X_r)

$\mu, \sigma, G_{rs} \leftarrow$ **SCALE**(G_r)

$U, Z_r \leftarrow$ **PCA**(G_{rs})

$\hat{Z}_r, R_r \leftarrow$ **HARMONIZE**(Z_r, X_r)

$Y \leftarrow \hat{Z}_r R_r^T$

$Y_{cos} \leftarrow {Y_{[\cdot,i]}} \big/ {\left\| Y_{[\cdot,i]} \right\|_2}$ $\triangleright\ L_2\ normalize\ cluster\ centroids$

$N_r \leftarrow rowSums(R_r)$ $\triangleright\ First\ compression\ term$

$C \leftarrow R_r \hat{Z}_r^T$ $\triangleright\ Second\ compression\ term$

$Ref \leftarrow (\mu, \sigma, U, Y_{cos}, N_r, C)$

return Ref $\triangleright\ Return\ minimal\ reference\ elements$

---

741 ## 1.4 Symphony mapping

742 The Symphony mapping algorithm localizes new query cells to their appropriate locations in the

743 harmonized embedding without the need to run integration on the reference and query cells altogether.

744 The joint embedding of reference and query cells can be used for downstream analyses, such as

745 transferring cell type annotations from the reference cells to the query cells.

Data structures

Symphony mapping takes as input the gene expression matrix for query cells (G_q), query design matrix assigning query cells to batches (X_q), and the precomputed minimal elements for a reference (Ref). It outputs a query object containing the locations of query cells in the integrated reference embedding $(\hat{Z}_q;$ **Algorithm 2**). **Table 3** lists the components of the query object that is returned by Symphony.

Table 3: Components of Symphony query

$G_q \in \mathbb{R}^{g \times m}$	Input query gene expression matrix, prior to scaling.
$X_q \in \{0,1\}^{c \times m}$	Design matrix assigning query cells (columns) to query batches (rows).
$Z_q \in \mathbb{R}^{d \times m}$	Query cell locations in original (non-harmonized) PC embedding.
$\hat{Z}_q \in \mathbb{R}^{d \times m}$	Approximate query cell locations in integrated embedding (hPC space).
$R_q \in [0,1]^{k \times m}$	Soft cluster assignment of query cells (columns) to clusters (rows). Each column is a probability distribution that sums to 1.
$B_q \in \mathbb{R}^{k \times (1+c) \times d}$	3D tensor of the estimated parameters (betas and intercepts) of the linear mixture model for each of k clusters.

Algorithm

The input to the query mapping procedure is a gene expression matrix (G_q) and design matrix (X_q) for query cells, and the output is the locations of the cells in the harmonized embedding $(\hat{Z}_q)$. At a high level, the mapping algorithm first projects the query cells into the original, non-harmonized PC space as the reference cells using the reference gene loadings (U) and assigns probabilistic cluster membership across the reference cluster centroid locations. Then, the query cells are modeled using the Symphony mixture model and corrected to their approximate locations in the integrated embedding by regressing out the query batch-dependent effects (**Algorithm 2**).

Projection of query cells into pre-harmonized PC Space

Symphony projects the query cells into the same original PCs (Z_r) as the reference. Symphony assumes that, given a much smaller query compared to the reference ($m<<n$), the PCs will remain

approximately stable with the addition of query cells. To project the query cells, we first subset the

query expression data by the same variable genes used in reference building and scale the normalized

expression of each gene by the same mean and standard deviations used to scale the reference cells

(μ, σ). Let G_{qs} denote the query gene expression matrix scaled by the reference gene means and

standard deviations. We can then use the reference gene loadings (U) to project G_{qs} into reference PC

space. In (4), $Z_q \in \mathbb{R}^{d \times m}$ denotes the PC embedding for the query cells. Note that if an alternate

starting embedding (e.g. CCA) is used instead of PCA, the gene loadings must be saved to enable this

query projection step.

$$Z_q = U^T G_{qs} = \Sigma_q V_q^T \tag{4}$$

Soft assignment across reference clusters

Once the query cells are projected into PC space, we soft assign the cells to the reference clusters

using the saved reference centroid locations (Y_{cos}). Symphony assumes that the reference cluster

centroid locations remain approximately stable with the addition of a much smaller query dataset since

the query contains no novel cell types. Under these conditions, we use a previously published objective

function for soft *k*-means clustering (5), which includes a distance term and an entropy regularization

term over R weighted by hyperparameter σ. This is the same objective function as the clustering step of

Harmony, except it does not include the diversity penalty term. In Harmony, the purpose of the diversity

term is to penalize clusters that are only represented by one or a few datasets (suggesting they do not

represent true cell types). In contrast, Symphony does not require the use of a diversity penalty

because the reference centroids have already been established. Furthermore, the query cell types can

comprise a subset of a larger set of reference cell types, and therefore not all clusters are necessarily

expected to be represented in the query. We can solve for R_q, the optimal probabilistic assignment for

query cells across each of the k reference clusters (**Implementation Details**).

$$\min_{R,Y} \sum_{i,k} R_{ki} \|Z_i - Y_k\|^2 + \sigma R_{ki} \log R_{ki} \tag{5}$$

$$\text{s.t. } \forall_i \forall_k R_{ki} > 0, \forall_i \sum_{k=1}^{K} R_{ki} = 1$$

Mixture of experts correction

The final step in Symphony mapping is to model then remove the query batch effects to obtain $\hat{Z}_q$, the

approximate location of query cells in the harmonized reference embedding. In equation (2), we

modeled the reference and query cells together and wish to solve for the query parameters $B_{qk} \in$

$\mathbb{R}^{(1+c) \times d}$ for each cluster k. The reference-dependent terms in (2) were previously computed and

saved in compressed form (N_r and C). With R_q and Z_q calculated from query cell projection and

clustering, we can finally solve for B_{qk}. Similar to the correction step of Harmony, we obtain cell-specific

correction values for the query cells by removing the batch-dependent terms captured in $B_{qk[1:c,\cdot]}$. Note

that the reference batch terms are neither modeled nor corrected during reference mapping, so the

harmonized reference cells do not move.

The final locations of the query cells in the harmonized embedding are estimated by iterating over all k

clusters and subtracting out the non-intercept batch terms for each cell weighted by cluster membership

(6). Intuitively, the query centroids are moved so that they overlap perfectly with the reference centroids

in the harmonized embedding. $\hat{Z}_{q[i]}$ denotes the approximate location in harmonized PC space for

query cell i.

$$Z_{q[i]} = \sum_k R_{q[k,i]} \left[B_{qk[0,\cdot]}^T + B_{qk[1:c,i]}^T X_q \right] + \varepsilon$$

$$\hat{Z}_{q[i]} = Z_{q[i]} - \sum_k R_{q[k,i]} B_{qk[1:c,\cdot]}^T X_q \tag{6}$$

$$\hat{Z}_{q[i]} = \sum_k R_{q[k,i]} B_{qk[0,\cdot]}^T + \varepsilon$$

---

801   **Algorithm 2** Map query cells onto reference

---

function QUERYMAPPING(G_q, X_q, Ref)

$\quad G_{qs} \leftarrow \textbf{SCALE}(G_q, Ref\$\mu, Ref\$\sigma) \qquad \rhd \$ \text{ denotes accessing a component of } Ref$

$Z_q \leftarrow \textbf{PCAPROJECTION}(G_{qs}, Ref\$U)$

$R_q \leftarrow \textbf{CLUSTER}(Z_q, Ref\$Y_{cos})$

$\hat{Z}_q \leftarrow Z_q$

for $k \leftarrow 1 \dots k$ **do**

$E \leftarrow X_q^* R_q^{(k)} X_q^{*T}$ ▷ X_q^*: *query design matrix augmented with row of 1s*

$E_{[0,0]} \leftarrow E_{[0,0]} + Ref\$N_{r(k)}$

$F \leftarrow X_q^* R_q^{(k)} Z_q^T$

$F_{[0,\cdot]} \leftarrow F_{[0,\cdot]} + Ref\$C_{[k,\cdot]}$

$B_{qk} \leftarrow (E + \lambda I)^{-1}(F)$

$B_{qk[0,\cdot]} \leftarrow 0$ ▷ *Do not correct the intercept terms*

$\hat{Z}_q \leftarrow \hat{Z}_q - B_{qk}^T X_q^* R_q^{(k)}$

return $\hat{Z}_q$ ▷ *Return query locations*

1.5 Implementation details

Reference building and compression

Variable gene selection and scaling

Starting with the gene expression matrix for reference cells, we perform log(CP10K) library size

normalization of the cells (if not already done), subset by the top g variable genes by the vst method

(as provided in Seurat[18]), which fits a line to the log(variance) and log(mean) relationship using local

polynomial regression, then standardizes the features by observed mean and expected variance,

calculating gene variance on the standardized values, which is re-implemented as a standalone

function at https://github.com/immunogenomics/singlecellmethods. The data is scaled such that the

expression of each gene has a mean expression of 0 and variance of 1 across all cells.

PCA

828   We perform dimensionality reduction on the scaled gene expression G_{rs} using principal component

829   analysis (PCA). PCA projects the data a low-dimensional, orthonormal embedding that retains most of

830   the variation of gene expression in the dataset. Singular value decomposition (SVD) is a matrix

831   factorization method that can calculate the PCs for a dataset. Here, we use SVD (irlba package in R[53])

832   to perform PCA. SVD states that matrix G_{rs} with dimensions $g \times n$ can be factorized as:

$$G_{rs} = U\Sigma V^T \tag{7}$$

In (7), $\Sigma V^T = Z_r$ (dimensions $d \times n$) represents the embedding of reference cells in PC space, after

truncating the matrix on the first d (by default, $d = 20$) PCs. The gene loadings ($U \in \mathbb{R}^{g \times d}$) are saved.

Note that an alternative embedding, such as canonical correlation analysis (CCA) may be used in place

of PCA, as long as the gene loadings are saved.

Harmony integration

The PCA embedding (Z_r) is then input to Harmony for dataset integration. By default, Symphony uses

the default parameters for the cluster diversity enforcement ($\theta = 2$), the entropy regularization

hyperparameter for soft k-means ($\sigma = 0.1$), and the number of clusters $k = \min\left(100, \frac{n}{30}\right)$. We save the

L2-normalized cluster centroid locations Y_{cos} to the reference object since query mapping employs a

cosine distance metric. If the reference has a single-level batch structure, no integration is performed,

and the clusters are defined using soft k-means.

Query mapping

Normalization and scaling

The gene expression for query cells are assumed to be library size normalized in the same manner that

was used to normalize the reference cells (e.g. log(CP10K)). During scaling, the query data is subset

by the same variable genes from the reference datasets, and query gene expression is scaled by the

reference gene means and standard deviations. Any genes present in the query but not the reference

are ignored, and any genes present in the reference but not the query have scaled expression set to 0.

Clustering step uses cosine distance

As in Harmony, in practice we use cosine distance rather than Euclidean distance in the clustering step.

For the computation of the distance term, we L2-normalize the columns (cells) of Z and columns

(centroids) of Y_k such that the squared values sum to 1 across each column. Let the terms $Z_{q\_cos[\cdot,i]}$ and

$Y_{\cos[\cdot,k]}$ represent the L2-normalized locations of query cell i and the reference centroid for cluster k in

PC space, respectively. We compute the cosine distance between the cells and centroids. Since all

$Z_{q\_cos[\cdot,i]}$ and $Y_{\cos[\cdot,k]}$ each have unity norm, the squared Euclidean distance $\left\|Z_{q\_cos[\cdot,i]} - Y_{\cos[\cdot,k]}\right\|^2$ is

equivalent to the cosine distance $2\left(1 - \cos(Y_{\cos[\cdot,k]}, Z_{q\_cos[\cdot,i]})\right) = 2(1 - Y^T_{\cos[k,\cdot]} Z_{q\_cos[\cdot,i]})$. Therefore, the

objective function for query assignment to centroids becomes:

$$\min_{R,Y} \sum_{i,k} 2R_{q[k,i]}(1 - Y^T_{\cos[k,\cdot]} Z_{q\_cos[\cdot,i]}) + \sigma\, R_{q[k,i]} \log R_{q[k,i]} \tag{8}$$

$$\text{s.t. } \forall_i \forall_k R_{q[k,i]} > 0, \forall_i \sum_{k=1}^{K} R_{q[k,i]} = 1$$

860 We can solve the optimization problem using an expectation-maximization framework. Following the

861 same strategy as Korsunsky et al. (2019), we calculate R_i, the optimal probabilistic assignment for each

862 query cell i across each of the k reference clusters. In (9), we can interpret $R_{q[k,i]}$ as the probability that

863 query cell i belongs to cluster k. The denominator term simply ensures that for any given cell i, the

864 probabilities across all k clusters sum to one. By default, sigma=0.1

$$R_{q(k,i)} = \frac{\exp\left(-\frac{2}{\sigma}(1 - Y^T_{\cos[k,\cdot]} Z_{q\_cos[\cdot,i]})\right)}{\sum_{k=1}^{K} \exp\left(-\frac{2}{\sigma}(1 - Y^T_{\cos[k,\cdot]} Z_{q\_cos[\cdot,i]})\right)} \tag{9}$$

2. Analysis details

2.1 10x PBMCs analysis

Preprocessing scRNA-seq data

The three 10x PBMCs datasets were previously preprocessed by our group as part of the Harmony

publication. We used the same log(1+CP10K) normalized expression data, filtered as described in

Korsunsky et al. (2019)[17]. The PBMCs consist of cells from three technologies: 3'v1 (n=4,808 cells),

3'v2 (8,372 cells), and 5' (7,612 cells).

Symphony mapping experiments

To construct each of three references for subsequent mapping, we aggregated two reference datasets

into a single normalized expression matrix and identified the top 2,000 variable genes across all cells

using the variance stabilizing transformation (VST) procedure[18]. We ran Harmony on the top 20 PCs

and default 100 clusters, harmonizing over 'technology' with default parameters. For Symphony

mapping, we specified query 'technology' covariate.

Constructing gold standard embedding

To construct the gold standard *de novo* Harmony embedding, we concatenated all three datasets

together into a single expression matrix, subsetted by the top 2,000 variable genes over all cells, and

ran Harmony integration on the top 20 PCs, harmonizing over 'technology' with default parameters.

Assigning ground truth cell types

We clustered the cells in the gold standard embedding using the Louvain algorithm as implemented in

the Seurat functions *BuildSNN* and *RunModularityClustering*[18]. For PBMCs, we used nn_k = 5 (to

capture rare HSCs), nn_eps = 0.5, and resolution = 0.8. We labeled clusters with ground truth cell types

according to expression of canonical lineage marker genes (**Table S2**). PBMCs were assigned across

7 types: T (*CD3D*), NK (*GNLY*), B (*MS4A1*), Monocytes (*CD14*, *FCGR3A*), DCs (*FCER1A*),

Megakaryocytes (*PPBP*), and HSCs (*CD34*). Clusters were labeled if the AUC (calculated using

presto[54]) for the corresponding lineage marker was >0.62. For clusters that did not express a specific

lineage marker, we manually assigned a cell type based on the top differentially expressed genes

(**Table S2**). PBMCs cluster 20 was identified as low-quality cells (high in mitochondrial genes; **Table**

S2). We removed all cells in this cluster (n=94) from further analyses. The final ground truth labels were

used in downstream analyses and cell type classification accuracy evaluation.

Evaluation of mixing and cell type classification accuracy

To compare dataset mixing between *de novo* integration and mapping, we calculated Local Inverse

Simpson Index (LISI) using the *compute_lisi* function from https://github.com/immunogenomics/LISI.

For each mapping experiment, we calculated dataset LISI on all cells, then subsetted the results for

query cell neighborhoods only to measure the effective number of datasets in the local neighborhood of

each query cell.

We predicted query cell types by transferring reference cell type annotations using the *knn* function in

the 'class' R package (k=5). We calculated overall accuracy across all query cells and cell type F1

scores (the harmonic mean of precision and recall, ranging from 0 to 1). Precision = TP/(TP+FP), recall

= TP/(TP+FN), F1 = (2 * precision * recall) / (precision + recall). Cell type F1 was the metric Abdelaal et

al. used to benchmark automated cell type classifiers[35]. We used their *evaluate.R* script to calculate

confusion matrices and F1 scores by cell type.

Quantifying local similarity between two embeddings

k-NN-correlation (k-NN-corr) is a new metric that quantifies how well a given alternative embedding

preserves the local neighborhood structure with respect to a gold standard embedding. Anchoring on

each query cell, we calculate (1) the pairwise similarities to its *k* nearest reference neighbors in the gold

standard embedding and (2) the similarities between the same query-reference neighbor pairs in an

alternate embedding (**Methods**), then calculate the Spearman (rank-based) correlation between (1)

and (2). For similarity, we use the radial basis function kernel: *similarity*$(x,y) = \exp(-\|x-y\|^2/(2\sigma^2))$. For

each query cell, we obtain a single k-NN-corr value capturing how well the relative similarities to its *k*

nearest reference neighbors are preserved. Note that k-NN-corr is asymmetric with respect to which

embedding is selected as the gold standard and which is selected as the alternative because the

nearest neighbor pairs are fixed based on how they were defined in the gold standard. The distribution

of k-NN-corr scores for all query cells can measure the embedding quality, where higher k-NN-corr

indicates greater recapitulation of the gold standard. Lower values for *k* assess more local

neighborhoods, whereas higher *k* assesses more global structure.

We calculated k-NN-corr between the gold standard Harmony embedding and two alternative

embeddings: (1) the full Symphony mapping algorithm (projection, clustering, and correction) and (2)

PCA-projection only as a comparison to a batch-naïve mapping. PCA-projection refers to the first step

of Symphony mapping, where query cells are projected from gene expression to pre-harmonized PC

space: $Z_q = U^T G_q$.

2.2 Benchmarking against automatic cell type classifiers

We downloaded the PbmcBench benchmarking dataset used by a recent comparison of automatic cell

type identification methods[35,39]. For each of 48 train-test experiments previously described[35], we used

the same evaluation metrics (median cell type F1 score) to evaluate Symphony in comparison to the 22

other classifiers. We obtained the numerical F1-score results for the other classifiers for all 48

experiments directly from the authors in order to determine Symphony's place within the rank ordering

of classifier performance.

During reference building, we explored two different gene selection methods: (1) unsupervised (top

2000 variable genes) and (2) supervised based on identifying the top 20 differentially expressed (DE)

genes per cell type. Option (2) was included to give Symphony the same information as prior-

knowledge classifiers (e.g. SCINA with 20 marker genes per cell type). We used the 'presto' package[54]

for DE analysis. No integration was performed because the reference had a single-level batch structure

(clusters were simply assigned using soft k-means). Onto each of 7 references (each representing 1

protocol for donor pbmc1), we mapped either a second protocol for donor pbmc1 (6 experiments) or the

same protocol for donor pbmc2 (1 experiment). Given the resulting Symphony joint feature

embeddings, we used three downstream classifiers to predict query cell types: 5-NN, SVM with a radial

kernel, and glm_net with ridge[55]. A total of 6 Symphony-based classifiers were tested (2 gene selection

methods * 3 downstream classifiers).

2.2 Pancreas benchmark

943

Constructing the pancreas query with mouse and human

944

945 The pancreas query dataset (Baron et al., 2016; inDrop, n=8,569 human and 1,886 mouse cells) along

946 with author-defined cell type labels were downloaded from https://hemberg-

947 lab.github.io/scRNA.seq.datasets/human/pancreas/. In order to combine the human and mouse

948 matrices into a single aggregated query, we "humanized" the mouse expression matrix by mapping

949 mouse genes to their orthologous human genes. This mapping was computed using the biomaRt R

950 package[56], mapping `mgi_symbol` from the `mmusculus_gene_ensembl` database to `hgnc_symbol`

951 from the `hsapien_gene_ensembl` database. We added additional ortholog pairs from HomoloGene

952 (https://ftp.ncbi.nih.gov/pub/HomoloGene/build37.2/homologene.data) to obtain a total of 22,578 human

953 to mouse gene ortholog pairs. We represented this map as a matrix, with mouse genes as rows, human

954 genes as columns, and values in {0,1} assigned to denote whether a mouse gene maps to a human

955 gene. We then normalized the matrix to have each column sum to one, effectively creating a count-

956 preserving probabilistic map from d mouse to D human genes $M \in R^{D \times d}$. Mapping from mouse to

957 human genes is then performed with matrix multiplication: $U_{human} = MU_{mouse}$. Note that while the mouse

958 gene expression matrix U_{mouse} contains only integers ($U_{mouse} \in Z^{d \times N}$), the many-to-many mapping means

959 that the mapped human gene expression matrix U_{human} may contain non-integers ($U_{human} \in R^{D \times N}$). For

960 any human orthologs that were missing in the mouse expression data, we filled in the expression with

961 zeroes. We then log(CP10K+1) normalized the query cells.

962 ***Preprocessing reference scRNA-seq data***

963 The pancreas reference datasets were each sequenced with a different technology: Fluidigm C1

964 (n=638 cells), CEL-seq (946 cells), CEL-seq2 (2,238 cells), Smart-seq2 (2,355 cells). We obtained the

965 log(1+CP10K) normalized data from the Harmony publication[17]. The pancreas cells were previously

966 assigned across 9 types within each dataset individually according to cluster-specific expression of

967 marker genes: alpha (*GCG*), beta (*MAFA*), gamma (*PPY*), delta (*SST*), acinar (*PRSS1*), ductal

(*KRT19*), endothelial (*CDH5*), stellate (*COL1A2*), and immune (*PTPRC*). We removed 290 cells that

were left unassigned as part of ambiguous or outlier clusters during within-dataset annotation, leaving

5,887 reference cells.

We benchmarked three reference mapping methods as follows:

Symphony mapping onto a Harmony reference

We calculated the top 1,000 variable genes within each of the four reference dataset separately using

VST then pooled them (total 2,236 variable genes) for PCA. For reference integration, we ran Harmony

on the top 20 PCs, harmonizing over 'donor' ($\theta = 2$) and 'technology' ($\theta = 4$), with $\tau = 5$. For Symphony

mapping, we specified query 'donor', 'species', and 'technology' covariates.

As a comparison with *de novo* integration, we ran Harmony integration on all 5 datasets together. We

pooled the top 1,000 variable genes within each dataset (total 2,650 genes), calculated the top 20 PCs,

and harmonized over 'species' ($\theta = 2$), 'donor' ($\theta = 2$), and 'technology' ($\theta = 2$).

Seurat v4 mapping onto a Seurat reference

We ran Seurat version 4 (beta)[30] (Seurat_3.9.9.9024) and followed the steps from the author's tutorial

(https://satijalab.org/seurat/v3.2/integration.html) to integrate the reference datasets given that the

FindIntegrationAnchors and *IntegrateData* functions for de *novo* integration are equivalent between

Seurat v3 and v4 to our understanding. We used the same 2,236 variable genes as above and 20 PCs.

We followed the tutorial (https://satijalab.org/seurat/v4.0/reference_mapping.html) to map each donor

dataset from the query individually. We used the *FindTransferAnchors* function with reduction =

'pcaproject' and *MapQuery* function with reference.reduction = 'pca' (as the documentation

recommends for unimodal analysis).

As a comparison with *de novo* integration, we ran Seurat v3/4 integration (*FindIntegrationAnchors* and

IntegrateData) on all 5 datasets (integrating over plate-based technologies and Baron donors as

batches) with the same 2,650 variable genes as above.

scArches mapping onto a trVAE reference

We ran scArches[28] version 0.3 with trVAE[33] using default parameters provided in the authors'

notebooks (https://github.com/theislab/scarches/tree/master/notebooks). For the pancreas analysis, we

only had access to normalized expression data and therefore ran scArches with trVAE using the mse

reconstruction loss function. We included query batch information in the condition_key parameter.

As a comparison with *de novo* integration, we ran trVAE on all 5 datasets with default parameters,

specifying batch as 'dataset' for the 4 plate-based datasets and 'donor' for the Baron et al. dataset.

Evaluation metrics

We used the resulting joint (reference and query) cell embedding to predict query cell types from

reference cells using a 5-NN classifier and calculated cell type prediction F1 scores, as described

above. Note that for the cell type prediction and cell type F1 score calculation, we excluded query

Schwann cells from the accuracy metrics because that cell type is not present in the reference.

To assess degree of mixing, we calculated ref_query LISI and query donor LISI on query cell

neighborhoods using the *compute_lisi* function as above. ref_query LISI measures how well the

reference and query datasets are mixed (max ref_query LISI = 2), whereas query donor LISI measures

how well the individual donors within the query dataset are mixed (max = 6).

We measured mapping runtime and corresponding *de novo* integration runtime for each method as

elapsed time starting from gene expression. Symphony and Seurat were run in interactive Jupyter

notebooks on a Linux server (Intel Xeon E5-2690 v.3 processors), whereas scArches/trVAE was run on

GPUs (graphics card GP100GL [Tesla P100 PCIe 16GB]) to speed up runtime.

2.3 Fetal liver hematopoiesis trajectory inference example

We obtained post-filtered, post-doublet removal data directly from the authors[46] along with author-

defined cell type annotations for 113,063 cells sequenced with 10x 3' end bias and a separate 25,367

cells sequenced with 10x 5' end bias. For building the harmonized reference from all 3' cells, we

followed the same variable gene selection procedures as the original authors, using the Seurat

variance/mean ratio (VMR) method with parameters min_expr = .0125, max_expr = 3, and

min_dispersion = 0.625 (resulting in 1,917 variable genes). For each of 14 held-out donor experiments

within the 3' dataset, we integrated the reference with Harmony on 13 donors (θ = 3). During Symphony

mapping, we specified query 'donor' covariate. For mapping 5' cells against a 3' reference, we removed

two donors (F2 and F5, n=3,953) from the 5' query based on low library complexity (**Fig. S5b**), leaving

n=21,414 cells from 5 donors. We integrated the reference (all 14 donors sequenced with 3' end bias)

with Harmony over 'donor' (θ = 3). During Symphony mapping, we specified both 'donor' and

'technology' as covariates. We predicted query cell types by transferring reference cell type annotations

using the *knn* function in the 'class' R package (k=30). We visualized the aggregated confusion matrix

across all 14 held-out donor experiments as well as the confusion matrix for the single 5'-to-3'

experiment using ComplexHeatmap R package[57].

For the trajectory inference analysis, we obtained trajectory coordinates from the force directed graph

(FDG) embedding of all 3'-sequenced cells from the original authors[46], forming a reference trajectory.

We restricted the trajectory to immune cell types only (excluding hepatocytes, fibroblasts, and

endothelial). We then mapped a subset of the query cells belonging to the MEM lineage (MEMPs,

megakaryocytes, mast cells, early-late erythroid; n=5,141) to the reference-defined trajectory by

averaging the FDG coordinates of the 10 reference immune cell neighbors in the Symphony

embedding.

035   2.4 Memory T cell surface protein inference example

We used a memory T cell CITE-seq dataset collected from a tuberculosis disease progression cohort of

259 individuals of admixed Peruvian ancestry[40]. The dataset includes expression of the whole

transcriptome (33,538 genes) and 30 surface protein markers from 500,089 memory T cells isolated

from PBMCs. Including technical replicates, 271 samples were processed across 46 batches.

To assess protein prediction accuracy using Symphony embeddings, we randomly selected 217

samples (411,004 cells), normalized the expression of each gene (log2(CP10K)) and built a Symphony

reference based on mRNA expression, correcting for donor and batch. The held-out 54 samples

comprised the query that we mapped onto the reference. We predicted the expression of each of the 30

surface proteins in each of the query cells by averaging the protein's expression across the cell's 50

nearest reference neighbors. Nearest neighbors were defined based on Euclidean distance in the

batch-corrected low-dimensional embedding. As a ground truth for each protein in each query cell, we

computed a smoothed estimate of the cells' measured protein expression by averaging the protein's

expression across the cell's 50 nearest neighbors in the batch-corrected complete PCA embedding of

all 259 donors. We did not use the cells' raw measured protein expression due to dropout. We

computed the Pearson correlation coefficient between our predicted expression and the ground truth

expression across all cells per donor for each marker.

To assess protein prediction accuracy based on mapping to a joint mRNA and protein-based

Symphony reference, we first built an integrated reference by using canonical correlation analysis

(CCA) to project cells into a low-dimensional embedding maximizing correlation between mRNA and

protein features. We randomly selected 217 samples (395,373 cells) to comprise this reference, and

normalized the expression of each gene (log2(CP10K)), selected the top 2,865 most variable genes,

and scaled (mean = 0, variance = 1) all mRNA and protein features. We computed 20 canonical

variates (CVs) with the *cc* function in the CCA R package[58] and corrected the mRNA CVs for donor and

batch effects with Harmony. Then, we used Symphony to construct a reference based on the batch-

corrected CVs, gene loadings on each CV, and mean and standard deviation used to scale each gene

prior to CCA. The held-out 54 samples comprised the query that we mapped onto the reference. As

described above, we predicted the expression of each of the 30 surface proteins in each of the query

cells based on the cell's 5, 10, or 50 nearest neighbors in the reference, estimated the smoothed

ground truth expression of each protein in each query cell (now based on the batch-corrected CCA

embedding of all 259 donors) and computed the Pearson correlation coefficient for each marker.

2.5 Visualization

For visualizing the embeddings using UMAP[59] (and included as the default in Symphony), we used the

'uwot' R package with the following parameters: n_neighbors=30, learning_rate=0.5, init = 'laplacian',

metric = 'cosine', min_dist=0.1 (except min_dist=0.3 for pancreas and fetal liver examples). For each

Symphony reference, we saved the uwot model at the time of UMAP using the *uwot::save_uwot*

function and saved the path to the model file as part of the Symphony reference object. Saving the

reference UMAP model allows for the fast projection of new query cells into reference UMAP space

from the query embedding from Symphony mapping using the function *uwot::transform*.

For the pancreas benchmarking, we computed a *de novo* UMAP embedding on the joint reference and

query embedding because a UMAP projection can potentially obscure differences between the

projected data and dataset used to construct the UMAP model. For general purposes, we recommend

UMAP projection when the reference cell UMAP coordinates are desired to remain stable.

To distinguish the reference plots from query plots, we visually present the reference embedding as a

contour density instead of individual cells. The density plots were generated using ggplot2 function

stat_density_2d with geom = 'polygon' and contour_var = 'ndensity'. We provide custom functions to

generate these plots as part of the Symphony package.

2.6 Runtime scalability analysis

We downsampled a large memory T cell dataset[40] to create benchmark reference datasets with 20,000,

50,000, 100,000, 250,000, and 500,000 cells. For each, we built a reference (20 PCs, 100 centroids)

integrating over 'donor' and mapped three different-sized queries: 1,000, 10,000, and 100,000 cells. To

isolate the separate effects of number of query cells and number of query batches on mapping time, we

mapped against the 50,000-cell reference: (1) varying the number of query cells (from 1,000 to 10,000

cells) while keeping the number of donors constant and (2) varying the number of query donors (6 to

120 donors) while keeping the number of cells constant (randomly sampling 10,000 cells). We also

performed separate experiments varying the number of reference centroids (25 to 400) and number of

dimensions (10 to 320 PCs) while keeping all other parameters constant. We ran all jobs on Linux

servers allotted 4 cores and 64 GB of memory (Intel Xeon E5-2690 v.3 processors) and used the

system.time R function to measure elapsed time.

Data availability

095   Datasets for all analyses were obtained from the links in **Table S1.** All datasets are publicly available

096   except the memory T cell CITE-seq data, which will be available at GEO accession GSE158769.

Code availability

098   We provide an efficient implementation of Symphony at https://github.com/immunogenomics/symphony

099   along with documentation, tutorials, and pre-built references. Scripts reproducing figures for all

100   examples will be made available at https://github.com/immunogenomics/symphony_reproducibility.

References

1.   Klein, A. M. & Treutlein, B. Single cell analyses of development in the modern era. *Development*

146, (2019).

2.   Han, X. *et al.* Construction of a human cell landscape at single-cell level. *Nature* (2020)

doi:10.1038/s41586-020-2157-4.

3.   Svensson, V., da Veiga Beltrame, E. & Pachter, L. A curated database reveals trends in single-cell

transcriptomics. *Database* **2020**, (2020).

4.   Cao, J. *et al.* The single-cell transcriptional landscape of mammalian organogenesis. *Nature* **566**,

496–502 (2019).

5.   Jerber, J. *et al.* Population-scale single-cell RNA-seq profiling across dopaminergic neuron

differentiation. *bioRxiv* 2020.05.21.103820 (2020) doi:10.1101/2020.05.21.103820.

6.   Zhang, F. *et al.* Defining inflammatory cell states in rheumatoid arthritis joint synovial tissues by

integrating single-cell transcriptomics and mass cytometry. *Nat. Immunol.* **20**, 928–942 (2019).

7.   Reyes, M. *et al.* An immune-cell signature of bacterial sepsis. *Nat. Med.* **26**, 333–340 (2020).

8.   Kotliarov, Y. *et al.* Broad immune activation underlies shared set point signatures for vaccine

responsiveness in healthy individuals and disease activity in patients with lupus. *Nat. Med.* **26**,

618–629 (2020).

9.   Schafflick, D. *et al.* Integrated single cell analysis of blood and cerebrospinal fluid leukocytes in

multiple sclerosis. *Nat. Commun.* **11**, 247 (2020).

10.   Smillie, C. S. *et al.* Intra- and Inter-cellular Rewiring of the Human Colon during Ulcerative Colitis.

Cell **178**, 714-730.e22 (2019).

11.   Litviňuková, M. *et al.* Cells of the adult human heart. *Nature* (2020) doi:10.1038/s41586-020-2797-

4.

12.   Rozenblatt-Rosen, O., Stubbington, M. J. T., Regev, A. & Teichmann, S. A. The Human Cell Atlas:

from vision to reality. *Nature* **550**, 451–453 (2017).

13.   Haghverdi, L., Lun, A. T. L., Morgan, M. D. & Marioni, J. C. Batch effects in single-cell RNA-

sequencing data are corrected by matching mutual nearest neighbors. *Nat. Biotechnol.* **36**, 421–

427 (2018).

14.   Hie, B., Bryson, B. & Berger, B. Efficient integration of heterogeneous single-cell transcriptomes

using Scanorama. *Nat. Biotechnol.* **37**, 685–691 (2019).

15.   Welch, J. D. *et al.* Single-Cell Multi-omic Integration Compares and Contrasts Features of Brain

Cell Identity. *Cell* **177**, 1873-1887.e17 (2019).

16.   Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep generative modeling for single-

cell transcriptomics. *Nat. Methods* **15**, 1053–1058 (2018).

17.   Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data with Harmony. *Nat.*

Methods **16**, 1289–1296 (2019).

18.   Stuart, T. *et al.* Comprehensive Integration of Single-Cell Data. *Cell* **177**, 1888-1902.e21 (2019).

19.   He, Z., Brazovskaja, A., Ebert, S., Camp, J. G. & Treutlein, B. CSS: cluster similarity spectrum

integration of single-cell genomics data. *Genome Biol.* **21**, 224 (2020).

20.   Tran, H. T. N. *et al.* A benchmark of batch-effect correction methods for single-cell RNA

sequencing data. *Genome Biol.* **21**, 12 (2020).

21. Zhang, Q. *et al.* Landscape and Dynamics of Single Immune Cells in Hepatocellular Carcinoma.

Cell **179**, 829-845.e20 (2019).

22. Wei, K. *et al.* Notch signalling drives synovial fibroblast identity and arthritis pathology. *Nature* **582**,

259–264 (2020).

23. Kirita, Y., Wu, H., Uchimura, K., Wilson, P. C. & Humphreys, B. D. Cell profiling of mouse acute

kidney injury reveals conserved cellular responses to injury. *Proc. Natl. Acad. Sci. U. S. A.* **117**,

15874–15883 (2020).

24. Sandu, I. *et al.* Landscape of Exhausted Virus-Specific CD8 T Cells in Chronic LCMV Infection.

Cell Rep. **32**, 108078 (2020).

25. Korsunsky, I. *et al.* Cross-tissue, single-cell stromal atlas identifies shared pathological fibroblast

phenotypes in four chronic inflammatory diseases. *bioRxiv* 2021.01.11.426253 (2021).

26. Zhang, F. *et al.* IFN- γ and TNF- α drive a CXCL10 + CCL2 + macrophage phenotype expanded in

severe COVID-19 and other diseases with tissue inflammation. *bioRxiv* (2020)

doi:10.1101/2020.08.05.238360.

27. Lähnemann, D. *et al.* Eleven grand challenges in single-cell data science. *Genome Biol.* **21**, 31

(2020).

28. Lotfollahi, M. *et al.* Query to reference single-cell integration with transfer learning. *bioRxiv* (2020).

29. Cao, Z.-J., Wei, L., Lu, S., Yang, D.-C. & Gao, G. Searching large-scale scRNA-seq databases via

unbiased cell embedding with Cell BLAST. *Nat. Commun.* **11**, 3458 (2020).

30. Hao, Y. *et al.* Integrated analysis of multimodal single-cell data. *bioRxiv* 2020.10.12.335331 (2020).

31. Kiselev, V. Y., Yiu, A. & Hemberg, M. scmap: projection of single-cell RNA-seq data across data

sets. *Nat. Methods* **15**, 359–362 (2018).

32. Xu, C. *et al.* Probabilistic harmonization and annotation of single-cell transcriptomics data with

deep generative models. *Mol. Syst. Biol.* **17**, e9620 (2021).

33. Lotfollahi, M., Naghipourfar, M., Theis, F. J. & Wolf, F. A. Conditional out-of-distribution generation

for unpaired data using transfer VAE. *Bioinformatics* **36**, i610–i617 (2020).

34. Polański, K. *et al.* BBKNN: fast batch alignment of single cell transcriptomes. *Bioinformatics* **36**,

964–965 (2020).

35. Abdelaal, T. *et al.* A comparison of automatic cell identification methods for single-cell RNA

sequencing data. *Genome Biol.* **20**, 194 (2019).

36. Zhang, Z. *et al.* SCINA: A Semi-Supervised Subtyping Algorithm of Single Cells and Bulk Samples.

Genes **10**, (2019).

37. Alquicira-Hernandez, J., Sathe, A., Ji, H. P., Nguyen, Q. & Powell, J. E. scPred: accurate

supervised method for cell-type classification from single-cell RNA-seq data. *Genome Biol.* **20**, 264

(2019).

38. Tan, Y. & Cahan, P. SingleCellNet: A Computational Tool to Classify Single Cell RNA-Seq Data

Across Platforms and Across Species. *Cell Syst* **9**, 207-213.e2 (2019).

39. Ding, J. *et al.* Systematic comparative analysis of single cell RNA-sequencing methods. *bioRxiv*

632216 (2019) doi:10.1101/632216.

40. Nathan, A. *et al.* Multimodal memory T cell profiling identifies a reduction in a polyfunctional Th17

state associated with tuberculosis progression. *bioRxiv* 2020.04.23.057828 (2020)

doi:10.1101/2020.04.23.057828.

41. Segerstolpe, Å. *et al.* Single-Cell Transcriptome Profiling of Human Pancreatic Islets in Health and

Type 2 Diabetes. *Cell Metab.* **24**, 593–607 (2016).

42. Lawlor, N. *et al.* Single-cell transcriptomes identify human islet cell signatures and reveal cell-type-

specific expression changes in type 2 diabetes. *Genome Res.* **27**, 208–222 (2017).

43. Grün, D. *et al.* De Novo Prediction of Stem Cell Identity using Single-Cell Transcriptome Data. *Cell*

Stem Cell **19**, 266–277 (2016).

44. Muraro, M. J. *et al.* A Single-Cell Transcriptome Atlas of the Human Pancreas. *Cell Syst* **3**, 385-

394.e3 (2016).

45. Baron, M. *et al.* A Single-Cell Transcriptomic Map of the Human and Mouse Pancreas Reveals

Inter- and Intra-cell Population Structure. *Cell Syst* **3**, 346-360.e4 (2016).

46. Popescu, D.-M. *et al.* Decoding human fetal liver haematopoiesis. *Nature* **574**, 365–371 (2019).

47. Stoeckius, M. *et al.* Simultaneous epitope and transcriptome measurement in single cells. *Nat.*

Methods **14**, 865–868 (2017).

48. Peterson, V. M. *et al.* Multiplexed quantification of proteins and transcripts in single cells. *Nat.*

Biotechnol. **35**, 936–939 (2017).

49. Luecken, M. D. & Theis, F. J. Current best practices in single-cell RNA-seq analysis: a tutorial. *Mol.*

Syst. Biol. **15**, e8746 (2019).

50. Berger, B. & Cho, H. Emerging technologies towards enhancing privacy in genomic data sharing.

Genome Biol. **20**, 128 (2019).

51. Wang, S., Pisco, A. O., Karkanias, J. & Altman, R. B. Unifying single-cell annotations based on the

Cell Ontology. *bioRxiv* 810234 (2019) doi:10.1101/810234.

52. Gayoso, A. *et al.* A Joint Model of RNA Expression and Surface Protein Abundance in Single Cells.

bioRxiv 791947 (2019) doi:10.1101/791947.

53. Baglama, J. & Reichel, L. Augmented Implicitly Restarted Lanczos Bidiagonalization Methods.

SIAM Journal on Scientific Computing vol. 27 19–42 (2005).

54. Korsunsky, I., Nathan, A., Millard, N. & Raychaudhuri, S. Presto scales Wilcoxon and auROC

analyses to millions of observations. *bioRxiv* 653253 (2019) doi:10.1101/653253.

55. Friedman, J., Hastie, T. & Tibshirani, R. Regularization Paths for Generalized Linear Models via

Coordinate Descent. *J. Stat. Softw.* **33**, 1–22 (2010).

56. Durinck, S., Spellman, P. T., Birney, E. & Huber, W. Mapping identifiers for the integration of

genomic datasets with the R/Bioconductor package biomaRt. *Nat. Protoc.* **4**, 1184–1191 (2009).

57. Gu, Z., Eils, R. & Schlesner, M. Complex heatmaps reveal patterns and correlations in

multidimensional genomic data. *Bioinformatics* **32**, 2847–2849 (2016).

58. Leurgans, S. E., Moyeed, R. A. & Silverman, B. W. Canonical Correlation Analysis When the Data

are Curves. *J. R. Stat. Soc. Series B Stat. Methodol.* **55**, 725–740 (1993).

59. McInnes, L., Healy, J. & Melville, J. UMAP: Uniform Manifold Approximation and Projection for

Dimension Reduction. *arXiv [stat.ML]* (2018).