Unveiling functions of the visual cortex using task-specific deep neural networks

Kshitij Dwivedi[1,3,*], Michael F. Bonner[2],

Radoslaw Martin Cichy[1,†], Gemma Roig[3,†,*]

[1]Department of Education and Psychology, Freie Universität Berlin, Germany
[2]Department of Cognitive Science, Johns Hopkins University, Baltimore, MD, United States
[3]Department of Computer Science, Goethe University, Frankfurt am Main, Germany

[†]jointly directed work

[*]To whom correspondence should be addressed;

E-mails: dwivedi@em.uni-frankfurt.de, roig@cs.uni-frankfurt.de

Abstract:

The human visual cortex enables visual perception through a cascade of hierarchical computations in cortical regions with distinct functionalities. Here, we introduce an AI-driven approach to discover the functional mapping of the visual cortex. We related human brain responses to scene images measured with functional MRI (fMRI) systematically to a diverse set of deep neural networks (DNNs) optimized to perform different scene perception tasks. We found a structured mapping between DNN tasks and brain regions along the ventral and dorsal visual streams. Low-level visual tasks mapped onto early brain regions, 3-dimensional scene perception tasks mapped onto the dorsal stream, and semantic tasks mapped onto the ventral stream. This mapping was of high fidelity, with more than 60% of the explainable variance in nine key regions being explained. Together, our results provide a novel functional mapping of the human visual cortex and demonstrate the power of the computational approach.

1. Introduction

The human visual system transforms incoming light into meaningful representations that underlie perception and guide behavior. This transformation is

believed to take place through a cascade of hierarchical processes implemented in a set

of brain regions along the so-called ventral and dorsal visual streams[1]. Each of these

regions has been stipulated to fulfill a distinct sub-function in enabling perception[2].

However, discovering the exact nature of these functions and providing computational

models that implement them has proven challenging. Recently, computational modeling

using deep neural networks (DNNs) has emerged as a promising approach to model, and

predict neural responses in visual regions[3–7]. These studies have provided a first

functional mapping of the visual brain. However, the resulting account of visual cortex

functions has remained incomplete. This is so because previous studies either explain

the function of a single or few candidate regions by investigating many DNNs or explain

many brain regions comparing it to a single DNN trained on one task only (usually object

categorization). In contrast, for a systematic and comprehensive picture of human brain

function that does justice to the richness of the functions that each of its subcomponents

implements, DNNs trained on multiple tasks, i.e., functions, must be related and

compared in their predictive power across the whole cortex.

Aiming for this systematic and comprehensive picture for the visual cortex we here

relate brain responses across the whole visual brain to a wide set of DNNs, in which each

DNN is optimized for a different visual task, and hence, performs a different function.

To reliably reveal the functions of brain regions using DNNs performing different

functions, we need to ensure that only function and no other crucial factor differs between

the DNNs. The parameters learned by a DNN depend on a few fundamental factors,

namely, its architecture, training dataset, learning mechanism, and the function the DNN

was optimized for. Therefore, in this study, we select a set of DNNs[8] that have an identical

encoder architecture and are trained using the same learning mechanism and the same

set of training images. Thus, the parameters learned by the encoder of the selected DNNs

differ only due to their different functions.

We generate a functional map of the visual cortex by comparing the fMRI

responses to scene images[9] with the activations of multiple DNNs optimized on different

tasks[8] related to scene perception, e.g., scene classification, depth estimation, and edge

detection. Our key result is that different regions in the brain are better explained by DNNs

performing different tasks, suggesting different computational roles in these regions. In

particular, we find that early regions of the visual cortex are better explained by DNNs performing low-level vision tasks, such as edge detection. Regions in the dorsal stream are better explained by DNNs performing tasks related to 3-dimensional (3D) scene perception, such as occlusion detection and surface normal prediction. Regions in the ventral stream are best explained by DNNs performing tasks related to semantics, such as scene classification. Importantly, the top-3 best predicting DNNs explain more than 60% of the explainable variance in nine ventral-temporal and dorsal-lateral visual regions, demonstrating the quantitative power and potential of our AI-driven approach for discovering fine-grained functional maps of the human brain.

2. Results

2.1 Functional map of visual cortex using multiple DNNs

Our primary goal is to generate a functional map of the visual brain in terms of the functions each of the regions implements. Our approach is to relate brain responses to activations of DNNs performing different functions. For this, we used an fMRI dataset recorded while human subjects (N=16) viewed indoor scenes[9] and performed a categorization task; and a set of 18 DNNs[8] optimized to perform 18 different functions related to visual perception (some of the tasks can be visualized here: https://sites.google.com/view/dnn2brainfunction/home#h.u0nqne179ys2) plus an additional DNN with random weights as a baseline. The different DNNs' functions were associated with indoor scene perception, covering a broad range of tasks from low-level visual tasks, (e.g., edge detection) to 3-dimensional visual perception tasks (e.g., surface normals prediction) to categorical tasks (e.g., scene classification). Each DNN consisted of an encoder-decoder architecture, where the encoder had an identical architecture across tasks, and the decoder varied depending on the task. To ensure that the differences in variance of fMRI responses explained by different DNNs from our set were not due to differences in architecture, we selected the activations from the last two layers of the identical encoder architecture for all DNNs.

87
Figure 1: Methods and results of functional mapping of the visual cortex by task-specific DNNs: **a)**
Schema of DNN-fMRI comparison. As a first step, we extracted DNN activations from the last two layers
(block 4 and output) of the encoders, denoted as $b4_1(x^i)$, $o_1(x^i)$ for DNN_1 and $b4_n(x^i)$, $o_n(x^i)$ for DNN_n in the
figure, from n DNNs and the fMRI response of a region $f(x^i)$ for the i^{th} image x^i in the stimulus set. We
repeated the above procedure for all the images in the stimulus set. **b)** We used the extracted activations
to compute the RDMs, two for the two DNN layers and one for the brain region. Each RDM contains the
pairwise dissimilarities of the DNN activations or brain region activations, respectively. We then used
multiple linear regression to obtain an R_1^2 score to quantify the similarity between DNN_1 and the brain
region. We repeated the same procedure using other DNNs to obtain corresponding R^2 **c)** We obtained a
ranking based on R^2 to identify the DNNs with the highest R^2 for fMRI responses in that brain region. To
visualize the results, we color-coded the brain region by the color indexing the DNN showing the highest
R^2 in that brain region. **d)** Functional map of the visual brain generated through a spatially unbiased
searchlight procedure, comparing 18 DNNs optimized for different tasks and a randomly initialized DNN as
a baseline. We show the results for the voxels with significant noise ceiling and R^2 with DNN ($p < 0.05$,
permutation test with 10,000 iterations, FDR-corrected). An interactive visualization of the functional brain
map is available in this weblink (https://sites.google.com/view/dnn2brainfunction/home#h.ub1chq1k42n6)
104

The layer selection was based on an analysis finding the most task-specific layers of the
encoder (see Supplementary Section 2). Furthermore, all DNNs were optimized using the
same set of training images, and the same backpropagation algorithm for learning.
Hence, any differences in our findings across DNNs cannot be attributed to the training
data statistics, architecture, or learning algorithm, but to the task for which each DNN was
optimized.

To compare fMRI responses with DNNs, we first extracted fMRI responses in a
spatially delimited portion of the brain for all images in the stimulus set (Figure 1a). This
could be either a group of spatially contiguous voxels for searchlight analysis[10–12] or
voxels confined to a particular brain region as defined by a brain atlas for a region-of-
interest (ROI) analysis. Equivalently, we extracted activations from the encoders of each
DNN for the same stimulus set.

We then used Representational Similarity Analysis (RSA)[13] to compare brain
activations with DNN activations. RSA defines a similarity space as an abstraction of the
incommensurable multivariate spaces of the brain and DNN activation patterns. This
similarity space is defined by pairwise distances between the activation patterns of the
same source space, either fMRI responses from a brain region or DNN activations, where
responses can be directly related. For this, we compared all combinations of stimulus-
specific activation patterns in each source space (i.e., DNN activations, fMRI activations).
Then, the results for each source space were noted in a two-dimensional matrix, called
representational dissimilarity matrices (RDMs). The rows and columns of RDMs represent
the conditions compared. To relate fMRI and DNNs in this RDM-based similarity space
we performed multiple linear regression predicting fMRI RDM from DNN RDMs of the last
two encoder layers. We obtained the adjusted coefficient of determination R^2 (referred to
as R^2 in the subsequent text) from the regression to quantify the similarity between the
fMRI responses and the DNN (Figure 1b). We performed this analysis for each of the 18
DNNs investigated, which we group into 2D, 3D, or semantic DNNs when those are
optimized for 2D, 3D, or semantic tasks, respectively, and an additional DNN with random
weights as a baseline. The tasks were categorized into three groups (2D, 3D, and
semantic) based on different levels of indoor scene perception and were verified in
previous works using transfer performance using one DNN as the initialization to other

target tasks[8] and representational similarity between DNNs[14]. We finally used the

obtained DNN rankings based on R^2 to identify the DNNs with the highest R^2 for fMRI

responses in that brain region (Figure 1c top). To visualize the results, we color-coded

the brain region by color indexing the DNN showing the highest R^2 in that brain region

(Figure 1c bottom).

To generate a functional map across the whole visual cortex we performed a

searchlight analysis[11,12]. In detail, we obtain the R^2-based DNN rankings on the local

activation patterns around a given voxel, as described above. We conducted the above

analysis for each voxel, resulting in a spatially unbiased functional map.

We observed that different regions of the visual cortex showed the highest

similarity with different DNNs. Importantly, the pattern with which different DNNs predicted

brain activity best was not random but spatially organized: 2D DNNs (in shades of blue in

Figure 1d; interactive map visualization available here:

https://sites.google.com/view/dnn2brainfunction/home#h.ub1chq1k42n6) show a higher

similarity with early visual regions, 3D DNNs (in shades of green) show a higher similarity

with dorsal regions, while semantic DNNs (in shades of magenta) show a higher similarity

with ventral regions and some dorsal regions.

Together, the results of our AI-driven mapping procedure suggest that early visual

regions perform functions related to low-level vision, dorsal regions perform functions

related to both 3D and semantic perception, and ventral regions perform functions related

to semantic perception.

2.2 Nature and predictive power of the functional map

Figure 2: Nature and predictive power of the functional map: **a)** Cortical overlay showing locations of selected cortical regions from the probabilistic atlas used. **b)** Absolute total variance (R^2) explained in 15 ROIs by using the top-3 DNNs together. The Venn diagram for each ROI illustrates the unique and shared variance of the ROI responses explained by the combination of the top-3 DNNs. The bar plot shows the unique variance of each ROI explained by each of the top-3 DNNs individually. The asterisk denotes the

significance of unique variance and the difference in unique variance (p<0.05, permutation test with 10,000

iterations, FDR-corrected across DNNs). The error bars show the standard deviation calculated by

bootstrapping 90% of the conditions (10,000 iterations). **c)** Variance of each ROI explained by top-3 best

predicting DNNs (cross validated across subjects and conditions) indicated in blue bars compared with

lower and upper bound of noise ceiling indicated by shaded gray region. The error bars show the 95%

confidence interval calculated across N=16 subjects. All the R^2 values are statistically significant (p<0.05,

two-sided t-test, FDR-corrected across ROIs).

Using the searchlight results from Figure 1d, we identified the DNN that showed the

highest R^2 for each searchlight. This poses two crucial questions that require further

investigation for an in-depth understanding of the functions of brain regions. Firstly, does

a single DNN prominently predict a region's response (one DNN-to-one region) or a group

of DNNs together predict its response (many DNNs-to-one region)? A one-to-one

mapping between DNN and a region would suggest a single functional role while a many-

to-one mapping would suggest multiple functional roles of the brain region under

investigation. Secondly, given that the DNNs considered in this study predict fMRI

responses, how well do they predict on a quantitative scale? A high prediction accuracy

would suggest that the functional mapping obtained using our analysis is accurate, while

a low prediction accuracy would suggest that DNNs considered in this study are not

suitable to find the function of that brain region. Although it is possible to answer the above

questions for each voxel, for conciseness we consider 25 regions of interest (ROIs) tiling

the visual cortex from a brain atlas[15].

To determine how accurately DNNs predict fMRI responses, we calculated the

lower and upper bound of the noise ceiling for each ROI. We included ROIs (15 out of 25)

with a lower noise ceiling above 0.1 and discarded other ROIs due to low signal-to-noise

ratio. We show the locations of the investigated ROIs in the visual cortex in Figure 2a.

For each ROI we used RSA to compare fMRI responses (transformed into fMRI

RDMs) with activations of all 18 DNNs plus a randomly initialized DNN as a baseline

(transformed into DNN RDMs). This yielded one R^2 value for each DNN per region (see

Supplementary SFigure 4). We then selected the top-3 DNNs showing the highest R^2 and

performed a variance partitioning analysis[16]. We used the top-3 DNN RDMs as the

independent variables and the ROI RDM as the dependent variable to find out how much

variance of ROI responses is explained uniquely by each of these DNNs while considered
together with the other two DNNs. Using the variance partitioning analysis (method
illustrated in Supplementary SFigure 1) we were able to infer the amount of unique and
shared variance between different predictors (DNN RDMs) by comparing the explained
variance (R^2) of a DNN used alone with the explained variance when it was used with
other DNNs. Variance partitioning analysis (Figure 2b) using the top-3 DNNs revealed the
individual DNNs that explained the most variance uniquely for a given ROI along with the
unique and shared variance explained by other DNNs. The DNN that detects edges
explained significantly higher variance ($p < 0.05$, permutation test, FDR corrected across
DNNs) in ROIs in early and mid-level visual regions (V1v, V1d, V2v, V2d, V3v, and hV4)
uniquely than the other two DNNs, suggesting a function related to edge detection.
Semantic segmentation DNN explained significantly higher unique variance in ventral
ROIs VO1 and VO2, suggesting a function related to the perceptual grouping of objects.
3D DNNs (3D Keypoints, 2.5D Segmentation, 3D edges, curvature) were best predicting
DNNs for dorsal ROIs V3d and V3b suggesting their role in 3D scene understanding. A
combination of 3D and semantic DNNs were best predicting DNNs for other ROIs (PHC1,
PHC2, LO1, LO2, and V3a). It is crucial to note that if two DNNs from the same task group
are in the top-3 best predicting DNNs for an ROI, the unique variance of ROI RDM
explained by DNNs in the same group will generally be lower than by DNN not in the
group. We have observed that DNNs in the same task group show a higher correlation
with each other as compared to DNNs in other task groups[14]. A higher correlation
between the DNNs of the same task group leads to an increase in shared variance and
reduces the unique variance of the ROI RDM explained by within task group DNNs. For
instance, we can observe this in PHC2 (also in PHC1, V3a), where two semantic DNNs
explain less unique variance than a 3D DNN. Therefore, in such cases, we restrain from
interpreting that one type of DNN is significantly better than others.
Overall, we observed a many-to-one relationship between function and region for
multiple regions, i.e., multiple DNNs explained jointly a particular brain region. In early
and mid-level regions (V1v, V1d, V2v, V3v) the most predictive functions were related to
low-level vision (2D edges, denoising, and 2D segmentation). In dorsal regions V3d and
V3b, the most predictive functions were related to 3D scene understanding. In later

ventral and dorsal regions (V2d, hV4, VO1, VO2, PHC1, PHC2, LO1, LO2, and V3a) we
observed a mixed mapping of 2D, 3D, and semantic functions suggesting multiple
functional roles of these ROIs. The predictability of a region's responses by multiple DNNs
demonstrates that a visual region in the brain has representations well suited for distinct
functions. A plausible conjecture of the above findings is that these regions might be
performing a function related to the best predicting DNNs but is not present in the set of
DNNs investigated in this study.

To determine the accuracy of the functional mapping of the above ROIs, we
calculated the percentage of the explainable variance explained by the top-3 best
predicting DNNs. We calculated the explained variance by best predicting DNNs using
cross-validation across subjects (N-fold) and conditions (two-fold). As we use multiple
models together for multiple linear regression, we need to cross-validate using different
sets of RDMs for fitting and evaluating the fit of the regression. Here, we perform cross-
validation across subjects by fitting the regression on one-subject-left-out subject-
averaged RDMs on half of the images in the stimulus set and evaluating on the left-out
single subject RDM on the other half of the images. The above method is a stricter
evaluation criterion as compared to the commonly used one without cross-validation (See
Supplementary SFigure 5). We compared the variance explained by the top-3 DNNs with
the lower estimate of the noise ceiling which is an estimate of the explainable variance.
We found that variance explained in nine ROIs (V1v, V1d, V2v, V3v, VO1, PHC1, LO2,
LO1, V3a) is higher than 60% of the lower bound of noise ceiling (Figure 2c, absolute R^2
= 0.085 ± 0.046). In absolute terms, the minimum, median, and maximum cross-validated
R^2 values across the 15 ROIs were 0.014 (PHC2), 0.044 (VO1), and 0.27 (V1v) which
are comparable to related studies[60] performing evaluation in a similar manner. This shows
that the DNNs selected in this study predict fMRI responses well and therefore are
suitable for mapping the functions of the investigated ROIs.

In sum, we demonstrated that in many regions of the visual cortex, DNNs trained
on different functions predicted activity. This suggests that these ROIs have multiple
functional roles. We further showed quantitatively that more than 60% of the explainable
variance in nine visual ROIs is explained by the set of DNNs we used, demonstrating that
the selected DNNs are well suited to investigate the functional roles of these ROIs.

2.3 Functional map of visual cortex through 2D, 3D, and semantic tasks

In the previous section, we observed a pattern qualitatively suggesting different functional roles of early (2D), dorsal (3D and semantic), and ventral (semantic) regions in the visual cortex. To quantitatively assess this, we investigated the relation of brain responses and DNNs not at the level of single tasks, but task groups (2D, 3D, and semantic), where DNNs belonging to a task group showed a higher correlation with other DNNs in the group than with DNNs in other task groups (see Supplementary Section 2).

Figure 3: Functional mapping of the visual cortex with respect to 2D, 3D, and semantic tasks: **a)** Functional map of the visual cortex showing the regions where unique variance explained by one DNN group (2D, 3D, or semantic) is significantly higher than the variance explained by the other two DNN groups (p<0.05, permutation test with 10,000 iterations, FDR-corrected). We show the results for the voxels with a significant noise ceiling (p<0.05, permutation test with 10,000 iterations, FDR-corrected across DNNs and searchlights). The functional brain map can be visualized in this weblink (https://sites.google.com/view/dnn2brainfunction/home#h.xi402x2hr0p3). **b)** Absolute variance (R^2) explained in 15 ROIs by using 3 DNN RDMs averaged across task groups (2D, 3D, or semantic). The Venn diagram for each ROI illustrates the unique and shared variance of the ROI responses explained by the combination of 3 task groups. The bar plot shows the unique variance of each ROI explained by each task group individually. The asterisk denotes whether the unique variance or the difference in unique variance was significant (p<0.05, permutation test with 10,000 iterations, FDR-corrected across DNNs). The error bars show the standard deviation calculated by bootstrapping 90% of the conditions (10,000 iterations).

We averaged the RDMs of DNNs in each task group to obtain aggregate 2D, 3D, and semantic RDMs. Averaging the RDMs based on task groups reduced the number of DNN comparisons from 18 to 3. This allowed us to perform variance partitioning analysis to compare fMRI and DNN RDMs, which would be impractical with 18 single DNNs due to a large number of comparisons and computational complexity. When used in this way, variance partitioning analysis reveals whether and where in the brain one task group explained brain responses significantly better than other task groups.

We first performed a searchlight analysis to identify where in the cortex one task group explains significantly higher variance uniquely than the other task groups. We selected the grouped DNN RDM that explains the highest variance in a given region uniquely to create a functional map of the task groups in the visual cortex (Figure 3a). Here, due to the reduced number of comparisons, we can clearly observe distinctions where one grouped DNN explains fMRI responses better than the other grouped DNNs (p<0.05, permutation test with 10,000 iterations, FDR corrected across DNNs and searchlights). The resulting functional map (Figure 3a; interactive visualization available in this link: https://sites.google.com/view/dnn2brainfunction/home#h.xi402x2hr0p3) is different from the functional map in Figure 1d in two ways. First, in the functional map here we highlight the searchlight where one DNN group explained significantly higher variance uniquely than the other 2 DNN groups. In the functional map of Figure 1d, we

highlighted the DNN that explained the highest variance of a searchlight without

performing any statistical analysis whether the selected DNN was significantly better than

the second best DNN or not due to the higher number of comparisons. Second, here we

compared functions using groups of DNNs (3 functions: 2D, 3D and semantic), whereas

in the previous analysis we compared functions using single DNNs (18 functions). The

comparison using groups of DNNs allows us to put our findings in context with previous

neuroimaging findings that are typically reported at this level.

We observed that the 2D DNN RDM explained responses in the early visual

cortex, semantic DNN RDM explained responses in the ventral visual stream, and some

parts in the right hemisphere of the dorsal visual stream, and 3D DNN RDM explained

responses in the left hemisphere of the dorsal visual stream. The above findings

quantitatively reinforce our qualitative findings from the previous section that early visual

regions perform functions related to low-level vision, dorsal regions perform functions

related to both 3D and semantic perception, and ventral regions perform functions related

to semantic perception.

While the map of the brain reveals the most likely function of a given region, to find

out whether a region can have multiple functional roles we need to visualize the variance

explained by other grouped DNN RDMs along with the best predicting DNN RDM. To

achieve that, we performed a variance partitioning analysis using 3 grouped DNN RDMs

as the independent variable and 15 ROIs in the ventral-temporal and the dorsal-ventral

stream as the dependent variable. The results in Figure 3b show the unique and shared

variance explained by group-level DNN RDMs (2D, 3D, and semantic) for all the 15 ROIs.

From Figure 3b we observed that the responses in early ROIs (V1v, V1d, V2v,

V3v, hV4) are explained significantly higher ($p < 0.05$, permutation test with 10,000

iterations, FDR corrected across DNNs) by 2D DNN RDM uniquely, while responses in

later ventral-temporal ROIs (VO1, VO2, PHC1, and PHC2) are explained by semantic

DNN RDM uniquely. In dorsal-lateral ROIs (V3a, V3d) responses are explained by 3D

RDM uniquely. In LO1, LO2, and V3b 3D and semantic DNN RDMs explained significant

variance uniquely while in V2d all 2D, 3D, and semantic DNN RDMs explained significant

unique variance. It is crucial to note that for the ROI analysis here we use grouped DNN

RDMs as compared to Figure 2b where we selected top-3 single DNNs that showed the

highest R^2 with a given ROI. The comparison with grouped DNN RDMs provides a holistic

view of the functional role of ROIs which might be missed if one of the DNNs that is related

to the functional role of a ROI is not in the top-3 DNNs (as analyzed in Figure 2b). For

instance, in Figure 3b the results suggest both 3D and semantic functional roles of V3b

which is not evident from Figure 2b where the top 3-DNNs were all optimized on 3D tasks.

Together, we found that the functional role of the early visual cortex is related to

low-level visual tasks (2D), the dorsal stream is related to tasks involved in 3-dimensional

perception and categorical understanding of the scene (3D and semantic), and in the

ventral stream is related to the categorical understanding of the scene (semantic).

2.4 Functional roles of scene-selective regions

In the previous sections, we focused on discovering functions of regions

anatomically defined by an atlas. Since the stimulus set used to record fMRI responses

consisted of indoor scenes, in this section we investigate functional differences in

functionally localized scene-selective regions. We here focus on two major scene-

selective ROIs: occipital place area (OPA) and parahippocampal place area (PPA),

putting results into context with the early visual cortex (EVC) as an informative contrast

region involved in basic visual processing. The analysis followed the general rationale as

used before.

We first investigated the functional differences in these regions by performing

variance partitioning analysis using top-3 DNNs (see R^2 based ranking of all DNNs in

Supplementary SFigure 3) that best explained a given ROIs' responses (Figure 4a). We

found that the DNN that detects edges explained significantly higher variance (p<0.05,

permutation test, FDR-corrected) in EVC uniquely than the other two DNNs, suggesting

a function related to edge detection. 3D DNNs (3D Keypoints, 2.5D Segmentation, 3D

edges) were best predicting DNNs for OPA suggesting its role in 3D scene understanding.

A combination of semantic (semantic segmentation, scene classification) and 3D (3D

keypoints) DNNs were best predicting DNNs for PPA suggesting its role in both semantic

and 3D scene understanding.

We then investigated the functional differences by performing variance partitioning

analysis using aggregated 2D, 3D, and semantic DNN RDMs obtained by averaging the

individual DNN RDMs in each task group (Figure 4b). We found that for EVC and OPA
results are highly consistent with top-3 DNN analysis showing a prominent unique
variance explained by the 2D DNN RDM in EVC and the 3D DNN RDM in OPA.
Interestingly, in PPA we find that the semantic DNN RDM shows the highest unique
variance with no significant unique variance explained by the 3D DNN RDM. The
insignificant unique variance explained by the 3D DNN RDM is potentially due to
averaging the DNN RDMs of all 3D DNNs (high ranked as well as low ranked) which may
lead to diminishing the contribution of an individual high ranked 3D DNN RDM (e.g. 3D
keypoints that was in top-3 DNNs for PPA). Overall, we find converging evidence that
OPA is mainly related to tasks involved in 3-dimensional perception (3D), and PPA is
mainly related to semantic (categorical) understanding of the scene.

Figure 4: Functional roles of localized ROIs: **a)** Absolute total variance (R^2) explained in functionally
localized ROIs by using the top-3 DNNs together. The Venn diagram for each ROI illustrates the unique
and shared variance of the ROI responses explained by the combination of the top-3 DNNs. The bar plot
shows the unique variance of each ROI explained by each of the top-3 DNNs individually. The asterisk
denotes the significance of unique variance and the difference in unique variance (p<0.05, permutation test
with 10,000 iterations, FDR-corrected across DNNs). The error bars show the standard deviation calculated
by bootstrapping 90% of the conditions (10,000 iterations). **b)** Absolute total variance (R^2) explained in

functionally localized ROIs by using 3 DNN RDMs averaged across task groups (2D, 3D, or semantic). The
Venn diagram for each ROI illustrates the unique and shared variance of the ROI responses explained by
the combination of 3 DNN task groups. The bar plot shows the unique variance of each ROI explained by
each task group individually. The asterisk denotes whether the unique variance or the difference in unique
variance was significant (p<0.05, permutation test with 10,000 iterations, FDR-corrected across DNNs).
The error bars show the standard deviation calculated by bootstrapping 90% of the conditions (10,000
iterations).

3. Discussion

In this study, we harvested the potential of discovering functions of the brain from comparison to DNNs by investigating a large set of DNNs optimized to perform a set of diverse visual tasks. We found a systematic mapping between cortical regions and function: different cortical regions were explained by DNNs performing different functions. Importantly, the selected DNNs explained 60% of the explainable variance in nine out of 15 visual ROIs investigated, demonstrating the accuracy of the AI-driven functional mapping obtained using our analysis.

Our study provides a systematic and comprehensive picture of human brain functions using DNNs trained on different tasks. Previous studies[3,4,6,7,17–21,51,52] have compared model performance in explaining brain activity, but were limited to a few preselected regions and models, or had a different goal (comparing task structure)[22]. Using the same fMRI dataset as used in this study, a previous study[17] showed that representation in scene-selective ROIs consists of both location and category information using scene-parsing DNNs. We go beyond these efforts by comparing fMRI responses across the whole visual brain using a larger set of DNNs, providing a comprehensive account of the function of human visual brain regions.

We obtained the functional mapping of different regions in the visual cortex on both individual (e.g., 2D edges, scene classification, surface normals, etc.) and group (2D, 3D, semantic) levels of visual functions. We discuss the novel insights gained at the level of individual functions that inform about the fine-grained functional role of cortical regions.

First, we consider 2D DNNs, where the denoising DNN explained significant unique variance in V1v, V1d, V2v, V2d, V3v, and hV4. The denoising task requires the DNN to reconstruct an unperturbed input image from slightly perturbed (e.g., adding

Gaussian noise in the current case) input image that encourages learning representations robust to slight perturbations and limited invariance. This suggests that these ROIs might be generating a scene representation robust to high frequency noise.

When considering 3D DNNs, the 3D Keypoint and the 2.5d segment were among the top-3 best predicting DNNs in multiple ROIs. The 3D Keypoints DNN explained significant unique variance in V3d, PHC1, PHC2, LO2, LO1, V3a, V3b, OPA, and PPA. The 3D Keypoints task requires the DNN to identify locally important regions of the input image based on object boundary information and surface stability. This suggests that the ROIs in which 3D Keypoints DNN explained significant variance may be identifying locally important regions in a scene. The identification of locally important regions might be relevant to selectively attend to these key regions to achieve a behavioral goal e.g., searching for an object. The 2.5d segment DNN explained significant unique variance in V3d, LO2, LO1, V3b, V3a, and OPA. The 2.5d segment task requires the DNN to segment images into perceptually similar groups based on color and scene geometry (depth and surface normals). This suggests that the ROIs in which 2.5d segment DNN explained significant variance may be grouping regions in the images based on color and geometry cues even without any knowledge of the categorical information. Grouping regions based on geometry could be relevant to behavioral goals such as reaching for objects or identifying obstacles.

Among semantic DNNs, the semantic segmentation DNN explained significant unique variance in VO1, VO2, PHC1, PHC2, V3a, and PPA. The semantic segmentation task requires the DNN to segment objects present in the image based on categories. This suggests that the ROIs in which semantic segmentation DNN explained significant variance may be grouping regions in the image based on categorical information.

Other DNNs (2D edges, scene classification, and object classification) that showed significant unique variance in ROIs provided functional insights mostly consistent with the previous studies[23–25,31,32]. Overall, the key DNNs (denoising, 3D keypoints, 2.5D segment, and semantic segmentation) that explained significant variance in multiple ROI responses uniquely promote further investigation by generating novel hypotheses about the functions of these ROIs. Future experiments can test these hypotheses in detail in dedicated experiments.

The functional mapping obtained using grouped DNNs is complementary to that at
the individual level and helps us put functional mapping obtained here in context with
previous literature. We found that early visual regions (V1v, V1d, V2v) have a functional
role related to low-level 2D visual tasks which is consistent with previous literature
investigating these regions[23–25]. In dorsal-ventral ROIs (V3a, V3d, LO1, and LO2) we
found functional roles related to 3D and semantic tasks converging with evidence from
previous studies[26–30]. Similarly, the prominent semantic functional role of later ventral-
temporal ROIs (VO1, VO2, PHC1, and PHC2) found in this study converges with findings
in previous literature[31,32]. In scene-selective ROIs, we found a semantic functional role for
PPA and 3D functional role for OPA respectively. Our study extends the findings of a
previous study[51] relating OPA and PPA to 3D models by differentiating between OPA and
PPA functions through a much broader set of models. To summarize, the functional
mapping using individual DNNs optimized to perform different functions revealed new
functional insights for higher ROIs in the visual cortex while at the same time functional
mapping using grouped DNNs showed highly converging evidence with previous
independent studies investigating these ROIs.

Beyond clarifying the functional roles of multiple ROIs, our approach also identifies
quantitatively highly accurate prediction models of these ROIs. We found that the DNNs
explained 60% of the explainable variance in nine out of 15 ROIs. Our findings, thus,
make advances towards finding models that generate new hypotheses about potential
functions of brain regions as well as predicting brain responses well.[20,33–35].

A major challenge in meaningfully comparing two or more DNNs is to vary only a
single factor of interest while controlling the factors that may lead to updates of DNN
parameters. In this study, we address this challenge by selecting a set of DNNs trained
on the same set of training images using the same learning algorithm, with the same
encoder architecture, while being optimized for different tasks. Our results, thus,
complement previous studies that focused on other factors influencing the learning of
DNN parameters such as architecture[19,35–37], and the learning mechanism[38–40]. Our
approach accelerates the divide-and-conquer strategy of investigating human brain
function by systematically and carefully manipulating the DNNs used to map the brain in
their fundamental parameters one by one[20,41–43]. Our high-throughput exploration of

potential computational functions was initially inspired by Marr's computational level of

analysis[44] which aims at finding out what the goal of the computation carried out by a

brain region is. While Marr's approach invites the expectation of a one-to-one mapping

between regions and goals, we found evidence for multiple functional roles (3D +

semantic) using DNNs in some ROIs (e.g. LO1, LO2, PHC1, PHC2). This indicates a

many-to-one mapping[59] between functions and brain regions. We believe such a

systematic approach that finds the functional roles of multiple brain regions provides a

starting point for a further in-depth empirical inquiry into functions of the investigated brain

regions.

Our study is related to a group of studies[53-55,61] applying DNNs in different ways to

achieve a similar goal of mapping functions of brain regions using DNNs. Some studies[53-

54,61] applied optimization algorithms (genetic algorithm or activation maximization) to find

images that maximally activate a given neuron's or group of neurons' response. Another

related study[55] proposes Neural Information Flow (NIF) to investigate functions of brain

regions where they train a DNN with the objective function to predict brain activity while

preserving a one-to-one correspondence between DNN layers and biological neural

populations. While sharing the overall goal to discover functions of brain regions,

investigating DNN functions allows investigation in terms of which computational goal a

given brain region is best aligned with. With new computer vision datasets[62] investigating

a diverse set of tasks relevant to human behavioral goals[63,64] our approach opens new

avenues to investigate brain functions.

A limitation of our study is that our findings are restricted to functions related to

scene perception. Thus, the functions we discovered for non-scene regions correspond

to their functions when humans are perceiving scenes. In contrast, our study does not

characterize the functions of these regions when humans perceive non-scene categories

such as objects, faces, or bodies. We limited our study to scene perception because there

are only a few image datasets[8,45] that have annotations corresponding to a diverse set of

tasks, thus, allowing DNNs to be optimized independently on these tasks. The

Taskonomy dataset[8] with annotations of over 20 diverse scene perception tasks and

pretrained DNNs available on these tasks along with the availability of an fMRI dataset

related to scene perception[9], therefore, provided a unique opportunity. However, the

approach we presented in this study is not limited to scene perception. It can in principle
be extended to more complex settings such as video understanding, active visual
perception, and even outside the vision modality, given an adequate set of DNNs and
brain data. While in this study we considered DNNs that were trained independently,
future studies might consider investigating multitask models[56,57] which are trained to
perform a wide range of functions using a single DNN. Multitask modeling has the
potential to model the entire visual cortex using a single model as compared to several
independent models used in this study. Another potential limitation is that our findings are
based on a single fMRI and image dataset, so it is not clear how well they would
generalize to a broader sample of images. Given the explosive growth of the deep
learning field[43,46] and the ever increasing availability of open brain imaging data sets[47,58]
we see a furtive ground for the application of our approach in the future.

Beyond providing theoretical insight with high predictive power, our approach can
also guide future research. In particular, the observed mapping between cortical region
and function can serve as a quantitative baseline and starting point for an in-depth
investigation focused on single cortical regions. Finally, the functional hierarchy of the
visual cortex from our results can inspire the design of efficient multi-task artificial visual
systems that perform multiple functions similar to the human visual cortex.

4. Materials and Methods

4.1 fMRI Data

We used fMRI data from a previously published study[9]. The fMRI data were
collected from 16 healthy subjects (8 females, mean age 29.4 years, SD = 4.8). The
subjects were scanned on a Siemens 3.0T Prisma scanner using a 64-channel head coil.
Structural T1-weighted images were acquired using an MPRAGE protocol (TR = 2,200
ms, TE = 4.67 ms, flip angle = 8°, matrix size = 192 × 256 × 160, voxel size = 0.9 × 0.9 ×
1 mm). Functional T2*-weighted images were acquired using a multi-band acquisition
sequence (TR = 2,000 ms for main experimental scans and 3,000 ms for localizer scans,
TE = 25 ms, flip angle = 70°, multiband factor = 3, matrix size = 96 × 96 × 81, voxel size
= 2 × 2 × 2 mm).

During the fMRI scan, subjects performed a category detection task while viewing
images of indoor scenes. On each trial, an image was presented on the screen at a visual
angle of ~17.1° x 12.9° for 1.5 s followed by a 2.5s interstimulus interval. Subjects had to
respond by pressing a button indicating whether the presented image was a bathroom or
not while maintaining fixation on a cross. The stimulus set consisted of 50 images of
indoor scenes (no bathrooms), and 12 control images (five bathroom images, and seven
non-bathroom images). fMRI data were preprocessed using SPM12. For each participant,
the functional images were realigned to the first image followed by co-registration to the
structural image. Voxelwise responses to 50 experimental conditions (50 indoor images
excluding control images) were estimated using a general linear model.

542 4.2 Deep neural networks

For this study, we selected 18 DNNs trained on the Taskonomy[8] dataset optimized
on 18 different tasks covering different aspects of indoor scene understanding. The
Taskonomy dataset is a large-scale indoor image dataset consisting of annotations for 18
single image tasks, thus, allowing optimization of DNNs on 18 different tasks using the
same set of training images. We briefly describe the objective functions and DNN
architectures below. For a detailed description, we refer the reader to Zamir et al.[8].

549 **4.2.1 Tasks and objective functions of the DNNs**

The Taskonomy dataset consists of annotations for tasks that require pixel-level
information such as edge detection, surface normal estimation, semantic segmentation,
etc. as well as high-level semantic information such as object/scene classification
probabilities. The tasks can be broadly categorized into 4 groups: relating to low-level
visual information (2D), the three-dimensional layout of the scene (3D), high-level object
and scene categorical information (semantic), and low-dimensional geometry
information(geometrical). The above task categorization was obtained by analyzing the
relationship between the transfer learning performance on a given task using the models
pretrained on other tasks as the source tasks. The 2D tasks were edge detection, keypoint
detection, 2D segmentation, inpainting, denoising, and colorization; 3D tasks were
surface normals, 2.5D segmentation, occlusion edges, depth estimation, curvature

estimation, and reshading; semantic tasks were object/scene classification and semantic

segmentation, and low-dimensional geometric tasks were room layout estimation and

vanishing point. A detailed description of all the tasks and annotations is provided in

http://taskonomy.stanford.edu/taskonomy_supp_CVPR2018.pdf. In this study, we did not

consider low dimensional geometric tasks as they did not fall into converging clusters

according to RSA and transfer learning as in the case of 2D, 3D, and semantics tasks.

To perform a given task, DNN's parameters were optimized using an objective function

that minimizes the loss between the DNN prediction and corresponding ground truth

annotations for that task. All the DNNs' parameters were optimized using the

corresponding objective function, on the same set of training images. Due to the use of

the same set of training images the learned DNN parameters vary only due to the

objective function and not the difference in training dataset statistics. A complete list of

objective functions used to optimize for each task is provided in this link

(https://github.com/StanfordVL/taskonomy/tree/master/taskbank). We downloaded the

pretrained models using this link

(https://github.com/StanfordVL/taskonomy/tree/master/taskbank), where further details

can be found.

4.2.2 Network architectures

The DNN architecture for each task consists of an encoder and a decoder. The

encoder architecture is consistent across all the tasks. The encoder architecture is a

modified ResNet-50[48] without average pooling and convolutions with stride 2 replaced by

convolutions with stride 1. ResNet-50 is a 50-layer DNN with shortcut connections

between layers at different depths. Consistency of encoder architecture allows us to use

the outputs of the ResNet-50 encoder as the task-specific representation for a particular

objective function. For all the analysis in this study, we selected the last two layers of the

encoder as the task-specific representation of the DNN. Our selection criteria was based

on an analysis (Supplementary Section 2) that shows task-specific representation is

present in those layers as compared to earlier layers. In this way, we ensure that the

difference in representations is due to the functions these DNNs were optimized for and

not due to the difference in architecture or training dataset. The decoder architecture is

task-dependent. For tasks that require pixel-level prediction, the decoder is a 15-layer
fully convolutional model consisting of 5 convolutional layers followed by alternating
convolution and transposed convolutional layers. For tasks, which require low
dimensional output, the decoder consists of 2-3 fully connected layers.

4.3 Representational Similarity Analysis (RSA)

To compare the fMRI responses with DNN activations we first need to map both
the modalities in a common representational space and then by comparing the resulting
mappings we can quantify the similarity between fMRI and DNNs. We mapped the fMRI
responses and DNN activations to corresponding representational dissimilarity matrices
(RDMs) by computing pairwise distances between each pair of conditions. We used the
variance of upper triangular fMRI RDM (R^2) explained by DNN RDMs as the measure to
quantify the similarity between fMRI responses and DNN activations. To calculate R^2, we
assigned DNN RDMs (RDMs of the last two layers of the encoder) as the independent
variables and assigned fMRI RDM as the dependent variable. Then a multiple linear
regression was fitted to predict fMRI RDM from the weighted linear combination of DNN
RDMs. We evaluated the fit by estimating the variance explained (R^2). We describe how
we mapped from fMRI responses and DNN activations to corresponding RDMs in detail
below.
609

Taskonomy DNN RDMs: We selected the last two layers of the Resnet-50 encoder as
the task-specific representation of DNNs optimized on each task. For a given DNN layer,
we computed the Pearson's distance between the activations for each pair of conditions
resulting in a condition x condition RDM for each layer. This resulted in a single RDM
corresponding to each DNN layer. We followed the same procedure to create RDMs
corresponding to other layers of the network. We averaged the DNN RDMs across task
clusters (2D, 3D, and semantic) to create 2D, 3D, and semantic RDMs.
617

Probabilistic ROI RDMs: We downloaded probabilistic ROIs[15] from the link
(http://scholar.princeton.edu/sites/default/files/napl/files/probatlas_v4.zip). We extracted
activations of the probabilistic ROIs by applying the ROI masks on the whole brain

response pattern for each condition, resulting in ROI-specific responses for each

condition for each subject. Then for each ROI, we computed the Pearson's distance

between the voxel response patterns for each pair of conditions resulting in a RDM (with

rows and columns equal to the number of conditions) independently for each subject. To

compare the variance of ROI RDM explained by DNN RDMs with the explainable variance

we used independent subject RDMs. For all the other analyses, we averaged the RDMs

across the subjects resulting in a single RDM for each ROI due to a higher signal to noise

ratio in subject averaged RDMs.

Searchlight RDMs: We used Brainiak toolbox code[49] to extract the searchlight blocks for

each condition in each subject. The searchlight block was a cube with radius = 1 and

edge size = 2. For each searchlight block, we computed the Pearson's distance between

the voxel response patterns for each pair of conditions resulting in a RDM of size condition

times independently for each subject. We then averaged the RDMs across the subjects

resulting in a single RDM for each searchlight block.

4.4 Variance partitioning

Using RSA to compare multiple DNNs we do not obtain a complete picture of how

each model is contributing to explaining the fMRI responses when considered in

conjunction with other DNNs. Therefore, we determined the unique and shared

contribution of individual DNN RDMs in explaining the fMRI ROI RDMs when considered

with the other DNN RDMs using variance partitioning.

We performed two variance partitioning analyses on probabilistic ROIs: first using

the top-3 DNNs that best explained a given ROI's responses and second using RDMs

averaged according to task type (2D, 3D, and semantic). For the first analysis, we

assigned a fMRI ROI RDM as the dependent variable (referred to as predictand) and

assigned RDMs corresponding to the top-3 DNNs as the independent variables (referred

to as predictors). For the second analysis, we assigned an fMRI ROI (searchlight) RDM

as the dependent variable (referred to as predictand). We then assigned three DNN

RDMs (2D, 3D, and semantic) as the independent variables (referred to as predictors).

For both variance partitioning analyses, we performed seven multiple regression

analyses: one with all three independent variables as predictors, three with different pairs

of two independent variables as the predictors, and three with individual independent

variables as the predictors. Then, by comparing the explained variance (R^2) of a model

used alone with the explained variance when it was used with other models, we can infer

the amount of unique and shared variance between different predictors (Supplementary

SFigure 1).

4.5 Searchlight analysis

We perform two different searchlight analyses in this study: first to find out if

different regions in the brain are better explained by DNNs optimized for different tasks

and second to find the pattern by taking the averaged representation DNNs from three

task types (2D, 3D, and semantic). In the first searchlight analysis, we applied RSA to

compute the variance of each searchlight block RDM explained by 19 DNN RDMs (18

Taskonomy DNNs and one randomly initialized as a baseline) independently. We then

selected the DNN that explained the highest variance as the preference for the given

searchlight block. In the second searchlight analysis, we applied variance partitioning with

2D, 3D, and semantic DNN RDMs as the independent variables, and each searchlight

block RDM as the dependent variable. For each searchlight block, we selected the task

type whose RDMs explained the highest variance uniquely as the function for that block.

We used the nilearn (https://nilearn.github.io/index.html) library to plot and visualize the

searchlight results.

4.6 Comparison of Explained with Explainable Variance

To relate the variance of fMRI responses explained by a DNN to the total variance

to be explained given the noisy nature of the fMRI data, we first calculated the lower and

upper bounds of the noise ceiling as a measure of explainable variance and then

compared cross-validated explained variance of each ROI by top-3 best predicting DNNs.

In detail, the lower noise ceiling was estimated by fitting each individual subject RDMs as

predictand with mean subject RDM of other subjects (N-1) as the predictor and calculating

the R^2. The resulting subject-specific R^2 values were averaged across the N subjects.

The upper noise ceiling was estimated in a similar fashion while using mean subject
RDMs of all the subjects (N) as the predictor. To calculate variance explained by the best
predicting DNNs we fit the regression using cross validation in 2N folds (2 folds across
conditions, N folds across subjects) where the regression was fit using the subject
averaged RDMs of N-1 subjects and the fit was evaluated using R^2 on the left out subject
and left out conditions. Finally, we then calculated the mean R^2 across 2N folds and
divided it by the lower bound of the noise ceiling to obtain the ratio of the explainable
variance explained by the DNNs.

4.7 Statistical Testing

We applied nonparametric statistical tests to assess the statistical significance in
a similar manner to a previous related study[50]. We assessed the significance of the R^2
through a permutation test by permuting the conditions randomly 10,000 times in either
the neural ROI/searchlight RDM or the DNN RDM. From the distribution obtained using
these permutations, we calculated p-values as one-sided percentiles. We calculated the
standard errors of these correlations by randomly resampling the conditions in the RDMs
for 10,000 iterations. We used re-sampling without replacement by subsampling 90% (45
out of 50 conditions) of the conditions in the RDMs. We used an equivalent procedure for
testing the statistical significance of the correlation difference and unique variance
difference between different models.

For ROI analysis, we corrected the p-values for multiple comparisons by applying
FDR correction with a threshold equal to 0.05. For searchlight analyses, we applied FDR
correction to correct for the number of DNNs compared as well as to correct for the
number of searchlights that had a significant noise ceiling.

We applied a two-sided t-test to assess the statistical significance of the cross-
validated explained variance across N subjects. We corrected the p-values for multiple
comparisons by applying FDR correction.

Acknowledgements

G.R. thanks the support of the Alfons and Gertrud Kassel Foundation. R.M.C. is
supported by DFG grants (CI241/1-1, CI241/3-1) and the ERC Starting Grant (ERC-2018-

StG 803370). The authors thank Agnessa Karapetian and Greta Häberle for their valuable

comments on the manuscript.

Author Contributions

K.D., R.M.C., and G.R. designed research. K.D., M.F.B. performed data analyses. K.D.

performed the computational modeling and the statistical analyses. K.D., R.M.C, and G.R

analyzed the results. All authors discussed the results and contributed to the manuscript.

G.R and R.M.C jointly directed the work.

Data and code availability

Data   and   code   to   reproduce   all   the   results   is   available   here:

https://sites.google.com/view/dnn2brainfunction/home

Data and code availability

The authors declare no competing interests.

REFERENCES

1.   Mishkin, M. & Ungerleider, L. G. Contribution of striate inputs to the visuospatial

functions of parieto-preoccipital cortex in monkeys. *Behav. Brain Res.* **6**, 57–77

(1982).

2.   Grill-Spector, K. & Malach, R. The Human Visual Cortex. *Annu. Rev. Neurosci.* **27**,

649–677 (2004).

3.   Cadieu, C. F. *et al.* Deep Neural Networks Rival the Representation of Primate IT

Cortex for Core Visual Object Recognition. *PLoS Comput. Biol.* **10**, e1003963

(2014).

4.   Cichy, R. M., Khosla, A., Pantazis, D., Torralba, A. & Oliva, A. Comparison of deep

neural networks to spatio-temporal cortical dynamics of human visual object

recognition reveals hierarchical correspondence. *Sci. Rep.* **6**, 27755 (2016).

5. Guclu, U. & van Gerven, M. A. J. Deep Neural Networks Reveal a Gradient in the

Complexity of Neural Representations across the Ventral Stream. *J. Neurosci.* **35**,

10005–10014 (2015).

6. Khaligh-Razavi, S.-M. & Kriegeskorte, N. Deep supervised, but not unsupervised,

models may explain IT cortical representation. *PLoS Comput. Biol.* **10**, e1003915

(2014).

7. Yamins, D. L. *et al.* Performance-optimized hierarchical models predict neural

responses in higher visual cortex. *Proc. Natl. Acad. Sci.* **111**, 8619–8624 (2014).

8. Zamir, A. R. *et al.* Taskonomy: Disentangling Task Transfer Learning. in

Proceedings of the IEEE conference on computer vision and pattern recognition

3712–3722 (2018)..

9. Bonner, M. F. & Epstein, R. A. Coding of navigational affordances in the human

visual system. *Proc. Natl. Acad. Sci.* **114**, 4793–4798 (2017).

10. Etzel, J. A., Zacks, J. M. & Braver, T. S. Searchlight analysis: promise, pitfalls, and

potential. *NeuroImage* **78**, 261–269 (2013).

11. Haynes, J.-D. *et al.* Reading Hidden Intentions in the Human Brain. *Curr. Biol.* **17**,

323–328 (2007).

12. Kriegeskorte, N., Goebel, R. & Bandettini, P. Information-based functional brain

mapping. *Proc. Natl. Acad. Sci.* **103**, 3863–3868 (2006).

13. Kriegeskorte, N., Mur, M. & Bandettini, P. A. Representational similarity analysis-

connecting the branches of systems neuroscience. *Front. Syst. Neurosci.* **2**, 4

(2008).

14. Dwivedi, K. & Roig, G. Representation Similarity Analysis for Efficient Task

Taxonomy & Transfer Learning. in *Proceedings of the IEEE conference on computer*

vision and pattern recognition 12379–12388 (2019).

15. Wang, L., Mruczek, R. E. B., Arcaro, M. J. & Kastner, S. Probabilistic Maps of Visual

Topography in Human Cortex. *Cereb. Cortex* **25**, 3911–3931 (2015).

16. Legendre, P. Studying beta diversity: ecological variation partitioning by multiple

regression and canonical analysis. *J. Plant Ecol.* **1**, 3–8 (2008).

17. Dwivedi, K., Cichy, R. M. & Roig, G. Unraveling Representations in Scene-selective

Brain Regions Using Scene-Parsing Deep Neural Networks. *J. Cogn. Neurosci.* 1–

12 (2020) doi:10.1162/jocn_a_01624.

18. Groen, I. I. *et al.* Distinct contributions of functional and deep neural network

features to representational similarity of scenes in human brain and behavior. *Elife*

7, e32962 (2018).

19. Nayebi, A. *et al.* Task-Driven convolutional recurrent models of the visual system. in

Advances in Neural Information Processing Systems 5290–5301 (2018).

20. Yamins, D. L. & DiCarlo, J. J. Using goal-driven deep learning models to understand

sensory cortex. *Nat. Neurosci.* **19**, 356 (2016).

21. Kell, A. J. E., Yamins, D. L. K., Shook, E. N., Norman-Haignere, S. V. & McDermott,

J. H. A Task-Optimized Neural Network Replicates Human Auditory Behavior,

Predicts Brain Responses, and Reveals a Cortical Processing Hierarchy. *Neuron*

98, 630-644.e16 (2018).

22. Wang, A., Tarr, M., & Wehbe, L. Neural taskonomy: Inferring the similarity of task-

derived representations from brain activity. In *Advances in Neural Information*

Processing Systems 15501-15511 (2019).

23. Avidan, G. *et al.* Contrast Sensitivity in Human Visual Areas and Its Relationship to

Object Recognition. *J. Neurophysiol.* **87**, 3102–3116 (2002).

24. Boynton, G. M., Demb, J. B., Glover, G. H. & Heeger, D. J. Neuronal basis of

contrast discrimination. *Vision Res.* **39**, 257–269 (1999).

25. Ress, D. & Heeger, D. J. Neuronal correlates of perception in early visual cortex.

Nat. Neurosci. **6**, 414–420 (2003).

26. Backus, B. T., Fleet, D. J., Parker, A. J. & Heeger, D. J. Human Cortical Activity

Correlates With Stereoscopic Depth Perception. *J. Neurophysiol.* **86**, 2054–2068

(2001).

27. Grill-Spector, K., Kourtzi, Z. & Kanwisher, N. The lateral occipital complex and its

role in object recognition. *Vision Res.* **41**, 1409–1422 (2001).

28. Kourtzi, Z., Erb, M., Grodd, W. & Bülthoff, H. H. Representation of the perceived 3-D

object shape in the human lateral occipital complex. *Cereb. Cortex N. Y. N 1991* **13**,

911–920 (2003).

29. Moore, C. & Engel, S. A. Neural Response to Perception of Volume in the Lateral

Occipital Complex. *Neuron* **29**, 277–286 (2001).

30. Stanley, D. A. & Rubin, N. fMRI Activation in Response to Illusory Contours and

Salient Regions in the Human Lateral Occipital Complex. *Neuron* **37**, 323–331

(2003).

31. Arcaro, M. J., McMains, S. A., Singer, B. D. & Kastner, S. Retinotopic Organization

of Human Ventral Visual Cortex. *J. Neurosci.* **29**, 10638–10652 (2009).

32. Grill-Spector, K. & Weiner, K. S. The functional architecture of the ventral temporal

cortex and its role in categorization. *Nat. Rev. Neurosci.* **15**, 536–548 (2014).

33. Cichy, R. M. & Kaiser, D. Deep neural networks as scientific models. *Trends Cogn.*

Sci. (2019).

34. Khaligh-Razavi, S.-M., Henriksson, L., Kay, K. & Kriegeskorte, N. Fixed versus

mixed RSA: Explaining visual representations by fixed and mixed feature sets from

shallow and deep computational models. *J. Math. Psychol.* **76**, 184–197 (2017).

35. Schrimpf, M. *et al.* Integrative Benchmarking to Advance Neurally Mechanistic

Models of Human Intelligence. *Neuron* (2020) doi:10.1016/j.neuron.2020.07.040.

36. Kar, K., Kubilius, J., Schmidt, K., Issa, E. B. & DiCarlo, J. J. Evidence that recurrent

circuits are critical to the ventral stream's execution of core object recognition

behavior. *Nat. Neurosci.* **22**, 974 (2019).

37. Kietzmann, T. C. *et al.* Recurrence is required to capture the representational

dynamics of the human visual system. *Proc. Natl. Acad. Sci.* **116**, 21854–21863

(2019).

38. Lillicrap, T. P., Santoro, A., Marris, L., Akerman, C. J. & Hinton, G. Backpropagation

and the brain. *Nat. Rev. Neurosci.* **21**, 335–346 (2020).

39. Roelfsema, P. R. & Holtmaat, A. Control of synaptic plasticity in deep cortical

networks. *Nat. Rev. Neurosci.* **19**, 166–180 (2018).

40. Whittington, J. C. R. & Bogacz, R. Theories of Error Back-Propagation in the Brain.

Trends Cogn. Sci. **23**, 235–250 (2019).

41. Epstein, R. & Baker, C. Scene Perception in the Human Brain. *Annu. Rev. Vis. Sci.*

(2019).

42. Lindsay, G. W. Convolutional Neural Networks as a Model of the Visual System:

830   Past, Present, and Future. *ArXiv200107092 Cs Q-Bio* (2020).

831 43. Richards, B. A. *et al.* A deep learning framework for neuroscience. *Nat. Neurosci.*

832   **22**, 1761–1770 (2019).

833 44. Marr, D. *Vision: A Computational Investigation Into the Human Representation and*

834   *Processing of Visual Information*. (MIT Press, 2010).

835 45. Lin, T.-Y. *et al.* Microsoft COCO: Common Objects in Context. in *Computer Vision –*

836   *ECCV 2014* (eds. Fleet, D., Pajdla, T., Schiele, B. & Tuytelaars, T.) 740–755

837   (Springer International Publishing, 2014). doi:10.1007/978-3-319-10602-1_48.

838 46. LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521**, 436–444 (2015).

839 47. Poldrack, R. A. & Gorgolewski, K. J. Making big data open: data sharing in

840   neuroimaging. *Nat. Neurosci.* **17**, 1510–1517 (2014).

841 48. He, K., Zhang, X., Ren, S. & Sun, J. Deep residual learning for image recognition. in

842   *Proceedings of the IEEE conference on computer vision and pattern recognition*

843   770–778 (2016).

844 49. Kumar, M. *et al.* BrainIAK tutorials: User-friendly learning materials for advanced

845   fMRI analysis. *PLOS Comput. Biol.* **16**, e1007549 (2020).

846 50. Bonner, M. F. & Epstein, R. A. Computational mechanisms underlying cortical

847   responses to the affordance properties of visual scenes. *PLoS Comput. Biol.* **14**,

848   e1006111 (2018).

849 51. Lescroart, M.D. and Gallant, J.L., 2019. Human scene-selective areas represent 3D

850   configurations of surfaces. *Neuron*, *101*(1), pp.178-192.

851 52. Güçlü, U. and van Gerven, M.A., 2017. Increasingly complex representations of

852   natural movies across the dorsal stream are shared between

subjects. *NeuroImage*, *145*, pp.329-336.

53. Ponce, C.R., Xiao, W., Schade, P.F., Hartmann, T.S., Kreiman, G. and Livingstone,

M.S., 2019. Evolving images for visual neurons using a deep generative network

reveals coding principles and neuronal preferences. Cell, 177(4), pp.999-1009.

54. Bashivan, P., Kar, K. and DiCarlo, J.J., 2019. Neural population control via deep

image synthesis. Science, 364(6439).

55. Seeliger, K., Ambrogioni, L., Güçlütürk, Y., van den Bulk, L.M., Güçlü, U. and van

Gerven, M.A.J., 2021. End-to-end neural system identification with neural

information flow. PLoS Computational Biology, 17(2), p.e1008558.

56. Scholte, H.S., Losch, M.M., Ramakrishnan, K., de Haan, E.H. and Bohte, S.M.,

2018. Visual pathways from the perspective of cost functions and multi-task deep

neural networks. cortex, 98, pp.249-261.

57. Kokkinos, I., 2017. Ubernet: Training a universal convolutional neural network for

low-, mid-, and high-level vision using diverse datasets and limited memory. In

Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition

(pp. 6129-6138).

58. Allen, E.J., St-Yves, G., Wu, Y., Breedlove, J.L., Dowdle, L.T., Caron, B., Pestilli, F.,

Charest, I., Hutchinson, J.B., Naselaris, T. and Kay, K., 2021. A massive 7T fMRI

dataset to bridge cognitive and computational neuroscience. bioRxiv.

59. Klein, Colin. "Cognitive Ontology and Region- versus Network-Oriented Analyses."

Philosophy of Science 79 (2012): 952-960.

60. Storrs, K.R., Kietzmann, T.C., Walther, A., Mehrer, J. and Kriegeskorte, N., 2020.

Diverse deep neural networks all predict human IT well, after training and fitting.

bioRxiv.

61. Gu, Z., Jamison, K.W., Khosla, M., Allen, E.J., Wu, Y., Naselaris, T., Kay, K.,

Sabuncu, M.R. and Kuceyeski, A., 2021. NeuroGen: activation optimized image

synthesis for discovery neuroscience. arXiv preprint arXiv:2105.07140.

62. Weihs, L., Salvador, J., Kotar, K., Jain, U., Zeng, K.H., Mottaghi, R. and Kembhavi,

A., 2020. Allenact: A framework for embodied ai research. arXiv preprint

arXiv:2008.12760.

63. Batra, D., Gokaslan, A., Kembhavi, A., Maksymets, O., Mottaghi, R., Savva, M.,

Toshev, A. and Wijmans, E., 2020. Objectnav revisited: On evaluation of embodied

agents navigating to objects. arXiv preprint arXiv:2006.13171.

64. Weihs, L., Kembhavi, A., Ehsani, K., Pratt, S.M., Han, W., Herrasti, A., Kolve, E.,

Schwenk, D., Mottaghi, R. and Farhadi, A., 2019. Learning Generalizable Visual

Representations via Interactive Gameplay. arXiv preprint arXiv:1912.08195.

<h1 style="text-align:center">Supplementary information</h1>

899
900
901 Here, we provide the supplementary material that complements the main manuscript.
902   1. Illustration of variance partitioning method
903   2. Selecting Task-specific DNN representations
904   3. R^2 ranking for all the DNNs in localized and anatomical ROIs
905   4. Effect of cross validation on explained variance (R^2)
906
907

908 **S1: Variance partitioning**

909
SFigure 1: Variance partitioning overview: Given a set of multiple independent variables and dependent

variables, multiple linear regression results in R-squared (r^2) that represents the proportion of the variance

for a dependent variable that is explained by independent variables in a regression model. To find how 3

DNN RDMs together explain the variance of a given fMRI RDM we perform 7 multiple regression and

illustrate unique and shared variance explained by models through a Venn diagram

S2: Selecting Task-specific DNN representations

Our aim was to select the layers of the encoders of the DNN that had task-specific

representation. By task-specific representation, we refer to representation learned by the

DNN to perform the corresponding task. We performed multiple analyses to find out which

layers of the encoder consisted of the most task-specific information. In the first analysis, we calculated the Spearman's correlation of one DNN RDM from a given layer with all the other DNN RDMs from the same layer. We performed this analysis for all pairwise combinations of DNNs investigated in this study and plotted the mean correlation for all pairwise DNN comparisons per layer in SFigure 2a. In SFigure 2a, we observed that early

SFigure 2: Selecting task-specific DNN representation to compare with fMRI data: **a)** Spearman's correlation of all DNN RDMs at a given layer of the encoder with other DNN RDMs computed at the same layer. We report the mean pairwise correlation of all 18 DNNs at different layers of the encoder. **b)** Spearman's correlation of all DNN RDMs at a given layer of the encoder with a randomly initialized model with the same architecture computed at the same layer. We report the mean correlation of all 18 DNNs with the randomly initialized DNN at different layers of the encoder. **c)** Spearman's correlation of all DNN RDMs

at a given layer of the encoder with deeper layers (block4 and encoder output) of 2D DNNs. We report the
mean correlation of the key layers of all 18 DNNs with deeper layers (block4 and encoder output) of 2D
DNNs. **d)** Spearman's correlation between layers at different depths for DNNs corresponding to different
task types. We report the mean correlation between different layers averaged across different DNNs of the
same task type. **e)** Effect of adding all the key layers on unique and shared variance of fMRI RDMs from
different ROIs as compared to selecting only task-specific layers for variance partitioning analysis. We
report the change in variance explained (variance change) for 7 variance partitions when all key layers were
used for analysis as compared to selecting task-specific layers.

layers of the encoder showed a higher mean pairwise correlation than the deeper layers.

The results suggest that early layers of DNN learn similar representation irrespective of

the task DNN was optimized for, while task-specificity increases as we go deeper in the

network. In the second analysis, we calculated the Spearman's correlation of RDMs of a

given layer from all the 18 DNNs investigated in this study and compared with the RDM

of the same layer from a randomly initialized network having the exact same encoder

architecture (SFigure 2b). In SFigure 2b, we observed that early layers showed a higher

correlation with randomly initialized DNN than deeper layers. The results reinforce our

argument that early layers learn a general representation irrespective of the task DNN

was optimized for while deeper layers consist of more task-specific information.

An arguably attractive procedure for layer selection is to select all key layers for

each of the DNNs and then perform the comparison. We argue against this by performing

an analysis comparing the representation of late layers of 2D DNNs (block 4 and encoder

output) with key layers of all the DNNs (Sfigure 2c). We find that early layers of all the

DNNs show a high correlation with late layers of 2D DNNs, suggesting that early layers

of all DNNs learn a representation required to perform low-level 2D tasks irrespective of

the tasks they need to perform (3D or semantic). We further validate this argument by

comparing the correlation between different layers of DNNs within a task type (Sfigure

2d). We find that in 2D DNNs the late layers show a high correlation with early layers,

suggesting that to perform 2D functions DNNs learn very similar representations at

different depths of the network. In the case of 3D and semantic DNNs, the late layers

show low correlation with early layers, suggesting that a different representation is

required to perform these tasks and that these representations are found in late layers.

The early layer representations of all DNNs are very similar to representations learned by 2D DNNs. Including these layers into the variance partitioning analysis could diminish the unique variance of fMRI RDMs explained by 2D DNNs due to an increase in shared variance explained by all the DNNs together. We show the above effect by reporting the change in unique and shared variance when all key layers were used in variance partitioning analysis corresponding to Section 3 of main text instead of the last 2 layers of the encoder (Sfigure 2e). We observe that adding early layers of all 3 different types of DNNs in the analysis leads to an increase in shared variance explained by all these models together and reducing the unique variance contribution of 2D DNNs significantly in the early visual regions. We further observe that in high-level ROIs for which the unique variance of 2D DNNs was insignificant in the original analysis, we barely notice any changes in the unique variance explained. Therefore, to observe the differences in the DNNs due to the task they were optimized to perform we selected the last two layers of the DNNs as the task-specific representation.

S3: R^2 ranking for all the DNNs in localized and anatomical ROIs

SFigure 3: R^2 ranking for 18 Taskonomy DNNs and random baseline in functionally localized ROIs. The bar plot shows the absolute total variance of each ROI RDM explained by task-specific layer RDMs of a given DNNs. The asterisk denotes the significance of total variance ($p<0.05$, permutation test with 10,000 iterations, FDR-corrected across DNNs). The error bars show the standard deviation calculated by bootstrapping 90% of the conditions (10,000 iterations).

985 **SFigure 4: R^2 ranking for 18 Taskonomy DNNs and random baseline in anatomical ROIs.** The bar plot

986 shows the absolute total variance of each ROI RDM explained by task-specific layer RDMs of a given

987 DNNs. The asterisk denotes the significance of total variance (p<0.05, permutation test with 10,000

988   iterations, FDR-corrected across DNNs). The error bars show the standard deviation calculated by

989   bootstrapping 90% of the conditions (10,000 iterations).

S4: Effect of cross validation on explained variance (R^2)

SFigure 5: Effect of cross validation on variance explained (R^2) a) Variance of each ROI explained by

top-3 best predicting DNNs compared for different cross-validation settings (blue bars: no cross validation;

orange bars: cross validation across subjects; green bars: cross validation across subjects and stimuli).

The error bars show the 95% confidence interval calculated across N=16 subjects. All the R^2 values are

statistically significant (p<0.05, two-sided t-test, FDR-corrected across ROIs) **b)** Variance of each ROI

explained by 1000 randomly generated RDMs compared for different cross-validation settings (blue bars:

no cross validation; orange bars: cross validation across subjects; green bars: cross validation across

subjects and stimuli). The error bars show the 95% confidence interval calculated across N=16 subjects.

1000