Coherent natural scene structure facilitates the extraction of task-relevant object information in visual cortex

Daniel Kaiser[1], Greta Häberle[2,3,4], Radoslaw M. Cichy[2,3,4,5]

[1]*Department of Psychology, University of York, York, UK*

[2]*Department of Education and Psychology, Freie Universität Berlin, Berlin, Germany*

[3]*Charité – Universitätsmedizin Berlin, Einstein Center for Neurosciences Berlin, Berlin, Germany*

[4]*Humboldt-Universität zu Berlin, Faculty of Philosophy, Berlin School of Mind and Brain, Berlin, Germany*

[5]*Bernstein Center for Computational Neuroscience Berlin, Berlin, Germany*

Correspondence:

Dr. Daniel Kaiser

Department of Psychology

University of York

Heslington, York

YO10 5DD, UK

danielkaiser.net@gmail.com

Abstract

Looking for objects within complex natural environments is a task everybody performs multiple times each day. In this study, we explore how the brain uses the typical composition of real-world environments to efficiently solve this task. We recorded fMRI activity while participants performed two different categorization tasks on natural scenes. In the object task, they indicated whether the scene contained a person or a car, while in the scene task, they indicated whether the scene depicted an urban or a rural environment. Critically, each scene was presented in an "intact" way, preserving its coherent structure, or in a "jumbled" way, with information swapped across quadrants. In both tasks, participants' categorization was more accurate and faster for intact scenes. These behavioral benefits were accompanied by stronger responses to intact than to jumbled scenes across high-level visual cortex. To track the amount of object information in visual cortex, we correlated multi-voxel response patterns during the two categorization tasks with response patterns evoked by people and cars in isolation. We found that object information in object- and body-selective cortex was enhanced when the object was embedded in an intact, rather than a jumbled scene. However, this enhancement was only found in the object task: When participants instead categorized the scenes, object information did not differ between intact and jumbled scenes. Together, these results indicate that coherent scene structure facilitates the extraction of object information in a task-dependent way, suggesting that interactions between the object and scene processing pathways adaptively support behavioral goals.

Keywords

1 Introduction

Despite the complexity of our everyday environments, perceiving objects embedded

in natural scenes is remarkably efficient. This efficiency is illustrated by studies that

require participants to categorize objects under conditions of limited visual exposure:

For instance, participants can tell whether a scene contains an animal or not from just

a single glance (Thorpe et al., 1996; Potter, 1975, 2012), and even when only limited

attentional resources are available (Li et al., 2002).

The ability to effortlessly make such categorization responses is underpinned

by the efficient extraction of object information in visual cortex. Neuroimaging

research has shown that the category of task-relevant objects can be reliably

decoded from fMRI activity patterns in visual cortex, even when the objects are

embedded in complex natural scenes (Peelen et al., 2009; Peelen & Kastner, 2011;

Seidl et al., 2012) or movies (Cukur et al., 2013; Nastase et al., 2017; Shahdloo et al.,

2020). M/EEG studies demonstrate that object category is represented well within the

first 200ms of vision, even when the object is shown under such naturalistic

conditions (Cauchoix et al., 2014; Kaiser et al., 2016; VanRullen & Thorpe, 2001;

Thorpe et al., 1996). Together, these results highlight that the cortical processing of

objects appearing within rich real-world environments is surprisingly efficient.

This processing efficiency becomes less surprising if scene context is not just

considered as a nuisance that puts additional strain on our visual resources. Indeed,

contextual information can facilitate object processing (Bar, 2004): For instance,

scene context allows for efficient allocation of attention (Torralba et al., 2006; Wolfe

et al., 2011; Võ et al., 2019), or for disambiguating object information under

uncertainty (Brandmann & Peelen, 2017; Oliva & Torralba, 2007). Such findings

demonstrate that object and scene processing mechanisms interact with each other

to enable the efficient processing of object information.

Here, we investigated how the coherent spatial structure of the scene context

aids the extraction of object information from the scene. To this end, we used a

jumbling paradigm, in which we disrupted the scenes' coherent structure by dividing

them into multiple rectangular pieces and shuffling those pieces. Classical studies

suggest that jumbling drastically impairs participants' ability to categorize both the

scene itself (Biederman et al., 1974), and the object embedded within the scene

(Biederman et al., 1972, 1973). Such impairments can be linked to changes in cortical

scene processing: We have recently shown that scene-selective brain responses are

less pronounced and contain less scene category information when the scene is

jumbled (Kaiser et al., 2020a, 2020b). However, it is unclear how these changes in

scene-selective activations modulate the representation of objects within the scene.

In the current study, we thus set out to characterize how the presence of an

intact – versus a jumbled – scene context modulates object representations in visual

cortex. First, we asked whether cortical object processing is indeed facilitated by the

presence of a coherent scene context. Second, we asked whether such facilitation

effects depend on the objects being relevant or irrelevant for current behavioral goals.

To answer these questions, we recorded fMRI activity while participants

categorized objects contained in intact or jumbled scenes. We found that fMRI

responses across high-level visual cortex were generally higher for intact scenes than

for jumbled scenes, revealing widespread sensitivity to scene structure. When

analyzing object category information in multi-voxel response patterns, we found that

coherent scene structure enhanced object information in object-selective visual

cortex. However, this enhancement was task-specific: When participants categorized

the scenes instead of the objects, we found no such enhancement of object

information. These results suggest that the visual brain uses coherent real-world

structure to more efficiently extract task-relevant object information from complex

scenes.

2 Materials and Methods

2.1 Participants

Twenty-five healthy adults (mean age 26.4 years, SD=5.3; 15 female, 10 male) participated. All participants had normal or corrected-to-normal vision. They all provided informed written consent and received either monetary reimbursement or course credits. Procedures were approved by the ethical committee of the Department of Psychology at Freie Universität Berlin and were in accordance with the Declaration of Helsinki.

2.2 Stimuli

The stimulus set consisted of colored natural scene photographs (640×480 pixels resolution). Scenes were selected to cover three independent manipulations. First, each scene contained one of two object categories: half of the scenes contained a person (or multiple people), whereas the other half contained a car (or multiple cars). Second, the person or car appeared equally often in each of the quadrants of the scene. Third, each scene belonged to one of two scene categories: half of the scenes depicted urban environments, the other half depicted rural environments. For each possible combination of these factors (e.g., a person appearing in the bottom left quadrant of a rural scene), 10 unique scene exemplars were available, yielding 160 scenes in total (2 object categories × 4 object locations × 2 scene categories × 10 exemplars). During the experiment, the scenes could be presented in their original orientation or mirrored along their vertical axis (as in Kaiser et al., 2016), yielding a total of 320 different scene stimuli. Example scenes are shown in Figure 1a.

To manipulate scene structure, we either presented the scenes in a coherent, "intact" condition or in an incoherent, "jumbled" condition. Jumbled scenes were generated by shuffling the four quadrants of the image in a crisscrossed way (Figure 1b). This manipulation solely affected the scene's structure, but not the people or cars contained in the scene: First, as the objects never straddled the boundary between quadrants, the objects themselves always remained unaltered. Second, as the objects appeared equally often in each quadrant before jumbling the scenes, they also appeared equally often in each quadrant after jumbling them.

In total, 640 scene images were used, which covered 320 intact scenes and
320 jumbled scenes. Additionally, 200 colored texture masks (Kaiser et al., 2016) were
used to visually mask the scenes during the experiment (see below).

Figure 1. Stimuli, paradigm, and behavioral results. a) *Stimuli consisted of natural*
scene images from two categories: urban or rural environments. Each of the scenes
contained one of two object categories: people or cars. ***b)*** *During the experiment,*
these scenes were shown in an unaltered way ("intact" condition) or with their
quadrants intermixed ("jumbled" condition). The jumbled scenes were created by
shuffling the quadrants in a crisscrossed way, as illustrated. ***c)*** *Participants viewed*
each scene briefly, followed by a visual mask. In separate runs, they performed two
different tasks: They were either asked to indicate whether the scene contained a
person or a car ("object task") or whether the scene depicted an urban or a rural
environment ("scene task"). ***d)*** *In both tasks, scene structure impacted behavioral*
performance: Participants were significantly more accurate and faster for the intact
scenes than for the jumbled scenes. Error bars represent standard errors of the mean.

2.3 Experimental Paradigm
Each participant completed four experimental runs of 17 minutes each. Each run
contained 320 experimental trials, corresponding to 320 unique scene stimuli. For

half of the participants, the even runs only contained the original scenes, while the
odd runs only contained the horizontally mirrored scenes; for the other half of the
participants, the odd runs only contained the original scenes, while the even runs only
contained the horizontally mirrored scenes. Each of the scenes was presented once
during the run, with order fully randomized.

On each trial, the scene was presented for 83ms, immediately followed by a
visual mask (chosen randomly from the 200 available masks) for 800ms. Images were
shown within a black rectangle (10deg X 7.5deg visual angle). After an inter-trial
interval of 1,617ms, during which a pink fixation dot was shown, the next trial started.
An example trial is illustrated in Figure 1c. In addition to the experimental trials, each
run contained 80 fixation-only trials, during which only the fixation dot was displayed.
Runs started and ended with a brief fixation period.

In two of the four runs, participants were asked to categorize the object
contained in each scene as either a person or a car ("object task"). In the other two
runs, participants were asked to categorize the scene as either a rural or an urban
environment ("scene task"). Participants were instructed to respond as accurately
and quickly as possible, with an emphasis on accuracy. Button-press responses were
recorded during the whole inter-trial interval (i.e., until 2,500s after stimulus onset).
The four runs were alternating between the object and scene tasks. The task in the
first run was counter-balanced between participants. Notably, physical stimulation
was completely identical across the object and scene tasks.

All stimuli were back-projected onto a translucent screen mounted to the head
end of the scanner bore. Participants viewed the stimulation through a mirror
attached to the head coil. Stimulus presentation was controlled using the
Psychtoolbox (Brainard, 1997).

2.4 Benchmark Localizer Paradigm

In addition to the experimental runs, each participant completed a benchmark
localizer run, which was designed to obtain "benchmark" patterns in response to
people and cars in isolation (Peelen et al., 2009; Peelen & Kastner, 2011). During this
run, participants viewed images of bodies, cars, and scrambled images of bodies and
cars. For each of the three categories, 40 images were used. All images were different

than the ones used in the main experiment. These images were presented in a block

design. Each block lasted 20 seconds and contained 20 images of one of the three

categories, or only a fixation cross. Images were presented for 500ms (5deg × 5deg

visual angle), separated by a 500ms inter-stimulus interval. The benchmark localizer

run consisted of a total of 24 blocks (6 blocks for each of the three stimulus

categories, and 6 fixation-only blocks). Four consecutive blocks always contained the

four different conditions in random order. Participants were instructed to respond to

one-back image repetitions (i.e., two identical images back-to-back), which

happened once during each non-fixation block. The benchmark localizer run lasted

8:30 minutes and was completed halfway through the experiment, after two of the

four experimental runs.

2.5 fMRI recording and preprocessing

MRI data was acquired using a 3T Siemens Tim Trio Scanner equipped with a 12-

channel head coil. T2*-weighted gradient-echo echo-planar images were collected

as functional volumes (TR=2s, TE=30ms, 70° flip angle, $3mm^3$ voxel size, 37 slices,

20% gap, 192mm FOV, 64×64 matrix size, interleaved acquisition). Additionally, a T1-

weighted anatomical image (MPRAGE; $1mm^3$ voxel size) was obtained.

Preprocessing and hemodynamic response modelling was performed using

SPM12 (www.fil.ion.ucl.ac.uk/spm/). Functional volumes were realigned and

coregistered to the anatomical image. Further, the T1 image was segmented to obtain

transformation parameters to standard MNI-305 space.

Functional data from each experimental run were modelled in a general linear

model (GLM) with 16 experimental predictors (2 object categories × 4 object locations

× 2 scene categories). Additionally, we included the six movement regressors

obtained during realignment. Data from the benchmark localizer run were modelled

in a GLM with three experimental predictors (person, car, scrambled) and six

movement regressors.

2.6 Region of interest definition

We restricted fMRI analyses to five regions of interest (ROIs): early visual cortex (V1),

object-selective lateral occipital cortex (LO), body-selective extrastriate body area

(EBA), scene-selective occipital place area (OPA), and scene-selective
parahippocampal place area (PPA). ROIs masks were defined using group-level
activation masks from functional brain atlases (for V1: Wang et al., 2015; for LO, EBA,
OPA, and PPA: Julian et al., 2012). ROIs were defined separately for each
hemisphere. All ROI masks were inverse-normalized into individual-participant space
using the parameters obtained during T1 segmentation. Voxel counts in individual-
participant space amounted to 248/271 (V1; left/right), 929/947 (LO), 402/443 (EBA),
26/47 (OPA), and 140/105 (PPA). Notably, the LO and EBA ROIs overlapped to some
extent (300/406 voxels overlap, left/right); the inclusion of the EBA allowed us to see
whether the results hold in a smaller cortical region with a narrower category
preference for bodies. As we did not have any hypothesis related to hemispheric
differences, all results for the left- and right-hemispheric ROIs were averaged before
statistical analysis.
237

2.7 Univariate analysis
Response magnitudes during the experimental runs were analyzed separately for
each ROI. We first averaged beta values across the two object-task and scene-task
runs, respectively. We then averaged beta values across object categories, object
locations, and scene categories. This way, we obtained response magnitudes for four
conditions: (1) responses to intact scenes in the object task, (2) responses to jumbled
scenes in the object task, (3) responses to intact scenes in the scene task, and (4)
responses to jumbled scenes in the scene task. These four conditions allowed us to
separately estimate the effects of task (object task versus scene task) and scene
structure (intact versus jumbled) on neural responses across the five ROIs.
248

2.8 Multivariate pattern analysis
Multivariate pattern analysis (MVPA) was carried out in CoSMoMVPA (Oosterhof et
al., 2016). Our MVPA approach closely followed similar fMRI studies that investigated
the representation of objects in natural scenes (Peelen et al., 2009; Peelen & Kastner,
2011). We first computed a one-sample t-contrasts for every condition against
baseline. In the benchmark localizer run, there were 2 such t-contrasts (one for people
versus baseline, and one for cars versus baseline). In the object task and scene task

runs, there were 16 t-contrasts each (one contrast for each experimental condition against baseline, reflecting 2 object categories × 4 object locations × 2 scene categories). For each of the three tasks (benchmark localizer, object task, and scene task), the resulting t-values were normalized for each voxel by subtracting the average t-value across conditions. For each ROI, multi-voxel response patterns were constructed by concatenating the t-values across all voxels belonging to the ROI.

To obtain an index of object discriminability (i.e., how discriminable people and cars in scenes are based on multi-voxel response patterns), we performed a cross-correlation MVPA. The goal of this analysis was to quantify how "person-like" or "car-like" the cortical representation of each of the scenes was, thereby isolating the amount of object category information in visual cortex. To this end, we correlated multi-voxel response patterns evoked by people and cars in isolation (from the benchmark localizer) with response patterns evoked by people and cars contained in a scene (from one of the experimental tasks). These correlations were Fisher-transformed. To quantify object discriminability, we then subtracted the correlations between different categories (e.g., person in isolation and car within a scene) from correlations between the same categories (e.g., person in isolation and person within a scene). This yielded an index of category-discriminability, with values greater than zero indicating that the two categories are represented differently (Haxby et al., 2001).

Before performing this analysis, response patterns in the main experiment were averaged across object locations and scene categories. This way, we obtained an index of object category-discriminability for four separate conditions: (1) category-discriminability for intact scenes in the object task, (2) category-discriminability for jumbled scenes in the object task, (3) category-discriminability for intact scenes in the scene task, and (4) category-discriminability for jumbled scenes in the scene task. The resulting four conditions allowed us to estimate the effects of scene structure on the quality of object representations in visual cortex, both when the objects were task-relevant and task-irrelevant.

2.9 Statistical testing

To compare behavioral performance, univariate responses, and multi-voxel pattern

information across conditions, we used repeated-measures ANOVAs and paired-

sample t-tests.

2.10 Data availability

Data are publicly available on OSF (doi.org/10.17605/osf.io/gs2t5). Other materials

are available from the corresponding author upon request.

3 Results

3.1 Coherent scene structure facilitates the perception of objects within scenes

We first analyzed participants' behavioral performance in the object and scene tasks, separately for the intact and jumbled scenes (Figure 1d). In the object task, participants' categorization (person versus car) of objects within the intact scenes was more accurate, t(24)=8.28, p<.001, and faster, t(24)=3.26, p=.0033, compared to the jumbled scenes. In the scene task, participants' categorization (rural versus urban) of the intact scenes was more accurate, t(24)=4.77, p<.001, and faster, t(24)=3.26, p=.0033, compared to the jumbled scenes. These results are in line with classical findings on object and scene categorization in jumbling paradigms (Biederman, 1972; Biederman et al., 1973, 1974), showcasing that scene jumbling has a profound impact on perception.

Further, when directly comparing the two tasks, we did not find differences in accuracy, F(1,24)=3.13, p=.090, or response times, F(1,24)=0.04, p=.84. Any differences in neural responses are therefore unlikely to reflect differences in task difficulty, and therefore attentional engagement, between the two tasks.

Together, these results demonstrate that jumbling similarly impairs the perception of the scene and the objects contained in it, demonstrating a cross-facilitation between scene and object vision that can be observed on the behavioral level.

3.2 Scene structure impacts univariate responses across object- and scene-selective cortex

To quantify the effects of scene jumbling on the neural level, we first ran univariate analyses. In these analyses, we compared fMRI response magnitudes across the intact and jumbled scenes and across the two tasks (Figure 2). To do so, we performed a 2×2 repeated measures ANOVA with the factors scene structure (intact versus jumbled) and task (object task versus scene task). The analysis was performed separately and in turn for each of the five ROIs: V1, LO, EBA, OPA, and PPA. Detailed results for these analyses can be found in Table 1.

In V1, responses were comparable across all conditions, all F<1.25, p>.27,

suggesting that V1 is not sensitive to typical scene composition.

In all extrastriate ROIs, we found a main effect of scene structure, which

indicated stronger responses to intact than to jumbled scenes, all F(1,24)>7.95,

p<.010. Comparing this effect across regions, we found that it was more pronounced

in the scene-selective regions, OFA versus LO/EBA, both F(1,24)>31.17, p<.001, and

PPA versus LO/EBA, both F(1,24)>35.55, p<.001. This finding confirms our previous

fMRI results, which revealed particularly strong effects of scene jumbling in scene-

selective areas of visual cortex (Kaiser et al., 2020a).

Table 1: *Univariate responses, analyzed in a 2×2 repeated measures ANOVA with the*

factors scene structure (intact versus jumbled) and task (object task versus scene

task). Significant effects are highlighted in bold.

ROI	Main Effect Scene Structure	Main Effect Task	Interaction Effect Structure × Task
V1	F(1,24)=1.25, p=.28	F(1,24)<0.01, p=.98	F(1,24)=0.09, p=.76
LO	**F(1,24)=9.74, p=.005**	F(1,24)=0.04, p=.85	F(1,24)=0.97, p=.33
EBA	**F(1,24)=7.95, p=.009**	F(1,24)=0.21, p=.65	F(1,24)=2.46, p=.13
OPA	**F(1,24)=27.18, p<.001**	F(1,24)=0.09, p=.77	F(1,24)=0.97, p=.34
PPA	**F(1,24)=48.02, p<.001**	**F(1,24)=6.51, p=.017**	F(1,24)=0.51, p=.48

In all ROIs, scene structure affected univariate responses similarly across the

two tasks, as indexed by no significant interaction effects, all F<2.46, p>0.12. This

pattern of results mirrors the pattern observed in behavior, where scene jumbling

produced comparable effects in the object and scene tasks.

PPA was the only region that additionally showed an effect of task,

F(1,24)=6.51, p=.017, with stronger responses in the scene task compared to the

object task. This suggests an increased importance of computations in higher-level

scene-selective cortex when scene attributes were behaviorally relevant.

Having established that scene structure enhanced cortical responses across

object- and scene-selective cortex, and similarly for both tasks, we next asked how

scene structure contributes to the extraction of object information – both when the

objects are behaviorally relevant and when they are not.

Figure 2. Univariate results. *In all extrastriate regions, but not in V1, we found a*
significant main effect of scene structure: Intact scenes led to significantly stronger
responses than jumbled scenes. This effect was comparable across the two tasks and
most pronounced in scene-selective ROIs. PPA was the only region that additionally
showed a modulation by task, with significantly stronger responses when participants
were categorizing the scenes, compared to when they were categorizing the objects
within them. For illustration purposes, ROI masks are shown on the right hemisphere
of a standard-space template using MRIcroGL (Li et al., 2016); the displayed results
are averaged across ROIs in both hemispheres. Error bars represent standard errors
of the mean.

3.2 Coherent scene structure enhances task-relevant object information in
multi-voxel response patterns
To understand how the coherent spatial structure of the scene impacts cortical object
processing, we performed a cross-correlation multivariate pattern analysis (MVPA).
In this analysis, we correlated the multi-voxel response patterns evoked by objects
embedded in scenes (from the object and scene tasks) with the patterns evoked by
the objects in isolation (from the benchmark localizer) (Figure 3a). This approach
allowed us to quantify how "person-like" or "car-like" the cortical representation of
each of the scenes was, thereby isolating the amount of object information present
in visual cortex. When object information is operationalized in this way, it can be
separated from differences in the scene context (as in the benchmark localizer no

scene context is presented) and task-related differences (as in the benchmark localizer participants perform a different task).

To quantify object information, we computed a cross-correlation measure by subtracting correlations between different categories (e.g., person in isolation and car within a scene) from correlations between the same categories (e.g., person in isolation and person within a scene) (Figure 3a). This measure was computed separately for each the object and scene tasks, the intact and jumbled scenes, and all ROIs.

To test whether multi-voxel response patterns contained any information at all about the object contained in the scenes, we first averaged the cross-correlation measure across all conditions. We then tested whether the average category information was significantly different from zero, separately for each ROI. As expected, people and cars could be reliably discriminated from response patterns in the object-selective LO, $t(24)=7.56$, $p<.001$, and body-selective EBA, $t(24)=8.00$, $p<.001$, but not from response patterns in V1, $t(24)=0.80$, $p=.43$, or scene-selective OPA, $t(24)=0.49$, $p=.63$, and PPA, $t(24)=0.70$, $p=.49$.

Given that we only found robust object information in LO and EBA, we only performed further analyses for these two regions (Figure 3b). Data were again analyzed in a 2×2 ANOVA with factors scene structure (intact vs jumbled) and task (object task vs scene task), separately for LO and EBA.

When analyzing the amount of object information contained in LO response patterns, we found a significant interaction between task and scene structure, $F(1,24)=5.63$, $p=.026$: When participants performed the object task, object information in LO was more pronounced for objects embedded in intact compared to jumbled scenes, $t(24)=2.65$, $p=.014$. This effect was absent when participants performed the scene task, $t(24)=1.22$, $p=.24$. A similar interaction effect was found in the EBA, $F(1,24)=5.19$, $p=.032$: Object information was again enhanced for intact scenes during the object task, $t(24)=2.30$, $p=.030$, but not during the scene task, $t(24)=0.92$, $p=.37$. These results demonstrate that coherent scene structure indeed enhances object representations in visual cortex. However, this enhancement depends on the behavioral relevance of the object: When scene category, rather than object category, was task-relevant, no such enhancement was observed.

Figure 3. Cross-correlation MVPA logic and results. a) *To measure object discriminability, we extracted multi-voxel response patterns for each ROI, separately for objects in isolation (from the benchmark localizer) and objects appearing within the scenes (from the main experiment). We then computed within- and between-category correlations. By subtracting the between-category from the within-category correlations, we obtained an index of category information (Δr).* **b)** *In both LO and EBA, category information was significantly higher for objects that were embedded in intact scenes than for objects embedded in jumbled scenes. However, this was only true when participants performed the object task; when they performed the scene task, no significant difference in object category information was observed when comparing intact and jumbled scenes. For illustration purposes, ROI masks are shown on the right hemisphere of a standard-space template using MRIcroGL (Li et al., 2016); the displayed results are averaged across ROIs in both hemispheres. Error bars represent standard errors of the mean.*

4 Discussion

4.1 Coherent scene structure facilitates task-relevant object processing

In this study, we shed light on neural object processing in situations where the object

is either embedded within a coherent, intact scene or an incoherent, jumbled scene.

Consistent with classical studies (Biederman, 1972; Biederman et al., 1973, 1974),

our participants were more accurate and faster in perceiving intact, compared to

jumbled scenes, both when performing an object categorization task and a scene

categorization task. Consistent with our own recent fMRI work (Kaiser et al., 2020a),

intact scenes yielded stronger neural responses than jumbled scenes across high-

level visual cortex. Importantly, our current results show that scene structure also

matters when it comes to the neural representation of objects within the scene: When

analyzing the amount of object information contained in multi-voxel response

patterns in object and body-selective visual cortex, we found an enhancement of

object information when the objects were embedded within intact scenes, compared

to jumbled scenes. Critically, this enhancement only emerged in the object

categorization task, suggesting that coherent scene structure facilitates the

extraction of object information only when the objects are relevant for current

behavioral goals.

4.2 Interactions between object and scene processing are mediated by scene

structure

Our findings support the view that the scene and object processing pathways are not

functionally separate, but that scene information can aid the extraction of object

information (Brandmann & Peelen, 2017). Theories of contextual facilitation propose

that scene structure is analyzed rapidly, potentially based on coarse low-spatial

frequency information (Bar, 2004; Bar et al., 2006). This idea is consistent with the

observation that an initial representation of scene meaning – the scene's "gist" – can

be extracted from just a single glance (Greene & Oliva, 2009; Oliva & Torralba, 2006,

2007). Contextual facilitation theories argue that detailed object analysis is facilitated

by this more readily available information about scene gist (Bar, 2004; Hochstein &

Ahissar, 2002). Informing object analysis through the analysis of coarse scene
properties may be particularly useful when perception is challenged by the presence
of many distracter items and limited visual exposure. Probing perception with such a
challenging task, our study shows that the cross-facilitation between object and
scene processing is mediated by the scene's structural coherence: When the analysis
of scene gist is disrupted by jumbling the scene, contextual information cannot
amplify object processing in the same way as it can for intact scenes.

The enhanced extraction of object information from the intact scenes suggests
that useful information about scene gist is extracted less efficiently from the jumbled
scenes. Indeed, the rapid analysis of scene gist depends on our priors about typical
scene composition (Csathó et al., 2015; Greene et al., 2015). Neuroimaging studies
suggest that the cortical scene processing network is tuned to these priors (Kaiser et
al., 2020a; Torralbo et al., 2013), and that the early extraction of properties like the
scene's basic-level category depends on the structural coherence of the scene
(Kaiser et al., 2020b). Jumbling is a strong manipulation in the sense that is disrupts
multiple aspects of the scene's spatial coherence at the same time: it disrupts the
spatial positioning of individual pieces of information in visual space (Kaiser et al.,
2018; Mannion, 2015), the positioning of objects relative to each other (Kaiser et al.,
2019; Kaiser & Peelen, 2018), as well as the typical geometry of the scene (Dillon et
al., 2018; Spelke & Lee, 2012). Future research is needed to disentangle these
different factors, and how much they each contribute to the facilitation of object
representation.

Although jumbling is a strong manipulation that conflates multiple factors of
scene structure, it preserves critical characteristics of the objects: First, the objects
remain completely unaltered across the intact and jumbled scenes. Second, the
objects' absolute positions in visual space were matched across the intact and
jumbled scenes. Finally, each object's local visual context remains constant across
the intact and jumbled scenes. These properties allow us to attribute differences in
object representations to facilitates effects from cortical scene analysis: If the visual
brain would not take global scene context into account and would only analyze the
objects in their local visual surroundings, our paradigm should yield comparable
results for structurally coherent, intact scenes and incoherent, jumbled scenes.

4.2 Attention mediates contextual facilitation effects

4.2 Attention mediates contextual facilitation effects

Unlike task-relevant objects, task-irrelevant objects were not processed differently as
a function of scene coherence. This finding shows that contextual facilitation of object
processing is not an automatic process. On the contrary, interactions between the
object and scene processing systems seem to be mediated by attention. This
observation fits well with previous results from studies on object detection in natural
scenes. Compared to task-relevant objects, multi-voxel response patterns in visual
cortex contain far less information about unattended objects (Peelen et al., 2009;
Peelen & Kastner, 2011). Further, MEG decoding results suggest strong differences
in the representation of attended and unattended object categories (Kaiser et al.,
2016): Particularly at early stages of processing, within the first 200ms after stimulus
onset, the category of unattended objects is represented less accurately. Beyond the
visual brain, differences in task demands also affect more widespread activations
across the cortex (Cukur et al., 2013; Harel et al., 2014; Hebart et al., 2018; Nastase
et al., 2017), potentially causing substantial task-related changes in processing
dynamics. One such change may be an alteration of the crosstalk between
representations in different visual domains. Our data indeed suggests that the
exchange of information between the object and scene processing pathways is not
mandatory, but rather constitutes an adaptive mechanism for improving task
performance. Under this view, interactions between the scene and object processing
pathways may be specifically "switched on" when objects are part of current
attentional templates (Battistoni et al., 2017; Peelen & Kastner, 2011). The specific
mechanism underlying this adaptive control of the crosstalk between scene and
object processing needs further investigation.

How does the apparent importance of attention tie in with previous studies that
reported a cross-facilitation between the object and scene-processing systems
(Brandmann & Peelen, 2017, 2019)? While these studies did not use object
categorization tasks, they still explicitly asked participants to attend to the objects
appearing within the scene (either by asking them to memorize them or through one-
back tasks). In our scene categorization task, the situation was entirely different, as
the objects were completely irrelevant for solving the task. In fact, this orthogonality

of object and scene category in our design may have introduced an active
suppression of object information when participants performed the scene
categorization task. Previous studies suggest that task-irrelevant distracter objects
can be suppressed effectively and quickly (Seidl et al., 2012; Hickey et al., 2019).
During the scene task, we indeed found numerically better object representations for
jumbled scenes. This tentative reversal of the facilitation effect could hint at a more
efficient suppression of object information when the object is embedded in a
structurally coherent scene. Although largely speculative at this point, this assertion
could be tested in future experiments that include additional conditions in which the
scene and the objects are similarly task-relevant.
531

4.4 Conclusion

In conclusion, our results show that the object and scene processing pathways can
interact to facilitate the processing of task-relevant object information embedded in
coherent scenes. However, such interactions are not mandatory. They rather seem
to be guided by current behavioral goals. Our findings therefore suggest that the
visual brain adaptively exploits coherent scene context to resolve object perception
in challenging real-world situations.

Acknowledgements

We thank Sina Schwarze for helping with the stimulus collection. D.K. and R.M.C. are

supported by Deutsche Forschungsgemeinschaft (DFG) grants (KA4683/2-1,

CI241/1-1, CI241/3-1). G.H. is supported by a PhD fellowship of the Einstein Center

for Neurosciences Berlin. R.M.C. is supported by a European Research Council

Starting Grant (ERC-2018-StG 803370).

References

Bar M. (2004). Visual objects in context. *Nat Neurosci, 5*, 617-629.

Bar M, Kassam KS, Ghuman AS, Boshyan J, Schmid AM, Dale AM, Hämäläinen MS,
Marinkovic K, Schacter DL, Rosen BR, Halgren E. (2006). Top-down facilitation
of visual recognition. *Proc Natl Acad Sci USA, 103*, 449-454.

Battistoni E, Stein T, Peelen MV. (2017). Preparatory attention in visual cortex. *Ann N
Y Acad Sci, 1396*, 92-107.

Biederman I. (1972). Perceiving real-world scenes. *Science, 177*, 77-80.

Biederman I, Glass AL, Stacy EW. (1973). Searching for objects in real-world scenes.
J Exp Psychol, 97, 22-27.

Biederman I, Rabinowitz JC, Glass AL, Stacy EW. (1974). On the information
extracted from a glance at a scene. *J Exp Psychol, 103*, 597-600.

Brandman T, Peelen MV. (2017). Interaction between scene and object processing
revealed by human fMRI and MEG decoding. *J Neurosci, 37*, 7700-7710.

Brandman T, Peelen MV. (2019). Signposts in the fog: objects facilitate scene
representations in left scene-selective cortex. *J Cogn Neurosci, 31*, 390-400.

Brainard DH. (1997). The psychophysics toolbox. *Spat Vis, 10*, 433-436.

Cauchoix M, Barragan-Jason G, Serre T, Barbeau EJ. (2014). The neural dynamics of
face detection in the wild revealed by MVPA. *J Neurosci, 34*, 846-854.

Csathó Á, van der Linden D, Gács B. (2015). Natural scene recognition with increasing
time-on-task: the role of typicality and global image properties. *Q J Exp
Psychol, 68*, 814-828.

Cukur T, Nishimoto S, Huth AG, Gallant JL. (2013). Attention during natural vision
warps semantic representation across the human brain. *Nat Neurosci 16*, 763-
770.

Dillon MR, Persichetti AS, Spelke ES, Dilks DD. (2018). Places in the brain: bridging
layout and object geometry in scene-selective cortex. *Cereb Cortex, 28*, 2365-
2374.

Greene MR, Botros AP, Beck DM, Fei-Fei L. (2015). What you see is what you expect:
rapid scene understanding benefits from prior experience. *Atten Percept*
Psychophys, 77, 1239-1251.

Greene MR, Oliva A. (2009). Recognition of natural scenes from global properties:
seeing the forest without representing the trees. *Cogn Psychol, 58*, 137-176.

Harel A, Kravitz DJ, Baker CI. (2014). Task context impacts visual object processin
differentially across the cortex. *Proc Natl Acad Sci USA, 111*, 962-971.

Haxby JV, Gobbini IM, Furey ML, Ishai A, Schouten JL, Pietrini P. (2001). Distributed
and overlapping representations of faces and objects in ventral temporal
cortex. *Science, 293*, 2425-2430.

Hebart MN, Bankson BB, Harel A, Baker CI, Cichy RM. (2018). *eLife, 7*, e32816.

Hickey C, Pollicino D, Bertazzoli G, Barbaro L. (2019). Ultrafast object detection in
naturalistic vision relies on ultrafast distractor suppression. *J Cogn Neurosci,*
31, 1563-1572.

Hochstein S, Ahissar M. (2002). View from the top: hierarchies and reverse hierarchies
in the visual system. *Neuron, 36*, 791-804.

Julian JB, Fedorenko E, Webster J, Kanwisher N. (2012). An algorithmic method for
functionally defining regions of interest in the ventral visual pathway.
Neuroimage, 60, 2357-2364.

Kaiser D, Cichy RM. (2018). Typical visual-field locations enhance processing in
object-selective channels of human occipital cortex. *J Neurophysiol, 120*, 848-
853.

Kaiser D, Häberle G, Cichy RM. (2020a). Cortical sensitivity to natural scene structure.
Hum Brain Mapp, 41, 1286-1295.

Kaiser D, Häberle G, Cichy RM. (2020b). Real-world structure facilitates the rapid
emergence of scene category information in visual brain signals. *J*
Neurophysiol, 124, 145-151.

Kaiser D, Oosterhof NN, Peelen MV. (2016). The neural dynamics of attentional
selection in natural scenes. *J Neurosci, 36*, 10522-10528.

Kaiser D, Quek GL, Cichy RM, Peelen MV. (2019). Object vision in a structured world.
Trends Cogn Sci, 23, 672-685.

Kaiser D, Peelen MV. (2018). Transformation from independent to integrative coding
of multi-object arrangements in human visual cortex. *Neuroimage, 169*, 334-
341.

Li FF, VanRullen R, Koch C, Perona P. (2002). Rapid natural scene categorization in
the near absence of attention. *Proc Natl Acad Sci USA, 99*, 9596-9601.

Li X, Morgan PS, Ashburner J, Smith J, Rorden C. (2016). The first step for
neuroimaging data analysis: DICOM to NIfTI conversion. *J Neurosci Methods,*
264, 47-56.

Mannion DJ. (2015). Sensitivity to the visual field origin of natural image patches in
human low-level visual cortex. *PeerJ, 3*, e1038.

Nastase SA, Connolly AC, Oosterhof NN, Halchenko YO, Guntupalli JS, Visconti di
Oleggio Castello M, Gobbini I, Haxby JV. (2017). Attention selectively reshapes
the geometry of distributed semantic representation. *Cereb Cortex, 27*, 4277-
4291.

Oliva A, Torralba A. (2006). Building the gist of a scene: the role of global image
features in recognition. *Prog Brain Res, 155*, 23-36.

Oliva A, Torralba A. (2007). The role of context in object recognition. *Trends Cogn Sci,*
11, 520-527.

Oosterhof NN, Connolly AC, Haxby JV. (2016). CoSMoMVPA: Multi-modal
multivariate pattern analysis of neuroimaging data in Matlab/GNU Octave.
Front Neuroinform, 10, 20.

Peelen MV, Fei-Fei L, Kastner S. (2009). Neural mechanisms of rapid natural scene
categorization in human visual cortex. *Nature, 460*, 94-97.

Peelen MV, Kastner S. (2011). A neural basis for real-world visual search in human
occipitotemporal cortex. *Proc Natl Acad Sci USA, 108*, 12125-12130.

Potter MC. (1975). Meaning in visual search. *Science, 187*, 965-966.

Potter MC. (2012). Recognition and memory for briefly presented scenes. *Front*
Psychol, 3, 32.

Seidl KN, Peelen MV, Kastner S. (2012). Neural evidence for distracter suppression
during visual search in real-world scenes. *J Neurosci, 32*, 11812-11819.

Shahdloo M, Celik E, Cukur T. (2020). Biased competition in semantic representation
during natural visual search. *Neuroimage, 216*, 116383.

Spelke ES, Lee SA. (2012). Core systems of geometry in animal minds. *Philos Trans*
R Soc Lond B Biol Sci, 367, 2784-2793.

Thorpe S, Fize D, Marlot C. (1996). Speed of processing in the human visual system.
Nature, 381, 520-522.

Torralba A, Oliva A, Castelhano MS, Henderson JM. (2006). Contextual guidance of
eye movements and attention in real-world scenes: the role of global features
in object search. *Psychol Rev, 113*, 766-786.

Torralbo A, Walther DB, Chai B, Caddigan E, Fei-Fei L, Beck DM. (2013). Good
exemplars of natural scene categories elicit clearer patterns than bad
exemplars but not greater BOLD activity. *Plos One, 8*, e58594.

VanRullen R, Thorpe SJ. (2001). The time course of visual processing: from early
perception to decision-making. *J Cogn Neurosci, 13*, 454-461.

Võ MLH, Boettcher SEP, Draschkow D. (2019). Reading scenes: How scene grammar
guides attention and aids perception in real-world environments. *Curr Opin*
Psychol, 29, 205-210.

Wang L, Mruczek RE, Arcaro MJ, Kastner S. (2015). Probabilistic maps of visual
topography in human cortex. *Cereb Cortex, 25,* 3911-3931.

Wolfe JM, Võ ML-H, Evans KK, Greene MR. (2011). Visual search in scenes involves
selective and nonselective pathways. *Trends Cogn Sci, 15,* 77-84.