A hierarchy of linguistic predictions during natural language comprehension

Micha Heilbron[1,2] , Kristijan Armeni[1], Jan-Mathijs Schoffelen[1],
Peter Hagoort[1,2], Floris P. de Lange[1]

[1]Donders Institute, Radboud University, Nijmegen, the Netherlands
[2]Max Planck Institute for Psycholinguistics, Nijmegen, the Netherlands
m.heilbron@donders.ru.nl

Abstract

Understanding spoken language requires transforming ambiguous stimulus streams into a hierarchy of increasingly abstract representations, ranging from speech sounds to meaning. It has been suggested that the brain uses predictive computations to guide the interpretation of incoming information. However, the exact role of prediction in language understanding remains unclear, with widespread disagreement about both the ubiquity of prediction, and the level of representation at which predictions unfold. Here, we address both issues by analysing brain recordings of participants listening to audiobooks, and using a state-of-the-art deep neural network (GPT-2) to quantify predictions in a fine-grained, contextual fashion. First, we establish clear evidence for predictive processing, confirming that brain responses to words are modulated by probabilistic predictions. Next, we factorised the model-based predictions into distinct linguistic dimensions, revealing dissociable neural signatures of syntactic, phonemic and semantic predictions. Finally, we show that high-level (word) predictions inform low-level (phoneme) predictions, supporting theories of hierarchical predictive processing. Together, these results underscore the ubiquity of prediction in language processing, and demonstrate that linguistic prediction is not implemented by a single system but occurs throughout the language network, forming a hierarchy of linguistic predictions across all levels of analysis.

INTRODUCTION

Understanding spoken language requires transforming ambiguous stimulus streams into a hierarchy of increasingly abstract representations, ranging from speech sounds to meaning. It is often argued that during this process, the brain relies on prediction to guide the interpretation of incoming information [1, 2]. Such a 'predictive processing' strategy has not only proven effective for artificial systems processing language [3, 4], but has also been found to occur in neural systems in related domains such as perception and motor control and might constitute a canonical neural computation [5, 6].

There is a considerable amount of evidence that appears in line with predictive language processing. For instance, behavioural and brain responses are highly sensitive to violations of linguistic regularities [7–10] and to deviations from linguistic expectations more broadly [11–15]. While such effects are well-documented, two important questions about the role of prediction in language processing remain unresolved [16].

The first question concerns the *ubiquity* of prediction. While some models cast prediction as a routine, integral part of language processing [1, 17–19], others view it as relatively rare, pointing out that apparent widespread prediction effects might instead reflect other processes like semantic integration [20, 21]; or that such prediction effects might be exaggerated by the use of artificial, prediction-encouraging

Figure 1: SCHEMATIC OF EXPERIMENTAL AND ANALYTICAL FRAMEWORK **a)** Top row: in both experiments participants listened to continuous recordings from audiobooks while brain activity was recorded. Bottom row: the texts participants listened to were analysed by a deep neural network (GPT-2) to quantify the contextual probability of each word. A regression-based technique was used to estimate the effects of (different levels of) linguistic unexpectedness on the evoked responses within the continuous recordings. **b)** Datasets analysed: one group-level EEG dataset, and one individual subject source-localised MEG dataset.

experiments [20]. But even among accounts viewing prediction as ubiquitous and important, there remains substantial disagreement regarding the representational status of these predictions: Does linguistic prediction occur primarily at the level of syntax [17, 22–24] or rather at the lexical [18, 25], semantic [26, 27] or the phonemic level [15, 28–31]?

Here, we address both issues, probing the ubiquity and nature of linguistic prediction during natural language understanding. Specifically, we analysed brain recordings from two independent experiments in which participants listened to audiobooks, and use a state-of-the-art deep neural network (GPT-2) to quantify linguistic predictions in a fine-grained, contextual fashion. First, we obtain clear evidence for predictive processing, confirming that brain responses to words are modulated by probabilistic predictions. Next, we investigated at which linguistic level prediction occurs. To this end, we factorised the model-based predictions into distinct linguistic dimensions, revealing dissociable neural signatures of syntactic, phonemic and semantic predictions. Finally, we found that higher-level (word) predictions constrain lower-level (phoneme) predictions, supporting the hierarchical nature of prediction. These results underscore the ubiquity of prediction in language processing, and demonstrate that prediction is not confined to a a single level of abstraction but

occurs throughout the language network, forming a hierarchy of predictions across all levels of analysis, from phonemes to meaning.

RESULTS

We consider data from two independent experiments, in which brain activity was recorded while participants listened to natural speech from audiobooks. The first experiment is part of publicly available dataset [29, 32], and contains 1 hour of electroencephalographic (EEG) recordings in 19 participants. The second experiment collected 9 hours of magneto-encephalographic (MEG) data in three individuals, using individualised head casts that allowed us to localise the neural activity with high precision. While both experiments had a similar setup (see Figure 1), they yield complementary insights, both at the group level and in three individuals.

Neural responses to speech are modulated by probabilistic linguistic predictions

We first tested for evidence for linguistic prediction in general. We reasoned that if the brain is constantly predicting upcoming language, neural responses to words should be sensitive to violations of contextual predictions, yielding 'prediction error' signals which are considered a hallmark of predictive processing [5]. To this end, we used a regression-

Figure 2: NEURAL RESPONSES ARE MODULATED BY PROBABILISTIC PREDICTIONS
a) Model comparison. Cross-validated correlation coefficients for EEG (left) and each MEG participant (right). EEG: dots with connecting lines represent individual participants (averaged over all channels). MEG: bars represent median across runs, bars represent bootstrapped absolute deviance (averaged over language network sources). **b)** EEG: coefficients describing the significant effect of lexical surprise (see Figure S3 for the full topography over time). **c)** Difference in prediction performance for each cortical source (transparency indicates FWE-corrected p-values). Significance levels correspond to P<0.001 (***) in a two-tailed one-sample Student's *t* or Wilcoxon sign rank test.

based deconvolution approach to estimate the effects of prediction error on evoked responses within the continuous recordings. We focus on this event-related, low-frequency evoked response because it connects most directly to earlier influential neural signatures of prediction in language [21, 33, 34].

To quantify linguistic predictions, we analysed the books participants listened to with a state-of-the-art neural language model: GPT-2 [35]. GPT-2 is a large transformer-based model that predicts the next word given the previous words, and is currently among the best publicly-available models of its kind. Note that we do not use GPT-2 as a model of human language processing, but purely as a tool to quantify how expected each word is in context.

To test whether neural responses to words are modulated by contextual predictions, we compared three regression models (see S5). The baseline model formalises the hypothesis that natural, passive language comprehension does not invoke pre-

diction. This model did not include regressors related to contextual predictions, but did include several potentially confounding variables (such as word frequency, semantic integration, and acoustics). The *constrained guessing* model formalised the hypothesis that language processing *sometimes* (in constraining contexts) invokes prediction, and that such predictions are an all-or-none phenomenon – together representing how the notion of prediction was classically used in the psycholinguistic literature [36]. This model included all non-predictive variables from the baseline model, plus, in constraining contexts, a linear estimate of word improbability (since all-or-none predictions result in a linear relationship between word probability and brain responses; see methods for details). Finally, the *probabilistic prediction* model included all confounding regressors from the baseline model, plus for every word a logarithmic estimate of word improbability (i.e. *surprise*). This formalises the hypothesis that the brain constantly

generates *probabilistic predictions*, as proposed by predictive processing accounts of language [1, 34, 37] and of neural processing more broadly [5, 6].

When we compared the ability of these models to predict brain activity using cross-validation, we found that the probabilistic prediction model performed better than both other models (see Figure 2a). The effect was highly consistent, found in virtually all EEG participants (probabilistic vs constrained guessing, $t_{18} = 5.34$, $p = 4.46 \times 10^{-5}$; probabilistic vs baseline, $t_{18} = 6.43$, $p = 4.70 \times 10^{-6}$) and within each MEG participant (probabilistic vs constrained guessing, all $p's < 1.54 \times 10^{-6}$; probabilistic vs baseline, all $p's < 5.17 \times 10^{-12}$).

As the *constrained guessing* model differed from the probabilistic model in two ways – by assuming that predictions are (i) categorical and (ii) limited to constraining contexts – we also considered a control model. Like the constrained guessing model, this extended guessing model included a linear estimate of word probability, but for every word rather than only for constraining contexts. Although this model did not outperform the probabilistic prediction model, it did substantially outperform the constrained model (Fig S5). This demonstrates that the effects of prediction are not limited to constraining contexts, but apply much more broadly – in line with the idea that predictions are ubiquitous and automatic.

Having established that word unexpectedness modulates neural responses, we characterised this effect in space and time. In the MEG dataset, we asked for which neural sources lexical surprise was most important in explaining neural data, by comparing the prediction performance of the baseline model to the predictive model in a spatially resolved manner. This revealed that overall word unexpectedness modulated neural responses throughout the language network (see Fig. 2c). To investigate the temporal dynamics of this effect, we inspected the regression coefficients, which describe how fluctuations in lexical surprise modulate the neural response at different time lags – together forming a modulatoin function also known as the *regression evoked response* [38] or Temporal Response Func-

tion (TRF) [29, 32, 39]. When we compared these across participants in the EEG experiment, cluster-based permutation tests revealed a significant effect ($p = 2 \times 10^{-4}$) based on a posterio-central cluster with a negative polarity between 0.2 and 0.9 seconds (see Figure 2b and S8). This indicates that surprising words lead to a stronger negative deflection of evoked responses, evoked responses, an effect peaking at 400 ms post word onset and strongly reminiscent of the classic N400 [7, 21, 26, 33]. Coefficients for MEG subjects revealed a similar, slow effect at approximately the same latencies (see Fig S4).

Together, these results constitute clear evidence for predictive processing by confirming that brain responses to words are modulated by contextual predictions. These modulations occur throughout the language network, evoke an effect reminiscent of the N400, and are best explained by a probabilistic model of prediction, suggesting that the brain constantly generates such predictions – even during passive listening to natural language.

Linguistic predictions are feature-specific

The results so far revealed modulations of neural responses by *overall* word unexpectedness. What type of linguistic prediction might be driving these effects? Earlier research suggests a range of possibilities, with some proposing that the effect of overall word surprise primarily reflects syntax [17, 22], while others propose that prediction unfolds at the semantic [26, 27], or the phonemic level [15, 28, 29] – or at all levels simultaneously [1].

To evaluate these possibilities, we factorised the aggregate, word-level linguistic predictions from the artificial neural network into distinct linguistic dimensions (Fig 3). This allows us to derive model-based estimates of three feature-specific predictions: the syntactic prediction (defined as the conditional probability distribution over parts-of-speech, given context), semantic prediction (defined as the predicted semantic embedding) and phonemic prediction (i.e. the conditional probability of the next phoneme, given the phonemes within the word so far and the prior context). By comparing these predictions to

Figure 3: PARTITIONING MODEL-DERIVED PREDICTIONS INTO DISTINCT LINGUISTIC DIMENSIONS.
To disentangle syntactic, semantic and phonemic predictions, the lexical predictions from GPT-2 were analysed. For the syntactic prediction, part-of-speech was tagging performed over all potential sentences (e.g. "It made the boy sad to *think*"). To compute the phonemic prediction, each predicted word was decomposed into its constituent phonemes, and the predicted probabilities were used as a contextual prior in a phoneme model (see Fig. 6). For the semantic prediction, a weighted average was computed over the GLoVE embeddings of all predicted words.

the presented words, we derived *feature-specific prediction errors* which quantified not just the extent to which a word is surprising overall, but also in what way: semantically, syntactically or phonemically.

We reasoned that if the brain is generating predictions at a given level (e.g. syntax), then the neural responses should be sensitive to prediction errors specific to this level. Moreover, because these different features are processed by partly different brain areas over different timescales, the prediction errors should be at least partially dissociable. To test this, we formulated a new regression model (Figure S6). This included all variables from the lexical prediction model as nuisance regressors, and added three regressors of interest: syntactic surprise (defined for each word), semantic prediction error (defined for each content word), and phonemic surprise (defined for each word-non-initial phoneme).

Because these regressors were to some degree correlated, we first asked whether, and in which brain area, each of the feature-specific prediction errors explained any unique variance, not explained by the other regressors. In this analysis, we turn to the MEG data because of its spatial specificity. As a control, we first performed the analysis for a predictor with a known source: the acoustics. This

revealed a clear peak around auditory cortex (Fig S7) especially in the right hemisphere. This aligns with prior work [40, 41] and confirms that this approach can localise which areas are especially sensitive to a given regressor. We then tested the three prediction errors, finding that each type of prediction error explained significant unique variance in each individual (Figure 4), except in participant 1 where phonemic surprise did not survive multiple comparisons correction (but see Figure 6c and Discussion). This shows that the brain responds differently to different types of prediction errors, implying that linguistic predictions are feature-specific.

Although we observed considerable variation in lateralisation and exact spatial locations between individuals, the overall pattern of sources aligned well with prior research on the neural circuits for each level. For instance, only for semantic prediction errors we observed a widely distributed set of neural sources – consistent with the fact that the semantic (but not the syntactic or phonological) system is widely distributed [42–44]. Moreover, the temporal areas showing the strongest effect of syntactic surprise are indeed key areas for syntactic processing [43, 45, 46] and for the posterior temporal areas predictive syntax in particular [23, 47–49] – though a

Figure 4: DISSOCIABLE PATTERNS OF EXPLAINED VARIANCE BY SYNTACTIC, SEMANTIC AND PHONEMIC PREDICTIONS. Unique variance explained by each feature-specific prediction error across cortical sources in each MEG participant. In all plots, colour indicates amount of additional variance explained by the predictor; opacity indicates FWE-corrected statistical significance across cross-validation folds. Note that $p < 0.05$ is equivalent to $-\log_{10}(p) > 1.3$.

clear syntactic effect in the inferior frontal gyrus (IFG) was interestingly absent [45]. When we compared the sources of phonemic surprise to those obtained for lexical surprise, we observed a striking overlap in all individuals (see Fig. S7, S4 and S13), suggesting that the phonemic predictions as formalised here mostly relate to predictive (incremental) word recognition at the phoneme level rather than describing phonological or phonotactic predictions *per se*.

Dissociable signatures of syntactic, semantic and phonemic predictions

Having established that syntactic, phonemic and semantic prediction errors independently modulated neural responses in different brain areas, we further investigated the nature of these effects. This was done by inspecting the coefficients (or modulation functions), which describe how fluctuations in a given regressor modulate the response over time. We first turn to the EEG data because there the sample size allows for population-level statistical inference on the coefficients. We fitted the same integrated model (Figure S6) and performed cluster-based permutation tests on the modulation functions. This revealed significant effects for each type of prediction error (Figure 5).

First, syntactic surprise evoked an early, positive deflection ($p = 0.027$) based on a frontal cluster between 200 and 500 ms. This early frontal positivity converges with two recent studies that investigated specifically syntactic prediction using models trained explicitly on syntax [24, 50]. We also observed a late negative deflection for syntactic surprise ($p = 0.025$; Fig. S9), but this was neither in line with earlier findings nor replicated in the MEG data. The semantic prediction error also evoked a positive effect ($p = 9.1 \times 10^{-3}$) but this was based on a much later, spatially distributed cluster between 600 and 1100 ms. Although such a late positivity has been prominently associated with *syntactic* violations [9], there is also a considerable body of work reporting such late positivities for purely semantic anomalies [51–53] which is more in line with the semantic prediction error as quantified here (see Discussion). Notably, we did not find a significant N400-like effect for semantic prediction error – possibly because this

Figure 5: SPATIOTEMPORAL SIGNATURES OF SYNTACTIC, SEMANTIC AND PHONEMIC PREDICTION ERRORS.
Coefficients describing the effects of each prediction-error. EEG (left column): modulation functions averaged across the channels participating for at least one sample in the three main significant clusters (one per predictor). Highlighted area indicates temporal extent of the cluster. Shaded area around waveform indicates bootstrapped standard errors. Stars indicate cluster-level significance; $p < 0.05$ (*) , $p < 0.05$ (**), $p < 0.001$ (***). Insets represent selected channels and distribution of absolute t-values. Note that these plots only visualise the *effects*; for the full topographies of the coefficients and respective statistics, see Fig. S8. MEG (right column): polarity aligned responses averaged across the sources with significant explained variance (Fig. 4) across participants. Shaded area represents absolute deviation. Insets represent topography of absolute value of coefficients averaged across the highlighted period. Note that due to polarity alignment, sign information is to be ignored for the MEG plots. For average coefficients for each source, see Fig. S10; for coefficients of each individual, see Figs. S11–S14.

negative deflection was already explained by the overall lexical surprise, which was included as a nuisance regressor (Figure S10). Finally, the phonemic surprise evoked a negative effect ($p = 3 \times 10^{-4}$) based on an early, distributed cluster between 100 and 500 ms. This effect was similar to the word-level surprise effect (Figure 2C and S10) but occurred earlier. This timecourse corresponds to recent studies using similar regression-based techniques to study (predictive) phoneme processing in natural listening [15, 30, 54].

When we performed the same analysis on the MEG data, we observed striking differences in the exact shape and timing of the modulation func-
tions between individuals (see Figs. S11–S14). While this might partly reflect variance in the coefficients due to inherent correlations between the variables, it clearly also reflects true individual differences, demonstrated by one of the strongest and least correlated regressors (the acoustics) also showing considerable variability (see Figure S14). Overall however, we could recover a temporal pattern of effects similar to the EEG results: phonemic and syntactic surprise modulating early responses, and semantic prediction error modulating later responses – although not as late in the EEG data. This temporal order holds on average (Figs. 5 and S10) and is especially clear within individuals (Figs. S11–S13).

Overall, our results (Figs. 4 and 5) demonstrate that syntactic, phonemic and semantic prediction errors evoke brain responses that are both temporally and spatially dissociable. Specifically, while phonemic and syntactic predictions modulate relatively early neural responses (100-400 ms) in a set of focal temporal (and frontal) areas that are key for syntactic and phonetic/phonemic processing, semantic predictions modulate later responses (>400 ms) across a widely distributed set of areas across the distributed semantic system. These results reveal that linguistic prediction is not implemented by a single system but occurs throughout the speech and language network, forming a hierarchy of linguistic predictions across all levels of analysis.

Phoneme predictions reveal hierarchical inference

Having established that the brain generates linguistic predictions across multiple levels of analysis, we finally asked whether predictions at different levels might interact. One option is that they are encapsulated: Predictions in separate systems might use different information, for instance unfolding over different timescales, rendering them independent. Alternatively, predictions at different levels might inform and constrain each other, effectively converging into a single multilevel prediction – as suggested by theories of hierarchical cortical prediction [5, 55].

One way to adjudicate between these hypotheses is by evaluating different schemes of deriving phoneme predictions. One possibility is that such predictions are only based on information unfolding over short timescales. In this scheme, the predicted probability of the next phoneme is derived from the *cohort* of words that are compatible with the phonemes presented so far, with each candidate word weighted by its overall frequency of occurrence (see Fig. 6A). As such, this scheme proposes a *single-level model*: phoneme predictions are based only on information at the level of within-word phoneme sequences unfolding over short timescales, plus a fixed frequency-based prior (capturing statistical knowledge of word frequencies within a language).

Alternatively, phoneme predictions might not only be based on sequences of phonemes within a word, but also on the longer prior linguistic context. In this case, the probability of the next phoneme would still be derived from the cohort of words compatible with the phonemes presented so far, but now each candidate word is not weighted by its overall frequency but by its *contextual probability* (Fig. 6A). Such a model would be hierarchical, in the sense that predictions are based both – at the first level – on short sequences of phonemes (i.e. of hundreds of milliseconds long), and on a contextual prior which itself is based – at the higher level – on long sequences of words (i.e. of tens of seconds to minutes long).

Here, the first model is more in line with the classic Cohort model of incremental (predictive) word recognition, which suggests that context is only integrated after the selection and activation of lexical candidates [56]. By contrast, the second model is more in line with contemporary theories of hierarchical predictive processing which propose that high-level cortical predictions (spanning larger spatial or temporal scales) inform and shape low-level predictions (spanning finer spatial or temporal scales) [55, 57, 58]. Interestingly, recent studies of phoneme predictions during natural listening have used both the frequency-based single level model [29, 31] and a context-based (hierarchical) model [15]. However, the models have not been explicitly compared to test which model can best account for prediction-related fluctuations in neural responses to phonemes.

To compare these possibilities, we constructed 3 phoneme-level regression models (see Fig. S15), which all only included regressors at the level of phonemes. First, the baseline model only included non-predictive control variables: phoneme onsets, acoustics, word boundaries and uniqueness points. This can be seen as the phoneme-level equivalent of the baseline model in Figs. 2 and S5. The baseline model was compared with two regression models which additionally included phoneme surprise. In one of the regression models, this was calculated using a single-level model (with a fixed, frequency-based prior), in the other regression model it was

Figure 6: EVIDENCE FOR HIERARCHICAL INFERENCE DURING PHONEME PREDICTION.

a) Two models of phoneme prediction during incremental word recognition. Phonemic predictions were computed by grouping candidate words by their identifying next phoneme, and weighting each candidate word by its prior probability. This weight (or prior) could be either based on a word's overall probability of occurrence (i.e. frequency) or on its conditional probability in that context (from GPT-2). Critically, in the frequency-based model, phoneme predictions are based on a single level: short sequences of within words phonemes (hundreds of ms long) plus a fixed prior. By contrast, in the contextual model, predictions are based not just on short sequences of phonemes, but also on a contextual prior which is itself based on long sequences of prior words (up to minutes long), rendering the model hierarchical (see Methods). **b-c)** Model comparison results in EEG (**b**) and all MEG participants (**c**). EEG: dots with connecting lines represent individual participants (averaged over all channels). MEG: bars represent median across runs, error bars represent bootstrapped absolute deviance (averaged over language network sources). Significance levels correspond to P<0.01 (******) or P<0.001 (*******) in a two-tailed paired *t* or Wilcoxon sign rank test.

derived from a hierarchical model (with a dynamic, contextual prior derived from GPT-2). To improve our ability to discriminate between the hierarchical and single-level model, we not only included surprise but also phoneme entropy (calculated with

either model) as a regressor [15].

When we compared the cross-validated predictive performance, we first found that in both datasets the predictive model performed significantly better than the non-predictive baseline (Fig. 6b-c hierarchi-

cal vs baseline, EEG: $t_{18} = 3.80$, $p = 1.31 \times 10^{-3}$; MEG: all $p's < 5.69 \times 10^{-12}$). This replicates the basic evidence for predictive processing but now at the phoneme rather than word level (Figs. 2 and S5). Critically, when we compared the two predictive models, we found that the hierarchical model performed significantly better, both in EEG ($t_{18} = 3.03$, $p = 7.28 \times 10^{-3}$) and MEG (all $p's < 9.44 \times 10^{-4}$). This suggests that neural predictions of phonemes (based on short sequences of within-word speech sounds) are are informed by lexical predictions, effectively incorporating long sequences of prior words as contexts. This is a signature of hierarchical prediction, supporting theories of hierarchical predictive processing.

DISCUSSION

Across two independent data sets, we combined deep neural language modelling with regression-based deconvolution of human electrophysiological (EEG and MEG) recordings to ask if and how evoked responses to speech are modulated by linguistic expectations that arise naturally while listening to a story. Our results demonstrated that evoked responses are modulated by *probabilistic* predictions. We then introduced a novel technique that allowed us to quantify not just how much a linguistic stimulus is surprising, but also at what level – phonemically, syntactically and/or semantically. This revealed dissociable effects, in space and time, of different types of prediction errors: syntactic and phonemic prediction errors modulated early responses in a set of focal, mostly temporal areas, while semantic prediction errors modulated later responses across a widely distributed set of cortical areas. Finally, we found that phonemic prediction error signals were best modelled by a hierarchical model incorporating two levels of context: short sequences of within-word phonemes (hundreds of milliseconds long) and long sequences of prior words (up to minutes long). Together, these results demonstrate that during natural listening, the brain is engaged in prediction across multiple levels of linguistic representation, from speech sounds to meaning. The findings underscore the ubiquity of prediction during language processing, and fit naturally in predictive processing accounts of language [1, 2, 59] and neural computation more broadly [5, 6, 57, 60, 61].

A principal result of this paper is that evoked responses to words are best explained by a predictive processing model: models including unexpectedness performed better than a baseline model with only non-predictive variables like semantic integration difficulty, in line with recent studies aimed specifically at distinguishing prediction from semantic integration [62, 63]. When we further compared different accounts of prediction, responses were best explained by a model casting predictions as *ubiquitous* and *probabilistic*. This supports the probabilistic view as opposed to more classical views of prediction as the all-or-none pre-activation of specific words in certain highly constraining contexts [25, 36]. Consistency of these results notwithstanding, a limitation the model comparison approach (applying to both Figs. 2 and 6) is that it only affords relative conclusions – i.e. one model predicting brain responses *better* than others. These conclusions could be further strengthened by future work assessing not just average performance of models, but also testing for qualitative signatures that are *uniquely characteristic* of certain types of models – thus allowing to not just deem a specific model less likely, but to falsify it [64].

Because our deconvolution analysis focussed on evoked responses, the results can be linked to the rich literature on linguistic violations using traditional ERP methods. This is powerfully illustrated by the modulation function of lexical surprise (Fig. 2b) tightly following the N400 modulation effect, one of the first proposed, most robust and most debated ERP signatures of linguistic prediction [21, 26, 33, 65]. Similarly, the early negativity we found for phonemic surprise and later positivity for semantic prediction error (Fig. 5) align well with N200 and the semantic P600 or PNP effects of phonological mismatch and semantic anomaly respectively [36, 51, 66]. Unlike most ERP studies, we observed these effects in participants listening to natural stimuli – without any

anomalies or violations – not engaged in any task. This critically supports the idea that these responses reflect deviations from *predictions* inherent to the comprehension process – rather than reflecting either detection of linguistic anomalies or expectancy effects introduced by the experiment [20].

While we found several striking correspondences between the modulation functions recovered from the data and classic effects from the ERP literature, there were also some differences. Specifically, for syntactic surprise, we found neither a late positive effect resembling the syntactic P600 [9] nor an early negative effect akin to the ELAN [67]. One potential explanation for this is that our formalisation (part-of-speech surprise) might not fully capture syntactic violations used in ERP studies. Indeed, a recent paper on syntactic prediction using a similar model-based approach found a P600-like effect not for syntactic surprise but for the number of syntactic reinterpretation attempts a word induced [24]. Conversely, the early positive effect of syntactic surprise we found – which replicated other model-based findings, despite using a different formalisation of syntactic surprise [24, 50] – does not have a clear counterpart in the traditional ERP literature. Better understanding such systematic differences between the traditional experimental and model-based approach provides an interesting challenge for future work.

A key innovation of our study is how we computed predictions at different levels (Fig. 3). Earlier model-based papers generally either used only feature-unspecific word unexpectedness [12, 14, 34, 68, 69] or quantified predictions at a single level such as syntax [13, 24, 50, 70], phonemes [15, 29, 30] or semantics [26]. In all cases, predictions at a specific level were based on a separate model that had to be independently trained and often only incorporated linguistic context in a limited way. An advantage our method is that one can derive multiple feature-specific predictions from a single model. This not only allows for studying predictions at each level while statistically controlling for predictions at other levels; it also allows leveraging the power of large pre-trained models like GPT-2 which have a much deeper grasp of linguistic context and would be prohibitively expensive to train independently. However, our method also imposes some limitations. Specifically, different levels of predictions derived from one model are not independent and are based on the same contextual information. So while our method allows to ask *if* the brain is predicting at a given level, you cannot test if predictions at different levels interact – or what kind of information guides prediction – without also creating a separate, domain-specific model. Some domain-specific models also allow for asking more nuanced questions, like which kind of grammar is underlying syntactic predictions [24, 48]. As such, the single-model approach we used is complementary to the separate models approach used earlier. Future work could combine the two, for instance to test if the hierarchical prediction we observed for phonemes applies to all linguistic levels – or whether predictions at some levels (e.g. syntax) might be independent.

In our study, we probed predictions indirectly, via the neural markers of *deviations* from these predictions. An interesting future direction would be to study the pre-stimulus aspects of predictions. Ideally, one would directly decode the prediction itself (e.g. full probability distribution) as is starting to become possible in vision [71, 72]. Doing this in a time-resolved manner for language, however, would likely require better neural recording and decoding techniques than currently available. A more directly feasible way to probe pre-stimulus predictions is via a summary statistic such as prior uncertainty. Because pre-stimulus activity is unlikely to be time-locked to stimulus onset, this might be best done by probing ongoing frequency band-limited activity, such as activity in the alpha/beta band which has been linked to prediction and uncertainty [73–75]. Apart from pre-stimulus prediction, another interesting direction is the informational effects of prediction. Prediction is thought to guide information processing, and different forms of context have been found to enhance low-level representations during reading and listening [76–78] (cf. [79, 80]). Future work could test for such top-down enhancement ef-

fects of predictions during natural comprehension and at different linguistic levels.

In the field of artificial intelligence, the model we used (GPT-2) is the result of recent breakthroughs which lead to large improvements in language models. While these models are only trained to predict words in a context, they then can be applied to – and have improved the state-of-the-art in – a wide range of tasks, ranging from sentiment analysis to text comprehension [35, 81, 82]. The rise of these 'generic models of language' has lead some to use them not just as engineering tools but as potential cognitive models. Some have shown, for instance, that activity patterns of language models can be used as encoders to predict brain responses to language [83–85]; others proposed new mechanistic hypotheses about human language processing based on emergent mechanisms in deep networks [86, 87].

Here, we only used the model's output, so our study does not address whether its inner workings are in any sense 'brain-like'. Critically, however, our results do shed new light on what it means for language processing to be 'brain-like' in the first place. We can now conclude that in the brain, language processing invokes a hierarchy of predictions across representational levels. Recent work suggests that deep language models do develop representational separation, with basic syntactic information being represented early and high-level semantics at later layers [81, 88]. However, whether these models are *predicting* unseen language at each representational level is not clear. Explicitly, they are only trained to predict at the lexical level. Assuming that the predictions we observe in the brain also drive learning (as theories propose), it would be interesting to implement a similar learning scheme in deep networks in which surprise is jointly minimised across representational levels [6, 57]. If such learning is more 'brain-like', this may significantly improve models, which currently still learn orders of magnitude slower than humans do.

Beyond the domain of language, there have been other reports of hierarchies of neural prediction, but these have been limited to artificial, predictive tasks or to restricted representational spans, such as successive stages in the visual system [89–92]. Our results demonstrate that even during passive listening of natural stimuli, the brain is engaged in prediction across disparate levels of abstraction (from speech sounds to meaning) based on timescales separated by three orders of magnitude (hundreds of milliseconds to minutes). These findings provide important evidence for hierarchical predictive processing in cortex. As such, they highlight how language processing in the brain is shaped by a domain-general neurocomputational principle: the prediction of perceptual inputs across multiple levels of abstraction.

METHODS

We analysed EEG and source localised MEG data from two experiments. The EEG data is part of a public dataset that has been published about before [29, 32].

Participants

All participants were native English speakers. In the EEG experiment, 19 subjects (13 male) between 19 and 38 years old participated; in the MEG experiment, 3 subjects participated (2 male) aged 35, 30, and 28. Both experiments were approved by local ethics committees (EEG: ethics committee of the School of Psychology at Trinity College Dublin; MEG: CMO region Arnhem-Nijmegen).

Stimuli and procedure

In both experiments, participants were presented continuous segments of narrative speech extracted from audiobooks. The EEG experiment used a recording of Hemingway's *The Old Man and the Sea*. The MEG experiment used 10 stories from the *The Adventures of Sherlock Holmes* by Arthur Conan Doyle. In total, EEG subjects listened to ~1 hour of speech (containing ~11,000 words and ~35,000 phonemes); MEG subjects listened to ~9 hours of speech (containing ~85,000 words and ~290,000 phonemes).

In the EEG experiment, each participants performed only a single session, which consisted of 20 runs of 180s long, amounting to the first hour of the book. Participants were instructed to maintain fixation and minimise movements but were otherwise not engaged in any task.

In the MEG experiment, each participant performed a total of ten sessions, each ~1 hour long. Each session was subdivided in 6-7 runs of roughly ten minutes, although

the duration varied as breaks only occurred at meaningful moments (making sure, for example, that prominent narrative events were not split across runs). Unlike in the EEG experiment, participants in the MEG dataset participants were asked to listen attentively and had to answer questions in between runs: one multiple choice comprehension question, a question about story appreciation (scale 1-7) and a question about informativeness.

MRI acquisition and headcast construction

To produce the headcast, we needed to obtain accurate images of the participants's scalp surface, which were obtained using structural MRI scans with a 3T MAGNETOM Skyra MR scanner (Siemens AG). We used a fast low angle shot (FAST) sequence with the following image acquisition parameters: slice thickness of 1 mm; field-of-view of 256 $\times$ 256 $\times$ 208 mm along the phase, read, and partition directions respectively; TE/TR = 1.59/4.5 ms.

Data acquisition and pre-processing

The EEG data were originally acquired using a 128-channel (plus two mastoid channels) using an ActiveTwo system (BioSemi) at a rate of 512 Hz, and downsampled to 128 Hz before being distributed as a public dataset. We visually inspected the raw data to identify bad channels, and performed independent component analysis (ICA) to identify and remove blinks; rejected channels were linearly interpolated with nearest neighbour interpolation using MNE-python.

The MEG data were acquired using a 275 axial gradiometer system at 1200 Hz. For the MEG data, preprocessing and source modelling was performed in MATLAB 2018b using fieldtrip [93]. We applied notch filtering (Butterworh IIR) at the bandwidth of 49–51, 99–101, and 149–151 Hz to remove line noise. Artifacts related to muscle contraction and squidjumps were identified and removed using fieldtrip's semi-automatic rejection procedure. The data were downsampled to 150 Hz. To identify and remove eye blink artifacts, ICA was performed using the FastICA algorithm.

For both MEG and EEG analyses, we focus on the slow, evoked response and hence restricted our analysis to low-frequency components. To this end, we filtered the data between 0.5 and 8 Hz using a bidirectional FIR bandpass filter. Restricting the analysis to such a limited range of low frequencies (which are known to best follow the stimulus) is common when using regression ERP or TRF analysis, especially when the regressors are sparse impulses [30, 39,

94, 95]. The particular upper bound of 8 Hz is arbitrary but was based on earlier papers using the same EEG dataset to study how EEG tracks acoustic and linguistic content of speech [69, 77, 95].

Head and source models

The MEG sensors were co-registered to the subjects' anatomical MRIs using position information of three localization coils attached to the headcasts. To create source models, FSL's Brain Extraction Tool was used to strip non-brain tissue [96]. Subject-specific cortical surfaces were reconstructed using Freesurfer, and post-processing (downsampling and surface-based alignment) of the reconstructed cortical surfaces was performed using the Connectome Workbench command-line tools (v 1.1.1). This resulted in cortically-constrained source models with 7,842 source locations per hemisphere. We created single-shell volume conduction models based on the inner surface of the skull to compute the forward projection matrices (leadfields).

Beamformer and parcellation

To estimate the source time series from the MEG data, we used linearly constrained minimum variance (LCMV) beamforming [97], performed separately for each session, using Fieldtrip's `ft_sourceanalysis` routine. To reduce the dimensionality, sources were parcellated, based on a refined version of the Conte69 atlas, which is based on Brodmann's areas. We computed, for each session, parcel-based time series by taking the first principal component of the aggregated time series of the dipoles belonging to the same cortical parcel .

Self-attentional language model

Contextual predictions were quantified using GPT-2 – a large, pre-trained language model [35]. Formally, a language model can be cast as a way of assigning a probability to a sequence of words (or other symbols), $(x_1, x_2, ..., x_n)$. Because of the sequential nature of language, the joint probability, $P(X)$ can, via the chain rule, be factorised as the product of conditional probabilities:

$$P(X) = p(x_1) \times p(x_2 \mid x_1) \times \cdots \times p(x_n \mid x_{n-1}, \ldots, x_1)$$
$$= \prod_{i=1}^{x} p(x_n \mid x_1, \ldots, x_{n-1})$$

(1)

Since the advent of neural language models [98], as opposed to statistical (Markov) models, methods to compute

these conditional probabilities have strongly improved. Improvements have been especially striking in the past two years with the introduction of the *Transformer* [99] architecture, which allows efficient training of very large networks on large, diverse data. This resulted in models that dramatically improved the state-of-the art in language modelling on a range of domains.

GPT-2 [35] is one of these large, transformer-based language models and is currently among the best publcicly released models of English. The architecture of GPT-2 is based on the decoder-only version of the transformer [100]. In a single forward pass, it takes a sequence of tokens $U = (u_1, \dots, u_k)$ and computes a sequence of conditional probabilities, $(p(u_1), p(u_2|u_1), \dots, p(u_k \mid u_1, \dots, u_{k-1}))$. Roughly, the full model (see Figure S1) consists of three steps: first, an embedding step encodes the sequence of symbolic tokens as a sequence of vectors which can be seen as the first hidden state h_o. Then, a stack of transformer blocks, repeated n times, each apply a series of operations resulting in a new set of hidden states h_l, for each block l. Finally, a (log-)softmax layer is applied to compute (log-)probabilities over target tokens. Formally, then, the model can be summarised in three equations:

$$h_0 = UW_e + W_p \tag{2}$$
$$h_l = \text{transformer\_block}\,(h_{l-1})\,\forall i \in [1, n] \tag{3}$$
$$P(u) = \text{softmax}\left(h_n W_e^T\right), \tag{4}$$

where W_e is the token embedding and W_p is the position embedding (see below).

The most important component of the transformer-block is the *masked multi-headed self-attention* (Fig S1). The key operation is self-attention, a seq2seq operation turning a sequence of input vectors $(\mathbf{x}_1, \mathbf{x}_2, \dots \mathbf{x}_k)$ into a sequence of output vectors $(\mathbf{y}_1, \mathbf{y}_2, \dots, \mathbf{y}_k)$. Fundamentally, each output vector $\mathbf{y}_i$ is a weighted average of the input vectors: $\mathbf{y}_i = \sum_{j=1}^k w_{ij}\mathbf{x}_j$. Critically, the weight $w_{i,j}$ is not a parameter but is *derived* from a function over input vectors $\mathbf{x}_i$ and $\mathbf{x}_j$. The Transformer uses (scaled) *dot product attention*, meaning that the function is simply a dot product between the input vectors $\mathbf{x}_i^T\mathbf{x}_j$, passed through a softmax make sure that the weights sum to one, scaled by a constant determined by the dimensionality, $\frac{1}{\sqrt{d_k}}$ (to avoid the dot-products growing too large in magnitude): $w_{ij} = \left(\exp \mathbf{x}_i^T\mathbf{x}_j / \sum_{j=1}^k \exp \mathbf{x}_i^T\mathbf{x}_j\right)\frac{1}{\sqrt{d_k}}$.

In self-attention, then, each input $\mathbf{x}_i$ is used in three ways. First, it is multiplied by the other vectors to derive the weights for its own output, $\mathbf{y}_i$ (as the *query*). Second, it is multiplied by the other vectors to determine the weight for any other output $\mathbf{y}_j$ (as the *key*). Finally, to compute the actual outputs it is used in the weighted sum (as the *value*). Different (learned) linear transformations are applied to the vectors in each of these use cases, resulting in the Query, Key and Value matrices (Q, K, V). Putting this all together, we arrive at the following equation:

$$\text{self\_attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V, \tag{5}$$

where d_k is dimension of the keys/queries. In other words, self_attention simply computes a weighted sum of the values, where the weight of each value is determined by the dot-product similarity of the query with its key. Because the queries, keys and values are linear transformations of the same vectors, the input *attends itself*.

To be used as a language model, two elements need to be added. First, the basic self-attention operation is not sensitive to the order of the vectors: if the order of the input vectors is permuted, the output vectors will be identical (but permuted). To make it position-sensitive, a position embedding W_p is simply added during the embedding step – see Equation 2. Second, to enforce that the model only uses information from one direction (i.e left), a mask is applied to the attention weights (before the softmax) which sets all elements above the diagonal to $-\infty$. This makes the self-attention *masked*.

To give the model more flexibility, each transformer block actually contains multiple instances of the basic self-attention mechanisms from (5). Each instance (each *head*) applies different linear transformations to turn the same input vectors into a different set of Q, K and V matrices, returning a different set of output vectors. The outputs of all heads are concatenated and then reduced to the initial dimensionality with a linear transformation. This makes the self-attention *multi-headed*.

In total, GPT-2 (XL) contains $n = 48$ blocks, with 12 heads each; a dimensionality of $d = 1600$ and a context window of $k = 1024$, yielding a total 1.5×10^9 parameters. We used the PyTorch implementation of GPT-2 provided by HuggingFace's *Transformers* package [101].

Lexical predictions

We passed the raw texts through GPT-2 (Equations 2-4) for each run independently (assuming that listeners' expectations would to some extent 'reset' during the break).

This resulted in a (log-)probability distribution over tokens $P(U)$. Since GPT-2 uses Byte-Pair Encoding, a token can be either punctuation or a word or (for less frequent words) a word-part. How many words actually fit into a context window of length k therefore depends on the text. For words spanning multiple tokens, we computed word probabilities simply as the joint probability of the tokens. For texts longer than the context window of $k = 1024$, we passed the text through the network multiple times using a moving window and then concatenated the predictions. For window-placement, we used the constraint that the windows had an overlap of at least 700 tokens, and that they could not start mid-sentence (ensuring that the first sentence of the window was always well-formed).

As such, for each word w_i we computed $p(w_i|\text{context})$, where 'context' consisted either of all preceding words in the run, or of a sequence of prior words constituting a well-formed context that was at least 700 tokens long.

Syntactic and semantic predictions

Feature-specific predictions were computed from the lexical prediction. To this end, we first truncated the unreliable tail from the distribution using a combination of top-k and nucleus truncation [102]. The nucleus was defined as the "top" k tokens with the highest predicted probability, where k was set dynamically such that the cumulative probability was at least 0.9. To have enough information also for very low entropy cases (where k becomes small), we forced k to be a least 40.

From this truncated distribution, we derived feature-specific predictions by analysing the predicted words. For the syntactic predictions, we performed part of speech tagging on every potential sentence (i.e. the context plus the predicted word) with Spacy [103] to derive the probability distribution over parts-of-speech, from which the syntactic surprise was calculated as the negative log probability of the POS of a word, $-\log(P(\text{POS}_n|\text{context}))$.

For the semantic prediction, we took a weighted average of the glove embeddings of the predicted words to compute the expected vector: $\mathbb{E}[\text{G}(w_n)] = \sum_{i=1}^{k} P(x_i)\,\text{G}(x_i)$, where $\text{G}(w_i)$ is the GloVe embedding [104] for predicted word w_i. From this prediction, we computed the semantic prediction error as the cosine distance between the predicted and observed vector:

$$\text{PE}_{semantic} = 1 - \frac{\mathbb{E}[\text{G}(w_n)]\text{G}(w_n)}{\|\mathbb{E}[\text{G}(w_n)]\|\|\text{G}(w_n)\|} \qquad (6)$$

Phonemic predictions

Phonemic predictions were formalised in the context of incremental word recognition [29, 31]. This process can be cast as probabilistic prediction by assuming that brain is tracking the *cohort* of candidate words consistent with the phonemes so far, each word weighted by its prior probability. We compared two such models that differed only in the prior probability assigned to each word.

The first model was the single-level or frequency-weighted model (Fig. 6), in which prior probability of words was fixed and defined by a word's overall probability of occurrence (i.e. lexical frequency). The probability of a specific phoneme (A), given the prior phonemes within a word, was then calculated using the statistical definition:

$$P(\varphi_t = A \mid \varphi_{1:t-1}) = \frac{f(C_{\varphi_t = A})}{f(C_{\varphi_{1:t-1}})}. \qquad (7)$$

Here, $f(C_{\varphi_t = A})$ denotes the cumulative frequency of all words in the remaining cohort of candidate words if the next phoneme were A, and $f(C_{\varphi_{(1:t-1)}})$ denotes the cumulative frequency of all words in the prior cohort (equivalent to $f(C)$ of all potential continuations). If a certain continuation did not exist and the cohort was empty, $f(C_{\varphi_t = A})$ was assigned a laplacian pseudocount of 1. To efficiently compute (7) for every phoneme, we constructed a statistical phonetic dictionary as a digital tree that combined frequency information from SUBTLEX database and pronunciation from the CMU dictionary [105, 106].

The second model was equivalent to the first model, except that the prior probability of each word was not defined by its overall probability of occurrence, but by its conditional probability in that context (based on GPT-2). This was implemented by constructing a separate phonetic dictionary for every word, in which lexical frequencies were replaced by implied counts derived from the lexical prediction. We truncated the unreliable tail from the distribution and replaced that by a flat tail that assigned each word a pseudocount of 1. This greatly simplifies the problem as it only requires requires to assign implied counts for the top k predicted words in the dynamic nucleus. Since all counts in the tail are 1, the cumulative implied counts of the nucleus is complementary to the the length of the tail, which is simply the difference between the vocabulary size and nucleus size ($V - k$). As such a little algebra reveals:

$$\text{freqs}_n = P_{tr}(w^{(i)}|\text{context})\frac{V - k}{1 - \sum_{j=1}^{k} P(w_j^{(i)}|\text{context})}, \qquad (8)$$

where $P_{tr}(w^{(i)}|\text{context})$ is the trunctated lexical lexical prediction, and $P(w_j^{(i)}|\text{context})$ is predicted probability that word i in the text is word j in the sorted vocabulary.

Although we computed probabilities using the simple statistical definition of probability, these two ways of assigning lexical frequencies are equivalent to two kinds of priors in a Bayesian model. Specifically, in the first model the prior over words is the fixed unconditional word probability, while in the second model the prior is the contextual probability, itself based on a higher level (lexical) prediction. This makes the second computation *hierarchical* because phoneme predictions are based on not just (at the first level) on short sequences of within-word phonemes, but also on a contextual prior which itself (at the second level) is based on long sequences of prior words.

Non-predictive control variables

To ensure we were probing effects of predictions, we had to control for various non-predictive variables: onsets, acoustics, frequency and semantic congruency. We will briefly outline our definitions of each.

For speech, it is known that the cortical responses are sensitive to fluctuations in the envelope – which is specifically driven by rapid increases of the envelope amplitude (or 'acoustic edges') [107, 108]. To capture these fluctuations in a sparse, impulse-based regressor we quantified the amplitude of these edges as the variance of the envelope over each event (e.g. phoneme) following [77]. A second non-predictive variable is frequency. We accounted for frequency as the overall base rate or unconditional probability of a word, defining it similarly to lexical surprise as the unigrams surprise $-\log P(\text{word})$ based on its frequency of occurrence in subtlex [105].

The final non-predictive variable was semantic congruency or integration difficulty. This speaks to the debate wether effects of predictability reflect prediction or rather post-hoc effects arising when integrating a word into the semantic context. This can be illustrated by considering a constraining context ('coffee with milk and ...'). When we contrast a highly expected word ('sugar') and an unexpected word (e.g. 'dog'), the unexpected word is not just less likely, but also semantically incongruous in the prior context. As such, the increased processing cost reflected by effects like N400 increases might not (only) be due to a violated *prediction* but due to difficulty integrating the target word ('dog') in the semantic context ('coffee with milk') [62, 63, 65, 109]. As a proxy for semantic integration difficulty we computed the semantic congruency of a word in its context defined as the cosine dissimilarity (see (6)) between the average semantic vector of the prior context words and the target content word, following [95]. This metric is known to predict N400-like modulations and can hence capture the extent to which such effects can be explained by semantic congruency only [63, 95].

Word-level regression models

The word-level models (see Fig. S2 for graphical representation) captured neural responses to words as a function of word-level variables. The *baseline* model formalised the hypothesis that responses to words were not affected by word unexpectedness but only by the following non-predictive confounds: word onsets, envelope variability (acoustic edges), semantic congruency (integration difficulty) and word frequency.

The *probabilistic prediction* model formalised the hypothesis that predictions were continuous and probabilistic. This model was identical to the baseline model plus the lexical surprise (or negative log probability of a word), for every word. This was based on normative theories of predictive processing which state that the brain response to a stimulus should be proportional to the negative log probability of that stimulus [6].

The *constrained guessing* model formalised the classical psycholinguistic notion of prediction as the all-or-none pre-activation of specific words in specific (highly constraining) contexts [36]. We translated the idea of all-or-none prediction into a regression model using an insight by Smith and Levy which implied that all-or-none predictions result in a linear relationship between word probability and brain responses [11]. The argument follows from two assumptions: (1) all predictions are all-or-none; and (2) incorrect predictions incur a cost, expressed as a prediction error brain response (fixed in size because of assumption 1). For simplicity, we first consider the unconstrained case (i.e. subjects make a prediction for *every* stimulus), and we bracket all other factors affecting brain responses by absolving them into an average brain response, y_{baseline}. As such, the response to any word is either y_{baseline} (if the prediction is correct) or $y_{\text{baseline}} + y_{\text{error}}$ (if it was false). For any individual stimulus, this equation cannot be used (as we don't know what a subject predicted). But if we assume that predictions are approximately correct, then the probability of a given prediction to be incorrect simply becomes $\sim(1 - p)$. As such, *on average*, the response becomes $y_{\text{resp}} = y_{\text{baseline}} + (1 - p)y_{\text{error}}$. In other words, a linear function of word improbability. To extend this

to the constrained case, we only define the improbability regressor for constraining contexts, and add a constant to those events to capture (e.g. suppressive) effects of correct predictions (Fig. S2). To identify 'constraining contexts', we simply took the 10% of words with the lowest prior lexical entropy. The choice of 10% was arbitrary – however, using a slightly more or less stringent definition would not have changed the results because the naive guessing model (which included linear improbability for *every* word) performed so much better (see Fig. S5).

Integrated regression model

For all analyses on feature-specific predictions, we formulated an integrated regression model with both word-level and phoneme-level regressors (Fig. S6). To avoid collinearity between word and phoneme level regressors, phoneme-level regressors were only defined for word-non-initial phonemes, and word-level regressors were define for word-onset. As regressors of interest this model included phonemic surprise, syntactic surprise and semantic prediction error. In principle, we could have also included phoneme and syntactic entropy rather than just surprise (e.g. [15]) – however, these were highly correlated with the respective surprise. Since this was already a complex regression model, including more correlated regressors would have made the coefficients estimates less reliable and hence more difficult to interpret. As such, we did not include both but focussed on surprise because it has the most direct relation to stimulus evoked effect.

Phoneme-level regression models

To compare different accounts of phoneme prediction, we formulated three regression models with only regressors at the individual phoneme level (Fig. S15). In all models, following [29] we used separate regressors for word-initial and word-non-initial phonemes, to account for juncture phonemes being processed differently. The baseline model only included non-predictive factors of word-boundaries, phoneme onsets, envelope variability, and uniqueness points. The two additional models also included phoneme surprise and phoneme entropy from either the hierarchical model or non-hierarchical model. To maximise our ability to dissociate the hierarchical prediction and non-hierarchical prediction, we included both entropy and surprise. Although these metrics are correlated, adding both should add more information to the model-comparison, assuming that there is some effect of entropy [15]. (Note that here, we were only interested in

model comparison, and not in comparing the coefficients, which may become more difficult when including both.)

Time resolved regression

As we were interested in the evoked responses, variables were regressed against EEG data using time-resolved regression, within a regression ERP/F (or impulse TRF) framework [38, 110]. Briefly, this involves using impulse regressors for both constants and covariates defined at event onsets, and then temporally expanding the design matrix such that each predictor column C becomes a series of columns over a range of temporal lags $C_{t_{min}}^{t_{max}} = (C_{t_{min}}, ..., C_{t_{max}})$. For each predictor one thus estimates a series of weights $\beta_{t_{min}}^{t_{max}}$ (Fig 1) which can be understood as the *modulation function* describing how a given regressor modulates the neural response over time, and which corresponds to the *effective* evoked response that would have been obtained in a time-locked ERP/ERF design. Here, used a range between -0.2 and 1.2 seconds. All data and regressors were standardised and coefficients were estimated with ℓ_2-norm regularised (Ridge) regression:

$$\hat{\beta} = \underset{\beta}{\mathrm{argmin}} \|y - X\beta\|_2^2 + \lambda\|\beta\|_2^2, \tag{9}$$

using the scikit learn sparse matrix implementation [111]. In both datasets, models were estimated by concatenating the (time-expanded) design matrix across all runs and sessions. Regularisation was set based on leave-one-run-out R^2 comparison; for inference on the weights in the EEG data this was done across subjects to avoid doing statistics over coefficients with different amounts of shrinkage.

Model comparison

In both datasets, model comparison was based on comparing cross-validated correlation coefficients. Cross-validation was performed in a leave-one-run-out cross-validation scheme, amounting to 19-fold cross-validation in the EEG data and between 63 and 65-fold cross-validation for the MEG data (in some subjects, some runs were discarded due to technical problems).

For the EEG data, models' cross-validated prediction performance was performed across subjects to perform population-level inference. To this end, we reduced the scores into a single n_{subs} dimensional vector by taking the median across folds and the mean across channels. Critically, we did not select any channels but used the average across the scalp. For the MEG data, models were only statistically compared on a within within-subject basis. Because the MEG data was source localised we could

discard sources known to be of no interest (e.g. early visual cortex). To this end, we focussed on the language network, using a rather unconstrained definition encompassing all Brodmann areas in the temporal lobe, plus the temporo-parietal junction, and inferior frontal gyrus and dorsolateral prefrontal cortex; all bilaterally (see Fig. S16).

Statistical testing

All statistical tests were two-tailed and used an alpha of 0.05. For all simple univariate tests performed to compare model-performance within and between subjects, we first verified that the distribution of the data did not violate normality and was outlier free, determined by the D'Agostino and Pearson's test implemented in SciPy and the 1.5 IQR criterion, respectively. If both criteria were met, we used a parametric test (e.g. paired t-test); otherwise, we resorted to a non-parametric alternative (e.g. Wilcoxon sign rank).

In EEG, we performed mass-univariate tests on the coefficients across participants between 0 and 1.2 seconds. This was firstly done using cluster-based permutation tests [112, 113] to identify clustered significant effects as in Fig. 5 (10,000 permutations per test). Because the clustered effects as in Fig. 5 only provide a partial view, we also reported more comprehensive picture of the coefficients across all channels (Figs. S3 and S8); there, we also provide multiple-comparison corrected p-values to indicate statistical consistency of the effects; these were computed using TFCE. In the MEG, multiple comparison correction for comparison of explained variance across cortical areas was done using Treshold Free Cluster Enhancement (TFCE). In both datasets, mass-univariate testing was performed based on one-sample t-tests plus the 'hat' variance adjustment method with $\sigma = 10^{-3}$.

Polarity-alignment

In the source localised MEG data, the coefficients in individuals (e.g. Figs. S11–S14) are symmetric in polarity, with the different sources in a single response having an arbitrary sign due to ambiguity of the source polarity. To harmonise the polarities, and avoid cancellation when visualising the average coefficient, we performed a polarity-alignment procedure. This was based on first performing SVD, $\mathbf{A} = \mathbf{U}\mathbf{\Sigma}\mathbf{V}^\top$, where $\mathbf{A}$ is the $m \times n$ coefficient matrix, with m being the number of sources and n the number of regressors; and then multiplying each row of $\mathbf{A}$ by the sign of the first right singular vector. Because the right singular vectors (columns of $\mathbf{U}$) can be interpreted as the eigen vectors of the source-by-source correlation matrix, this can be thought of as flipping the sign of each source as a function of its polarity with respect to the dominant correlation. This procedure was used for visualisation purposes only (see Fig. S4 and Figs. S11–S14).

Data and code availlability

Data and code to reproduce all results will be made public at the Donders Repository. The full MEG dataset will be made public in a separate resource publication.

REFERENCES

1. Kuperberg, G. R. & Jaeger, T. F. What do we mean by prediction in language comprehension? *Language, cognition and neuroscience* **31,** 32–59. ISSN: 2327-3798 (2016).

2. Kutas, M., DeLong, K. A. & Smith, N. J. in *Predictions in the brain: Using our past to generate a future* 190–207 (Oxford University Press, New York, NY, US, 2011). ISBN: 978-0-19-539551-8. doi:10.1093/acprof:oso/9780195395518.003.0065.

3. Jelinek, F. *Statistical methods for speech recognition* ISBN: 978-0-262-10066-3 (MIT Press, Cambridge, MA, USA, 1998).

4. Graves, A., Mohamed, A.-r. & Hinton, G. *Speech recognition with deep recurrent neural networks* in *2013 IEEE international conference on acoustics, speech and signal processing* (IEEE, 2013), 6645–6649.

5. Keller, G. B. & Mrsic-Flogel, T. D. Predictive Processing: A Canonical Cortical Computation. en. *Neuron* **100,** 424–435. ISSN: 0896-6273 (October 2018).

6. Friston, K. J. A theory of cortical responses. eng. *Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences* **360,** 815–836. ISSN: 0962-8436 (April 2005).

7. Kutas, M. & Hillyard, S. A. Reading senseless sentences: brain potentials reflect semantic incongruity. en. *Science* **207,** 203–205. ISSN: 0036-8075, 1095-9203 (January 1980).

8. Osterhout, L. & Holcomb, P. J. Event-related brain potentials elicited by syntactic anomaly. en. *Journal of Memory and Language* **31,** 785–806. ISSN: 0749-596X (December 1992).

9. Hagoort, P., Brown, C. & Groothusen, J. The syntactic positive shift (SPS) as an ERP measure of syntactic processing. *Language and Cognitive Processes* **8,** 439–483. ISSN: 1464-0732(Electronic),0169-0965(Print) (1993).

10. Faustmann, A., Murdoch, B. E., Finnigan, S. P. & Copland, D. A. Event-Related Brain Potentials Elicited by Semantic and Syntactic Anomalies during Auditory Sentence Processing. *Journal of the American Academy of Audiology* **16,** 708–725 (October 2005).

11. Smith, N. J. & Levy, R. The effect of word predictability on reading time is logarithmic. en. *Cognition* **128,** 302–319. ISSN: 0010-0277 (September 2013).

12. Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P. & van den Bosch, A. Prediction During Natural Language Comprehension. en. *Cerebral Cortex* **26,** 2506–2516. ISSN: 1047-3211 (June 2016).

13. Henderson, J. M., Choi, W., Lowder, M. W. & Ferreira, F. Language structure in the brain: A fixation-related fMRI study of syntactic surprisal in reading. eng. *NeuroImage* **132,** 293–300. ISSN: 1095-9572 (2016).

14. Armeni, K., Willems, R. M., van den Bosch, A. & Schoffelen, J.-M. Frequency-specific brain dynamics related to prediction during language comprehension. *NeuroImage.* ISSN: 1053-8119. doi:10.1016/j.neuroimage.2019.04.083. (Visited on 05/20/2019) (May 2019).

15. Donhauser, P. W. & Baillet, S. Two Distinct Neural Timescales for Predictive Speech Processing. en. *Neuron* **105,** 385–393.e9. ISSN: 0896-6273 (January 2020).

16. Ryskin, R., Levy, R. P. & Fedorenko, E. Do domain-general executive resources play a role in linguistic prediction? Re-evaluation of the evidence and a path forward. en. *Neuropsychologia* **136,** 107258. ISSN: 0028-3932 (January 2020).

17. Levy, R. Expectation-based syntactic comprehension. en. *Cognition* **106,** 1126–1177. ISSN: 0010-0277 (March 2008).

18. Fitz, H. & Chang, F. Language ERPs reflect learning through prediction error propagation. en. *Cognitive Psychology* **111,** 15–52. ISSN: 0010-0285 (June 2019).

19. Dell, G. S. & Chang, F. The P-chain: relating sentence production and its disorders to comprehension and acquisition. eng. *Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences* **369,** 20120394. ISSN: 1471-2970 (2014).

20. Huettig, F. & Mani, N. Is prediction necessary to understand language? Probably not. *Language, Cognition and Neuroscience* **31,** 19–31 (2016).

21. Nieuwland, M. S. *et al.* Large-scale replication study reveals a limit on probabilistic prediction in language comprehension. *eLife* **7** (ed Shinn-Cunningham, B. G.) e33468. ISSN: 2050-084X (April 2018).

22. Hale, J. *A Probabilistic Earley Parser as a Psycholinguistic Model* in *Second Meeting of the North American Chapter of the Association for Computational Linguistics* (2001). <https://www.aclweb.org/anthology/N01-1021> (visited on 08/21/2020).

23. Brennan, J. R., Dyer, C., Kuncoro, A. & Hale, J. T. Localizing syntactic predictions using recurrent neural network grammars. en. *Neuropsychologia,* 107479. ISSN: 0028-3932 (May 2020).

24. Hale, J., Dyer, C., Kuncoro, A. & Brennan, J. *Finding syntax in human encephalography with beam search* in *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)* (Association for Computational Linguistics, Melbourne, Australia, July 2018), 2727–2736. doi:10.18653/v1/P18-1254. <https://www.aclweb.org/anthology/P18-1254> (visited on 07/28/2020).

25. Van Berkum, J. J. A., Brown, C. M., Zwitserlood, P., Kooijman, V. & Hagoort, P. Anticipating upcoming words in discourse: evidence from ERPs and reading times. eng. *Journal of Experimental Psychology. Learning, Memory, and Cognition* **31,** 443–467. ISSN: 0278-7393 (May 2005).

26. Rabovsky, M., Hansen, S. S. & McClelland, J. L. Modelling the N400 brain potential as change in a probabilistic representation of meaning. En. *Nature Human Behaviour* **2,** 693. ISSN: 2397-3374 (September 2018).

27. Federmeier, K. D. Thinking ahead: the role and roots of prediction in language comprehension. eng. *Psychophysiology* **44,** 491–505. ISSN: 0048-5772 (July 2007).

28. Gagnepain, P., Henson, R. N. & Davis, M. H. Temporal Predictive Codes for Spoken Words in Auditory Cortex. English. *Current Biology* **22.** Publisher: Elsevier, 615–621. ISSN: 0960-9822 (April 2012).

29. Brodbeck, C., Hong, L. E. & Simon, J. Z. Rapid Transformation from Auditory to Linguistic Representations of Continuous Speech. eng. *Current biology: CB* **28,** 3976–3983.e5. ISSN: 1879-0445 (December 2018).

30. Di Liberto, G. M., Wong, D., Melnik, G. A. & de Cheveigne, A. Low-frequency cortical responses to natural speech reflect probabilistic phonotactics. en. *NeuroImage* **196,** 237–247. ISSN: 1053-8119 (August 2019).

31. Gwilliams, L., Poeppel, D., Marantz, A. & Linzen, T. *Phonological (un)certainty weights lexical activation* in *Proceedings of the 8th Workshop on Cognitive Modeling and Computational Linguistics (CMCL 2018)* (Association for Computational Linguistics, Salt Lake City, Utah, January 2018), 29–34. doi:10.18653/v1/W18-0104. <https://www.aclweb.org/anthology/W18-0104> (visited on 10/28/2020).

32. Di Liberto, G., O'Sullivan, J. & Lalor, E. Low-Frequency Cortical Entrainment to Speech Reflects Phoneme-Level Processing. en. *Current Biology* **25,** 2457–2465. ISSN: 0960-9822 (October 2015).

33. DeLong, K. A., Urbach, T. P. & Kutas, M. Probabilistic word pre-activation during language comprehension inferred from electrical brain activity. en. *Nature Neuroscience* **8.** Number: 8 Publisher: Nature Publishing Group, 1117–1121. ISSN: 1546-1726 (August 2005).

34. Frank, S. L., Otten, L. J., Galli, G. & Vigliocco, G. The ERP response to the amount of information conveyed by words in sentences. en. *Brain and Language* **140,** 1–11. ISSN: 0093-934X (January 2015).

35. Radford, A. *et al.* Language models are unsupervised multitask learners. *OpenAI Blog* **1,** 8 (2019).

36. Van Petten, C. & Luka, B. J. Prediction during language comprehension: Benefits, costs, and ERP components. en. *International Journal of Psychophysiology. Predictive information processing in the brain: Principles, neural mechanisms and models* **83,** 176–190. ISSN: 0167-8760 (February 2012).

37. Smith, N. J. & Levy, R. *Optimal processing times in reading: a formal model and empirical investigation* in *Proceedings of the Annual Meeting of the Cognitive Science Society* **30.** Issue: 30 (2008).

38. Smith, N. J. & Kutas, M. Regression-based estimation of ERP waveforms: I. The rERP framework. *Psychophysiology* **52,** 157–168. ISSN: 0048-5772 (February 2015).

39. Ding, N. & Simon, J. Z. Emergence of neural encoding of auditory objects while listening to competing speakers. en. *Proceedings of the National Academy of Sciences* **109.** Publisher: National Academy of Sciences Section: Biological Sciences, 11854–11859. ISSN: 0027-8424, 1091-6490 (July 2012).

40. Abrams, D. A., Nicol, T., Zecker, S. & Kraus, N. Right-Hemisphere Auditory Cortex Is Dominant for Coding Syllable Patterns in Speech. *The Journal of Neuroscience* **28,** 3958–3965. ISSN: 0270-6474 (April 2008).

41. Lam, N. H. L., Hulten, A., Hagoort, P. & Schoffelen, J.-M. Robust neuronal oscillatory entrainment to speech displays individual variation in lateralisation. *Language, Cognition and Neuroscience* **33.** Publisher: Routledge _eprint: https://doi.org/10.1080/23273798.2018.1437456, 943–954. ISSN: 2327-3798 (September 2018).

42. Binder, J. R., Desai, R. H., Graves, W. W. & Conant, L. L. Where Is the Semantic System? A Critical Review and Meta-Analysis of 120 Functional Neuroimaging Studies. en. *Cerebral Cortex* **19.** Publisher: Oxford Academic, 2767–2796. ISSN: 1047-3211 (December 2009).

43. Hickok, G. & Poeppel, D. The cortical organization of speech processing. en. *Nature Reviews Neuroscience* **8.** Number: 5 Publisher: Nature Publishing Group, 393–402. ISSN: 1471-0048 (May 2007).

44. Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E. & Gallant, J. L. Natural speech reveals the semantic maps that tile human cerebral cortex. en. *Nature* **532.** Number: 7600 Publisher: Nature Publishing Group, 453–458. ISSN: 1476-4687 (April 2016).

45. Hagoort, P. On Broca, brain, and binding: a new framework. en. *Trends in Cognitive Sciences* **9,** 416–423. ISSN: 1364-6613 (September 2005).

46. Matchin, W. & Hickok, G. The Cortical Organization of Syntax. eng. *Cerebral Cortex (New York, N.Y.: 1991)* **30,** 1481–1498. ISSN: 1460-2199 (2020).

47. Matchin, W., Brodbeck, C., Hammerly, C. & Lau, E. The temporal dynamics of structure and content in sentence comprehension: Evidence from fMRI-constrained MEG. en. *Human Brain Mapping* **40.** _eprint: https://onlinelibrary.wiley.com/doi/pdf/10.1002/hbm.24403, 663–678. ISSN: 1097-0193 (2019).

48. Nelson, M. J. *et al.* Neurophysiological dynamics of phrase-structure building during sentence processing. en. *Proceedings of the National Academy of Sciences* **114.** Publisher: National Academy of Sciences Section: PNAS Plus, E3669–E3678. ISSN: 0027-8424, 1091-6490 (May 2017).

49. Lopopolo, A., Frank, S. L., Bosch, A. v. d. & Willems, R. M. Using stochastic language models (SLM) to map lexical, syntactic, and phonological information processing in the brain. en. *PLOS ONE* **12.** Publisher: Public Library of Science, e0177794. ISSN: 1932-6203 (2017).

50. Brennan, J. R. & Hale, J. T. Hierarchical structure guides rapid linguistic predictions during naturalistic listening. en. *PLOS ONE* **14.** Publisher: Public Library of Science, e0207741. ISSN: 1932-6203 (January 2019).

51. Van Herten, M., Kolk, H. H. J. & Chwilla, D. J. An ERP study of P600 effects elicited by semantic anomalies. eng. *Brain Research. Cognitive Brain Research* **22,** 241–255. ISSN: 0926-6410 (February 2005).

52. Brouwer, H., Fitz, H. & Hoeks, J. Getting real about semantic illusions: rethinking the functional role of the P600 in language compre-

hension. eng. *Brain Research* **1446,** 127–143. ISSN: 1872-6240 (March 2012).

53. Brouwer, H., Crocker, M. W., Venhuizen, N. J. & Hoeks, J. C. J. A Neurocomputational Model of the N400 and the P600 in Language Processing. *Cognitive Science* **41,** 1318–1352. ISSN: 0364-0213 (May 2017).

54. Gwilliams, L., King, J.-R., Marantz, A. & Poeppel, D. *Neural dynamics of phoneme sequencing in real speech jointly encode order and invariant content* en. preprint (Neuroscience, April 2020). doi:10.1101/2020.04.04.025684. <http://biorxiv.org/lookup/doi/10.1101/2020.04.04.025684> (visited on 09/20/2020).

55. Friston, K. Hierarchical Models in the Brain. en. *PLOS Computational Biology* **4.** Publisher: Public Library of Science, e1000211. ISSN: 1553-7358 (November 2008).

56. Marslen-Wilson, W. in *Lexical representation and process* 3–24 (The MIT Press, Cambridge, MA, US, 1989). ISBN: 978-0-262-13240-4.

57. Rao, R. P. N. & Ballard, D. H. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. en. *Nature Neuroscience* **2.** Number: 1 Publisher: Nature Publishing Group, 79–87. ISSN: 1546-1726 (January 1999).

58. Kiebel, S. J., Daunizeau, J. & Friston, K. J. A Hierarchy of Time-Scales and the Brain. en. *PLOS Computational Biology* **4.** Publisher: Public Library of Science, e1000209. ISSN: 1553-7358 (November 2008).

59. Farmer, T. A., Brown, M. & Tanenhaus, M. K. Prediction, explanation, and the role of generative models in language processing. en. *Behavioral and Brain Sciences* **36.** Publisher: Cambridge University Press, 211–212. ISSN: 0140-525X, 1469-1825 (June 2013).

60. Heilbron, M. & Chait, M. Great expectations: Is there evidence for predictive coding in auditory cortex? *Neuroscience.* ISSN: 0306-4522. doi:10.1016/j.neuroscience.2017.07.061 (August 2017).

61. De Lange, F. P., Heilbron, M. & Kok, P. How Do Expectations Shape Perception? *Trends in Cognitive Sciences* **22,** 764–779. ISSN: 1364-6613 (September 2018).

62. Mantegna, F., Hintz, F., Ostarek, M., Alday, P. M. & Huettig, F. Distinguishing integration and prediction accounts of ERP N400 modulations in language processing through experimental design. en. *Neuropsychologia* **134,** 107199. ISSN: 0028-3932 (November 2019).

63. Nieuwland, M. S. *et al.* Dissociable effects of prediction and integration during language comprehension: evidence from a large-scale study using brain potentials. *Philosophical Transactions of the Royal Society B: Biological Sciences* **375.** Publisher: Royal Society, 20180522 (February 2020).

64. Palminteri, S., Wyart, V. & Koechlin, E. The Importance of Falsification in Computational Cognitive Modeling. en. *Trends in Cognitive Sciences* **21,** 425–433. ISSN: 1364-6613 (June 2017).

65. Kutas, M. & Hillyard, S. A. Brain potentials during reading reflect word expectancy and semantic association. *Nature* **307.** Place: United Kingdom Publisher: Nature Publishing Group, 161–163. ISSN: 1476-4687(Electronic),0028-0836(Print) (1984).

66. Van den Brink, D., Brown, C. M. & Hagoort, P. Electrophysiological Evidence for Early Contextual Influences during Spoken-Word Recognition: N200 Versus N400 Effects. *Journal of Cognitive Neuroscience* **13.** Publisher: MIT Press, 967–985. ISSN: 0898-929X (October 2001).

67. Friederici, A. D. Towards a neural basis of auditory sentence processing. en. *Trends in Cognitive Sciences* **6,** 78–84. ISSN: 1364-6613 (February 2002).

68. Weissbart, H., Kandylaki, K. D. & Reichenbach, T. Cortical Tracking of Surprisal during Continuous Speech Comprehension. eng. *Journal of Cognitive Neuroscience* **32,** 155–166. ISSN: 1530-8898 (2020).

69. Heilbron, M., Ehinger, B., Hagoort, P. & de Lange, F. P. Tracking Naturalistic Linguistic Predictions with Deep Neural Language Models. *2019 Conference on Cognitive Computational Neuroscience.* arXiv: 1909.04400. doi:10.32470 / CCN . 2019 . 1096 – 0. (Visited on 09/25/2019) (2019).

70. Shain, C., Blank, I. A., van Schijndel, M., Schuler, W. & Fedorenko, E. fMRI reveals language-specific predictive coding during naturalistic sentence comprehension. en. *Neuropsychologia* **138,** 107307. ISSN: 0028-3932 (February 2020).

71. Walker, E. Y., Cotton, R. J., Ma, W. J. & Tolias, A. S. A neural basis of probabilistic computation in visual cortex. en. *Nature Neuroscience* **23.** Number: 1 Publisher: Nature Publishing Group, 122–129. ISSN: 1546-1726 (January 2020).

72. Ekman, M., Kok, P. & de Lange, F. P. Time-compressed preplay of anticipated events in human primary visual cortex. en. *Nature Communications* **8.** Number: 1 Publisher: Nature Publishing Group, 15276. ISSN: 2041-1723 (May 2017).

73. Spitzer, B. & Haegens, S. Beyond the Status Quo: A Role for Beta Oscillations in Endogenous Content (Re)Activation. en. *eNeuro* **4.** Publisher: Society for Neuroscience Section: Review. ISSN: 2373-2822. doi:10.1523/ ENEURO . 0170 – 17 . 2017. <https://www. eneuro.org/content/4/4/ENEURO.0170– 17.2017> (visited on 11/02/2020) (July 2017).

74. Meyniel, F. Brain dynamics for confidence-weighted learning. en. *PLOS Computational Biology* **16.** Publisher: Public Library of Science, e1007935. ISSN: 1553-7358 (June 2020).

75. Iemi, L. *et al.* Multiple mechanisms link prestimulus neural oscillations to sensory responses. *eLife* **8** (eds Hanslmayr, S. & Colgin, L.) Publisher: eLife Sciences Publications, Ltd, e43620. ISSN: 2050-084X (June 2019).

76. Heilbron, M., Richter, D., Ekman, M., Hagoort, P. & de Lange, F. P. Word contexts enhance the neural representation of individual letters in early visual cortex. en. *Nature Communications* **11,** 321. ISSN: 2041-1723 (January 2020).

77. Broderick, M. P., Anderson, A. J. & Lalor, E. C. Semantic Context Enhances the Early Auditory Encoding of Natural Speech. en. *Journal of Neuroscience,* 0584–19. ISSN: 0270-6474, 1529-2401 (August 2019).

78. Sohoglu, E., Peelle, J. E., Carlyon, R. P. & Davis, M. H. Predictive Top-Down Integration of Prior Knowledge during Speech Perception. en. *Journal of Neuroscience* **32.** Publisher: Society for Neuroscience Section: Articles, 8443–8453. ISSN: 0270-6474, 1529-2401 (June 2012).

79. Sohoglu, E. & Davis, M. H. Rapid computations of spectrotemporal prediction error support perception of degraded speech. *eLife* **9** (eds King, A. J., Kok, P., Kok, P., Press, C. & Lalor, E. C.) Publisher: eLife Sciences Publications, Ltd, e58077. ISSN: 2050-084X (November 2020).

80. Blank, H. & Davis, M. H. Prediction Errors but Not Sharpened Signals Simulate Multivoxel fMRI Patterns during Speech Perception. eng. *PLoS biology* **14,** e1002577. ISSN: 1545-7885 (November 2016).

81. Peters, M. E. *et al. Deep contextualized word representations* in *Proceedings of NAACL-HLT* (2018), 2227–2237.

82. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. *BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding* in *NAACL-HLT (1)* (2019).

83. Caucheteux, C. & King, J.-R. Language processing in brains and deep neural networks: computational convergence and its limits. en. *bioRxiv,* 2020.07.03.186288 (July 2020).

84. Schrimpf, M. *et al.* Artificial Neural Networks Accurately Predict Language Processing in the Brain. en. *bioRxiv,* 2020.06.26.174482 (June 2020).

85. Toneva, M. & Wehbe, L. Interpreting and improving natural-language processing (in machines) with natural language-processing (in the brain). en. *Advances in Neural Information Processing Systems* **32,** 14954–14964 (2019).

86. Lakretz, Y. *et al. The emergence of number and syntax units in LSTM language models* in *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)* (Association for Computational Linguistics, Minneapolis, Minnesota, June 2019), 11–20. doi:10.18653/v1/N19-1002. <https://www.aclweb.org/anthology/N19-1002> (visited on 11/11/2020).

87. Lakretz, Y. *et al.* Exploring Processing of Nested Dependencies in Neural-Network Language Models and Humans. *arXiv:2006.11098 [cs].* arXiv: 2006.11098. <http://arxiv.org/abs/2006.11098> (visited on 11/12/2020) (June 2020).

88. Tenney, I., Das, D. & Pavlick, E. *BERT Rediscovers the Classical NLP Pipeline* in *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics* (Association for Computational Linguistics, Florence, Italy, July 2019), 4593–4601. doi:10.18653/v1/P19-1452. <https://www.aclweb.org/anthology/P19-1452> (visited on 11/12/2020).

89. Issa, E. B., Cadieu, C. F. & DiCarlo, J. J. Neural dynamics at successive stages of the ventral visual stream are consistent with hierarchical error signals. *eLife* **7** (eds Connor, E., Marder, E. & Connor, E.) Publisher: eLife Sciences Publications, Ltd, e42870. ISSN: 2050-084X (November 2018).

90. Schwiedrzik, C. M. & Freiwald, W. A. High-Level Prediction Signals in a Low-Level Area of the Macaque Face-Processing Hierarchy. eng. *Neuron* **96,** 89–97.e4. ISSN: 1097-4199 (September 2017).

91. Wacongne, C. *et al.* Evidence for a hierarchy of predictions and prediction errors in human cortex. eng. *Proceedings of the National Academy of Sciences of the United States of America* **108,** 20754–20759. ISSN: 1091-6490 (December 2011).

92. Bastos, A. M., Lundqvist, M., Waite, A. S., Kopell, N. & Miller, E. K. Layer and rhythm specificity for predictive routing. en. *bioRxiv.* Publisher: Cold Spring Harbor Laboratory Section: New Results, 2020.01.27.921783 (January 2020).

93. Oostenveld, R., Fries, P., Maris, E. & Schoffelen, J.-M. FieldTrip: Open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data. eng. *Computational Intelligence and Neuroscience* **2011,** 156869. ISSN: 1687-5273 (2011).

94. O'Sullivan, J. A., Shamma, S. A. & Lalor, E. C. Evidence for Neural Computations of Temporal Coherence in an Auditory Scene and Their Enhancement during Active Listening. en. *Journal of Neuroscience* **35.** Publisher: Society for Neuroscience Section: Articles, 7256–7263. ISSN: 0270-6474, 1529-2401 (May 2015).

95. Broderick, M. P., Anderson, A. J., Di Liberto, G. M., Crosse, M. J. & Lalor, E. C. Electrophysiological correlates of semantic dissimilarity reflect the comprehension of natural, narrative speech. *Current Biology* **28,** 803–809 (2018).

96. Smith, S. M. *et al.* Advances in functional and structural MR image analysis and implementation as FSL. en. *NeuroImage. Mathematics in Brain Imaging* **23,** S208–S219. ISSN: 1053-8119 (January 2004).

97. Van Veen, B. D., van Drongelen, W., Yuchtman, M. & Suzuki, A. Localization of brain electrical activity via linearly constrained minimum variance spatial filtering. eng. *IEEE transactions on bio-medical engineering* **44,** 867–880. ISSN: 0018-9294 (September 1997).

98. Bengio, Y., Ducharme, R., Vincent, P. & Jauvin, C. A neural probabilistic language model. *Journal of machine learning research* **3,** 1137–1155 (2003).

99. Vaswani, A. *et al. Attention is all you need* in *Advances in neural information processing systems* (2017), 5998–6008.

100. Liu, P. J. *et al. Generating Wikipedia by Summarizing Long Sequences* in *International Conference on Learning Representations* (2018).

101. Wolf, T. *et al.* HuggingFace's Transformers: State-of-the-art Natural Language Processing. *arXiv:1910.03771 [cs].* <http://arxiv.org/abs/1910.03771> (visited on 07/30/2020) (July 2020).

102. Holtzman, A., Buys, J., Du, L., Forbes, M. & Choi, Y. *The Curious Case of Neural Text Degeneration* in *International Conference on Learning Representations (ICLR)* (2019).

103. Honnibal, M. & Montani, I. spacy 2: Natural language understanding with bloom embeddings, convolutional neural networks and incremental parsing. *To appear* **7** (2017).

104. Pennington, J., Socher, R. & Manning, C. D. *Glove: Global vectors for word representation* in *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)* (2014), 1532–1543.

105. Brysbaert, M. & New, B. Moving beyond Kucera and Francis: A critical evaluation of current word frequency norms and the introduction of a new and improved word frequency measure for American English. en. *Behavior Research Methods* **41,** 977–990. ISSN: 1554-3528 (November 2009).

106. Weide, R. *The CMU pronunciation dictionary* (Carnegie Mellon University Pittsburgh, PA, 1998).

107. Oganian, Y. & Chang, E. F. A speech envelope landmark for syllable encoding in human superior temporal gyrus. en. *Science Advances* **5.** Publisher: American Association for the Advancement of Science Section: Research Article, eaay6279. ISSN: 2375-2548 (November 2019).

108. Daube, C., Ince, R. A. A. & Gross, J. Simple Acoustic Features Can Explain Phoneme-Based Predictions of Cortical Responses to Speech. en. *Current Biology* **29,** 1924–1937.e9. ISSN: 0960-9822 (June 2019).

109. Brown, C. & Hagoort, P. The Processing Nature of the N400: Evidence from Masked Priming. *Journal of Cognitive Neuroscience* **5.** Publisher: MIT Press, 34–44. ISSN: 0898-929X (January 1993).

110. Lalor, E. C., Pearlmutter, B. A., Reilly, R. B., McDarby, G. & Foxe, J. J. The VESPA: A method for the rapid estimation of a visual evoked potential. en. *NeuroImage* **32,** 1549–1561. ISSN: 1053-8119 (October 2006).

111. Pedregosa, F. *et al.* Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research* **12,** 2825–2830. ISSN: ISSN 1533-7928 (2011).

112. Gramfort, A. *et al.* MNE software for processing MEG and EEG data. en. *NeuroImage* **86,** 446–460. ISSN: 1053-8119 (February 2014).

113. Maris, E. & Oostenveld, R. Nonparametric statistical testing of EEG- and MEG-data. en. *Journal of Neuroscience Methods* **164,** 177–190. ISSN: 0165-0270 (August 2007).

114. Radford, A., Narasimhan, K., Salimans, T. & Sutskever, I. *Improving language understanding by generative pre-training* (2018).

Supplementary materials

Figure S1 – GPT-2 ARCHITECTURE. Note that this panel is a re-rendered version of the original GPT schematic from [114], slightly modifyied and re-arranged to match the architecture of GPT-2. For more details on the overall architecture and on the critical operation of self-attention, see *Methods*. In this graphic, Layer Norm refers to layer normalisation as described by Ba et al. Not visualised here is the initial tokenisation, mapping a sequence of characters into tokens.

Figure S2 – WORD-LEVEL REGRESSION MODELS. Schematic of the main models plus the control model of the initial model comparison to test for predictive processing at the word level. Because we use a regression ERP/ERF scheme [38], aimed at capturing (modulations of) the evoked response to discrete events like words or phonemes, all regressors are modelled as impulses (see *Methods*).

Figure S3 – FULL EEG TOPOGRAPHIES OF THE EFFECTS OF LEXICAL SURPRISE These topographies show the average t-statistics of the coefficients (upper row) and respective FWE-corrected significance (lower row) of the lexical surprise regressor from the *probabilistic prediction* model (Fig. S2). As such, while Fig. 2b shows the coefficients averaged over channels participating in the cluster (thereby only visualising *the effect*) these topographies visualise the results comprehensively across all channels over time.

Figure S4 – Coefficients for lexical surprise from the lexical model (Figure S2) Left column: timecourses of the coefficients at each MEG source-localised parcel for lexical surprise for all MEG participants, and the polarity-aligned average across them. Right column: Absolute value of the coefficients averaged across the highlighted period plotted across the brain.

Figure S5 – MODEL COMPARISON RESULTS ACROSS ALL CHANNELS (EEG) AND THE FULL LANGUAGE NETWORK (MEG). Same as in Fig. 2a, but now including the 'naive guessing' control model. Like the constrained guessing model, this model included a linear estimate of word probability, but defined for every word rather than only for constraining contexts. This model was introduced to identify which of the two differences between the *probabilistic prediction* and *constrained guessing* model – i.e. assuming that predictions are (i) categorical vs. probabilistic and (ii) occasional vs. continuous – made the largest difference in model performance. As can be seen, the *naive guessing* model performed considerably better than the *constrained guessing* model, but consistently worse than the *probabilistic prediction* model. This clearly shows that the modulatory effect of unexpectedness is not limited to only highly constraining contexts, but that that it applies much more generally – in line with the notion of continuous prediction.

Strictly speaking, the naive guessing model formalises the hypothesis that the brain 'naively' makes *all-or-none* guesses about *every* upcoming word. Given that this hypothesis is a-priori so implausible, it may seem surprising that the model still performs comparably well. However, we should note that the probabilistic prediction regressor (*surprise*) and the categorical prediction regressor (linear (im)probability) are highly correlated (~0.7) because one is a monotonic function of the other. Therefore, we suggest the results are better interpreted the other way around: the fact that – despite being so correlated – the log-probability is consistently a better linear predictor of neural responses than the linear probability clearly supports predictive processing theories, which postulate that the neural response to a stimulus should be proportional to negative log-probability of that stimulus.

Integrated model

word onset (word-initial phoneme)

syntactic surprise

envelope variance (acoustic edges of initial phoneme)

lexical surprise

unigram surprise (lexical frequency)

content word

semantic prediction error

semantic incongruency

phoneme onset (word-non-initial phonemes)

phoneme surprise

envelope variance (around word-non-initial phoneme)

uniqueness point

Figure S6 – Regressors of the integrated feature-specific model. Same as Fig. S5, but for the integrated feature-specific regression model. The three regressors of interest – syntactic surprise, semantic prediction error and phonemic surprise – are coloured, all control regressors are in black. Following the regression ERP/ERF scheme [38], aimed at capturing (modulations of) the evoked response to discrete events like words or phonemes, all regressors are modelled as impulses (see *Methods*). To avoid collinearity between word an and phoneme regressors, phoneme regressors (both events and covariates) are restricted to all non-initial phonemes.

Figure S7 – Unique explained variance for five regressors across the brain.
Same as Fig. 4, but including 2 control regressors (lexical surprise and acoustic variance) for comparison. Colours indicate amount of additional variance explained by each regressor; opacity indicates the FWE-corrected statitsical significance (across cross-validation folds). Note that $p < 0.05$ is equivalent to $-\log_{10}(p) > 1.3$.

Figure S8 – Full topographies of the coefficients and significance of feature-specific prediction errors For each feature-specific prediction error regressor, the topographies show the t-statistics of the coefficients (upper row) and the respective TFCE-corrected significance (lower row). So while Fig. 5 only shows the coefficients averaged over channels participating in the cluster (thereby only visualising *the effect*) these topographies visualise the results comprehensively across all channels, over time.

Figure S9 – Significant effects of syntactic surprise in the EEG data. Two significant effects were observed in the modulation functions for syntactic surprise: an early positive effect with a frontal topography (upper panel) and a later negative effect based on a distributed cluster (lower panel). The early effect tightly replicates recent model-based studies on EEG effects of syntactic surprise, and was also found in the MEG data. By contrast, the late effect of syntactic surprise is not in line with any earlier study (note that it is negative unlike the syntactic P600) and importantly was not replicated in the MEG data. Therefore we only consider the early effect a 'main' effect of syntactic surprise (visualised in the main Fig. 5) and we advice to refrain from interpreting the late effect before it is independently replicated.

Figure S10 – Coefficients for each prediction error, plus two control variables.
EEG (left column): coefficient modulation function averaged across the channels participating for at least one sample in the significant clusters. Highlighted area indicates temporal extent of the cluster. Shaded area around waveform indicates bootstrapped standard errors. Stars indicate cluster-level significance; $p < 0.05$ (*) , $p < 0.05$ (**), $p < 0.001$ (***). Insets represent channels assigned to the cluster (white dots) and the distribution of absolute values of t-statistics. MEG (right column): polarity aligned responses averaged across participants for all sources (same as in Fig. 5 but without averaging over sources, and including two control variables). Insets represent topography of absolute value of coefficients averaged across the highlighted period. Note that due to polarity alignment, sign information is to be ignored for the MEG plots.

Figure S11 – Coefficients for syntactic surprise from the integrated model (Figure S6)
Lef column: coefficients for each source for each individual in the MEG experiment, and the polarity-aligned average across participants. Right column: absolute value of the coefficients across the brain, averaged across the highlighted time-period.

Figure S12 – Coefficients for semantic prediction error from the integrated model (Figure S6) Lef column: coefficients for each source for each individual in the MEG experiment, and the polarity-aligned average across participants. Right column: absolute value of the coefficients across the brain, averaged across the highlighted time-period.

Figure S13 – COEFFICIENTS FOR PHONEMIC SURPRISE FROM THE INTEGRATED MODEL (FIGURE S6)
Lef column: coefficients for each source for each individual in the MEG experiment, and the polarity-aligned average across participants. Right column: absolute value of the coefficients across the brain, averaged across the highlighted time-period..

Figure S14 – COEFFICIENTS FOR ENVELOPE VARIABILITY FROM THE INTEGRATED MODEL (FIGURE S6)
Lef column: coefficients for each source for each individual in the MEG experiment, and the polarity-aligned average across participants. Right column: absolute value of the coefficients across the brain, averaged across the highlighted time-period.

phoneme onset (word initial; word-non-initial)

phoneme surprise

phoneme entropy

envelope variance

uniqueness point

Figure S15 – REGRESSORS OF THE PHONEME MODEL. As indicated by the different colours, both the constants and covariates were modelled separately for word-initial and word-non-initial phonemes.

Figure S16 – LANGUAGE NETWORK DEFINITION The language network was defined as temporal cortex plus temporo-parietal junction, and IFG and dorsolateral prefrontal cortex; all bilaterally. In terms of Brodmann areas this corresponded to 20, 21, 22, 38, 39, 40, 41, 42, 44, 45, 46 and 47, amounting to a total of 100 out of 370 cortical parcels.