Automated Machine Learning for High-Throughput Image-Based Plant Phenotyping

Joshua C.O. Koh[1], German Spangenberg[2,3], Surya Kant[1,4*]

[1] Agriculture Victoria, Grains Innovation Park, 110 Natimuk Rd, Horsham, Victoria 3400, Australia

[2] Agriculture Victoria, AgriBio, Centre for AgriBioscience, 5 Ring Road, Bundoora, Victoria 3083,
Australia

[3] School of Applied Systems Biology, La Trobe University, Bundoora, Victoria 3083, Australia

[4] Centre for Agricultural Innovation, School of Agriculture and Food, Faculty of Veterinary and
Agricultural Sciences, The University of Melbourne, Victoria 3010, Australia

8
9   *** Correspondence:**
10   Surya Kant
11   Surya.kant@agriculture.vic.gov.au
12

Keywords: machine learning, deep learning, AutoML, UAV, wheat lodging, high-throughput
phenotyping, NAS.

Abstract

Automated machine learning (AutoML) has been heralded as the next wave in artificial intelligence
with its promise to deliver high performance end-to-end machine learning pipelines with minimal
effort from the user. AutoML with neural architecture search which searches for the best neural
network architectures in deep learning has delivered state-of-the-art performance in computer vision
tasks such as image classification and object detection. Using wheat lodging assessment with UAV
imagery as an example, we compared the performance of an open-source AutoML framework,
AutoKeras in image classification and regression tasks to transfer learning using modern
convolutional neural network (CNN) architectures pretrained on the ImageNet dataset. For image
classification, transfer learning with Xception and DenseNet-201 achieved best classification
accuracy of 93.2%, whereas Autokeras had 92.4% accuracy. For image regression, transfer learning
with DenseNet-201 had the best performance (R^2=0.8303, RMSE=9.55, MAE=7.03,
MAPE=12.54%), followed closely by AutoKeras (R^2=0.8273, RMSE=10.65, MAE=8.24,
MAPE=13.87%). Interestingly, in both tasks, AutoKeras generated compact CNN models with up to
40-fold faster inference times compared to the pretrained CNNs. The merits and drawbacks of
AutoML compared to transfer learning for image-based plant phenotyping are discussed.

1   Introduction

High-throughput plant phenotyping (HTP) plays a crucial role in meeting the increasing demand for
large-scale plant evaluation in breeding trials and crop management systems (Mir, Reynolds, Pinto,
Khan, & Bhat, 2019; Ninomiya, Baret, & Cheng, 2019; Tardieu, Cabrera-Bosquet, Pridmore, &
Bennett, 2017). Concurrent with the development of various ground-based and aerial (e.g. unmanned
aerial vehicle, UAV) HTP systems is the rise in use of imaging sensors for phenotyping purposes.
Sensors for color (RGB), thermal, spectral (multi- and hyperspectral) and 3D (e.g. LiDAR) imaging

have been applied extensively for phenotyping applications encompassing plant morphology, physiology, development and postharvest quality (Jiang & Li, 2020; Mir et al., 2019). Consequently, the meteoric rise in big image data arising from HTP systems necessitates the development of efficient image processing and analytical pipelines. Conventional image analysis pipelines typically involve computer vision tasks (e.g. wheat head counting using object detection) which are addressed through the development of signal processing and/or machine learning (ML) algorithms. However, these algorithms are sensitive to image quality (e.g. illumination, sharpness, distortion) variations and do not tend to generalize well across datasets with different imaging conditions (Jiang & Li, 2020). Although traditional ML approaches have to some degree improved upon algorithm generalization, most of them still fall short of the current phenotyping demands and require significant expert guidance in designing features that are invariant to imaging environments. To this end, deep learning (DL), a subset of ML has emerged in recent years as the leading answer to meeting these challenges. One key benefit of DL is that features are automatically learned from the input data, thereby negating the need for laborious manual feature extraction and allow well-generalized models to be trained using datasets from diverse imaging environments. A common DL architecture is deep convolutional neural networks (CNNs) which have delivered state-of-the-art (SOTA) performance for computer vision tasks such as image classification/regression, object detection and image segmentation (Khan, Sohail, Zahoora, & Qureshi, 2020; Minaee et al., 2020; Wu, Sahoo, & Hoi, 2020). The progress of transfer learning, a technique which allows the use of pre-trained SOTA CNNs as base models in DL and the availability of public DL libraries have contributed to the exponential adoption of DL in plant phenotyping. Deep CNN approaches for image-based plant phenotyping have been applied for plant stress evaluation, plant development characterization and crop postharvest quality assessment (Chandra, Desai, Guo, & Balasubramanian, 2020; Jiang & Li, 2020; Watt et al., 2020). However, not all modern CNN solutions can be readily implemented for plant phenotyping applications and adoption will require extra efforts which may be technically challenging (Jiang & Li, 2020). In addition, the process of building a high-performance DL network for a specific task is time-consuming, resource expensive and relies heavily on human expertise through a trial-and-error process (Jiang & Li, 2020; Khan et al., 2020).

Following the exponential growth of computing power and availability of cloud computing resources in recent years, automated machine learning (AutoML) has received tremendous attention in both industry and academia. AutoML provides an attractive alternative to the manual ML practice as it promises to deliver high-performance end-to-end ML pipelines covering data preparation (cleaning and preprocessing), feature engineering (extraction, selection and construction), model generation (selection and hyperparameter tuning) and model evaluation requiring minimal effort or intervention from the user (X. He, Zhao, & Chu, 2019; Truong et al., 2019; Zoller & Huber, 2019). AutoML services have become a standard offering in many technology companies, for example Cloud ML by Google and SageMaker by Amazon. Early work by Zoph et al. (Zoph & Le, 2016) highlighted the potential of AutoML in which a recurrent network was trained with reinforcement learning to automatically search for the best performing architecture. Since then, research interest in AutoML has exploded, with a primary focus on neural architecture search (NAS) which seeks to construct well-performing neural architectures through the selection and combination of various basic modules from a predefined search space (Elsken, Metzen, & Hutter, 2019; X. He et al., 2019; Wistuba, Rawat, & Pedapati, 2019). NAS algorithms can be categorized based on three dimensions: the search space which defines the type of model that can be designed, the search strategy used to explore the search space and the performance estimation strategy which evaluates the performance of possible models from its design (Elsken et al., 2019; Wistuba et al., 2019). NAS-generated models have achieved SOTA performance and outperformed manually designed architectures on computer vision tasks

87   such as image classification (Tan & Le, 2019), object detection (Wang et al., 2019) and semantic
88   segmentation (Weng, Zhou, Li, & Qiu, 2019).
89
However, despite AutoML showing great promise for computer vision tasks, to the best of our
knowledge, no study has used AutoML for image-based plant phenotyping. To address this gap in
knowledge, we examined the application of AutoML for image-based plant phenotyping using wheat
lodging assessment with UAV imagery as an example. The performance of an open-source AutoML
system, AutoKeras was compared to transfer learning using pretrained CNN architectures on image
classification and image regression tasks. For image classification, plot images were classified as
either non-lodged or lodged; for image regression, lodged plot images were used as inputs to predict
lodging scores. The merits and drawbacks of AutoML compared to transfer learning for image-based
plant phenotyping are discussed.
99

2   Materials and Methods

2.1   Field Experiment

A wheat breeding experiment was conducted at Agriculture Victoria, Horsham, Australia during the
winter-spring cropping season of 2018 (Lat:$36^o44'35.21''$S Lon:$142^o6'18.01''$E) (Figure 1). Seeds
were sown to a planting density of 150 plants/m^2 in individual plots measuring 5 m long and 1 m
wide (5 m^2), with a total of 1,248 plots. Severe wind events toward the end of the cropping season
(30^{th} November – 9^{th} December) resulted in significant lodging of wheat plots across the experiment.
Ground truth labels for "lodged" and "non-lodged" were provided by an experienced field technician
and a plant scientist.
109

2.2   Image Acquisition and Processing

High resolution aerial imaging of wheat plots with different lodging grades was performed on 11^{th}
December 2018. Aerial imagery was acquired on a DJI Matrice M600 Pro (Shenzhen DJI Sciences
and Technologies Ltd., China) UAV with a Sony A7RIII RGB camera (35.9 mm x 24.0 mm sensor
size, 42.4 megapixels resolution) mounted on a DJI Ronin MX gimbal. Flight planning and automatic
mission control was performed using DJI's iOS application Ground Station Pro (GS Pro). The
camera was equipped with a 55 mm fixed focal length lens and set to 1 s interval shooting with JPEG
format in shutter priority mode. Images were geotagged using a GeoSnap Express system (Field of
View, USA). The flight mission was performed at an altitude of 45 m with front and side overlap of
75% under clear sky conditions. Seven black and white checkered square panels (38 cm x 38 cm)
were distributed in the field experiment to serve as ground control points (GCPs) for accurate geo-
positioning of images (Figure 1). A real-time kinematic global positioning system (RTK-GPS)
receiver, EMLID Reach RS (https://emlid.com) was used to record the centre of each panel with < 1
centimeter accuracy.
124
Images were imported into Pix4Dmapper version 4.4.12 (Pix4D, Switzerland) to generate an
orthomosaic image, with the coordinates of the GCPs used for geo-rectification. The resulting
orthomosaic had a ground sampling distance (GSD) of 0.32 cm/pixel. Individual plot images were
clipped and saved in TIFF format from the orthomosaic using a field plot map with polygons
corresponding to the experimental plot dimension of 5 m x 1 m in ArcGIS Pro version 2.5.1 (Esri,
USA).
131

2.3 Lodging Assessment

A two-stage assessment of lodging was performed in this study and the results were used as the basis for image classification and image regression tasks (see Section 2.4) (Figure 2). The image classification task corresponded to the first stage of assessment in which the lodging status i.e. whether the plot is lodged (yes) or non-lodged (no) was provided by the ground truth data and this could be verified easily from visual inspection of the high-resolution plot images (Figure 3). The image regression task corresponded to the second stage of assessment where plots identified as lodged were evaluated using a modified lodging score based on the method of Fisher and Stapper (Fischer & Stapper, 1987):

$$Lodging\ score\ =\ \frac{Lodging\ severity}{3} \times Lodged\ area\ (\%)$$

Lodging severity values of 1 to 3 were assigned to three main grades of lodging based on the inclination angle between the wheat plant and the vertical line as follows: light lodging (severity 1; $10^o - 30^o$), moderate lodging (severity 2; $30^o - 60^o$) and heavy lodging (severity 3; $60^o - 90^o$)(Figure 3)(Sun et al., 2019). The lodged area (%) was determined visually from the plot images as the percentage of area lodged in the plot in proportion to the total plot area. The derived lodging score ranged between values of $1 - 100$, with a score of 100 indicating that the entire plot was lodged with heavy lodging.

2.4 Deep Learning Experiments

Deep learning experiments were conducted in the Python 3.7 environment. Performance of the open-source AutoML framework, AutoKeras (Jin, Song, & Hu, 2019) version 1.0.1 in image classification and image regression was compared to a manual approach using transfer learning with pretrained modern CNN architectures implemented in Keras, Tensorflow-GPU version 2.1. For the image classification task, a binary classification scheme assigning individual plot images to either non-lodged (class 0) or lodged (class 1) was performed as the images had a relatively balanced distribution between the two classes. For the image regression task, plot images were used as inputs to predict the lodging score. Training and evaluation of the models were performed on a NVIDIA Titan RTX GPU (24 GB of GPU memory) at SmartSense iHub, Agriculture Victoria.

2.4.1 Training, Validation and Test Datasets

For image classification, the image dataset consisted of 1,248 plot images with 528 plots identified as non-lodged (class 0) and 720 plots identified as lodged (class 1). Images were first resized to the dimensions of 128 width x 128 height x 3 channels (Section 2.4.2) and these were split 80:20 (seed number=123) into training (998 images) and test (250 images) datasets. For image regression, the 720 resized plot images identified as lodged were split 80:20 (seed number=123) into training (576 images) and test (144 images) datasets. Images were fed directly into AutoKeras without preprocessing as this was done automatically by AutoKeras. In contrast, images were preprocessed to the ResNet-50 format using the provided preprocess_input function in Keras. For model training on both image classification and regression, the training dataset was split further 80:20 (seed number=456) into training and validation datasets. The validation dataset is used to evaluate training efficacy, with lower validation loss (as defined by the loss function, Section 2.4.2) indicating a better trained model. Performance of trained models was evaluated on the test dataset (section 2.2.4).

2.4.2 AutoML with AutoKeras

AutoKeras is an open-source AutoML framework built using Keras which implements state-of-the-
art NAS algorithms for computer vision and machine learning tasks (Jin et al., 2019). It is also the
only open-source NAS framework to offer both image classification and regression abilities at the
time of this study. In our study, we experienced great difficulty in getting AutoKeras to stably
complete experiments in default settings due to errors relating to GPU memory usage and model
tuning. This is not entirely unexpected as beginning version 1.0, AutoKeras has undergone
significant application programming interface (API) and system architecture redesign to incorporate
KerasTuner ver. 1.0 and Tensorflow ver. 2.0. This change was necessary for AutoKeras to capitalize
on recent developments in NAS and the DL framework, Tensorflow, in addition to providing support
for the latest graphics processing unit (GPU) hardware. To partly circumvent the existing issues, we
had to implement two approaches for the DL experiments to stably complete up to 100 trials, which
is the number of models evaluated by AutoKeras (i.e. 100 trials = 100 models). Firstly, all images
were resized to the dimensions of 128 x 128 x 3 and secondly, for image classification, we had to
implement a custom image classifier using the provided AutoModel class in AutoKeras. We were not
successful in completing experiments beyond 100 trials, as such only results up to 100 trials were
presented in this study.

For image classification, a custom image classifier was defined using the AutoModel class which
allows the user to define a custom model by connecting modules/blocks in AutoKeras (Figure 4). In
most cases, the user only needs to define the input node(s) and output head(s) of the AutoModel, as
the rest is inferred by AutoModel itself. In our case, the input nodes were first an ImageInput class
accepting image inputs (128 x 128 x 3), which in turn was connected to an ImageBlock class which
selects iteratively from either a ResNet (K. He, Zhang, Ren, & Sun, 2016), ResNext (Xie, Girshick,
Dollár, Tu, & He, 2017), Xception (Chollet, 2017) or simple CNN building blocks to construct
neural networks of varying complexity and depth. The input nodes were joined to a single output
head, the ClassificationHead class which performed the binary classification (Figure 4). The
AutoModel was fitted to the training dataset with the tuner set as "bayesian", loss function as
"binary_crossentropy", evaluation metrics as "accuracy" and 200 training epochs (rounds) for 10, 25,
50 and 100 trials with a seed number of 10. For image regression, the default Autokeras image
regression class, ImageRegressor was fitted to the training dataset with the loss function as mean
squared error (MSE), evaluation metrics as mean absolute error (MAE) and mean absolute
percentage error (MAPE), and 200 training epochs for 10, 25, 50 and 100 trials with a seed number
of 45 (Figure 4).

The performance of the best models from 10, 25, 50 and 100 trials were evaluated on their respective
test datasets (Section 2.4.4) and exported as Keras models to allow neural network visualization
using the open-source tool, Netron (https://github.com/lutzroeder/netron).

2.4.3 Transfer Learning with pretrained CNNs

Transfer learning is a popular approach in DL where a pretrained model is reused as the starting point
for a model on a second task (Jiang & Li, 2020). This allows the user to rapidly deploy complex
neural networks, including state-of-the-art DL architectures without incurring time and computing
costs. In this study, transfer learning was performed using VGG networks (Simonyan & Zisserman,
2015), residual networks (ResNets)(K. He et al., 2016), InceptionV3(Szegedy, Vanhoucke, Ioffe,
Shlens, & Wojna, 2016), Xception (Chollet, 2017) and densely connected CNNs
(DenseNets)(Huang, Liu, & Weinberger, 2017) pretrained on the ImageNet dataset. These networks
were implemented in Keras as a base model using the provided Keras API with the following

parameters: weights="imagenet", include_top=False and input_shape=(128, 128, 3) (Figure 5).
Output from the base model was joined to a global average pooling 2D layer and connected to a final
dense layer, with the activation function set as either "sigmoid" for image classification or "linear"
for image regression. The model was compiled with the batch size as 32, optimizer as 'Adam' and
corresponding loss functions and evaluation metrics as described in section 2.4.2. Model training
occurred in two stages for both image classification and regression tasks: in the first stage (100
epochs), weights of the pre-trained layers were frozen and the Adam optimizer had a higher learning
rate (1×10^{-1} or 1×10^{-2}) to allow faster training of the top layers; in the second stage (200 epochs),
weights of the pre-trained layers were unfrozen and the Adam optimizer had a smaller learning rate
(1×10^{-2} to 1×10^{-5}) to allow fine-tuning of the model. Learning rates were optimized for each
pretrained CNN and the values which provided the best model performance are provided in
supplementary Table S1. Performance of the trained models was evaluated on their respective test
datasets (Section 2.4.4).
237

2.4.4 Model Evaluation Metrics

For image classification, model performance on the test dataset was evaluated using classification
accuracy (%). For image regression, in addition to the mean absolute error (MAE) and the mean
absolute percentage error (MAPE) provided by AutoKeras and Keras, the coefficient of
determination (R^2) and the root mean-squared error (RMSE) were also calculated to determine model
performance on the test dataset. Models were also evaluated based on total model training time (in
minutes, min) and inference time on the test dataset presented as mean ± standard deviation in
milliseconds (ms).
246

3   Results

3.1   Image Classification

Both transfer learning with pretrained CNNs and AutoKeras performed strongly in the image
classification task (Table 1). Transfer learning performance with pretrained CNNs ranged from 91.6
to 93.2% classification accuracy, with Xception and DenseNet-201 giving the best overall accuracy
of 93.2% (Table 1). Among the pretrained CNNs, InceptionV3 had the fastest training (5.42 min) and
inference (100.54 ± 15.08 ms) times, whereas DenseNet-201 had the slowest training (11.79 min)
and inference (188.09 ± 24.19 ms) times. In comparison, AutoKeras (AK) performance ranged from
86.8 to 92.4% accuracy, with performance improving as more models (trials) were evaluated (Table
1). The best AutoKeras model was discovered from 100 trials and had the same 92.4% accuracy as
the ResNet-50 (Table 1). Impressively, AutoKeras was able to achieve this result using a simple 2-
layers CNN (43,859 parameters) consisting only of a single 2D convolutional layer (Figure 6) as
opposed to the 50-layers deep ResNet-50 architecture (~23.6 million parameters). Incidentally, the 2-
layers CNN had the fastest overall inference time (5.71 ± 0.12 ms) on the test dataset compared to
other models, which was ~18-fold faster compared to the InceptionV3 and up to ~33-fold faster
compared to the DenseNet-201 (Table 1). However, model training times for AutoKeras were
significantly higher compared to the transfer learning approaches, with the longest training time of
251 min recorded for 100 trials, which was ~21-fold higher compared to the DenseNet-201 (Table 1).
Examination of the model architectures returned by AutoKeras revealed that the best model
architecture resulting from the 10 and 25 trials was a deep CNN model comparable in depth and
complexity to the ResNet-50 (Figure S1), highlighting the ability of AutoKeras to explore deep CNN
architectures even in a small model search space. Subsequently, when the model search space was

extended to 50 and 100 trials, the best model architecture discovered by AutoKeras was the 2-layers
CNN model (Figure 6).
271

3.2   Image Regression

For the image regression task, transfer learning with DenseNet-201 gave the best overall performance
(R^2=0.8303, RMSE=9.55, MAE=7.03, MAPE=12.54%), followed closely by AutoKeras (AK) with
the model from 100 trials (R^2=0.8273, RMSE=10.65, MAE=8.24, MAPE=13.87%)(Table 2). The
CNN models varied in regression performance, with R^2 ranging between 0.76 – 0.83. Within the
pretrained CNNs, DenseNet-201 had the slowest model training (7.01 min) and inference (117.23 $\pm$
15.25 ms) times, with ResNet-50 having the fastest training (3.55 min) and inference (79.23 $\pm$ 10.31
ms) times. For AutoKeras, performance generally improved from 10 to 100 trials (Table 2).
AutoKeras was able to achieve the second-best performance using an 8-layers CNN resembling a
truncated mini Xception network with 207,560 total parameters (Figure 7). Two prominent features
of the original 71-layers deep Xception network, namely the use of depthwise separable convolution
layers and skip connections were evident in the AutoKeras model (Figure 7). Notably, the mini
Xception network outperformed the original pretrained Xception network (R^2=0.7709, RMSE=11.08,
MAE=8.22, MAPE=13.51%)(Table 2). Not surprisingly, the mini Xception network had the fastest
inference time (2.87 $\pm$ 0.12 ms) compared to the other models, which was ~27-fold faster compared
to the ResNet-50 and up to 41-fold faster compared to the DenseNet-201 (Table 2). However, model
training times for AutoKeras was again significantly higher compared to the transfer learning
approaches, with the longest training time of 325 min recorded for 100 trials, which was ~46 fold
higher compared to the DenseNet-201 (Table 2). Examination of the model architectures returned by
AutoKeras revealed that the best model architecture resulting from the 10 and 25 trials was a deep
CNN model (Figure S2) whereas the best model architecture discovered from 50 and 100 trials was
the 8-layers mini Xception model (Figure 7).

4   Discussion

Using wheat lodging assessment as an example, we compared the performance of an open-source
AutoML framework, AutoKeras to transfer learning using modern CNN architectures for image
classification and image regression. As a testament to the power and efficacy of modern DL
architectures for computer vision tasks, both AutoKeras and transfer learning approaches performed
well in this study, with transfer learning exhibiting a slight performance advantage over AutoKeras.
301
For the image classification task, plot images were classified as either non-lodged or lodged. The best
classification performance of 93.2% was jointly achieved by transfer learning with Xception and
DenseNet-201 networks. This is not entirely surprising as both Xception (Chollet, 2017) and
DenseNet (Huang et al., 2017) were developed later (chronologically speaking) as improved
architectures compared to the other CNNs in this study. In contrast, the best AutoKeras model (from
100 trials) achieved an accuracy of 92.4%, which is the same as those obtained by transfer learning
with ResNet-50. Classification results in this study are comparable to those reported in a smaller
study which classified 465 UAV-acquired wheat plot multispectral images (red, green, blue channels
used in models) as either non-lodged/lodged with a hand-crafted deep neural network, LodgedNet
(97.7% accuracy) and other modern DL networks (97.7 – 100.0% accuracies) via transfer learning
(Mardanisamani et al., 2019). The higher classification accuracies reported in that study may be due

to the use of image data augmentation (i.e. increasing training dataset via image transformations)
which generally improves model performance and that images were acquired pre-maturity (plants
were still green) allowing variations in color to potentially contribute more informative features for
modelling (Mardanisamani et al., 2019; Sun et al., 2019). Results in our study suggest that NAS
generated models can provide competitive performance compared to modern human designed CNN
architectures, with transfer learning using pretrained CNNs exhibiting a slight performance
advantage (~1% improvement) over AutoML models. A recent survey comparing the performance of
manually designed models against those generated by NAS algorithms on the CIFAR-10 dataset, a
public dataset commonly used for benchmarking in image classification, found that the top two best-
performing models were both manually designed models (X. He et al., 2019). However, the gap
between the manual and AutoML models was very small (<1% accuracy difference). In our study,
AutoKeras was able to achieve results comparable to those of the 50-layers deep ResNet-50 model
(~25 million parameters) using only a simple 2-layers CNN model (43,859 parameters). The 2-layers
CNN had the fastest inference time (5.71 ± 0.12 ms) compared to the other models, which was up to
33-fold faster compared to the DenseNet-201 which had the slowest inference time. As such, the 2-
layers CNN could prove useful for real-time inferencing, but it's simple or shallow architecture raises
concern about its generalizability across different datasets. This can be addressed in future studies by
using datasets derived from multiple trials or imaging conditions for model training to obtain a
solution generalized across different environments.
332
For the image regression task, lodged plot images were used as inputs to predict the lodging score.
The best performance (R^2=0.8303, RMSE=9.55, MAE=7.03, MAPE=12.54%) was obtained using
transfer learning with DenseNet-201, followed closely by AutoKeras (R^2=0.8273, RMSE=10.65,
MAE=8.24, MAPE=13.87%) with the model discovered from 100 trials. In both image classification
and regression tasks, transfer learning with DenseNet-201 achieved the best results. DenseNet can be
considered as an evolved version of the ResNet (K. He et al., 2016), where the outputs of the
previous layers are merged via concatenation with succeeding layers to form blocks of densely
connected layers (Huang et al., 2017). However, similarly for image classification, the DenseNet-201
had the slowest inference time (117.23 ± 15.25 ms) on the test dataset in image regression, making it
less suitable for time-critical applications such as real-time inferencing. In comparison, the
AutoKeras model resembled a mini 8-layers Xception model (207,560 parameters) and had the
fastest inference time (2.87 ± 0.12 ms) on the test dataset, which was ~41-fold faster compared to the
DenseNet-201. In its original form, the Xception network is 71-layers deep (~23 million parameters)
and consists of three parts: the entry flow, middle flow and exit flow (Chollet, 2017). These three
parts and two key features of the Xception network, namely the depthwise separable convolutions
and skip connections originally proposed in ResNet were discernable from the mini Xception model.
Research in the area of network pruning which compresses deep neural network through the
removal/pruning of redundant parameters showed that it is possible to have equally performant
models with up to 97% of the parameters pruned (Salama, Ostapenko, Klein, & Nabi, 2019).
Although dissimilar to network pruning, as evidenced in our study, AutoKeras can discover efficient
and compact model architectures through the NAS process. However, NAS generated models are
typically limited to variants or combinations of modules derived from existing human designed CNN
architectures (Elsken et al., 2019; X. He et al., 2019; Wistuba et al., 2019); although recent
innovations in NAS have uncovered novel CNN architectures such as SpineNet for object detection
(Du et al., 2019).
358
The lodging score originally proposed by Fisher and Stapper (Fischer & Stapper, 1987) is calculated
from the lodging angle and lodged area (lodging score = angle of lodging from vertical position/90 x
% lodged area). In our study, the angle of lodging is replaced by lodging severity, which is a score of

1 to 3 assigned to light, moderate and heavy lodging grades as determined by visual assessment of
lodged plot images. Consequently, under- or over-estimation of lodging scores may happen for plots
within the same lodging severity grade. For example, plots with 100% lodged area and lodging angle
of 65^0 (lodging severity 3) and 90^0 (lodging severity 3) will have the same lodging score of 100 in this
study as opposed to scores of 72 and 100 according to the original method. This may partly account
for the model prediction errors in the image regression task. Nonetheless, the modified lodging score
allowed a rapid evaluation of wheat lodging based on visual assessments of UAV imagery and was
useful as a target for image regression. For detailed assessment of lodging and model performance in
lodging score prediction, future studies should incorporate manual ground-truthing of the lodging
angle and lodged area to enable a more accurate calculation of lodging scores.

One of the challenges in this study was getting AutoKeras to perform stably and complete the DL
experiments. Initial attempts were often met with an out of memory (OOM) error message, arising
from AutoKeras trying to load models too large to fit in the GPU memory. Prior to version 1.0,
AutoKeras had a GPU memory adaptation function which limits the size of neural networks
according to the GPU memory (Jin et al., 2019). However, beginning version 1.0, this function is no
longer implemented in AutoKeras (personal communication with Haifeng Jin, author of AutoKeras)
and may partially account for the OOM errors. To partly circumvent this issue, we had to resize all
input images (1544 x 371) to a smaller size of 128 x 128, which allowed AutoKeras to complete
experiments up to 100 trials. The impact of the downsized images on AutoKeras model performance
would need to be ascertained in future studies, although the 128 x 128 image size is within common
ranges observed in DL models, for example, LodgedNet (64 x 128)(Mardanisamani et al., 2019) and
established modern CNN architectures (224 x 224)(K. He et al., 2016; Huang et al., 2017; Simonyan
& Zisserman, 2015). As AutoKeras is undergoing active development, we are hopeful that issues
encountered in our study will be resolved in future releases. It will be interesting to explore
AutoKeras' performance with larger model search space (>100 trials) using higher resolution input
images coupled with image data augmentation where appropriate in future studies.

Transfer learning using existing modern CNN architectures achieved better results compared to
AutoML in both image classification and regression tasks in this study. However, a major limitation
is that these CNN models have been trained using 3-channels RGB images and this prevents direct
application of these models for image sources beyond 3-channels, such as multispectral and
hyperspectral images (Mardanisamani et al., 2019). In addition, existing CNN architectures may not
always provide the best performance compared to custom-designed models. However, modification
of existing CNN architectures or manually designing CNN models are time-consuming and
technically challenging. In this regard, AutoML provides an attractive alternative as it can deliver
CNN models with good performance out-of-the-box and can accept inputs of varying sizes and
dimensions, making it ideal for use on diverse sensor-derived data including multispectral and
hyperspectral imagery. Furthermore, an added benefit of AutoML is its potential through NAS to
discover compact model architectures which are ideal for real-time inferencing. However, to ensure
generalizability of the NAS-generated models across datasets, it is vital to employ training dataset
representative of the diverse trial environments and imaging conditions in future studies. The primary
downside of AutoML is the long training times (hours as opposed to minutes) required to achieve
models with competitive performance compared to transfer learning even when using modern GPU
hardware. The time and GPU computational costs associated with AutoML hinders it from being
widely adopted by DL practitioners for now. However, this is expected to be offset in time by the
rapid growth in GPU computing power and concurrent rise in GPU affordability. Another concern
relating to AutoML is the reproducibility of results owing to the stochastic nature of NAS (Li &
Talwalkar, 2019). This concern can largely be addressed through making available all datasets,

source codes (including exact seeds used) and best models reported in the NAS study – a practice embraced in this study (see Data Availability).

Results in our study demonstrate that transfer learning with modern CNNs performed better compared to AutoML, although the performance differences were minimal. For most computer vision tasks using RGB image datasets, transfer learning with existing CNNs will provide a good starting point and should yield satisfactory results in most cases with minimal effort and time. However, for plant phenotyping applications that are time-critical and generate image datasets beyond the standard RGB 3-channels, AutoML is a good alternative to manual DL approaches and should be in the toolbox of both novice and expert users alike. For field-based crop phenotyping, portable multispectral and hyperspectral sensors are becoming common on ground-based and aerial HTP platforms (Mir et al., 2019), providing ample avenues for AutoML application. Moving forward, with the exponential rise in GPU computing power and strong interests in NAS research, AutoML systems are expected to become more ubiquitous. In tandem with existing DL practices, they can contribute significantly towards streamlined development of image analytical pipelines for HTP systems integral to improving breeding program and crop management efficiencies. Results in our study provide a basis for the adoption and application of AutoML systems for high-throughput image-based plant phenotyping.

Table 1. Model performance metrics for image classification.

Network	Parameters	Training (min)	Inference (ms)	Accuracy (%)
VGG16	14,715,201	6.03	146.70 ± 20.54	92.0
VGG19	20,024,897	7.01	161.70 ± 25.87	91.6
ResNet-50	23,589,761	5.89	119.41 ± 15.52	92.4
ResNet-101	42,660,225	9.88	186.73 ± 26.14	92.8
InceptionV3	21,804,833	5.42	100.54 ± 15.08	92.8
Xception	20,863,529	9.06	148.20 ± 20.75	93.2
DenseNet-169	12,644,545	9.23	152.83 ± 22.93	92.8
DenseNet-201	18,323,905	11.79	188.09 ± 24.19	93.2
AK-10_trials	23,566,856	16.06	102.34 ± 14.33	86.8
AK-25_trials	23,566,856	29.18	110.45 ± 13.25	88.4
AK-50_trials	43,859	102.43	5.83 ± 0.64	89.6
AK-100_trials	43,859	251.80	5.71 ± 0.12	92.4

Network	Parameters	Training (min)	Inference (ms)	R^2	RMSE	MAE	MAPE (%)
VGG16	14,715,201	3.71	90.86 ± 12.72	0.7590	11.37	8.97	14.02
VGG19	20,024,897	4.32	103.86 ± 16.43	0.7707	11.03	9.19	16.01
ResNet-50	23,589,761	3.55	79.23 ± 10.31	0.7844	10.79	8.28	15.51
ResNet-101	42,660,225	5.85	114.85 ± 16.08	0.7730	11.10	8.38	15.67
InceptionV3	21,804,833	3.32	62.18 ± 9.33	0.7642	11.09	8.07	13.90
Xception	20,863,529	5.33	92.91 ± 13.01	0.7709	11.08	8.22	13.51
DenseNet-169	12,644,545	6.65	94.25 ± 14.14	0.7985	10.31	7.68	13.63
DenseNet-201	18,323,905	7.01	117.23 ± 15.25	0.8303	9.55	7.03	12.54
AK-10_trials	23,566,856	32.25	80.26 ± 0.14	0.7568	12.43	9.54	14.55

AK-25_trials	23,566,856	123.08	82.36 ± 0.12	0.7772	12.28	8.62	14.38
AK-50_trials	207,560	184.91	2.86 ± 0.11	0.8133	10.71	8.31	13.92
AK-100_trials	207,560	325.62	2.87 ± 0.12	0.8273	10.65	8.24	13.87

432 **Table 2. Model performance metrics for image regression.**

434 **5　Acknowledgments**

435 We thank Dennis Ward and Emily Thoday-Kennedy for technical support in conducting the field
436 experiment.
437

438 **6　Author Contributions**

439 JCOK designed the deep learning experiments and analyzed the data. JCOK, GS and SK conceived
440 and designed the study. SK managed the field experiment. JCOK, GS and SK wrote and edited the
441 paper. All authors read and approved the final manuscript.
442

443 **7　Funding**

444 This study is funded by Agriculture Victoria.
445

446 **8　Conflict of Interest Statement**

447 The authors declare that the research was conducted in the absence of any commercial or financial
448 relationships that could be construed as a potential conflict of interest.

450 **9　Data Availability**

451
Dataset containing 1,248 digital images (1,544 x 371 pixels) of individual wheat plots with varying
grades of lodging and corresponding lodging data are available on Zenodo (Joshua Koh, German
Spangenberg, & Surya Kant, 2020). Ground truth data for lodging status and calculated lodging
scores are provided as a CSV file. Source codes required to replicate the analyses in this article and
the best performing models reported for AutoKeras are provided in a GitHub repository (Joshua Koh,
German Spangenberg, & Surya Kant, 2020).
458

459 **10　Figure Captions**

460 **Figure 1. Wheat breeding field experiment.** Ground control points (GCPs) indicated in figure.

461 **Figure 2. Experimental workflow for wheat lodging assessement.**

Figure 3. Different wheat lodging severities. Wheat plot images were first classified as non-lodged or lodged using ground truth data. Plots identified as lodged were assessed visually and divided into three lodging severities (light, moderate and heavy) based on lodging angles.

Figure 4. Automated machine learning with AutoKeras. (A) AutoModel for image classification. (B) ImageRegressor for image regression.

Figure 5. Transfer learning with pretrained CNN architectures. Output from a pretrained CNN was joined to a global average pooling 2D layer and connected to a final dense layer, with the activation function set as either "sigmoid" for image classification or "linear" for image regression.

Figure 6. Best AutoKeras model architecture for image classification. A simple 2-layers CNN model with 43,895 parameters was the best architecture discovered in 50 and 100 trials. The best AutoKeras classification performance was provided by the model from 100 trials.

Figure 7. Best AutoKeras model architecture for image regression. An 8-layers mini Xception model with 207,560 parameters was the best architecture discovered in 50 and 100 trials. Three main parts (entry, middle and exit flows) and two key features (examples indicated by green boxes), namely the depthwise separable convolutional layers and skip connections from the original Xception network (Chollet, 2017) can be discerned from the architecture. The best AutoKeras regression performance was provided by the model from 100 trials.

11   Supplementary Materials

Figure S1. Best AutoKeras model architecture from 10 and 25 trials for image classification.

Figure S2. Best AutoKeras model architecture from 10 and 25 trials for image regression.

Table S 1. Adam optimizer learning rates for pretrained CNNs fine-tuning.

12   References

Chandra, A., Desai, S. V., Guo, W., & Balasubramanian, V. N. (2020). Computer Vision with Deep Learning for Plant Phenotyping in Agriculture: A Survey. *ArXiv, abs/2006.11391*.

Chollet, F. (2017). Xception: Deep Learning with Depthwise Separable Convolutions. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 1800-1807.

Du, X., Lin, T.-Y., Jin, P., Ghiasi, G., Tan, M., Cui, Y., . . . Song, X. (2019). SpineNet: Learning Scale-Permuted Backbone for Recognition and Localization. *ArXiv, abs/1912.05027*.

Elsken, T., Metzen, J. H., & Hutter, F. (2019). Neural Architecture Search: A Survey. *ArXiv, abs/1808.05377*.

Fischer, R. A., & Stapper, M. (1987). Lodging effects on high-yielding crops of irrigated semidwarf wheat. *Field Crops Research, 17*(3), 245-258. doi:https://doi.org/10.1016/0378-4290(87)90038-4

He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep Residual Learning for Image Recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770-778.

He, X., Zhao, K., & Chu, X. (2019). AutoML: A Survey of the State-of-the-Art. *ArXiv, abs/1908.00709*.

Huang, G., Liu, Z., & Weinberger, K. Q. (2017). Densely Connected Convolutional Networks. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2261-2269.

Jiang, Y., & Li, C. (2020). Convolutional Neural Networks for Image-Based High-Throughput Plant Phenotyping: A Review. *Plant Phenomics, 2020*, 4152816. doi:10.34133/2020/4152816

Jin, H., Song, Q., & Hu, X. (2019). Auto-Keras: An Efficient Neural Architecture Search System. *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*.

Khan, A., Sohail, A., Zahoora, U., & Qureshi, A. S. (2020). A survey of the recent architectures of deep convolutional neural networks. *Artificial Intelligence Review*, 1 - 62.

Koh, J., Spangenberg, G., & Kant, S. (2020). Dataset for AutoML Manuscript (Publication no. 10.5281/zenodo.3952422). from Zenodo https://doi.org/10.5281/zenodo.3952422

Koh, J., Spangenberg, G., & Kant, S. (2020). Source Codes for AutoML Manuscript. Retrieved from https://github.com/AVR-PlantPhenomics/automl_paper

Li, L., & Talwalkar, A. (2019). *Random Search and Reproducibility for Neural Architecture Search.* Paper presented at the UAI.

Mardanisamani, S., Maleki, F., Kassani, S. H., Rajapaksa, S., Duddu, H. S., Wang, M., . . . Eramian, M. G. (2019). Crop Lodging Prediction From UAV-Acquired Images of Wheat and Canola Using a DCNN Augmented With Handcrafted Texture Features. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 2657-2664.

Minaee, S., Boykov, Y., Porikli, F. M., Plaza, A. J., Kehtarnavaz, N., & Terzopoulos, D. (2020). Image Segmentation Using Deep Learning: A Survey. *ArXiv, abs/2001.05566*.

Mir, R. R., Reynolds, M., Pinto, F., Khan, M. A., & Bhat, M. A. (2019). High-throughput phenotyping for crop improvement in the genomics era. *Plant Science, 282*, 60-72. doi:https://doi.org/10.1016/j.plantsci.2019.01.007

Ninomiya, S., Baret, F., & Cheng, Z.-M. (2019). Plant Phenomics: Emerging Transdisciplinary Science. *Plant Phenomics, 2019*, 2765120. doi:10.34133/2019/2765120

Salama, A. I., Ostapenko, O., Klein, T., & Nabi, M. (2019). Pruning at a Glance: Global Neural Pruning for Model Compression. *ArXiv, abs/1912.00200*.

Simonyan, K., & Zisserman, A. (2015). Very Deep Convolutional Networks for Large-Scale Image Recognition. *CoRR, abs/1409.1556*.

Sun, Q., Sun, L., Shu, M., Gu, X., Yang, G., & Zhou, L. (2019). Monitoring Maize Lodging Grades via Unmanned Aerial Vehicle Multispectral Image. *Plant Phenomics, 2019*, 5704154. doi:10.34133/2019/5704154

Szegedy, C., Vanhoucke, V., Ioffe, S., Shlens, J., & Wojna, Z. (2016). Rethinking the Inception Architecture for Computer Vision. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2818-2826.

Tan, M., & Le, Q. V. (2019). EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks. *ArXiv, abs/1905.11946*.

Tardieu, F., Cabrera-Bosquet, L., Pridmore, T., & Bennett, M. (2017). Plant Phenomics, From Sensors to Knowledge. *Current Biology, 27*(15), R770-R783. doi:10.1016/j.cub.2017.05.055

Truong, A., Walters, A., Goodsitt, J., Hines, K., Bruss, C. B., & Farivar, R. (2019, 4-6 Nov. 2019). *Towards Automated Machine Learning: Evaluation and Comparison of AutoML Approaches and Tools.* Paper presented at the 2019 IEEE 31st International Conference on Tools with Artificial Intelligence (ICTAI).

Wang, N., Gao, Y., Chen, H., Wang, P., Tian, Z., & Shen, C. (2019). NAS-FCOS: Fast Neural Architecture Search for Object Detection. *ArXiv, abs/1906.04423*.

Watt, M., Fiorani, F., Usadel, B., Rascher, U., Muller, O., & Schurr, U. (2020). Phenotyping: New
Windows into the Plant for Breeders. *Annual Review of Plant Biology, 71*(1), 689-712.
doi:10.1146/annurev-arplant-042916-041124
Weng, Y., Zhou, T., Li, Y., & Qiu, X. (2019). NAS-Unet: Neural Architecture Search for Medical
Image Segmentation. *IEEE Access, 7*, 44247-44257. doi:10.1109/ACCESS.2019.2908991
Wistuba, M., Rawat, A., & Pedapati, T. (2019). A Survey on Neural Architecture Search. *ArXiv,*
abs/1905.01392.
Wu, X., Sahoo, D., & Hoi, S. C. H. (2020). Recent advances in deep learning for object detection.
Neurocomputing, 396, 39-64. doi:https://doi.org/10.1016/j.neucom.2020.01.085
Xie, S., Girshick, R. B., Dollár, P., Tu, Z., & He, K. (2017). Aggregated Residual Transformations
for Deep Neural Networks. *2017 IEEE Conference on Computer Vision and Pattern*
Recognition (CVPR), 5987-5995.
Zoller, M.-A., & Huber, M. F. (2019). Benchmark and Survey of Automated Machine Learning
Frameworks. *arXiv: Learning*.
Zoph, B., & Le, Q. V. (2016). Neural Architecture Search with Reinforcement Learning. *ArXiv,*
abs/1611.01578.
563

(A)

(B)