1

3 Task dependence of neural representations of global scene properties but

4 not scene categories in the prefrontal cortex

8 Yaelan Jung & Dirk B. Walther

9 University of Toronto, Department of Psychology,

10 Toronto, ON, Canada

11                                    Abstract

Natural scenes deliver rich sensory information about the world. Decades of research has shown

that the scene-selective network in the visual cortex represents various aspects of scenes. It is,

however, unknown how such complex scene information is processed beyond the visual cortex,

such as in the prefrontal cortex. It is also unknown how task context impacts the process of scene

perception, modulating which scene content is represented in the brain. In this study, we

investigate these questions using scene images from four natural scene categories, which also

depict two types of global scene properties, temperature (warm or cold), and sound-level (noisy

or quiet). A group of healthy human subjects from both sexes participated in the present study

using fMRI. In the study, participants viewed scene images under two different task conditions;

temperature judgment and sound-level judgment. We analyzed how different scene attributes

(scene categories, temperature, and sound-level information) are represented across the brain

under these task conditions. Our findings show that global scene properties are only represented

in the brain, especially in the prefrontal cortex, when they are task-relevant. However, scene

categories are represented in the brain, in both the parahippocampal place area and the prefrontal

cortex, regardless of task context. These findings suggest that the prefrontal cortex selectively

represents scene content according to task demands, but this task selectivity depends on the types

of scene content; task modulates neural representations of global scene properties but not of

scene categories.

31                                          Introduction

Real-world scenes provide a wealth of complex sensory experiences. Research has demonstrated

that various components of scenes are processed across several brain regions of the scene-

selective network in the visual cortex, such as the parahippocampal place area (PPA, Epstein &

Kanwisher, 1998), the retrosplenial cortex (RSC, Maguire, 2001), and the occipital place area

(OPA, Dilks et al., 2013). However, recent studies have shown that visual scene processing takes

place beyond the visual cortex and involves the associative cortex such as the parietal (Silson et

al., 2016; Silson et al., 2019) and the prefrontal cortex (Jung et al., 2018). Does this indicate that

the scene processing network can be extended to the prefrontal cortex (PFC)? In the current

study, we investigate whether and how scene content is processed beyond the visual cortex,

especially in PFC.

We have previously demonstrated that scene images and sounds elicit neural representations of

scene categories in PFC. Intriguingly, these representations are modality-independent, suggesting

that PFC represents scene content in an abstract way (Jung et al., 2018). Natural scenes also

comprise other attributes, often referred to as global scene properties, such as openness,

temperature, or transience (Greene & Oliva, 2009), which are also processed in scene-selective

visual brain regions (Kravitz et al., 2011; Park et al., 2011; Persichetti and Dilks, 2019).

However, we do not know yet whether the PFC represents global scene properties as it does

scene categories, and whether the neural presentations of global scene properties in PFC are also

modality-independent.

Scene representations in PFC may also depend on task context. One of the PFC's fundamental

functions is to modulate the neural representation of sensory inputs according to task demands

(Chadick & Gazzaley, 2011; Harel et al., 2014; Zanto et al., 2011). Thus, although scene content

can be represented in PFC, it could be only when such scene content is task-relevant.

Specifically, we hypothesize that task context is more likely to impact the processing of global

scene properties than that of scene categories, as supported by previous research. First,

behavioral studies have shown that scene category information is accessible with limited

attention (Li et al., 2002; Mack & Rock, 1998), and even when it is not relevant to the task

context (Greene & Fei-Fei, 2014). Second, it has been shown that scene categories can be

represented in PFC in a passive-viewing paradigm (Jung et al., 2018; Walther et al., 2009),

which does not explicitly require attention to scene categories. Thus, we predict that scene

category information may be represented in PFC regardless of task context. We explore these

possibilities by assessing the neural representations of global scene properties and scene

categories in PFC under different task conditions.

The current study employs two global scene properties (temperature and sound-level) and four

natural scene categories (beaches, cities, mountain, and train stations) to examine how global

scene properties and scene category information are represented in PFC across different task

contexts. To construct different task conditions for each scene property, we instructed

participants to make a judgment on a global scene property, which would encourage them to

attend to a particular property in a scene.

Finally, the present study also explores whether representations of global scene properties in PFC

are modality-independent in the same way as scene categories (Jung et al., 2018). We do so by

comparing the neural representation of global scene properties inferred from images to the neural

representation of direct thermal and auditory percepts. Our findings demonstrate that both global

scene properties and scene categories are represented in PFC in a modality-independent way.

Neural representations of global scene properties generalize across sensory modalities, as

indicated by similar neural activity patterns across percepts inferred from images and direct

sensation.

# Materials & Methods

1. Participants

Twenty-five healthy adults recruited from the University of Toronto participated in the fMRI

study (10 male, 15 females; mean age = 22.17, SD = 1.99, all right-handed). All participants

reported normal or corrected-to-normal vision and normal hearing and no history of neurological

abnormalities. Five participants did not complete both sessions, and their data were excluded

from the analysis. Participants provided informed consent before the experiment, and all aspects

of the experiment were approved by the Research Ethics Board (REB) at University of Toronto

(protocol number 33720).

2. Experiment design & Stimuli

The study consisted of two sessions, the main experiment session and the localizer session. For

all participants, the main experiment session was performed first, except for three, who did the

localizer experiment first for logistical reasons (e.g., last-minute cancellation). The main

experiment session consisted of three different types of tasks: fixation monitoring, temperature

judgment, and sound-level judgment. Participants always performed two runs of the fixation task

first, and then the other two tasks in alternation (either T-S-T-S or S-T-S-T). The localizer

session consisted of three different experiments; the sound experiment, the stone experiment, and

the face-place-object localizer, which were always performed in this order.

2-1. Visual Stimuli

Sixty-four scene images from four natural scene categories were selected according to three

scene properties: entry-level category (beaches, city streets, forests, and train stations),

temperature of the depicted scene (warm versus cold), and sound level (noisy versus quiet). The

selection procedure ensured that all three properties vary *independently* within the image set.

We measured the properties of scene images with a set of three behavioral experiments on

Amazon MTurk. Workers in the behavioral experiments viewed each image and rated the

temperature and the sound level on a seven-point Likert scale. Each type of property was

measured in a separate block. The order of the tests was counterbalanced across participants.

Before the rating, a detailed description of each scale was provided, followed by six practice

trials separately for the temperature rating and the sound-level rating (see Supplementary Figure

1).

In the first rating experiment, 27 MTurk workers rated 292 scene images which were collected

from the internet. Ratings were z-scored for each participant and averaged across participants for

each image. We excluded 87 images with extreme temperature or sound scores, added 100 new

images, and repeated the rating experiment with 15 participants, first on 305 images and then on

a subset 128 images. After this procedure, we selected the final set of 64 images and repeated the

rating experiment on these images with 45 participants. These final ratings show that neither

temperature nor sound level are related to category labels. A one-way ANOVA was conducted to

find the effect of category labels on the temperature rating, showing that there is no effect of

category labels, $F(3, 60) = 0.31$ , $p = .817$; a one-way ANOVA to measure the effect of category

labels on sound-level ratings also reveal no effect of category labels, $F(3, 60) = 2.15$, $p = .103$).

Furthermore, the temperature ratings and the sound-level ratings were not correlated to each

other, $r = .037$, $p = .781$ (see Figure 1D; also see Supplementary Figure 2 for the example

stimuli).  This final set of 64 images was used in the main experiment.

2-2. Auditory Stimuli

Ten different sounds from different places (e.g., beaches, forests, and city streets) were

downloaded from an open database, Freesound (freesound.org). The sounds were cut to 12

seconds length and presented using Sensimetrics S14 MR-compatible in-ear noise-canceling

headphones. The noisy and quiet sounds differed in two aspects. First, the noisy sounds had more

auditory objects (i.e. birds, people, waves at a beach) than the quiet sounds. Also, based on the

perceived loudness which was estimated using a sound meter over the headphones, the noisy

sounds had greater volume (on average 81 dB) than the quiet sounds (on average 53 dB).

2-3. Stone Stimuli

Six massage stones (approximately 6×8×2 cm) were used in the temperature experiment. To

deliver stones at a particular temperature, three stones were soaked in warm water

(approximately 45℃) in a plastic thermal cup, and the other three stones were soaked in cold

water (approximately 9℃) for about 10 minutes before the experiment. We measured the

temperature of the stones before and after each run with a digital infrared thermometer. On

average across different runs and participants, the cold stones were 11.0 ℃ (SD = 1.3℃) before

the runs and 15.3 ℃ (SD = 0.93 ℃) after the runs. The warm stones were 44.4 ℃ (SD = 0.93℃)

before and 39.8 ℃ (0.81 ℃) after the runs (see Figure 3B).

3. Procedure

3.1. Main experiment

The main fMRI experiment was event-related with six runs of image presentations with three

different tasks (two runs for each task). In all three task conditions, participants viewed the same

set of 64 images one at a time for one second, with a 5-seconds inter-trial interval (Figure 1A).

The trial sequence also contained 16 blank trials with only the fixation cross visible; the first and

last two trials in each run were always blank, and the other twelve blank trials were randomly

distributed throughout the run. Visual stimuli were presented on the screen at a distance of

approximately 134 cm from the participant with images subtending approximately 12.3 degrees

of visual angle. Stimulus presentation, timing of all stimuli, and recording of responses were

controlled with custom Matlab scripts, using the Psychophysics Toolbox (Brainard, 1997).

In the fixation monitoring runs, participants were asked to press a button to report whether the

fixation cross was white (75% of the time) or red (25% of the time). In the temperature-

judgement runs, participants were asked to indicate whether the depicted scene looked warm or

cold (Figure 1B). In the sound-level judgement runs, participants were asked to indicate whether

the depicted scene looked noisy or quiet (Figure 1C). It was emphasized that there is no right or

wrong answer in the temperature and sound-level judgement tasks. The same set of 64 images

were repeated in all six runs, and the order of images was randomized in each run. Before the

onset of each run, participants were reminded of the task by text on the screen as well as verbal

instructions from the experimenter. All participants first performed the two fixation-monitoring

runs and then the temperature runs and the sound-level runs interleaved (either T-S-T-S or S-T-

S-T). The order was counter-balanced across participants.

3.2. Localizer experiments

The localizer experiment consisted of the sound experiment, the temperature experiment, and the

face-place-object localizer. All of these experiments used a block design.

The sound experiment consisted of two runs. Each run had 10 blocks, during which 12-second

sound clips were played. The clips in half of the blocks were noisy sounds, and the other half of

the blocks contained quiet sounds. The order of the sound sequences was randomized for each

run and for each participant. A fixation cross was presented at the center of the screen during the

entire experiment.

The stone experiment consisted of four runs and was performed by two experimenters, one in the

control room and one in the exam room next to the MRI scanner. Each run had six blocks, and

each block was one stone event. At every onset or offset of a block, the experimenter in the

control room signaled the event by presenting a colored flag (red: for warm stone, blue: for cold

stone, green: for taking the stone away) through the control room window.  The experimenter in

the exam room dried a warm or cold stone on a towel and handed it to the left hand of the

participant. Participants were holding the stone without any particular task for 10 seconds, and

then the experimenter in the exam room took the stone from the participant's hand at the green

flag signal.

The face-place-object localizer experiment consisted of two runs. Each run had 4 blocks, and

there were four mini-blocks with images of faces, objects, places, and scrambled object pictures

in each block (Epstein & Kanwisher, 1998). Each mini block was 16 seconds long, and each

image was presented for 1 second with an inter-trial interval of 500 ms. There were 12 seconds

fixation periods between blocks and also at the beginning and the end of the run.

**Figure 1** A) Illustration of the image presentation in the main experiment. B & C) Image
presentation with different labels in the temperature judgment condition (B) and in the sound-
level judgment condition (C). D) Behavioral ratings of global scene properties
188

5. fMRI data acquisition

Imaging data were recorded on a 3 Tesla Siemens Prisma MRI scanner with a 32-channel head

coil at the Toronto Neuroimaging Centre (ToNI) at the University of Toronto. High resolution

anatomical images were acquired with a MPRAGE (magnetization-prepared rapid acquisition

with gradient echo) protocol with multiband factor of 2. Images were then reconstructed using

GRAPPA (Griswold et al., 2002), with sagittal slices covering the whole brain; inversion time TI

= 912ms, repetition time TR = 1900ms, echo time TE = 2.67ms, flip angle = 9°, voxel size = 1 x

1 x 1 mm, matrix size = 224 x 256 x 160 mm. Functional images for the main and localizer

experiments were recorded with a multiband acquisition sequence; TR = 2 s, TE = 32 ms, flip

angle = 70 degrees, multiband factor = 4, voxel size = 2 x 2 x 2 mm, matrix size = 220 x 220 x

136 mm, 68 axial slices.

6. Data analyses

6.1. fMRI data preprocessing

FMRI data from the main experiment runs were motion corrected to one EPI image (the middle

volume in the middle run), followed by spatial smoothing with a Gaussian kernel with 2 mm full

width at half maximum (FWHM). Data were converted to percent signal change with respect to

the mean of each run. Preprocessing was performed using AFNI (Cox, 1996).

6.2 Region of Interest

PPA was defined using data from the face-place-object localizer runs. FMRI data from this

localizer were pre-processed the same way as the main experiment data, but spatially smoothed

with a 4 mm FWHM Gaussian filter. Data were further processed using a general linear model

(3dDeconvolve in AFNI) with regressors for all four image types (scenes, faces, objects,

scrambled objects). PPA was defined as contiguous clusters of voxels with significant contrast (q

< 0.05, corrected using false discovery rate) of scenes > (faces and objects) (Epstein &

Kanwisher, 1998).

The representation of the left hand in somatosensory cortex (S1) was also functionally defined

using data from the temperature localizer runs as we are interested in a region that specifically

corresponds to thermal perception driven by the stone stimuli. fMRI data from the temperature

localizer runs were pre-processed the same way as the main experiment data and spatially

smoothed with a 4mm FWHM Gaussian Filter. Data were then further processed using a general

linear model (3dDeconvolve in Afni) with regressors for stone events (stone, and no stone),

irrespective of temperature. S1 for the left hand was defined as a contiguous cluster of voxels in

the right hemisphere with significant contrast (q < 0.05, corrected using false discovery rate) of

stone > no-stone. In all participants except one, we observed a cluster with significant contrast

near the central gyrus in the right hemisphere (contralateral to the left hand where the stone was

given). The cluster was then masked by the anatomical extent of the post-central gyrus, which is

known as the location of the primary somatosensory cortex (see Supplementary Figure 3). The

subject for whom we could not functionally define S1 was excluded from the decoding analysis

performed in this area.

Anatomically defined ROIs were extracted using a probabilistic atlas in AFNI (DD Desai MPM;

Destrieux et al., 2010): middle frontal gyrus (MFG), superior frontal gyrus (SFG), and inferior

frontal gyrus (IFG). Anatomical masks for primary auditory cortex (Heschl's gyrus) were made

available by Sam Norman-Haignere (Norman-Haignere et al., 2013). After nonlinear alignment

of each participants' anatomical image to MNI space using AFNI's 3dQwarp function, the

inverse of the alignment was used to project anatomical ROI masks back into original subject

space using 3dNwarpApply. All decoding analyses, including for the anatomically defined ROIs,

were performed in original subject space.

6.3. Decoding analyses

6.3.1. Multi-voxel pattern analysis of the main experiment

Decoding analysis was performed for each task condition, the temperature judgment condition

and the sound-level judgment condition. Data from the fixation-monitoring condition were

included as training but not as test data for both conditions. For each participant, we trained a

linear support vector machine (SVM; using LIBSVM, Chang & Lin, 2011) to assign the correct

labels to the voxel activations inside an ROI based on the fMRI data from three runs: one of the

task-specific runs as well both of the fixation-monitoring runs. The SVM decoder then produced

predictions for the labels of the data in the left-out task run. This cross-validation procedure was

repeated with the other task run left out, thus producing predicted labels for both task-specific

runs. This procedure was performed for scene categories (beaches, forests, city streets, train

stations), scene temperature (warm, cold), and sound level (noisy, quiet) separately for

temperature judgment and sound-level judgement runs. Decoding accuracy was assessed as the

fraction of predictions with correct labels. Group-level statistics was computed over all twenty

participants using one-tailed t tests, determining if decoding accuracy was significantly above

chance level (0.5 for temperature and sound level and 0.25 for scene categories). In all the

statistical tests performed here, we adjusted significance of the t-test for multiple comparisons

using false discovery rate (FDR) (Westfall & Young, 1993).

To curb over-fitting of the classifier to the training data, we reduced the dimensionality of the

neural data by selecting a subset of voxels in each ROI. Voxel selection was performed by

ranking voxels in the training data according to the F statistics of a one-way ANOVA of each

voxel's activity with temperature, sound level, or scene categories as the main factor (Pereira et

al., 2009). We determined the optimal number of voxels by performing a nested leave-one-run-

out (LORO) cross validation within the training data. Optimal voxel numbers varied by ROI and

participant, showing an overall average of 99 voxels across all ROIs and participants in the

analysis of the main experiment.

6.3.2. Multivariate pattern analysis of the localizer experiments

To decode temperature from the localizer experiment, we performed a GLM analysis on the

preprocessed data with regressors for warm and hot blocks as well as nuisance regressors for

motion and scanner drift within the run. We obtained eight sets of beta weights (4 runs x 2

conditions) and performed a LORO cross-validation analysis using an SVM classifier. A voxel

selection procedure (as described above) was also included in this decoding procedure. For each

cross-validation fold, the voxels were ranked based on the F statistics of an ANOVA of each

voxel's activity with temperature as the factor. We determined the optimal number of voxels by

performing a LORO cross-validation analysis within the training data (mean = 211.11).

There were only two runs of data in the sound experiment. Thus, we performed a GLM analysis

at the level of blocks instead of runs. We used the sets of beta weights for each block as input to

the decoder. Specifically, in this GLM analysis, the preprocessed data from the sound localizer

runs were analyzed with regressors for noisy and quiet sound blocks as well as nuisance

regressors for motion and scanner drift within the run (second-order polynomial). As a result, we

obtained twenty sets of beta weights (10 blocks x 2 conditions). These sets of betas were used in

a one-block-leave-out cross-validation analysis (similar to LORO, but on each block instead of

runs) using an SVM. A voxel selection procedure (as described above) was also performed for

each fold in the decoding procedure, and average optimal number of voxels (across all ROIs)

was 304.02. The decoding accuracy for each ROI and each subject was determined by averaging

the performance across all the folds of the cross-validation procedure.

6.3.3. Cross-decoding analysis

In the cross-decoding analysis, we trained a decoder on data from the localizer session and tested

it with data from the main experiment. Since training and test data were completely separate in

these conditions, we used all data from the localizer session for training and voxel selection. We

here used the accuracy values from the whole-brain searchlight analysis to rank voxels (see the

following section for the detail). Using the training data, we performed LORO cross validation

analyses with the number of selected voxels varying from 125 to 500 (step size of 25). We

included voxels according to decreasing rank order of their decoding accuracies in the

searchlight analysis. We compared the decoding performance for different voxel numbers and

determined the optimal number of voxels (mean = 171.25), which showed the best decoding

performance within the training data. The decoder was then trained on the entire training set,

using the optimal number of voxels, and then tested on the data from the main experiment at

those same voxel locations.

6.3.4. Searchlight analysis

To explore representations of scene categories outside of pre-defined ROIs, we performed a

searchlight analysis. We defined a cubic "searchlight" of 5x5x5 voxels (10 x10 x10 mm). The

searchlight was centered on each voxel in turn (Kriegeskorte et al., 2006), and LORO cross-

validation analysis was performed within each searchlight location using a linear SVM classifier

(CosmoMVPA Toolbox; Oosterhof et al., 2016). Decoding accuracy at a given searchlight

location was assigned to the central voxel.

For group analysis, we first co-registered each participant's anatomical brain to the Montreal

Neurological Institute (MNI) 152 template using a diffeomorphic transformation as calculated by

AFNI's 3dQWarp. We then used the same transformation parameters to register individual

decoding accuracy maps to MNI space using 3dNWarpApply, followed by spatial smoothing

with a 4 mm FWHM Gaussian filter. To identify voxels with decodable categorical information

at the group level, we performed one-tailed t-tests to test whether decoding accuracy at each

searchlight location was above chance (0.5 for non-visual properties and cross-decoding, and

0.25 for categories). After thresholding at $p < 0.05$ (one-tailed) from the t-test, we conducted a

cluster-level correction for multiple comparisons. We used AFNI's 3dClustSim to conduct alpha

probability simulations for each participant. The estimated smoothness parameters computed by

3dFWHMx were used to conduct the cluster simulation. In the simulations, a p-value of 0.05 was

used to threshold the simulated data prior to clustering and a corrected alpha of 0.05 was used to

determine the minimum cluster size. We used the average of the minimum cluster sizes across all

the participants as the cluster threshold, which was 215 voxels.

316                                                    Results

Decoding of global scene properties

To assess neural representations of temperature and sound level from images, we performed

MVPA for each ROI and for each task condition.

**Figure 2** Decoding from the main experiment. Decoding of temperature (A), sound-level
properties (B), and categories (C) of scenes in each ROIs in the temperature judgment condition
(orange bars) and in the sound-level judgment condition (green bars). * q< 0.05, *** q < 0.001

As illustrated in Figure 2A, we were able to decode temperature (warm versus cold) in the PPA,

mean decoding accuracy = 58.75%, $t(19) = 2.67$, $q = 0.01$, and in MFG, mean decoding accuracy

= 62.5%, $t(19) = 2.94$, $q = 0.02$, when participants performed the temperature judgment task.

However, when participants were performing the sound-level judgment task, the temperature

property was decoded neither in the PPA, mean accuracy = 50%, $t(19) = 0$, $q = 0.62$; nor in the

MFG, mean accuracy = 50%, $t(19) = 0$, $q = 0.62$ (see Table 1, for decoding performance in other

ROIs). Sound level (noisy versus quiet) was decoded in the sound-level judgment condition, in

the MFG, mean accuracy = 62.5%, $t(19) = 2.52$, $q = 0.01$ and the IFG, mean accuracy = 63.75%,

$t(19) = 2.98$, $q = 0.02$. However, when the participants were performing the temperature

judgment task, sound level could not be decoded in these areas, in MFG, mean accuracy = 55%,

$t(19) = 0.94$, $q = 0.18$; in IFG, mean accuracy = 48.75%, $t(19) = -0.29$, $q = 0.61$.

To directly examine the effect of task context on decoding of scene properties, we performed a

two-way ANOVA for each ROI with task (temperature-judgment versus sound-level judgment)

and decoded property (temperature versus sound level) as a factor. In all ROIs, there was no

main effect of either task or decoded property [all $Fs < 3.32$, $ps > .07$], as well as no significant

interaction between the two [all $Fs < 3.3$, $ps > 0.07$, except in MFG. In the MFG, although there

was no main effect of task, or decoded property, the interaction between decoded property and

task was significant, $F(1,76) = 4.57$, $p = 0.003$. These results indicate that task context impacts

which type of non-visual properties are represented in the MFG.

349  **Table 1** Mean of decoding accuracy and statistical analysis in each ROI for the temperature and
350  the sound-level properties

| ROI | Decoding of temperature | | | | | | | | Decoding of sound-level | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Temperature condition | | | | Sound-level condition | | | | Temperature condition | | | | Sound-level condition | | | |
| | mean | t stats | q | effect size | mean | t stats | q | effect size | mean | t stats | q | effect size | mean | t stats | q | effect size |
| PPA | 58.75 | 2.67 | 0.01 | 0.60 | 50.00 | 0.00 | 0.50 | 0.00 | 58.75 | 2.10 | 0.12 | 0.47 | 53.75 | 1.14 | 0.22 | 0.26 |
| S1 | 50.00 | 0.00 | 0.50 | 0.00 | 52.63 | 0.81 | 0.21 | 0.18 | - | - | - | - | - | - | - | - |
| A1 | - | - | - | - | - | - | - | - | 46.25 | -1.00 | 0.84 | -0.22 | 50.00 | 0.00 | 0.50 | 0.00 |
| MFG | 62.50 | 2.94 | 0.02 | 0.66 | 50.00 | 0.00 | 0.50 | 0.00 | 55.00 | 0.94 | 0.45 | 0.21 | 62.50 | 2.52 | 0.03 | 0.56 |
| SFG | 51.25 | 0.27 | 0.49 | 0.06 | 43.75 | -1.16 | 0.87 | -0.26 | 50.00 | 0.00 | 0.77 | 0.00 | 51.25 | 0.25 | 0.50 | 0.06 |
| IFG | 56.25 | 1.23 | 0.20 | 0.27 | 53.75 | 0.72 | 0.60 | 0.16 | 48.75 | -0.29 | 0.77 | -0.07 | 63.75 | 2.98 | 0.02 | 0.67 |

## Decoding of scene categories

Scene categories were decoded with a linear SVM classifier using the same data from each task

condition but with category labels as ground truth. Here, chance level was 25% since there were

four different scene categories.

As illustrated in Figure 2, scene categories were decoded in both task conditions in PFC as well

as in PPA. In the temperature judgement condition, decoding accuracies for scene categories

were significantly higher than chance in PPA, mean accuracy = 48.75%, $t(19) = 7.29$, $q < 0.001$;

in MFG, mean accuracy = 31.67%, $t(19) = 2.36$, $q = 0.03$; and in IFG, mean accuracy = 30%,

$t(19) = 2.51$, $q = 0.03$. In the sound-level judgment condition, decoding accuracy for scene

categories was significantly higher than chance in PPA; mean accuracy = 43.14%, $t(19) = 5.78$, $q$

$< 0.001$; in MFG, mean accuracy = 31.87%, $t(19) = 2.77$, $q = 0.02$, and in SFG; mean accuracy =

30.94%, $t(19) = 2.17$, $q = 0.04$ (see Table 2 for other ROIs). To test whether the task impacts

decoding accuracy of scene categories, one-way ANOVA was performed on decoding accuracy

with task as a factor in each ROI. In all ROIs, there was no significant effect of task on decoding

accuracy for scene categories, all *Fs* <1.55, all *ps* > 0.22. Thus, these findings indicate that

unlike global scene properties, scene categories are represented in PFC regions regardless of task

context.

**Table 2** Mean of decoding accuracy and statistical analysis in each ROI
for scene category

| ROI | Decoding of scene category | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | Temperature judgment task | | | | Sound-level judgment task | | | |
| | mean | t stats | q | effect size | mean | t stats | q | effect size |
| PPA | 48.75 | 7.29 | < .001 | 1.63 | 43.18 | 5.78 | < .001 | 1.29 |
| S1 | 23.68 | -0.67 | 0.74 | -0.15 | 25.66 | 0.32 | .38 | 0.07 |
| A1 | 27.71 | 1.29 | 0.09 | 0.33 | 27.5 | 0.98 | 0.20 | 0.22 |
| MFG | 31.67 | 2.36 | 0.03 | 0.53 | 31.87 | 2.77 | 0.02 | 0.62 |
| SFG | 28.75 | 1.56 | 0.09 | 0.35 | 30.94 | 2.17 | 0.04 | 0.48 |
| IFG | 30.00 | 2.51 | 0.03 | 0.56 | 28.12 | 1.36 | 0.14 | 0.31 |

As we identified the neural representations of temperature and sound level in scene images, we

here further explore these representations to better understand how scene content is represented

in PFC. Previous research has demonstrated that the prefrontal cortex represents scene categories

at an abstract-level, which generalizes between visual and auditory input (Jung et al., 2018).

Thus, it is possible that the prefrontal cortex represents global scene properties, temperature and

sound-level information, at such an abstract level as well. To examine this possibility, we first

tested how both properties are represented in the brain when participants perceived them through

direct sensory stimulation. We then performed cross-decoding analyses from direct sensations to

percepts inferred from images to explore whether global scene properties are also represented

beyond specific sensory domains.

Decoding of direct percepts & cross-decoding: temperature properties

We first examined the neural representation of temperature that arises from direct thermal

sensation. In the localizer experiment, participants were holding a stone in their left hand which

was either warm (around 42°C, averaged across before and after each run) or cold (around 13°C,

averaged across before and after each run) (see Figure3A & B). We performed a LORO cross-

validation analysis on these data to decode the temperature across different brain regions. In this

analysis, we included the representation of the left hand in somatosensory cortex. Since the stone

stimulus was always handed to the left hand of participants, we only considered the contralateral

(right) side of somatosensory cortex. We also included the prefrontal regions, inferior, middle,

and superior frontal gyri, in which we observed neural coding of inferred thermal sensation from

the main experiment.

As illustrated in Figure 3C, the decoder was significantly more accurate than chance (50%) in the

right S1, mean accuracy = 57.89%, $t(18) = 2.584$, $q = 0.031$, suggesting that the temperature of

the stones is represented in S1. Furthermore, the classifier can predict the temperature of the

stones in the MFG, mean accuracy = 60.62%, $t(19) = 2.43$, $q = 0.044$, indicating that, just like

inferred temperature information from scene images, the thermal percept is also represented in

PFC.

Having identified brain regions that represent temperature delivered from direct sensations, we

here investigate whether such neural representation is similar to the percepts inferred from

images, which we observed in the main experiment. We do so by performing a cross-decoding

analysis in the ROIs that showed significant decoding of sensory properties from images as well

as direct percepts. For the temperature property, only MFG shows significant decoding of

temperature from images (Figure 2A) and from direct percepts (Figure 3C). An SVM classifier

was trained on the data from the direct percept of temperature in the localizer experiment and

then tested on the data from viewing scene images in the main experiment (Figure 3D).

Cross-decoding from the stone experiment to the main scene image experiment was significantly

above chance in MFG, mean accuracy = 55%, $t(19) = 1.9$, $p = 0.036$, suggesting that the

representation of temperature generalizes well from direct to inferred percepts in this brain

region (Figure 3E).

**Figure 3** Decoding of temperature property. A) Illustration of the stimuli presentation and the experiment design for the temperature localizer runs. B) Temperature of warm and cold stones before and after runs. C) Decoding of temperature from thermal sensations. D) Schematic of cross-decoding analysis across direct and indirect thermal percepts. E) Decoding accuracy of the cross-decoding analysis in the post-central sulcus and MFG. * $q < 0.05$, # $p < 0.05$

Decoding of direct percepts & cross-decoding: sound-level properties

Similarly, we examined whether direct auditory sensations generalize to the neural

representations of inferred sounds which were identified in the main experiment. First, we

examined neural representations of noisy and quiet sounds from actual auditory percepts; an

SVM classifier was trained and tested on the neural activity patterns from the sound localizer

runs. As illustrated in Figure 4B, the decoder correctly classified the sound level of scene sounds

in A1, mean accuracy $= 84\%$, $t(19) = 9.95$, $q < 0.001$, and in the IFG, mean accuracy $= 58\%$,

$t(19) = 3.046$, $q = 0.006$.

As we confirmed that there are distinct patterns of neural representation for each type of sound

level in both primary auditory cortex and PFC, we further examined whether these neural codes

generalize to the sound level inferred from images. Cross-decoding of sound level was tested in

IFG, which was the only brain area where we could decode both inferred (Figure 2B) and direct

(Figure 4B) sensations of sound-level. In IFG, decoding succeeded at mean accuracy $= 56.25\%$,

$t(19) = 2.032$, $p = 0.028$ (Figure 4D).

**Figure 4** Decoding of sound properties. A) Illustration of the design of the sound experiment, and amplitude of an exemplar of the noisy sound clips and an exemplar of the quiet sound clips used in the localizer experiment. B) Sound-level decoding accuracy in each ROI C) Schematic of cross-decoding analysis across direct and indirect auditory percepts. D) Decoding performance of the cross-decoding analysis in IFG. # $p < 0.05$, ** $q < 0.01$, *** $q < 0.001$

These results indicate that in PFC, global scene properties are represented at an abstract level and generalize across sensory modalities, from direct sensations of temperature and sound level to scene properties inferred from visual percepts.

Searchlight analysis

To explore how scene information is represented beyond the predefined ROIs, we performed a whole-brain searchlight analysis with a 5x5x5 voxels (10x10x10 mm) cube searchlight. The same decoding analyses for global scene properties and scene categories as in the ROI-based

analysis were performed at each searchlight location using a linear SVM classifier, followed by a

cluster-level correction for multiple comparisons.

**Figure 5** Searchlight maps of temperature and category decoding in the temperature judgment
condition (A) and sound-level and category decoding in the sound-level judgment condition (B).
Maps are thresholded at $p < 0.05$ and cluster-wise correction was conducted for multiple
comparison (minimal cluster size of 215). MNI coordinate for (A): x= 20, y = -10, z = 15; for (B),
x = -5, y = 32, z = 26.

Confirming the ROI-based analysis, both temperature and scene categories were decoded from

PFC in the temperature judgment condition (Figure 5A). Clusters for category decoding were

located in the anterior part of the MFG and SFG (highlighted in purple in Figure 5A), whereas

the clusters for temperature decoding were located in posterior and medial part of PFC

(highlighted in orange in Figure 5A) with little overlap.

In the sound-level judgment condition, scene categories were decoded in the anterior and

posterior part of PFC, whereas the sound-level properties were decoded mainly in the medial

prefrontal gyrus. A small overlap between the clusters can be observed in the MFG (Figure 5B).

**Figure 6** Searchlight maps of cross-decoding analysis for temperature (orange) and sound-level
(green) decoding. Maps are thresholded at $p < 0.05$ and cluster-wise correction was conducted for
multiple comparison (minimal cluster size of 215).
470

Cross-decoding from the localizer experiment (direct percepts) to the main experiment (indirect

percepts) was also performed in the whole brain using a searchlight analysis (Figure 6).

Consistent to the ROI-based analysis, we identified clusters showing successful cross-decoding

of temperature and sound level in the prefrontal regions. Specifically, for temperature decoding,

we found three clusters overlapping with SFG in both hemispheres as well as with the right

MFG, and the left IFG. For sound-level decoding, a cluster with successful decoding accuracy ($p$

$< 0.05$) was located in the right MFG and IFG. We did not find any other clusters anywhere else

in the brain that allowed for cross-modal decoding.

480                                          Discussion

The present study demonstrates that both scene categories and global scene properties are

represented in PFC. Specifically, global scene properties are represented in PFC only when the

information is task-relevant. Across the two task conditions, the temperature of scenes was only

decoded when participants were required to judge the temperature of a depicted scene, and the

sound level was only decoded when participants needed to judge how noisy a scene was.

Intriguingly, when scene properties were represented in PFC, they were computed at an abstract

level, which transcended the level of specific sensory instances. Direct thermal or auditory

percepts elicited equivalent neural activity patterns to those that were evoked when participants

inferred these properties from scene images, suggesting that PFC generalizes across direct and

indirect (inferred) perception.

The current study provides strong and clear evidence that PFC represents scene information,

suggesting that scene information processing is not restricted to the scene-selective regions in the

visual cortex but extends to the associative cortex. Our findings demonstrate that PFC represents

both temperature and sound-level properties as well as scene category information. These

findings are in line with previous studies that show that different aspects of scene information are

processed separately beyond the scene-processing network in the visual cortex (Epstein & Baker,

2019; Groen et al., 2018).

The findings of the current study are also in line with previous work showing that neural

representations in PFC can change according to task context (Bugatus et al., 2017; Harel et al.,

2014; McKee et al., 2014). Both temperature and sound-level information were represented in

PFC only when participants were making a decision about these properties; temperature

properties were decoded in MFG when participants were judging scene temperature, but not

when they were engaged in the sound-level judgment task. Similarly, sound-level properties of

scenes were decoded in IFG and MFG only in the sound-level judgment condition. To some

extent, these findings suggest that PFC might represent scene content that is not represented in

the visual or auditory cortex; sound-level information of the scene was not represented in PPA or

A1 but in PFC. Nonetheless, PFC only represents this information when it is relevant to

behavioral demands, suggesting that scene representations in PFC are largely modulated by task

context or behavioral goals, rather than automatically computed by a mere exposure to a scene

image.

In contrast to global scene properties, the current study shows that scene categories are

represented in both the PPA and the PFC regardless of task context. The decoding accuracy of

scene categories does not vary systemically across different task conditions, suggesting that

category information is represented in the PFC even when category information is not directly

related to behavioral demands. These findings are in line with previous behavioral studies, which

showed that scene categories are processed automatically and obligatorily (Greene & Fei-Fei,

2014). Furthermore, several neuroimaging studies have shown successful decoding of scene

categories using a passive-viewing paradigm without any task (Park et al., 2011; Walther et al.,

2009, 2011). However, in these fMRI studies, participants could have been deliberately tracking

categories of scenes, even though it was not explicitly required. The findings of the present study

exclude this possibility by showing that categories are decoded even when the task manipulation

is orthogonal to scene categories, providing clear evidence that categories are automatically

processed and represented in the brain.

These findings might appear to contradict previous work showing that distinct neural signals for

categories are diluted in the PFC: Bugatus et al (2017) showed that the neural representations for

visual categories, such as faces, words, and body parts, are evident in the ventral temporal cortex

under different task contexts, but not in the prefrontal regions; the PFC represents task context

rather than categories of visual stimuli. There are, however, differences in the level of categories

across the two studies that could contribute to category-specific neural activity patterns in the

PFC. Unlike in Bugatus et al (2017), where superordinate categories, such as faces, pseudo-

words, and body parts were used, the current study employs basic-level scene categories, which

are shown to be the 'default' level where real-world sensory inputs are represented (Grill-Spector

& Kanwisher, 2005; Jolicoeur et al., 1984; Mack et al., 2008). Several studies have demonstrated

that such basic-level categories are accessible with very limited exposure (Mack et al., 2008;

Mack & Palmeri, 2010) and with limited attention or cognitive resource (Greene & Fei-Fei,

2014; Li et al., 2002). Further, it should be also noted that tasks are largely different across the

two studies, and in the current study, the tasks in different conditions are still all related to scene

understanding. Thus, future research is needed to better understand how different tasks may

impact category-selective representations in PFC.

The current study also broadens our understanding of what kinds of scene content are

represented in the PPA. To our knowledge, our findings are the first to show that temperature can

be decoded in PPA, just like scene categories (Walther et al., 2009), and global scene properties

related to spatial structure of a scene (e.g. openness, Park & Chun, 2009). Why would PPA

represent temperature information? One possibility is that temperature is indicated by the color

profile of the image, and that we in fact decode color as a visual feature rather than inferred

temperature. We explore this possibility by determining the average color for each image and

relating it to the temperature rating of the image. Color was indeed correlated with temperature

rating (Supplementary Figure 4A). To test the effect of color on our decoding results, we

repeated the analysis, but included average image color as nuisance regressors in the GLM in

order to extract beta weights for color information in the decoding analysis. Regressing out color

did not impact the decoding results (Supplementary Figure 4B); we observed the same decoding

outcomes in PPA and MFG when color was regressed out. Thus, the neural representation of

scene temperature in PPA is not merely based on the color distribution of scene images.

We here provide evidence supporting the notion that representations in PFC generalize across

sensory modalities, such as between the perceptions of images and stones, or images and sounds.

Specifically, our findings are novel for the following aspects. First, we show that generalization

across sensory modalities can occur when sensory information is inferred, not directly perceived.

Although the previous studies have shown that the prefrontal cortex represent sensory experience

regardless of sensory modalities, participants in these studies always experienced direct

stimulations in the corresponding modalities, such as hearing beach sounds and looking at a

beach image (Jung et al., 2018; Vetter et al., 2014). The present study extends these findings by

demonstrating that percepts inferred from a different modality (i.e. temperature or sound cues

inferred from images) can elicit similar neural codes as the direct sensation would.

To summarize, the current study demonstrates that both scene categories and global scene

properties are represented in PFC, however, neural representations of global scene properties in

PFC, not scene categories, are modulated by task context. These findings suggest that PFC

flexibly represents scene content that is relevant to behavioral demands, allowing for efficient

adaptation of behavior to varying situations in the real world.

**References**

Brainard, D. H. (1997). The psychophysics toolbox. *Spatial vision*, *10*(4), 433-436.

Bugatus, L., Weiner, K. S., & Grill-Spector, K. (2017). Task alters category representations in prefrontal

but not high-level visual cortex. *NeuroImage*, *155*, 437-449.

Chadick, J. Z., & Gazzaley, A. (2011). Differential coupling of visual cortex with default or frontal-

parietal network based on goals. *Nature neuroscience*, *14*(7), 830-832.

Chang, C. C., & Lin, C. J. (2011). LIBSVM: A library for support vector machines. *ACM transactions on*

*intelligent systems and technology (TIST)*, *2*(3), 1-27.

Cox, R. W. (1996). AFNI: software for analysis and visualization of functional magnetic resonance

neuroimages. *Computers and Biomedical research*, *29*(3), 162-173.

Destrieux, C., Fischl, B., Dale, A., & Halgren, E. (2010). Automatic parcellation of human cortical gyri

and sulci using standard anatomical nomenclature. *Neuroimage*, *53*(1), 1-15.

Dilks, D. D., Julian, J. B., Paunov, A. M., & Kanwisher, N. (2013). The occipital place area is causally

and selectively involved in scene perception. *Journal of Neuroscience*, 33(4), 1331-1336.

Epstein, R. A., & Baker, C. I. (2019). Scene perception in the human brain. *Annual Review of Vision*

*Science*, 5, 373-397.

Epstein, R., & Kanwisher, N. (1998). A cortical representation of the local visual

environment. *Nature*, 392(6676), 598-601.

Greene, M. R., & Fei-Fei, L. (2014). Visual categorization is automatic and obligatory: Evidence from

Stroop-like paradigm. *Journal of vision*, *14*(1), 14-14.

Greene, M. R., & Oliva, A. (2009). Recognition of natural scenes from global properties: Seeing the

forest without representing the trees. *Cognitive psychology*, 58(2), 137-176.

Grill-Spector, K., & Kanwisher, N. (2005). Visual recognition: As soon as you know it is there, you know

what it is. *Psychological Science*, *16*(2), 152-160.

Griswold, M. A., Jakob, P. M., Heidemann, R. M., Nittka, M., Jellus, V., Wang, J., ... & Haase, A.

(2002). Generalized autocalibrating partially parallel acquisitions (GRAPPA). *Magnetic*

*Resonance in Medicine: An Official Journal of the International Society for Magnetic Resonance*

*in Medicine*, *47*(6), 1202-1210.

Groen, I. I., Greene, M. R., Baldassano, C., Fei-Fei, L., Beck, D. M., & Baker, C. I. (2018). Distinct

contributions of functional and deep neural network features to representational similarity of

scenes in human brain and behavior. *Elife*, *7*, e32962.

Harel, A., Kravitz, D. J., & Baker, C. I. (2014). Task context impacts visual object processing

differentially across the cortex. *Proceedings of the National Academy of Sciences*, *111*(10), E962-

E971.

Jolicoeur, P., Gluck, M. A., & Kosslyn, S. M. (1984). Pictures and names: Making the

connection. *Cognitive psychology*, *16*(2), 243-275.

Jung, Y., Larsen, B., & Walther, D. B. (2018). Modality-independent coding of scene categories in

prefrontal cortex. *Journal of Neuroscience*, 38(26), 5969-5981.

Kravitz, D. J., Peng, C. S., & Baker, C. I. (2011). Real-world scene representations in high-level visual

cortex: it's the spaces more than the places. *Journal of Neuroscience*, *31*(20), 7322-7333.

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences*, *103*(10), 3863-3868.

Li, F. F., VanRullen, R., Koch, C., & Perona, P. (2002). Rapid natural scene categorization in the near

absence of attention. *Proceedings of the National Academy of Sciences*, *99*(14), 9596-9601.

Mack, A., & Rock, I. (1998). *Inattentional blindness*. MIT press

Mack, M. L., & Palmeri, T. J. (2010). Decoupling object detection and categorization. *Journal of*

616           *Experimental Psychology: Human Perception and Performance*, *36*(5), 1067.

617    Mack, M. L., Gauthier, I., Sadr, J., & Palmeri, T. J. (2008). Object detection and basic-level

618           categorization: Sometimes you know it is there before you know what it is. *Psychonomic Bulletin*

619           *& Review*, *15*(1), 28-35.

620    Maguire, E. (2001). The retrosplenial contribution to human navigation: a review of lesion and

621           neuroimaging findings. *Scandinavian journal of psychology*, 42(3), 225-238.

622    McKee, J. L., Riesenhuber, M., Miller, E. K., & Freedman, D. J. (2014). Task dependence of visual and

623           category representations in prefrontal and inferior temporal cortices. *Journal of*

624           *Neuroscience*, *34*(48), 16065-16075.

625    Norman-Haignere, S., Kanwisher, N., & McDermott, J. H. (2013). Cortical pitch regions in humans

626           respond primarily to resolved harmonics and are located in specific tonotopic regions of anterior

627           auditory cortex. *Journal of Neuroscience*, *33*(50), 19451-19469.

628    Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: multi-modal multivariate

629           pattern analysis of neuroimaging data in Matlab/GNU Octave. *Frontiers in neuroinformatics*, *10*,

630           27.

631    Park, S., & Chun, M. M. (2009). Different roles of the parahippocampal place area (PPA) and

632           retrosplenial cortex (RSC) in panoramic scene perception. *Neuroimage*, *47*(4), 1747-1756.

633    Park, S., Brady, T. F., Greene, M. R., & Oliva, A. (2011). Disentangling scene content from spatial

634           boundary: complementary roles for the parahippocampal place area and lateral occipital complex

635           in representing real-world scenes. *Journal of Neuroscience*, 31(4), 1333-1340.

636    Pereira, F., Mitchell, T., & Botvinick, M. (2009). Machine learning classifiers and fMRI: a tutorial

637           overview. *Neuroimage*, *45*(1), S199-S209.

Persichetti, A. S., & Dilks, D. D. (2019). Distinct representations of spatial and categorical relationships

across human scene-selective cortex. *Proceedings of the National Academy of Sciences*, *116*(42),

21312-21317.

Silson, E. H., Gilmore, A. W., Kalinowski, S. E., Steel, A., Kidder, A., Martin, A., & Baker, C. I. (2019).

A posterior–anterior distinction between scene perception and scene construction in human

medial parietal cortex. *Journal of Neuroscience*, 39(4), 705-717.

Silson, E. H., Steel, A. D., & Baker, C. I. (2016). Scene-selectivity and retinotopy in medial parietal

cortex. *Frontiers in human neuroscience*, 10, 412.

Vetter, P., Smith, F. W., & Muckli, L. (2014). Decoding sound and imagery content in early visual

cortex. *Current Biology*, *24*(11), 1256-1262.

Walther, D. B., Caddigan, E., Fei-Fei, L., & Beck, D. M. (2009). Natural scene categories revealed in

distributed patterns of activity in the human brain. *Journal of neuroscience*, *29*(34), 10573-10581.

Walther, D. B., Chai, B., Caddigan, E., Beck, D. M., & Fei-Fei, L. (2011). Simple line drawings suffice

for functional MRI decoding of natural scene categories. *Proceedings of the National Academy of*

*Sciences*, *108*(23), 9661-9666.

Westfall, P. H., & Young, S. S. (1993). *Resampling-based multiple testing: Examples and methods for p-*

*value adjustment* (Vol. 279). John Wiley & Sons.

Zanto, T. P., Rubens, M. T., Thangavel, A., & Gazzaley, A. (2011). Causal role of the prefrontal cortex in

top-down modulation of visual processing and working memory. *Nature neuroscience*, *14*(5),

656-661.

**Supplementary materials**

**Supplementary Figure 1**
Instructions for the rating scales in the temperature judgment task (A), and in the sound-level judgment
task (B).

A. Instruction for the temperature judgment task

Here is the description for our scales!
Please read carefully and make sure you understand what each scale indicates.

**Very cold** - you could see your breath and you would wear gloves

**Cold** - you would wear a jacket and maybe a scarf to go outside

**Average** - you would be comfortable without a jacket! It's like the room temerature.

**Hot** - you would wear a short-sleeve t-shirt to go outside

**Very hot** - you would get sweaty whatever you wear

**Press spacebar to continue!**

B. Instruction for the noise-level judgment task

Here is the description for our scales!
Please read carefully and make sure you understand what each scale indicates.

**Very quiet** - you don't hear any sound from background at all

**Quiet** - you might hear background sounds, but you could clearly hear someone
if they whispered

**Average** - you could hear someone if they whispered, but you might miss some words
because of the background sounds

**Noisy** - you could maintain a normal conversation

**Very noisy** - You would have to raise your voice to be heard

**Press spacebar to continue!**

**Supplementary Figure 2**

**Supp. Figure 2**. Examples of scene images used in the experiment. Based on the behavioral
rating, each image was labeled as either warm or cold (temperature property) and at the same
time, either noisy or quite (sound-level property). Also, these images belong to four basic-level
scene categories: beach, city, forest, or train station.

**Supplementary Figure 3**

Functionally defined somatosensory cortex

**Supp. Figure 3.** The localization of somatosensory cortex, where larger response was observed
when participants were holding the stone in their left hand compared to when the stone stimuli
was taken away (stone > no stone). The voxels where 6 or more participants show significant
contrast (in stone > no stone) were first defined, and then this cluster (in red) was masked by the
anatomical ROI of the right post-central gyrus (depicted in dotted line).

**Supplementary Figure 4**

A. Relationship between CIELAB color values and temperature ratings

B. Decoding of temperature from images with LAB color values regressed out
of the fMRI data (compare to Figure 2A)

**Supp. Figure 4.** A. CIELAB color values (luminance, a, b value for each plot) from individual
images and the group-level average of the temperature rating score for the corresponding images.
Temperature rating was collected in a separate behavioral experiment from a separate group of
participants, and the rating scores were z-scored within each participant. B. Decoding accuracies
of temperature (warm vs. cold) from images when LAB color values were regressed out from
neural signals. * $q < 0.05$, ** $q < 0.01$