Uncovering novel mutational signatures by *de novo* extraction with SigProfilerExtractor

S M Ashiqul Islam[1,2,3], Yang Wu[4], Marcos Díaz-Gay[1,2,3], Erik N Bergstrom[1,2,3], Yudou He[1,2,3], Mark Barnes[1,2,3], Mike Vella[5], Jingwei Wang[6], Jon W Teague[6], Peter Clapham[6], Sarah Moody[6], Sergey Senkin[7], Yun Rose Li[8], Laura Riva[6], Tongwu Zhang[9], Andreas J Gruber[10,11], Raviteja Vangara[12], Christopher D Steele[13], Burçak Otlu[1,2,3], Azhar Khandekar[1,2,3], Ammal Abbasi[1,2,3], Laura Humphreys[6], Natalia Syulyukina[2], Samuel W Brady[14], Boian S Alexandrov[11], Nischalan Pillay[13,15], Jinghui Zhang[14], David J Adams[6], Iñigo Marticorena[6], David C Wedge[10,11], Maria Teresa Landi[9], Paul Brennan[7], Michael R Stratton[6], Steven G Rozen[4], and Ludmil B Alexandrov[1,2,3*]

Affiliations

[1]Department of Cellular and Molecular Medicine, UC San Diego, La Jolla, CA, 92093, USA
[2]Department of Bioengineering, UC San Diego, La Jolla, CA, 92093, USA
[3]Moores Cancer Center, UC San Diego, La Jolla, CA, 92037, USA
[4]Centre for Computational Biology and Programme in Cancer & Stem Cell Biology, Duke NUS Medical School, 169857, Singapore
[5]NVIDIA Corporation, 2788 San Tomas Expressway, Santa Clara, CA, 95051, USA
[6]Cancer, Ageing and Somatic Mutation, Wellcome Sanger Institute, Wellcome Genome Campus, Cambridge, CB10 1SA, UK
[7]Genetic Epidemiology Group, International Agency for Research on Cancer, 69372 Lyon CEDEX 08, France
[8]Helen Diller Family Comprehensive Cancer Center, San Francisco, CA, 94158, USA
[9]Division of Cancer Epidemiology and Genetics, National Cancer Institute, Bethesda, MD, 20892, USA
[10]Big Data Institute, Nuffield Department of Medicine, University of Oxford, Oxford, OX3 7LF, UK
[11]Manchester Cancer Research Centre, The University of Manchester, Manchester, M20 4GJ, UK
[12]Theoretical Division, Los Alamos National Laboratory, Los Alamos, NM, 87545, USA
[13]Research Department of Pathology, Cancer Institute, University College London, London, WC1E 6BT, UK
[14]Department of Computational Biology, St. Jude Children's Research Hospital, Memphis, 38105, Tennessee, USA
[15]Department of Cellular and Molecular Pathology, Royal National Orthopaedic Hospital NHS Trust, Stanmore, Middlesex, HA7 4LP, UK

*Correspondence should be addressed to L2alexandrov@health.ucsd.edu.

ABSTRACT

Mutational signature analysis is commonly performed in genomic studies surveying cancer and

normal somatic tissues. Here we present SigProfilerExtractor, an automated tool for accurate *de*

novo extraction of mutational signatures for all types of somatic mutations. Benchmarking with a

total of 33 distinct scenarios encompassing 1,106 simulated signatures operative in more than

200,000 synthetic genomes demonstrates that SigProfilerExtractor outperforms ten other tools

across all datasets with and without noise. For simulations with 5% noise, reflecting high-quality

genomic datasets, SigProfilerExtractor outperforms other approaches by elucidating between

20% and 50% more true positive signatures while yielding more than 5-fold less false positive

signatures. Applying SigProfilerExtractor to 2,778 whole-genome sequenced cancers reveals

three previously missed mutational signatures. Two of the signatures are confirmed in

independent cohorts with one of these signatures associating with tobacco smoking. In summary,

this report provides a reference tool for analysis of mutational signatures, a comprehensive

benchmarking of bioinformatics tools for extracting mutational signatures, and several novel

mutational signatures including a signature putatively attributed to direct tobacco smoking

mutagenesis in bladder cancer and in normal bladder epithelium.

INTRODUCTION

De novo extraction of mutational signatures[1] is an unsupervised machine learning approach where a matrix, M, which corresponds to the somatic mutations in a set of cancer genomes under a mutational classification[2], is approximated by the product of two low-rank matrices, S and A. The matrix S reflects the set of mutational signatures while the matrix A encompasses the activities of the signatures; an activity corresponds to the number of mutations contributed by a signature in a sample. Algorithmically, *de novo* extraction of mutational signatures has relied on nonnegative matrix factorization (NMF)[3] or on approaches mathematically analogous to NMF[4-6]. The main advantage of NMF over other factorization approaches is its ability to yield nonnegative factors that are part of the original data, thus, allowing interpretation of the identified nonnegative factors[3]. Biologically, mutational signatures extracted from cancer genomes have been attributed to exposures to environmental carcinogens, failure of DNA repair pathways, infidelity/deficiency of replicating polymerases, iatrogenic events, and others[7-14].

Since we introduced the mathematical concept of mutational signatures[1], a number of computational frameworks have been developed for performing *de novo* extraction of mutational signatures (**Table 1**)[15-25]. Notably, the majority of existing *de novo* extraction tools *(i)* predominately support the simplest mutational classification, *viz.*, SBS-96 which encompasses single base substitutions with their immediate 5' and 3' sequence context[2]; *(ii)* lack automatic selection for the number of mutational signatures; *(iii)* do not identify a robust solution leading to different results following re-analysis of the same dataset; *(iv)* require pre-selection of a large number of priors and/or hyperparameters; *(v)* do not decompose *de novo* signatures to the set of

reference COSMIC signatures[11]. Importantly, there has been no extensive benchmark of the

existing tools for *de novo* extraction leading to uncertainty in regard to their performance.

To address these limitations, here, we present SigProfilerExtractor – a reference tool for *de novo*

extraction of mutational signatures. SigProfilerExtractor allows analysis of all types of

mutational classifications, performs automatic selection of the number of signatures, yields

robust solutions, requires only minimum setup, and decomposes *de novo* extracted signatures to

known COSMIC signatures. A comprehensive benchmark including 2,879 applications of

SigProfilerExtractor and ten other tools across a total of 33 distinct scenarios reveals that

SigProfilerExtractor is robust to noise and it outperforms all other computational tools for *de*

novo extraction of mutational signatures (**Supplementary Tables 1–3**). Applying

SigProfilerExtractor to the recently published set of 2,778 whole-genome sequenced cancers

from the Pan-Cancer Analysis of Whole Genomes (PCAWG) project[26] elucidates three novel

signatures that were not found in the original PCAWG analysis of mutational signatures[11]. Two

of the signatures are confirmed in independent cohorts and a putative etiology of tobacco-

associated mutagenesis is attributed to one of these signatures.

RESULTS

Overview of SigProfilerExtractor and its implementation

SigProfilerExtractor is implemented as a Python package, with an R wrapper, allowing users to run it in both Python and R environments: https://github.com/AlexandrovLab/SigProfilerExtractor . The tool is also extensively documented including a detailed Wiki page: https://osf.io/t6j7u/wiki/home/. By default, the tool requires only a single parameter – the input dataset containing the mutational catalogues of interest. SigProfilerExtractor supports most commonly used formats outputted by variant calling algorithms (*e.g.*, VCF and MAF), which are internally converted to a matrix, *M,* by SigProfilerMatrixGenerator[2]. SigProfilerExtractor can also be applied to a text file containing a matrix, *M*, thus supporting nonnegative matrix factorization for any custom matrix dataset. By default, the tool decomposes the matrix *M* searching for an optimal solution between 1 and 25 mutational signatures (**Figure 1*a***). For each decomposition, SigProfilerExtractor performs 500 independent factorizations and, for each repetition, the matrix *M* is first Poisson resampled and normalized and, subsequently, factorized with the multiplicative update NMF algorithm[3] by minimizing an objective function based on the Kullback–Leibler divergence measure[27] (**Figure 1*b***). Custom partition clustering, that utilizes the Hungarian algorithm[28] for comparing different repetitions, is applied to the 500 factorizations to identify stable solutions[29] (**Figure 1*b***). Specifically, SigProfilerExtractor selects the centroids of stable clusters as optimal solutions, thus, making these solutions resistant to fluctuations in the input data and to the lack of uniqueness of NMF due to the potential existence of multiple convergent stationary points in the solution[30]. Lastly, when applicable, the optimal set of *de novo* signatures are matched to the set

of reference COSMIC mutational signatures (**Figure 1c**) with any *de novo* signature reported as

novel when it cannot be decomposed by a combination of known COSMIC signatures.

Framework for benchmarking tools for de novo extraction of mutational signatures

To allow comprehensive benchmarking of tools for *de novo* extraction of mutational signatures,

more than 200,000 synthetic cancer genomes were generated with known ground-truth

mutational signatures (**Supplementary Note 1**). These synthetic data included 32 distinct

noiseless scenarios and one scenario with five different levels of noise. Each scenario contained

between 3 and 40 known signatures operative in 200 to 3,000 simulated cancer genomes

(**Supplementary Tables 1–3**). Some of the scenarios were generated up to 20 times to account

for variability in the simulated data. The majority of noiseless scenarios (20/32) were based on

SBS-96 mutational classification; 12 scenarios based on extended mutational classifications, *i.e.,*

matrices with more than 96 mutational channels, were also included (**Supplementary Table 3**).

To avoid bias in evaluating each tool's performance, three sets of SBS-96 mutational signatures

were used for generating the synthetic data: *(i)* COSMICv3 reference signatures[11]; *(ii)* SA

signatures previously extracted by SignatureAnalyzer[11]; and *(iii)* randomly generated signatures.

For presentation simplicity, scenarios were labeled based on their complexity as easy, medium,

or hard. Easy scenarios were generated using ≤5 signatures and provide a good indication of each

tool's performance on approximately 7.4% of human cancer types (*e.g.*, pediatric brain tumors).

Medium scenarios contained 11 to 21 signatures and biologically reflect 15.9% of cancer types

(*e.g.*, cervical cancer). Hard scenarios have more than 25 signatures and reflect 59.5% of human

cancer types (*e.g.*, breast, lung, liver, *etc.*) as well as pan-cancer datasets. In addition to the 32

noiseless scenarios, one SBS-96 scenario with five different levels of noise (average noise per

sample ranging between 0% and 10%) was included in the benchmark (**Supplementary Note 1**).

To compare the performance between different tools for *de novo* extraction of mutational

signatures, we developed a standard set of evaluation metrics (**Supplementary Figure 1**).

Specifically, each *de novo* extracted signature is classified as either a *true positive* (TP), *false*

positive (FP), or *false negative* (FN) signature. An extracted signature is considered TP if it

matches one of the ground-truth signatures above a cosine similarity threshold of 0.90. In

contrast, a signature is classified as FP when it has a maximum cosine similarity below 0.90 with

all ground-truth signatures. Lastly, FN signatures are ground-truth signatures that were not

detected in the data. These standard metrics allow calculating each tool's precision, sensitivity,

and F_1 score. Precision is defined as $\frac{TP}{TP+FP}$, sensitivity as $\frac{TP}{TP+FN}$, and F_1 score is the harmonic

mean of the precision and sensitivity: $2 * \frac{Precision * Sensitivity}{Precision + Sensitivity}$.

Benchmarking SigProfilerExtractor and ten other tools using SBS-96 noiseless data

SigProfilerExtractor and ten other tools (**Table 1**) were first applied to all noiseless scenarios

based on the SBS-96 mutational classification. Each tool was applied to each scenario by using

its suggested method for selecting the number of operative signatures and, with the exception of

SignatureAnalyzer which lacks this capability, by forcing each tool to extract the known number

of ground-truth signatures. Results from the suggested approach reflect the expected outcome

from running a tool on an unknown dataset, while results from the forced approach allow

understanding limitations in each tool's implementation. Our evaluation reveals that most tools

are able to successfully extract mutational signatures from easy scenarios with the majority of F_1

scores between 0.90 and 1.00 (**Figure 2a**). This is perhaps unsurprising as many of these tools

used synthetic data with ≤5 signatures to evaluate their performance in the respective original

publications[15-25]. In contrast, medium scenarios have proven to be a challenge for the majority of

tools with only SigProfilerExtractor and SignatureAnalyzer exhibiting an F_1 score above 0.90.

All tools had worst performance for the hard set of scenarios with F_1 scores below 0.70; only

SigProfilerExtractor had an F_1 score above 0.85 (**Figure 2a**).

To evaluate whether the type of ground-truth signatures affects the *de novo* extraction, we

compared the ratio of F_1 scores (rF_1) from scenarios generated using COSMIC, SA, or random

signatures (**Figure 2b**). Most tools had similar performance ($rF_1 \approx 1$) between COSMIC and

random signatures and worst performance with SA signatures ($rF_1 < 1$). SomaticSignatures was an

exception as it performed well on random signatures but had similarly suboptimal performance

on COSMIC and SA signatures. SigProfilerExtractor outperformed all other tools regardless of

whether the synthetic data were generated using COSMIC, SA, or random signatures

(**Supplementary Table 1**).

To examine the performance of *de novo* extraction between the suggested and forced selection of

the total number of signatures, we evaluated rF_1 across all medium and hard scenarios (**Figure**

2c). SigProfilerExtractor exhibited almost identical F_1 scores between the suggested and forced

selection indicating a good performance of the automatic selection algorithm. Most other tools

had similar F_1 scores between the suggested and forced selection albeit with more variability

across the different scenarios (**Figure 2c**). For example, MutSpec had $rF_1 \approx 1$ in both medium and

hard scenarios indicating that MutSpec is performing worse than SigProfilerExtractor (**Figure**

2a) not because of its algorithm for selecting the total number of signatures but likely due to its

implementation of the utilized numerical factorization. SigneR (hard scenarios), SigMiner

(medium), and SigFit (all) had lower F_1 scores for automatic solutions compared to forced

solutions ($rF_1<1$), thus, indicating that their automatic approaches for selecting the total number

of signatures are not optimally performing (**Figure 2c**). Surprisingly, EMu had higher F_1 scores

for automatic solutions in some hard scenarios. Considering the overall performance of EMu

(**Figure 2a**), this outcome likely reflects the lack of convergence during the minimization of the

EMu objective function for certain number of signatures in the hard scenarios.

Overall, across all suggested extractions from noiseless medium and hard scenarios,

SigProfilerExtractor outperformed all other tools. SigProfilerExtractor was able to identify

between 7% and 25% more true positive signatures while yielding between 3.7-and 16-fold less

false positive signatures compared to the next six best performing tools: SignatureAnalyzer,

SigneR, MutationalPatterns, MutSpec, SomaticSignatures, and SignatureTools (**Figure 2d** and

Supplementary Table 1).

Extended benchmarking of SigProfilerExtractor and the other six top performing tools

The reported comparisons for SBS-96 scenarios rely on a cosine similarity ≥0.90 for determining

TP signatures and <0.90 for determining FP signatures. Note that a cosine similarity ≥0.90 is

highly unlikely to happen purely by chance (p-value = 5.90×10^{-9}) as two random nonnegative

vectors are expected to have an average cosine similarity of 0.75 purely by chance[31].

SigProfilerExtractor's performance does not depend on the specific value of the cosine similarity

threshold (**Figure 3a**) as the tool consistently outperforms other bioinformatics approaches for

almost any value of the threshold above 0.80 (p-value: 0.057). Cosine similarity thresholds

below 0.80 were not explored as extracted signature may be similar to ground-truth signatures

purely by chance.

Additional benchmarking was performed by generating 12 scenarios simulated using between 3

and 30 signatures with an extended number of mutational channels (**Supplementary Note 1**).

SigProfilerExtractor and SignatureAnalyzer are the only two tools that support analysis of

custom size matrices and also provide GPU support (**Table 1**), thus, allowing analysis of data

with extended number of mutational channels within a reasonable timeframe. In contrast, all

other tools rely solely on CPU implementations with full runs expected to take many months for

each tool applied to these scenarios (**Table 1**). SigProfilerExtractor and SignatureAnalyzer

exhibited similar performance on the extended noiseless scenarios to that observed on SBS-96

noiseless scenarios. Overall, SigProfilerExtractor outperformed SignatureAnalyzer with average

F1 scores of 0.92 and 0.85, respectively (**Supplementary Table 2**).

To further compare SigProfilerExtractor with the other six top performing tools, we applied each

tool to a dataset with 30 ground-truth SBS-96 signatures operative in 1,000 genomes and random

noise between 0% and 10%. Analysis for each noise level was repeated 20 times to account for

any variability in the noise. SigProfilerExtractor, SomaticSignatures, MutSpec,

SignatureToolsLib were robust to noise with mostly unaffected performance (**Figure 3b** and

Supplementary Table 3). In contrast, SignatureAnalyzer, SigneR, and MutationalPatterns were

susceptible to noise (**Figure 3b**). For example, 2.5% noise reduced SignatureAnalyzer's F_1 from

0.76 to 0.66 while 10% noise reduced its F_1 to 0.07. Similarly, 10% noise reduced the F_1 of

SigneR from 0.61 to 0.43 and the F_1 of MutationalPatterns from 0.60 to 0.37.

SignatureAnalyzer's reduced performance on data with noise is due to its automated approach

for selecting total number of signatures. SignatureAnalyzer uses automatic relevance

determination[32] for selecting the number of signatures with this number increasing from 26 (no

noise; 30 ground-truth signatures) to 96 signatures (10% noise; **Supplementary Table 3**). In

contrast, SigneR and MutationalPatterns exhibit similar performance between forced and

suggested solutions on data with noise (**Supplementary Table 3**) indicating that their reduced

performance is likely due to the numerical implementation of their respective factorization

approaches.

SigProfilerExtractor outperformed all other tools regardless of the levels of noise. Simulations

with 5% noise reflect genomics datasets with ~0.95 average sensitivity and precision of single

base substitutions, similar to the recently published PCAWG cohort which has 95% sensitivity

(90% confidence interval, 88–98%) and 95% precision (90% confidence interval, 71–99%)[26].

For simulations with 5% noise, SigProfilerExtractor was able to identify between 20% and 50%

more true positive signatures while yielding more than 5-fold less false positive signatures

compared to the next six best performing tools: SignatureAnalyzer, SigneR, MutationalPatterns,

MutSpec, SomaticSignatures, and SignatureTools (**Figure 3c** and **Supplementary Table 3**).

Analysis of 2,778 whole-genome sequenced human cancers with SigProfilerExtractor

To demonstrate its ability to yield novel biological results, SigProfilerExtractor was applied to

the recently published set of 2,778 whole-genome sequenced cancers[26]. As previously done in

our original PCAWG analysis of mutational signatures[11], extraction of mutational signatures was

performed within each cancer type as well as across all samples (**Supplementary Data**). In

addition to all previously detected signatures[11], three novel mutational signatures were identified

in the PCAWG dataset: SBS92, SBS93, and SBS94 (**Figure 4** and **Supplementary Table 4**).

Signature SBS92 was found predominately in PCAWG bladder cancers; the signature was

characterized by T>C mutations with strong transcriptional strand bias consistent with damage

on purines for all types of single base substitutions (**Figure 4*a***). Signature SBS92 was 9-fold

elevated (**Figure 4*d***; p-value: 7.6×10^{-3} using Wilcoxon rank sum test) in bladder cancers of ever

smokers compared to never smokers in the PCAWG cohort. An almost identical signature was

identified by re-analyzing a recently published cohort of 88 whole-genome sequenced

microbiopsies of histologically normal urothelium[33] with the similarity extending to both

trinucleotide context and transcriptional strand bias (**Figure 4*a***; cosine similarity: 0.98; p-value <

10^{-256}). Indeed, this signature was reported in the original publication and found to be enriched in

smokers[33]. In our analysis, SBS92 was found to be 3-fold elevated in the normal urothelium of

tobacco ever smokers compared to never smokers (**Figure 4*d***; p-value: 8.3×10^{-3} using

Wilcoxon rank sum test).

Signature SBS93 was identified almost exclusively in PCAWG stomach cancers. SBS93 was

characterized by T>C and T>G mutations with a strand bias consistent with damage on

pyrimidines for TpTpA contexts (mutated base underlined; **Figure 4*b***). *De novo* extraction from

the Mutographs cohort of 552 whole-genome sequenced esophageal squamous cell carcinomas[34],

a cancer type not included in the PCAWG dataset[26], identified an analogous mutational signature

with the similarity extending to both trinucleotide context and transcriptional strand bias (**Figure**

4b; cosine similarity: 0.88; p-value: 1.1×10^{-6}). Signature SBS94 was found at high levels in a

single colorectal PCAWG cancer with smaller contributions to another 8 colorectal cancers. The

pattern of SBS94 was characterized by C>A mutations with a strand bias indicative of damage

on guanine (**Figure 4c**). Validation of somatic mutations by visual inspection confirmed that

98% of mutations contributed by SBS94 are likely real. Signatures SBS93 and SBS94 did not

associate with any of the available PCAWG metadata[26] and their etiologies remain unknown.

DISCUSSION

The performed large-scale benchmarking demonstrates that SigProfilerExtractor outperforms ten

other tools for *de novo* extraction of mutational signatures for noiseless datasets as well as for

datasets containing matrices with different levels of random noise. Importantly,

SigProfilerExtractor generates almost no false positive signatures while still identifying a higher

number of true positive signatures when compared to any of the other tools (**Figure 2d** and

Figure 3c). *De novo* extraction of mutational signatures relies both on a factorization approach

and on a model selection algorithm for determining the total number of operative signatures

(**Figure 1**). Benchmarking with forced model selection, where tools were required to extract the

known number of ground-truth mutational signatures, reveals that SigProfilerExtractor's

factorization performs better when compared to the factorizations of other tools (**Figure 2a** and

Supplementary Tables 1-3). Similarly, benchmarking with suggested model selection, which

most closely matches analysis of a real dataset with unknown number of signatures, further

demonstrates SigProfilerExtractor's ability to reveal novel biological results (**Figure 2a** and

Supplementary Tables 1-3).

While our benchmarking evaluated ten additional tools, six of the ten tools internally rely on the

same computational engine. Maftools, MutationalPatterns, MutSpec, SignatureToolsLib,

SigMiner, and SomaticSignatures use the NMF R package[35] to perform their factorization (**Table

1**), albeit with slightly different hyperparameters and, in some cases, distinct pre-processing of

the input matrix. Predictably, these six tools have similar performance across many of the

scenarios (**Supplementary Tables 1-3**). SigFit also uses a previously developed nonnegative

factorization method, *viz.*, Stan R package[36]. In contrast, EMu, SignatureAnalyzer, SigneR, and

SigProfilerExtractor provide original implementations of their factorization algorithms (**Table**

1). EMu was originally developed and tested on small datasets (*e.g.,* 21 breast genomes)[15] and its

benchmarking performance is perhaps unsurprising considering the large number of synthetic

samples used in all scenarios. Surprisingly, the original implementations of SignatureAnalyzer

and SigneR were susceptible to noise, yielding high numbers of false-positive signatures (**Figure**

3b).

Six of the other ten tools did not provide an automatic approach for selecting the total number of

operative signatures in a dataset (**Table 1**). Instead, these tools offered methodologies for

manually selecting the optimal number of signatures bringing user-dependence and arbitrariness

in selecting solutions. EMu, SigFit, SignatureAnalyzer, SigMiner, SigneR, and

SigProfilerExtractor provided capabilities for automatically selecting the total number of

signatures. EMu and SigneR select the total number of signatures using Bayesian information

criterion (BIC)[37], while SignatureAnalyzer and SigMiner utilize automatic relevance

determination (ARD)[32]. SigFit's selection approach is based on the Elbow method[38].

SigProfilerExtractor leverages a modified version of the NMFk selection approach which was

previously tested on more than 55,000 synthetic random matrices with pre-determined latent

factors and shown to outperform other model selection approaches[39]. Importantly, our

simulations demonstrate that SigProfilerExtractor's model selection is robust to noise while the

implemented BIC and ARD approaches are affected even by low levels of noise (**Figure 3b**).

In addition to outperforming ten other tools on simulated datasets, SigProfilerExtractor is able to

reveal additional biological results as demonstrated by identifying three novel signatures from

reanalysis of the PCAWG dataset. Importantly, SigProfilerExtractor identifies signature SBS92

(**Figure 4**) which is associated with tobacco smoking in whole-genome sequenced bladder

cancers and in whole-genome sequenced microbiopsies from normal bladder urothelium. The

strong transcriptional strand bias observed in SBS92 is indicative of an environmental mutagen

exposure that damages purines. Tobacco smoke is a complex mixture of at least 60 chemicals[14],

many capable of causing damage on purines. Interestingly, our and other prior analyses of exome

sequenced bladder cancers from The Cancer Genome Atlas (TCGA) project[14,40] did not reveal

SBS92. Reanalysis of the set of TCGA bladder cancer exomes[41] with SigProfilerExtractor was

also unable to detect SBS92 (**Supplementary Data**). We suspect that the lack of SBS92 in the

TCGA bladder cancers was due to the use of exome sequencing; note that SBS92 is

predominately found in intergenic regions (**Figure 4a**) with most samples expected to have less

than 15 mutations from SBS92 in their exomes. To confirm this hypothesis, we downsampled the

whole-genome sequenced bladder cancers and the whole-genome sequenced microbiopsies from

normal bladder urothelium to exomes. SigProfilerExtractor's analysis of these downsampled

genomes was unable to detect SBS92 confirming that exome sequencing is insufficient to

identify signature SBS92 (**Supplementary Data**).

In summary, here we report SigProfilerExtractor – a computational tool for *de novo* extraction of

mutational signatures. We demonstrate that SigProfilerExtractor outperforms ten other tools by

conducting the largest benchmarking of bioinformatics approaches for extracting mutational

signatures. Further, we apply SigProfilerExtractor to 2,778 whole-genome sequenced cancers

and reveal several novel mutational signatures including a signature putatively attributed to

tobacco smoking mutagenesis in bladder cancer and in normal bladder epithelium.

ONLINE METHODS

Computational implementation of SigProfilerExtractor and its seven modules

The implementation of SigProfilerExtractor can be separated into seven distinct modules which

are packaged together into a single bioinformatics tool. *Module 1* processes the initial input data,

which can be provided as either a mutational catalogue containing a set of somatic mutations or a

mutational matrix. *Module 2* is responsible for resampling and normalization of the mutational

matrix prior to performing nonnegative matrix factorization. *Module 3* performs matrix

factorization using nonnegative matrix factorization with multiple replicates. *Module 4* utilizes

custom clustering to derive consensus solutions and to perform model selection. *Module 5*

decomposes the derived set of *de novo* signatures to a set of previously derived COSMIC

signatures. *Module 6* is responsible for calculating the activities of different signatures in

individual samples. *Module 7* handles the extensive outputting and plotting of the different

analysis performed by SigProfilerExtractor. In principle, each of these modules allows extensive

customization. SigProfilerExtractor provides a seamless integration of these seven modules that

allows using them in an orchestrated and preconfigured manner with little input from a user.

Module 1: Processing of input mutational catalogues or input mutational matrices

SigProfilerExtractor deciphers mutational signatures from a mutational matrix M with t rows

and n columns; rows represent mutational channels while columns reflect individual cancer

samples (**Figure 1***a*). The value of each cell in the matrix, M, corresponds to the number of

somatic mutations from a particular mutational channel in a given sample. The mutational matrix

can be provided as a text file with the first column containing the names of the mutational

channels and the first row containing the names of the examined samples. Alternatively, users

can provide a mutational catalogue of somatic mutations in a commonly used format (*e.g.,* VCF,

MAF, *etc.*) and this mutational catalogue will be internally converted into the appropriate

mutational matrix by SigProfilerMatrixGenerator[2].

Module 2: Resampling of the input mutational matrix and normalizing the resampled matrix

SigProfilerExtractor does not factorize the original input matrix. Rather, prior to performing

matrix factorization, SigProfilerExtractor performs independent Poisson resampling of the

original matrix for each replicate[1]. As such, the matrix factorized in each replicate is never the

same for a given value of *k* (**Figure 1*b***). The resampling is performed to ensure that Poisson

fluctuations of the matrix do not impact the stability of the factorization results. Additional

normalization is performed after resampling to overcome potential skewing of the factorization

from any hypermutators. SigProfilerExtractor supports four standard normalization methods[42]:

(i) Gaussian mixture model (GMM) normalization (default); *(ii)* 100X normalization; *(iii)* log2

normalization; *(iv)* no normalization. *No normalization* does not perform any additional

transformation on the Poisson resampled matrix. In *log2 normalization*, the sum of each column

in the matrix is derived and logarithm with base 2 is calculated for each of these sums. Each cell

in a column of the matrix is multiplied by the log2 of the column-sum and subsequently divided

by the original column sum. In *100X normalization*, the sum of each column in the matrix is

derived. For each column where the sum exceeds 100 times the number of mutational channels

(*i.e.*, 100 times the number of rows in the matrix), each cell in the column is multiplied by the

100 times the number of mutational channels and subsequently divided by the original column

sum. This normalization ensures that no sample has a total number of mutations above 100 times

the number of mutational channels. *GMM normalization* encompasses a two-step process. The

first step derives the normalization cutoff value in a data-driven manner using a Gaussian

mixture model (GMM). The second step normalizes the appropriate columns using the derived

cutoff value. The first step uses a GMM to separate the samples into two groups based on their

total number of mutations; the total number of mutations in a sample reflects the sum of a

column in the matrix. The group with larger number of samples is subsequently selected, and the

same process is applied iteratively until it converges. Convergence is achieved when the mean of

the two groups is separated by no more than four standard deviations of the larger group. A

cutoff value is derived as the average value plus two standard deviations from the total number

of somatic mutations in the last large group. If the derived cutoff value is below 100 times the

number of mutational channels, the cutoff value is adjusted to 100 times the number of

mutational channels. For each column where the sum exceeds the derived cutoff value, each cell

in the column is multiplied by the cutoff value and subsequently divided by the original column

sum. Note that no normalization is performed if the means of the first two groups are not

separate by at least four standard deviations. In all cases, columns with a sum of zero, reflecting,

genomes without any somatic mutations, are ignored to avoid division by zero.

Module 3: Matrix Factorization Using Nonnegative Matrix Factorization with Replicates

By default, SigProfilerExtractor factorizes the matrix M with different ranks searching for an

optimal solution between $k=1$ and $k=25$ mutational signatures. For each value of k, by default,

the tool performs 500 independent nonnegative matrix factorizations of the normalized Poisson

resampled input matrix. Thus, for each value of k, SigProfilerExtractor generates 500 distinct

factorizations of normalized Poisson resampled matrices resulting into 500 different matrices S,

each matrix reflecting the patterns of the *de novo* mutational signatures, and 500 different

matrices *A*, each matrix reflecting the activities of the *de novo* mutational signatures (**Figure 1b**).

To perform each of these factorizations, SigProfilerExtractor utilizes a custom implementation of

the multiplicative update algorithm[3]. Specifically, SigProfilerExtractor initializes the *S* and *A*

matrices in the first step of the factorization using either random initial conditions (default) or

one of the derivatives of nonnegative double singular vector decomposition[43].

SigProfilerExtractor provides internal support for minimizing three different objective functions

based on: *(i)* generalized Kullback-Leibler updates (default); *(ii)* Euclidean updates; *(iii)* Itakura-

Saito updates. By default, the tool performs all factorization using multithreading of central

processing units (CPUs) and also provides support for factorization using graphics processing

units (GPUs) by leveraging PyTorch[44]. In all cases, by default, the implemented minimization

performs at least 10,000 iterations (also known as NMF updates or NMF multiplicative update

steps) with a maximum of 1,000,000 iterations. By default, the convergence tolerance of the

algorithm is set to 10^{-15}. Note that SigProfilerExtractor allows configuring all factorization

parameters.

Module 4: Custom partition clustering and performing model selection

The previously described *Module 3* generates a number of sets with each set containing, by

default, 500 different matrices *S*, where each matrix reflects the patterns of *de novo* mutational

signatures for a particular factorization of a normalized Poisson resampled matrix. One set,

containing 500 different matrices *S*, is generated for each of the interrogated total number of

operative signatures, *k*, with a default range for *k* between 1 and 25 signatures. For each value of

k, *Module 4* first performs custom clustering of the *S* matrices and, subsequently, applies a

modified version of the NMFk model selection approach to select the optimal value of k[39]

(**Figure 1*b***). Specifically, for each value of k, the clustering is initialized with k random

centroids. One of the ***S*** matrices is randomly chosen, and its columns matched to the most similar

centroids with no two columns assigned to the same cluster. The process is repeated until the

columns of all ***S*** matrices in the set are assigned to their respective clusters. SigProfilerExtractor

implements the Hungarian algorithm[28] to pair consensus vectors from two matrices (*i.e.,* cluster

centroids and mutational signature from a matrix ***S***); the Hungarian algorithm maximizes the

total cosine similarities of all paired vectors between two matrices[28]. After assigning all columns

to a cluster, the centroids of each cluster are recalculated by evaluating the average of all

columns/vectors in a cluster. This process continues iteratively until the average silhouette

coefficient converges (*i.e.,* its value does not change by more than 10^{-12}). After convergence for a

given value of k, the centroids of the clusters are reported as consensus mutational signatures, an

overall reconstruction error is calculated for describing the original input matrix, ***M***, and stability

is calculated for each signature by computing the silhouette value[45] of the cluster corresponding

to that signature (**Figure 1*b***). The silhouette value of a cluster measures the similarities of the

objects assigned to that cluster compared to any other cluster. Silhouette values range from -1.0

to +1.0 with values above zero indicating that, on average, objects have a higher similarity with

their own cluster compared to their nearest clusters. Note that signatures with low stability

correspond to a lack of uniqueness of the NMF due to Poisson resampling and/or to the potential

existence of multiple convergent stationary points in the NMF solution[30].

Our custom clustering is performed for each of the interrogated total number of operative

signatures, k, with a default range for k between 1 and 25 signatures. After performing clustering,

for each value of k, one has derived: *(i)* the consensus set of mutational signatures; *(ii)* an overall

reconstruction error for describing the original input matrix; and *(iii)* stability value for each of

the identified consensus mutational signatures.

SigProfilerExtractor performs a solution selection based on the stability of signatures in a

solution and the ability of these signatures to reconstruct the original input matrix. By default,

SigProfilerExtractor will consider solutions stable if the signatures derived in the solution have

an average stability above 0.80 with no individual signature having stability below 0.20. To

reduce overfitting, the tool also measures the information gained from the extracted set of

signatures in each solution. SigProfilerExtractor compares, using Wilcoxon rank-sum tests, the

reconstruction errors across all samples from the stable solution with the greatest number of

signatures to the reconstruction errors across all samples from stable solutions with lower

number of signatures. Stable solutions with lower number of signatures are compared in a

decreasing order to their total number of signatures with comparison stopping if the Wilcoxon

rank-sum test yields a *p-value* below 0.05 (*i.e.*, reflecting that a solution does not describe the

original data as good as the stable solution with the greatest number of signatures). The stable

solution with lowest number of signatures and a Wilcoxon rank-sum test *p-value* above 0.05 is

selected as the optimal solution. If no solution has a Wilcoxon rank-sum test *p-value* above 0.05,

the stable solution with the greatest number of signatures is selected as the optimal solution. Note

that while SigProfilerExtractor selects an optimal solution, it outputs all the information

necessary to evaluate mutational signatures and their activities for all other stable and unstable

solutions.

Module 5: Decomposing de novo extracted signatures to known COSMIC signatures

SigProfilerExtractor provides a module for decomposing each of the *de novo* extracted

mutational signatures to a set of previously derived signatures. By default, the tool decomposes

each of the signatures in the optimal solution to a set of COSMICv3 reference signatures[11] with

support for signatures of single base substitutions (SBS), doublet base substitutions (DBS), and

small insertions and deletions (ID). Since the SBS COSMICv3 reference signatures were derived

under the SBS-96 classification[2], any extended classification of single base substitutions (*e.g.*,

SBS-288 and SBS-1536)[2] is first collapsed to the SBS-96 classification and, subsequently,

decomposed to the COSMICv3 reference signatures[11]. The decomposition functionality

leverages nonnegative least square (NNLS) algorithm[46] as its main computational engine. A

mixture of addition and removal steps (add-remove functionality) were developed to estimate the

list of COSMIC signatures for a *de novo* signature. Specifically, for each *de novo* signature, a

COSMIC signature is iteratively added to a list of signatures used to explain the *de novo*

signature, NNLS is applied, and the signature which addition causes the greatest decrease of the

L2 error is selected. If this greatest decrease is more than a specific threshold (default value of

0.05) then the signature is included in the list of signatures used to explain the *de novo* signature.

The addition is immediately followed by a removal step. Each COSMIC signature in the list of

signatures used to explain the *de novo* signature are iteratively removed, NNLS is applied, and

the signature that causes the least decrease of the L2 error is selected. If this least decrease is less

than a specific threshold (default value of 1%) then the signature is removed from the list of

signatures used to explain the *de novo* signature. The addition and removal steps are iterated until

no signatures are added or removed from the list of signatures used to explain the *de novo*

signature. Several previously implemented rules for mutational signatures are incorporated by

default in the decomposition module[11]. Specifically, for signatures of single base substitutions:

(i) the list of signatures used to explain the *de novo* signature is initialized with clock-like

signatures SBS1 and SBS5;[12] *(ii)* biologically connected signatures are included as previously

done in Ref [11] (*e.g.,* if SBS17a is included in the list then SBS17b is also included the list). The

decomposition module is highly customizable as it allows changing all default parameters as

well as adding additional new rules or removing existing rules for inclusion and exclusion of

particular signatures.

Module 6: Evaluating activities of mutational signatures in individual samples

De novo extracted and COSMIC derived signatures are refitted to individual samples using

nonnegative least squares (NNLS)[46]. *Module 6* internally utilizes the add-remove functionality of

Module 5 with each sample in the original matrix, **M**, being individually examined. For *de*

novo mutational signatures, all *de novo* signatures are initially added to the list of signatures used

to explain the sample and a removal step with a cutoff of 2% is applied. To assign COSMIC

signatures in a sample, the module first derives the set of *de novo* signatures in that sample.

Decomposition to the COSMICv3 signatures using *Module 5* is performed for each of the *de*

novo signatures and the identified COSMICv3 signatures are refitted using the add-remove

functionality with a removal and addition cutoffs set at 5%. Finally, the activity matrix is

constructed by combining the activity vectors generated for all samples in the dataset.

Module 7: Outputting and plotting of analysis results

All previous modules make use of *Module 7* for outputting and plotting of the generated results.

It should be noted that SigProfilerExtractor provides extensive output for the interrogated total

number of operative signatures, *k*, with a default range of *k* between 1 and 25 signatures. For

each value of *k*, SigProfilerExtractor outputs the set of operative *de novo* mutational signatures,

the activities of the operative signatures, and an extensive set of information related to individual

samples, individual *de novo* signatures, and the overall convergence of the factorization and

clustering. *Module 7* also provides additional information when ran in debug mode. In addition

to outputting information, SigProfilerExtractor also generates a bouquet of plots both for each

value of *k* as well as for the suggested optimal solution. SigProfilerExtractor utilizes all

previously implemented plots in SigProfilerPlotting[2] as well as includes a number of newly

developed plots.

548
549
Analysis of the genomics data from cancer and normal somatic tissues

For all examined cancer and normal somatic tissues, *de novo* extraction of mutational signatures

was performed with SigProfilerExtractor with default parameters using two distinct mutational

classifications: SBS-96 and SBS-288. The SBS-96 mutation classification incorporates the six

types of single base substitutions: C>A, C>G, C>T, T>A, T>C, and T>G. Each type of single

base substitution is further separated into 16 subtypes determined by the four possible bases 5'

and 3' adjacent to each mutated base. The SBS-288 mutation classification extends the SBS-96

mutation classification by adding additional information for each of the 96 subtypes.

Specifically, SBS-288 incorporates whether a single base substitution is in non-

transcribed/intergenic DNA, on the transcribed strand of a gene, or on the untranscribed strand of

the gene. *De novo* extraction was performed separately for all examined datasets. Specifically,

SigProfilerExtractor was applied: *(i)* to all 2,778 whole-genome sequenced cancers from the Pan-

Cancer Analysis of Whole Genomes project[26]; *(ii)* to all samples in each of the 37 cancer types

of Pan-Cancer Analysis of Whole Genomes project[26] with each cancer type examined separately;

(iii) to all 88 whole-genome sequenced microbiopsies of histologically normal urothelium[33]; *(iv)*

to the complete set of bladder cancers from TCGA[41]; *(v)* to exome downsampling of all bladder

whole-genome sequenced cancers from the Pan-Cancer Analysis of Whole Genomes project[26];

(vi) to exome downsampling of all 88 whole-genome sequenced microbiopsies of histologically

normal urothelium[33]. In all cases, the mutational catalogues of each samples were taken from the

respective original publications. The results from all performed *de novo* extractions can be found

in **Supplementary Data**. Downsampling of a whole-genome sequenced sample to a whole-

exome was performed using SigProfilerMatrixGenerator[2].

Additional approaches for miscellaneous analysis

Synthetic scenarios were labeled as easy, medium, and hard based on the number of operative

signatures in each scenario. Based on our most recent analysis of mutational signatures in 82

cancer types[11], approximately 7.4% of human cancer types have 5 or less signatures (reflected in

simulations of easy scenarios), 15.9% have 11 to 21 signatures (medium scenarios), and 59.5%

have 25 or more signatures (hard scenarios). Note that 17.2% of cancer types have either

between 5 and 10 signatures or between 22 and 24 signatures.

Cosine similarity was used to compare the profiles of different mutational signatures. P-values

can be attributed to cosine similarities based on a null hypothesis of uniform random distribution

of nonnegative vectors[31].

Briefly, the prevalence of somatic mutations in a whole-exome sample was calculated based on

the identified mutations in protein coding genes and assuming that an average whole-exome has

sufficient coverage of 30.0 megabase-pairs in protein coding genes. The prevalence of somatic

mutations in a whole-genome sample was calculated based on all identified mutations and

assuming that an average whole-genome has sufficient coverage of 3.00 gigabase-pairs.

All methods related to the generation of the benchmarking scenarios and the application of the

different tools to these scenarios can be found in **Supplementary Note 1**.

595 TABLES

Tool Name	Input	Platform	Factorization Approach			Selection Approach			Supported Contexts		COSMIC Comparison
			Method	Computational Engine	GPU	Manual	Automatic	Automatic Algorithm	Mutational Catalogue Support	Plotting	
EMu[15]	Matrix	C++	EM	Original implementation[15]	No	Yes	Yes^	BIC[37]	SBS-96	No	No
Maftools[16]	Matrix MAF	R-Bioconductor	NMF	NMF R package[35]	No	Yes	No	-	SBS-96	SBS-96	1-to-1
MutationalPatterns[17]	Matrix VCF	R-Bioconductor	NMF	NMF R package[35]	No	Yes	No	-	SBS-96 SBS-192	SBS-96 SBS-192	1-to-1
MutSpec[18]	Matrix VCF Custom	Galaxy Perl R	NMF	NMF R package[35]	No	Yes	No	-	SBS-96 SBS-192	SBS-96 SBS-192	1-to-1
SigFit[19]	Matrix	R	Bayesian Inference	Stan R package[36]	No	Yes	Yes^	Elbow method[38]	SBS-96	SBS-96 SBS-192	1-to-1
SigMiner[20]	Matrix MAF	R	[automatic] Bayesian NMF [manual] NMF	[automatic] SignatureAnalyzer implementation[21] [manual] NMF R package[35]	No	Yes^	Yes	ARD[32]	SBS-96 DBS-78 ID-83	Generic	1-to-1
SignatureAnalyzer[21,22]	Matrix MAF	R [CPU][18] Python [GPU][19]	Bayesian NMF	Original implementation[21,22]	Yes	No	Yes	ARD[32]	SBS-96 DBS-78 ID-83	SBS-96 DBS-78 ID-83	1-to-1
SignatureToolsLib[23]	Matrix VCF Custom	R	NMF	NMF R package[35]	No	Yes	No	-	SBS-96 DBS-78 ID-83 SV-32	SBS-96 SV-32 Generic	No
SigneR[24]	Matrix VCF	R-Bioconductor C++	Bayesian NMF	Original implementation[24]	No	Yes	Yes^	BIC[37]	SBS-96	SBS-96	No
SigProfilerExtractor	Matrix VCF MAF Custom	Python R wrapper	NMF	[current report] Original implementation	Yes	Yes	Yes^	NMFk[39]	SBS-96 DBS-78 ID-83 Others[2] Any	SBS-96 DBS-78 ID-83 SV-32 Others[2] Generic	1-to-many
SomaticSignatures[25]	Matrix VCF	R-Bioconductor	NMF PCA	NMF R package[35] pcaMethods R package[47]	No	Yes	No	-	SBS-96	SBS-96	No

Table 1: Overview of bioinformatics tools for *de novo* extraction of mutational signatures.

Tools are ordered alphabetically. Notations: ^ denotes the default approach for selecting the total

number of signatures when a tool supports both manual and automatic selection; 1-to-1 refers to

one *de novo* signature being matched with exactly one COSMIC signature; 1-to-many refers to

one *de novo* signature being matched with a combination of one or more COSMIC signatures.

Abbreviations: MAF: mutation annotation format; VCF: variant call format; EM: expectation-

maximization algorithm; NMF: nonnegative matrix factorization; ARD: automatic relevance

determination; BIC: Bayesian information criterion; COSMIC: catalogue of somatic mutations in

cancer; SBS: single base substitutions; DBS: doublet base substitutions; ID: small insertions and

deletions; SV: structural variants.

 FIGURE LEGENDS

Figure 1. Overview of SigProfilerExtractor. *(a)* SigProfilerExtractor's general workflow is

outlined starting from an input of somatic mutations and resulting in an output of *de novo*

mutational signatures. An example is shown for a solution with three *de novo* signatures.

Somatic mutations are first converted into a mutational matrix. Subsequently, the matrix is

factorized with different ranks using nonnegative matrix factorization. Model selection is applied

to identify the optimal factorization rank based on each solution's stability and its reconstruction

of the original data. *(b)* Schematic representation for an example decomposition with a

factorization rank of *k=3*. By default, SigProfilerExtractor performs 500 independent

nonnegative matrix factorizations with the matrix M being Poisson resampled and normalized

(denoted by ^) prior to each factorization. Partition clustering of the 500 factorizations is used to

evaluate the factorization stability rank, measured in silhouette values; clustering can also be

presented as two-dimensional projections revealing more similar mutational signatures as shown

for the three example signatures. The centroid of the clustered solutions (denoted by –) is

compared to the original matrix M. *(c)* All identified *de novo* signatures are matched to a

combination of known COSMIC mutational signatures. An example is given for *de novo*

extracted signature SBS96B which matches a combination of COSMIC signatures SBS1, SBS2,

and SBS13.

Figure 2. Benchmarking of bioinformatics tools for *de novo* extraction of mutational

signatures using SBS-96 noiseless scenarios. *(a)* Average precision (x-axes), sensitivities (y-

axes), and F_1 scores (harmonic mean of precision and sensitivity; red curves) are shown across

the three types of scenarios. Different tools are displayed using circles and triangles with

different colors. Circles are used to display results for suggested model selection, which most

closely matches analysis of a real dataset. Triangles are used to display results for forced model

selection, where tools were required to extract the known total number of ground-truth

mutational signatures. All triangles are located on the diagonal as the forced model selection

results in equal numbers of false positive and false negative signatures. *(b)* Evaluating the effect

of ground-truth signatures on the *de novo* extraction by different tools (x-axes). Ratio of F_1

scores (y-axes) with confidence intervals were calculated for medium complexity scenarios

simulated using COSMIC, SA, or random signatures. Ratio of approximately 1.00 indicates a

similar performance between different types of signatures. *(c)* Evaluating the performance of *de*

novo extraction between suggested and forced selection for different tools (x-axes). Ratio of F_1

scores (y-axes) with confidence intervals were calculated for all medium and hard scenarios.

Ratio of approximately 1.00 indicates a similar performance between suggested and forced

model selection. *(d)* Summary of the performance for the top seven tools on medium and hard

SBS-96 noiseless scenarios with suggested model selection. Y-axes reflect F_1 score (left plot),

sensitivity (middle plot), and false discovery rate (right plot), respectively. Results from

SignatureAnalyzer are not displayed in panels *(a)*, *(b)*, and *(c)* for forced model selection as

SignatureAnalyzer does not support predefined/forced solution with a specific total number of

signatures.

Figure 3. Additional evaluations of the top seven bioinformatics tools for *de novo* extraction

of mutational signatures. *(a)* Average F_1 scores for the top seven tools based on different

thresholds for cosine similarity in suggested medium and hard scenarios; thresholds for cosine

similarity are used for determining true positive signatures (**Supplementary Figure 1**). X-axes

reflect the cosine similarity thresholds, while the Y-axes correspond to the average F_1 scores

corresponding to cosine similarity thresholds. *(b)* Precision and sensitivity of the top seven tools

for SBS-96 scenarios with different levels of noise. Noise levels reflect the average number of

somatic mutations in a cancer genome affected by additive white Gaussian noise; for example,

1% noise corresponds to approximately 1% of mutations in a sample being due to noise. *(c)*

Summary of the performance of the top seven tools on SBS-96 scenarios with 5% noise. Y-axes

reflect F_1 score (left plot), sensitivity (middle plot), and false discovery rate (right plot),

respectively.

Figure 4. Novel signatures identified in the PCAWG cohort of 2,778 whole-genome

sequenced cancers. Mutational signatures are displayed using 96-plots. Single base substitutions

are shown using the six subtypes of substitutions: C>A, C>G, C>T, T>A, T>C, and T>G.

Underneath each subtype are 16 bars reflecting the sequence contexts determined by the four

possible bases 5' and 3' to each mutated base. Additional information whether mutations from a

signature are in non-transcribed/intergenic DNA, on the transcribed strand of a gene, or on the

untranscribed strand of the gene is provided adjacent to the 96 plots. *(a)* Mutational profile of

signature SBS92 derived from the PCAWG cohort (top). Confirmation of the profile of signature

SBS92 (bottom) by analysis of an independent whole-genome sequenced set of microbiopsies of

histologically normal urothelium[33]. *(b)* Mutational profile of signature SBS93 derived from the

PCAWG cohort (top). Confirmation of the profile of signature SBS93 (bottom) by analysis of an

independent whole-genome sequenced set of esophageal squamous cell carcinomas[34]. *(c)*

Mutational profile of signature SBS94 derived from the PCAWG cohort. Signature SBS94 was

not identified in any additional independent cohort. *(d)* Bars are used to display average values

for numbers of somatic substitutions per megabase (Mb) attributed to signature SBS92 in bladder

cancer and normal bladder urothelium. Green bars represent never smokers, whereas blue bars

correspond to ever smokers. Error bars correspond to 95% confidence intervals. Each p-value is

based on a Wilcoxon rank sum test.

SUPPLEMENTARY INFORMATION

Supplementary Figure 1. Standard set of performance metrics used for benchmarking all

bioinformatics tools. An example demonstrating the derivation of *true positive* (TP), *false*

positive (FP), or *false negative* (FN) signatures for a tool applied to a synthetic dataset generated

using 6 ground truth signatures (termed, Ground Truth Signatures 1 through 6). The tool extracts

4 signatures (termed, Extracted Signatures A through D). In this example, an extracted signature

is considered a true positive if it matches one of the ground-truth signatures with a cosine

similarity threshold of at least 0.90.

Supplementary Table 1. Detailed performance metrics after applying each tool across all

SBS-96 noiseless synthetic scenarios. Performance metrics are calculated as per *Supplementary*

Figure 1. An extracted signature is considered a true positive if it matches one of the ground-

truth signatures with a cosine similarity threshold of at least 0.90.

Supplementary Table 2. Detailed performance metrics after applying the seven best

performing tools across SBS-96 synthetic scenarios with different levels of noise.

Performance metrics are calculated as per *Supplementary Figure 1*. An extracted signature is

considered a true positive if it matches one of the ground-truth signatures with a cosine similarity

threshold of at least 0.90.

Supplementary Table 3. Detailed performance metrics of applying SigProfilerExtractor

and SignatureAnalyzer to extended synthetic scenarios. Performance metrics are calculated

as per *Supplementary Figure 1*. An extracted signature is considered a true positive if it matches

one of the ground-truth signatures with a cosine similarity threshold of at least 0.90.

Supplementary Table 4. Profiles of three novel mutational signatures identified in the

PCAWG cohort of 2,778 whole-genome sequenced cancers. The profiles of the novel

mutational signatures are reported using the SBS-288 classification which incorporates the

trinucleotide context and strand information (intergenic region, untranscribed strand, or

transcribed strand) for each type of single base substitution. The SBS-288 classification can be

easily collapsed to the commonly used SBS-96 classification.

Supplementary Note 1. Detailed description of the performed benchmarking. The

supplementary note provides extensive details about each of the generated synthetic scenarios as

well as about applying each of the tools to these scenarios. The results from applying all tools to

all scenarios, including appropriate input and out files, can be found in **Supplementary Data**.

Supplementary Data

All results from the benchmarking with synthetic datasets, including the appropriate input used

to run each of the tools as well as the output generated by each of the tools, can be found at:

ftp://alexandrovlab-ftp.ucsd.edu/pub/publications/Islam_et_al_SigProfilerExtractor/Benchmark/.

All results from the *de novo* extraction of mutational signatures from the PCAWG dataset can be

found at: ftp://alexandrovlab-

ftp.ucsd.edu/pub/publications/Islam_et_al_SigProfilerExtractor/PCAWG_Reanalysis/.

All results from the *de novo* extraction of mutational signatures for confirming the patterns of the

novel signatures for additional datasets can be found at: ftp://alexandrovlab-

ftp.ucsd.edu/pub/publications/Islam_et_al_SigProfilerExtractor/Confirmation_of_Novel_Signatu

res/.

All results from the *de novo* extraction of mutational signatures from downsampling of whole-

genome sequenced samples to whole-exomes can be found at: ftp://alexandrovlab-

ftp.ucsd.edu/pub/publications/Islam_et_al_SigProfilerExtractor/Downsampling_of_whole_geno

mes/

ACKNOWLEDGEMENTS

The authors would like to thank Allan Balmain (UC San Francisco) for the many useful

discussions as well as Ville Mustonen (University of Helsinki) and Israel Tojal Da Silva (A.C.

Camargo Cancer Center) for help in configuring EMu and SigneR, respectively. This work was

supported by Cancer Research UK Grand Challenge Award C98/A24032 (LBA, PB, and MRS),

Wellcome grant reference 206194 (MRS), and US National Institute of Health grants

R01MH116281-01A1 (BSA) and R01ES030993-01A1 (LBA). This work was also supported by

Singapore National Medical Research Council grants NMRC/CIRG/1422/2015 and MOH-

000032/MOHCIRG18may-0004 and the Singapore Ministry of Health via the Duke-NUS

Signature Research Programmes. LBA is an Abeloff V Scholar and he is supported by an Alfred

P. Sloan Research Fellowship. Research at UC San Diego was also supported by a Packard

Fellowship for Science and Engineering to LBA. AJG was funded by a postdoctoral fellowship

(grant nr. P2BSP3_178591). NP receives funding through the Cancer Research UK Clinician

Scientist Fellowship scheme and is supported by University College London Cancer Institute.

Research at Los Alamos National Laboratory was conducted under Contract No.

89233218CNA000001 by the U.S. Department of Energy's National Nuclear Security

Administration and supported by Laboratory Directed Research and Development (LDRD) grant

20190020DR (BSA). CDS is supported by the GEM consortium and acknowledges funding for

this work through a Cancer Research UK travel grant. The funders had no roles in study design,

data collection and analysis, decision to publish, or preparation of the manuscript.

AUTHOR CONTRIBUTIONS

LBA and SMAI designed both SigProfilerExtractor's methodology and the performed analyses

with help from NP, JZ, DJA, IM, BSA, LH, DCW, MTL, PB, MRS, and SGR. SMAI developed

SigProfilerExtractor with help from MV, ENB, YH, CDS, RV, and JW. All synthetic

benchmarking datasets were generated by YW and SGR. SMAI documented

SigProfilerExtractor and performed the benchmarking of all tools on synthetic data with help

from MDG, MB, BO, AK, and AA. Additional validations, confirmations, and applications of

SigProfilerExtractor to real and synthetic datasets were performed by SMAI, SM, SS, YRL, NS,

LR, TZ, AJG, YH, CDS, and SWB. LBA directed the overall research and wrote the manuscript

with help from SMAI and input from all other authors. All authors read and approved the final

manuscript.

COMPETING INTERESTS

MV is an employee of NVIDIA corporation. All other authors declare no competing interests.

TOOL AVAILABILITY

SigProfilerExtractor and all its modules are open source and freely available for use under the

permissive 2-clause BSD license. SigProfilerExtractor and its modules are implemented in

Python with an R wrapper package allowing users to run the tool from an R environment.

SigProfilerExtractor can be installed using the PyPI package manager from

https://pypi.org/project/SigProfilerExtractor/ or downloaded from GitHub from

https://github.com/AlexandrovLab/SigProfilerExtractor. The R version of the tool can be

downloaded from https://github.com/AlexandrovLab/SigProfilerExtractorR. A detailed wiki

page including installation, usage, and explanation of result is provided at

https://osf.io/t6j7u/wiki/home/. SigProfilerExtractor is compatible with Windows, Linux, Unix,

and macOS operating systems.

REFERENCE

Alexandrov, L. B., Nik-Zainal, S., Wedge, D. C., Campbell, P. J. & Stratton, M. R. Deciphering signatures of mutational processes operative in human cancer. *Cell Rep* **3**, 246-259, doi:10.1016/j.celrep.2012.12.008 (2013).

Bergstrom, E. N. *et al.* SigProfilerMatrixGenerator: a tool for visualizing and exploring patterns of small mutational events. *BMC Genomics* **20**, 685, doi:10.1186/s12864-019-6041-2 (2019).

Lee, D. D. & Seung, H. S. Learning the parts of objects by non-negative matrix factorization. *Nature* **401**, 788-791, doi:10.1038/44565 (1999).

Févotte, C. & Cemgil, A. T. in *2009 17th European Signal Processing Conference.* 1913-1917.

Dempster, A. P., Laird, N. M. & Rubin, D. B. Maximum Likelihood from Incomplete Data Via the EM Algorithm. *Journal of the Royal Statistical Society: Series B (Methodological)* **39**, 1-22, doi:10.1111/j.2517-6161.1977.tb01600.x (1977).

Suri, P. & Roy, N. R. in *2017 3rd International Conference on Computational Intelligence & Communication Technology (CICT).* 1-5.

Alexandrov, L. B. Understanding the origins of human cancer. *Science* **350**, 1175, doi:10.1126/science.aad7363 (2015).

Alexandrov, L. B. *et al.* Signatures of mutational processes in human cancer. *Nature* **500**, 415-421, doi:10.1038/nature12477 (2013).

Petljak, M. & Alexandrov, L. B. Understanding mutagenesis through delineation of mutational signatures in human cancer. *Carcinogenesis* **37**, 531-540, doi:10.1093/carcin/bgw055 (2016).

Pich, O. *et al.* The mutational footprints of cancer therapies. *Nat Genet* **51**, 1732-1740, doi:10.1038/s41588-019-0525-5 (2019).

Alexandrov, L. B. *et al.* The repertoire of mutational signatures in human cancer. *Nature* **578**, 94-101, doi:10.1038/s41586-020-1943-3 (2020).

Alexandrov, L. B. *et al.* Clock-like mutational processes in human somatic cells. *Nat Genet* **47**, 1402-1407, doi:10.1038/ng.3441 (2015).

Alexandrov, L. B., Nik-Zainal, S., Siu, H. C., Leung, S. Y. & Stratton, M. R. A mutational signature in gastric cancer suggests therapeutic strategies. *Nat Commun* **6**, 8683, doi:10.1038/ncomms9683 (2015).

Alexandrov, L. B. *et al.* Mutational signatures associated with tobacco smoking in human cancer. *Science* **354**, 618-622, doi:10.1126/science.aag0299 (2016).

Fischer, A., Illingworth, C. J., Campbell, P. J. & Mustonen, V. EMu: probabilistic inference of mutational processes and their localization in the cancer genome. *Genome Biol* **14**, R39, doi:10.1186/gb-2013-14-4-r39 (2013).

Mayakonda, A., Lin, D. C., Assenov, Y., Plass, C. & Koeffler, H. P. Maftools: efficient and comprehensive analysis of somatic variants in cancer. *Genome Res* **28**, 1747-1756, doi:10.1101/gr.239244.118 (2018).

Blokzijl, F., Janssen, R., van Boxtel, R. & Cuppen, E. MutationalPatterns: comprehensive genome-wide analysis of mutational processes. *Genome Med* **10**, 33, doi:10.1186/s13073-018-0539-0 (2018).

18 Ardin, M. *et al.* MutSpec: a Galaxy toolbox for streamlined analyses of somatic mutation
spectra in human and mouse cancer genomes. *BMC Bioinformatics* **17**, 170,
doi:10.1186/s12859-016-1011-z (2016).
19 Gori, K. & Baez-Ortega, A. sigfit: flexible Bayesian inference of mutational signatures.
bioRxiv, 372896, doi:10.1101/372896 (2020).
20 Wang, S. *et al.* Copy number signature analyses in prostate cancer reveal distinct
etiologies and clinical outcomes. *medRxiv*, 2020.2004.2027.20082404,
doi:10.1101/2020.04.27.20082404 (2020).
21 Kasar, S. *et al.* Whole-genome sequencing reveals activation-induced cytidine deaminase
signatures during indolent chronic lymphocytic leukaemia evolution. *Nat Commun* **6**,
8866, doi:10.1038/ncomms9866 (2015).
22 Taylor-Weiner, A. *et al.* Scaling computational genomics to millions of individuals with
GPUs. *Genome Biol* **20**, 228, doi:10.1186/s13059-019-1836-7 (2019).
23 Degasperi, A. *et al.* A practical framework and online tool for mutational signature
analyses show inter-tissue variation and driver dependencies. *Nat Cancer* **1**, 249-263,
doi:10.1038/s43018-020-0027-5 (2020).
24 Rosales, R. A., Drummond, R. D., Valieris, R., Dias-Neto, E. & da Silva, I. T. signeR: an
empirical Bayesian approach to mutational signature discovery. *Bioinformatics* **33**, 8-16,
doi:10.1093/bioinformatics/btw572 (2017).
25 Gehring, J. S., Fischer, B., Lawrence, M. & Huber, W. SomaticSignatures: inferring
mutational signatures from single-nucleotide variants. *Bioinformatics* **31**, 3673-3675,
doi:10.1093/bioinformatics/btv408 (2015).
26 Consortium, I. T. P.-C. A. o. W. G. Pan-cancer analysis of whole genomes. *Nature* **578**,
82-93, doi:10.1038/s41586-020-1969-6 (2020).
27 Kullback, S. & Leibler, R. A. On Information and Sufficiency. *Ann. Math. Statist.* **22**, 79-
86, doi:10.1214/aoms/1177729694 (1951).
28 Kuhn, H. W. The Hungarian method for the assignment problem. *Naval Research
Logistics Quarterly* **2**, 83-97, doi:10.1002/nav.3800020109 (1955).
29 Huang, K., Sidiropoulos, N. D. & Swami, A. Non-Negative Matrix Factorization
Revisited: Uniqueness and Algorithm for Symmetric Decomposition. *IEEE Transactions
on Signal Processing* **62**, 211-224, doi:10.1109/TSP.2013.2285514 (2014).
30 Lin, C. On the Convergence of Multiplicative Update Algorithms for Nonnegative Matrix
Factorization. *IEEE Transactions on Neural Networks* **18**, 1589-1596,
doi:10.1109/TNN.2007.895831 (2007).
31 Bergstrom, E. N., Barnes, M., Martincorena, I. & Alexandrov, L. B. Generating realistic
null hypothesis of cancer mutational landscapes using SigProfilerSimulator. *BMC
Bioinformatics* **21**, 438, doi:10.1186/s12859-020-03772-3 (2020).
32 Tan, V. Y. F. & Févotte, C. Automatic Relevance Determination in Nonnegative Matrix
Factorization with the /spl beta/-Divergence. *IEEE Transactions on Pattern Analysis and
Machine Intelligence* **35**, 1592-1605, doi:10.1109/TPAMI.2012.240 (2013).
33 Lawson, A. R. J. *et al.* Extensive heterogeneity in somatic mutation and selection in the
human bladder. *Science* **370**, 75-82, doi:10.1126/science.aba8347 (2020).
34 Moody, S. *et al.* Mutational signatures in esophageal squamous cell carcinoma from eight
countries of varying incidence. *bioRxiv, 372XXX* (2020).
35 Gaujoux, R. & Seoighe, C. A flexible R package for nonnegative matrix factorization.
BMC Bioinformatics **11**, 367, doi:10.1186/1471-2105-11-367 (2010).

36   Carpenter, B. *et al.* Stan: A Probabilistic Programming Language. *Journal of Statistical*
Software **76**, doi:10.18637/jss.v076.i01 (2017).
37   Schwarz, G. Estimating the Dimension of a Model. *The Annals of Statistics* **6**, 461-464,
doi:10.1214/aos/1176344136 (1978).
38   Thorndike, R. L. Who belongs in the family? *Psychometrika* **18**, 267-276,
doi:10.1007/bf02289263 (1953).
39   Benjamin, N., Raviteja, V., Miguel, A. H.-H., Svetlana, K. & Boian, A. A neural network
for determination of latent dimensionality in Nonnegative Matrix Factorization. *Machine*
Learning: Science and Technology (2020).
40   Kim, J. *et al.* Somatic ERCC2 mutations are associated with a distinct genomic signature
in urothelial tumors. *Nat Genet* **48**, 600-606, doi:10.1038/ng.3557 (2016).
41   Cancer Genome Atlas Research, N. Comprehensive molecular characterization of
urothelial bladder carcinoma. *Nature* **507**, 315-322, doi:10.1038/nature12965 (2014).
42   Shalabi, L. A. & Shaaban, Z. in *2006 International Conference on Dependability of*
Computer Systems. 207-214.
43   Žitnik, M. & Zupan, B. Nimfa: A python library for nonnegative matrix factorization.
The Journal of Machine Learning Research **13**, 849-853 (2012).
44   Lew, J. *et al.* in *2019 IEEE International Symposium on Performance Analysis of Systems*
and Software (ISPASS). 151-152.
45   Aranganayagi, S. & Thangavel, K. in *International Conference on Computational*
Intelligence and Multimedia Applications (ICCIMA 2007). 13-17 (IEEE).
46   Franc, V., Hlaváč, V. & Navara, M. in *Computer Analysis of Images and Patterns.* (eds
André Gagalowicz & Wilfried Philips) 407-414 (Springer Berlin Heidelberg).
47   Stacklies, W., Redestig, H., Scholz, M., Walther, D. & Selbig, J. pcaMethods--a
bioconductor package providing PCA methods for incomplete data. *Bioinformatics* **23**,
1164-1167, doi:10.1093/bioinformatics/btm069 (2007).
903

a

Transformation of Somatic Mutations into a Matrix

Matrix Factorization (NMF)

Model Selection

De Novo Signatures

b

Decomposition example for *K=3 de novo* signatures

Clustering

*minimum of 10,000 iterations per replicate

distance$(M, \overline{M}_3)$
Average Reconstruction Error: 0.2%

$$\overline{M}_3 = \overline{S}_3 \times \overline{A}_3$$

Average Stability: 0.98

c

De novo extracted signature

Reconstruction of a *de novo* signature using COSMIC signatures

Decomposition of a *de novo* signature using COSMIC signatures

Cosine similarity: 0.981
Correlation coefficient: 0.985

COSMIC SBS1   13.44%
COSMIC SBS2   59.98%
COSMIC SBS13   26.58%

Fig.2

Fig. 4