Expectation violation dynamically engages a bottom-up encoding state

Darya Frank[1,2], Alex Kafkas[1], Daniela Montaldi[1]

[1] Division of Neuroscience and Experimental Psychology, School of Biological Sciences, The University of Manchester, UK
[2] Laboratory for Clinical Neuroscience, Centre for Biomedical Technology, Universidad Politécnica de Madrid, Spain

Abstract

Expectation violation has been shown to engage adaptive memory formation,
resulting in better memory for unexpected information. In two experiments we tested
whether this mechanism is engaged dynamically in a goal-irrelevant manner during
retrieval, and how it affects trial-by-trial recognition. Participants encoded images of
objects, and then learned a contingency between a cue and category (man-made or
natural) with new objects. Targets and parametrically manipulated similar foils,
comprising set events, were used at retrieval. In each retrieval trial a cue appeared,
which either matched or mismatched (according to the established contingency) the
following object, for which participants made an old/new decision. We found that
unexpected events at retrieval were associated with increased activation along the
ventral visual stream, whereas expected events engaged parietal regions of the core
recollection network. For targets and most similar foils, we found an interaction
between current and previous expectation status on memory performance, such that
expected events following unexpected ones ($U_{prev}E_{curr}$) showed a boost in
performance. This behavioural effect was associated with activation in the
hippocampus, SN/VTA and occipital cortex. A combination of two unexpected events
($U_{prev}U_{curr}$) resulted in the poorest memory performance and was associated with
increased activation in occipital cortex. Taken together, our findings suggest
expectation violation engages an encoding mechanism, supported by bottom-up
processing, in a task-independent manner. Therefore, when the goal is to retrieve
information, the mnemonic consequences of the shift towards an encoding state is
detrimental in real-time, but beneficial for subsequent similar events.
32
33   Abstract word count: 245
34

Introduction

Environmental setting and contextual features shape how we perceive and remember our daily life. In order to efficiently process the inputs it receives, the brain shifts between top-down and bottom-up information streams to balance processing sensory inputs versus utilising stored information. Bottom-up processing can reflect an encoding state, prioritising transformation of perceptual inputs into memories. Discrepancies between expected and observed events have been shown to engage such an encoding state in the hippocampus (Axmacher et al., 2010; Bein, Duncan, & Davachi, 2020; Kafkas & Montaldi, 2015; Kumaran & Maguire, 2007; Meeter, Murre, & Talamini, 2004). Nevertheless, it is still unclear whether this encoding state can be engaged dynamically, in a goal-irrelevant manner (i.e. peripheral or irrelevant to the decision made in the task). Here we examine whether expectation violation, taking place at retrieval and orthogonal to the recognition task, results in a shift towards an encoding state, as indicated by a gain on bottom-up processing. We further examined how this violation and ensuing bottom-up processing affect trial-by-trial recognition of similar events.

Predictive processing frameworks postulate bottom-up processing is modulated by top-down predictions (Friston, 2005). In memory research, prediction errors, or expectation violation, have been shown to engage hippocampal processing (Duncan, Ketz, Inati, & Davachi, 2012; Frank, Montemurro, & Montaldi, 2020; Hindy, Ng, & Turk-Browne, 2016; Kafkas & Montaldi, 2015; Kumaran & Maguire, 2007; Long, Lee, & Kuhl, 2016), which together with the midbrain dopaminergic system (Kafkas & Montaldi, 2018b; Lisman & Grace, 2005; Shohamy & Wagner, 2008), support adaptive memory formation. To date, evidence for this adaptive mechanism, showing better memory performance for unexpected information, comes mostly from paradigms in which expectation violation takes place before or during learning (Garrido, Barnes, Kumaran, Maguire, & Dolan, 2015; Greve, Cooper, Kaula, Anderson, & Henson, 2017; Gruber, Watrous, Ekstrom, Ranganath, & Otten, 2013; Li, Cullen, Anwyl, & Rowan, 2003; Long et al., 2016). Therefore, any additional resources diverted toward encoding in these scenarios is likely to boost later memory performance, similar to attention effects (for a review see Aly & Turk-Browne, 2017). However, to demonstrate a ubiquitous expectation-driven encoding mechanism, it is critical to provide evidence of a dynamic shift towards encoding in a

task-independent manner, for example, when retrieval is necessary. Under these
circumstances, a shift towards encoding still serves an adaptive purpose, but it might
no longer be 'beneficial' in terms of reporting memory for the unexpected event.
Evidence for such task-independent encoding effects (e.g. expectation-driven
encoding at the expense of retrieval) is currently lacking.

Given the malleability of existing memories following expectation violation (G. Kim,
Lewis-Peacock, Norman, & Turk-Browne, 2014), it is also worth considering what the
mnemonic consequences of a dynamic shift towards encoding may be. Should
expectation violation trigger an encoding state, which comes at the expense of a
memory search, it might result in poor recognition of the unexpected event at
retrieval. This is in line with the view that the hippocampus continuously shifts
between encoding and retrieval states (Buzsáki, 2002; Colgin, 2016; Hasselmo,
Bodelon, & Wyble, 2002; Ketz, Morkonda, & O'Reilly, 2013). These states can be
viewed as a pendulum, and certain environmental factors can disrupt the on-going
swing between states, favouring one over another, to support effective processing.
Previous research has shown a strategy cue (e.g. encode or integrate) can indeed
foster hippocampal trade-off between encoding and retrieval of information (Richter,
Chanales, & Kuhl, 2016). Here, we test whether such shifts can also occur following
an implicit, task-irrelevant expectation violation, and their continuous mnemonic
outcomes in the form of correct recognition of targets and similar foils.

Engagement of an encoding state should also be demonstrated in enhanced
perceptual processing, as encoding relies on sensory inputs. Previous research has
shown increased activity along the ventral visual stream in response to
novelty/expectation violation (Hawco & Lepage, 2014; Kafkas & Montaldi, 2015;
Stoppel et al., 2009). We have also shown that expectation-modulated memory is
sensitive to perceptual similarity between existing representations and current inputs
(Frank et al., 2020). Therefore, in order to tap the proposed encoding mechanism
engaged by expectation violation, a high level of perceptual load, achieved by using
similar set events (target and similar foils), is necessary. This allows us to examine
how expectation violation affects trial-by-trial memory decisions and representations
(Duncan, Sadanand, & Davachi, 2012). For example, if the first unexpected target
was missed due to a shift towards encoding, the following expected similar foil might
benefit from the re-encoding of the target, and more likely to be correctly rejected.

Therefore, we can better tap the interplay between memory search and shift to
encoding due to expectation violation, and how this relationship may affect
subsequent processing (and recognition) of similar events.

In two experiments, we examined a) whether expectation violation dynamically
engages an encoding state, b) whether this response is dependent on the perceptual
similarity between inputs, and c) its mnemonic consequences. To do so, we used a
paradigm in which expectation was manipulated at retrieval, implicitly and
independently of the requirements of the recognition task. Following encoding of
images of objects, participants performed a rule-learning task in which they learned a
contingency between a cue and the object's category (man-made or natural). Then,
at retrieval, the same cues were presented followed by an old (target) or new
(parametrically manipulated similar foils) object for which participants were asked to
make an old/new recognition decision. In one-third of the retrieval trials, the pre-
established cue and object category sequence was violated. This design allowed us
to answer two questions; first whether expectation violation engages a bottom-up
encoding mechanism, even when it's not goal-relevant. Second, what the mnemonic
consequences of this violation are in real time as well as for subsequent similar
objects (interactions between previous and current set events' expectation status).
We reasoned that an expectation-driven encoding could harm online retrieval
processes, but aid recognition of subsequent similar events.

Experiment 1
Methods

Participants. 30 participants (4 males) between the ages 18-22 (M = 19, SD = 1.04)
gave informed consent and took part in the experiment. Participants had normal or
corrected-to-normal vision and no history of neurological or psychiatric disorders. All
procedures were approved by the University of Manchester Research Ethics
Committee. Four participants were excluded from any further analysis due to failure
to learn the cue-outcome association (3) and recognition performance below chance
(1). Data from 26 participants are reported below.

Materials. 78 images of natural (39) and man-made (39) objects were selected from
the Similar Objects-Lures Image Database (SOLID; Frank, Gray, & Montaldi, 2019).
These images were used as the target objects, presented during encoding. Using

the dissimilarity index from SOLID, three foils of decreasing levels of similarity (F1 –
most similar, F2 – mid-level F3- lowest similarity) were selected for each target
image. Additionally, similarity was parametrically manipulated by keeping the
average distance between the levels constant (average dissimilarity 2100 DI; see
Figure 1 for examples and Frank et al., 2019 for further explanation on DI values).
Therefore, 78 object sets (one target and three foils; total 312 stimuli) were utilised.

Procedure. The experiment was controlled using PsychoPy version 1.82 (Peirce,
2007) and consisted of four parts (similar to design used by Kafkas and Montaldi,
2018a). First, at encoding, participants were presented with the target objects twice
to ensure sufficient exposure. During the first presentation, the object was shown on
the screen for 3 seconds, and participants were asked to decide whether the object
was man-made or natural; pressing the left arrow key for natural, and the right arrow
key for man-made. In the second presentation participants were asked to pay close
attention to the images (shown for 5s each) and were informed that they would be
asked to distinguish between the presented ('old') object and similar ('new') objects
later; they did not have to make any response during the second encoding
presentation. The order of image presentation was randomised across participants.
The next part involved a 5-minute filled delay task, during which participants solved
arithmetic problems.

In the third part, a rule-learning task was used to allow manipulation of expectation
later at retrieval. Participants were asked to learn the contingency between a symbol
(acting as a cue) and an object's category, man-made or natural. Four symbols were
used in total, two for each category, and these were counterbalanced between
participants. Each cue was presented 14 times. Trials began with a 500ms fixation
point, followed by the cue, presented for 1 second. During this time participants were
instructed to guess the following object's category by using the same keys as in the
encoding phase. Feedback and a new object (not tested) were then presented
together for 2 seconds. This task established participant's expectation regarding the
cue-object sequences, and critically this was manipulated at retrieval. To ensure
expectations were set, only data from participants who reached criterion (above 50%
accuracy in the first half, and 75% accuracy in the second half of the task) were
analysed (See Supplementary Figure S.1 for accuracy and RT in the rule-learning
task).

The final part was an old/new recognition task, during which all set events (targets,
F1, F2 and F3) were presented. The experimenter informed participants that they will
be presented with old (target) objects, and similar new ones (foils). Each retrieval
trial began with a fixation point (500ms), followed by a cue (1 second) and an object
(up to 5 seconds). Participants were told to focus on the object and press 'old' if they
thought it was exactly the same as the target they had previously seen. Participants
were instructed to press 'new' if they noticed anything different in the object.
Following 12 practice trials, the main task began. The key manipulation at retrieval
was the validity of the cue. One-third of the cues were misleading, making the object
to-be-recognised unexpected. Valid trials (e.g. cue natural followed by a natural
object) were marked as expected. As an old/new recognition task was used, the four
old/new decisions per object set were independent of each other, meaning an 'old'
response could be given for multiple set events (i.e. for target and foils).

Figure 1 | Experimental design. A) In Experiment 1, during the first round of encoding, participants
responded whether the object was man-made or natural. In the second encoding round, participants
were asked to study the object carefully. In Experiment 2, each object appeared three times
consecutively; in addition to the two presentation form experiment 1, participants were asked to
respond whether the object was more likely to be found indoors or outdoors. The order of man-
made/natural and in/outdoor questions was randomised, the third presentation was always 'study
carefully' B) In the rule-learning task participants learned a contingency between a cue and an
object's category, man-made or natural. In Experiment 1 participants had 1 second to make a
decision, and 3 seconds in Experiment 2 C) In the final retrieval task, the same cues were presented

before each set event, old objects (targets) and new similar foils (F1, F2, F3; only F1 and F2 in
Experiment 2). On 30% of these trials there was a mismatch between the cue and the object's
category, these are unexpected trials. Participants were instructed to ignore the symbols and respond
whether the object is old or new. D) Example of set events.

Data analysis. To assess expectation-modulated dynamic encoding, we collated

object sets (apples, scissors etc.). In each set, there were four set events (target, F1

- most similar, F2 – mid similarity, and F3 – least similar), each with a randomly

assigned (a) expectation condition, (b) presentation position (1-4) within the set, and

(c) order of presentation at retrieval (1-312 trials). We ran a mixed-effects binary

logistic regression model on these ungrouped data. Models were computed using

the lme4 package (Bates, Mächler, Bolker, & Walker, 2015) in the R environment (R

Development Core Team, 2008). The parameters of such models can be used to

assess the probability of giving a correct response ('old' for targets, 'new' for foils)

and also account for each participant's unique intercept (response bias). To assess

the slope of each predictor in the best-performing model (H_0: $\beta = 0$), we used an

omnibus χ^2 Wald test (West, Welch, & Galecki, 2014), as implemented in the car

package (Fox & Weisberg, 2018). Extraction and plotting of the effects reported

below was conducted using the effects (Fox, 2003), emmeans (Searle, Speed, &

Milliken, 1980) and ggplot2 (Wickham, 2009) packages. To examine the dynamic

interaction between item similarity and expectation status, for each set event we

devised three models of interest, modelling each event separately as a function of

the preceding set event. For example, targets preceded by F1 were modelled

separately from targets preceded by F2. Each model thus included the current and

previous set events' expectation status, as well as the order of presentation at

retrieval as a covariate.

Results

Predicting hits

For targets following F1 set events, we found significant main effects of the previous

F1 expectation ($\beta = 0.57$, $X^2(1) = 6.8$, $p = 0.009$), as well as a significant interaction

between the target's expectation and the previous F1's expectation status ($\beta = -$

0.735, $X^2(1) = 4.14$, $p = 0.042$). All other main effects were not significant (all p's >

0.585). Subsequent contrast tests revealed that expected targets were more likely to

be remembered following an unexpected F1, compared to an expected F1 set event

($z = 2.59$, $p = 0.009$). Furthermore, when the previous F1 set event was unexpected,

the subsequent expected targets were more likely to be correctly remembered,

compared to unexpected targets (z = 2.39, p = 0.016). When examining targets that

followed F2 and F3 set events, we did not observe any significant predictors (all p's

> 0.127).

Predicting correct rejections of F1 (CR1)

For F1 events following targets, we found a trend towards an interaction between the

two events' expectation status (β = -0.58, $X^2(1)$ = 3.59, p = 0.058), with simple

contrasts showing more CR1 for expected F1 events following unexpected targets,

than unexpected F1 (z = 2.29, p = 0.022). All other effects were not significant (all

p's > 0.255). When examining F1 events that followed F2 and F3 set events, we did

not observe any significant predictors (all p's > 0.196).

Predicting correct rejections of F2 (CR2) and F3 (CR3)

F2 events were not affected by previous targets from the same set (all p's > 0.21).

We found more CR2 for unexpected F2, following F1 and F3 events, compared to

expected F2 (for F1 β = 0.35, $X^2(1)$ = 4.65, p = 0.031; for F3 β = 0.32, $X^2(1)$ = 4.34, p

= 0.037). For F2 following F3 events we found more CR2 for unexpected F2 events

(β = 0.323, $X^2(1)$ = 4.34, p = 0.037). CR3 were not modulated by any preceding set

events (all p's > 0.263).

Figure 2 | Experiment 1 Results. A) Predicting hits. More hits were observed for expected targets
following unexpected F1 foils, compared to unexpected targets following unexpected F1, and
compared to expected targets following expected F1. **B) Predicting CR1.** More CR1 for expected F1
following unexpected targets, compared to unexpected F1 following unexpected targets. **C)**
Collapsed hits and CR1. Similar results showing an interaction between the previous and current set
events' expectation status, with $U_{prev}E_{curr}$ events showing the best memory performance, compared to
$U_{prev}U_{curr}$ and $E_{prev}E_{curr}$.

Concatenated targets and F1

Given the similar effects observed for targets and F1 events independently, we
collapsed the two, to examine whether these effects are complementary (i.e. whether
there is an interaction between current and previous expectation status). Although
hits and correct rejections are not necessarily products of the same mnemonic
process, in this paradigm they provide an opportunity to examine how perceptual
load (in the form of similarity) interacts with dynamic expectation modulations. The
mnemonic comparison between the current set event (target or F1) and the previous
one (F1 or target, respectively), forms the highest load, or interference in relation to
the encoded object, as the participant makes a recognition decision. Therefore, if
perceptual processes are engaged upon encountering an unexpected event, the
effects observed for each set event individually should replicate. To eliminate any
effects driven by memory strength differences, we only included in this model events
for which the previous response was correct (i.e. for targets following F1 events, we
only included targets that followed CR1). Similar results were observed when
including all trials in the model (see Supplementary Figure S.3). We found a
significant main effect of previous event's expectation status ($\beta = 0.341$, $X^2(1) = 4.9$,
$p = 0.027$), as well as a significant interaction between expectation status of the
current and previous events ($\beta = -0.682$, $X^2(1) = 6.5$, $p = 0.01$). Subsequent contrast
tests revealed that when the previous set event was unexpected, more correct
responses were observed for expected compared to unexpected events ($U_{prev}E_{curr} >$
$U_{prev}U_{curr}$; $z = 3.1$, $p = 0.002$). Additionally, there were more correct responses for
current expected events following unexpected ones, compared to following expected
events ($E_{prev}E_{curr} < U_{prev}E_{curr}$; $z = -2.21$, $p = 0.027$).

276
Taken together, these results suggest expectation-violation dynamically shifts
processing away from retrieval and towards encoding, and the mnemonic
consequences of this shift are reflected on the subsequent set event, as a function of
perceptual similarity. When the previous and current events are both unexpected
($U_{prev}U_{curr}$), we observed poor memory performance for targets and F1 foils. On the
other hand, when an unexpected event is followed by an expected one ($U_{prev}E_{curr}$) a
boost in performance was observed. To examine whether these effects engage the
circuit involved in adaptive memory formation (hippocampus and midbrain; Kafkas &
Montaldi, 2018; Shohamy & Adcock, 2010), as well as to test the notion that
expectation violation engages an encoding mechanism, supported by the bottom-up

information stream (ventral visual pathway), in Experiment 2 a new set of
participants performed a similar task while fMRI data was acquired.
289

Experiment 2

<u>Methods</u>

Experiment 2 was Identical to Experiment 1 except the following details.

Participants. 25 participants (8 males, ages 18-33, M = 25, SD = 4.2) gave informed consent and took part in the study. Participants had normal or corrected-to-normal vision and no history of neurological or psychiatric disorders. All procedures were approved by the University of Manchester Research Ethics Committee. One participant was excluded from all analyses due to failure to learn the cue-outcome contingency during the rule-learning task.

Procedure. A similar paradigm and expectation manipulation was used in Experiment 2, with the following exceptions; in the encoding phase, each object was presented three times consecutively. Each object was on the screen for 2000ms, with a jittered fixation cross (250-750ms) between each presentation. During the first and second presentations participants were asked to make a semantic decision about the object, whether it is man-made or natural, and whether it is more likely to be found indoors or outdoors. The order of these questions was random. During the third presentation participants were always asked to study the object carefully focusing on the details. Following the third presentation there was another jittered fixation cross, for a longer period of time (800-1200ms), to create mini-blocks separating each object.

The rule-learning task was identical to that used in Experiment 1, except a longer response presentation time of the cue (3s instead of 1s) and a jittered fixation cross (250-750ms) between each trial (see Supplementary Figure S.1 for behavioural and Figure S.2 for fMRI results from the rule learning task). Before the retrieval task, participants solved arithmetic problems for two minutes (not scanned). At retrieval, we used two levels of foil similarity (F1 and F2) in each set, instead of three. F3 objects were not used, as they did not yield any effects of interest in the Experiment 1. Each retrieval trial started with a jittered fixation cross (250-750ms), followed by a presentation of the cue for 1000ms and then the set event (target, F1 or F2) for

3000ms. In all scanned tasks, we used implicit baselines (fixation crosses for

3500ms in encoding and rule-learning tasks, 4500ms in retrieval) in 30% of trials.

Behavioural data analysis. Following the analysis and results from Experiment 1, we

collapsed targets and F1 events and modelled the probability of making a correct

decision (hits and correct rejections) based on the current set event's expectation

status and the previous set event's expectation status. As in Experiment 1, to

eliminate the memory strength confound, only correct responses were included (See

Supplementary Figure S.3 for similar results when including all trials, and

Supplementary Figure S.4 for separate analyses of targets and F1). Correct

rejections of F2 foils were also modelled as a function of previous set events, as was

done for Experiment 1.

fMRI acquisition and analysis. MR scanning was carried out on a 3T MRI scanner

(Philips, Achieva). To minimise movement during the scan, foam wedges and soft

pads were used to stabilise the participant's head. First, T1-weighted images (matrix

size: 256x256, 160 slices, voxel size 1mm isotropic) were collected while participants

rested in the scanner. A gradient echo-planar imaging (EPI) sequence was used to

collect T2* images for the BOLD signal. 40 slices parallel to the AC-PC line, covering

the whole brain (matrix size 80 x 80, voxel size 3 x 3 x 3.5mm^3), were obtained for

each volume (TR = 2.5s, TE = 35ms). Participants performed three tasks in the

scanner (encoding 313 volumes; rule-learning 143 volumes; retrieval 534 volumes)

and a distractor task, which was not scanned.

fMRI data were pre-processed and analysed using SPM12 (Statistical Parameter

Mapping, Wellcome Centre for Human Neuroimaging, University College London

https://www.fil.ion.ucl.ac.uk/spm/software/spm12/). Images were realigned to the

mean image using a six-parameter rigid body transformation, resliced using sinc

interpolation and slice-time corrected to the middle slice. T1 anatomical images were

co-registered to the corresponding mean EPI image. Spatial normalisation to the

Montreal Neurological Institute (MNI) template was carried out using the DARTEL

toolbox implemented in SPM12 (Ashburner, 2007). An isotropic 8mm FWHM

Gaussian kernel was used for smoothing the normalised EPI data for univariate

analyses. The same pre-processing pipeline, without smoothing, was used for the

encoding-retrieval similarity analysis (see *reinstatement analysis below*). Two a-priori

regions of interest (ROIs), the bilateral hippocampus, and a midbrain ROI including
only the substantia nigra (SN) and ventral tegmentum area (VTA) were used. The
hippocampus mask was taken from the Harvard-Oxford anatomical atlas (threshold
at 25% probability; Desikan et al., 2006). The midbrain mask was taken from the
probabilistic atlas of the midbrain (Murty et al., 2014).

Univariate analyses. Each participant's functional data from the retrieval session was
analysed using the general linear model (GLM) framework within an event-related
design modelling the canonical hemodynamic response function. The six motion
parameters produced at realigmnet for each session were used as nuisance
regressors. To minimise residual motion artefacts the ArtRepair toolbox
(http://cibsr.stanford.edu/tools/human-brain-project/artrepair-software.html) was used
to produce additional nuisance regressors for each participant. The time series were
high-pass filtered to remove low frequency noise (128s cut-off). All activations
reported are significant at the uncorrected level p < 0.001 with at least 9 contiguous
voxels. Given our a priori hypothesis for the ROIs introduced above (bilateral
hippocampus and SN/VTA), a small volume correction (SVC) approach was
adopted. When SVC was applied, activations were also corrected for family-wise
error (FWE) for the ROI volume.

To test the behavioural effect of an interaction between a previous event's contextual
expectation and the current event's contextual expectation, we collapsed targets and
F1 and classified them based on presentation order (which came first) and their
expectation status. F2 events were modelled as a separate condition. In this
analysis, we compare the current item between current and previous expectation
status (e.g. $E_{prev}U_{curr} > E_{prev}E_{curr}$; see Supplementary materials for analysis of the
previous item). Given our experimental design, there are four parameters whose
interactions could be further explored: set event (target, F1, F2), contextual
expectation (expected or unexpected), memory response given (correct or incorrect)
and presentation order within the set (first, second or last). This results in 36
conditions, however, these could not be modelled together due to insufficient number
of trials per bin (n < 7) for the majority of participants. Therefore, we devised two
separate models; in the first model, we examined expectation x set event x
successful memory interactions by collapsing trials across presentation order, and
modelling only correct responses for each event (all incorrect responses were

modelled as a separate regressor). In the second model, we explored the interaction
of expectation, set event and presentation order, irrespective of recognition
responses.

Bottom-up encoding analysis. In this analysis we examined regions in which retrieval
activity correlated with block-by-block estimates of encoding activity. To do so, we
extracted hippocampal univariate encoding activity (beta estimates) during each
encoding mini-block (three repetitions of the same item). These estimates were used
as parametric modulators applied to retrieval data in a GLM analysis splitting
retrieval trials by expectation status. Next, we converted the beta estimates of
encoding activity within this mask into t-maps and used them as parametric
modulators applied to retrieval data (using the beta estimates did not change the
results). This approach allowed us to query retrieval data looking for regions whose
retrieval activity correlated with hippocampal encoding activity for expected vs.
unexpected events.

Reinstatement analysis. To identify which regions showed top-down retrieval-
oriented activity, we conducted an encoding-retrieval similarity (ERS) analysis using
CosmoMVPA (Oosterhof, Connolly, & Haxby, 2016) in Matlab R2018a (MathWorks
Inc.). For this purpose, we modelled each encoding mini-block as a condition of
interest. For each of the 78 blocks, we converted the beta estimate map into a t-
statistics (Dimsdale-Zucker & Ranganath, 2019). As one participant's last trial at
encoding could not be estimated, only 77 sets were analysed for this participant.
Data were mean-centred and pairwise Pearson's correlations between all trials were
calculated and Fisher z-transformed. This analysis was carried out in bilateral
hippocampus, as an a-priori ROI. Hippocampal ERS scores were then used as
parametric regressors that were applied to retrieval data in a model splitting trials
based on their expectation status and set event. This was done to examine which
regions exhibited retrieval activation that correlated with hippocampal ERS, capturing
reinstatement of the encoded object.

Behavioural Results

Examining responses to targets and F1 events, we found a main effect of the
previous set event's expectation status ($\beta = 0.309$, $X^2(1) = 4.13$, $p = 0.042$), as well
as an interaction between the current and previous events' expectation status ($\beta = -$

0.59, $X^2(1) = 4.47$, p = 0.034). Subsequent contrast tests revealed better memory
performance for expected events following unexpected ones, compared to those
following expected events ($U_{prev}E_{curr} > E_{prev}E_{curr}$; z = 2.55, p = 0.011). For set events
following unexpected ones, better memory was also found for expected compared to
unexpected events ($U_{prev}E_{curr} > U_{prev}U_{curr}$; z = 2.68 p = 0.007). Therefore, these
results provide a direct replication of the results from Experiment 1. Next, we
examined CR2 as a function of the previously seen targets and F1 events, and their
expectation status. For F2 following targets, a main effect of the target's expectation
status was observed (β = 0.488, $X^2(1) = 6.4$, p = 0.011), with more CR2 following
unexpected targets. All other effects were not significant (all p's > 0.193). For F2
following F1 events, there was a trend towards a main effect of the previous F1
expectation (β = 0.367, $X^2(1) = 3.14$, p = 0.076), with more CR2 following
unexpected F1 events.
429
<u>fMRI results</u>
Current by previous expectation interactions. We first examined the neural correlates
of the behavioural contextual expectation interaction reported above. For current
expected events that followed unexpected events, compared to those following a
previous expected event ($U_{prev}E_{curr} > E_{prev}E_{curr}$; see Figure 3b), we found increased
activation in the hippocampus, bilaterally (right: x = 36, y = -33, z = -12, k = 12, SVC
p_{FWE} = 0.04; left: x = -36, y = -45, z = -9, k = 10), SN/VTA (x = 9, y = -24, z = -12, k =
11, SVC p_{FWE} = 0.039), and left inferior occipital gyrus (BA 18; x = -18, y = -87, z = 0,
k = 26). There was also increased activation in the right hippocampus (x = 24, y = -
33, z = -6, k = 10, SVC p_{FWE} = .045) and left parahippocampus (x = -33, y = -45, z = -
6, k = 10) for current unexpected events following previous expected ones,
compared to current unexpected events, which followed an unexpected event
($E_{prev}U_{curr} > U_{prev}U_{curr}$). Critically, in both contrasts the examined set events had the
same expectation status, and differed only on the expectation status of the previous
event.

y = -26   x = -18   z = 16

Figure 3 | Behavioural and neural expectation interactions for targets and F1 foils. A)
Behavioural results. Replicating the results from Experiment 1, a current by previous expectation
status interaction was observed, with $U_{prev}E_{curr}$ showing a boost in memory performance. **B)**
UprevEcurr > EprevEcurr contrast. Increased activation in the right hippocampus, SN/VTA and left
inferior occipital cortex. **C) Unexpected > Expected interactions.** Increased activation in right
occipital cortex (BA 18) was observed for $U_{prev}U_{curr} > E_{prev}E_{curr}$, $U_{prev}U_{curr} > E_{prev}U_{curr}$, despite poor
memory performance for $U_{prev}U_{curr}$ events. **D) Expected > Unexpected interactions.** Increased
activation in right retrosplenial cortex/precuneus for $U_{prev}E_{curr} > U_{prev}U_{curr}$, and increased activation in
right primary motor cortex for $E_{prev}E_{curr} > E_{prev}U_{curr}$.

Comparing current expected vs. unexpected events, following previously unexpected

events ($U_{prev}E_{curr} > U_{prev}U_{curr}$; Figure 3d) revealed activation in the right retrosplenial

cortex/precuneus (x = 21, y = -45, z = 12, k = 24). The complementary contrast

following expected events, $E_{prev}E_{curr} > E_{prev}U_{curr}$ (Figure 3d), was associated with

increased activation in primary motor cortex (BA 4, x = 60, y = 0, z = 15, k = 11). For

contrasts in which unexpected events elicited more activations than expected ones,

despite showing reduced memory performance ($U_{prev}U_{curr} > E_{prev}E_{curr}$ and $U_{prev}U_{curr} >$

$E_{prev}U_{curr}$; Figure 3c), we found increased activation in right occipital cortex ($U_{prev}U_{curr}$

> $E_{prev}U_{curr}$: BA 18, x = 15, y = -93, z = 9, k =25; $U_{prev}U_{curr} > E_{prev}E_{curr}$: BA 18, x = 18,

y = -93, z = 9, k = 36). Comparing the first (previous) event between conditions (first

expected vs. first unexpected) did not reveal any significant effects (see

Supplementary Figure S.5 for behavioural results of all first set events).

Main effects of expectation. To explore whether expected and unexpected events,
across event types, responses, and positions elicited differential activations in a
bottom-up (ventral visual stream) or reinstatement (recollection network) manner, we
also compared the two conditions using an F contrast (see Figure 4a). We found
increased activity for unexpected > expected events in right occipital cortex (BA 19, x
= 39, y = -75 z = 15, k = 28; and BA 18, x = 18, y = -93, z = 12, k = 10) and right
fusiform gyrus (BA 37, x = 27, y = -48, z = -18, k = 38). Increased activation in the
right inferior parietal lobe (angular and supramarginal gyri; BA 39 and BA 40, x = 39,
y = -51, z = 30, k = 9), was observed for expected > unexpected events.

Expectation by memory interactions. To unpack the overall unexpected > expected
effect, we tested how contextual expectation interacted with successful recognition
decisions (hits and CR), across presentation order. Whilst no differential neural
responses were found for expected and unexpected hits or correct rejections of F2
events, we observed increased activation in the right inferior occipital gyrus (BA 19, x
= 27, y = -78, z = -6, k = 20) for unexpected CR1 > expected CR1.

Expectation by presentation order interactions. Finally, we examined interactions
between expectation status and presentation order (across set events in Figure 4b;
see Supplementary Figure S.6 for break-down per set event). We observed again
increased activity in two clusters in occipital cortex (BA19, x = 33, y = -78, z = 15, k =
424, and BA 18, x = -21, y =-90, z = 15, k = 72) as well as in right fusiform gyrus (BA
37, x = 21, y = -42, z = -12, k = 25) for unexpected > expected events presented
second in the set (no unexpected > expected effects were found for first or third set
events).

Figure 4 | Overall neural expectation effects. A) Main effect of expectation. Unexpected events,
compared to expected ones, engaged more activation in right middle occipital cortex and right
fusiform. Conversely, excepted events, compared to unexpected ones, engaged activation in right
angular and supramarginal gyri. **B) Expectation by presentation order interaction.** Unexpected
events presented second in the set engaged regions along the ventral visual stream. No effects were
observed for first or third set events. **c) Schematic of reinstatement and encoding analyses.**
Encoded-related hippocampal activity and encoding-retrieval similarity were used as parametric
modulators (in separate analyses) to query retrieval activation for expected and unexpected events.
D) Reinstatement analysis results. Activity in the supramarginal gyrus and right middle temporal
gyrus (not shown) during retrieval of expected events correlated with hippocampal ERS. No effects
were observed for unexpected events. **E) Bottom-up analysis results.** ACC activation during
unexpected events at retrieval correlated with hippocampal encoding activity, no effects were
observed for expected events.

Bottom-up parametric encoding analysis. Using hippocampal encoding activity as a

parametric modulator (Figure 4e), we found increased hippocampal encoding

correlated with increased involvement of anterior cingulate cortex (x = 1, y = 39, z =

3, k = 173; Figure 4e) for unexpected events. We did not observe any activation for

expected events at retrieval that was modulated as a function of hippocampal

encoding activity.

Reinstatement analysis. Increased hippocampal encoding-retrieval similarity (Figure

4d) was associated with increased activity in middle temporal gyrus (x = -42, y = -36,

z = -3, k = 11) and supramarginal gyrus (x = 30, y = -30, z = 36, k = 9) during
retrieval of expected events. We did not observe any activation for unexpected
events at retrieval that correlated with hippocampal ERS.

Figure 5 | Illustration of the brain networks involved in processing unexpected and expected
events. A) Expectation-driven, task-independent encoding. Expectation violation engages
bottom-up processing along the ventral visual stream, regardless of memory performance. The later
mnemonic consequences of this shift towards encoding involve the hippocampus and midbrain
dopaminergic regions, underlying beneficial memory performance. The ACC possibly interacts with
the dopaminergic system to instigate encoding. B) **Task-driven retrieval.** In the absence of
expectation violation (expected events), engagement of parietal regions of the core recollection
network support reinstatement and memory performance.
526

Discussion

In two experiments, we used a contextual expectation manipulation during retrieval
to examine how expectation violation dynamically modulates information processing
and subsequent hippocampal-dependent memory. We found unexpected events
were associated with increased involvement of regions along the ventral visual
stream and correlated with hippocampal encoding activity. Furthermore, the
combination of two unexpected similar events ($U_{prev}U_{curr}$) resulted in the poorest
memory performance, suggesting expectation violation can hamper memory
performance by preferentially engaging a bottom-up encoding state. Interestingly, we
also found a later beneficial effect of contextual surprise, such that presentation of an
unexpected event did not support its recognition, but it did boost correct recognition
of the following expected and similar set events (targets and F1). This behavioural
effect was associated with increased activity in the hippocampus, midbrain
dopaminergic regions (SN/VTA), and occipital cortex. Expected events, on the other
hand, were associated with reinstatement-like activity in parietal regions. Taken
together, these results provide first direct evidence for dynamic engagement of a

bottom-up encoding mechanism, at the expense of retrieval, and its mnemonic
consequences (Figure 5).

Expectation violation is often associated with improved memory performance,
attributed to adaptive memory formation (Kumaran & Maguire, 2007; Lisman &
Grace, 2005; Shohamy & Wagner, 2008). Our results lend support to the latter part
of this notion, and extend it to account for task-independent effects. In line with the
idea that increased weight is given to bottom-up inputs upon encountering a
prediction error (Kafkas & Montaldi, 2018b; Stoppel et al., 2009), we found increased
involvement of visual processing regions in occipital cortex and fusiform gyrus for
unexpected events. These regions have been found to preferentially respond to
stronger levels of unexpected novelty (Kafkas & Montaldi, 2014), resulting in
increased perceptual processing of unexpected events. Although memory formation
relies on such bottom-up processing, in order to provide evidence for an encoding
mechanism it is necessary to also demonstrate mnemonic consequences of the
increased weight on sensory inputs. Indeed, we observed an interaction between
current and previous expectation status of similar events (targets and F1), such that
memory performance was modulated by a previous unexpected event (improved
recognition performance for $U_{prev}E_{curr}$, reduced for $U_{prev}U_{curr}$).

Whilst occipital involvement was observed for both $U_{prev}E_{curr}$ and $U_{prev}U_{curr}$ events
(i.e. irrespective of memory performance), $U_{prev}E_{curr}$ events were also associated with
hippocampal and SN/VTA activation. This finding, together with the memory boost
for $U_{prev}E_{curr}$ events, pertains to the role these regions play in mediating processing
of perceptual inputs for memory formation. In terms of shifting the weight towards
bottom-up inputs, the hippocampus is well placed at the apex of the sensory
hierarchy and well connected with midbrain dopaminergic regions (Lisman & Grace,
2005), to be in the driver's seat. This could also explain why we did not observe
hippocampal or SN/VTA activation for any other unexpected contrasts; their co-
activation is likely associated with a boost in memory performance (Kafkas &
Montaldi, 2015). Taken together, these findings suggest that expectation-driven
increased weight on bottom-up inputs is task-independent, but its mnemonic
consequences appear to depend on the task at hand. During learning or exploration,
further encoding supports later memory for the unexpected event (Garrido, Barnes,

Kumaran, Maguire, & Dolan, 2015; Greve, Cooper, Kaula, Anderson, & Henson,
2017; Gruber, Watrous, Ekstrom, Ranganath, & Otten, 2013; Li, Cullen, Anwyl, &
Rowan, 2003; Long et al., 2016). On the other hand, when retrieval is necessary (as
in the current paradigm), the shift towards encoding, despite increased perceptual
processing, results in worse memory performance (Duncan, Sadanand, et al., 2012;
G. Kim et al., 2014). Therefore, the consequences of processing unexpected events
may be contrasting in the short- and the long-term. In the short-term, while another
task is performed, unexpected events can be disruptive, while in the long-term they
can be beneficial, when memory for similar events is tested (as in the present study)
or when memory for the unexpected stimulus is tested after a delay (Frank et al.,
2020; Kafkas & Montaldi, 2015).

Most of the previous research into shifts between encoding and retrieval states was
done in rodents (Hasselmo & Stern, 2014), or in humans where explicit instructions
were utilised (Richter et al., 2016). Recently, Bein and colleagues (2020) showed
functional connectivity between hippocampal subfield CA1 and entorhinal cortex or
CA3 (reflecting a bias towards an encoding or a retrieval state, respectively) was
modulated by mnemonic prediction errors. Bein et al. (2020) postulated the bias they
observed towards one hippocampal state or another could be modulated by
dopaminergic inputs (Kafkas & Montaldi, 2018b; Lisman & Grace, 2005). In line with
these results, using a manipulation that was independent of the memory task (and
completely implicit to most participants), we found expectation-driven hippocampal
and midbrain activation, which we suggest reflects an encoding response triggered
by expectation violation (Bein et al., 2020). The mnemonic consequences of this shift
are manifested in more accurate recognition of later highly similar expected events.
Further support for engagement of hippocampal encoding state can be found in the
increased activity along the ventral visual stream for unexpected compared to
expected events, reflecting increased bottom-up processing (Haque, Inati, Levey, &
Zaghloul, 2020). We propose the increased gain on bottom-up inputs, together with
the hippocampal-midbrain activations, are markers of encoding state triggered by
expectation violation, even in the absence of explicit reward or instructions.

Although a shift towards encoding, and away from retrieval, upon encountering an
unexpected event can explain why we do not observe a memory boost for these

events (but for subsequent expected events), it is worth considering why increased
encoding of the U_{prev} event results in better memory performance for the subsequent
E_{curr} event. One possibility is that the initial shift towards encoding results in a
sharper representation of U_{prev}. This then representation stands out in memory,
when the subsequent expected similar event is presented (Haque et al., 2020).
Therefore, the current expected event could be compared to originally encoded
objects, and the unexpected one from earlier at retrieval. The combined delta
similarity between these representations can inform and aid the current recognition
decision for the current expected event. An alternative interpretation for this finding is
a prospective memory enhancement (Dunsmoor, Murty, Davachi, & Phelps, 2015;
Oyarzún, Packard, de Diego-Balaguer, & Fuentemilla, 2016). Aversive (Dunsmoor et
al., 2015) and rewarding (Oyarzún et al., 2016) stimuli have been shown to up-
regulate encoding and consolidation of temporally- or semantically close stimuli,
supporting prospective memory enhancement for these inconsequential items.
Whilst prospective enhancement could explain the boost in E_{curr} memory
performance, this account does not explain the poor memory performance for
$U_{prev}U_{curr}$ events, nor does it predict the selectivity of these effects to highly similar
inputs in a relatively short period of time (i.e. without offline consolidation).
629
Critically, the interactions between current and previous events' expectation were
observed only for targets and F1 (i.e. the highest degree of similarity to the encoded
object). Moreover, these effects were unaffected by interfering events from the same
set (F2, and in Experiment 1 also F3) or events from different sets presented during
the task (i.e. there could be up to 200 trials between targets and F1s from the same
set). The selectivity of the expectation interactions to the higher end of the
perceptual similarity scale, and their robustness with respect to interference from
other stimuli, suggests that a high perceptual and memorial load is required to trigger
this encoding mechanism, extending previous findings (Bein et al., 2020; Haque et
al., 2020). In such situations, the ability to process and compare fine details in
current inputs and stored representations underpins correct recognition decisions
(Yassa & Stark, 2011). Therefore, engagement of perceptual processing by
expectation violation serves an adaptive purpose (Hawco & Lepage, 2014; Stoppel
et al., 2009). For less similar events, which are more easily recognised as new (F2,

F3), the effect of a sharper representation elicited by expectation violation is less
relevant and therefore redundant (Frank et al., 2020).

Further support for the role of perceptual load in engaging encoding state can be
seen in the occipital and fusiform effects for unexpected events presented second
within the set, compared to their expected counterparts. Recognition decisions for
these events encompass interference from the first set event, and may therefore
lead to increased engagement of perceptual processing in order to better compare
the current sensory input to the stored representations. Whilst the encoding effects
of unexpected events observed along the ventral visual stream can be explained by
the bottom-up account (Kafkas & Montaldi, 2018b; H. Kim, 2011), we also found
hippocampal encoding activity correlated with ACC activation for unexpected events
at retrieval. ACC has been implicated in cognitive control and error monitoring
(Carter & van Veen, 2007). These functions are directly relevant to the unexpected
events utilised in the current task, but they do not necessarily explain the correlation
to hippocampal encoding reported above. More recent findings suggest that ACC
interacts with the dopaminergic system to instigate encoding of rewarding
information (Aberg, Kramer, & Schwartz, 2020; Elston & Bilkey, 2017). Our results
are in line with this notion, suggesting ACC is not only involved in error detection, but
also in subsequent encoding of the unexpected outcome even when reward is not
explicitly present in the task.

As the expectation manipulation took place during retrieval, it remains unclear
whether expected events resulted in a task-relevant retrieval, or an active
engagement of a retrieval state, irrespective of task demands. Although the
observed activation in regions of the core recollection network (Hayama, Vilberg, &
Rugg, 2012) in response to expected events (in the univariate and in the ERS
analyses) is indicative of reinstatement, it does not differentiate between the two
alternatives. To elucidate whether these effects relate to task-specific retrieval, or a
dynamic engagement of retrieval (irrespective of the task at hand), future studies
could orthogonalise expectation and memorial state, therefore allowing both
encoding and retrieval states to be engaged and measured independently.
Alternatively, one could include a baseline (expectation-less) measure for retrieval
performance, to be compared to retrieval of expected events. Such examinations of

shifts towards a retrieval state, perhaps coupled with designs optimised for functional
and effective connectivity, will contribute to on-going efforts to elucidate how the
hippocampus shifts between memory states (Bein et al., 2020; Colgin, 2016; Kafkas
& Montaldi, 2018b). Finally, it would be of interest to characterise the temporal
dynamics of the expectation violation and bottom-up processing. This approach
could shed light on the role ventral visual processing stream plays in modulating
memory circuits, and vice versa.

In conclusion, we found novel evidence for a ubiquitous encoding mechanism,
triggered by expectation violation in a goal-irrelevant matter. Overall, unexpected
events were associated with activation along the ventral visual stream, whereas
expected events were associated with activations in parietal regions of the core
recollection network. A combination of unexpected followed by expected similar
events, was associated with a boost in recognition performance and activation in the
hippocampus, SN/VTA and occipital cortex. On the other hand, a combination of two
unexpected events was associated with poor recognition, and activation in occipital
cortex. These results indicate that the expectation-driven shift towards an encoding
state, supported by bottom-up processing, is detrimental to memory performance in
real time, but beneficial for correct recognition of subsequent similar events.

References

Aberg, K. C., Kramer, E. E., & Schwartz, S. (2020). Interplay between midbrain and

dorsal anterior cingulate regions arbitrates lingering reward effects on memory

encoding. *Nature Communications*, *11*(1), 1829. https://doi.org/10.1038/s41467-

020-15542-z

Aly, M., & Turk-Browne, N. B. (2017). How Hippocampal Memory Shapes, and Is

Shaped by, Attention. In *The Hippocampus from Cells to Systems* (pp. 369–

403). Cham: Springer International Publishing. https://doi.org/10.1007/978-3-

319-50406-3_12

Ashburner, J. (2007). A fast diffeomorphic image registration algorithm. *NeuroImage*,

38(1), 95–113. https://doi.org/10.1016/j.neuroimage.2007.07.007

Axmacher, N., Cohen, M. X., Fell, J., Haupt, S., Dümpelmann, M., Elger, C. E., …

Ranganath, C. (2010). Intracranial EEG Correlates of Expectancy and Memory

Formation in the Human Hippocampus and Nucleus Accumbens. *Neuron*, *65*(4),

541–549. https://doi.org/10.1016/j.neuron.2010.02.006

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects

Models Using lme4. *Journal of Statistical Software*, *67*(1).

https://doi.org/10.18637/jss.v067.i01

Bein, O., Duncan, K., & Davachi, L. (2020). Mnemonic prediction errors bias

hippocampal states. *Nature Communications*, *11*(1), 3451.

https://doi.org/10.1038/s41467-020-17287-1

Buzsáki, G. (2002). Theta Oscillations in the Hippocampus. *Neuron*, *33*(3), 325–340.

https://doi.org/10.1016/S0896-6273(02)00586-X

Carter, C. S., & van Veen, V. (2007). Anterior cingulate cortex and conflict detection:

an update of theory and data. *Cognitive, Affective & Behavioral Neuroscience*,

7(4), 367–379. https://doi.org/10.3758/cabn.7.4.367

Colgin, L. L. (2016). Rhythms of the hippocampal network. *Nature Reviews*

Neuroscience, *17*(4), 239–249. https://doi.org/10.1038/nrn.2016.21

Desikan, R. S., Ségonne, F., Fischl, B., Quinn, B. T., Dickerson, B. C., Blacker, D.,

… Killiany, R. J. (2006). An automated labeling system for subdividing the

human cerebral cortex on MRI scans into gyral based regions of interest.

NeuroImage, *31*(3), 968–980. https://doi.org/10.1016/j.neuroimage.2006.01.021

Dimsdale-Zucker, H. R., & Ranganath, C. (2019). Representational Similarity

Analyses: A Practical Guide for Functional MRI Applications. *Handbook of*

732 *Behavioral Neuroscience*, *28*, 509–525. https://doi.org/10.1016/B978-0-12-
733 812028-6.00027-6

734 Duncan, K., Ketz, N., Inati, S., & Davachi, L. (2012). Evidence for area CA1as a
735 match/mismatch detector: A high-resolution fMRI study of the human
736 hippocampus. *Hippocampus*, *22*(3), 389–398.
737 https://doi.org/10.1002/hipo.20933.Evidence

738 Duncan, K., Sadanand, A., & Davachi, L. (2012). Memory's Penumbra: Episodic
739 Memory Decisions Induce Lingering Mnemonic Biases. *Science*, *337*(6093),
740 485–487. https://doi.org/10.1126/science.1221936

741 Dunsmoor, J. E., Murty, V. P., Davachi, L., & Phelps, E. A. (2015). Emotional
742 learning selectively and retroactively strengthens memories for related events.
743 *Nature, 520*(7547), 345–348. https://doi.org/10.1038/nature14106

744 Elston, T. W., & Bilkey, D. K. (2017). Anterior Cingulate Cortex Modulation of the
745 Ventral Tegmental Area in an Effort Task. *Cell Reports*, *19*(11), 2220–2230.
746 https://doi.org/10.1016/j.celrep.2017.05.062

747 Fox, J. (2003). Effect Displays in R for Generalised Linear Models. *Journal of*
748 *Statistical Software*, *8*(15). https://doi.org/10.18637/jss.v008.i15

749 Fox, J., & Weisberg, S. (2018). *An R Companion to Applied Regression*. Sage.

750 Frank, D., Gray, O., & Montaldi, D. (2019). SOLID-Similar object and lure image
751 database. *Behavior Research Methods*. https://doi.org/10.3758/s13428-019-
752 01211-7

753 Frank, D., Montemurro, M. A., & Montaldi, D. (2020). Pattern Separation Underpins
754 Expectation-Modulated Memory. *The Journal of Neuroscience*, *40*(17), 3455–
755 3464. https://doi.org/10.1523/JNEUROSCI.2047-19.2020

756 Friston, K. J. (2005). A theory of cortical responses. *Philosophical Transactions of*
757 *the Royal Society B: Biological Sciences, 360*(1456), 815–836.
758 https://doi.org/10.1098/rstb.2005.1622

759 Garrido, M. I., Barnes, G. R., Kumaran, D., Maguire, E. A., & Dolan, R. J. (2015).
760 NeuroImage Ventromedial prefrontal cortex drives hippocampal theta
761 oscillations induced by mismatch computations. *NeuroImage*, *120*, 362–370.
762 https://doi.org/10.1016/j.neuroimage.2015.07.016

763 Greve, A., Cooper, E., Kaula, A., Anderson, M. C., & Henson, R. N. (2017). Does
764 prediction error drive one-shot declarative learning? *Journal of Memory and*
765 *Language, 94*, 149–165. https://doi.org/10.1016/j.jml.2016.11.001

Gruber, M. J., Watrous, A. J., Ekstrom, A. D., Ranganath, C., & Otten, L. J. (2013).

Expected reward modulates encoding-related theta activity before an event.

NeuroImage, *64*(1), 68–74. https://doi.org/10.1016/j.neuroimage.2012.07.064

Haque, R. U., Inati, S. K., Levey, A. I., & Zaghloul, K. A. (2020). Feedforward

prediction error signals during episodic memory retrieval. *Nature*

Communications, *11*(1), 1–14. https://doi.org/10.1038/s41467-020-19828-0

Hasselmo, M. E., Bodelon, C., & Wyble, B. P. (2002). A Proposed Function for

Hippocampal Theta Rhythm□: Separate Phases of Encoding and Retrieval

Enhance Reversal of Prior Learning. *Neural Computation*, *14*, 793–817.

Hasselmo, M. E., & Stern, C. E. (2014). Theta rhythm and the encoding and retrieval

of space and time. *NeuroImage*, *85*, 656–666.

https://doi.org/10.1016/j.neuroimage.2013.06.022

Hawco, C., & Lepage, M. (2014). Overlapping patterns of neural activity for different

forms of novelty in fMRI. *Frontiers in Human Neuroscience*, *8*.

https://doi.org/10.3389/fnhum.2014.00699

Hayama, H. R., Vilberg, K. L., & Rugg, M. D. (2012). Overlap between the Neural

Correlates of Cued Recall and Source Memory: Evidence for a Generic

Recollection Network? *Journal of Cognitive Neuroscience*, *24*(5), 1127–1137.

https://doi.org/10.1162/jocn_a_00202

Hindy, N. C., Ng, F. Y., & Turk-Browne, N. B. (2016). Linking pattern completion in

the hippocampus to predictive coding in visual cortex. *Nature Neuroscience*,

(April), 1–7. https://doi.org/10.1038/nn.4284

Kafkas, A., & Montaldi, D. (2014). Two separate, but interacting, neural systems for

familiarity and novelty detection: A dual-route mechanism. *Hippocampus*, *24*(5),

516–527. https://doi.org/10.1002/hipo.22241

Kafkas, A., & Montaldi, D. (2015). Striatal and midbrain connectivity with the

hippocampus selectively boosts memory for contextual novelty. *Hippocampus*,

25(11), 1262–1273. https://doi.org/10.1002/hipo.22434

Kafkas, A., & Montaldi, D. (2018a). Expectation affects learning and modulates

memory experience at retrieval. *Cognition*, *180*(July), 123–134.

https://doi.org/10.1016/j.cognition.2018.07.010

Kafkas, A., & Montaldi, D. (2018b). How do memory systems detect and respond to

novelty? *Neuroscience Letters*, *680*(January), 60–68.

https://doi.org/10.1016/j.neulet.2018.01.053

Ketz, N., Morkonda, S. G., & O'Reilly, R. C. (2013). Theta Coordinated Error-Driven
Learning in the Hippocampus. *PLoS Computational Biology*, *9*(6), e1003067.
https://doi.org/10.1371/journal.pcbi.1003067

Kim, G., Lewis-Peacock, J. a, Norman, K. A., & Turk-Browne, N. B. (2014). Pruning
of memories by context-based prediction error. *Proceedings of the National*
Academy of Sciences, *111*(24), 8997–9002.
https://doi.org/10.1073/pnas.1319438111

Kim, H. (2011). Neural activity that predicts subsequent memory and forgetting: A
meta-analysis of 74 fMRI studies. *NeuroImage*, *54*(3), 2446–2461.
https://doi.org/10.1016/j.neuroimage.2010.09.045

Kumaran, D., & Maguire, E. A. (2007). Which computational mechanisms operate in
the hippocampus during novelty detection? *Hippocampus*, *17*(9), 735–748.
https://doi.org/10.1002/hipo.20326

Li, S., Cullen, W. K., Anwyl, R., & Rowan, M. J. (2003). Dopamine-dependent
facilitation of LTP induction in hippocampal CA1 by exposure to spatial novelty.
Nature Neuroscience, *6*(5), 526–531. https://doi.org/10.1038/nn1049

Lisman, J. E., & Grace, A. a. (2005). The Hippocampal-VTA Loop: Controlling the
Entry of Information into Long-Term Memory. *Neuron*, *46*(5), 703–713.
https://doi.org/10.1016/j.neuron.2005.05.002

Long, N. M., Lee, H., & Kuhl, B. a. (2016). Hippocampal Mismatch Signals Are
Modulated by the Strength of Neural Predictions and Their Similarity to
Outcomes. *The Journal of Neuroscience*, *36*(50), 12677–12687.
https://doi.org/10.1523/JNEUROSCI.1850-16.2016

Meeter, M., Murre, J. M. J., & Talamini, L. M. (2004). Mode shifting between storage
and recall based on novelty detection in oscillating hippocampal circuits.
Hippocampus, *14*(6), 722–741. https://doi.org/10.1002/hipo.10214

Murty, V. P., Shermohammed, M., Smith, D. V., Carter, R. M., Huettel, S. A., &
Adcock, R. A. (2014). Resting state networks distinguish human ventral
tegmental area from substantia nigra. *NeuroImage*, *100*, 580–589.
https://doi.org/10.1016/j.neuroimage.2014.06.047

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal
Multivariate Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave.
Frontiers in Neuroinformatics, *10*(July), 1–27.
https://doi.org/10.3389/fninf.2016.00027

Oyarzún, J. P., Packard, P. A., de Diego-Balaguer, R., & Fuentemilla, L. (2016).

Motivated encoding selectively promotes memory for future inconsequential

semantically-related events. *Neurobiology of Learning and Memory*, *133*, 1–6.

https://doi.org/10.1016/j.nlm.2016.05.005

Peirce, J. W. (2007). PsychoPy-Psychophysics software in Python. *Journal of*

Neuroscience Methods, *162*(1–2), 8–13.

https://doi.org/10.1016/j.jneumeth.2006.11.017

R Development Core Team. (2008). R: A language and environment for statistical

computing. Retrieved from http://www.r-project.org

Richter, F. R., Chanales, A. J. H., & Kuhl, B. A. (2016). Predicting the integration of

overlapping memories by decoding mnemonic processing states during

learning. *NeuroImage*, *124*, 323–335.

https://doi.org/10.1016/j.neuroimage.2015.08.051

Searle, S. R., Speed, F. M., & Milliken, G. A. (1980). Population Marginal Means in

the Linear Model: An Alternative to Least Squares Means. *The American*

Statistician, *34*(4), 216–221. https://doi.org/10.1080/00031305.1980.10483031

Shohamy, D., & Adcock, R. A. (2010). Dopamine and adaptive memory. *Trends in*

Cognitive Sciences, *14*(10), 464–472. https://doi.org/10.1016/j.tics.2010.08.002

Shohamy, D., & Wagner, A. D. (2008). Integrating Memories in the Human Brain:

Hippocampal-Midbrain Encoding of Overlapping Events. *Neuron*, *60*(2), 378–

389. https://doi.org/10.1016/j.neuron.2008.09.023

Stoppel, C. M., Boehler, C. N., Strumpf, H., Heinze, H.-J., Hopf, J. M., Düzel, E., &

Schoenfeld, M. A. (2009). Neural correlates of exemplar novelty processing

under different spatial attention conditions. *Human Brain Mapping*, *30*(11),

3759–3771. https://doi.org/10.1002/hbm.20804

West, B. T., Welch, K. B., & Galecki, A. T. (2014). *Linear Mixed Models*. Chapman

and Hall/CRC. https://doi.org/10.1201/b17198

Wickham, H. (2009). *ggplot2*. New York, NY: Springer New York.

https://doi.org/10.1007/978-0-387-98141-3

Yassa, M. A., & Stark, C. E. L. (2011). Pattern separation in the hippocampus.

Trends in Neurosciences, *34*(10), 515–525.

https://doi.org/10.1016/j.tins.2011.06.006

866