1   Experiencing surprise: the temporal dynamics of its impact on memory
2
3
4   Darya Frank[1,2], Alex Kafkas[1], Daniela Montaldi[1]
5

6   [1] Division of Neuroscience and Experimental Psychology, School of Biological Sciences,
7   The University of Manchester, UK
8   [2] Laboratory for Clinical Neuroscience, Centre for Biomedical Technology, Universidad
9   Politécnica de Madrid, Spain

10
11
12
13

Abstract
To efficiently process information, the brain shifts between encoding and retrieval
states, prioritising bottom-up or top-down processing accordingly. Expectation
violation before or during learning has been shown to trigger an adaptive encoding
mechanism, resulting in better memory for unexpected events. Using fMRI we explored
(1) whether this encoding mechanism is also triggered during retrieval, and if so, (2)
what the temporal dynamics of its mnemonic consequences are. Male and female
participants studied object images, then, with new objects, they learned a contingency
between a cue and a semantic category. Rule-abiding (expected) and violating
(unexpected) targets and similar foils were used at test. We found interactions between
previous and current similar events' expectation, such that when an expected event
followed a similar but unexpected event, its performance was boosted, underpinned by
activation in the hippocampus, midbrain, and occipital cortex. In contrast, a sequence of
two unexpected similar events also triggered occipital engagement, however, this did
not enhance memory performance. Taken together, our findings suggest that when the
goal is to retrieve, encountering surprising events engages an encoding mechanism,
supported by bottom-up processing, that may enhance memory for future related
events.
32
Significance statement
Optimising the balance between new learning and the retrieval of existing knowledge is
an ongoing process, at the core of human cognition. Previous research into memory
encoding suggests experiencing surprise leads to the prioritisation of the leaning of new
memories, forming an adaptive encoding mechanism. We examined whether this
mechanism is also engaged when the current goal is to retrieve information. Our results
demonstrate that an expectation-driven shift towards an encoding state, supported by
enhanced perceptual processing, is beneficial for the correct identification of
subsequent expected similar events. These findings have important implications for our
understanding of the temporal dynamics of the adaptive encoding of information into
memory.
44
45
46

Introduction

To efficiently process inputs, the brain shifts between top-down and bottom-up
streams, balancing processing of sensory inputs versus utilisation of stored
representations. This is reflected by the existence of distinct encoding and retrieval
states (Buzsáki, 2002). Bottom-up processing supports the hippocampal encoding state,
prioritising transformation of perceptual inputs into memories, while top-down
processing supports a retrieval state by facilitating access to stored information. The
specific mechanisms that govern encoding-retrieval shifts, which may or may not
function competitively, are not well understood, but will be driven, at least in part, by
the factors that induce each memory state. Whilst there is ample evidence that an
adaptive encoding state is triggered upon experiencing discrepancies between expected
and encountered events, it remains unclear whether such an implicit learning
mechanism might also be engaged when the dominant goal is to retrieve, rather than
encode. Using behavioural (Experiment 1) and fMRI (Experiment 2) data, we examine
whether surprise produced by expectation violation at retrieval, results in a shift
towards an encoding state, accompanied by increased perceptual processing; and
whether this occurs at the expense of retrieval. We also investigate the extended
consequences of this expectation violation, and the potential encoding-retrieval
iterative shifts it might generate, by examining trial-by-trial recognition of subsequent
similar events.
67
Surprise, produced by expectation violation, has been shown to engage hippocampal
encoding (Axmacher et al., 2010; Kafkas and Montaldi, 2015; Long et al., 2016; Frank et
al., 2020), which together with the midbrain dopaminergic system (Lisman and Grace,
2005; Shohamy and Wagner, 2008; Kafkas and Montaldi, 2018a) and enhanced
perceptual processing (Stoppel et al., 2009; Hawco and Lepage, 2014; Kafkas and
Montaldi, 2014, 2015), supports adaptive memory formation. Evidence for this adaptive
mechanism comes mostly from paradigms in which expectation violation takes place
before or during learning (Li et al., 2003; Garrido et al., 2015; Long et al., 2016; Greve et
al., 2017; Kafkas, 2021). Therefore, any additional resources diverted towards encoding
in these scenarios is likely to boost later memory performance (e.g. attention effects see
Aly and Turk-Browne, 2017). However, to demonstrate the ubiquity of an adaptive
encoding mechanism, it is critical to provide evidence of a shift towards encoding also

during retrieval. This is likely to shed light on the effects of the rapid and implicit real-

life interplay between these states. Under these circumstances, engaging encoding still

serves an adaptive purpose, but it might not be 'beneficial' in real-time.

Given the malleability of memories triggered by surprise (Kim et al., 2014), it becomes

important to consider what the mnemonic consequences of a shift towards encoding

may be. Should expectation violation trigger an encoding state, at the expense of a

memory search, it might modulate processing of the unexpected event. This is

consistent with the view that the hippocampus continuously shifts between encoding

and retrieval states (Buzsáki, 2002; Hasselmo et al., 2002). This system can be likened

to a pendulum swinging rhythmically between the two memory states, optimising

information processing. Should situational factors disrupt the on-going swing between

states, favouring one over another, the result can be a change in memory efficiency.

Previous research has shown that an explicit strategy cue fosters a hippocampal trade-

off between encoding and retrieval of information (Richter et al., 2016).

We examined whether expectation violation at retrieval spontaneously engages an

encoding state, and if so, whether this response is dependent on the perceptual

similarity between inputs. We also considered the sustained mnemonic consequences of

such iterative shifts on current and subsequent recognition decisions. Expectation was

manipulated implicitly and independently of the requirements of the retrieval task,

allowing us to address two important questions; first whether expectation violation

engages a bottom-up encoding mechanism, even when it is not goal-relevant. Second,

what are the temporal dynamics of the mnemonic consequences of expectation status,

for an event and subsequent similar events. We reasoned that heightened expectation-

driven encoding might modulate current retrieval processes, but aid accuracy of

recognition of subsequent similar events.

<u>Methods</u>

Experiment 1

Participants. 30 participants (4 males) between the ages 18-22 (M = 19, SD = 1.04) gave

informed consent and took part in the experiment. The sample size was selected based

on previous studies utilising a similar design and analysis approach (Kafkas and

Montaldi, 2018b; Frank et al., 2020). Participants had normal or corrected-to-normal

vision and no history of neurological or psychiatric disorders. All procedures were

approved by the University of Manchester Research Ethics Committee. Four

participants were excluded from any further analysis due to failure to learn the cue-

outcome association (3) or recognition performance below chance (1). Data from 26

participants are reported.

Materials. 78 images of natural (39) and man-made (39) objects were selected from the

Similar Objects-Lures Image Database (SOLID; Frank et al., 2019). These images were

used as the target objects, presented during encoding. Using the dissimilarity index

from SOLID, three foils of decreasing levels of similarity (F1 – most similar, F2 – mid-

level F3 - lowest similarity) were selected for each target image. Additionally, similarity

was parametrically manipulated by keeping the average distance between the levels

constant (average dissimilarity 2100 DI; see Figure 1 for examples and Frank et al.,

2019 for further explanation on DI values). These levels of similarity were chosen based

on our previous results (Frank et al., 2020), where we observed a quadratic pattern of

expectation effects on inputs similarity, when expectation was manipulated at encoding,

with respect to memory performance. Therefore, 78 object sets (one target and three

foils; total 312 stimuli) were utilised.

Experimental design. The experiment was controlled using PsychoPy version 1.82

(Peirce, 2007) and consisted of four parts (similar to design used in Kafkas and

Montaldi, 2018b). First, at encoding, participants were presented with the target objects

twice to ensure sufficient exposure. During the first presentation, the object was shown

on the screen for 3 seconds, and participants were asked to decide whether the object

was man-made or natural; pressing the left arrow key for natural, and the right arrow

key for man-made. In the second presentation participants were asked to pay close

attention to the images (shown for 5s each) and were informed that they would be

asked to distinguish between the presented ('old') object and similar ('new') objects

later; they did not have to make any response during the second encoding presentation.

The order of image presentation was randomised across participants. The next phase

involved a 5-minute filled delay task, during which participants solved arithmetic

problems.

In the third phase, a rule-learning task was used to allow manipulation of expectation
later at retrieval. Participants were asked to learn the contingency between a symbol
(acting as a cue) and an object's category, man-made or natural. Four symbols were
used in total, two for each category, and these were counterbalanced between
participants. Each cue was presented 14 times. Trials began with a 500ms fixation point,
followed by the cue, presented for 1 second. During this time participants were
instructed to guess the following object's category by using the same keys as in the
encoding phase. Feedback and a new object (not tested) were then presented together
for 2 seconds. This task established participants' expectation regarding the cue-object
sequences, and critically this was manipulated at retrieval. To ensure expectations were
set, only data from participants who reached criterion (above 50% accuracy in the first
half, and 75% accuracy in the second half of the task) were analysed (See
Supplementary Figure S.1 for accuracy and RT in the rule-learning task).

The final phase was an old/new recognition task, during which all set events (targets,
F1, F2 and F3) were presented. The experimenter informed participants that they will
be presented with old (target) objects, and similar new ones (foils). Each retrieval trial
began with a fixation point (500ms), followed by a cue (1 second) and an object (up to 5
seconds). Participants were told to focus on the object and press 'old' if they thought it
was exactly the same as the target they had previously seen. Participants were
instructed to press 'new' if they noticed anything different in the object. Following 12
practice trials, the main task began. The key manipulation at retrieval was the validity of
the cue. One-third of the cues were misleading, making the object to-be-recognised
unexpected. Valid trials (e.g. cue natural followed by a natural object) were marked as
expected. As an old/new recognition task was used, the four old/new decisions per
object set were independent of each other, critically meaning that an 'old' response
could be given for multiple set events (i.e. for target and one or more foils). After
completing the experiment participants were debriefed regarding the expectation
manipulation at retrieval. Only two participants in Experiment 1 and five participants in
Experiment 2 reported noticing the mismatch between cue and object during the task.

Statistical analysis. To assess expectation-modulated dynamic encoding, we collated
object sets (apples, scissors etc.). In each set, there were four set events (target, F1 -
most similar, F2 – mid similarity, and F3 – least similar), each with a randomly assigned

(a) expectation condition, (b) presentation position within the set, and (c) order of

presentation at retrieval (1-312 trials). We ran a mixed-effects binary logistic

regression model on these ungrouped data, using expectation status of the current and

previous set events, and the presentation position at retrieval as a covariate. Models

were computed using the lme4 package (Bates et al., 2015) in the R environment (R

Development Core Team, 2008). The parameters of such models can be used to assess

the probability of giving a correct response ('old' for targets, 'new' for foils) and also

account for each participant's unique intercept (response bias). To assess the slope of

each predictor in the model (H$_0$: $\beta = 0$), we used an omnibus χ^2 Wald test (West et al.,

2014), as implemented in the car package (Fox and Weisberg, 2018). Extraction and

plotting of the effects reported below was conducted using the effects (Fox, 2003),

emmeans (Searle et al., 1980) and ggplot2 (Wickham, 2009) packages. To examine the

dynamic interaction between perceptual similarity and expectation status, for each set

event we devised three models of interest, modelling each event separately as a

function of the preceding event sequence. For example, targets preceded by F1 were

modelled separately from targets preceded by F2. To eliminate any effects driven by

memory strength differences, we only included in this model events for which the

previous response was correct (i.e. for targets following F1 events, we only included

targets that followed CR1). Similar results were observed when including all trials in the

model (see GitHub repository for code to run analyses and generate figures). Each

model thus included the current and previous set events' expectation status, as well as

the order of presentation at retrieval as a covariate. Code and data are available here:

https://github.com/frdarya/DynamicExpectation.

Experiment 2

Participants. 25 participants (8 males, ages 18-33, M = 25, SD = 4.2) gave informed

consent and took part in the study. Participants had normal or corrected-to-normal

vision and no history of neurological or psychiatric disorders. All procedures were

approved by the University of Manchester Research Ethics Committee. One participant

was excluded from all analyses due to failure to learn the cue-outcome contingency

during the rule-learning task.

Experimental design. A similar paradigm and expectation manipulation was used in

Experiment 2, with the following exceptions: in the encoding phase, each object was

presented three times consecutively. Each object was on the screen for 2000ms, with a
jittered fixation cross (250-750ms) between each presentation. During the first and
second presentations participants were asked to make a semantic decision about the
object, whether it is man-made or natural, and whether it is more likely to be found
indoors or outdoors. The order of these questions was random. During the third
presentation participants were always asked to study the object carefully focusing on
the details. Following the third presentation there was another jittered fixation cross,
for a longer period of time (800-1200ms), to create mini-blocks separating each object.

The rule-learning task was identical to that used in Experiment 1, except for a longer
response presentation time of the cue (3s instead of 1s) and a jittered fixation cross
(250-750ms) between each trial (see Supplementary Figure S.1 for behavioural and
Figure S.2 for fMRI results from the rule learning task). Before the retrieval task,
participants solved arithmetic problems for two minutes (not scanned). At retrieval, we
used two levels of foil similarity (F1 and F2) in each set, instead of three. In the interest
of optimising time-in-scanner, F3 objects were not used, as they did not yield any effects
of interest in Experiment 1. Each retrieval trial started with a jittered fixation cross
(250-750ms), followed by a presentation of the cue for 1000ms and then the set event
(target, F1 or F2) for 3000ms. In all scanned tasks, we used implicit baselines (fixation
crosses for 3500ms in encoding and rule-learning tasks, 4500ms in retrieval) in 30% of
trials.

Behavioural statistical analysis. Following the analysis and results from Experiment 1,
we collapsed targets and F1 events and modelled the probability of making a correct
decision (hits and correct rejections) based on the current set event's expectation status
and the previous set event's expectation status. As in Experiment 1, to eliminate the
memory strength confound, only correct responses were included (see GitHub
repository for similar results when including all trials, and for separate analyses of
targets and F1). Correct rejections of F2 foils were also modelled as a function of
previous set events, as was done for Experiment 1.

fMRI acquisition and statistical analysis. MR scanning was carried out on a 3T MRI
scanner (Philips, Achieva). To minimise movement during the scan, foam wedges and
soft pads were used to stabilise the participant's head. First, T1-weighted images
(matrix size: 256x256, 160 slices, voxel size 1mm isotropic) were collected while

participants rested in the scanner. A gradient echo-planar imaging (EPI) sequence was
used to collect T2* images for the BOLD signal. 40 slices parallel to the AC-PC line,
covering the whole brain (matrix size 80 x 80, voxel size 3 x 3 x 3.5mm^3), were obtained
for each volume (TR = 2.5s, TE = 35ms). Participants performed three tasks in the
scanner (encoding 313 volumes; rule-learning 143 volumes; retrieval 534 volumes) and
a distractor task, which was not scanned.

fMRI data were pre-processed and analysed using SPM12 (Statistical Parameter
Mapping, Wellcome Centre for Human Neuroimaging, University College London
https://www.fil.ion.ucl.ac.uk/spm/software/spm12/). Images were realigned to the
mean image using a six-parameter rigid body transformation, resliced using sinc
interpolation and slice-time corrected to the middle slice. T1 anatomical images were
co-registered to the corresponding mean EPI image. Spatial normalisation to the
Montreal Neurological Institute (MNI) template was carried out using the DARTEL
toolbox implemented in SPM12 (Ashburner, 2007). An isotropic 8mm FWHM Gaussian
kernel was used for smoothing the normalised EPI data for univariate analyses. To
remove low-frequency noise the data was high-pass filtered using a cut-off of 128s. Two
a-priori regions of interest (ROIs), the bilateral hippocampus, and a midbrain ROI
including only the substantia nigra (SN) and ventral tegmentum area (VTA) were used.
The hippocampus mask was taken from the Harvard-Oxford anatomical atlas (threshold
at 25% probability; Desikan et al., 2006). The midbrain mask was taken from the
probabilistic atlas of the midbrain (Murty et al., 2014).

Each participant's functional data from the retrieval session was analysed using the
general linear model (GLM) framework within an event-related design modelling the
canonical hemodynamic response function. The six motion parameters produced at
realigmnet for each session were used as nuisance regressors. To minimise residual
motion artefacts the ArtRepair toolbox (http://cibsr.stanford.edu/tools/human-brain-
project/artrepair-software.html) was used to produce additional nuisance regressors
for each participant. The time series were high-pass filtered to remove low frequency
noise (128s cut-off). Given our a priori hypothesis for the ROIs introduced above
(bilateral hippocampus and SN/VTA), a small volume correction (SVC) approach was
adopted for these regions, corrected for family-wise error (FWE) for the ROI volume
(initial cluster-forming threshold of p < 0.001). For more exploratory whole-brain

analyses, a non-parametric permutation-based (n = 5000) approach was used to
identify significant clusters using the SnPM toolbox
(https://warwick.ac.uk/fac/sci/statistics/staff/academic-
research/nichols/software/snpm/). An initial cluster-forming threshold of $p < 0.005$
was used, and clusters significant at a non-parametric $p < 0.05$ are reported.
Unthresholded group-level T-maps from SPM and SnPM are available here:
https://neurovault.org/collections/TTDMPHLE/.

To test the behavioural effect of an interaction between a previous event's contextual
expectation and the current event's contextual expectation, we collapsed targets and F1
and classified them based on presentation order (which came first) and their
expectation status. F2 events were modelled as a separate condition. In this analysis, we
compare the current item between current and previous expectation status (e.g.
$E_{prev}U_{curr} > E_{prev}E_{curr}$). Given our experimental design, there are four parameters whose
interactions could be further explored: set event (target, F1, F2), contextual expectation
(expected or unexpected), memory response given (correct or incorrect) and
presentation order within the set (first, second or last). This results in 36 conditions,
however, these could not be modelled together due to insufficient number of trials per
bin (n < 7) for the majority of participants. Therefore, we devised three separate
models; in the first model, we examined the main effect of expectation, irrespective of
set event or recognition decision. In the second model, we examined expectation x set
event x successful memory interactions by collapsing trials across presentation order,
and modelling only correct responses for each event (all incorrect responses were
modelled as a separate regressor). In the third model, we explored the interaction of
expectation, set event and presentation order, irrespective of recognition responses.

<u>Results</u>
We conducted two experiments, Experiment 1 examined behavioural responses, and
Experiment 2 employed a similar paradigm whilst fMRI data was collected. In both
Experiments, our behavioural task included three stages (see Figure 1 for experimental
design): following the encoding of object images, participants performed a rule-learning
task in which they learned a contingency between a cue and the object's category (man-
made or natural). Then, at retrieval, the same cues were presented, followed by an old

(target) or new (foil) object. Foils were parametrically manipulated similar objects, F1,

F2, F3 in a decreasing order of similarity to the target. Participants were asked to make

an old/new recognition decision. In one-third of the retrieval trials, the pre-established

cue and object category contingency was violated. To assess expectation-modulated

encoding, and its sensitivity to perceptual similarity, we used mixed-effects logistic

regression to model the response (correct/incorrect recognition) to each set event

(targets and similar foils) as a function of the preceding event from that set (e.g. if first

an F1 is presented, and later on a target, these would be noted $F1_{prev}$ $Target_{curr}$).

Furthermore, each set event was associated with an expectation status determined by

the preceding cue (rule-abiding events were marked as expected rule-violating as

unexpected). Each model also included an interaction between current and previous set

events' expectation status to examine dynamic changes (e.g. how a previous unexpected

foil affects recognition of a current expected target; see Figure 1c, and Methods for full

details).

318
Figure 1 | Experimental design. A) During the first round of **encoding**, participants responded whether
the object was man-made or natural. In the second encoding round, participants are asked to study the
object carefully. In Experiment 2, each object appeared three times consecutively; in addition to the two
presentations from Experiment 1, participants were asked to respond whether the object was more likely
to be found indoors or outdoors. The order of man-made/natural and in/outdoor questions was
randomised, the third presentation was always 'study carefully'. **B)** In the **rule-learning** task participants
learned a contingency between a cue and an object's category, man-made or natural. Participants had 1
second to make a decision in Experiment 1, and 3 seconds in Experiment 2. See Extended Data Figure 1-1
and 1-2 for rule-learning performance. **C)** In the **retrieval task**, the same cues were presented before
each set event, old objects (targets) and new similar foils (F1, F2, F3 in Experiment 1; F1 and F2 in
Experiment 2). On 30% of these trials there was a mismatch between the cue and the object's category,
these are unexpected trials (e.g., a cue for a natural object is followed by a man-made object, marked in
red). Participants were instructed to indicate whether the object is old or new. *$U_{prev}F1$, $EcurrT$* =
Unexpected F1 presented before an expected target, from the same set. **D) Example of range of**
perceptual similarity within set events.

Experiment 1

Memory for targets is modulated by preceding unexpected similar set events

For targets following F1 set events, we found significant main effects of the F1

expectation (β = 0.659, $X^2(1)$ = 4.63, p = 0.031), as well as a marginal interaction

between the target's expectation and the previous F1's expectation status (β = -0.939,

$X^2(1)$ = 3.65, p = 0.056; Figure 2a). Subsequent contrast tests revealed that expected

targets were more likely to be remembered following an unexpected F1, compared to

an expected F1 set event (z = 2.15, p = 0.031). Furthermore, when the previous F1 set

event was unexpected, the subsequent expected targets were more likely to be correctly

remembered, compared to unexpected targets (z = 2.37, p = 0.017). When examining

targets that followed F2 and F3 set events, we did not observe any significant predictors

(all p's > 0.127).

Correct rejection of similar foils is modulated by the expectation status of preceding

targets

For F1 events following targets, we found an interaction between the two events'

expectation status (β = -0.79, $X^2(1)$ = 5.29, p = 0.021; Figure 2B), with contrasts showing

more correct rejections of F1 events (CR1), for expected F1 than unexpected F1 events

following unexpected targets (z = 2.65, p = 0.008) and marginally less correct rejections

for unexpected F1 when the previous target was unexpected, compared to when it was

expected (z = 1.95, p = 0.0507; Figure 2 middle panel). All other effects were not

significant (all p's > 0.255). When examining F1 events that followed F2 and F3 set

events, we did not observe any significant predictors (all p's > 0.274).

Expectation sequence modulation decreases as perceptual similarity decreases

F2 events were not affected by previous targets (all p's > 0.171), F1s (all p's > 0.197), or

F3s (all p's > 0.174) from the same set. Similarlary, responses to F3 events were not

modulated by any preceding set events (targets: all p's > 0.484, F1s: all p's > 0.148, F2s:

all p's > 0.321).

Figure 2 | Experiment 1 Results. A) Predicting hits. More hits were observed for expected targets following unexpected F1 foils, compared to unexpected targets following unexpected F1, and compared to expected targets following expected F1. **B) Predicting CR1.** More CR1 for expected F1 following unexpected targets, compared to unexpected F1 following unexpected targets, and a marginal effect of poorer memory (less CR1) for a sequence of unexpected events. **C) Collapsed hits and CR1.** Similar results showing an interaction between the previous and current set events' expectation status, with $U_{prev}E_{curr}$ events showing the best memory performance, compared to $U_{prev}U_{curr}$ and $E_{prev}E_{curr}$. **D) First set events.** More hits for expected compared to unexpected targets presented first in the event sequence. No other significant effects, although F1 events follow a similar direction. Unless otherwise stated, all error bars represent 95% confidence intervals. $^{•}$ p = 0.0507 , * p < 0.05, ** p < 0.01.

Targets and their most similar foils show analogous expectation sequence effects

Given the similar effects observed for targets and F1 events independently, we collapsed the two, to examine whether these effects are complementary (i.e., whether there is an interaction between current and previous expectation status; Figure 2C). Although hits and correct rejections are not necessarily products of the same mnemonic process, in this paradigm they provide an opportunity to examine how perceptual load

(in the form of similarity) interacts with dynamic expectation modulations. The
mnemonic comparison between the current set event (target or F1) and its previous set
event (F1 or target, respectively), forms the highest load, or interference, in relation to
the encoded object, as the participant makes a recognition decision. Therefore, if
perceptual processes are engaged, upon encountering an unexpected event, the effects
observed for each set event individually should replicate. We found a significant main
effect of previous event's expectation status (β = 0.341, X^2(1) = 4.9, p = 0.027), as well as
a significant interaction between expectation status of the current and previous events
(β = -0.682, X^2(1) = 6.5, p = 0.01). Subsequent contrast tests revealed that when the
previous set event was unexpected, more correct responses were observed for expected
compared to unexpected events ($U_{prev}E_{curr} > U_{prev}U_{curr}$; z = 3.1, p = 0.002). $U_{prev}U_{curr}$ was
numerically smaller than $E_{prev}U_{curr}$, but this effect did not reach statistical significance (p
= 0.116). Additionally, there were more correct responses for current expected events
following unexpected than expected events ($E_{prev}E_{curr} < U_{prev}E_{curr}$; z = -2.22, p = 0.027).
396
Taken together, these results suggest expectation violation shifts processing away from
retrieval and towards encoding, and that the temporal dynamics of the mnemonic
consequences of this shift are reflected in the memory for the subsequent set event
(effects of first set events depicted in Figure 2D), as a function of perceptual similarity.
When subsequent events are unexpected ($U_{prev}U_{curr}$), we observed poor accuracy for F1
foils, and to a lesser extent for targets. On the other hand, when an unexpected event is
followed by an expected event ($U_{prev}E_{curr}$) a boost in performance was observed for the
current event, driven mainly by responses to targets. To examine whether these effects
engage the circuit involved in adaptive memory formation (including the hippocampus
and midbrain (Shohamy and Adcock, 2010; Kafkas and Montaldi, 2018a), as well as to
test the hypothesis that expectation violation engages an encoding mechanism,
supported by the bottom-up information stream (ventral visual pathway), in
Experiment 2 a new set of participants performed a similar task while fMRI data was
acquired (see Methods for minor task adjustments).
411
Experiment 2
<u>Behavioural Results</u>

Replicating the effects observed in Experiment 1, we found a main effect of the previous

set event's expectation status (β = 0.309, $X^2(1)$ = 4.13, p = 0.042), as well as an

interaction between the current and previous events' expectation status (β = -0.59,

$X^2(1)$ = 4.47, p = 0.034; Figure 3A). Subsequent contrast tests revealed better memory

performance for expected events following unexpected ones, compared to those

following expected events ($U_{prev}E_{curr}$ > $E_{prev}E_{curr}$; z = 2.55, p = 0.011). For set events

following unexpected ones, better memory was also found for expected compared to

unexpected events ($U_{prev}E_{curr}$ > $U_{prev}U_{curr}$; z = 2.68 p = 0.007). Next, we examined CR2 as

a function of the previously seen targets and F1 events, and their expectation status. For

F2 following targets, a main effect of the target's expectation status was observed (β =

0.473, $X^2(1)$ = 4.4, p = 0.036), with more CR2 following unexpected targets. All other

effects were not significant (all p's > 0.169). Correct responses to F2 events were not

affected by preceding F1 events (all p's > 0.263).

<u>fMRI results</u>

Expectation sequence interactions engage hippocampal, midbrain, and occipital

regions to support subsequent mnemonic processing.

We first examined the neural correlates of the behavioural contextual expectation

interaction reported above. For current expected events that followed unexpected

events, compared to those following an expected event ($U_{prev}E_{curr}$ > $E_{prev}E_{curr}$; see Figure

3B), we found increased activation in the right hippocampus (x = 36, y = -33, z = -12, k =

12, SVC p_{FWE} = 0.04), SN/VTA (x = 9, y = -24, z = -12, k = 11, SVC p_{FWE} = 0.039), and left

inferior occipital gyrus (BA 18; x = -21, y = -81, z = -18, non-parametric $p_{cluster}$ = 0.018).

For current unexpected events following previous expected ones, compared to those

which followed an unexpected event ($E_{prev}U_{curr}$ > $U_{prev}U_{curr}$), reflecting poorer

performance, we also found increased activation in the right hippocampus (x = 24, y = -

33, z = -6, k = 10, SVC p_{FWE} = .045) and left parahippocampus (x = -33, y = -45, z = -6,

non-parametric $p_{cluster}$ = 0.049). Critically, in both contrasts the current set events had

the same expectation status and differed only on the expectation status of the previous

event.

Figure 3 | Behavioural and neural expectation interactions for targets and F1 foils. A) Behavioural results. Replicating the results from Experiment 1, a current by previous expectation status interaction was observed, with $U_{prev}E_{curr}$ showing a boost in memory performance. **B) UprevEcurr > EprevEcurr contrast.** Increased activation in the right hippocampus, SN/VTA and left inferior occipital cortex. **C) Unexpected > Expected interactions.** Increased activation in right occipital cortex (BA 18) was observed for $U_{prev}U_{curr} > E_{prev}E_{curr}$, despite poor memory performance for $U_{prev}U_{curr}$ events. **D) Expected > Unexpected interactions.** Increased activation in right retrosplenial cortex/precuneus for $U_{prev}E_{curr} > U_{prev}U_{curr}$.

Comparing current expected vs. unexpected events, following previously unexpected events ($U_{prev}E_{curr} > U_{prev}U_{curr}$; Figure 3d) revealed activation in the right retrosplenial cortex/precuneus (x = 24, y = -45, z = 12, non-parametric $p_{cluster}$ = 0.0213). The complementary contrast, following expected events, $E_{prev}E_{curr} > E_{prev}U_{curr}$ did not reveal significant effects. For the $U_{prev}U_{curr} > E_{prev}E_{curr}$ contrast in which unexpected events elicited more activations than expected ones, despite showing reduced memory performance (Figure 3C), we found increased activation in right occipital cortex (BA 18, x = 18, y = -93, z = 12 , non-parametric $p_{cluster}$ = 0.0318). The complementary contrast $U_{prev}U_{curr} > E_{prev}U_{curr}$ did not reveal significant effects. Comparing the first (previous) event between conditions (first expected vs. first unexpected) did not reveal any significant effects.

Expectation status differentially engages encoding and retrieval-related regions.

To explore whether expected and unexpected events, across event types, responses, and

temporal positions elicited differential activations in a bottom-up (ventral visual

stream) or reinstatement (retrieval network) manner, we also compared the two

conditions (see Figure 4A). We found increased activity for unexpected > expected

events in right occipital cortex (BA 19, x = 39, y = -75 z = 12 and BA 18, x = 39, y = -75, z

= 12, non-parametric $p_{cluster}$ = 0.015) and right fusiform gyrus (x = 27, y = -48, z = -18,

non-parametric $p_{cluster}$ = 0.0173). For expected > unexpected, we observed increased

activation in the right inferior parietal lobe (angular gyrus; BA 39 x = 48, y = -48, z = 33,

non-parametric $p_{cluster}$ = 0.0206) and bilateral primary motor cortex (right: x = 60, y =

03, z = 18, non-parametric $p_{cluster}$ FWE = 0.045; left: x = -57, y = -6, z = 24, non-

parametric $p_{cluster}$ = 0.0339).

476
Figure 4 | Overall fMRI expectation effects. A) Main effect of expectation. Unexpected events,
compared to expected ones, engaged more activation in right middle occipital cortex and fusiform.
Conversely, excepted events, compared to unexpected ones, engaged activation in right angular and
supramarginal gyri. **B) Expectation by presentation order interaction.** Unexpected events presented
second in the set engaged regions along the ventral visual stream. No effects were observed for first or
third set events.

Occipital activation supports the interaction between expectation and memory

performance for similar events.

To unpack the overall unexpected > expected effect, we tested how contextual

expectation interacted with successful recognition decisions (hits and CR), across

presentation order. Whilst no differential neural responses were found for expected and

unexpected hits or correct rejections of F2 events, we observed increased activation in

the right inferior occipital gyrus (BA 19, x = 24, y = -81, z = -6, non-parametric $p_{cluster}$ =

0.0345) for unexpected CR1 > expected CR1.

Increased perceptual load interacts with expectation status to engage ventral visual

stream regions.

Finally, we examined interactions between expectation status and presentation order

(across set events; see Figure 4B). We observed again increased activity in bilateral

occipital cortex (BA 19, x = -39, y = -78, z = 18, non-parametric $p_{cluster}$ = 0.008, and BA

18, x = 18, y =-57, z = 21, non-parametric $p_{cluster}$ = 0.009; x = 15, y = -87, z = -3, non-

parametric $p_{cluster}$ = 0.0129) for unexpected > expected events presented second in the

set (no unexpected > expected effects were found for first or third set events).

499
Figure 5 | Illustration of the brain networks involved in processing unexpected and expected
events. Left and middle: Expectation-driven, goal-irrelevant encoding. Expectation violation engages
bottom-up processing along the ventral visual stream (inferior occipital in pink, fusiform in yellow),
regardless of memory performance. The subsequent mnemonic consequences of this shift towards
encoding involve the hippocampus (red) and midbrain (orange) dopaminergic regions, underlying
subsequent beneficial memory performance. **Right**: **Task-driven retrieval.** In the absence of expectation
violation (expected events), engagement of retrieval-driven network regions to support reinstatement
and memory performance, in accordance with goal to retrieve.
508

<u>Discussion</u>

The experience of surprise, or expectation violation, has a beneficial effect on learning,

but whether surprise also triggers an encoding response even when the dominant goal

is to retrieve, has remained unclear. In two experiments, we used a contextual

expectation manipulation to better understand the dynamic nature of the adaptive

memory mechanism triggered by expectation violation during retrieval, and its

potential mnemonic consequences on hippocampal-dependent memory. We found that

encountering unexpected events at retrieval, elicited increased involvement of regions

along the ventral visual stream, even when memory performance was poor ($U_{prev}U_{curr}$).

Interestingly, we also found a later beneficial effect of contextual surprise, such that the

presentation of an unexpected event did not support its own recognition, but it did

boost the correct recognition of the following, expected, and similar set events
($U_{prev}E_{curr}$). This behavioural effect was associated with increased activity in the
hippocampus, midbrain dopaminergic regions (SN/VTA), and occipital cortex. Expected
events, conversely, were associated with activity in retrieval-driven network regions.
Given our replicated finding of the modulation of memory by previous unexpected
events, the increased involvement of ventral visual stream regions, and previous
research on expectation-modulated encoding, we postulate that engaging with
unexpected information at retrieval engages an implicit bottom-up encoding
mechanism (Figure 5). The consequences of this engagement become clear in the
subsequent recognition trial, with a divergence in performance, and differential pattern
of fMRI activation depending on whether the subsequent event was expected or
unexpected.

Expectation violation is associated with improved memory performance, attributed to
adaptive memory formation (Lisman and Grace, 2005; Kumaran and Maguire, 2007;
Shohamy and Wagner, 2008), and impaired encoding of predictive information
(Sherman and Turk-Browne, 2020). Our results support this view, but critically, extend
it to account for retrieval effects. In line with the idea that increased weight is given to
bottom-up inputs upon encountering a prediction error (Stoppel et al., 2009; Kafkas and
Montaldi, 2018a), we found increased involvement of visual processing regions in
occipital cortex and fusiform gyrus for unexpected events. These regions have been
found to increase their activity with stronger levels of unexpected novelty (Kafkas and
Montaldi, 2014), reflecting the increased perceptual processing of unexpected events.
Although memory formation relies on bottom-up processing, evidence of an encoding
mechanism requires that the mnemonic consequences of increased dependence on
sensory inputs are demonstrated. Without subsequent mnemonic consequences, it
could be argued that encountering an unexpected event only modulates online attention
(Poort et al., 2022). Indeed, we observed an interaction whereby current memory
performance was modulated by the previous unexpected occurrence of a similar event;
when the previous event was expected, current expectation did not modulate
performance ($E_{prev}E_{curr} \approx E_{prev}U_{curr}$), whereas when the previous event was unexpected,
we found a divergence in performance ($U_{prev}E_{curr} > U_{prev}U_{curr}$).

Taken together, these findings suggest that a surprise-driven increased weight on
bottom-up inputs is goal-independent, but its mnemonic consequences appear to
depend on the task at hand. During learning or exploration, further encoding supports
later memory for the unexpected event (Li et al., 2003; Garrido et al., 2015; Long et al.,
2016; Greve et al., 2017; Frank and Kafkas, 2021). When retrieval is the goal (as in the
current paradigm), the implicit shift towards encoding, despite increased perceptual
processing, results in numerically worse memory performance for the current to-be-
retrieved information (Duncan et al., 2012; Kim et al., 2014). This is at odds with the
notion that expectation violation always supports improved memory. Further support
for the role played by perceptual load in engaging an encoding state, can be seen in the
occipital and fusiform effects for those unexpected events presented second within the
set sequence, compared to their expected counterparts. Recognition decisions for these
events must overcome interference from the first set event, likely requiring increased
perceptual processing to better compare the current sensory input with the stored
representations.

Upon encountering the first unexpected event (U_{prev}), a shift towards encoding, and
away from retrieval, can explain why we do not observe a retrieval boost for these
events. It is less obvious why this shift towards encoding produces better memory
performance only for subsequent expected events. One possibility is that the initial
expectation-violation driven shift towards encoding results in a sharper representation
of the initial unexpected event (Gilboa and Moscovitch, 2021), optimising pattern
completion of the second similar event (even when expected), as the delta similarity
between the encoding and retrieval representations now stands out. Support for this
account can be found in our fMRI findings; whilst occipital involvement was observed
for both $U_{prev}E_{curr}$ and $U_{prev}U_{curr}$ events (i.e. independent of mnemonic consequence),
only $U_{prev}E_{curr}$ events were associated with hippocampal and SN/VTA activation. This
finding, together with the memory boost for $U_{prev}E_{curr}$ events, highlights the temporal
contingency driven by U_{prev}, as indexed by co-activation of SN/VTA and hippocampus
(Kafkas and Montaldi, 2015). This co-activation is likely indicative of the expectation-
driven (re)encoding of U_{prev} which then boosts memory for E_{curr}.

Critically, interactions between current and previous events' expectation were observed
only for targets and F1 (i.e. the foil with most similarity to the encoded target).
Moreover, these effects were unchanged by interfering events from the same set (F2,
F3) or events from different sets presented during the task. That the expectation
interactions are selective to high perceptual similarity, and are robust with respect to
interference from other stimuli, suggests that a high perceptual and memorial load is
required to trigger this encoding mechanism, consistent with, and extending, previous
findings (Bein et al., 2020; Frank et al ., 2020). In such situations, the ability to process
and compare the fine details of current inputs and recently stored representations
underpins correct recognition decisions (Yassa and Stark, 2011). Therefore, the
triggering of enhanced perceptual processing by expectation violation serves an
adaptive purpose (Stoppel et al., 2009; Hawco and Lepage, 2014). For less similar
events, which are more readily recognised as new, a sharper representation, elicited by
expectation violation, has little effect (Frank et al., 2020).

It is also important to consider how the shift towards encoding is manifested in the first
event presentation; only first targets demonstrated a benefit for expected compared to
unexpected previous events (and when examining only first set events). Whilst the
increased hit rate for first expected targets is in line with our interpretation of the data,
we did not observe a significant effect for F1 events. We suggest that this could be due
to the intrinsic small differences in perceptual overlap between encountering a target
and a very similar foil. It is possible that the increased difficulty associated with a first
F1 event, driven by high but not full overlap with the encoded object, outweighs any
potential effect of the implicit engagement of encoding. For targets, on the other hand
there is a full perceptual overlap with the encoded object, that may facilitate recognition
of expected targets, whereas expectation violation would deter it. Support for this
interpretation can be found in the subsequent contrasts of the interaction in
Experiment 1, where targets dominate the boost in $U_{prev}E_{curr}$, whereas F1 seem to drive
the poor memory for $U_{prev}U_{curr}$. Furthermore, as discussed above, the lack of effects for
lower-similarity foils suggests that perceptual load plays an important role in how
expectation modulates memory processes. Given the robust behavioural interaction
between subsequent events, and the complementary fMRI findings, we believe that an
expectation-modulated shift towards encoding account best explains our data.

As the expectation manipulation took place at retrieval, it remains unclear whether
encountering expected events resulted in task-relevant retrieval, or the active
engagement of a retrieval state, irrespective of task demand. Although the engagement
of temporo-parietal regions of a retrieval-driven network (Hayama et al., 2012) is
indicative of reinstatement, this does not differentiate between the two alternatives.
Future studies could orthogonalise expectation and memorial state, therefore allowing
a factorial design of goal (encoding/retrieval) and expectation status. Examinations of
shifts towards a retrieval state, perhaps coupled with designs optimised for functional
and effective connectivity, will contribute to on-going efforts to explain how the
hippocampus shifts between memory states (Colgin, 2016; Kafkas and Montaldi, 2018a;
Bein et al., 2020). Whilst unexpected events during which you experience a high level of
surprise are particularly memorable, it remains to be determined to what extent explicit
awareness of surprise modulates this mechanism, and how memory demands might
direct activity in the visual system.

In conclusion, we report novel evidence for the ubiquity of the adaptive encoding
mechanism, here triggered at retrieval by expectation violation, resulting in differential
effects on recognition performance. We propose that the increased demand on bottom-
up occipital inputs, together with hippocampal-midbrain activations, are markers of an
encoding state triggered by expectation violation, even in the absence of explicit reward
or instruction. The complex temporal dynamics of the effects of this mechanism on
memory demonstrate that the expectation-driven shift towards an encoding state
engages increased perceptual processing, exerting a beneficial effect on correct
recognition of subsequent similar events. These findings have important implications
for our understanding of how our processing of sequential events, expected or
unexpected, is modulated by the temporal dynamics of the event sequence.

References

Aberg KC, Kramer EE, Schwartz S (2020) Interplay between midbrain and dorsal
anterior cingulate regions arbitrates lingering reward effects on memory encoding.
Nat Commun 11:1829 Available at: http://www.nature.com/articles/s41467-020-
15542-z.

Aly M, Turk-Browne NB (2017) How Hippocampal Memory Shapes, and Is Shaped by,
Attention. In: The Hippocampus from Cells to Systems, pp 369–403. Cham:
Springer International Publishing. Available at:
http://link.springer.com/10.1007/978-3-319-50406-3_12.

Ashburner J (2007) A fast diffeomorphic image registration algorithm. Neuroimage
38:95–113 Available at:
https://linkinghub.elsevier.com/retrieve/pii/S1053811907005848.

Axmacher N, Cohen MX, Fell J, Haupt S, Dümpelmann M, Elger CE, Schlaepfer TE, Lenartz
D, Sturm V, Ranganath C (2010) Intracranial EEG Correlates of Expectancy and
Memory Formation in the Human Hippocampus and Nucleus Accumbens. Neuron
65:541–549.

Bates D, Mächler M, Bolker B, Walker S (2015) Fitting Linear Mixed-Effects Models
Using lme4. J Stat Softw 67 Available at: http://arxiv.org/abs/1406.5823.

Bein O, Duncan K, Davachi L (2020) Mnemonic prediction errors bias hippocampal
states. Nat Commun 11:3451 Available at:
http://www.nature.com/articles/s41467-020-17287-1.

Buzsáki G (2002) Theta Oscillations in the Hippocampus. Neuron 33:325–340 Available
at: http://linkinghub.elsevier.com/retrieve/pii/S089662730200586X.

Colgin LL (2016) Rhythms of the hippocampal network. Nat Rev Neurosci 17:239–249
Available at: http://www.nature.com/articles/nrn.2016.21.

Desikan RS, Ségonne F, Fischl B, Quinn BT, Dickerson BC, Blacker D, Buckner RL, Dale
AM, Maguire RP, Hyman BT, Albert MS, Killiany RJ (2006) An automated labeling
system for subdividing the human cerebral cortex on MRI scans into gyral based
regions of interest. Neuroimage 31:968–980 Available at:
https://linkinghub.elsevier.com/retrieve/pii/S1053811906000437.

Dimsdale-Zucker HR, Ranganath C (2019) Representational Similarity Analyses: A
Practical Guide for Functional MRI Applications. Handb Behav Neurosci 28:509–
525.

Duncan K, Sadanand A, Davachi L (2012) Memory's Penumbra: Episodic Memory

Decisions Induce Lingering Mnemonic Biases. Science (80-) 337:485–487.

Dunsmoor JE, Murty VP, Davachi L, Phelps EA (2015) Emotional learning selectively and

retroactively strengthens memories for related events. Nature 520:345–348

Available at: http://www.nature.com/articles/nature14106.

Elston TW, Bilkey DK (2017) Anterior Cingulate Cortex Modulation of the Ventral

Tegmental Area in an Effort Task. Cell Rep 19:2220–2230 Available at:

https://linkinghub.elsevier.com/retrieve/pii/S2211124717307192.

Fox J (2003) Effect Displays in R for Generalised Linear Models. J Stat Softw 8 Available

at: http://www.jstatsoft.org/v08/i15/.

Fox J, Weisberg S (2018) An R Companion to Applied Regression. Sage.

Frank D, Gray O, Montaldi D (2019) SOLID-Similar object and lure image database.

Behav Res Methods Available at: http://link.springer.com/10.3758/s13428-019-

01211-7.

Frank D, Kafkas A (2021) Expectation-driven novelty effects in episodic memory.

Neurobiol Learn Mem 183:107466 Available at:

https://linkinghub.elsevier.com/retrieve/pii/S1074742721000885.

Frank D, Montemurro MA, Montaldi D (2020) Pattern Separation Underpins

Expectation-Modulated Memory. J Neurosci 40:3455–3464 Available at:

http://www.jneurosci.org/lookup/doi/10.1523/JNEUROSCI.2047-19.2020.

Garrido MI, Barnes GR, Kumaran D, Maguire EA, Dolan RJ (2015) NeuroImage

Ventromedial prefrontal cortex drives hippocampal theta oscillations induced by

mismatch computations. Neuroimage 120:362–370 Available at:

http://dx.doi.org/10.1016/j.neuroimage.2015.07.016.

Gilboa A, Moscovitch M (2021) No consolidation without representation:

Correspondence between neural and psychological representations in recent and

remote memory. Neuron 109:2239–2255 Available at:

https://linkinghub.elsevier.com/retrieve/pii/S0896627321002919.

Greve A, Cooper E, Kaula A, Anderson MC, Henson RN (2017) Does prediction error

drive one-shot declarative learning? J Mem Lang 94:149–165 Available at:

http://dx.doi.org/10.1016/j.jml.2016.11.001.

Hasselmo ME, Bodelon C, Wyble BP (2002) A Proposed Function for Hippocampal Theta

Rhythm: Separate Phases of Encoding and Retrieval Enhance Reversal of Prior

Learning. Neural Comput 14:793–817.

Hawco C, Lepage M (2014) Overlapping patterns of neural activity for different forms of

novelty in fMRI. Front Hum Neurosci 8 Available at:

http://journal.frontiersin.org/article/10.3389/fnhum.2014.00699/abstract.

Hayama HR, Vilberg KL, Rugg MD (2012) Overlap between the Neural Correlates of

Cued Recall and Source Memory: Evidence for a Generic Recollection Network? J

Cogn Neurosci 24:1127–1137 Available at:

http://www.mitpressjournals.org/doi/10.1162/jocn_a_00202.

Kafkas A (2021) Encoding-linked pupil response is modulated by expected and

unexpected novelty: Implications for memory formation and neurotransmission.

Neurobiol Learn Mem.

Kafkas A, Montaldi D (2014) Two separate, but interacting, neural systems for

familiarity and novelty detection: A dual-route mechanism. Hippocampus 24:516–

527 Available at: http://doi.wiley.com/10.1002/hipo.22241.

Kafkas A, Montaldi D (2015) Striatal and midbrain connectivity with the hippocampus

selectively boosts memory for contextual novelty. Hippocampus 25:1262–1273

Available at: http://www.ncbi.nlm.nih.gov/pubmed/25708843.

Kafkas A, Montaldi D (2018a) How do memory systems detect and respond to novelty?

Neurosci Lett 680:60–68 Available at:

http://dx.doi.org/10.1016/j.neulet.2018.01.053.

Kafkas A, Montaldi D (2018b) Expectation affects learning and modulates memory

experience at retrieval. Cognition 180:123–134 Available at:

https://linkinghub.elsevier.com/retrieve/pii/S0010027718301938.

Kim G, Lewis-Peacock J a, Norman KA, Turk-Browne NB (2014) Pruning of memories by

context-based prediction error. Proc Natl Acad Sci 111:8997–9002 Available at:

http://www.pnas.org/cgi/doi/10.1073/pnas.1319438111.

Kumaran D, Maguire EA (2007) Which computational mechanisms operate in the

hippocampus during novelty detection? Hippocampus 17:735–748 Available at:

http://onlinelibrary.wiley.com/doi/10.1002/hipo.20207/abstract%5Cnpapers3:/

/publication/doi/10.1002/hipo.20207.

Li S, Cullen WK, Anwyl R, Rowan MJ (2003) Dopamine-dependent facilitation of LTP

induction in hippocampal CA1 by exposure to spatial novelty. Nat Neurosci 6:526–

531.

Lisman JE, Grace A a. (2005) The Hippocampal-VTA Loop: Controlling the Entry of
Information into Long-Term Memory. Neuron 46:703–713 Available at:
http://linkinghub.elsevier.com/retrieve/pii/S0896627305003971.

Long NM, Lee H, Kuhl B a. (2016) Hippocampal Mismatch Signals Are Modulated by the
Strength of Neural Predictions and Their Similarity to Outcomes. J Neurosci
36:12677–12687 Available at:
http://www.jneurosci.org/lookup/doi/10.1523/JNEUROSCI.1850-16.2016.

Misaki M, Kim Y, Bandettini PA, Kriegeskorte N (2010) Comparison of multivariate
classifiers and response normalizations for pattern-information fMRI. Neuroimage
53:103–118 Available at:
https://linkinghub.elsevier.com/retrieve/pii/S1053811910007834.

Murty VP, Shermohammed M, Smith D V., Carter RM, Huettel SA, Adcock RA (2014)
Resting state networks distinguish human ventral tegmental area from substantia
nigra. Neuroimage 100:580–589 Available at:
https://linkinghub.elsevier.com/retrieve/pii/S1053811914005242.

Oosterhof NN, Connolly AC, Haxby J V. (2016) CoSMoMVPA: Multi-Modal Multivariate
Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. Front Neuroinform
10:1–27 Available at:
http://journal.frontiersin.org/Article/10.3389/fninf.2016.00027/abstract.

Oyarzún JP, Packard PA, de Diego-Balaguer R, Fuentemilla L (2016) Motivated encoding
selectively promotes memory for future inconsequential semantically-related
events. Neurobiol Learn Mem 133:1–6.

Peirce JW (2007) PsychoPy-Psychophysics software in Python. J Neurosci Methods
162:8–13.

R Development Core Team (2008) R: A language and environment for statistical
computing. Available at: http://www.r-project.org.

Richter FR, Chanales AJH, Kuhl BA (2016) Predicting the integration of overlapping
memories by decoding mnemonic processing states during learning. Neuroimage
124:323–335 Available at:
http://linkinghub.elsevier.com/retrieve/pii/S1053811915007703.

Searle SR, Speed FM, Milliken GA (1980) Population Marginal Means in the Linear
Model: An Alternative to Least Squares Means. Am Stat 34:216–221 Available at:
http://www.tandfonline.com/doi/abs/10.1080/00031305.1980.10483031.

Sherman BE, Turk-Browne NB (2020) Statistical prediction of the future impairs
episodic encoding of the present. Proc Natl Acad Sci 117:22760–22770 Available
at: http://www.pnas.org/lookup/doi/10.1073/pnas.2013291117.
Shohamy D, Adcock RA (2010) Dopamine and adaptive memory. Trends Cogn Sci
14:464–472.
Shohamy D, Wagner AD (2008) Integrating Memories in the Human Brain:
Hippocampal-Midbrain Encoding of Overlapping Events. Neuron 60:378–389
Available at: http://dx.doi.org/10.1016/j.neuron.2008.09.023.
Stoppel CM, Boehler CN, Strumpf H, Heinze H-J, Hopf JM, Düzel E, Schoenfeld MA (2009)
Neural correlates of exemplar novelty processing under different spatial attention
conditions. Hum Brain Mapp 30:3759–3771 Available at:
http://doi.wiley.com/10.1002/hbm.20804.
West BT, Welch KB, Galecki AT (2014) Linear Mixed Models. Chapman and Hall/CRC.
Available at: https://www.taylorfrancis.com/books/9781466561021.
Wickham H (2009) ggplot2. New York, NY: Springer New York. Available at:
http://link.springer.com/10.1007/978-0-387-98141-3.
Yassa MA, Stark CEL (2011) Pattern separation in the hippocampus. Trends Neurosci
34:515–525 Available at:
http://linkinghub.elsevier.com/retrieve/pii/S0166223611001020.