The Wood Image Analysis and Dataset (WIAD): open-access

visual analysis tools to advance the ecological data revolution

Running headline

Wood Image Analysis and Dataset

Author details

Tim Rademacher[1,2,3,*], Bijan Seyednasrollah[2,3], David J. Basler[1,4], Jian Cheng[5], Tessa

Mandra[1], Elise Miller[1,6], Zuid Lin[7], David A. Orwig[1], Neil Pederson[1], Hanspeter Pfister[7], Donglai

Wei[7], Li Yao[5], Andrew D. Richardson[2,3]

[1] Harvard Forest, Harvard University, Petersham, Massachusetts, USA.

[2] School of Informatics, Computing and Cyber Systems, Northern Arizona University, Flagstaff, Arizona, USA.

[3] Center for Ecosystem Science and Society, Northern Arizona University, Flagstaff, Arizona, USA.

[4] Department of Environmental Sciences, University of Basel, Basel, Switzerland.

[5] Southeast University, Nanjing, Jiangsu, China.

[6] University of Minnesota Duluth, Duluth, Minnesota, USA.

[7] School of Engineering and Applied Sciences, Harvard University, Cambridge, Massachusetts, USA.

* Corresponding author, email: trademacher@fas.harvard.edu, 324 North Main Street, Petersham, 01366,

Massachusetts, USA.

Keywords: Automation, dendrochronology, dendroecology, data revolution, GUI, repository,

tree rings, visual analysis, wood.

Abstract

1.   Ecological data is collected and shared at an increasingly rapid pace, but it is often

shared in inconsistent and untraceable processed forms. Images of wood contain a wealth of

information such as colours and textures but are most commonly reduced to ring-width

measurements before they can be shared in various common file formats. Archiving digital

images of wood samples in libraries, that have been developed for ecological analysis and are

publicly available, remains the exception.

2.   We developed the Wood Image Analysis and Dataset (WIAD) an open-source

application including a web-interface to integrate basic visual analysis of wood samples, such as

increment cores, thin sections or x-ray films, basic data processing, and archiving of the images

and derived data to facilitate transparency and reproducibility in studies using visual

characteristics of wood.

3.   WIAD provides user-friendly tools to manipulate images of wood samples, mark and

measure wood characteristics such as growth increments, density fluctuations, early- and

latewood widths, and fire scars, and to visualise, process, and archive images, metadata, and

the derived data.

4.   WIAD constitutes a step towards the reproducible automation of tree-ring analysis, while

establishing an open-source foundation to create improved community developed repositories

which would enable novel ecological studies harnessing the wealth of existing visual data.

1. Introduction

Ecological data is collected at an increasingly rapid pace, but to optimise its use data needs

to be shared in its raw format with accompanying ancillary and metadata (Michener, 2015).

While the community of science using tree rings has been leading data sharing efforts (e.g.,

International Tree Ring Database and DendroEcological Network), there is still an urgent need

for improved tree-ring archives (Babst et al., 2017; Zhao et al., 2018). Recently, digital archives

have been developed to accommodate the need to share raw images of wood samples and

meet the challenge of image size (e.g., DendroElevator). However, there are still no open-

source analysis tools that easily interface with such archives. Wood samples, such as increment

cores, cross sections and microcores are mostly still prepared according to standard

procedures, extracting visual properties such as ring-width series (Fritts, 1976), blue intensity as

a proxy for wood density (Björklund et al., 2014), or cellular dimensions (Björklund et al., 2017;

von Arx & Carrer, 2014). The rich information embedded in the colours, textures and structures

of each wood sample, which are used to identify these visual features in the first place, are

generally collapsed to a simple one-dimensional geometric measurement (i.e., ring width)

before they are shared in one of many common file formats (Brewer et al., 2011).

While multiple specialised tools for digital analysis of wood images exist (e.g., WinDendro,

ROXAS, CooRecorder) and have been adopted widely, none of these tools is completely open-

source and free, slowing down further community-driven development. While ROXAS (von Arx

& Carrer, 2014) provides a very powerful interface it depends on expensive libraries and is

programmed in a discontinued programming language. CooRecorder provides a cheaper, albeit

not free, and well-supported alternative to measure basic wood features, but does not provide

its code base, prohibiting further development by the community. The only freeware, that we are

aware of (e.g., ImageJ plug-ins), have not been widely adopted, presumably due to issues

related to functionality, ease of installation and use, and/or support. As a result, a large part of

the community either uses proprietary commercial software (e.g., WinDendro, CooRecorder)

and many scientists still prefer manual measurements using "linear tables", although the

accuracy of digital analysis was already comparable to manual measurements about a decade

ago for some species (Maxwell et al., 2011). Digital technology has advanced rapidly since and

offers generally recognised benefits of simplified evaluation, corrections and amendment of

previous measurements. Moreover, R packages such as *dlpR* (Bunn, 2008; Bunn et al., 2021),

which allows tree-ring analyses from standard file formats, have enjoyed enormous success,

arguably in part because the community is familiar with the R programming environment.

To move towards unlocking the wealth of underlying visual data from images of wood, we

created an open source pipeline, the Wood Image Analysis and Dataset (WIAD), that integrates

digital analysis and data archiving, while also laying the foundation for open-access sharing of

images and derived data. WIAD is an easily-installed, simple R shiny application, whose

graphical user interface can currently be accessed at https://wiad.science or run locally (see

Code and Data availability for installation instructions). WIAD provides an interactive user-

friendly interface for simple pre- and post-processing of wood images and metadata entry to

facilitate a standardized workflow for labeling, measuring and detrending of radial growth. Both

the web-interface and locally running copies allow making, evaluating and editing

measurements and associate a minimal set of metadata (Table 1). When running WIAD locally,

outputs are saved on the local machine enabling the upload and sharing of local collections at

any point thereafter (e.g., upon acceptance for publication). Thus, the user can embargo the

data by running a copy locally and only uploading the data upon publication as per terms of use.

When using the web interface, data is archived straight away to the WIAD repository.

In the following sections, we explain WIAD's current functionality, provide an illustrative

example of how it can be used, describe anticipated developments and the future potential of

such a community-developed platform. Community-developed platforms to archive, share, and

analyse images in a transparent and reproducible way is applicable for a vast array of visual

data in ecology, such as leaf or root scans, and have proven very successful for digital images

of canopies (Hufkens et al., 2018; Richardson et al., 2018). WIAD aims to provide a blueprint of

an integrated repository and analysis framework to advance the ecological data revolution using

agile software development and state-of-the-art practices in scientific software development

(Ahmed et al., 2014; List et al., 2017; Wilson et al., 2014, 2017).

Table 1: The following metadata is associated and archived with each image and derived data on the Wood Image Analysis and Database (WIAD). Metadata can be uploaded using a metadata form or filled in manually. Data types can be character strings (C), dates (D), integers (I), logical variables (L), or doubles (N). The units column displays the assumed units for each metadata field. The optional column specifies whether the metadata is optional (✔), required (*) or provided by the software (✗).

Variable name	Type	Units	Optional	Description
Version	C	NA	✗	Version of WIAD used to produce this file.
Image file name	C	NA	✗	Name of the image file
Name	C	NA	✔	User's full name
Email address	C	NA	✔	Email address of user
Species	C	Unitless	✔	Genus or, if available, species name after
Sample date	D	yyyy-mm-dd	✔	Date of sample collection
Growing season	C	NA	*	Factor determining whether the growing season had not started (default), only started, or already finished
Schulman Shift	L	NA	*	Determine whether a shift of the associated year (mainly necessary in Southern Hemisphere) should be performed according to Schulman (1956). The default is no shift.
Scan resolution	I	Dots per inch	✔	True (not interpolated) resolution of the scan
Site location	C	NA	✔	Detailed description of site location including area, town, and country
Latitude	N	decimal °	✔	Bounding latitudes in decimal notation for the sample location
Longitude	N	decimal °	✔	Bounding longitudes in decimal notation for the sample location
Site ID	C	Unitless	✔	Unique identifier used by contributor for the specific site
Plot ID	C	Unitless	✔	Unique identifier used by contributor for the specific plot
Sample ID	C	Unitless	✔	Unique identifier used by contributor for the sample
Sample height	N	m	✔	Height aboveground at which the sample was taken
Sample azimuth	I	°	✔	Azimuth angle at which the sample was taken
Sample note	C	NA	✔	Any additional notes pertaining to the specific sample
Collection	C	NA	✔	Name of the collection to which this sample belongs
Contributor	C	NA	✔	Full name of the contributor who led the collection effort and owns the collection
Pith in image	L	NA	*	Determine whether the image and data series contains the pith. By default it is assumed that there is no pith in the image.
Bark first	L	NA	*	Determine whether the measurement series starts at the bark (default) or at the pith

2. WIAD functionality

After the initial installation as an R package (available on CRAN and github, see Code and

Data availability for installation instructions) including its dependencies (most prominent R and

the shiny package), WIAD can be run locally by one simple command. Alternatively, WIAD can

be accessed through a web-interface at https://wiad.science. The application currently has four

tabs: Toolbox, Plot Board, About and Fair use policy.

2.1 Toolbox

The toolbox provides basic interactive image manipulation tools (Fig. 1), which require the

upload of an image in TIFF, PNG or JPEG format. Once uploaded, the image can be rotated,

processed with colour transformations (i.e., display true colour, total brightness, or blue channel

only), and enlarged using a zoom bar (digital magnification up to a maximum image width of 20

000 pixels). The user can enter - either manually or via the upload of an XLSX, JSON or CSV

file - and needs to confirm the metadata, which is then associated with the image and all derived

data. To convert the distances in the image from pixels to micrometers, the user needs to

provide the true scan resolution (in dots per inch), otherwise distances will be provided in pixels.

Once the metadata is confirmed, the toolbox allows setting, deleting, and inserting five types

of labels through a simple graphical user interface. A simple click on the image sets a normal

label marking the end of a growth increment (overlaid in yellow), a double click sets a

miscellaneous label (overlaid in turquoise), which marks miscellaneous features that can be

selected from a pop-up dialog. Radial growth (i.e., one-dimensional distance between labels in

micrometers) and association of a particular year with each annual growth increment (including

a one-year shift when desired in the southern hemisphere sensu Schulman (1956)) are

performed automatically and displayed in a data table below the image. The user can delete a

specific label, the last label, or all labels with the "Bin" of the specific data table row, the "Undo",

or the "Erase" button below the image, respectively. The user can switch a normal label to a link

label (overlaid in blue) by pressing the "Link" button below the image, once the label was set.

Links can bridge gaps in the sample, when two consecutive linker labels are used, or relocate

the start point for a measurement (as visible in Fig. 1). Another action button converts a normal

label to mark the oldest completely visible ring or pith (overlaid in red). Checkboxes below the

image represent a choice whether the labelling started at the bark side of a core, whether the

image contains the pith, and whether years, labels and/or label numbers should be displayed.

Additional labels, including missing rings, can be inserted before any existing label by clicking

on the "Add" button of the respective row of the data table. Users can also upload images,

metadata and labels to evaluate previously analysed images or add images that were analysed

offline to the online archive. Finally, users can download a CSV or JSON file, which contains

labels, derived measurements and metadata (the latter is not included in CSV format) to save

their progress or for further analysis offline.

To use the tool for teaching or demonstration, the "Demo" button switches demonstration

mode on/off. In demonstration mode, an example image is automatically loaded, but can be

replaced, and data or images are neither archived locally, nor in the online database.

Figure 1 - Screenshot of WIAD Toolbox with an example image of white pine and uploaded labels from a previous

measurement. The metadata automatically populates the fields in the left column, but needs to be confirmed with the

radio button below. Normal labels are overlaid onto the image in yellow, miscellaneous labels in turquoise and link

labels in blue.

2.2 Plot board

The WIAD plot board tab provides two interactive plots to quickly assess the derived growth

data and detrended ring-width indices. The upper plot displays the measured annual radial

growth increments over time, while the second graph shows ring-width indices based on

residuals from an expected growth curve (Cook & Peters, 2016). The user can select a

detrending curve from the *dplR* package (Bunn, 2008; Bunn et al., 2021) to obtain ring-width

indices via controls on the left and examine them in real-time. Finally, a JSON file including the

labels, derived measurements, detrended ring-width indices, detrending parameters, and

metadata can be downloaded.

Figure 2 - Screenshot of the WIAD Plot board showing the controls for detrending on the left and interactive plots of

the radial growth increments (blue line and markers; top graph) including a detrending curve (red curve; top graph)

and ring-width indices (mauve line and markers; bottom graph).

2.3 About and Fair use policy

The "About" tab provides basic information about WIAD, whereas the "Fair use policy" tab

outlines the conditions of use with regard to the tools and data. WIAD code base is publicly

available for noncommercial reuse under the Affero General Public License v3 license

(https://www.gnu.org/licenses/agpl-3.0). Accumulated images, derived data, and metadata will

be made publicly available every couple of years after thorough review. We request that the

WIAD core development team and data contributors are appropriately acknowledged in work

using WIAD by citing this paper and the appropriate software citation. Contributors' names and

email addresses are attached to each datum in the repository through the accompanying

metadata (if they were provided) and we expect data users to contact data contributors. Data

contributors will have a deeper understanding of the data and additional insight; thus we

consider them crucial collaborators for any data-user.

Despite higher resolution scans being generally desirable, as they capture more details,

which may lead to additional uses in the future, larger images also require more storage. Image

rendering is the computational bottleneck of WIAD, hence larger images also slow down

processing. Therefore, we recommend a scan resolution of 3200 dpi, which balances the

tradeoff between visual quality and file size for standard increment cores. To reduce storage

requirements and optimise processing speed images should always be cropped (using open-

source image manipulation programs like GNU Image Manipulation Program) to only the region

of interest prior to upload. For particularly large samples (e.g., cross-sections), hence files,

segmentation into multiple images can be considered for faster processing and reduced

storage. When pre-processing scans, care must be taken to avoid changing the image

resolution or features. Due to storage limitations, maximum image size of the web-interface is

currently limited to 30 MB (i.e., sufficient for a 3200 dpi scan of a 30 cm long and 6mm wide

sample). When running WIAD offline, the maximum image size can be adjusted via the

maxImageSize variable in the *server.R* file.

193 3. Example: Measuring ring width and density fluctuations in white pine

To provide an example data set we measured and uploaded images for ten mature white

pines (*Pinus strobus* L.) from Harvard Forest, USA. For this data set, we collected two

increment cores at breast height using a standard increment corer (5.15mm, Haglöf Company

Group, Långsele, Sweden). The cores were glued to wooden mounts and sanded with

progressively finer sandpaper (from 80 to 8000 grit) until visual features of the wood were

clearly visible by the naked eye. A subset of these images and derived data of 250 MB can be

downloaded with the getExampleData function. To download the entire example dataset (1.83

GB) the function's "dataset" parameter must be set to "full".

203 3.2 Imaging samples

Samples were scanned with an Epson Perfection V500 Photo Scanner (Long Beach,

California, USA) at 3200 dpi with an advanced reflective colour-calibration target (10x15cm

target printed on Kodak Professional Endura, LaserSoft Imaging, Kiel, Germany). The colour

calibration target allows for tracking and potential future correction of drift in colours over time

and between scanners. We recommend digitising samples on a flatbed scanner with a charge-

coupled devices (CCD) imaging array. The CCD imaging arrays have a larger depth of focus

compared to the increasingly popular complementary metal oxide semiconductor arrays,

although the latter may outperform CCD arrays in the future (Janesick & Putnam, 2003).

4. Anticipated developments and future potential

WIAD complements existing tools by providing a free and open-source alternative in a widely used programming language, which facilitates further community-driven development. While size limitation of the online versions (i.e., 30 MB) and the basic nature of the processing and analysis tools in the current implementation are clear limitations, we plan to extend the framework to provide a pipeline that allows users to process, measure, and analyse images as well as archive the raw, derived, and meta-data all in one place. Such a pipeline will improve transparency and reproducibility of studies based on wood images by enabling easy sharing of data and provenance tracing. We intend to regularly publish curated data sets from the WIAD archive every couple of years. This approach has proven a workable solution for the PhenoCam network (Richardson et al., 2018; Seyednasrollah et al., 2019), as it reduces the need for intensive and immediate quality control and provides cleaned and citable versions of data sets to the community. In the hope that other developers will join our efforts, we outline a few specific directions below.

4.1 Exploiting the potential of already existing collections by digitisation

Wood is arguably the most abundant biological tissue on earth (Bar-On et al., 2018) and records information about past climates (Mann et al., 2008), disturbances (Bergeron et al., 2002; Lorimer, 1984) and biotic interactions (Cook, 1987). Scientists of multiple disciplines (ecology, physiology, archeology, etc.) have collected millions of wood samples in the form of increment cores, micro-cores (Rossi et al., 2006), and stem cross-sections, which are archived in laboratories across the world. Publicly available digital images of collected samples would move these fields to a big data domain and provide the foundation for major advances in our understanding of the process of wood formation, its abiotic and biotic constraints, and resulting

anatomy. Improved archives will be instrumental for teaching the next generation of scientists,

reconstructing past environments and will improve forecasts of future carbon sequestration that

are based in ecological realities. Digitisation and data sharing have multiple proven benefits

such as accelerating science and improving trust in science (Michener, 2015; and references

therein). WIAD paves the way to digitise large collections of wood samples and contribute to

improved archives. Additionally, WIAD can be used as a teaching tool in demonstration mode,

especially if users share specific image libraries addressing teaching goals (e.g., containing

drought-induced intra-annual density fluctuations).

While WIAD provides the foundational tools, several aspects would profit from refinement

such as more comprehensive metadata, association with ancillary data, batch processing of

images and integration of data provenance. WIAD associates images with a minimal set of

metadata (Table 1) and we plan to integrate handling of more comprehensive metadata using

the Ecological Metadata Language (Fegraus et al., 2005; Jones et al., 2006). Similarly, WIAD

intends to comply with Darwin Core Standard (Wieczorek et al., 2012) to ensure compatibility

with other data collections of biological diversity. Finally, future versions should allow the upload

of ancillary data such as data of non-visual chemical or physical properties (isotopic

composition, nonstructural carbon concentrations, lignin content, etc.).

4.2 Streamline data processing through automation and enable community science

To further automate the processing of digital analysis of wood samples, low hanging fruit will

be the automatic detection of visual properties. Initial algorithms correctly identified almost

100% of rings in four conifer species, roughly 85% in six diffuse-porous species, but only 40-

50% in two ring-porous species (Fabijańska et al., 2017; Subah, Derminder, & Sanjeev, 2017),

despite being based on comparatively small and homogenous training data. Recently,

convolutional neural networks have also succeeded at segmenting anatomical sections of wood

(Garcia-Pedrero et al., 2018). The integration of visual computing algorithms into WIAD to

automate the analysis and reduce analysis time, by suggesting ring boundaries to the user after

image upload, is under development. For this purpose, we are currently creating the first fully

labeled image library of sufficient size (more than 100 000 labels in 1000 images) to train a

robust ring detection algorithm that works for ten species including ring-, diffuse- and non-

porous wood. Specifically, we adopt the U-Net model (Ronneberger et al., 2015) to predict the

pixel-wise probability of ring boundaries. Since models trained with the default pixel-wise cross-

entropy loss usually yield boundaries with blurry artifacts, we incorporate a perceptual

discriminator energy function to improve the sharpness of the boundaries while preserving the

connectivity, following the high-level idea of Mosinska et al. (2018). Beyond identifying rings, the

identification of other visual features such as wood morphology (e.g., ring-porous, diffuse-

porous, and non-porous), density fluctuations or frost and fire scars, could equally be automated

using similar techniques. Another useful addition would be the integration of cross-dating tools

that help to visually and statistically crossdate multiple measurement series such as xDateR

(Bunn, 2008, 2010) or ringdater (Reynolds et al., 2020). Similar to suggestions of ring

boundaries, fast fuzzy subsequence matching (Gong et al., 2019) and unsupervised anomaly

detection algorithms for either time-series (Ren et al., 2019) or high dimensional data like raw

images (Wang et al., 2019) could be used to assist in the crossdating and identification of

missing rings, which would further increase processing speed and improve reproducibility of

results.

Beyond streamlining sample processing, these features could enable scientists and

potentially even citizen scientists to contribute to the repository in the long-term. However,

sufficient skills of the software must be demonstrated rigorously before expert opinion can be

meaningfully complemented. Nonetheless, the general public could already help in the labelling

of datasets and thereby provide training data for the refinement of algorithms. Crowd-sourcing

through a community science platform (e.g., Zooniverse) could be used to label training data

and evaluate annotations of existing collections. Community-science projects come with

tradeoffs in data quality, privacy protection, resource security, transparency, and trust by

citizens (Anhalt-Depies et al., 2019), which we will consider during further development.

In conclusion, WIAD provides simple tools and a framework for further development to make

analysis of wood images more transparent and reproducible. By offering integrated data

processing and archival services, platforms such as WIAD facilitate analysis by making data

accessible, tracking provenance, assuring metadata standards and, therefore, creating data

products that can be used, amalgamated, scaled, built upon, and modified seamlessly.

References

Ahmed, Z., Zeeshan, S., & Dandekar, T. (2014). Developing sustainable software solutions for

bioinformatics by the "Butterfly" paradigm. *F1000Research*, *3*, 71. doi:

10.12688/f1000research.3681.1

Anhalt-Depies, C., Stenglein, J. L., Zuckerberg, B., & Townsend, P. A. (2019). Tradeoffs and

tools for data quality, privacy, transparency, and trust in citizen science. *Biological*

Conservation, *238*, 108195. doi: 10.1016/j.biocon.2019.108195

Babst, F., Poulter, B., Bodesheim, P., Mahecha, M. D., & Frank, D. C. (2017). Improved tree-

ring archives will support earth-system science. *Nature Ecology & Evolution*, *1*, 0008.

doi: 10.1038/s41559-016-0008

Bar-On, Y. M., Phillips, R., & Milo, R. (2018). The biomass distribution on Earth. *Proceedings of*

the National Academy of Sciences, *115*(25), 6506–6511. doi: 10.1073/pnas.1711842115

Bergeron, Y., Denneler, B., Charron, D., & Girardin, M.-P. (2002). Using dendrochronology to

reconstruct disturbance and forest dynamics around Lake Duparquet, northwestern

Quebec. *Dendrochronologia*, *20*(1), 175–189. doi: 10.1078/1125-7865-00015

Björklund, J. A., Gunnarson, B. E., Seftigen, K., Esper, J., & Linderholm, H. W. (2014). Blue

intensity and density from northern Fennoscandian tree rings, exploring the potential to

improve summer temperature reconstructions with earlywood information. *Climate of the*

Past, *10*(2), 877–885. doi: 10.5194/cp-10-877-2014

Björklund, J., Seftigen, K., Schweingruber, F., Fonti, P., Arx, G. von, Bryukhanova, M. V., …

Frank, D. C. (2017). Cell size and wall dimensions drive distinct variability of earlywood

and latewood density in Northern Hemisphere conifers. *New Phytologist*, *216*(3), 728–

740. doi: 10.1111/nph.14639

Brewer, P. W., Murphy, D., & Jansma, E. (2011). TRICYCLE: A UNIVERSAL CONVERSION

TOOL FOR DIGITAL TREE-RING DATA. *Tree Ring Research*, *67*(2), 135–144.

Bunn, A. G. (2008). A dendrochronology program library in R (dplR). *Dendrochronologia*, *26*(2),

115–124. doi: 10.1016/j.dendro.2008.01.002

Bunn, A. G. (2010). Statistical and visual crossdating in R using the dplR library.

Dendrochronologia, *28*(4), 251–258. doi: 10.1016/j.dendro.2009.12.001

Bunn, A.G., Korpela, M., Biondi, F., Campelo, P., Mérian, P., Qaedan, F., & Zang, C. (2021)

dplR: Dendrochronology Program Library in R,https://CRAN.R-project.org/package=dplR

Cook, E. R. (1987). The decomposition of tree-ring series for environmental studies. *Tree-Ring*

Bulletin, *47*, 37–59.

Cook, E. R., & Peters, K. (2016). Calculating unbiased tree-ring indices for the study of climatic

and environmental change: *The Holocene*. (Sage CA: Thousand Oaks, CA). doi:

10.1177/095968369700700314

Fabijańska, A., Danek, M., Barniak, J., & Piórkowski, A. (2017). Towards automatic tree rings

detection in images of scanned wood samples. *Computers and Electronics in*

Agriculture, *140*, 279–289. doi: 10.1016/j.compag.2017.06.006

Fegraus, E. H., Andelman, S., Jones, M. B., & Schildhauer, M. (2005). Maximizing the Value of

Ecological Data with Structured Metadata: An Introduction to Ecological Metadata

Language (EML) and Principles for Metadata Creation. *The Bulletin of the Ecological*

Society of America, *86*(3), 158–168. doi: 10.1890/0012-

9623(2005)86[158:MTVOED]2.0.CO;2

Fritts, H. C. (1976). *Tree Rings and Climate*. Elsevier. doi: 10.1016/B978-0-12-268450-0.X5001-

0

Garcia-Pedrero, A., Garcia-Cervigon, A., Caetano, C., Calderon-Ramirez, S., Olano, J. M.,

Gonzalo-Martin, C., … Garcia-Hidalgo, M. (2018). Xylem Vessels Segmentation

Through a Deep Learning Approach: A First Look. *2018 IEEE International Work*

Conference on Bioinspired Intelligence (IWOBI), 1–9. San Carlos: IEEE. doi:

10.1109/IWOBI.2018.8464184

Gong, X., Fong, S., & Si, Y.-W. (2019). Fast fuzzy subsequence matching algorithms on time-

series. *Expert Systems with Applications*, *116*, 275–284. doi:

10.1016/j.eswa.2018.09.011

Himmelbauer, M. L., Loiskandl, W., & Kastanek, F. (2004). Estimating length, average diameter

and surface area of roots using two different Image analyses systems. *Plant and Soil*,

260(1/2), 111–120.

Hufkens, K., Basler, D., Milliman, T., Melaas, E. K., & Richardson, A. D. (2018). An integrated

phenology modelling framework in r. *Methods in Ecology and Evolution*, *9*(5), 1276–

1285. doi: 10.1111/2041-210X.12970

Janesick, J., & Putnam, G. (2003). Developments and Applications of High-Performance Ccd

and Cmos Imaging Arrays. *Annual Review of Nuclear and Particle Science*, *53*(1), 263–

300. doi: 10.1146/annurev.nucl.53.041002.110431

Jones, M. B., Schildhauer, M. P., Reichman, O. J., & Bowers, S. (2006). The New

Bioinformatics: Integrating Ecological Data from the Gene to the Biosphere. *Annual*

Review of Ecology, Evolution, and Systematics, *37*(1), 519–544. doi:

10.1146/annurev.ecolsys.37.091305.110031

List, M., Ebert, P., & Albrecht, F. (2017). Ten Simple Rules for Developing Usable Software in

Computational Biology. *PLOS Computational Biology*, *13*(1), e1005265. doi:

10.1371/journal.pcbi.1005265

Lorimer, C. G. (1984). Methodological considerations in the analysis of forest disturbance

history. *Canadian Journal of Forest Research*, *15*, 200–213.

Mann, M. E., Zhang, Z., Hughes, M. K., Bradley, R. S., Miller, S. K., Rutherford, S., & Ni, F.

(2008). Proxy-based reconstructions of hemispheric and global surface temperature

variations over the past two millennia. *Proceedings of the National Academy of*

Sciences, *105*(36), 13252–13257. doi: 10.1073/pnas.0805721105

Michener, W. K. (2015). Ecological data sharing. *Ecological Informatics*, *29*, 33–44. doi:

10.1016/j.ecoinf.2015.06.010

Mosinska, A., Marquez-Neila, P., Kozinski, M., & Fua, P. (2018). Beyond the Pixel-Wise Loss

for Topology-Aware Delineation. *Proceedings of the IEEE Conference on Computer*

Vision and Pattern Recognition, 3136–3145. Retrieved from

http://arxiv.org/abs/1712.02190

Ren, H., Xu, B., Wang, Y., Yi, C., Huang, C., Kou, X., … Zhang, Q. (2019). Time-Series

Anomaly Detection Service at Microsoft. *Proceedings of the 25th ACM SIGKDD*

International Conference on Knowledge Discovery & Data Mining, 3009–3017. doi:

10.1145/3292500.3330680

Reynolds, D. J., Edge, D. C., & Black, B. A. (2020). RingdateR: A Statistical and Graphical Tool

for Crossdating. *Dendrochronologia*, 125797. doi: 10.1016/j.dendro.2020.125797

Richardson, A. D., Hufkens, K., Milliman, T., Aubrecht, D. M., Chen, M., Gray, J. M., … Frolking,

S. (2018). Tracking vegetation phenology across diverse North American biomes using

PhenoCam imagery. *Scientific Data*, *5*, 180028. doi: 10.1038/sdata.2018.28

Ronneberger, O., Fischer, P., & Brox, T. (2015, May 18). *U-Net: Convolutional Networks for*

Biomedical Image Segmentation. 234–241. Retrieved from

http://arxiv.org/abs/1505.04597

Rossi, S., Anfodillo, T., & Menardi, R. (2006). Trephor: A New Tool for Sampling Microcores

from tree stems. *IAWA Journal*, 89–97. doi: 10.1163/22941932-90000139

Schulman, E. (1956). *Dendroclimatic Changes in Semiarid America*. University of Arizona

Press.

Seyednasrollah, B., Young, A.M., Hufkens, K., Milliman, T., Friedl M.A., Frolking, S., &

Richardson, A.D. (2019) Tracking vegetation phenology across diverse biomes using

Version 2.0 of the PhenoCam Dataset. *Sci Data* **6,** 222 (2019). doi.org:10.1038/s41597-

019-0229-9

Solly, E. F., Brunner, I., Helmisaari, H.-S., Herzog, C., Leppälammi-Kujansuu, J., Schöning, I.,

… Hagedorn, F. (2018). Unravelling the age of fine roots of temperate and boreal

forests. *Nature Communications*, *9*(1), 1–8. doi: 10.1038/s41467-018-05460-6

Subah, S., Derminder, S., & Sanjeev, C. (2017). An Interactive Computer Vision System for

Tree Ring Analysis. *Current Science*, *112*(06), 1262. doi: 10.18520/cs/v112/i06/1262-

1265

von Arx, G., & Carrer, M. (2014). ROXAS – A new tool to build centuries-long tracheid-lumen

chronologies in conifers. *Dendrochronologia*, *32*(3), 290–293. doi:

10.1016/j.dendro.2013.12.001

Wang, S., Zeng, Y., Liu, X., Zhu, E., Yin, J., Xu, C., & Kloft, M. (2019). Effective End-to-end

Unsupervised Outlier Detection via Inlier Priority of Discriminative Network. In H.

Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, & R.

Garnett (Eds.), *Advances in Neural Information Processing Systems 32* (pp. 5962–

5975). Curran Associates, Inc. Retrieved from http://papers.nips.cc/paper/8830-effective-

416    end-to-end-unsupervised-outlier-detection-via-inlier-priority-of-discriminative-network.pdf

417 Wieczorek, J., Bloom, D., Guralnick, R., Blum, S., Döring, M., Giovanni, R., … Vieglais, D.

418    (2012). Darwin Core: An Evolving Community-Developed Biodiversity Data Standard.

419    *PLOS ONE*, *7*(1), e29715. doi: 10.1371/journal.pone.0029715

420 Wilson, G., Aruliah, D. A., Brown, C. T., Hong, N. P. C., Davis, M., Guy, R. T., … Wilson, P.

421    (2014). Best Practices for Scientific Computing. *PLOS Biology*, *12*(1), e1001745. doi:

422    10.1371/journal.pbio.1001745

423 Wilson, G., Bryan, J., Cranston, K., Kitzes, J., Nederbragt, L., & Teal, T. K. (2017). Good

424    enough practices in scientific computing. *PLOS Computational Biology*, *13*(6),

425    e1005510. doi: 10.1371/journal.pcbi.1005510

426 Zhao, S., Pederson, N., D'Orangeville, L., HilleRisLambers, J., Boose, E., Penone, C., …

427    Manzanedo, R. D. (2018). The International Tree-Ring Data Bank (ITRDB) revisited:

428    Data availability and global ecological representativity. *Journal of Biogeography*, *46* (2).

429    doi: 10.1111/jbi.13488

431 Author contributions

432 TR conceived the idea and developed it with BS and DB. BS developed the code with input

433 and additions from TR and DB. TR cored the trees, mounted and sanded the cores. EM, TM,

434 and TR scanned images and tested the tools. JC, ZL, and DW developed the algorithm for

435 automatic boundary detection. All authors provided ideas on how to improve the tools. TR led

436 the writing of the manuscript. All authors contributed critically to drafts and approved the final

437 manuscript.

Code and data availability

All data is publicly available through getWIADExampleData function built into the package. The

R package requires R to be installed and underlying code are also publicly accessible under a

AGPL v3 license on github at https://github.com/bnasr/wiad and is easily installed via CRAN:

```
utils::install.packages('wiad',repos='https://cran.us.r-project.org')
```

Or directly from github using:

```
if (!require (devtools)) {install.packages ('devtools')}
devtools::install_github ('bnasr/wiad')
```

The interactive mode can be launched from an interactive R environment by one of the following

commands.

```
Library (wiad)
```

```
Launch ()
```

Or

```
wiad::Launch()
```

or form the command line (e.g., shell in Linux, Terminal in macOS and Command Prompt in

Windows machines) where an R engine is already installed by:

```
Rscript -e "wiad::Launch(Interactive = TRUE)"
```

Calling the Launch function opens up the WIAD app in the system's default web browser.

Acknowledgements

TR and TM acknowledge the support from Microsoft "AI for Earth" grant program (271089). AR, EM and TR acknowledge support from the National Science Foundation (DEB- 1741585, HF LTER DEB-1237491 and DEB-1832210). DB acknowledges support through the Swiss National Science Foundation (PSBSP3-168701) and the Harvard Forest Bullard Fellowship. EM was also benefited from NSF DBI-1459519 and the Harvard Forest Summer Research Program in Ecology. We also thank Patrick Baker, Greg Caporaso, Allyson Carroll, Patrick Fonti, George Koch, Rubén D. Manzanedo, Steve Sillett, Laura G. Smith, Yiping Zhang for their valuable feedback.