# Robust data storage in DNA by de Bruijn graph-based decoding

Li-Fu Song[1,2], Feng Geng[3], Zi-Yi Gong[1,2], Bing-Zhi Li[1,2*], Ying-Jin Yuan[1,2*]

[1] Frontier Science Center for Synthetic Biology and Key Laboratory of Systems Bioengineering (Ministry of Education), Tianjin University, Tianjin 300072, China

[2] School of Chemical Engineering and Technology, Tianjin University, Tianjin 300072, China

[3] College of Pharmacy, Binzhou Medical University, Yantai 264003, China

*Corresponding authors: bzli@tju.edu.cn, yjyuan@tju.edu.cn

## Abstract

DNA data storage is a rapidly developing technology with great potential due to its high density, long-term stability, and low maintenance cost. The major technical challenges include various errors such as the indels, rearrangements, and strand breaks that frequently arise during DNA synthesis, amplification, sequencing, and preservation. Here, we report the development of a de Bruijn graph-based, greedy path search algorithm (DBG-GPS) aiming to handle such issues. We demonstrate that accurate data recovery could be achieved from

deep error-prone PCR products. The robustness of this method was further

verified with one hundred parallel data retrievals from PCR products containing

numerous rearrangements introduced by intended unspecific amplifications.

With DBG-GPS, we successfully decoded the original information even after

treating the DNA at 70°C for 65 days. DBG-GPS shows linear decoding

complexity and is faster than the multiple alignment-based methods by two

orders of magnitude, suited for large-scale data storage.

## Keywords

Synthetic Biology, DNA data retrieval, DNA codec system, de Bruijn graph,

Fountain codes

## Introduction

DNA is the natural solution for the preservation of genetic information of all life

forms on earth. Recently, million years old genomic DNA of mammoths was

successfully decoded revealing its high stability as an information carrier under

frozen conditions[1]. Owing to its stability, high density, and low maintenance

cost revealed by recent studies, DNA has been considered an ideal storage

medium to meet the challenge of data explosion in the future[2–9]. Frequently

occurring errors in DNA synthesis, amplification, sequencing, and preservation,

however, challenge the reliability of data storage in DNA. Efforts to solve this

problem led to the implementation of a codec system which requires two layers

of error correction (EC) codes, the outer layer codes handling the strand

dropouts and the inner layer codes dealing with intramolecular errors, ensuring

accurate information readouts[10–13]. Strand dropouts are erasures and
therefore they can be well solved by erasure codes, *e.g.* Fountain,
Reed-Solomon (RS) codes[10–12]. By contrast, the performance of existing inner
layer codec systems, *e.g.* multiple alignment-based methods, is less
satisfactory as they are not efficient in correcting indel errors, and in particular,
not capable of dealing with rearrangements and strand breaks. Highly robust
inner codec systems remain to be explored.

Base-shift arises from indel is difficult to handle with traditional EC codes,
which detect indels but cannot position them. A two-dimensional coding
strategy with traditional EC codes can transform the indel errors into
substitutions. In this strategy, a single indel in one dimension will lead to a
series of 'substitutions' in another dimension (**Fig. S1**). Thus, this strategy only
works with low indel rates. Increasing indels will lead to an overwhelming
number of "substitutions" exhausting the column EC codes[8,10]. Recently
developed hash encoded, decoded by greedy exhaustive search (HEDGES)
codes can be used to correct higher frequency of indels[14]. Based on the
simulation, HEDGES codes require 40% redundancy codes for correction of 3%
indel errors, which would significantly increase the cost of data writing. Strand
rearrangements caused by unspecific amplifications are frequently
encountered and could be a potential threat to data integrity especially when
massive multiple retrievals from a large oligo pool are required. Currently,
people optimize PCR conditions to avoid rearrangements to occur and use gel
purification to physically exclude rearranged strands from the data pool. None
of the existing methods can be used to correct rearrangements. DNAs are
subjected to hydrolysis and degradation[12,13] under certain conditions and in

long-term storage, highlighting the importance of data stability studies on

influences of harsh conditions, such as high temperature or UV exposure, and

methods of DNA protection[8,14]. New coding methods that can tolerate

fragmented DNA strands are nevertheless critical for enhancing the

robustness of DNA data storage.

As the synthesis of long DNA is currently impractical, data storage in DNA

relies on a large number of fragments. Consequently, data decoding involves

the assembly of information pieces carried by individual DNA fragments, a

process similar to genome assembly from shotgun sequencing. De Bruijn

graph theory uses $k$-mer components to represent sequences. The analogy of

genome assembly to data decoding and the success of the application of De

Bruijn graph theory to genome assembly[20,21] prompted us to investigate its

potentials in DNA data storage.

In this study, we report a strand reconstruction algorithm, de Bruijn

Graph-based Greedy Path Searching (DBG-GPS) that allows robust DNA data

storage. This algorithm handles indels, rearrangements, and strand breaks by

strand reconstruction from multiple, error-rich strand copies, resulting in

accurate and rapid data retrievals. Using this method, an up to 10% high indel

rate, intended rearrangements and forced DNA strand breaks were shown to

be efficiently corrected. DBG-GPS is faster than the clustering and multiple

alignment (CL-MA) based methods in decoding by two orders of magnitudes.

The linear decoding complexity revealed by simulation suggests that

DBG-GPS could be adapted to large-scale data storage.

# Results

## The great potentials of de Bruijn graph-based decoding

To inspect the potentials of de Bruijn graph theory in DNA data storage, we first analyzed effects of representative substitutions, indels, and strand breaks in de Bruijn graph as shown in **Fig. 1a**. The simple de Bruijn graph on the right was constructed from the four sequence copies of "AACGGCGGCTGT" on the left with a *k*-mer size of four (**Fig. 1a-i**). The sequence of "AACGGCGGCTGT" is the path of "$a \to b \to c \to d \to e \to c \to f \to g \to h$" in the constructed graph. A substitution of "G" to "A" in sequence #2 will lead to a branch path, as shown in red color, and decreased coverages of the correct nodes (**Fig. 1a-ii**). With traditional EC codes, indels are much more difficult to handle than substitutions due to the base shift issue. The representative base indels in de Bruijn graph, however, are highly similar to substitutions (**Fig. 1a-iii**). Strand breaks also cause serious problems for traditional EC codes. With de Bruijn graph, the strand breaks only reduce the coverages of the correct nodes, without changes the graph structure. A greedy path search process, in combination with a path recognition mechanism, could decode the correct strand. In this way, the errors are transformed into a path search and selection problem by de Bruijn graph theory. With this mechanism, as long as the correct path, e.*g.* "$a \to b \to c \to d \to e \to c \to f \to g \to h$" in **Fig. 1a-i**, is preserved, the corresponding DNA strand can be decoded theoretically. Thus, the robustness of the correct path determines the potentials of the graph theory-based decoding.

Clearly, the sequence error rates and copy number together determine the

robustness of a strand path in de Bruijn graph. To further investigate how the

sequence copies and error rates affect path robustness, we simulated DNA

sequences with different error rates. Variant numbers of the simulated

error-containing sequences were utilized for de Bruijn graph construction and

path integrality analysis (**Fig. 1b, c**). The integrality of the correct path was

tested by checking the existence of all $k$-mers in this path in the constructed

graph. The rate of the sequences with a complete path in the graph was

defined as 'maximal strand decoding rate' ($S_m$), which stands for the maximal

strand decoding rate achievable by an actual de Bruijn graph-based decoder.

Sequences with different types of errors were separately simulated. Twenty

copies of sequences in a length of 320 bp containing different types and rates

of errors were estimated for $S_m$ values. As shown in **Fig. 1b**, the $S_m$ values as

expected are inversely related to the error rates but are similar regardless of

the error types at the same error rates. Importantly, with merely twenty

sequence copies, the sequence path in de Bruijn graph shows high robustness

with an error rate of 5%, a common error level in reported DNA data storage

studies[11,12,15]. In practice, emerged errors are mixtures of different types.

Therefore, we decided to investigate the sequence path robustness by

simulations with sequences containing mixed errors. The simulations were

performed with variable total error rates from 1% to 10%, among which the

errors are consisted of substitutions (50%), insertions, and deletions (25%

each), and variable strand copies from 5 to 100. As shown in **Fig. 1c**, even

with a high error rate of 10%, $S_m$ > 0.99 can still be obtained with sequence

copies of 60 only (red dashed line), revealing the great potentials of de Bruijn

graph-based decoding.

## Development of DBG-GPS for efficient strand reconstruction

The decoding process requires three basic steps, de Bruijn Graph construction,

greedy path search, and path recognition. The de Bruijn graph size is

dependent on the total number of correct *k*-mers plus noise *k*-mers. The

number of correct *k*-mers is fixed for the storage of any given volume of

information. The number of noise *k*-mers becomes a determinant with a larger

number increasing de Bruijn graph size and possible paths, leading to longer

path search time. Hence, we propose to include an additional step to exclude

noise *k*-mers to reduce search time, illustrated in **Fig. 2a**.

**Elimination of noise *k*-mers decreases the greedy path search**

**complexity**

With simulations, about thirty times enlargement of the de Bruijn graph size

was observed when 4% random errors were introduced into 10,000 DNA

strands with 100 sequence copies each (**Fig. S2a**). To quantify the noise

*k*-mers in a de Bruijn graph, we introduce an indicator $K_n$, which is the ratio of

noise *k*-mers and correct *k*-mers in a de Bruijn graph. Clearly, more strand

copies and errors will introduce more noise *k*-mers to the de Bruijn graph,

resulting in a larger $K_n$ value. Monte Carlo simulations show a quick increase

of $K_n$ by increasing either the error rate or the sequence copies (**Fig. S2a**).

The number of branch paths and decoding time increase exponentially with

error rates or strand copy numbers (**Fig. S2b**).

DNA data operations introduce a large number of errors. The occurrence of

each error is however a low probability event. Therefore, the coverage of noise

*k*-mers is generally much lower than that of the correct ones. Elimination of the

*k*-mers with only one occurrence significantly reduced branch paths not

affecting the integrity of correct paths (**Fig. S2b**). We next attempted to

mathematically describe the validity of using coverage as an indicator to

recognize noise *k*-mers. Monte Carlo simulations were performed with 10,000

DNA strands, in which a Poisson model was employed for the simulation of the

copy number distribution of each strand. The expectation value ($\lambda$) of strand

copies was pre-set to be 50 and the error rate being 4%. The resulting

coverage distribution of noise *k*-mers and correct *k*-mers were further analyzed.

A coverage cut-off of 8 was found effective in the removal of most noise *k*-mers

(**Fig. S2c**).

**Path recognition by CRC codes and both-way search strategy**

Noise *k*-mers cannot be completely removed solely by the elimination of low

coverage *k*-mers. Branch paths still exist due to the remaining noise *k*-mers. A

method to recognize the correct path is thus required. Traditional EC codes

including cyclic redundancy check (CRC), RS, and hash codes are choices for

this purpose. We failed to find a proper hash function that can generate short

keywords. RS codes, optimized for correcting erasures, are not suited for path

recognition, which does not involve erasures. CRC codes were chosen

because of the efficiency of these codes in error detection instead of error

correction. The effectiveness of CRC codes in path recognition was well

demonstrated by intensive (one million) Monte Carlo simulations.

To further reduce the greedy path search time, we proposed a both-way

search strategy that allows simultaneous search from both ends of DNA

strands. In this strategy, an additional 'anchor' element was designed for each

DNA strand. The anchor corresponds to the index located on the other end of

the DNA strand (**Fig. 2b)**, and is generated from the index by a specific

function. A given index processed by the function generates a specific number,

represented by the anchor sequence. For proof-of-concept, the pseudorandom

function of Python is used for the generation of the anchors from the indexes

as seeds. Pseudorandom function generates an identical 'random' value with

the same seed. Thus, informed with indexes, the greedy path search engine

calculates corresponding anchors, and carries out the both-way search

strategy. The both-way search strategy significantly reduced the decoding time,

with effects more obviously observed when sequence error rates are high. Up

to 60% reduction was evident with an error rate of 10% and a copy number of

100, while decoding accuracy was well maintained (**Fig. S3**).

**Integration of DBG-GPS with outer erasure codes and**

**performance test**

DBG-GPS is designed as an inner decoding mechanism for the error-free

reconstruction of DNA strands. It can be easily combined into the decoding

process of outer erasure codes, *e.g.* fountain codes or RS codes, as shown by

**Fig. 2c**. Python implementation of DBG-GPS using fountain codes as outer

codes                          is                          available                          at

https://switch-codes.coding.net/public/switch-codes/DNA-De-Bruijn-Decoding/

git/files.

To systematically analyze the decoding accuracy of our Python implementation

of DBG-GPS, Monte Carlo simulations of 10,000 DNA strands (each strand

with 60 copies) containing various error rates ranging from 1% to 10% were

performed and the results were subjected to decoding using the Python

implementation and even at 10% of error, decoding accuracy was still

remarkably satisfactory with the overall $S_r$ higher than 96.7% (**Tab. S2**). We

next tested the decoding speed of DBG-GPS in comparison with CL-MA based

methods. To the best of our knowledge, the CL-MA based methods are the

only methods that have been used to calculate the consensus sequence from

multiple error-rich strand copies[12,17]. To compare the decoding speed of

DBG-GPS with CL-MA based methods, DNA fountain codes were used to

generate 10,000 DNA droplets and fifty sequence copies for each droplet. 4%

errors (2% substitutions, 1% insertions and 1% deletions) were randomly

introduced. A total of 500,000 error-rich sequences were then subjected to

strand decoding by DBG-GPS and CL-MA respectively. Considering the

complexity of the clustering process for the CL-MA-based decoding, we fed the

Muscle 3.8.31[16] program with pre-clustered reads. For decoding speed

comparison, estimation based on the previously reported clustering time in

literature was used[14]. Since the multiple alignment process was performed by

a standalone program (Muscle 3.8.31[16]), there will be 10,000 times of IO (input

and output) with the file system during strand decoding by CL-MA. To estimate

the IO time, one sequence of the DNA droplet was repetitively submitted to

Muscle for multiple alignment analysis for 10,000 times. This process is

iterated three times and the average time is subtracted from CL-MA based

decoding time. The $k$-mer counting step of DBG-GPS was performed with

JellyFish 2.3. As shown in **Tab. 1**, DBG-GPS shows 103 times faster than the

CL-MA based methods. Importantly, in the range of data scale from 10 to

10,000 DNA droplets, DBG-GPS exhibited linear decoding complexity (**Fig.**

**S5**), suggesting that this method is suited for large-scale data storage.

Large-scale simulations were then used to assess the capacity of DBG-GPS
with big data sets. An Ubuntu server 20.10 installation disk image (~ 1 GB)
was used as the input file to generate DNA droplets. Each DNA droplet was set
to carry 60 bytes of information with a total DNA length of 316bp, around the
technical limits of current DNA synthesis technologies. Ten million DNA
droplets, representing a data scale of 600 megabytes (MB) were simulated.
With an expected copy number of fifty, error rate of 4% (approximately 2%
substitutions, 1% insertions, 1% deletions), a 155GB sequence file was
generated. Loading the $k$-mer counting results of Jellyfish on a computation
workstation equipped with 640GB memories, the Python script encountered
memory limitations. We had to reduce the DNA droplet number to five million,
representing a data size around 300MB. Preliminary decoding simulations on
this data scale revealed a problem of long decoding time. Detailed analysis
showed that this is due to repeated presentations of same $k$-mers located in
different strands. We then solved the problem using a combination of two
strategies, with the first employing a filtering process during the production of
DNA droplets to exclude seriously entangled DNA strands, and the second
setting an upper boundary for path number in greedy path search. The greedy
path search engine aborts search if the number of found paths exceeding this
boundary. Five million DNA droplets were simulated three times independently.
On average, 4,971,880 DNA droplets ($S_r$ = 99.44%) were recovered, proving
the great capacity of DBG-GPS.

## Experimental verification of the robustness of DBG-GPS

To verify the robustness of DBG-GPS, a 314 KB zipped file, including two text files and four jpeg pictures, was encoded into 12,000 DNA strands, each in a length of 200 bp using fountain as outer codes. Each strand encodes thirty bytes of data, three bytes of CRC codes, four bytes of index codes, and four bytes of anchor codes (**Fig. 2b**). The overall strand redundancy was designed as 10.5% based on the expectation of more than 92% of the strands could be correctly decoded. A final concentration of 2 ng/μl designed DNA strands were synthesized by Twist Bioscience (**Fig. 3a**), and used as templates for PCR amplification and data retrievals. Different types of errors, including indels, substitutions, rearrangements, and strand breaks were intentionally introduced by three harsh experiments (**Fig. 3b**-**d**), followed by decoding to examine the robustness of DBG-GPS.

### Data retrievals with deep error-prone PCR products

A serial of six error-prone PCR (ePCR), with each reaction containing 30 thermal cycles, was performed using an error-prone PCR Kit to amplify the ssDNA library introducing large numbers of substitution errors, estimated 8 errors per 1,000 bp per amplification cycle base on the manufacturer's instruction. All six ePCR products, ePCR#1-6, were sequenced by Illumina technology. Due to unspecific amplifications, in addition to substitution errors, ePCR#2-6 products contain DNAs of different sizes, evident by a smear from 100 to 4,000 bp on agarose gel (**Fig. 4a**). As some of these DNA sequences were too long to be sequenced by Illumina platform, these PCR products were digested with DNase I to a target length of 200 bp. After digestion, all

fragments were collected for sequencing. The sequencing raw reads were

subjected to DBG-GPS based decoding.

Regardless of rough amplification conditions expected to introduce a large

number of errors, strikingly the $S_m$ values of all six samples were higher than

99% (**Fig. 4b**), with the $S_m$ values of ePCR#1-3 being 100%, indicating perfect

reservation of all strand paths even after 90 cycles of ePCR. $S_r$ values in a

range of 93.2-99.8% were obtained for the six samples, ensuring reliable data

decoding by the outer fountain codes. Decrease of $S_r$ was observed with

increased ePCR cycles. More PCR errors were expected to increase branch

paths, raising the necessary cutoff for noise $k$-mers elimination. More correct

$k$-mers were consequently discarded by mistake, resulting in a lower $S_r$ value.

To further test the robustness of DBG-GPS, sequencing data with low

coverage ranging from 1 to 256 was obtained by random sub-sampling on the

sequencing results of ePCR#1 and ePCR#2. The $k$-mer dropout rates ($K_d$),

noise $k$-mer indicator ($K_n$) and strand recovery rate ($S_r$) were calculated and

plotted against coverage values (**Fig. 4c**). As expected, with the same

coverage, both $K_n$ and $K_d$ values of ePCR#2 are always higher than

ePCR#1, consistent with accumulating errors in each additional round of

ePCR. Upon increasing coverage, the $K_n$ values of both samples reflecting

the numbers of noise $k$-mers increased quickly, while the $K_d$ values reflecting

the dropouts of correct $k$-mers decreased quickly. As shown in **Fig. 4c**, the two

samples can be reliably decoded at coverage as low as 16 and 24.

**Multiple data retrieval and accelerated aging test**

Multiple data retrievals from storage media are required in practice. Thus, data robustness sustainable during multiple retrievals needs to be tested for our algorithm. Till now, only a limited number (<10) of multiple retrievals from high-quality PCR products have been reported for DNA data storage. To mimic the required multiple retrievals in practice and further demonstrate the robustness of our method, 100 times parallel data retrievals from PCR-amplified ssDNA library were carried out (**Fig. 3**), in which massive unspecific amplifications indicated by smears from 100 to 8,000 bp on agarose gel were observed (**Fig. 5a**). The $S_m$ values of all retrievals were still remarkably high in the range from 99.44% to 99.78% (**Fig. 5b**). The $S_r$ values ranged from 98.45% to 99.02%, ensuring accuracy in these data retrievals.

The CL-MA based codec systems highly rely on intact DNA strands for decoding, whereas DBG-GPS relies on short $k$-mers. Thus DBG-GPS likely tolerates DNA degradation. To test this hypothesis, accelerated aging experiments were performed as shown in **Fig. 3c**. The master pool was first PCR-amplified followed by incubation at 70°C for a prolonged period of time up to 65 days. Agilent 2100 Bioanalyzer was used to analyze the samples. A 14 days of incubation caused the complete disappearance of the 200bp peak prominent in the original sample, indicating that the integrity of the DNA strand has been severely damaged (**Fig. S6**). Such degree of degradation would have made it impossible to recover the encoded data using the previously reported codec systems. By contrast, DBG-GPS based decoding enabled high strand recovery rates, ensuring accurate data retrievals from all samples that

have been heat-treated for 7, 14, 30 and even 65 days. A high $S_r$ value of

98.18% was obtained with the sample treated at 70°C for 65 days (**Fig. 5c**).

This $S_r$ value is only slightly lower than that of the control stored at -20°C

(99.40%). Data retrievals from accelerated aged DNAs have been

reported[10,18,19]. In these studies, the authors tested the effects of different

methods for the preservation of data encoded DNA, among which embedment

in silicon beads was shown to be the best allowing recovery of information

after treatment at 70°C for 7 days. According to the authors, this was thermally

equivalent to storing information on DNA at 9.4°C for 2000 years[10]. Based on

this estimation, our DBG-GPS algorithm can be used to retrieve data from a

DNA solution preserved at 9.4°C for 18,571 years.

# Discussion

Data robustness, density and low-cost are important parameters, determining

the technical advancements of a storage medium. In general, higher data

robustness requires more redundancy codes, which decrease information

density and cost effectivity. Based on information theory, redundancy codes in

the form of "data repetition" are unfavorable since production of additional data

copies on traditional media is cost-ineffective and time-consuming. By contrast,

data repetition in the form of DNA strand copies can be obtained inexpensively

and speedily. The traditional definition of "coding efficiency" needs to be

adapted to DNA data channel. With current technologies, producing a single

copy of DNA data is not even doable. It has been reported that serial dilutions

to reduce the copy numbers of information-bearing DNA strands till the

average copy number below ten resulted in massive strand dropouts, making

reliable data retrieval impractical[20]. Even if a single copy of DNA data is

obtainable, it may be damaged due to DNA degradation under certain

conditions or during long-term storage. Taken together, the design for DNA

storage should be based on the reality and necessity, the presence of more

than one copies of DNA strands, and not too many copies (below 100) to

maintain high information density. In other words, "multicopy" is crucial for the

robustness of DNA data storage and should ideally be maintained in a

reasonable range. A new theory to design EC codes taking this unique

"multicopy" feature into consideration will help solving the main technical issue

in DNA storage, the error-free decoding of DNA sequences in a completely

different fashion.

To the best of our knowledge, CL-MA based methods are the only reported

methods used for DNA decoding from error-containing multicopies. These

methods are computation-intensive, and are not robust when dealing with

strand rearrangements and breaks. In this study, we developed a strand

reconstruction algorithm based on the de Bruijn graph theory and tested its

robustness. We were able to accurately and rapidly decode DNA data from

error-rich strand copies using this algorithm. The errors include indels,

rearrangements and strand breaks. It is worth noting that the encoded

information from a DNA solution that has been incubated at 70°C for 65 days

can be accurately recovered with our algorithm. The degree of damage to DNA

under this heating condition was estimated to be equivalent to that under 9.4°C

for more than 18,000 years[10]. Such unprecedented robustness highlights the

importance of our method and suggests the great potential of de Bruijn graph

theory in DNA data channel. Our algorithm is presumably compatible with a

variety of DNA preservation, *e.g.* silicon beads[10], nanoparticles[18], and alkaline

salts[19], to further enhance data stability.

The Python codes implemented in this study use a simple hash dictionary for

the retrieval of *k*-mers. C++ implementation with a more advanced *k*-mer data

structure[21,22] is expected to significantly reduce the memory cost, as well as

decoding time. In data decoding from 50 sequence copies containing 4%

errors, the performance of DBG-GPS is superior to that of the CL-MA based

methods in speed by one hundred fold. A higher ratio of noise *k*-mers is

expected to decrease decoding speed and accuracy with the DBG-GPS

method. Future incorporation of EC codes to help identify and exclude noise

*k*-mers prior to the greedy path search is expected to further improve the

decoding speed and accuracy, which is particularly important in the extreme

case of high error rate.

# Methods

**Library design, PCR and Sequencing**

A DNA library of 12,000 oligonucleotides in length of 200 nt was synthesized

by Twist Biosciences. Error-prone PCR was performed with Controlled

Error-prone PCR Kit, TIANDZ, CAT#:160903-100. Thermo cycle parameters

were 94°C for 3 mins, 94°C for 1min, 45°C for 1min, 72°C for 1min, 30 cycles.

Six serial error-prone PCR were performed to introduce high rates of errors.

The first round ePCR utilized 0.6 μl samples of the master pool as templates.

The five following ePCR use 1 μl products of the previous round ePCR as

templates. All PCR experiments were performed with the following primers: P1

5'-CCTGCAGAGTAGCATGTC-3', P2 5'-CGGATGCATCAGTGTCAG-3'. The

PCR products were sequenced by Tianjin Novogene Sequencing Center &

Clinical Lab. Sequencing libraries were generated with purified PCR products

using Illumina TruSeq DNA PCR-Free Library Preparation Kit (Illumina, USA)

following manufacturer's recommendations and index codes were added. For

the products of the second-round error-prone PCR with very large DNA

strands, DNase digestion is applied to break the long strands into small

fragments around 200~300 bp. After digestion, all fragments are collected for

further library construction using the protocol as just described. The library

quality was assessed on the Qubit@ 2.0 Fluorometer (Thermo Scientific) and

Agilent Bioanalyzer 2100 system. All the libraries were sequenced on Illumina

HiSeq platform and 150 bp paired-end reads were generated. For preparation

of the 100 PCR samples for parallel retrievals, we first performed one round of

PCR amplification with Taq DNA polymerase with a total volume of 100 μl.

Then, 100 parallel PCR amplification was performed using 1 μl of the first

round PCR reaction mixtures without purification. The purification step is

removed in purpose of enhancing unspecific amplification. The 100 PCR

samples were then sequenced by Illumina sequencing platform. All the Taq

DNA Polymerase based PCR amplifications, except the error-prone PCRs,

used Vazyme 2X Rapid Taq Master Mix (CAT#: P222-03).

***k*-mers counting and elimination of low coverage *k*-mers**

The python implementation provided in this study used a simple hash

dictionary structure for counting of k-mers, which is not memory efficient. Thus,

although the scripts implemented with functions to read the common

nucleotide sequence files, *i.e.* FastQ or FastA, and count the *k*-mers

accordingly, for large data sets, we strongly suggest to use a professional

*k*-mer counting system, *e.g.* Jellyfish[21], which is much more memory efficient

and supports multi-cores. To count *k*-mers by the python scripts, please call

the following functions of DeBruijnGraph() object: for reading and counting of

FastQ file, use DeBruijnGraph-openFastQ('file name'); for reading and

counting of Fasta file, use DeBruijnGraph-openFasta('file name').

For elimination of low coverage *k*-mers, call function DeBruijnGraph-

remove_low_cov_kmers(*n*), then all *k*-mers with coverages lower than *n* will be

removed. For usage of Jellyfish for counting of *k*-mers and dumping of *k*-mers

satisfying the criteria, please refer to the Jellyfish manual, which is available at

(http://www.cbcb.umd.edu/software/jellyfish/). The dumped *k*-mers can be

introduced to the DeBruijnGraph() object using DeBruijnGraph-openDump('file

name') function for further decoding test.

**Setting of *k*-mer size**

Obviously, with a specific *k*-mer size, the data scale can be decoded is limited.

For example, it is clear that only small amount of data can be decoded with an

extremely short *k*-mer size of three. However, the mathematical answer to this

question is yet unsolved. In de Bruijn Graph theory, for each *k*-mer, the front

*k*-1 bases were used for positioning (*i.e.* indexing), and the one base at the

terminal was used for extension of path, *i.e.* for encoding of data. Thus, we

estimate the decoding capacity ($p$) of *k*-mers with a specific size of $k$ as

follows:

$$p = 4^{k-1} \times 2\,bits$$

Where $4^{k-1}$ is the combination number of possible indexes with a length of

$k - 1$, 2 bits stands for the encoding capacity of one base at the tail. Based on

this formula, the decoding capacities of different *k*-mer sizes were calculated

and listed in **Tab. S3**. As shown in the table, the decoding capacity is estimated

to be around 57.6 PB with a *k*-mer size of 30, and $6 \times 10^5$ EB for a *k*-mer size of

40, indicating a capable method for large-scale data decoding. Additionally, it

should be noticed that, due to the repeated presentations of identical *k*-mers in

different DNA strands, the actual data scale can be higher than this estimation

theoretically.

**Details of greedy path search**

The greedy search process was illustrated in **Fig. S4**. The details are

described as follows: ***Step 1,*** Select an index, *e.g.* 562451, and calculate the

anchor value by the Python pseudorandom function using the index value as

seed in case of both-way search mode. An anchor value of 47736 is obtained

in the case of 562451. ***Step 2,*** Encode the index into DNA string based on the

corresponding binary string, *i.e.* 562451 = 10001001010100010011=

ATATATGGGATCAGAA. Similarly, the anchor of 47736 is encoded into DNA

string of ATATATATGCGTTTGG in case of both way search. The greedy path

search starts with ATATATGGGATCAGAA as an initial path. Similarly, the tail

search start with ATATATATGCGTTTGG as an initial path in the case of

both-way search. ***Step 3.*** Judgement step. This step is for the selection of an

end with few path numbers for extension of paths. ***Step 4,*** Extension of paths

on the end with fewer path numbers. ***Step 5,*** Judgment step. This step is to

judge if the path search has finished. **Step 6***,* This step is specifically required

for both-way search mode. The head paths are fused with tail paths if the

overlap sequences are identical. For one-way search, this step is not required.

**Step 7***,* Encode the complete paths into binary strings. Perform parity checks

and drop the wrong routes using the embedded CRC codes. For other EC

codes applied, use the checking mechanism correspondingly. **Step 8***,*

Judgement step. Check if there is only one path passed the CRC checking. If it

is true, choose it as decoded strands, otherwise, mark a missing strand for this

index. If multiple routes or no routes pass the CRC codes, the

searching-based decoding fails. Only in the case of one route passed the CRC

checking, the decoding succeeds. **Step 9***,* Judgement step. Judge if the

search is finished. If not, iterate *step 1* to *step 9* until all indexes are searched

for possible strands. If yes, finish the inner decoding process. This algorithm is

implemented in the deBruijnGraph.py object by Python. The deBruijnGraph()

object was implemented to search in both-way mode by default. Switch the

value of DeBruijnGraph() ->dual_search to 'False' to active the one-way

search mode.

**Error analysis in the concept of de Bruijn graph theory**

Although distribution profiles of error rate and copy number among different

strands shape the DNA data quality, they cannot reflect the data quality

straightforwardly. Additionally, the sequence error rate is complicated for

accurate accounting. For better estimation of the qualities of DNA data and

simplification of the error analysis process in the concept of de Bruijn graph

theory, here we introduce two indicators, *i.e.* $K_d$ (in range of 0 to 1) and $K_n$

(in range of one to $4^k$), which together can well define the data quality. The $K_d$

stands for dropout rate of all correct *k*-mers and $K_n$ is the ratio of noise *k*-mers

and correct *k*-mers. DNA data with a $K_d$ close to 1 and a $K_n$ close to 0 stands

for high-quality data with a high data coverage rate and low noises. Other than

error rate which is complicated for accounting, $K_d$ and $K_n$ can be easily

calculated by the following formulas:

$$K_d = K_{lost}/K_{ori} \qquad\qquad 1$$

$$K_n = K_{all}/K_{corr} \qquad\qquad 2$$

In formula 1, $K_{ori}$ stands for the number of *k*-mers in the original encoded

sequences and $K_{lost}$ stands for the number of *k*-mers that presented in the

original encoded sequences but not presented in the sequencing results. In

formula 2, $K_{all}$ stands for the number of *k*-mers in the sequencing results and

$K_{corr}$ stands for the number of correct *k*-mers, *i.e.* *k*-mers that presented in the

original encoded sequences. DNA data with a $K_d$ close to 1 and a $K_n$ close

to 0 stands for a high-quality data with high data integrity and low noises. The

maximal strand decoding rate $S_m$ is determined by $K_d$. With specific $K_d$, the

actual strand decoding rate $S_r$ is affected by the value of $K_n$. The greedy path

search becomes extremely slow when decoding DNA data with higher $K_n$

values, due to too many possible paths for each strand. The DBG-GPS will

stop decoding if the path number exceeds a specific threshold. In this

proof-of-concept study, we use 100 for fast decoding, 1,000 for high-quality

decoding.

**The fountain codes**

The outer fountain codes used in this study is modified from
https://github.com/dbieber/fountaincode. DNAFountain and DNADroplet
objects were implemented for the handling of DNA strings. The assignment
mechanism of the random degrees and chunk indexes of the Droplet object
was modified to support DBG-GPS based decoding. Luby transform is applied
for the generation of random degrees. Specific index encoded in the DNA
Droplet is used for the selection of a degree from a pre-generated degree table.
This index is also used as seed for the generation of the random strand
combinations. The decoding process of the original Glass object has been
modified to improve its performance.

**Details of the simulation experiments**

Simulations for investigation of the potentials of de Bruijn graph were
performed with 10,000 DNA strands generated by the fountain codes with a
strand length of 320 bp. For de Bruijn graph construction, a *k*-mer size of 21
was applied. The simulation studies on the both-way search strategy are
performed with 10,000 DNA droplets. 100 sequence copies with random base
errors in rates of 10%. For the large-scale simulations, an Ubuntu Server 20.10
live install disk image (Link provided in **Supplementary materials**) was used
as input file for the generation of random DNA droplets. Each DNA droplet was
set to encode 60 bytes of data and two bytes of CRC codes. The length of
index and anchor are both set to four bytes. Primers of P1
5'-CCTGCAGAGTAGCATGTC-3' and P2 5'-CGGATGCATCAGTGTCAG-3'
were added to the ends. This will result with a DNA droplet in length of 300 bp,

around the theoretical limits of current DNA synthesis technologies. To avoid

entangled DNA strands, a filter process that always discards the DNA droplets

contains a *k-1* mer that already presents more than four times was applied to

the droplet generating stage. For counting of *k*-mers by Jellyfish 2.3, a *k*-mer

size of 24, and *k*-mer coverage cut-off of 5.

**Data Availability**

All data files and raw sequencing data that support the findings of this study

have been deposited in public cloud server. The links are provided in

supplementary materials.

**Code availability**

All the original algorithms proposed in this study were implemented with

Python and the source codes are available at

https://switch-codes.coding.net/public/switch-codes/DNA-De-Bruijn-Decoding/

git/files.

# Acknowledgements

This work was supported by National Natural Science Foundation of China

under the grants 21621004 to Y.Y. ，Seed Foundation of Tianjin University to L.

S. and Natural Science Foundation of Shandong Province under the grants

ZR2017LC006 to F.G.. The authors would like to thank Dr. Yan Zhang for his

great efforts and constructive comments which have helped to improve this

manuscript significantly. The authors also would like to thank Dr. Sheng Ye, Dr.

Hao Qi and Dr. Weigang Chen for very helpful suggestions.

**Competing interests**

564 Li-Fu Song, Ying-Jin Yuan and Feng Geng have filed a patent covering the
565 encoding structure and the de Bruijn graph based decoding process (CN
566 110190858 A).

**Author contributions**

568 LFS and Y.Y. conceived the study. LFS proposed the idea, wrote the Python
569 codes, designed the experiments, performed the simulations, and analyzed
570 the data. FG helped with experiment design and data analysis. ZYG performed
571 the error-prone PCR experiments. BZL and YJY edited the manuscript and
572 supervised the whole work.

# References

1. van der Valk, T. *et al.* Million-year-old DNA sheds light on the genomic
history of mammoths. *Nature* **591,** 265–269; 10.1038/s41586-021-03224-9
(2021).

2. Anavy, L., Vaknin, I., Atar, O., Amit, R. & Yakhini, Z. Data storage in DNA
with fewer synthesis cycles using composite DNA letters. *Nature*
*biotechnology*; 10.1038/s41587-019-0240-x (2019).

3. Koch, J. *et al.* A DNA-of-things storage architecture to create materials with

embedded memory. *Nature biotechnology* **38,** 39–43;

10.1038/s41587-019-0356-z (2020).

4.  Zhirnov, V., Zadegan, R. M., Sandhu, G. S., Church, G. M. & Hughes, W. L.

Nucleic acid memory. *Nature materials* **15,** 366–370; 10.1038/nmat4594

(2016).

5.  Church, G. M., Gao, Y. & Kosuri, S. Next-generation digital information

storage in DNA. *Science (New York, N.Y.)* **337,** 1628;

10.1126/science.1226355 (2012).

6.  Ceze, L., Nivala, J. & Strauss, K. Molecular digital data storage using DNA.

*Nature reviews. Genetics* **20,** 456–466; 10.1038/s41576-019-0125-3

(2019).

7.  Ping, Z. *et al.* Carbon-based archiving: current progress and future

prospects of DNA-based data storage. *GigaScience* **8**;

10.1093/gigascience/giz075 (2019).

8.  Chen, W. *et al.* An artificial chromosome for data storage. *National Science*

*Review*; 10.1093/nsr/nwab028 (2021).

9.  Tabatabaei, S. K. *et al.* DNA punch cards for storing data on native DNA

sequences via enzymatic nicking. *Nature communications* **11,** 1742;

10.1038/s41467-020-15588-z (2020).

10.Grass, R. N., Heckel, R., Puddu, M., Paunescu, D. & Stark, W. J. Robust

chemical preservation of digital information on DNA in silica with

error-correcting codes. *Angewandte Chemie (International ed. in English)*

**54,** 2552–2555; 10.1002/anie.201411378 (2015).

11. Erlich, Y. & Zielinski, D. DNA Fountain enables a robust and efficient

storage architecture. *Science (New York, N.Y.)* **355,** 950–954;

10.1126/science.aaj2038 (2017).

12. Organick, L. *et al.* Random access in large-scale DNA data storage. *Nature*

*biotechnology* **36,** 242–248; 10.1038/nbt.4079 (2018).

13. Gao, Y. *et al. Low-Bias Amplification for Robust DNA Data Readout* (2020).

14. Press, W. H., Hawkins, J. A., Jones, S. K., Schaub, J. M. & Finkelstein, I. J.

HEDGES error-correcting code for DNA storage corrects indels and allows

sequence constraints. *Proceedings of the National Academy of Sciences of*

*the United States of America* **117,** 18489–18496;

10.1073/pnas.2004821117 (2020).

15. Heckel, R., Mikutis, G. & Grass, R. N. A Characterization of the DNA Data

Storage Channel. *Scientific reports* **9,** 9663; 10.1038/s41598-019-45832-6

(2019).

16. Edgar, R. C. MUSCLE: multiple sequence alignment with high accuracy

and high throughput. *Nucleic acids research* **32,** 1792–1797;

10.1093/nar/gkh340 (2004).

17. Antkowiak, P. L. *et al.* Low cost DNA data storage using photolithographic

synthesis and advanced information reconstruction and error correction.

*Nature communications* **11,** 5345; 10.1038/s41467-020-19148-3 (2020).

18.Chen, W. D. *et al.* Combining Data Longevity with High Storage

Capacity—Layer□by□Layer DNA Encapsulated in Magnetic Nanoparticles.

*Adv. Funct. Mater.* **29,** 1901672; 10.1002/adfm.201901672 (2019).

19.Kohll, A. X. *et al.* Stabilizing synthetic DNA for long-term data storage with

earth alkaline salts. *Chemical communications (Cambridge, England)* **56,**

3613–3616; 10.1039/d0cc00222d (2020).

20.Chen, Y.-J. *et al.* Quantifying molecular bias in DNA data storage. *Nature*

*communications* **11,** 3264; 10.1038/s41467-020-16958-3 (2020).

21.Marçais, G. & Kingsford, C. A fast, lock-free approach for efficient parallel

counting of occurrences of k-mers. *Bioinformatics (Oxford, England)* **27,**

764–770; 10.1093/bioinformatics/btr011 (2011).

22.Pandey, P., Bender, M. A., Johnson, R., Patro, R. & Berger, B. Squeakr: an

exact and approximate k-mer counting system. *Bioinformatics (Oxford,*

*England)* **34,** 568–575; 10.1093/bioinformatics/btx636 (2018).

23.Cyrus Rashtchian *et al.* Clustering Billions of Reads for DNA Data Storage.

**Fig. 1 | The potentials of de Bruijn graph-based decoding. a,**
Representations of base substitutions and indels in de Bruijn graph. *i,* Simple
de Bruijn graph constructed from four copies of "AACGGCGGCTGT" with a
*k*-mer size of four. The circles stand for the *k*-mers and the numbers inside the
circles are coverages of corresponding *k*-mers in all graphs. *ii,* De Bruijn graph
as consequence of one substitution occurring in sequence #2; *iii,* De Bruijn
graph as consequence of one base insertion on sequence #2 and one base
deletion on sequence #3; *iv,* De Bruijn graph involves four strand breaks. **b,**
Estimated maximal strand decoding rates ($S_m$) of different types and rates of
errors with 20 sequence copies; For clarity, the standard derivations are
detailed in **Tab. S1**. **c,** $S_m$ values estimated with different sequence copies and
rates of mixture errors (50% substitutions, 25% insertions and 25% deletions).

**Fig. 2 | Proposed four-step framework of DBG-GPS and its integration with outer erasure codes. a,** Proposed four-step
framework of DBG-GPS. **b,** Proposed structure of DNA strands for DBG-GPS. There are four major parts including: A1 – The
index/seed of the DNA strand; A2 – Data payload for encoding of data; A3 – Cyclic Redundancy Check codes (CRC) for selection of
the correct path; A4 – Anchor cods which can be calculated by specific function based on the value of A1. A4, Anchor codes
(optional) for both-way search; **c,** Integration of DBG-GPS with outer erasure codes. DBG-GPS is a full resolution for inner code
decoding.

**Fig. 3 | Experimental verification of the robustness of DBG-GPS**. **a**, A
314kb file is wrote on DNAs to generate a "Master Pool". **b,** Serial deep
error-prone PCR to introduce base errors. **c**, Multiple data retrievals with
intended unspecific amplifications to introduce strand rearrangements. **d**,
Accelerated aging experiments to introduce strand breaks.

**Fig. 4 | Reliable data recovery with deep error-prone PCR products. a,**
Agarose electrophoresis analysis of the serial error-prone PCR (ePCR)
products. **b**, Reliable strand reconstruction with low quality ePCR products.
The dashed red line stands for the decoding lower boundary of the outer
fountain codes in this case study. **c**, Low coverage decoding by random
sub-sampling. Sequencing reads of ePCR#1 and ePCR#2 are used for
random sub-sampling individually. For each coverage tested, 12 independent
sub-sampling simulations were performed and the averages values were
presented. The standard deviations are presented in **Tab. S5** for clarity.
Coverages in range of 1 to 256 were considered. The average strand recovery
rates ($S_r$), $k$-mer dropout rates ($K_d$) and $K_n$ values were presented. The dashed
curves are the strand recovery results without elimination of low coverage
$k$-mers. The horizontal dashed red line stands for the decoding limits by the
outer Fountain codes.

**Fig. 5 | Multiple retrieval and accelerated aging tests. a,** Agarose
electrophoresis analysis of the parallel PCR products for multiple data
retrievals. Twenty representatives out of 100 samples are shown. M stands for
the DNA Marker. **b**, Strand decoding results of the 100 multiple retrievals with
DBG-GPS. **c**, Strand decoding rates by DBG-GPS from accelerated aged DNA
samples.

**Tab. 1 | Comparison of the DBG-GPS and CL-MA based methods in**

**decoding speed.**

| DBG-GPS | | CL-MA | |
|---|---|---|---|
| **Stages** | **Time (s)** | **Stages** | **Time (s)** |
| ***k*-mer counting** *(Jellyfish 32 threats)* | 0.63 ± 0.04 | **Clustering**[23] *(32 threats)* | 0.36 |
| **Strand decoding** *(Python Script)* | 36.84 ± 0.91 | **Multi-alignment** *(Muscle[16], IO time subtracted)* | 3874.48 ± 30.82 |
| | | **Consensus calling** *(Majority voting[13])* | 15.42 ± 0.40 |
| **Total** | 37.47 ± 0.95 | **Total** | 3890.26 ± 31.22 |

## Supplementary materials

**Fig. S1 | A two-dimensional coding strategy of traditional EC codes handles the base shift problem of indel inefficiently.**

**Fig. S2 | Path search complexity caused by base errors can be remarkably released by elimination of low coverage $k$-mers.**

**Fig. S3 | A both-way search strategy reduces decoding time.**

**Fig. S4 | Details of DBG-GPS algorithm.**

**Fig. S5 | Linear decoding complexity of DBG-GPS.**

**Fig. S6 | Agilent 2100 analysis of the accelerated aged samples.**

**Tab. S1 | Computational estimation of the maximal strand decoding rates ($S_m$) of different types and rates of errors with 20 strand copies.**

**Tab. S2 | Strand decoding performance of four-step DBG-GPS algorithms estimated by Monte Carlo simulations.**

**Tab. S3 | Theoretical decoding capacities of DBG-GPS with different $k$-mers sizes.**

**Tab. S4 | Details of strand recovery results of deep ePCR experiments.**

**Tab. S5 | Details of the sub-sampling simulation results with ePCR#1 and ePCR#2.**