Super-robust data storage in DNA by de Bruijn graph-based decoding

Lifu Song[1,2], Feng Geng[3], Ziyi Gong[1,2], Bingzhi Li[1,2*], Yingjin Yuan[1,2*]

[1] Frontier Science Center for Synthetic Biology and Key Laboratory of Systems Bioengineering (Ministry of Education), Tianjin University, Tianjin 300072, PR China

[2] SynBio Research Platform, Collaborative Innovation Center of Chemical Science and Engineering, School of Chemical Engineering and Technology, Tianjin University, Tianjin 300072, PR China

[3] College of Pharmacy, Binzhou Medical University, Yantai 264003, PR China

*Corresponding authors: bzli@tju.edu.cn,yjyuan@tju.edu.cn

Abstract

High density and long-term features make DNA data storage a potential media. However, DNA data channel is a unique channel with unavoidable 'data reputations' in the forms of multiple error-rich strand copies. This multi-copy feature cannot be well harnessed by available codec systems optimized for single-copy media. Furthermore, lacking an effective mechanism to handle base shift issues, these systems perform poorly with indels. Here, we report the efficient reconstruction of DNA strands from multiple error-rich sequences directly, utilizing a De Bruijn Graph-based Greedy Path Search (DBG-GPS) algorithm. DBG-GPS can take advantage of the multi-copy feature for efficient

correction of indels as well as substitutions. As high as 10% of errors can be

accurately corrected with a high coding rate of 96.8%. Accurate data recovery

with low quality, deep error-prone PCR products proved the high robustness of

DBG-GPS (314Kb, 12K oligos). Furthermore, DBG-GPS shows 50 times faster

than the clustering and multiple alignment-based methods reported. The

revealed linear decoding complexity makes DBG-GPS a suitable solution for

large-scale data storage. DBG-GPS's capacity with large data was verified by

large-scale simulations (300 MB). A Python implementation of DBG-GPS is

available   at

https://switch-codes.coding.net/public/switch-codes/DNA-Fountain-De-Bruijn-

Decoding/git/files.

Keywords

34 DNA data storage, de Bruijn graph, Indel correction, Erasure codes,

35 Reed-Solomon, Fountain codes

Introduction

With properties of high density, low maintain cost, and long persistent period,

DNA as storage media is a potential candidate for solving the world crisis of

data explosion[1–4]. However, massive and complex errors that emerged make

reliable data retrieval a challenge. Previous studies have shown that the

implementation of a reliable codec system for DNA data storage requires two

layers of error correction (EC) codes. The outer codes handle the strand

dropouts and the inner codes correct the base errors within DNA strands[5–7].

Strand dropouts are erasures based on the definition of information theory,

which can be well solved by the sophisticated erasure codes, *e.g.* Fountain,

Reed-Solomon (RS) codes[5–7]. However, to the best of our knowledge, an

effective inner code, which can well handle all three types of base errors, *i.e.*

substitutions, insertions and deletions (indels), is still missing. The key

obstacle is the difficulty in handling the indels. Although the field of information

theory has developed elegant EC codes, they are not optimal for indels with

base shift problem. Base deletions have been treated as erasures in previous

studies[5–7]. However, other than unreadable bases, *i.e.* erasures, base

deletions also cause shift forwards of downstream nucleotide bases. This base

shift issue, which exists in base insertions as well, causes serious problems for

traditional erasure codes as illustrated in **Fig. S1**. Despite indels can be

detected by traditional erasure codes, the exact positions of the lost or odd

bases cannot be inferred. The successful data decoding in previous studies

using RS erasure codes as inner codes owing to a two-dimensional coding

strategy, accurate DNA synthesis and sequencing technologies[5,7]. However,

this mechanism is low efficient in handling the indels. As illustrated in **Fig. S1**,

a single indel in the row dimension (DNA strand) will lead to a series of

'substitution' errors in the column dimension. Thus, this strategy only works

when the error rate is very low. When slightly more indels are introduced, the

overwhelming 'substitutions' induced will quickly exhaust the column EC

codes.

DNA data storage achieves data manipulations by processes of DNA synthesis,

PCR, and sequencing. These processes always generate multiple copies of

DNA strands fast and cheaply. This unique 'multiple copy' feature, also termed

as "natural redundancy" in the previous studies, or 'data repetition' by definition

of information theory[8], makes DNA data storage a unique channel[8,9]. In the

view of traditional information theory, 'data repetition' is a low efficient way to

enhance the robustness of data. This deep-rooted idea is based on the fact

that additional copies are time- and cost-expensive for traditional media and

communication systems. However, as just mentioned, additional copies are

cheap, fast, and basically unavoidable for DNA data storage. Indeed, it may

increase the cost significantly to make a single copy DNA data. Efforts on

reducing the "multiple copy" feature by serial dilutions show that massive

strand dropouts are observed when reducing the average copy number blow

ten, making reliable data retrieval impractical[10]. Additionally, single DNA

molecules, as highly degradable polymers, break easily. Thus, even single

copy DNA data is obtained, the data stability is still questionable since strand

breaks, which cannot be handle by any reported codes, are fatal to DNA data

integrity. Recently, *Press et. al.* implemented a hash encoded, decoded by

greedy exhaustive search (HEDGES) codes which can correct indels with a

single copy of DNA recently[11]. Despite HEDEGES shows outstanding technical

achievements, the coding rate of HEDGES drops below 0.6 for correction of 3%

errors. This would increase the cost of DNA data storage by 66.7%

theoretically. To make use of the "multiple copy" feature, previous studies

applied the algorithms of clustering and multi-alignment[7,12]. However, such

strategy is not efficient and cannot scale up well. A new algorithm that can

efficiently decode DNA strands from multiple error-rich strand copies is highly

desirable.

Here, we describe the fast and accurate reconstruction of DNA strands from

multiple error-rich sequences directly, utilizing a de Bruijn Graph-based

Greedy Path Searching (DBG-GPS) algorithm. In combination with simple

Cyclic Redundancy Check (CRC) codes for path selection, DBG-GPS can take

advantage of the multi-copy feature for high-efficient correction of indels as

well as substitutions. While correction of multiple indels with single copy data is

still a big challenge[13,14], As high as 10% of errors can be corrected in high

coding rate (0.95) by DBG-GPS with merely sixty strand copies. More errors

still can be corrected by the incorporation of additional sequence copies.

Furthermore, DBG-GPS shows outstanding linear decoding complexity, which

is essential for large-scale DNA data storage. DBG-GPS shows much faster

decoding speed than the clustering and multiple alignment-based methods

reported. We verified the robustness of DBG-GPS by both deep error-prone

PCR experiments and large-scale *in silicon* simulations.

Results

Principles and potentials of de Bruijn graph-based decoding
with multiple error-rich sequences

Decoding of DNA data is a process of re-assembling the original data from

small pieces of information carried by massive short DNA fragments, which is

quite similar to the process of genome assembly. However, the accuracy

demand of data storage is much higher than genome assembly. Although it is

not possible to obtain accurate genome sequences by simple assembly

process, it is acceptable for genome sequencing applications since following

up gap-filling experiments can be performed[15]. Obviously, gap-filling is not an

acceptable option for data storage application. Fortunately, the extra options of

indexes for sorting of fragmented information and redundancy codes for error

correction bring opportunities to achieve this challenging goal. De Bruijn graph

theory, which is an efficient way to represent a sequence in terms of its k-mer

components, has been successfully applied to genome assembly with

second-generation sequencing data[15,16]. To reveal the potentials of de Bruijn

graph theory in DNA data storage, we first analyzed the representations of

substitution and indel errors in a de Bruijn graph as illustrated in **Fig. 1**. As

shown in Fig. 1**A-I**, a simple de Bruijn graph on the right was derived from the

four copies of "AACGGCGGCTGT" in the left with a *k*-mer size setting of four.

The DNA sequence of "AACGGCGGCTGT" can be represented by the path of

"*a→b→c→d→e→c→f→g→h*" in the graph. A base substitution error of "G" to

"A" in sequence 2 will lead to a branch path, as shown in red color, in de Bruijn

graph and the weights (coverages) of the correct path was reduced (**Fig. 1A-II**).

In the case of base indels, which are quite different from base substitutions in

the view of traditional information theory, the representations of base indels in

de Bruijn graph are similar to base substitutions: both creating interfering

path(s) and reducing the weight of the correct path (**Fig. 1A-III** and Fig. 1**A-IV**).

A greedy path search algorithm and a path selection mechanism, which in

combination can accurately find the correct path, could recover the DNA strand

theoretically. In this case, the base errors are transformed into a path search

and selection problem by de Bruijn graph theory with multiple sequence copies.

With this mechanism, as long as the correct path, *i.e.* "*a→b→c→d→e→c→f→*

g→h" in **Fig. 1**, is preserved, the corresponding DNA strand can be decoded

theoretically.

Clearly, the sequence error rates and copy number determine the robustness

of de Bruijn graph path. To further test the path robustness with variant rates

and types of random errors, as well as sequence copies, which indicates the

potentials of de Bruijn graph theory-based decoding, we utilized a Poisson

model to generate DNA sequences with different rates and types of random

errors. Variant numbers of the generated sequences with specific rates and

types of error were then committed for de Bruijn graph construction. The

integrality of the correct path was then tested by checking the existence of all

k-mers belong to this path in the constructed graph. To investigate the

effluences of different types of errors to the path integrity, we firstly run the

simulations with specific type of errors solely. With specific error rate and

sequence copy, different DNA strands with a total number of 10,000 was

applied for error-rich sequences generation and path integrity analysis. This

process was iterated for 3 times independently. The average frequency that

the paths maintain their integrality was defined as 'maximal strand decoding

rate' (S_m). S_m value is the theoretical maximal decoding rate which can be

achieved by an actual decoding implementation. Although it has been reported

that indels are much more challenging to handle compared with substitutions,

no significant differences of S_m values could be observed between the different

types of errors. Indeed, the simulated S_m values of substitutions is slightly

lower than that of indels, as shown by the case with an error rate of 0.1 and

sequence copies of 50 (**Fig. 1B**). In real situation, the emerged errors are

mixtures of three types of errors. We then perform series simulations with an

error type ratio of 50% substitutions, 25% insertions and 25% deletions. Total

error rates in range of 1% to 10% with a step length of 0.5%, and sequence

copy numbers in range of 5 to 100 with a step length of 5 were considered. As

shown in **Fig. 1**, S_m >0.99 can be obtained with merely 60 sequence copies

(red dashed line) with an arbitrary error rate below 10%, well proved the great

potentials of the de Bruijn graph theory in DNA data.

171 **Development of a general framework for de Bruijn**

172 **graph-based decoding with multiple error-rich sequences**

173 Based on the analysis of previous section, for decoding of DNA strands from

174 multiple error-rich sequence copies utilizing de Bruijn graph theory, two major

175 steps are required: 1) greedy path search for possible path candidates and 2)

176 selection of the correct path. In this section, we describe the issues emerged

177 during implementation of "DBG-GPS" and strategies to solve them. A four-step

178 framework is then proposed for effective strand reconstruction practice with de

179 Bruijn graph theory. Eventually, the DBG-GPS algorithm was implemented

180 following this framework using Python programming language.

181 **Elimination of low coverage *k*-mers remarkably reduce the greedy path**

182 **search complexity**

183 A serious problem emerged is the explosion of de Bruijn graph size caused by

184 errors. About forty times enlargement of the de Bruijn graph size was observed

185 when 4% random errors were introduced into 10,000 DNA strands with 100

186 copies each (**Fig. S 2**). Greedy path search with this enlarged de Bruijn graph

187 resulted with overwhelming number of possible paths, leading to unbearably

188 long path search time. The enlarged de Bruijn graph contains massive noisy

189 *k*-mers, i.e. *k*-mers introduced by base errors. To quantify the noisy *k*-mers, we

190 introduce an indicator K_n, which is the ratio of noisy *k*-mers and correct *k*-mers

191 in the de Bruijn graph. Clearly, more errors and strand copies will introduce

192 more noisy *k*-mers to the de Bruijn graph. Monte carlo simulations show quick

193 increase of K_n by increasing either the error rate or the sequence copies (**Fig.**

194 **2**A). The number of branch paths and decoding time increased exponentially

195 by increasing the error rates (**Fig. 2B-*i***) or the strand copies (**Fig. 2B-*ii***). Thus,

a pre-processing step which can remove the noisy k-mers is highly desirable.

Although DNA data operations can introduce massive errors to DNA data,

these errors are low probability events individually. Thus, the coverages, *i.e.*

the occurrences of noisy k-mers, should be significantly lower than the correct

ones. In other words, the low coverage k-mers are more likely to be noisy

k-mers. Preliminary testing with elimination of k-mers with a coverage cut-off of

one significantly reduced the decoding burden of branch paths with no

significant affections to the correct path integrity (**Fig. 2B-*iii*** and ***iv***). To further

investigate the feasibility of coverage as an indicator for distinguishing noisy

k-mers, we used a Poisson distribution model to simulate the copy number

distribution of DNA strands. The coverage distribution of noisy k-mers and

correct k-mers are then investigated based on Monte Carlo simulation. The

simulation is performed with 10,000 DNA strands, a λ value (*i.e.* the

expectation value) of fifty for strand copies and an error rate of 4% (a common

level of error rates reported in previous studies**)**. As shown in **Fig. S3**, vast

majority of the noisy k-mers show coverages lower than ten, while the correct

ones show coverages around fifty. Thus, a coverage cut-off of ten can

effectively remove most of the noisy k-mers (**Fig. S3**), suggesting an effective

mechanism for elimination of noisy k-mers.

Cyclic redundancy check (CRC) codes can effectively recognize the

correct path

Although elimination of low coverage k-mers can effectively remove most of

the branch paths based on Monte Carlo simulation, a small fraction branch

paths are conserved. For example, due to exponential replication feature of

DNA data storage, errors emerged in early stage can be enriched massively

which cannot be removed by low coverage cut-off. Thus, a mechanism to

recognize the correct path and verify its integrality is required. Kinds of

traditional EC codes can achieve this goal theoretically, *e.g.* CRC codes, RS

codes, or hash functions. Although hash functions are ideal for such kind of

tasks in principle, we failed to find a proper hash function that can generate

short key words with merely few bytes. Since erasure is not presented in the

path selection process, RS codes, which is capable of handling erasures, is

not an optimal solution hence. Here, we choose CRC codes which is powerful

in error detection, but do not have a built-in error-correction capability.

Intensive Monte Carlo experiments show that CRC codes can recognize the

correct path in all one million times of independent simulations, proving its

effectiveness on selection of correct paths, *i.e.* correct strands.

A both-way search strategy increases decoding speed

Although elimination of noisy *k*-mers based on coverage can reduce the

greedy path search complexity remarkably, significant amount of remained

noisy *k*-mers cannot be removed, especially when error rates are high. To

further reduce the greedy path search time, we proposed a both-way search

strategy which can search for possible paths simultaneously on both ends of

DNA strands. To enable this both-way search strategy, we designed a DNA

strand structure with an additional 'anchor' element as shown in **Fig. 3C (A4)**.

The anchor is an integer generated from the index by a hash-like function. This

function generates one specific number with a given index. For

proof-of-concept, the pseudorandom function of Python is used for generation

of the anchors using the indexes as seeds. Due to the feature of

pseudorandom function, it always gets a same anchor value when supply with

the same seed. Thus, the greedy path search engineer can calculate the

anchor based on the index without additional information, enabling the

both-way search strategy. Simulation shows that this both-way search strategy

can reduce the decoding time significantly, especially when sequence error

rates are high. As shown in **Fig. S4**. With an error rate of 10% and copy

number of 100, the both-way search strategy shows about 60% reduction in

decoding time compared with one-way search. No significant difference in

decoding accuracy is observed with the two search strategies.

Four-step framework for effective strand decoding practice with

DBG-GPS algorithm

For effective strand reconstruction with DBG-GPS, we suggested a four-step

framework as illustrated in **Fig. 3A** and detailed as follows: ***Step 1***,

construction of de Bruijn Graph. Here, the 'construction of de Bruijn Graph'

refer to the process of 'counting of k-mers'. In current python implementation, a

simple hash dictionary data structure was applied. For further studies with

more advanced data structure of the de Bruijn Graph, we suggest to create the

advanced data structure after elimination of noisy k-mers (Step 2). ***Step 2***,

elimination of noise k-mers. In present study, we use coverage as an indicator

for elimination of noisy k-mers. Additional codes for identification of noisy

k-mers can also be introduced to make the elimination more efficient in future

studies. ***Step 3***, greedy path search. If the error rate is still high, a both-way

search strategy can be applied to reduce the decoding time. ***Step 4***, selection

of the correct path. The paths found are translated into bit strings and the

embed EC codes are then used for selection of the correct path. Only in case

of one path passes the EC code checking, this path will be selected and the

decoding of corresponding strand succeed.

Integration of DBG-GPS with outer erasure codes

DBG-GPS is designed as inner decoding mechanism for correction of errors within DNA strands. It can be easily combined with an erasure code, *e.g.* fountain codes or RS codes, for large-scale data storage. Integration of DBG-GPS with erasure codes is quite simple. Simply add CRC codes for strand integrity verification during strand encoding, and use the DBG-GPS as inner decoding process for decoding of DNA strands. To use other kinds of codes for strand verification with DBG-GPS, just replace the CRC codes with specific codes and switch to the corresponding checking method during strand selection. Since the encoding process is basically the same as previous studies, we only illustrated the overall decoding process using DBG-GPS as inner decoding method as shown in **Fig. 3B**. There are three major steps in the decoding process. *Step 1*. High-throughput sequencing. The DNA strands are sequenced by high-throughput sequencing technologies. *Step 2*. Inner code decoding. The aim of this step is to decode DNA strands as many as possible. DBG-GPS is a complete solution for Step 2. *Step 3*. Decode the original information by outer erasure codes. In previous studies, clustering and multiple-alignment processes, which are time and computation intensive, are utilized for strand reconstruction[7,12,17]. DBG-GPS can directly rebuild the strands from error-rich sequencing reads without clustering and multi-alignments. A python implementation using fountain codes as outer codes and DBG-GPS as inner codes is available at https://switch-codes.coding.net/public/switch-codes/DNA-Fountain-De-Bruijn-Decoding/git/files. Except the strand integrity verification codes, no additional codes are required by DBG-GPS. Most previous studies also employed redundancy codes for checking of strand integrity [6,7,12]. Thus, the DBG-GPS

decoding algorithm can be directly applied to these systems theoretically, *e.g.*

DNA fountain codes[6], RS-based storage system[7,12] *etc.* However, to check the

effectiveness of DBG-GPS on these systems, both the encoded strand

sequences and the sequencing reads are required. The only study we found

matches this criteria is the recent study by Antkowiak *et al.*[12]. Low-cost

photolithographic synthesis in combination with a RS codec system is used for

low cost data writing. However, they reported a serious problem of massive

strand dropouts due to the error-prone synthesis process of photolithographic

synthesis[12]. Interestingly, preliminary test using DBG-GPS's principles on the

sequencing results of Antkowiak *et al.*'s study revealed a high theoretical

strand recovery rate above 99%, a potential remarkable improvement

compared with the reported recovery rate of 83%.

Simplified error analysis in concept of de Bruijn graph theory

Although distribution profiles of error rate and copy number among different

strands shapes the DNA data quality, they cannot reflect the data quality

straightforwardly. Additionally, the sequence error rate is complicated for

accurate accounting. For better estimation of the qualities of DNA data and

simplification of the error analysis process in concept of de Bruijn graph theory,

here we introduce two indicators, *i.e.* K_d (in range of 0 to 1) and K_n (in range

of one to ∞), which together can well define the data quality. The K_d stands for

dropout rate of all correct *k*-mers and K_n is the ratio of noisy *k*-mers and

correct *k*-mers. DNA data with a K_d close to 1 and a K_n close to 0 stands for

a high-quality data with high data coverage rate and low noises. Other than

error rate which is complicated for accounting, K_d and K_n can be easily

calculated by the following formulas:

$$323 \qquad\qquad K_d = K_{lost}/K_{ori} \qquad\qquad 1$$

$$324 \qquad\qquad K_n = K_{all}/K_{corr} \qquad\qquad 2$$

In formula 1, K_{ori} stands for the number of *k*-mers in the original encoded

sequences and K_{lost} stands for the number of *k*-mers that presented in the

original encoded sequences but not presented in the sequencing results. In

formula 2, K_{all} stands for the number of *k*-mers in the sequencing results and

K_{corr} stands for the number of correct *k*-mers, *i.e. k*-mers that presented in the

original encoded sequences. DNA data with a K_d close to 1 and a K_n close

to 0 stands for a high-quality data with high data integrity and low noises. The

maximal strand decoding rate S_m is determined by K_d. With specific K_d, the

actual strand decoding rate S_r is affected by the value of K_n. The greedy path

search becomes extremely slow when decoding DNA data with higher K_n

values, due to too many possible paths for each strand. The DBG-GPS will

stop decoding if the path number exceed specific threshold. In this

proof-of-concept study, we use 100 for fast decoding, 1,000 for high-quality

decoding.

Decoding speed of DBG-GPS

DBG-GPS shows an excellent linear decoding complexity while increasing the

total strand scale from 1 to 10,000 (**Fig. S6**). To compare the decoding speed

of DBG-GPS with clustering and multiple alignment-based methods (CL-MA),

we produced 10,000 DNA droplets with DNA fountain codes using CRC codes

as redundancy codes for strand selection. For each DNA droplet, we

generated fifty sequence copies with 4% random errors introduced (2%

substitutions, 1% insertions and 1 deletions). The 500,000 error-rich reads

generated were then utilized for strand decoding by DBG-GPS and CL-MA

respectively. Since the clustering process is quite complicated in reported

studies, for the CL-MA-based decoding, we feed the program with grouped

reads indicating perfect clustering. For decoding speed comparison, a

clustering time was estimated based on the recent study by Cyrus *et al.*[17].

Since multiple alignment process was performed by a standalone program

(Muscle[18]), there will be 10000 times of IO (input and output) with the hard disk

system during strand decoding with CL-MA. To estimate the IO time, one

sequence of the DNA droplet was repetitively submitted to Muscle for multiple

alignment analysis for 10,000 times. This process is iterated for three times

and the average time is subtracted in the CL-MA based decoding analysis.

As shown in **Tab. 1**, although a Python implementation of DBG-GPS was used

in decoding test, DBG-GPS shows 53 times faster than the CL-MA based

methods without significant differences in decoding accuracy. A C++

implementation of DBG-GPS can further enhance its performance.

Experimental verification of the robustness of DBG-GPS

As shown in **Fig. 4**, to experimentally verify the robustness of DBG-GSP, a 314

KB compressed file derived from 6 different types of files (two documents, four

pictures, detailed in **Methods**), was encoded into 12,000 DNA strands in

length of 200 bp with an overall strand redundancy of 14.6% by the DNA

fountain codes implemented in this study. Each oligo encodes thirty bytes of

data, as well as three bytes of CRC codes, four bytes of index, and four bytes

of anchor. The designed DNA strands were synthesized by Twist Bioscience.

The single strand DNAs (ssDNA) obtained from Twist Bioscience were

dissolved in ddH$_2$O. About 1,000 copies of the dissolved ssDNA were used as

templates for PCR amplification. The PCR products are sequenced by Illumina

technology. The sequencing reads were used for decoding of the original

information by DBG-GPS.

In details, to better understand the robustness of DBG-GPS, we utilized both

accurate PCR and error-prone PCR to amplify the ssDNA library obtained from

Twist Bioscience. The accurate amplification of the ssDNA library was

performed with high fidelity KAPA HiFi DNA Polymerase with 22 thermo cycles.

Two series of error-prone PCR (ePCR) were performed with 30 thermo cycles

using an error-prone PCR kit from TIANDZ using the highest error-rate settings.

The second round ePCR use 1 µl products of the first round ePCR to introduce

more errors. Thus, we obtained three PCR samples, *i.e.* accurate PCR

(A-PCR), two series of ePCR (E-PCR-1st, E-PCR-2st). The three samples

were sequenced by an Illumina NovaSeq platform and 150 bp paired-end

reads were generated. This result with 6,164,085, 19,972,663, and 17,430,377

raw reads respectively. We first tried to recover the original information by

using all sequencing reads of each sample independently. The S_m values of

the three sequencing samples were estimated to be 99.33% (11950), 100%

(12000), and 99.98% (11998) respectively. With optimized parameters for

elimination of noisy k-mers, the DBG-GPS recovered 11,915 (99.29%), 11,978

(99.8%), and 11,928 (99.4%) strands for the three samples respectively.

Although detailed analysis shows the ePCR products do have more base

errors than the accurate PCR products, it is surprising that the two ePCR

samples show higher data quality than the accurate PCR samples regarding to

the strand decoding rates.

To better look into the data qualities and prove the robustness of DBG-GPS,

we perform random sub-sampling of all sequencing reads with different

coverages, *i.e.* reading copies, range from 1 to 256. The strand recovery rates,

K_d, and K_n in different coverages were calculated corresponding. For each

coverage tested, three independent random sub-sampling experiments were

performed. As shown in **Fig. 5A**, all three samples can be reliably decoded in

low coverages (coverage of 8 for A-PCR, coverage of 12 for E-PCR-1st,

coverage of 16 for E-PCR-2st). It is worth to point out that low quality reads are

removed before decoding in reported systems. In this study, raw reads are

directly supplied to DBG-GPS for decoding without any pre-treatments proving

the capacity of DBG-GPS in handling low quality reads. It is also interesting to

notice that although the strand recovery rate of A-PCR is higher than the ePCR

examples at low coverages, the recovery rates of E-PCR-1st and E-PCR-2st

overtake that of A-PCR at coverages of 16 and 24 respectively, suggesting a

more uniformed distribution of DNA strands in the ePCR products. As shown

by red colour in **Fig. 5B**, the K_n values of ePCR products are higher than

A-PCR with E-PCR-2st as the highest one as expected. The K_n differences

among the three samples become more and more significant when increasing

the coverages. The K_d value of A-PCR is lower than the two ePCR samples

and E-PCR-2st shows the highest K_d value at low coverage. All K_d values of

the three samples dropped quickly while increasing the coverages. The two

ePCR samples shows faster dropping of K_d value than the A-PCR sample. At

a coverage of 6, the K_d values of ePCR samples all become lower than the

K_d value of A-PCR, which is consistent with the strand recovery rate results.

The higher K_d values of ePCR products at low coverages are caused by the

base errors introduced by error-prone PCR, which is consistent with the K_n

curves.

Exploration of DBG-GPS's capacity by large-scale simulations

Considering the expensive array-based DNA synthesis, we performed large-scale simulations to test DBG-GPS's performance with large-scale data sets. An ubuntu server 20.10 installation disk image (~ 1 GB) was used as input file for generation of DNA droplets. Each DNA droplet was set to carry 60 bytes of information with a total length of 316 bp, around the technical limits of current DNA synthesis technologies. We first tried with 10 million DNA droplets, representing a data scale of 600 mega bytes (MB). With an expected copy number of 50, error rate of 4% (approximately 2% substitutions, 1% insertions, 1% deletions), a 155 GB sequence file was generated. However, although a computation workstation equipped with 640 GB memories is employed, the k-mer counting step by Jellyfish encountered memory limitations. The usage of swap disk makes the counting extremely slow. We thus gave up the decoding simulation on this data scale. We then reduced the DNA droplet number to 5 million, representing 300 MB of input data. Preliminary decoding simulations on this data scale reveal a problem of long decoding time. Detailed analysis shows that this is due to the entangled DNA strands caused by repeated presentation of k-mers in different strands. To solve this problem, we provide two strategies. The first strategy is applying a filtering process during production of DNA droplets to filter out the seriously entangled DNA strands. The second strategy is setting a path number boundary for greedy path search. If the greedy path search engine founds more paths than this value, it aborts search. This will reduce the strand decoding rate theoretically. We run the simulations with 5 million DNA droplets for three times independently. On average 4,971,880 DNA droplets (recovery rate = 99.44%) were successfully recovered by DBG-GPS.

Discussion

In the forms of multiple error-rich strands, 'data reputation' is widely presented

in DNA data storage. However, no effective mechanism can utilize this data

'reputation' feature for robust data storage due to the challenge of handling the

massive errors. In this study, we developed an effective mechanism, named

'DBG-GPS', which can efficiently reconstruct the DNA strands from multiple,

error-rich sequences based on de Bruijn Graph theory. Unlike previous studies,

DBG-GPS can directly construct the DNA strands without

computation-intensive clustering and multi-alignment process which cannot

scale up well. Strategies of low coverage k-mers elimination, CRC codes, and

both-way search were introduced and solved the decoding challenges caused

by base errors. While traditional EC show difficulties in handling indels,

DBG-GPS can efficiently correct high rates (10%) errors of indels, as well as

substitutions or arbitrary mixtures of three types of errors, using merely 40

copies of sequences. More errors still can be corrected by incorporating more

sequences for decoding. The great linear decoding complexity revealed makes

DBG-GPS an ideal solution for large-scale DNA data storage. Furthermore,

DBG-GPS shows more than fifty times faster than the CL-MA based methods.

The robustness of DBG-GPS has been verified by both error-prone PCR

experiments (314KB) and large-scale (300MB) *in silicon* simulations. It is worth

to point out that while previous systems used high-quality reads for decoding

due to their incapacity of handling low-quality reads[6,7,12], raw reads were

directly used for decoding without any pre-processing step to remove the low

quality reads in this study. Furthermore, due to the unique decoding

mechanism, DBG-GPS does not rely on the DNA strand integrity for data

recovery. Preliminary test using single-end reads for decoding, simulating all

DNA strands with at least one break, shows no differences with pair-end reads

in decoding quality. DNA strand breaks are key threads to DNA data integrity.

Thus, although further studies are required, we strongly believe that DBG-GPS

has great potentials in promoting the data reliability of long-term storage.

Finally, DBG-GPS can work with low-quality PCR products with massive DNA

fragments with an incorrect length as proved by error-prone PCR, deep copy

experiments. Although DBG-GPS based decoding shows great potentials in

DNA data storage, the pure python implementation, is far from optimal. The

simple hash dictionary-based data structure for k-mer retrieval is memory

expensive. Although no theoretical limitation on the data scale is shown with

DBG-GPS, we failed to simulate with 500MB data on a computational

workstation with 640GB memories installed due to memory limitation. C++

implementation with more advanced k-mer data structure is expected to

significantly reduce the memory cost, as well as decoding time[19,20].

Furthermore, novel error correction codes that can incorporate with the noisy

k-mers elimination and greedy path search steps can further boost the

capacity of DBG-GPS.

Methods

Library design, PCR and Sequencing

A DNA library of 12,000 oligonucleotides in length of 200nt was synthesized by

Twist Biosciences. For accurate amplification of DNA library, KAPA HiFi

HotStart ReadyMix was used with thermo cycle parameters: 98□ for 30s, 98□

for 15s, 60□ for 15s, 72□ for 15s, 72□ for 15s, 22 cycles. The ssDNA of

synthesized DNA library with 1,000 copies was used as templates for

replication. Error-prone PCR was performed with Controlled Error-prone PCR

Kit, TIANDZ, CAT#:160903-100. Thermo cycle parameters were 94☐ for 3

mins, 94☐ for 1min, 45☐ for 1min, 72☐ for 1min, 30 cycles. Two series

error-prone PCR were performed to introduce high rates of errors. The first

round PCR used the synthesized ssDNA with an average copy number about

1,000 copies of each strand as templates. The second round PCR used 1μl

products of first round PCR as templates. All PCR experiments were

performed with the following primers: P1-'CCTGCAGAGTAGCATGTC', P2-

'CGGATGCATCAGTGTCAG'.   The PCR products were sequenced by Tianjin

Novogene Sequencing Center & Clinical Lab. Sequencing libraries were

generated with purified PCR products using Illumina TruSeq DNA PCR-Free

Library   Preparation   Kit   (Illumina,   USA)   following   manufacturer's

recommendations and index codes were added. For the products of the

second-round error-prone PCR with very large DNA strands, DNase digestion

is applied to break the long strands into small fragments around 200bp. After

digestion, all fragments are collected for further library construction using the

protocol as just described. The library quality was assessed on the Qubit@ 2.0

Fluorometer (Thermo Scientific) and Agilent Bioanalyzer 2100 system. All the

libraries were sequenced on an Illumina NovaSeq platform and 250 bp

paired-end reads were generated.

Counting of *k*-mers and elimination of low coverage *k*-mers

De Bruijn graph is quite memory expensive. The python implementation

provided in this study used simple hash dictionary structure which is not

memory efficient. Thus, although the scripts implemented with functions to

read the common nucleotide sequence files*, i.e.* FastQ or FastA, and count the

k-mers accordingly, for large data sets, we strongly suggest to use a

professional *k*-mer counting system, *e.g.* Jellyfish[19], which is much more

memory efficient and multi-core supporting. To count *k*-mers by the python

scripts, please call the following functions of DeBruijnGraph() object: for

reading and counting of FastQ file, use DeBruijnGraph-openFastQ('file name');

for reading and counting of Fasta file, use DeBruijnGraph-openFasta('file

name').

For elimination of low coverage *k*-mers, call function DeBruijnGraph-

remove_low_cov_kmers(*n*), then all *k*-mers with coverages lower than *n* will be

removed. For usage of Jellyfish for counting of *k*-mers and dumping of *k*-mers

satisfying the criteria, please refer to the Jellyfish manual, which is available at

(http://www.cbcb.umd.edu/software/jellyfish/). The dumped *k*-mers by Jellyfish

can be introduced to the DeBruijnGraph() object for further decoding test using

DeBruijnGraph-openDump('file name') function.

Choice of *k*-mer size

Obviously, with specific *k*-mer size, the data scale can be decoded is limited.

For example, it is clearly that only very small amount of data can be decoded

with an extremely short *k*-mer size of three. However, the mathematical

answer to this question is yet unsolved. In de Bruijn Graph theory, for each

k-mer, the front *k*-1 bases were used for positioning (*i.e.* indexing), and the one

base at the terminal was used for extension of path, *i.e.* for encoding of data.

Thus, we estimate the decoding capacity (p) of *k*-mers with a specific size of k

as follows:

$$p = 4^{k-1} \times 2bits$$

547   Where 4^{k-1} is the combination number of possible indexes with a length of

548    $k-1$, 2 bits stands for the encoding capacity of one base at the tail. Based on

549 this formula, the decoding capacities of different *k*-mer sizes were calculated

550 and listed in **Tab. S1**. As shown in the table, the decoding capacity is estimated

551 to be around 57.6 PB with a *k*-mer size of 30, and 6×10^5 EB for *k*-mer size of

552 40, indicating a highly capable method for large-scale data decoding.

553 Additionally, it should be noticed that, due to the repeated presentations of

554 identical *k*-mers in different DNA strands, the actual data scale can be higher

555 than this estimation. However, to avoid decoding troubles with entangled DNA

556 strands by repeated *k*-mers, we strongly recommend to use a *k*-mer size with a

557 decoding capacity ten times larger than the actually encoded data.

558 **Greedy path search**

559 The greedy search process was illustrated in **Fig. S5**. The details are

560 described as follows: ***Step 1.*** select an index, *e.g.* 562451, and calculate the

561 anchor value by the Python pseudorandom function using the index value as

562 seed in case of both-way search mode. An anchor value of 47736 is obtained

563 in the case of 562451. ***Step 2.*** encode the index into DNA string based on the

564 corresponding binary string, *i.e.* 562451 = 10001001010100010011=

565 ATATATGGGATCAGAA. Similarly, the anchor of 47736 is encoded into DNA

566 string of ATATATATGCGTTTGG in case of both way search. The greedy path

567 search start with ATATATGGGATCAGAA as initial path. Similarly, the tail

568 search start with ATATATATGCGTTTGG as initial path in case of both-way

569 search. ***Step 3.*** Judgement step. This step is for selection of an end with few

570 path numbers for extension of paths. ***Step 4.*** Extension of paths on the end

571 with fewer path number. ***Step 5.*** Judgement step. This step is for judge if the

572 path search has finished. ***Step 6.*** This step is specifically required for both-way

573 search mode. The head paths are fused with tail paths if the overlap

574 sequences are identical. For one-way search this step is not required. ***Step 7.***

Encode the complete paths into binary string. Perform parity checks and drop

the wrong routes using the embedded CRC codes. For other EC codes applied,

use the checking mechanism correspondingly. **Step 8.** Judgement step. Check

if there is only one path passed the CRC checking. If it is true, choose it as

decoded strands, otherwise, mark a missing strand for this index. If multiple

routes or no routes pass the CRC codes, the searching-based decoding fails.

Only in case of exactly one route passed the CRC checking, the decoding

succeeds. **Step 9**. Judgement step. Judge if the search finished. If not, iterate

step 1 to *step 9* until all index are searched for possible strands. If yes, finish

the inner decoding process. The DeBruijnGraph() was implemented to search

in both-way mode by default. To active the one-way search mode, switch the

value of DeBruijnGraph() ->dual_search to 'False'.

Large-scale simulations

For the large-scale simulations, an Ubuntu Server 20.10 live install disk image

(MD5: f51594d36008c456cf0360aeadd130d6, size: 1 GB) was used as input

file for generation of random DNA droplets. Each DNA droplet was set to

encode 60 bytes of data and two bytes of CRC codes. The length of index and

anchor are both set to four bytes. Primers of P1-'CCTGCAGAGTAGCATGTC'

and P2- 'CGGATGCATCAGTGTCAG' were added to the ends. This will result

with a DNA droplet length of 300 bp, around the theoretical limits of current

DNA synthesis technologies. To avoid of entangled DNA strands, a filter

process that always discard the DNA droplets contains a *k-1* mer that already

presents more than four times was applied to the droplet generating stage. For

counting of *k*-mers by Jellyfish, a *k*-mer size of 24, and *k*-mer coverage cut-off

of five, *i.e.* all *k*-mers with a coverage less than five is discarded, was applied.

Data Availability

All the algorithms proposed in this study were implemented with Python and

the source code is available at

https://switch-codes.coding.net/public/switch-codes/DNA-Fountain-De-Bruijn-

Decoding/git/files.

The compressed file in size of 314 KB is available at

https://switch-codes.coding.net/public/switch-codes/DNA-Fountain-De-Bruijn-

Decoding/git/files/master/input_files/314kb.rar.

The encoded files include:

Two famous talks, "I Have a Dream" from Martin Luther King and William

Faulkner's speech of accepting the Nobel Prize in literature, as well as four

pictures (two pictures of IBM RAMAC 350, one picture of the front page of

"Molecular Structure of Nucleic Acids", and one picture of Oracle) were

compressed into one binary file of 314kb with free version of WinRAR

(http://www.winrar.com/).

All sequencing data can be found in the following links:

Sequencing raw reads of accurate amplification:

https://pan.baidu.com/s/1XxvHwZR_B8UNBZKzyBBE2A (forward reads, fetch

codes: ATGC, MD5: b0e6ff9820c090a22c0ed360018c8e46)

https://pan.baidu.com/s/1fr23i-MoliMhjCqWwCBN_w (reverse reads, fetch

codes: ATGC, MD5: a97e8066d47052140422f501992fdacf)

Sequencing raw reads of two-rounds of error-prone PCR:

https://pan.baidu.com/s/1nNvWoIx85cpbXXnigMuyQw (first-round error-prone
PCR, forward reads, fetch codes: ATGC, MD5:
640142956d03f2de1b495e4cb55d37d5)

https://pan.baidu.com/s/14JMO-CEd9udfab7W-hkROA (first-round error-prone
PCR, reverse reads, fetch codes: ATGC, MD5:
ddb5d12e158316e6cd508b45b12e9469)

https://pan.baidu.com/s/1SZsy0-HP-lWxPq2ZNmdwlg (second-round
error-prone PCR, forward reads, fetch codes: ATGC, MD5:
7cd61814025f372aef2de48186f0c364)

https://pan.baidu.com/s/1B8ZbTgrAXs2d04KcbXdyyQ (second-round
error-prone PCR, reverse reads, fetch codes: ATGC, MD5:
b64cc129d7446623437481474624095a)

Acknowledgements

635   This work was supported by Seed Foundation of Tianjin University and Natural
636   Science Foundation of Shandong Province (ZR2017LC006).

Competing interests

638   The authors have declared that no competing interests exist.

Author contributions

640   LFS proposed the idea, wrote the Python codes, designed the experiments,

performed the simulations, and analysed the data. FG helped with experiment design and data analysis. ZYG performed the error-prone PCR experiments. BZL and YJY supervised the whole work.

References

1. Zhirnov, V., Zadegan, R. M., Sandhu, G. S., Church, G. M. & Hughes, W. L. Nucleic acid memory. *Nature materials* **15,** 366–370; 10.1038/nmat4594 (2016).

2. Church, G. M., Gao, Y. & Kosuri, S. Next-generation digital information storage in DNA. *Science (New York, N.Y.)* **337,** 1628; 10.1126/science.1226355 (2012).

3. Ceze, L., Nivala, J. & Strauss, K. Molecular digital data storage using DNA. *Nature reviews. Genetics* **20,** 456–466; 10.1038/s41576-019-0125-3 (2019).

4. Ping, Z. *et al.* Carbon-based archiving: current progress and future prospects of DNA-based data storage. *GigaScience* **8**; 10.1093/gigascience/giz075 (2019).

5. Grass, R. N., Heckel, R., Puddu, M., Paunescu, D. & Stark, W. J. Robust chemical preservation of digital information on DNA in silica with error-correcting codes. *Angewandte Chemie (International ed. in English)* **54,** 2552–2555; 10.1002/anie.201411378 (2015).

6. Erlich, Y. & Zielinski, D. DNA Fountain enables a robust and efficient storage architecture. *Science (New York, N.Y.)* **355,** 950–954;

10.1126/science.aaj2038 (2017).

7. Organick, L. *et al.* Random access in large-scale DNA data storage. *Nature*
biotechnology **36,** 242–248; 10.1038/nbt.4079 (2018).

8. Song, L. & Zeng, A.-P. Orthogonal Information Encoding in Living Cells with
High Error-Tolerance, Safety, and Fidelity. *ACS synthetic biology* **7,**
866–874; 10.1021/acssynbio.7b00382 (2018).

9. Anavy, L., Vaknin, I., Atar, O., Amit, R. & Yakhini, Z. Data storage in DNA
with fewer synthesis cycles using composite DNA letters. *Nature*
biotechnology; 10.1038/s41587-019-0240-x (2019).

10.Chen, Y.-J. *et al.* Quantifying molecular bias in DNA data storage. *Nature*
communications **11,** 3264; 10.1038/s41467-020-16958-3 (2020).

11.Press, W. H., Hawkins, J. A., Jones, S. K., Schaub, J. M. & Finkelstein, I. J.
HEDGES error-correcting code for DNA storage corrects indels and allows
sequence constraints. *Proceedings of the National Academy of Sciences of*
the United States of America **117,** 18489–18496;
10.1073/pnas.2004821117 (2020).

12.Antkowiak, P. L. *et al.* Low cost DNA data storage using photolithographic
synthesis and advanced information reconstruction and error correction.
Nature communications **11,** 5345; 10.1038/s41467-020-19148-3 (2020).

13.Brakensiek, J., Guruswami, V. & Zbarsky, S. in *Proceedings of the*
Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms,
edited by R. Krauthgamer (Society for Industrial and Applied Mathematics,

Philadelphia, PA, 012016), pp. 1884–1892.

14.Smagloy, I., Welter, L., Wachter-Zeh, A. & Yaakobi, E. in *2020 IEEE*

International Symposium on Information Theory (ISIT) (IEEESunday, June

21, 2020 - Friday, June 26, 2020), pp. 775–780.

15.Zerbino, D. R. & Birney, E. Velvet: algorithms for de novo short read

assembly using de Bruijn graphs. *Genome research* **18,** 821–829;

10.1101/gr.074492.107 (2008).

16.Pevzner, P. A., Tang, H. & Waterman, M. S. An Eulerian path approach to

DNA fragment assembly. *Proceedings of the National Academy of Sciences*

of the United States of America **98,** 9748–9753; 10.1073/pnas.171285098

(2001).

17.Cyrus Rashtchian *et al.* Clustering Billions of Reads for DNA Data Storage.

18.Edgar, R. C. MUSCLE: multiple sequence alignment with high accuracy

and high throughput. *Nucleic acids research* **32,** 1792–1797;

10.1093/nar/gkh340 (2004).

19.Marçais, G. & Kingsford, C. A fast, lock-free approach for efficient parallel

counting of occurrences of k-mers. *Bioinformatics (Oxford, England)* **27,**

764–770; 10.1093/bioinformatics/btr011 (2011).

20.Pandey, P., Bender, M. A., Johnson, R., Patro, R. & Berger, B. Squeakr: an

exact and approximate k-mer counting system. *Bioinformatics (Oxford,*

England) **34,** 568–575; 10.1093/bioinformatics/btx636 (2018).

Fig. 1 Potentials of de Bruijn graph-based decoding. A - Representations of base substitutions and indels in de Bruijn graph. ***a.***

Simple de Bruijn graph constructed from 12bp sequence of "AACGGCGGCTGT" with four identical copies. (*k*-mer size = 4). The

circles stand for the *k*-mers and the numbers inside the circles are coverages of corresponding *k*-mers. ***b.*** De Bruijn graph of four

sequence copies of "AACGGCGGCTGT" with one substitution in sequence 2; ***c.*** De Bruijn graph of four sequence copies of

"AACGGCGGCTGT" with one insertion and one deletion on sequence 2 and 3 respectively; ***d.*** De Bruijn graph of four sequence

copies of "AACGGCGGCTGT" with one strand break on each sequence. **B** - Simulated maximal recovery rates with vary copies of

DNA strands with 10% different types of errors respectively. The number of sequence copies is in range of 1 to 60 with a step size of

1. High error rate of 10% can be tolerated with merely 40 sequence copies. **C** - Simulated maximal recovery rates using ten copies of

DNA strands with different types and rates of errors; During the simulation, artificial random errors are introduced into ten copies of

sequences with specific type and rate of errors from 1% to 10% with a step size of 1%. The sequences with artificial errors were then

used for construction of the de Bruijn graph. The De Bruijn graph path of the correct sequence was checked. This process is iterated

for 10,000 times. The maximal decoding rates are the rates of "successful decoding events" during simulations. S_m stands for

"maximal strand decoding rate", which is calculated by checking the integrity of all strand paths.

A

I. Original sequences

1 AACGGCGGCTGT
2 AACGGCGGCTGT
3 AACGGCGGCTGT
4 AACGGCGGCTGT

$a \rightarrow b \rightarrow c \rightarrow d \rightarrow e \rightarrow c \rightarrow f \rightarrow g \rightarrow h$

II. Base substitution

1 AACGGCGGCTGT
2 AACGGCGACTGT
3 AACGGCGGCTGT
4 AACGGCGGCTGT

III. Base insertion

1 AACGGCGGCTGT
2 AACGTGCGGCTGT
3 AACGGCGGCTGT
4 AACGGCGGCTGT

IV. Base deletion

1 AACGGCGGCTGT
2 AACGGCGGCTGT
3 AACGGCG CTGT
4 AACGGCGGCTGT

B

S_m

Error rate 10%   Sequence copy 100

C

S_m

Fig. 2 Path search complexity caused by base errors can be significantly

released by elimination of low coverage *k*-mers. A – Massive noisy *k*-mers

are introduced by sequence errors. **B** - Greedy path search burden with the

enlarged de Bruijn graph can be remarkably reduced by elimination of low

coverage *k*-mers. The number of paths found and search time increased

exponentially as the rates of errors (**B-*i***) or the number of sequence copies

(**B-*ii***) increased; The greedy search time and revealed number of paths

decreased remarkably after elimination of low coverage *k*-mers (**B-*iii*** and

B-*iv*).

Fig. 3 Framework of DBG-GPS and its combination with an erasure outer code for large-scale data storage solutions

A – A proposed general framework for de Bruijn graph-based strand decoding with multiple error-rich sequences. For correct reconstruction of DNA strand sequences, we propose a four-step framework including: 1. Construction of de Bruijn Graph; 2. Elimination of noisy k-mers; 3. Greedy path search; 4. Path selection by traditional EC codes. **B** –Integration of DBG-GPS with an erasure outer codes for large-scale data storage solutions. **C** - Structure of the DNA strand. There are four parts in the designed DNA droplet strand: A1 – The index of the DNA droplet. The seed of the DNA strand can be calculated by pseudorandom function using the value of A1 as random seed. codes which is used for inferring the indexes of the data chunks involved in the present droplet; A2 – Data encoding part; A3 – Cyclic Redundancy Check codes (CRC) which are used for identification of the correct path if multiple paths were found after the path searching using the A1 as an index; A4 – Anchor cods which is generated using specific hashing function based on the value of A1.

745 **Tab. 1 Decoding speed of DBG-GPS in comparison with clustering and multi-alignment (CL-MA) based method.**

746 The time of clustering stage in CL-MA based decoding was estimated based on a recent study by Cyrus Rashtchian *et al.*[17] The

747 consensus calling stage used majority voting algorithm used in a recent study by Antkowiak, P.L. *et al.*[12]

DBG-GPS		CL-MA	
Stages	**Time**	**Stages**	**Time**
k-mer counting (*Jellyfish Single CPU*)	31.33 ± 0.65s	**Clustering**[17]	~11.45s
Strand decoding (*Python Script*)	**36.84 ± 0.91s**	**Multi-alignment** (*Muscle*[18], *IO time subtracted*)	**3874.48 ± 30.82s**
		Consensus calling (*Majority voting*[12])	15.42 ± 0.40s
Total	73.17 ± 1.56s	Total	~3901.35s

Fig. 4 Experimental verification the robustness of DBG-GPS by error-prone PCR.

Fig. 5 Low-coverage data decoding by random sub-sampling of all sequencing reads.

For each coverage, we run 12 times of independent sub-sampling. The average strand recovery rates (**A**), K_d and K_n values (**B**)

calculated with variant coverages illustrated. The dashed curves in Fig. A are the results without elimination of low coverage k-mers.

The horizontal dashed purple line stands for the decoding limits by the outer Fountain codes. The numbered dashed red line with

arrows point out the data point that data can be recovered by the outer Fountain codes and the numbers are the corresponding

minimal coverages for decoding. The blue dashed lines with arrows point out the data points that a k-mer elimination process was

applied.

Supplementary materials

Fig. S1 Traditional error correction codes cannot well handle indels due to the base shift problem. Erasure codes are designed for errors of unreadable data blocks without data shift issues. To correct indels by erasure codes, two-dimensional erasure codes must be applied. However, one indel in one dimension will lead to many substitution errors have to be corrected in another dimension making the efficiency of such treatments very low.

771　**Fig. S 2 The sizes of de Bruijn graph increased remarkably by increasing**

772　**the error rates (A) or the number of sequence copies (B).**

 Fig. S3 Coverage distributions of correct *k*-mers and noisy *k*-mers

revealed by monte carlo simulation. The simulation is performed with

10,000 DNA strands, a λ value (i.e. the expectation value) of 50 for strand

copies, a base error rate of 4% (a common error rate)

Fig. S4 Both-way search strategy shows fast decoding than one-way

search. The simulation is performed with 10,000 DNA droplets. 100 sequence

copies with random base errors in rates of 10% are generated for decoding

test.

Fig. S5 Details of de Bruijn graph-based greedy searching algorithms.

The detailed description is presented in **Methods** section.

Fig. S6 The algorithm shows excellent linear decoding complexity while

scaling up.

Fig. S7 Gel analysis of error-prone PCR products. A – The first-round

error-prone PCR. B – the second-round error-prone PCR using 1 µl first round

PCR products (A) as templates. Although the quality of the two PCR products,

especially the second-round (B), is very low, we can accurately retrieve the

original data without any mistakes in both cases. *Note, the designed length of*

DNA strands is 200bp.

Fig. S8 *k*-mer coverage distributions of three data retrieval experiments

by accurate PCR (A-PCR) and error-prone PCR (E-PCR-1st and

E-PCR-2st). This figure is used as reference for setting the cut-offs of low

coverage *k*-mers.

Tab. S1 Theoretical decoding capacities of DBG-GPS with different

***k*-mers sizes**

The formula used for decoding capacity estimation was described in **Methods**.

k-mer sizes	10	20	30	40
Theoretical decoding capacity	0.5 MB	0.55 TB	57.6 PB	6×10^5 EB

813