Robust data storage in DNA by de Bruijn graph-based decoding

Li-Fu Song[1,2], Feng Geng[3], Zi-Yi Gong[1,2], Bing-Zhi Li[1,2*], Ying-Jin Yuan[1,2*]

[1] Frontier Science Center for Synthetic Biology and Key Laboratory of Systems Bioengineering (Ministry of Education), Tianjin University, Tianjin 300072, China

[2] SynBio Research Platform, Collaborative Innovation Center of Chemical Science and Engineering, School of Chemical Engineering and Technology, Tianjin University, Tianjin 300072, China

[3] College of Pharmacy, Binzhou Medical University, Yantai 264003, China

*Corresponding authors: bzli@tju.edu.cn, yjyuan@tju.edu.cn

Abstract

Data storage in DNA, which store information in polymers, is a potential technology with high density and long-term features. However, the indels, strand rearrangements, and strand breaks that emerged during synthesis, amplification, sequencing, and storage of DNA molecules need to be handled. Here, we report a de Bruijn graph-based, greedy path search algorithm

(DBG-GPS), which can efficiently handle all these issues by efficient

reconstruction of the DNA strands. DBG-GPS achieves accurate data recovery

with low-quality, deep error-prone PCR products, and accelerated aged DNA

samples (solution, 70℃ for two weeks). The robustness of DBG-GPS was

verified with 100 times of multiple retrievals using PCR products with massive

unspecific amplifications. Moreover, DBG-GPS shows linear decoding

complexity and more than 100 times faster than the multiple alignment-based

methods, indicating a suitable solution for large-scale data storage.

Keywords

28 DNA data storage, de Bruijn graph, Indel, DNA rearrangements, DNA break,

29 Unspecific amplification, Erasure codes, Fountain codes, Reed-Solomon

30 codes

Introduction

With properties of high density, low maintenance, and long persistent period,

DNA as storage media is believed to be a potential candidate for solving the

world challenge of data explosion[1–6]. However, the massive errors that

emerged during DNA synthesis, amplification, sequencing, and storing make

reliable data storage in DNA a challenge. Previous studies have shown that

the implementation of a reliable codec system for DNA data storage requires

two layers of error correction (EC) codes. The outer layer codes handle the

strand dropouts and the inner layer codes respond for the error-free decoding

of DNA strands as many as possible[7–10]. Strand dropouts are erasures, which

can be well solved by erasure codes, *e.g.* Fountain, Reed-Solomon (RS)

codes[8–10]. However, for the design of robust inner codes, there exist three

challenges yet to be solved.

The first challenge is the efficient handling of indels. Although elegant EC

codes have been developed in the field of information theory, they are not

optimal for indels with base shift problem. Previously, base deletions have

been occasionally treated as erasures[8–10]. However, other than unreadable

bases, *i.e.* erasures, base deletions also cause shift forwards of downstream

nucleotide bases. This base shift issue, which applies to base insertions as

well, causes serious problems for traditional erasure codes as illustrated in **Fig.**

S1. Despite indels can be detected by traditional erasure codes, the positions

of the missed and inserted bases cannot be inferred. The successful data

decoding in previous studies using RS erasure codes as inner codes owing to

a two-dimensional coding strategy, accurate DNA synthesis and sequencing

technologies[8,10]. However, this mechanism is low efficient in handling the

indels. A single indel in the row dimension (DNA strand) will lead to a series of

'substitution' errors in the column dimension. Thus, this strategy only works

with low indel rate. When slightly more indels are introduced, the 'substitutions'

become overwhelming and quickly exhaust the column EC codes. Recently,

Press et. al. implemented a hash encoded, decoded by greedy exhaustive

search (HEDGES) codes that can correct indels with a single copy of DNA

strand[11]. Despite outstanding technical achievements in indel correction with

single copy data, HEDGES requires 40% redundancy codes for correction of

merely 3% indel errors. This would significantly increase the cost of DNA data

storage. A cost-efficient mechanism to handle the indels is highly desirable.

The second challenge is the correction of strand rearrangements. Copying and

retrieval of DNA data requires polymerase chain reaction (PCR) for

amplification of DNA strands. However, as a common sense in molecular

biology, PCR experiments result in unspecific amplification occasionally even

with optimized conditions. Large data storage in DNA requires enormous DNA

strands of various sequence contents. PCR amplification with various DNA

strands can result in unspecific amplifications even more frequently. Unspecific

amplification will cause massive strand re-arrangements. This is a serious

problem to the data integrity, which has not been solved yet. Although previous

studies have proved that perfect decoding of DNA data can be achieved with

high quality PCR products, limited number of data retrievals have been

performed, which is far from the industrial standards of storage media. The

robustness of DNA data storage under massive multiple retrievals is still not

verified yet. To achieve robust data retrieval, the unspecific amplification

problem emerged occasionally needs to be handled. The third challenge is the

strand break problem. As typical biological polymers, DNA molecules are

highly degradable[12,13]. Previous studies developed methods for protection of

DNA molecules by silicon beads or earth alkaline salts[8,14], which can reduce

the speed of DNA degradation significantly[8]. However, degradation of DNA

molecules is inevitable fundamentally, especially for long-term storage. Thus, a

new mechanism that can reconstruct the original DNA sequences from small

fragmented DNA strands is highly desirable for enhancing the robustness of

DNA data storage.

DNA data storage achieves data operations by DNA synthesis, PCR, and

sequencing processes. These processes always generate multiple error-rich

copies of DNA strands fast and cheaply. This unique 'multiple copy' feature,

also termed as "natural redundancy" in previous studies, or 'data repetition' by

definition of information theory[15], makes DNA data storage a unique

channel[15,16]. Data repetition is regarded as a low efficient way of redundancy

coding in traditional media and channels since additional data copies are super

time- and cost-expensive. However, data repetition in the forms of DNA strand

copies is cheap, fast, and basically unavoidable. Indeed, it may increase the

cost significantly to make a single copy DNA data since additional efforts are

required. Efforts on reducing the "multiple copy" feature by serial dilutions

observed massive strand dropouts when reducing the average copy number

under ten, making reliable data retrieval impractical[17]. Additionally, DNA

molecules, as highly degradable polymers, break easily. Thus, even DNA data

with single copy of each strand is obtained, the data stability is still

questionable because strand breaks, which cannot be handled by any

reported codes, are fatal to DNA data integrity. Taken together, a small number

of strand copies, *e.g.* 10 to 100, which do not hamper the data density, is

required for practical DNA data storage.

In this study, we report the robust data storage in DNA by an efficient strand

reconstruction algorithm based on de Bruijn Graph-based Greedy Path

Searching (DBG-GPS). DBG-GPS can handle all the three challenges by

taking advantage of the multi-copy feature for high-efficient DNA strand

reconstruction. With the optimized procedure, DBG-GPS shows high

resistance to indels as well as substitutions. While correction of indels with

single copy data is still challenging[18,19], errors (indels and/or substitutions) in a

high rate of 10% can be efficiently corrected by DBG-GPS. Importantly,

DBG-GPS achieves robust data retrieval with low-quality PCR products with

massive strand rearrangements caused by unspecific amplifications, and

highly degraded DNA samples with massive DNA strand breaks. Furthermore,

although python scripts are utilized, DBG-GPS shows more than 100 times

faster than the clustering and multiple alignment-based methods. The linear

decoding complexity revealed by simulations makes DBG-GPS a suitable

solution for large-scale data storage.

Results

Principles and potentials of de Bruijn graph-based decoding

Due to the difficulties of long DNA synthesis, large data storage in DNA has to

distribute the information in massive DNA fragments. Thus, decoding of DNA

data is assembly of the original data from small pieces of information carried

by massive DNA fragments. This process is similar to the process of genome

assembly, in which the complete genome sequences are assembled from

small pieces of DNA sequences obtained from shotgun genome sequencing.

However, as shown by a large number of genome sequencing projects, it is a

challenge to obtain the complete genome sequences by shotgun genome

sequencing solely[20]. Imperfect genome assembly is acceptable since following

up experiments can be performed to improve the assembly[20]. Obviously,

imperfect assembly is unacceptable for data storage applications. To decode

the DNA data accurately, the extra options of indexes and error correction

codes bring opportunities. De Bruijn graph theory, which is an efficient way to

represent a sequence in terms of its *k*-mer components, has been successfully

applied to genome assembly with second-generation sequencing data[20,21].

However, the potentials of de Bruijn graph theory in DNA data storage haven't

been explored thus far.

To investigate the potentials of de Bruijn graph theory in DNA data storage, we

first analyzed the representations of substitutions, indels and strand breaks in

de Bruijn graph as shown in **Fig. 1a**. The simple de Bruijn graph on the right

was constructed from the four sequence copies of "AACGGCGGCTGT" in the

left with a *k*-mer size of four (**Fig. 1a**-*i*). The DNA sequence of

"AACGGCGGCTGT" is a path, *i.e.* "$a \rightarrow b \rightarrow c \rightarrow d \rightarrow e \rightarrow c \rightarrow f \rightarrow g \rightarrow h$", in the

constructed graph. A substitution of "G" to "A" in sequence #2 will lead to a

branch path, as shown in red color, and reduced weights (coverages) of the

correct path (**Fig. 1a-*ii***). Indels are much more difficult to handle than

substitutions by traditional EC codes. However, the representations of base

indels in de Bruijn graph are very similar to substitutions: both creating

interfering path(s) and reducing the weights of the correct path (**Fig. 1a-*iii***).

Although strand breaks can cause serious problems for traditional EC codes,

they only cause subtle influence on the de Bruijn graph, by reducing weights of

the correct path without changing the graph structure. A greedy path search

algorithm and a path selection mechanism for recognition of the correct path,

could recover the DNA strand theoretically. In this way, the errors are

transformed into a path search and selection problem by de Bruijn graph

theory with multiple sequence copies. With this mechanism, as long as the

correct path, e.*g.* "$a \rightarrow b \rightarrow c \rightarrow d \rightarrow e \rightarrow c \rightarrow f \rightarrow g \rightarrow h$" in **Fig. 1a**, is preserved, the

corresponding DNA strand can be decoded theoretically. Thus, the path

robustness indicates the potentials of de Bruijn graph theory-based decoding.

Obviously, the sequence error rates and copy number together determine the

robustness of a de Bruijn graph path. To further investigate how the strand

copies and error rates affect path robustness, we simulated DNA strands with

different rates of errors. Variant numbers of the simulated containing

sequences were utilized for de Bruijn graph construction and path integrality

analysis. The integrality of the correct path was tested by checking the

existence of all k-mers in this path in the constructed graph. The rate of the

strands with a complete path in the graph was defined as 'maximal strand

decoding rate (S_m), which stands for the theoretical maximal strand decoding

rate which can be achieved by an actual de Bruijn graph-based decoder. Firstly,

we run the simulations with different types of errors separately. With twenty

strand copies, the path robustness with different types of errors in the range of

1% to 10% with a step length of 1% were estimated. As shown in **Fig. 1b**,

although substitutions, indels, and strand breaks are quite different errors

based on traditional information theory, they show very close S_m values with

the same error rates. Importantly, with merely 20 sequence copies, the de

Bruijn graph path shows high robustness with an error rate of 5%, which is a

common error level of DNA data storage reported[9,10,22]. In realistic situations,

the errors that emerged in DNA data channel are mixtures of all types of errors.

Thus, we then perform thorough simulations with an error mixture ratio of 50%

substitutions, 25% insertions and 25% deletions with different rates of errors

and copies of strands. Total error rates in the range of 1% to 10% with a step

length of 0.5%, and strand copies in the range of 5 to 100 with a step length of

5 were considered. As shown in **Fig. 1c**, S_m > 0.99 can be obtained with 60

sequence copies (red dashed line) with high rate errors of 10%, revealing the

great potentials of de Bruijn graph-based decoding.

Development of a general framework for de Bruijn graph-based decoding

Based on the analysis of previous section, two major steps are required for decoding of DNA strands from multiple error-rich sequence copies utilizing de Bruijn graph theory: 1) greedy path search for possible path candidates and 2) selection of the correct path. In this section, we describe the issues emerged during the implementation of a de Bruijn graph-based decoding algorithm and strategies to solve them. A four-step framework is then proposed for effective strand reconstruction practice with de Bruijn graph. Eventually, the DBG-GPS algorithm was implemented following this framework with Python.

Elimination of low coverage *k*-mers decreases the greedy path search complexity

A serious problem emerged is the explosion of de Bruijn graph size caused by base errors. About thirty times enlargement of the de Bruijn graph size was observed when 4% random errors were introduced into 10,000 DNA strands with 100 copies each (**Fig. S2a**). Greedy path search with this enlarged de Bruijn graph resulted in overwhelming number of possible paths, leading to unbearably long path search time. The enlarged de Bruijn graph contains massive noise *k*-mers, *i.e.* *k*-mers introduced by base errors. To quantify the noise *k*-mers, we introduce an indicator K_n, which is the ratio of noise *k*-mers and correct *k*-mers in the de Bruijn graph. Clearly, more errors and strand copies will introduce more noise *k*-mers to the de Bruijn graph, which will result in a larger K_n. Monte carlo simulations show a quick increase of K_n by

increasing either the error rate or the sequence copies (**Fig. S2a**). The number

of branch paths and decoding time increase exponentially with the

increasement of error rates (**Fig. S2b**) or strand copies (**Fig. S2b**). Thus, a

pre-processing step that can remove the noise *k*-mers is desirable.

Although DNA data operations can introduce massive errors, these errors are

low probability events individually. Thus, the occurrences, *i.e.* the coverages of

noise *k*-mers, should be significantly lower than the correct ones. In other

words, the low coverage *k*-mers are more likely to be noise *k*-mers.

Preliminary testing with the elimination of *k*-mers with coverage of one

significantly reduced the decoding burden of branch paths without significant

affections to the path integrity (**Fig. S2b**). To further investigate the feasibility of

coverage as an indicator for distinguishing noise *k*-mers, we used a Poisson

distribution model to simulate the copy number distribution of DNA strands.

The coverage distribution of noise *k*-mers and correct *k*-mers are then

investigated based on Monte Carlo simulations. The simulation is performed

with 10,000 DNA strands, a λ value (*i.e.* the expectation value) of fifty for

strand copies and an error rate of 4% (a common level of error rates reported

in previous studies**)**. The vast majority of the noise *k*-mers show coverages

lower than eight, while the correct ones show coverages higher than eight (**Fig.**

S2c). Thus, a coverage cut-off of eight can effectively remove most of the

noise *k*-mers suggesting an effective mechanism for the elimination of noise

k-mers.

Cyclic redundancy check (CRC) codes effectively recognize the correct path

Elimination of low coverage k-mers can effectively remove most of the noise k-mers based on Monte Carlo simulation, the remaining noise k-mers can still have great affections on the accuracy of strand decoding. Thus, a mechanism to recognize the correct path and verify its integrality is required. Kinds of traditional EC codes can achieve this goal theoretically, *e.g.* CRC codes, RS code, or hash functions. Although hash functions are suitable for such tasks in principle, we failed to find a proper hash function that can generate short key words of few bytes. Since erasure is not presented in the path selection process, RS codes, which is capable of handling erasures, is not an optimal solution hence. Here, we choose CRC codes which is powerful in error detection without unnecessary error-correction mechanism. Intensive Monte Carlo experiments show that CRC codes can recognize the correct path in all one million times of independent simulations, proving its effectiveness in the selection of correct paths, *i.e.* correct strands.

A both-way search strategy increases decoding speed

Although elimination of noise k-mers based on coverage can remarkably reduce the greedy path search burden, the remained noise k-mers still can increase the decoding time significantly, especially with high error rates. To further reduce the greedy path search time, we proposed a both-way search strategy which can search for possible paths simultaneously from both ends of DNA strands. To enable this both-way search strategy, we designed a DNA strand structure with an additional 'anchor' element as shown in **Fig. 2c**. The

anchor is an integer generated from the index by a hash-like function. This

function generates one specific number with a given index. For

proof-of-concept, the pseudorandom function of Python is used for the

generation of the anchors by using the indexes as seeds. Due to the feature of

pseudorandom function, it always gets the same 'random' value(s) with the

same seed. Thus, the greedy path search engine can calculate the anchor

based on the index without additional information, enabling the both-way

search strategy. Simulation shows that this both-way search strategy can

reduce the decoding time significantly, especially when sequence error rates

are high. With an error rate of 10% and a copy number of 100, the both-way

search strategy shows about 60% reduction in decoding time compared with

one-way search (**Fig. S3**). No significant difference in decoding accuracy is

observed with the two search strategies.

Four-step framework for effective strand reconstruction practice with

DBG-GPS algorithm

For effective strand reconstruction with DBG-GPS, we proposed a four-step

framework as illustrated in **Fig. 2a**: *Step 1*, Construction of de Bruijn Graph.

Here, the construction of de Bruijn Graph refers to the process of counting of

k-mers. In the current python implementation, a simple hash dictionary data

structure was applied. For further studies with a more advanced data structure

of the de Bruijn Graph, we suggest creating the advanced data structure after

the elimination of noise *k*-mers (Step 2). *Step 2*, Elimination of noise *k*-mers. In

the present study, we use coverage as an indicator for the elimination of noise

k-mers. Additional codes for the identification of noise *k*-mers can also be

introduced to make the elimination more efficient in future studies. ***Step 3***,

Greedy path search. If the error rate is still high, a both-way search strategy

can be applied to reduce the decoding time. ***Step 4***, Selection of the correct

path. The paths found are translated into bit strings and the embed EC codes

are then used for the selection of the correct path. Only in case of one path

passes the EC code checking, this path will be selected and strand decoding

succeed. Following this framework, we implemented the DBG-GPS algorithm

with Python. Reliable strand reconstruction ($S_r > 96.7\%$) was achieved with

various error rates range from 1% to 10% with sixty strand copies as proved by

Monte-Carlo simulations (**Tab. S2**).

Integration of DBG-GPS with outer erasure codes

DBG-GPS is designed as an inner decoding mechanism for the error-free

reconstruction of DNA strands. It can be easily combined with erasure codes,

e.g. fountain codes or RS codes, for large-scale data storage. Integration of

DBG-GPS with erasure codes is quite simple. Simply add CRC codes for

strand integrity verification during strand encoding, and use the DBG-GPS as

an inner decoding process for the decoding of DNA strands. To use other kinds

of codes for strand verification with DBG-GPS, just replace the CRC codes

with specific codes and switch to the corresponding checking method during

strand selection. Since the encoding process is highly similar to the previous

studies, we only illustrated the overall decoding process using DBG-GPS as

the inner decoding method as shown in **Fig. 2c**. There are three major steps in

the decoding process. ***Step 1***, High-throughput sequencing. The DNA strands

are sequenced by high-throughput sequencing technologies. ***Step 2***, Inner

code decoding. The aim of this step is to decode DNA strands as many as

possible. DBG-GPS is a complete solution for **Step 2**. **Step 3**, Decode the

original information by outer erasure codes. A python implementation using

fountain codes as outer codes and DBG-GPS as inner codes is available at

https://switch-codes.coding.net/public/switch-codes/DNA-Fountain-De-Bruijn-

Decoding/git/files.

Decoding speed of DBG-GPS

To the best of our knowledge, the clustering and multiple alignment-based

(CL-MA) methods are the only methods that can rebuild the DNA strands from

multiple error-rich strand copies[10,23,24]. To compare the decoding speed of

DBG-GPS with CL-MA methods, we produced 10,000 DNA droplets with DNA

fountain codes using CRC codes as redundancy codes for strand selection.

For each DNA droplet, we generated fifty sequence copies with 4% random

errors introduced (2% substitutions, 1% insertions and 1% deletions). The

500,000 error-rich reads generated were then utilized for strand decoding by

DBG-GPS and CL-MA respectively. Since the clustering process is quite

complicated in reported studies, for the CL-MA-based decoding, we feed the

program with grouped reads. For decoding speed comparison, a clustering

time was estimated based on the recent study by Cyrus *et al.*[23]. Since the

multiple alignment process was performed by a standalone program

(Muscle[25]), there will be 10,000 times of IO (input and output) with the file

system during strand decoding by CL-MA. To estimate the IO time, one

sequence of the DNA droplet was repetitively submitted to Muscle for multiple

alignment analysis 10,000 times. This process is iterated three times and the

average time is subtracted in the CL-MA based decoding speed test. The

k-mer counting step of DBG-GPS was performed with JellyFish. As shown in

Tab. 1, although a Python implementation of DBG-GPS was utilized in the

decoding speed test, DBG-GPS still shows 103 times faster than the CL-MA

based methods without significant differences in decoding accuracy. A C++

implementation of DBG-GPS is expected to further enhance its performance

remarkably. Importantly, DBG-GPS shows linear decoding complexity while

increasing the total strand scale from 10 to 10,000 (**Fig. S5**), making it a

suitable solution for large-scale data storage in DNA.

Experimental verification of the robustness of DBG-GPS

A 314 KB file compressed from two text files and four jpeg pictures, was

encoded into 12,000 DNA strands in the length of 200 bp using the DNA

fountain codes implemented in this study. Each oligo encodes thirty bytes of

data, three bytes of CRC codes, four bytes of index, and four bytes of anchor

codes. The overall strand redundancy is 10.5% enabling reliable data retrieval

if more than 92% of the strands could be decoded. The designed DNA strands

were synthesized by Twist Bioscience. The single strand DNAs (ssDNA)

obtained from Twist Bioscience were dissolved in ddH$_2$O. 0.6μl of the

dissolved ssDNA was used as template for PCR amplification and data

retrieval by sequencing. To verify the robustness of DBG-GPS with different

types of errors, *i.e.* the base errors (indels and substitutions), strand

rearrangements, and strand breaks, we performed three harsh experimental

tests, as shown in **Fig. 3a**, **b**, and **c** correspondingly.

Reliable data recovery with deep error-prone PCR products

To verify the robustness of DBG-GPS with high rates of base errors including indels and substitutions, we utilized error-prone PCR (ePCR) for amplification of the ssDNA library obtained from Twist Bioscience. Six series of ePCR were performed using an error-prone PCR Kit from TIANDZ. All ePCR experiments were performed for 30 thermal cycles with the highest error-rate settings instructed by the Kit manual. Accordingly, these settings could introduce eight errors per 1,000 bp per amplification cycle. The first round ePCR utilized 0.6 µl samples of the ssDNA master pool as templates. The five following ePCR experiments use 1 µl products of the previous round ePCR as templates. The six ePCR samples obtained, *i.e.* ePCR#1, ePCR#2, ePCR#3, ePCR#4, ePCR#5, and ePCR#6, were sequenced on Illumina HiSeq platform. Due to unspecific amplification, PCR products of ePCR#2, ePCR#3, ePCR#4, ePCR#5 and ePCR#6 show severe smear band in the range of 200 bp to 3,000 bp which cannot be sequenced directly by Illumina platform. Thus, the PCR products were digested with a target length of ~200 bp using DNase I. After digestion, all digested fragments are collected for sequencing and DBG-GPS based decoding.

As shown in **Fig. 4a**, the estimated S_m values of the six samples are all very high (>99%). It was surprising to notice that the S_m values of ePCR#1, ePCR#2, and ePCR#3 were estimated to be 100%, indicating perfect reservation of all strand paths even after 90 cycles of ePCR. We then apply DBG-GPS to recover the encoded DNA strands with the six ePCR samples. As expected, with high S_m values, high strand recovery rates (S_r), between 93.2%

to 99.8%, were obtained, especially for ePCR#1, ePCR#2, and ePCR#3.

However, significant decerase trend of S_r was observed with more error-prone

PCR cyles were introduced. Considering the S_m values of ePCR#5 and

ePCR#6 are still very high, the decrease of S_r is mainly caused by massive

base errors introduced. Although the S_r value of ePCR#6 (93.2%) is relatively

lower than the other samples, with the 10.5% strand redundancy codes, we

can recover the encoded data correctly by the outer fountain codes.

Interestingly, the maximal decoding rate (S_m) of ePCR#6 was estimated to be

up to 99.2%, which was just slightly decreased. In future studies, incorporation

of advanced codes designed for de Bruijn graph-based decoding could further

enhance the strand recovery rate up to 99.2%.

To further prove the robustness of DBG-GPS, we perform random

sub-sampling experiments on the sequencing results of ePCR#1 and ePCR#2

with different coverages, *i.e.* reading copies, range from 1 to 256. The *k-mer*

dropout rates, K_d, noise indicator K_n and S_r in different coverages were

calculated corresponding. For each coverage tested, 12 independent random

sub-sampling experiments were performed and the average values of

estimated K_d, K_n and S_r are presented. As shown in **Fig. 5a**, as expected,

the K_n values of ePCR#2 are higher than ePCR#1, indicating high rates of

errors were introduced to ePCR#2. The K_n differences of the two samples

become more and more significant when increasing the coverages. The K_d

value of ePCR#2 is higher than the K_d value of ePCR#1. The K_d values of

the two samples dropped quickly while increasing the coverages from 1 to 256.

As shown in **Fig. 5b**, the two samples can be reliably decoded at low

coverages (coverage 16 for ePCR#1, coverage 24 for ePCR#2).

403 **Massive parallel retrieval test with unspecific amplification PCR products**

404 For practical data storage, massive multiple retrievals to test the data

405 robustness is required. However, only a limited number of retrievals is tested

406 for DNA data storage yet. To achieve reliable data storage with multiple

407 retrievals, the occasionally emerged unspecific amplification problem of PCR

408 needs to be handled. As shown by the deep error-prone PCR experiments,

409 DBG-GPS based decoding can work with PCR with products with unspecific

410 amplifications. To further prove its robustness in handling unspecific

411 amplification, as well as the robustness of DNA data storage under multiple

412 reading, we performed 100 times of parallel data retrievals with PCR products

413 with serious intended unspecific amplifications. As shown in **Fig. 3**, we first

414 performed one round of PCR amplification with Taq DNA polymerase with a

415 total volume of 100 µl. Then, 100 parallel PCR amplification was performed

416 using 1 µl of the first round PCR reaction mixtures without purification. The

417 purification step is removed in purpose of enhancing unspecific amplification.

418 The 100 PCR samples were then sequenced by Illumina sequencing platform

419 and the sequencing results are committed for data decoding with DBG-GPS.

420 Although all PCR products show serious unspecific amplifications as expected

421 (**Fig. 6a**), DBG-GPS achieves high-quality strand recoveries on all of them as

422 shown by **Fig. 6b**. The S_m values are estimated to be in the range of 99.44% to

423 99.78%. The strand recovery rates S_r obtained by DBG-GPS are in range of

424 98.45% to 99.02%, suggesting a robust mechanism in handling unspecific

425 amplification problem.

Reliable data recovery with seriously degraded DNA samples

Different from the previously reported codec systems, which require complete DNA strands for decoding, the decoding process of DBG-GPS utilizes very short *k*-mer fragments. Thus, DBG-GPS can be utilized for data decoding with degraded DNA samples, of which massive truncated DNA strands caused by strand breaks. To verify the capability of DBG-GPS with degraded DNA samples, we performed accelerated aging experiments as shown in **Fig. 3c**. We first amplified the master pool with Taq DNA polymerase. Two liquid samples of 50 μl of the amplified Taq PCR products were accelerated aged at 70℃ for one and two weeks respectively. The accelerated aged samples were sequenced with Illumina sequencing platform. As shown by the analysis results of Agilent 2100 Bioanalyzer (**Fig. 7b** and **c**), the two DNA samples show serious degradation. Such degree of degradation would totally destroy the encoded data with previous reported codec systems. Dramatically, with DBG-GPS based decoding, accurate data decoding was achieved on both samples with high quality (>99% strand recovery, **Fig. 7d**). It worth mention that the DNA sample that accelerated aged at 70℃ for two weeks shows no obvious peak at the 200bp, indicating most of DNA strands are corrupted. The high-quality decoding with the two samples well proved the capacity of DBG-GPS in handling DNA degradation.

Exploration of DBG-GPS's capacity by large-scale simulations

To further test DBG-GPS's performance with large-scale data sets, large-scale simulations were also performed. An Ubuntu server 20.10 installation disk

image (~ 1 GB) was used as the input file for the generation of DNA droplets.

Each DNA droplet was set to carry 60 bytes of information with a total length of

316 bp, around the technical limits of current DNA synthesis technologies. We

first tried with ten million DNA droplets, representing a data scale of 600

megabytes (MB). With an expected copy number of 50, error rate of 4%

(approximately 2% substitutions, 1% insertions, 1% deletions), a 155 GB

sequence file was generated. However, although a computation workstation

equipped with 640 GB memories is employed, the k-mer counting step by

Jellyfish encountered memory limitations. We then reduced the DNA droplet

number to five million, representing a data size of 300 MB. Preliminary

decoding simulations on this data scale reveal a problem of long decoding time.

Detailed analysis shows that this is due to the entangled DNA strands caused

by repeated presentation of k-mers in different strands. To solve this problem,

we propose two strategies. The first strategy is applying a filtering process

during the production of DNA droplets to filter out the seriously entangled DNA

strands. The second strategy is setting a path number boundary for greedy

path search. If the greedy path search engine finds more paths than this value,

it aborts search. This will reduce the strand decoding rate theoretically. We run

the simulations with 5 million DNA droplets three times independently. On

average 4,971,880 DNA droplets (recovery rate = 99.44%) were successfully

recovered.

Conclusions

DNA data channel is unique with massive 'data repetition' in the forms of

multiple error-rich strands. Efficient mechanism that can utilize this data

'repetition' feature for robust data storage is still missing due to the challenge

of handling the massive errors, especially indels. Furthermore, the PCR-based

strand amplification and storage of DNA molecules can lead to critical issues of

strand rearrangement and strand break. In this study, we developed an

effective mechanism, named 'DBG-GPS', that can well handle these problems

by efficient strand reconstruction from multiple, error-rich sequences based on

de Bruijn graph. DBG-GPS is applicable for all kinds of molecular data storage

using any kind of polymers, *e.g.* DNA data storage with extended alphabets of

non-natural nucleotides. Unlike previous studies, DBG-GPS can directly

construct the DNA strands without computation-intensive clustering and

multi-alignment process which cannot scale up well. Strategies of low

coverage *k*-mers elimination, CRC codes, and both-way search were

introduced and solved the decoding challenges caused by base errors. While

traditional EC show difficulties in handling indels, DBG-GPS can efficiently

correct high rates (10%) errors of indels, as well as substitutions. More errors

can be corrected by incorporating more sequences for decoding. Importantly,

by the strand reconstruction mechanism with short *k*-mers, DBG-GPS

achieves reliable data recovery with unspecific amplification PCR products and

highly degraded DNA samples. These achievements greatly enhanced the

robustness of DNA data storage. This new mechanism, in combination with the

previous reported methods of protecting DNAs by silicon beads[8],

nanoparticles[26], and alkaline salts[14], could easily enable robust data storage in

DNA for over ten thousands of years even in room temperature. Furthermore,

despite Python scripts were utilized in this study, DBG-GPS shows more than

100 times faster than the CL-MA based methods. The linear decoding

complexity revealed by simulations makes DBG-GPS a potential solution for

large-scale DNA data storage. Although DBG-GPS based decoding shows

great potentials in DNA data storage, the pure python implementation, is far

from optimal. The simple hash dictionary-based data structure for *k*-mer

retrieval is memory intensive. Although no theoretical limitation on the data

scale is shown with DBG-GPS, we failed to simulate with 500MB data on a

computational workstation with 640 GB memories installed due to memory

limitation. *C++* implementation with a more advanced *k*-mer data structure is

expected to significantly reduce the memory cost, as well as decoding time[27,28].

Further studies on the design of error correction codes that can incorporate

with the noise *k*-mers elimination can further boost the capacity of DBG-GPS.

Methods

Library design, PCR and Sequencing

A DNA library of 12,000 oligonucleotides in length of 200 nt was synthesized

by Twist Biosciences. Error-prone PCR was performed with Controlled

Error-prone PCR Kit, TIANDZ, CAT#:160903-100. Thermo cycle parameters

were 94□ for 3 mins, 94□ for 1min, 45□ for 1min, 72□ for 1min, 30 cycles. Six

series error-prone PCR were performed to introduce high rates of errors. The

first round ePCR utilized 0.6 µl samples of the master pool as templates. The

five following ePCR use 1 µl products of the previous round ePCR as

templates. All PCR experiments were performed with the following primers:

P1-'CCTGCAGAGTAGCATGTC', P2- 'CGGATGCATCAGTGTCAG'. The

PCR products were sequenced by Tianjin Novogene Sequencing Center &

Clinical Lab. Sequencing libraries were generated with purified PCR products

using Illumina TruSeq DNA PCR-Free Library Preparation Kit (Illumina, USA)

following manufacturer's recommendations and index codes were added. For

the products of the second-round error-prone PCR with very large DNA

strands, DNase digestion is applied to break the long strands into small

fragments around 200~300 bp. After digestion, all fragments are collected for

further library construction using the protocol as just described. The library

quality was assessed on the Qubit@ 2.0 Fluorometer (Thermo Scientific) and

Agilent Bioanalyzer 2100 system. All the libraries were sequenced on Illumina

HiSeq platform and 150 bp paired-end reads were generated.

_k_-mers counting and elimination of low coverage _k_-mers

The python implementation provided in this study used simple hash dictionary

structure for counting of k-mers. De Bruijn graph is quite memory expensive.

which is not memory efficient. Thus, although the scripts implemented with

functions to read the common nucleotide sequence files_, i.e._ FastQ or FastA,

and count the _k_-mers accordingly, for large data sets, we strongly suggest to

use a professional _k_-mer counting system, _e.g._ Jellyfish[27], which is much more

memory efficient and multi-core supporting. To count _k_-mers by the python

scripts, please call the following functions of DeBruijnGraph() object: for

reading and counting of FastQ file, use DeBruijnGraph-openFastQ('file name');

for reading and counting of Fasta file, use DeBruijnGraph-openFasta('file

name').

For elimination of low coverage _k_-mers, call function DeBruijnGraph-

remove_low_cov_kmers(_n_), then all _k_-mers with coverages lower than _n_ will be

removed. For usage of Jellyfish for counting of _k_-mers and dumping of _k_-mers

satisfying the criteria, please refer to the Jellyfish manual, which is available at

(http://www.cbcb.umd.edu/software/jellyfish/). The dumped *k*-mers can be

introduced to the DeBruijnGraph() object using DeBruijnGraph-openDump('file

name') function for further decoding test.

Choice of *k*-mer size

Obviously, with specific *k*-mer size, the data scale can be decoded is limited.

For example, it is clearly that only very small amount of data can be decoded

with an extremely short *k*-mer size of three. However, the mathematical

answer to this question is yet unsolved. In de Bruijn Graph theory, for each

k-mer, the front *k*-1 bases were used for positioning (*i.e.* indexing), and the one

base at the terminal was used for extension of path, *i.e.* for encoding of data.

Thus, we estimate the decoding capacity (p) of *k*-mers with a specific size of k

as follows:

$$p = 4^{k-1} \times 2bits$$

Where 4^{k-1} is the combination number of possible indexes with a length of

$k-1$, 2 bits stands for the encoding capacity of one base at the tail. Based on

this formula, the decoding capacities of different *k*-mer sizes were calculated

and listed in **Tab. S3**. As shown in the table, the decoding capacity is estimated

to be around 57.6 PB with a *k*-mer size of 30, and 6×10^5 EB for *k*-mer size of

40, indicating a capable method for large-scale data decoding. Additionally, it

should be noticed that, due to the repeated presentations of identical *k*-mers in

different DNA strands, the actual data scale can be higher than this estimation.

However, to avoid decoding troubles with entangled DNA strands by repeated

k-mers, we strongly recommend to use a *k*-mer size with a decoding capacity

at least ten times larger than the actually encoded data.

Details of greedy path search

The greedy search process was illustrated in **Fig. S4**. The details are

described as follows: **Step 1**, Select an index, *e.g.* 562451, and calculate the

anchor value by the Python pseudorandom function using the index value as

seed in case of both-way search mode. An anchor value of 47736 is obtained

in the case of 562451. **Step 2**, Encode the index into DNA string based on the

corresponding binary string, *i.e.* 562451 = 10001001010100010011=

ATATATGGGATCAGAA. Similarly, the anchor of 47736 is encoded into DNA

string of ATATATATGCGTTTGG in case of both way search. The greedy path

search start with ATATATGGGATCAGAA as initial path. Similarly, the tail

search start with ATATATATGCGTTTGG as initial path in case of both-way

search. **Step 3.** Judgement step. This step is for selection of an end with few

path numbers for extension of paths. **Step 4**, Extension of paths on the end

with fewer path number. **Step 5**, Judgement step. This step is for judge if the

path search has finished. **Step 6**, This step is specifically required for both-way

search mode. The head paths are fused with tail paths if the overlap

sequences are identical. For one-way search this step is not required. **Step 7**,

Encode the complete paths into binary string. Perform parity checks and drop

the wrong routes using the embedded CRC codes. For other EC codes applied,

use the checking mechanism correspondingly. **Step 8**, Judgement step. Check

if there is only one path passed the CRC checking. If it is true, choose it as

decoded strands, otherwise, mark a missing strand for this index. If multiple

routes or no routes pass the CRC codes, the searching-based decoding fails.

Only in case of one route passed the CRC checking, the decoding succeeds.

Step 9*,* Judgement step. Judge if the search finished. If not, iterate *step 1* to

step 9 until all index are searched for possible strands. If yes, finish the inner

decoding process. The DeBruijnGraph() was implemented to search in

both-way mode by default. To active the one-way search mode, switch the

value of DeBruijnGraph() ->dual_search to 'False'.

Simplified error analysis in concept of de Bruijn graph theory

Although distribution profiles of error rate and copy number among different

strands shapes the DNA data quality, they cannot reflect the data quality

straightforwardly. Additionally, the sequence error rate is complicated for

accurate accounting. For better estimation of the qualities of DNA data and

simplification of the error analysis process in concept of de Bruijn graph theory,

here we introduce two indicators, *i.e.* K_d (in range of 0 to 1) and K_n (in range

of one to 4^k), which together can well define the data quality. The K_d stands

for dropout rate of all correct *k*-mers and K_n is the ratio of noise *k*-mers and

correct *k*-mers. DNA data with a K_d close to 1 and a K_n close to 0 stands for

a high-quality data with high data coverage rate and low noises. Other than

error rate which is complicated for accounting, K_d and K_n can be easily

calculated by the following formulas:

$$K_d = K_{lost}/K_{ori} \qquad\qquad 1$$

$$K_n = K_{all}/K_{corr} \qquad\qquad 2$$

In formula 1, K_{ori} stands for the number of *k*-mers in the original encoded

sequences and K_{lost} stands for the number of *k*-mers that presented in the

original encoded sequences but not presented in the sequencing results. In

formula 2, K_{all} stands for the number of *k*-mers in the sequencing results and

K_{corr} stands for the number of correct *k*-mers, *i.e. k*-mers that presented in the

original encoded sequences. DNA data with a K_d close to 1 and a K_n close

to 0 stands for a high-quality data with high data integrity and low noises. The

maximal strand decoding rate S_m is determined by K_d. With specific K_d, the

actual strand decoding rate S_r is affected by the value of K_n. The greedy path

search becomes extremely slow when decoding DNA data with higher K_n

values, due to too many possible paths for each strand. The DBG-GPS will

stop decoding if the path number exceed specific threshold. In this

proof-of-concept study, we use 100 for fast decoding, 1,000 for high-quality

decoding.

Details of the implementation of fountain codes

The   outer   fountain   codes   in   Python   is   modified   from

https://github.com/dbieber/fountaincode. DNAFountain   and   DNADroplet

objects were implemented for handling of DNA strings. The assignment

mechanism of the random degrees and chunk indexes of the Droplet object

were modified to support DBG-GPS based decoding. Luby transform is

applied for generation of random degrees. Specific index encoded in the DNA

Droplet is used for selection of a degree from a pre-generated degree table.

This index is also used as seed for generation of the random strand

combination. The decoding process of the original Glass object is improved.

Details of simulation experiments

Simulations for investigation of the potentials of de Bruijn graph were performed with 10,000 DNA strands generated by the fountain codes with a strand length of 320 bp. For de Bruijn graph construction, a k-mer size of 18 was applied supporting a data scale of ~4 GB theoretically.

For the large-scale simulations, an Ubuntu Server 20.10 live install disk image (MD5: f51594d36008c456cf0360aeadd130d6, size: 1 GB) was used as input file for generation of random DNA droplets. Each DNA droplet was set to encode 60 bytes of data and two bytes of CRC codes. The length of index and anchor are both set to four bytes. Primers of P1-'CCTGCAGAGTAGCATGTC' and P2- 'CGGATGCATCAGTGTCAG' were added to the ends. This will result with a DNA droplet length of 300 bp, around the theoretical limits of current DNA synthesis technologies. To avoid of entangled DNA strands, a filter process that always discard the DNA droplets contains a k-1 mer that already presents more than four times was applied to the droplet generating stage. For counting of k-mers by Jellyfish, a k-mer size of 24, and k-mer coverage cut-off of five, *i.e.* all k-mers with a coverage less than five is discarded, was applied.

Data Availability

All the algorithms proposed in this study were implemented with Python and the source code is available at https://switch-codes.coding.net/p/switch-codes/d/DNA-Fountain-De-Bruijn-De coding/git/tree/ForPublication.

The compressed file in size of 314 KB is available at:

https://switch-codes.coding.net/public/switch-codes/DNA-Fountain-De-Bruijn-

Decoding/git/files/master/input_files/314kb.rar.

The encoded files include:

Two famous talks, "I Have a Dream" from Martin Luther King and William

Faulkner's speech of accepting the Nobel Prize in literature, as well as four

pictures (two pictures of IBM RAMAC 350, one picture of the front page of

"Molecular Structure of Nucleic Acids", and one picture of Oracle) were

compressed into one binary file of 314kb with free version of WinRAR

(http://www.winrar.com/).

Sequencing reads of deep error-prone PCR experiments:

https://pan.baidu.com/s/1xi-sY6erk-jfZ81ygJJmzA (ePCR#1, fetch codes:

ATGC, MD5: 8690080a5081a963150e2f29fe3beafb)

https://pan.baidu.com/s/1Go0o6_gwrLnsGX1ZJicqTw (ePCR#2, fetch codes:

ATGC, MD5: b5526124551f449775aa7f0ad5a239b7)

https://pan.baidu.com/s/10edj1eeT1VPAm5wHjoNgyA (ePCR#3, fetch codes:

ATGC, MD5: 03a6c119dca076dd8db374ec7970d269)

https://pan.baidu.com/s/1DX8bODrUVSf9ceM2tyL5Vw (ePCR#4, fetch codes:

ATGC, MD5: 61bdfcb77c1735483776d072da69f5b9)

https://pan.baidu.com/s/1otVqB60PnEK_lCTaB9N8AQ (ePCR#5, fetch codes:

ATGC, MD5: c63cbd86ca7441382a62bb5b648b012f)

https://pan.baidu.com/s/1h9CapXHfORi6wNEnj3LYLg (ePCR#6, fetch codes:

ATGC, MD5: d7bffa155719aec7aea6f5162c719a32)

Sequencing reads of accelerated aging experiments:

https://pan.baidu.com/s/1fi4hEOiNser1bKHmqSS9mg (Control, fetch codes:

ATGC, MD5: eae7a080e5bbcb8c57a9f8359b032622)

https://pan.baidu.com/s/1XAGfCL0fzENED6mb7pV3zg (70℃ for one week,

fetch codes: ATGC, MD5: 5274eb78f640aef7b45c0382217901d4)

https://pan.baidu.com/s/1X3u9TBnLlTg39AXuHbks-Q (70℃ for two weeks,

fetch codes: ATGC, MD5: 9fc954c37a57dfea67a95b44193acaa7)

Sequencing reads of 100 parallel retrievals:

https://pan.baidu.com/s/1BmEh6RZvSR7sQyTOB8pA-w (1-20, fetch codes:

ATGC, MD5: fddf5f1811332da8ba0f5cd6f2ec7921)

https://pan.baidu.com/s/1vOoI_6V_iW8lO0J-CW84Gw (21-40, fetch codes:

ATGC, MD5: f31fa5cdb6d8d00c55804bbe3f3e2214)

https://pan.baidu.com/s/1Yhzk9__WdFnV2NRup6ynDA (41-60, fetch codes:

ATGC, MD5: 414b082eee36f1ce1996bd23014dd567)

https://pan.baidu.com/s/193erX4g9S5-mVYeNiV06YQ (61-80, fetch codes:

ATGC, MD5: a4bffa7e8595c0afab78f2c5f5d9de1c)

https://pan.baidu.com/s/1fPYyIJ8kmuQpWh2sON-RwQ (81-100, fetch codes:

ATGC, MD5: 789eecd1c452163391ffbe30fc30efc9)

Acknowledgements

704 This work was supported by Seed Foundation of Tianjin University and Natural
705 Science Foundation of Shandong Province (ZR2017LC006). The authors
706 would like to thank Dr. Sheng Ye and Dr. Weigang Chen for their constructive
707 comments in improving the manuscript.

Competing interests

709 A patent has been filed for the DBG-GPS based decoding method presented in
710 this study.

Author contributions

712 LFS proposed the idea, wrote the Python codes, designed the experiments,
713 performed the simulations, and analysed the data. FG helped with experiment
714 design and data analysis. ZYG performed the error-prone PCR experiments.
715 BZL and YJY supervised the whole work.

References

References

1. Tabatabaei, S. K. *et al.* DNA punch cards for storing data on native DNA
sequences via enzymatic nicking. *Nature communications* **11,** 1742;
10.1038/s41467-020-15588-z (2020).

2. Zhirnov, V., Zadegan, R. M., Sandhu, G. S., Church, G. M. & Hughes, W. L.
Nucleic acid memory. *Nature materials* **15,** 366–370; 10.1038/nmat4594
(2016).

3. Church, G. M., Gao, Y. & Kosuri, S. Next-generation digital information
storage in DNA. *Science (New York, N.Y.)* **337,** 1628;
10.1126/science.1226355 (2012).

4. Ceze, L., Nivala, J. & Strauss, K. Molecular digital data storage using DNA.
Nature reviews. Genetics **20,** 456–466; 10.1038/s41576-019-0125-3
(2019).

5. Ping, Z. *et al.* Carbon-based archiving: current progress and future
prospects of DNA-based data storage. *GigaScience* **8**;
10.1093/gigascience/giz075 (2019).

6. Chen, W. *et al.* An artificial chromosome for data storage. *National Science
Review*; 10.1093/nsr/nwab028 (2021).

7. Gao, Y. *et al. Low-Bias Amplification for Robust DNA Data Readout* (2020).

8. Grass, R. N., Heckel, R., Puddu, M., Paunescu, D. & Stark, W. J. Robust

chemical preservation of digital information on DNA in silica with

error-correcting codes. *Angewandte Chemie (International ed. in English)*

54, 2552–2555; 10.1002/anie.201411378 (2015).

9. Erlich, Y. & Zielinski, D. DNA Fountain enables a robust and efficient

storage architecture. *Science (New York, N.Y.)* **355,** 950–954;

10.1126/science.aaj2038 (2017).

10. Organick, L. *et al.* Random access in large-scale DNA data storage. *Nature*

biotechnology **36,** 242–248; 10.1038/nbt.4079 (2018).

11. Press, W. H., Hawkins, J. A., Jones, S. K., Schaub, J. M. & Finkelstein, I. J.

HEDGES error-correcting code for DNA storage corrects indels and allows

sequence constraints. *Proceedings of the National Academy of Sciences of*

the United States of America **117,** 18489–18496;

10.1073/pnas.2004821117 (2020).

12. An, R. *et al.* Non-enzymatic depurination of nucleic acids: factors and

mechanisms. *PloS one* **9,** e115950; 10.1371/journal.pone.0115950 (2014).

13. Zupanič Pajnič, I. *et al.* On the long term storage of forensic DNA in water.

Forensic science international **305,** 110031;

10.1016/j.forsciint.2019.110031 (2019).

14. Kohll, A. X. *et al.* Stabilizing synthetic DNA for long-term data storage with

earth alkaline salts. *Chemical communications (Cambridge, England)* **56,**

3613–3616; 10.1039/d0cc00222d (2020).

15. Song, L. & Zeng, A.-P. Orthogonal Information Encoding in Living Cells with

High Error-Tolerance, Safety, and Fidelity. *ACS synthetic biology* **7,**

866–874; 10.1021/acssynbio.7b00382 (2018).

16. Anavy, L., Vaknin, I., Atar, O., Amit, R. & Yakhini, Z. Data storage in DNA

with fewer synthesis cycles using composite DNA letters. *Nature*

biotechnology; 10.1038/s41587-019-0240-x (2019).

17. Chen, Y.-J. *et al.* Quantifying molecular bias in DNA data storage. *Nature*

communications **11,** 3264; 10.1038/s41467-020-16958-3 (2020).

18. Brakensiek, J., Guruswami, V. & Zbarsky, S. Efficient Low-Redundancy

Codes for Correcting Multiple Deletions. In *Proceedings of the*

Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms,

edited by R. Krauthgamer (Society for Industrial and Applied Mathematics,

Philadelphia, PA, 012016), pp. 1884–1892.

19. Smagloy, I., Welter, L., Wachter-Zeh, A. & Yaakobi, E. Single-Deletion

Single-Substitution Correcting Codes. In *2020 IEEE International*

Symposium on Information Theory (ISIT) (IEEESunday, June 21, 2020 -

Friday, June 26, 2020), pp. 775–780.

20. Zerbino, D. R. & Birney, E. Velvet: algorithms for de novo short read

assembly using de Bruijn graphs. *Genome research* **18,** 821–829;

10.1101/gr.074492.107 (2008).

21. Pevzner, P. A., Tang, H. & Waterman, M. S. An Eulerian path approach to

DNA fragment assembly. *Proceedings of the National Academy of Sciences*

of the United States of America **98,** 9748–9753; 10.1073/pnas.171285098

(2001).

22. Heckel, R., Mikutis, G. & Grass, R. N. A Characterization of the DNA Data

Storage Channel. *Scientific reports* **9,** 9663; 10.1038/s41598-019-45832-6

(2019).

23. Cyrus Rashtchian *et al.* Clustering Billions of Reads for DNA Data Storage.

24. Antkowiak, P. L. *et al.* Low cost DNA data storage using photolithographic

synthesis and advanced information reconstruction and error correction.

Nature communications **11,** 5345; 10.1038/s41467-020-19148-3 (2020).

25. Edgar, R. C. MUSCLE: multiple sequence alignment with high accuracy

and high throughput. *Nucleic acids research* **32,** 1792–1797;

10.1093/nar/gkh340 (2004).

26. Chen, W. D. *et al.* Combining Data Longevity with High Storage

Capacity—Layer-by-Layer DNA Encapsulated in Magnetic Nanoparticles.

Adv. Funct. Mater. **29,** 1901672; 10.1002/adfm.201901672 (2019).

27. Marçais, G. & Kingsford, C. A fast, lock-free approach for efficient parallel

counting of occurrences of k-mers. *Bioinformatics (Oxford, England)* **27,**

764–770; 10.1093/bioinformatics/btr011 (2011).

28. Pandey, P., Bender, M. A., Johnson, R., Patro, R. & Berger, B. Squeakr: an

exact and approximate k-mer counting system. *Bioinformatics (Oxford,*

England) **34,** 568–575; 10.1093/bioinformatics/btx636 (2018).

Fig. 1: Potentials of de Bruijn graph-based decoding. a, Representations of base substitutions and indels in de Bruijn graph. *i,*
Simple de Bruijn graph constructed from 12bp sequence of "AACGGCGGCTGT" with four copies with a *k*-mer size of four. The
circles stand for the *k*-mers and the numbers inside the circles are coverages of corresponding *k*-mers in all graphs. *ii,* De Bruijn
graph with one substitution in sequence #2; *iii,* De Bruijn graph with one insertion and one deletion on sequence #2 and #3
respectively; *iv,* De Bruijn graph with four strand breaks. **b,** Estimated maximal strand decoding rates (S_m) of different types and
rates of errors with 20 sequence copies; Random errors were introduced with specific type and rate of errors from 1% to 10% with a
step size of 1%. The error-rich sequences generated were then used for construction of the de Bruijn graph. The integrity of the
correct paths was checked. This process is iterated for five times and the average S_m values are shown. The standard derivations,
which are too small to be shown, are detailed in **Tab. S1**. **c,** S_m values estimated with different sequence copies and rates of mixture
errors (50% substitutions, 25% insertions and 25% deletions). Sequence copies in range of 1 to 100 with a step size of 5, mixture
error rates in range of 1% to 10% with a step length of 1% were considered. The maximal strand recovery rates (S_m) are the rates of
DNA strands with complete paths in the graph during simulations. A S_m value > 99% was obtained with merely sixty sequence copies
as shown by the dashed red line.

Fig. 2: Framework of DBG-GPS and its integration with outer erasure codes.

a, A proposed four-step framework for de Bruijn graph-based strand decoding with multiple error-rich sequences: ***Step 1***.

Construction of de Bruijn Graph; ***Step 2***. Elimination of noise k-mers; ***Step 3***. Greedy path search; ***Step 4***. Path selection by EC

codes. **b,** Proposed structure of the DNA strand for DBG-GPS. There are four parts in the designed DNA strand: **A1** – The

index/seed of the DNA strand; **A2** – Data payload for encoding of data; **A3** – Cyclic Redundancy Check codes (CRC) for selection of

the correct path if multiple paths were found; **A4** – Anchor cods which can be calculated by specific function based on the value of

A1. **A4** enables both-way search mode which is optional. **c,** Integration of DBG-GPS with outer erasure codes. DBG-GPS is a full

resolution for inner code decoding which can be easily combined with erasure codes, *e.g.* fountain codes, RS codes.

Fig. 3 Experimental verification of the robustness of DBG-GPS. **a**, Procedure of the series deep error-prone PCR experiments. **b**, Multiple retrieval test with unspecific amplification PCR products. **c**, Accelerated aging experiments. These three experiments were performed with focus of indels, strand rearrangements and strand breaks respectively. Although super harsh conditions were applied, we could decode the original data correctly in all cases presented.

Fig. 4 Reliable data recovery with deep error-prone PCR products. a,
Agarose electrophoresis analysis of the series error-prone PCR (ePCR)
products. The first-round ePCR (#1) using 0.6 µl sample of master pool as
templates. The following series ePCR used 1 µl of previous round PCR
products as templates. The six ePCR were performed with highest error rate
setting of 8 errors per 1,000 bp for each amplification cycle. *Note, the length of*
initially synthesized ssDNA is 200bp. **b**, Reliable strand reconstruction with low
quality ePCR products. The dashed red line stands for the decoding lower
boundary of the outer fountain codes in this case study. After 180 cycles (30
cycles × 6 = 180 cycles) of error-prone amplifications, the data still can be
correctly decoded using DBG-GPS.

 Fig. 5 Low-coverage decoding by random sub-sampling of sequencing reads.

 All sequencing reads of each sample are used for random sub-sampling individually. For each coverage tested, we run 12 times of

 independent sub-sampling and the averages values were presented. The standard deviations are too small to be visualized.

 Coverages in range of 1 to 256 were considered. The average strand recovery rates (S_r), k-mer dropout rates (K_d) and K_n values

 were presented. **a**, K_d and K_n values. **b**, S_r values. The dashed curves in **b** are the strand recovery results without elimination of low

 coverage k-mers. The horizontal dashed red line stands for the decoding limits by the outer Fountain codes. The blue dashed lines

 with arrows point out the data points that a k-mer elimination process was applied. The numbered red arrows show the coverages

 required by the two data sets for reliable data recovery by the outer Fountain codes.

Fig. 6 Massive multiple retrieval test using PCR products with massive
unspecific amplifications. a, Agarose electrophoresis analysis of the parallel
PCR products. All PCR samples show similar results. Thus, only 20 of the total
100 samples are presented. **b**, Strand decoding results of the 100 retrievals
using DBG-GPS. All samples show high quality strand decoding which support
accurate data retrieval.

Fig. 7 Reliable data retrieval with accelerated aged DNA samples. a, **b**, and **c** are DNA integrity analysis results of DNA samples without accelerated aging, accelerated aged for one week, and accelerated aged for two weeks respectively. **d**, strand recovery results of the three samples. Although the integrity of the DNA strands was damaged seriously after accelerated aged at 70℃ for two weeks as shown in figure **c**, high strand recovery rate ($S_r > 99\%$) was achieved by DBG-GPS based decoding. Indeed, no significant differences could be observed between the three samples, suggesting a robust decoding mechanism against DNA degradation.

Tab. 1 Decoding speed of DBG-GPS in comparison with clustering and multi-alignment (CL-MA) based method.
The simulations were performed with 10,000 DNA strands in length of 300 bp. For each strand, fifty strand copies with an error rate of 4% were generated and utilized for decoding. The time of clustering stage in CL-MA based decoding was estimated based on a recent study by Cyrus Rashtchian *et al.*[23] The consensus calling stage used majority voting algorithm same as the recent study by Antkowiak, P.L. *et al.*[24] DBG-GPS shows more than 100 times faster than CL-MA methods (3890.26s/37.47s ≈103.82).

DBG-GPS		CL-MA	
Stages	**Time**	**Stages**	**Time**
***k*-mer counting** *(Jellyfish 32 threats)*	0.63 ± 0.04s	**Clustering**[23] *(32 threats)*	~0.36s
Strand decoding *(Python Script)*	**36.84 ± 0.91s**	**Multi-alignment** *(Muscle*[25]*, IO time subtracted)*	**3874.48 ± 30.82s**
		Consensus calling *(Majority voting, Python*[24] *)*	15.42 ± 0.40s
Total	37.47 ± 0.95s	**Total**	~3890.26 ± 31.22s

Supplementary materials

Fig. S1 Traditional error correction codes cannot well handle indels due to the base shift problem. Erasure codes are designed for errors of unreadable data blocks without data shift issues. To correct indels by erasure codes, two-dimensional erasure codes must be applied. However, one indel in one dimension will lead to many substitution errors that have to be corrected by EC codes in another dimension. This leads to low efficiency of such strategy.

Fig. S2 Path search complexity caused by base errors can be remarkably
released by elimination of low coverage *k*-mers. a – Massive noise *k*-mers
introduced increase the de Bruijn graph scale remarkably. b - Greedy path
search burden caused by noise *k*-mers can be remarkably reduced by
elimination of low coverage *k*-mers. The number of paths found and search
time increased exponentially as increasing the rates of errors (b-*i*) or the
number of sequence copies (b-*ii*); The greedy search time and revealed
number of paths decreased remarkably after elimination of low coverage
k-mers (b-*iii* and b-*iv*). **c**, Coverage distributions of correct *k*-mers and noise
k-mers revealed by monte carlo simulation. The simulation is performed with
10,000 DNA strands, a λ value (i.e. the expectation value) of 50 for strand
copies, a base error rate of 4%.

Fig. S3 Both-way search strategy shows fast decoding than one-way
search. The simulation is performed with 10,000 DNA droplets. 100 sequence
copies with random base errors in rates of 10% are generated for decoding
test.

Fig. S4 Details of de Bruijn graph-based greedy searching algorithms.

The detailed description is presented in **Methods** section.

Fig. S5 Linear decoding complexity of DBG-GPS. a, Average decoding time
per DNA strand. **b**, Linear fitting of decoding times with data scales.

Tab. S1 Computational estimation of the maximal strand decoding rates (S_m) of different types and rates of errors with 20

strand copies.

Error Rates	Substitutions		Insertions		Deletions		Strand Breaks	
	S_m	SD	S_m	SD	S_m	SD	S_m	SD
1%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%
2%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%
3%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%
4%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%	100.0%	0.0%
5%	99.6%	0.1%	99.9%	0.1%	99.7%	0.1%	99.8%	0.0%
6%	96.7%	0.1%	98.7%	0.1%	97.3%	0.1%	98.1%	0.2%
7%	84.6%	0.3%	93.3%	0.3%	87.9%	0.1%	90.2%	0.3%
8%	58.7%	0.4%	77.0%	0.4%	64.7%	0.2%	70.0%	0.3%
9%	26.9%	0.6%	49.2%	0.8%	33.6%	0.5%	39.6%	0.3%
10%	7.3%	0.2%	21.0%	0.3%	10.6%	0.6%	13.7%	0.3%

Tab. S2 Performance of four-step DBG-GPS algorithms estimated by
Monte-Carlo simulations. The simulations were performed with 10,000 DNA
droplets produced by DNA fountain codes. For each DNA droplet strand, sixty
error-rich copies were generated with variant error rates in range of 1% to 10%
with a step length of 1%. For specific error rate considered, all simulated
error-rich DNA strand sequences were submitted to the python implementation
of DBG-GPS for strand decoding. Ten individual simulations were performed
for each error rates. The average maximal strand recovery rates (S_m), and
strand recovery rates (S_r) of DBG-GPS are listed.

Error rates	S_m	S_r
1%	100.00±0.00%	99.99±%
2%	100.00±0.00%	99.98±%
3%	100.00±0.00%	99.83±%
4%	100.00±0.00%	99.55±%
5%	100.00±0.00%	99.61±%
6%	100.00±0.00%	99.60±%
7%	100.00±0.00%	99.65±%
8%	99.99±0.01%	99.55±%
9%	99.96±0.02%	99.16±%
10%	99.70±0.07%	96.71±%

930 **Tab. S3 Theoretical decoding limits of DBG-GPS with different *k*-mers**
931 **sizes.** The formula used for decoding capacity estimation was described in
932 **Method** section.

k-mer sizes	10	20	30	40
Theoretical decoding limits	0.5 MB	0.55 TB	57.6 PB	6×10^5 EB

936 **Tab. S4 Details of data retrieval results of deep ePCR experiments.**

	Total reads	S_m	S_r
ePCR#1	19,972,663	100%	99.8% (11,978/12,000)
ePCR#2	17,430,377	100%	99.4% (11,928/12,000)
ePCR#3	17,075,696	100%	98.4% (11,808/12,000)
ePCR#4	20,614,695	99.9%	98.0% (11,764/12,000)
ePCR#5	16,651,758	99.8%	95.2% (11,420/12,000)
ePCR#6	18,281,133	99.2%	93.2% (11,179/12,000)