Analogous computations in working memory input, output and motor gating:

Electrophysiological and computational modeling evidence

Rachel Rac-Lubashevsky and Michael J. Frank

Affiliations:

Rachel Rac-Lubashevsky, Brown Institute for Brain Sciences, Department of Cognitive

Linguistic and Psychological Science, Brown University.

Michael J. Frank, Brown Institute for Brain Sciences, Department of Cognitive Linguistic

and Psychological Science, Brown University.

Corresponding author:

Rachel Rac-Lubashevsky

Department of Cognitive, Linguistic & Psychological Sciences

Brown University

190 Thayer St

Providence RI 02912-1821

Email: rac.hunrachel@gmail.com

Abstract

Adaptive cognitive-control is achieved through a hierarchical cortico-striatal gating system that supports selective updating, maintenance, and retrieval of useful cognitive and motor information. Here, we developed a novel task that independently manipulated selective gating operations of working-memory (input), from working-memory (output), and in response (motor) and tested the neural dynamics and computational principles that support them. Increases in gating demands, captured by gate switches, were expressed by distinct EEG correlates at each gating level that evolved dynamically in partially overlapping time windows. EEG decoding analysis further showed that neural indexes of working-memory (category) and motor (action) representations were prioritized particularly when the corresponding gate was switching. Finally, the control mechanisms involved in gate switches were quantified by the drift diffusion model, showing elevated motor decision threshold in all gating levels. Together these results support the notion that cognitive gating operations scaffold on top of mechanisms involved in motor gating.

Introduction

Optimal flexible behavior requires an agent to not only respond to incoming sensory events but to adaptively adjust action selection based on context, including previous events in memory [1]. Moreover, while some events in memory need to be robustly maintained over time in the face of distracting interference, sometimes sensory events dictate that such memories should be disrupted and rapidly updated. This challenge is referred to as the stability vs flexibility tradeoff [2-4] and highlights the need for a context-dependent control mechanism that selectively gates information into and out of working-memory (WM) to guide actions [5-10]. Adaptive control is particularly crucial given a capacity-limited WM system in a complex environment, where only a subset of perceptual information is task-relevant and only a subset of currently maintained WM items may be useful for guiding ongoing behavior.

The PBWM (prefrontal cortex basal ganglia working memory) model is a computational model that leverages powerful mechanisms of dopaminergic reinforcement learning (RL) in basal ganglia (BG) so as to optimize gating policies that control access to and from prefrontal cortex, to be held in WM [9-11]. According to PBWM, gating of both motor and WM actions are implemented by a common canonical set of operations whereby phasic DA signals reinforce BG gating actions that yield successful task performance. A distinguishing characteristic of the PBWM model is that WM gating is an elaboration of the more established BG mechanism of motor gating [7,9,11]. Indeed, according to PBWM, WM gating can be further divided into *input gating*, whereby BG can control access to stored information in PFC, and *output gating*, whereby other BG circuits can control which among several maintained WM items should influence motor decisions (*response gating;* see Fig. 1*)*. Moreover, PBWM extensions further assume that frontostriatal gating processes operate across a spectrum of abstract actions ranging from action

plans in premotor cortex (PMC) to context-relevant cognitive information (like rules and task

sets) in more anterior PFC [11-13]. Various imaging, lesion and pharmacological studies have

provided support for PBWM gating mechanisms (see [14-16] for reviews). These cognitive and

motor gating circuits are nested within a cortico-striatal hierarchical system that is arranged on a

rostral-caudal axis in the frontal lobe (Fig .1) [17-20], such that the posterior response gate is

dependent on, and constrained by, the more rostral cognitive gates [6,11,12]. Indeed, anatomical

studies have revealed asymmetric topography with more fibers projecting information from

anterior PFC to posterior BG [21]. Nevertheless, despite this converging evidence for

hierarchical PFC-BG gating interactions, the core assumption that response, input and output

gating share computational properties – or how they unfold in time – has not been rigorously

tested.

Figure 1. Schematic of the PBWM architecture for canonical gating operations. The gating system is composed of three core circuits that are hierarchically arranged from left to right. For illustration the operations needed to solve the task used in this paper are shown. Sensory information (e.g., the "X" in the visual input) is transiently represented in PFC-in. The input gate controls whether this information is updated to be maintained in a PFC memory layer, and if so, to which address or anatomical "stripe" within that layer (selective gating). The red frame represents a task cue signifying that memory should be updated, and the input gate selectively updates the left PFC stripe, replacing the "O" in memory with "X". The output gate controls which of the memory layer representations is represented in PFC-out (e.g., a deep layer of the PFC) to influence subsequent processing (e.g., here the relevant representation in memory is "O" and not "%", given that the input to be compared is in the letter category). The response gate controls which motor response to select (here, "same" or "different") by comparing the output-gated memory representation ("O") with the current visual input ("X"). At the beginning of a trial, the memory layer actively maintains the information from the previous trial. The orange arrow on the memory layer represents active maintenance. Dark orange arrow heads represent the gating signal by the BG that selects the relevant representation. The yellow squares represent the PFC stripe selected by the corresponding gating operation.

The N-back task is often used for examining variations in executive function [22-23]. While the N-back likely depends on both input and output gating (and can be modeled with PBWM [24]), experimentally, it provides a coarse measurement of WM control processes that are confounded with a variety of complex cognitive processes (e.g., encoding, inhibition, binding, matching, maintenance, updating and removal). To address this issue, and to focus on input gating specifically, we recently developed the reference-back task [25-29], a continuous WM updating task. Behavioral, EEG and fMRI data supports the notion that the reference-back task taxes BG input gating of PFC [27,29,30]. However, a core distinguishing feature of the PBWM framework from that of other gating models is that it affords *selective* gating, whereby items can be input gated to, and output gated from, distinct addresses in memory (represented as PFC "stripes" or ensembles in the PBWM model). Here we aimed to augment the reference-back task to more directly assess these separable content-addressable input and output gating functions, while also assessing how they relate to response gating.

To do so, we amended the reference-back task to mirror the SIR2 task, one of the key tasks

developed to illustrate the need for learning selective gating policies in PBWM [10]. To

manipulate the need for selective gating in a content-addressable manner, the SIR2 task includes

two separate store cues (S1 or S2) in which the associated WM items had to be updated

independently to separable WM stores and then accessed independently in response to

corresponding recall probes (R1 or R2), in arbitrary order and over intervening distractors [10].

Through RL, PBWM learned a selective input gating policy that placed S1 and S2 items into

separate PFC stripes, and an output gating policy that accesses the appropriate stripe given the

corresponding R1 or R2 probe, thus implementing content-addressable memory. Given the

unpredictable order in which items are stored and recalled, models without selective gating

policies cannot solve the SIR2 task. This same selective gating ability was shown to useful to

perform complex, hierarchically structured tasks and for supporting generalizability and task

structure learning (11, 12, 31, 32]. However, the SIR2 task does not have psychometric

properties useful for human experimentation.

147
148

150
Figure 2. Trial events in the reference-back-2 task. Trials with red frame are updating trials,
while blue trials are maintenance trials. On each trial, participants make a matching decision
between the probe and last stimulus presented in red from the same category. Each side of the
thought bubble represents an address (or PFC "stripe") in WM. During updating, input gates
assign information to an address based on its category. During output gating, the relevant
category is accessed from memory for the decision. The response gate makes the same/different
selection. See the method section for more detail.

The reference-back-2 task (Fig. 2) retains all the key features of SIR2 and allows

laboratory testing of content-addressable selective input and output gating. The reference-back-2

task, like the original reference-back, is a continuous WM updating task that is composed of two

trial types. *Updating trials* require both a matching decision and WM updating, whereas

maintenance trials are equivalent in their perceptual and decision making demands but do not

require WM updating. To introduce the need for selective gating, the reference-back-2 task

includes stimuli that belong to two different categories (e.g., symbol/letter), where only one of

these representations is relevant on each trial. In updating trials (marked with a red frame),

participants need to update only the stimulus in WM belonging to the same category as the

presented stimulus, while continuing to maintain that of the other category; thus demanding

selective input gating (see Fig. 1). The input gate, gates relevant information (e.g., the probed

"X") into a specific WM memory address (stripe) given the appropriate context (e.g., the red

frame indicates to update). Further, for making the matching decision, only the currently relevant

category item should be considered; thus demanding selective output gating. The output gate

selects amongst maintained WM representations (in the memory layer) and output gates relevant

information for subsequent processing (e.g., given the letter category in the probe, the relevant

representation in memory is "O" and not "%"). Finally, for motor responding, the participant

needs to compare the probed stimulus ("X") to the WM representation selected by the output

gate ("O"), in order to respond "same" or "different", thus demanding selective response gating.

Here, we aim to test three key predictions from PBWM. First, we assessed whether

input, output, and response gating share analogous computations that evolve dynamically in

time. In particular, PBWM predicts that when gating demands (at any level) switch from one

trial to the next, the resulting conflict is associated with an independent response time cost.

Neurally, such switches give rise to a transient period of conflict at the corresponding region of

PFC, analogous to the conflict experienced when needing to switch motor responses in PMC

[33] (see also Fig. 4 below). Switches in higher level task rules give rise to anterior EEG

signatures which precede those of more posterior motor EEG signatures (Collins et al., 2014).

We thus assessed whether such neural markers of input, output and response gating are

separately detectable, and whether they evolve serially or in parallel.

Second, we tested the core PBWM prediction that output gating is used to enhance the

representation associated with the currently relevant category (bolded representation in Fig 2).

Previous work has shown that attention to a relevant category, during either encoding or

subsequent retrieval, acts to prioritize the attended representation and improve its memory (see

reviews by [35-37]). WM prioritization is marked by sustained, elevated neural activity [38-40]

and persistent alpha suppression [41] that increases decodability of the prioritized representations

[42-44]. Such WM prioritization is thought to support "controlled attention" by enhancing top-

down influence on subsequent processes [36, 45]. Such an account is consistent with output

gating, but to date the gating WM literature and the WM prioritization literature have not been

linked. To this end, we aimed to directly test the prediction that output gating (and switches

thereof) places demands on prioritization to increase neural discriminability between the two

candidate categories. Analogously, we also predicted that response switching will boost the

neural decodability of the corresponding motor action representation, given that switches at the

motor level place additional demands on response gating.

Finally, we tested whether the behavioral costs associated with gate switching can be

assessed more quantitatively by computational models that summarize the impact of BG gating

on response time distributions. The behavioral dynamics of BG gating neural networks at the

motor level can be approximated by the drift diffusion model (DDM) [46]. Moreover, in these

models and related electrophysiological data, premotor conflict (e.g., following switches), lead

downstream in the BG to an increase in the effective "decision threshold", buying more time to

allow more cautious and deliberate response selection [33, 47-49]. Hierarchical PFC-BG models

further suggest that this same computation is recruited when conflict occurs at higher level

prefrontal task representations, preventing the lower level corticostriatal circuit from selecting

actions until such conflict is resolved [12]. Thus according to PBWM, conflict at the WM levels

(switches in WM gating) should give rise to an increase in the motor response decision threshold.

We thus aimed to test whether neural markers of response switching and conflict are also

impacted by switches of WM input and output gating, and whether they are accompanied by a

concomitant change in decision threshold.

In sum, the current study was designed to test the hypotheses that selective input, output

and response gating are managed by analogous computations and that they are distinguishable

temporally. Very little is known on the order in which selective cognitive and action decisions

are operating and how they unfold in time. This is important, in part, because input and output

gating rely on close cortico-striatal circuits that may require high temporal resolution to

disentangle. Furthermore, we investigate the functional role of WM gating and response gating.

We employ a trial-by-trial decoding approach of EEG signals to quantify the implications of

selective gating on the prioritization of WM and action representations. Finally, we will examine

if the same control mechanisms that are engaged to response conflict during motor switching are

also recruited in response to cognitive conflict arising from multiple items or task rules held in

WM. To quantify these dynamics, we will employ an abstract mathematical model, the

hierarchical drift-diffusion model (HDDM) [33,50].

Results

We first assessed the most basic prediction that switches at each gating level (input,

output, response) will translate into separable costs on behavior. Three-way repeated-measures

ANOVAs were run on mean RT and mean error rate as a function of switches in input (update,

maintain) × output category (letters, symbols) × response (same, different).

For RT, significant main effects were observed for switches at all levels: input ($F_{1,29}$=

103.99, $p<.001$, $\eta_p^2=.78$), output ($F_{1,29}$= 54.06, $p<.001$, $\eta_p^2=.65$) and response ($F_{1,29}$= 5.40, $p=.03$,

$\eta_p^2=.16$). The faster RT for repeats than for switches is consistent with the canonical gating

model in which a switch at any level incurs conflict and delays motor responding. Significant

under-additive interactions were also observed between input × output ($F_{1,29}$= 57.81, $p<.001$,

$\eta_p^2=.67$), input × response ($F_{1,29}$= 81.51, $p<.001$, $\eta_p^2=.74$), and output × response ($F_{1,29}$= 36.51,

$p<.001$, $\eta_p^2=.56$). The three-way interaction was also significant ($F_{1,29}$= 18.39, $p<.001$, $\eta_p^2=.39$)

indicating that the under-additive interactions between switches at two levels is limited to the

case where the third level was not switching.

For error rate, the only significant effect was for the 2-way input × response interaction

($F_{1,29}$= 43.00, $p<.001$, $\eta_p^2=.60$), such that switches in input gating demands were related to

increased accuracy for response switching. This result indicates a speed-accuracy tradeoff given

the RT results from that same interaction; this will be further investigated with the DDM model

below. None of the main effects nor the other interactions were significant ($F_{1,29}<3.7$, $p>.06$).

Note that an extended five-way ANOVA was also conducted with WM state (updating,

maintenance), updating frequency (rare, frequent) and the three gating levels (switch, repeat) in

input, output and response gating. The results of this larger analysis are reported in

Supplementary Results.

257   **Figure 3. Behavioral effects of switching in gating demands**. Mean RT (top row) and error
258   rate (bottom row) demonstrate differences in performance across all levels of gate switching (left
259   column), together with under-additive interactions at all levels (from left to right: input and
260   output, input and response, output and response and when all three gates are switching).

262   *Temporal evolution of neural gating dynamics across levels.*

263   Given that switches in gating demands at all levels had observable effects on behavior,

but with under-additive interactions, we also assessed whether such switches would be

observable in neural activity. In PBWM, gating signals are used to displace prefrontal activity

states with new information. Thus, the impact of gating is most observable during switch trials,

which induce a transient period of conflict in cortex (the equivalent of an ERP in the model)

when there is competition between the previous and currently relevant information (Fig 4a-b;

[12,33, 34]. Notably, these models are hierarchical, such that neural signatures of gate switching

evolve in time, with higher level gates inducing conflict prior to the response gate (Figure 4a;

[34]). However, despite this seemingly serial process, the same model predicts that these

processes evolve partly in parallel, leading to under-additive interactions. Indeed, previous

behavioral work has showed evidence for a combination of parallel and serial processing among

cognitive and response selections, a result that was captured using the same hierarchical PFC-BG

neural network model [51].

Figure 4. (a-b) Summed activation over units in PFC-BG neural network, showing impact of
gate switch vs repeat (a) early in PFC and (b) later in motor cortex (adapted from [34]). (c)
Current study. Scalp map topography for the predictors that survived permutation correction for
the three gating types (input, output, response in three rows from top to bottom). The color in the
scalp map represent the t-value of the average regression weights in each electrode at the time
range indicated above each scalp map. Input, output and response gating signatures evolve
sequentially in time, but with clear temporal overlap.

        To evaluate whether gating processes are observable and whether they evolve in parallel

or in serial, we focus on trial-to-trial switches that place demands on input, output, and response

gating independently. Accordingly, we leverage three orthogonal switch versus repeat trial

contrasts to index gating demands: (a) Input gating: The transition from maintenance trials to

updating trials requires a shift from a closed to an open input gate, in order to selectively update

the task-relevant category. These switch trials are compared to update repeat trials. (b) Output

gating: The relevant category for guiding the match decision is selected from within memory

using output gating. When the category switches across trials, a new address must be accessed,

placing higher demands on the output gate relative to when the category repeats. (c) Response

gating: Switches of the same/different response should result in transient conflict at the level of

the response decision relative to repeats.

We used a regression approach to extract spatiotemporal clusters that reflect the three

gating effects on the trial-by-trial EEG signal, controlling for RT and multiple comparisons (see

Methods; [52-53]). The results of this regression analysis yielded significant univariate patterns

for WM input gating, output gating and response gating (Fig 4). Notably, the neural markers of

all three gating levels (input, output and response) evolved dynamically in order (Fig 4), but with

substantial overlap in time (410ms – 470ms), consistent with previous empirical studies and

hierarchical computational models of cortico-striatal circuitry [12; 51]. The response index also

persisted on its own after the input and output gate signatures (see Fig 4). The distinct univariate

patterns of activity for each gating level, with largely overlapping time windows, provides neural

and temporal support for the PBWM prediction that WM is managed by independent gate

selection mechanisms operating sequentially but mostly in parallel [51].

Gating as a prioritization mechanism.

Having identified putative neural signatures of gating operations, we next sought to

assess the functional impact of gate switching in terms of prioritization of task-relevant

representations. The reference-back-2 task employed in this study is suited to study this question:

in every trial, two representations are held in WM. Only one, however, is relevant to guide action

selection (and to be selectively updated in WM when needed), while the other representation is

prospectively relevant and therefore still requires maintenance. This design allowed us to test if

selection within WM (output gating) shares the same neural manifestation as action selection

(response gating). We leveraged a trial-by-trial decoding approach [52-53]. Thus in contrast to

the last section, in which we identified neural signatures of gate switching, here we used GLM to

extract spatiotemporal clusters in the EEG signal that reflect the representations themselves (e.g.,

relevant category and response), controlling for RT, WM state (update, maintenance) and

multiple comparisons ([52-53] see methods).

Figure 5. The temporal dynamics of neural prioritization by gating. (a) Trial-by-trial
decoding of gated representations. Univariate patterns were identified for each representation of
interest (category, response) using GLM. Trial by trial similarity indices obtained by computing
the dot-product between the 2D voltage-time map on individual trials with that of the mask for
the relevant representation. This similarity index is obtained over sliding window time bins (red
rectangle). The result is a temporally evolving EEG index of similarity in time windows for
which mask was significant (see methods for more detail). (b) The temporal dynamics of
similarity indices to the relevant representations in updating (left) and maintenance (right) trials.
While neural similarity to the relevant representation was evident in all cases, category level
decoding was enhanced following switches in output gating, whereas response decoding was
enhanced following switches in responses. The shaded error bars represent standard error of the
mean (SEM) to reflect the time points where the difference between switch and repeat was
significant.

Supporting the notion that switches at the relevant level enhance the need for gating, we

found that the trial-wise neural similarity increased following switches of the relevant gate (see

figure 5b). Specifically, output switching enhanced the neural difference between the two

categories whereas response switching enhanced the neural difference between the two motor

action representations. These increases in decodability were very transient in maintenance trials

(only around 200ms) while in updating trials, the benefit for output switching lasted throughout

the trial (170-800ms; see Fig 5b). This finding is consistent with the PBWM model scheme in

which selective updating of WM further enhances activity in the memory layer (Fig.2) which is

compounded with impact of output and response switching operations. Together these results

support the notion that selective gating at both cognitive and the motor level share the functional

role of prioritization that increases decodability of the representation selected by the relevant

gate.

Gate switching at any level increases decision threshold.

The behavioral results described above revealed that switches at any level of gating were

related to increased RT cost. To further decompose separable cognitive processes that give rise

to such changes in RT, we leveraged the drift diffusion model (DDM). As noted in the

introduction, various studies have suggested that dorsomedial frontal cortex detects response

conflict (which is elevated following switches) and it recruits BG mechanisms that increase the

effective decision threshold [46-49], resulting in slower but more accurate decisions.

Hierarchical PFC-BG models further suggest that conflict at the level of PFC representations

recruits the same mechanism to prevent premature motor responding [12, 33]. We thus assessed

whether gate switches at all levels of the WM hierarchy are quantitatively related to adjustments

in decision threshold (thought to reflect cognitive control, thus related to slower but more

accurate responding), or whether any such effects could be attributed to alterations in drift rate

(thought to reflect increased difficulty and thus slower and less accurate) (Fig. 8).

Figure 6. Model fit to behavior (a) Behavioral RT distributions across the group are shown for switching at each level (red line) together with posterior predictive simulation from the HDDM (light blue). Distributions of correct (the right positive tail) and incorrect (left negative tail) trials in updating trials (left) and maintenance trials (right) show good correspondence between data and model.

Figure 7. Model fit with Quantile-Quantile plots (a) Model fit to behavior can be more
precisely viewed using quantile-quantile plots, showing quantiles of the empirical behavioral RT
distributions (black) against the 50 simulation of RT distribution (colored lines, capturing model
uncertainty) from the posterior predictive of the HDDM model, for correct response (positive
RT) and incorrect responses (negative RT). Quantiles were computed at the group level.

Bayesian parameter estimation with HDDM revealed that the DDM provided an adequate

fit to choice proportions and response time distributions (Fig 6). Moreover, switches at each

independent level of gating (input, output, and response) were related to increased decision

thresholds (see Fig 8 for statistics). Notably, in updating trials, such effects were incrementally

larger when switches were closer to the response level. This result supports the notion that

response conflict has preferential impact on motor decision threshold, but that switches in higher

level gates can nevertheless recruit the same process. Relatedly, parameter estimates revealed

under-additive interactions such that switches at higher gating levels had reduced impact if there

were already switches at the lower level gates (Fig 8). These under-additive interactions mirrored

those described in behavioral summary statistics above, and are also consistent with the EEG

findings that gate switches overlapped in time. Maintenance trials showed relatively similar

effects (Fig 8), with the exception that switches in input gating (i.e., closing the gate from

updating to maintenance) were associated with increases in threshold that were comparable to

those at the response level. We speculate about potential mechanisms for this effect in the

discussion.

Notably, these threshold effects were obtained even though drift rate was also allowed to

vary by condition. As noted, in the DDM, (lower) drift rates can also capture slowed RT when a

condition is more difficult, as opposed to a control mechanism. Accordingly, we did observe that

drift rates were slower in conditions that required more cognitive processing to succeed:

updating vs. maintenance trials and switches at the cognitive level vs. switches at the response

level. In both cases additional cognitive processing is required: updating trials require replacing

WM content in addition to accessing previous content for responding, and switches at the

cognitive levels are known to be more difficult than simple response switches (e.g., [54]). These

 findings boost the interpretation that gate switches at any given level are specifically related to

 elevated decision thresholds, while accounting for impact of difficulty on drift rate.

Figure 8. Under-additive interaction between gating selections. Decision threshold parameter estimates from HDDM in updating (first row, orange bars) and maintenance trials (third row, blue bars), exhibit main effects of gate switching at each independent level of gating (input, output, and response; left column), and under-additive interactions between gate switches in input-output, input-response, and output-response. Drift rate parameter estimations from the HDDM in updating (second row, orange bars) and maintenance trials (fourth row, blue bars) exhibit slowing in conditions that required more cognitive processing (left column) and exhibit facilitative interactions between gate switches. Dark color represents performance when the gates are switching together. Error bars reflect within-subject 95% highest density interval of the posterior distribution, in each case relative to maintenance repeat trials.

Discussion

These findings provide heretofore untested empirical support for the PBWM theoretical

framework in which working memory involves a hierarchy of (content-addressable) selective

input, output, and response gating operations. First, we developed a task that separately taxes the

need for input and output gating processes, motivated directly by the computations in PBWM.

The previous reference-back task focused on input gating [26, 27, 29] and its correlates in PFC

and BG [30]. Here, we augmented that task by adding the need to track two independent

categories over trials, thereby taxing selective input gating, while also orthogonally manipulating

output gating. The advantage of the reference-back-2 task is that it is a continuous task that

manipulates *selective* input and output gating demands to/from a particular address in memory,

while preserving the need for continued maintenance of other information across trials.

Second, we confirmed the basic prediction that neural correlates of input, output, and

response gating evolve dynamically and have analogous effects on behavior. The mass-

univariate analysis of the EEG provided the temporal confirmation of this prediction by showing

distinct spatiotemporal patterns for each gating level (input, output, response) that were

independent and sequential, but partially overlapping, in time (see [51] for similar conclusions in

PBWM simulations and behaviorally in a hierarchical rule task).

Third, we found that output gating (and particularly, switches therein) enhances the

decodability of WM content selectively for the relevant category. The probabilistic and

unpredictable switching between categories imposed a dynamic need to access distinct

"addresses" within WM to update to, and read out from. This task property also had the

important advantage of overcoming the challenge of measuring memory prioritization without

being contaminated by the removal of irrelevant information [55] that often coincides with such

prioritization manipulations (e.g., [36]). Decoding analyses suggested that neural representations

of relevant WM categories were enhanced following WM gate switches at the corresponding

levels. Analogously, neural representations of motor responses were enhanced following

response switches. We thus propose that gating operations, perhaps implemented by

corticostriatal circuits, are partially responsible for previous observations of prioritization.

Similar conclusions have been made in attentional shift experiments in which one or another

stimulus category becomes relevant, and where striatal activity dictates whether PFC selectively

enhances posterior representations of the relevant category [56]. Nevertheless, further

investigations are needed to determine which neural mechanisms provide prioritization gain

during gate switching. For example, gate switching may change the "active neural trace" (e.g.,

[43]) of representations or it may increase their accessibility for read-out (e.g., in other prefrontal

layers as in PBWM). Other studies suggest that prioritization does not simply amplify relevant

representations but that it also modifies the formatting of the non-selected representation so that

they are less similar to the form that would be read out (e.g., [57-58]). Future research should

also test whether gate switching facilitates coupling between cognitive rules and relevant task

features like action representations [45, 59]

Finally, the above neural and behavioral findings were further supported by quantitative

computational modeling using HDDM. We found that switches at any gating level were related

to increases in the estimated decision threshold. This finding builds on previous studies showing

that switches or response conflict gives rise to increased threshold via PFC-BG mechanisms [46,

48,49], but extends it to confirm the hierarchical PFC-BG model prediction that such effects hold

for switches at more cognitive levels [12]. Nevertheless, such effects were still more dominant

when gate switches were closer to the response level (they were strongest for response switch

then output switch then input switch). An exception to this conclusion was found whereby

switches from updating to maintenance ("closing the gate") were accompanied by similarly large

threshold adjustments as response switches. We speculate that closing the gate might also recruit

the same prefrontal subthalamic pathway thought to be involved in transient response inhibition

(e.g., [60-61]).

The cortico-striatal gating framework offers a theory of selective gating that includes not

only plausible mechanisms for learning and generalization of gating policies [6, 7, 9, 18, 34] but

also supports advanced cognitive control functions, like hierarchical control [12], and higher

order learning and cognitive flexibility [11] in complex tasks like the reference-back-2 task used

in this study. A key property of the cortico-striatal model that was further supported by current

findings is that higher order cognitive "actions" (input and output gating operations) scaffold on

top of the canonical computational motor gating operations. Indeed, striatal dysfunctions such as

in Parkinson's disease causes not only progressive motor degeneration but also cognitive deficits

that are both related to the dysfunction of the gating system [62]. More recent work also found

that degraded ability to perform selective updating of WM is the key marker of the cognitive

deficits in Parkinson's [63].

Furthermore, converging evidence from modeling [12, 64], and experimental work (e.g.,

[65-66]) demonstrated under-additive interactions when more than one order of switching was

needed (e.g., switching task-sets and responses or switching context and items in WM). These

results suggest that action selection is partially parallel, such that decisions about a response are

processed to some degree even while the identity of the cognitive rule is uncertain. Such an

interpretation is consistent with the parallel processing hypothesis across the gating system [51].

The HDDM analysis of the RT distribution of correct and error trials in the reference-back-2 task

further support the parallel processing account as under-additive interactions were observed

between the gating loops. Specifically, the threshold parameter showed greater slowing when

two gates were switching but with threshold predominated by the lower level gate. The drift-rate

on the other hand, showed an under-additive facilitation where switching two gates was as fast as

switching the lower level gate. The gain in processing speed for switching the higher level gate

together with a lower level gate, recapitulates an effect often described in the task-switching

literature (e.g., [64, 67]), whereby the task switch cost decreases or is abolished by response

alterations. A possible interpretation for the facilitation finding is that WM updating decisions

increase the mutually facilitative effect of switching across the gating system.

Finally, our study has various limitations. First and foremost, while the EEG method

allowed us to assess the temporal dynamics of gating signals and representation decoding, it does

not afford the ability to assess the involvement of corticostriatal circuits specifically. Functional

imaging studies have implicated striatum in input gating in the reference back task [30], and

output gating in other tasks [6], but testing the involvement of this circuit in selective content-

addressable gating awaits further study.

Second, with the aim to increase our understanding of the latent cognitive processes that

give rise to the full behavior in the reference-back-2 task and not just the mean RT and error rate,

we leveraged the HDDM framework. However, it is likely that the decision process engaged

during working memory gating diverges from that assumed by the standard DDM, and other

models should be considered in future work (including those with time-varying drift rates and/or

boundaries. Such models are difficult to estimate, but recent tools open the door for such

investigations [68]. Moreover, future research could also employ a model-based approach where

neural patterns are linked to cognitive mechanisms through computational models (e.g., [47,

69]).

Methods

Participants

Thirty-two right-handed adults (aged 18–35; X female, X male) with normal or

corrected-to-normal vision completed the experiment. All spoke English natively, were screened

for neurological medications/conditions, and provided informed consent in accordance with the

Research Protections Office at Brown University. Two participants were excluded from the

analysis, due to technical problems with the experiment.

Stimuli and Procedure

Stimuli presentation and behavioral data collection were implemented using the

Psychophysics Toolbox extensions in Matlab [70-71]. One out of four possible stimuli was

presented on each trial. The stimuli were each of a distinct category: letters ("X", "O") and

symbols ("%", "#") with two stimuli in each category. The stimuli appeared in a random order.

Each trial started with a presentation of a stimulus inside a colored frame (red or blue), that

indicated whether it was an updating trial or a maintenance trial. Participants had to make a

matching decision between the presented stimulus and the last item category that was presented

inside the updating color (e.g., red). Therefore, letters had to be compared with letters, and

symbols with symbols. For all trials (regardless of blue or red) required participants to follow the

same rule of comparing the stimulus with that of the corresponding category in the most recent

updating trial. Participants were instructed about the meaning of the color (i.e., which one

corresponded to reference to be updated and which one indicated the stimulus should only be

compared to that in memory). The selected reference color (red or blue) was counterbalanced

between participants. The color of the frame in each trial was biased with 75% probability for

one color in the first six blocks of the experiment and 75% probability for the other color for the

last six blocks of the experiment. The order of color bias was chosen randomly. The biased color

manipulation allowed us to have a more stable measure of selective output gating where the

relevant category changed (output switch) but fewer trials in which there was also a color (input

policy) switch. Participants were instructed that there will be a color bias that will flip once

during the experiment. "Same" and "different" responses were indicated by using the right and

left index fingers, respectively, to press 'Z' and '/' on the keyboard. Response mappings were

chosen randomly for each participant.

Stimulus presentation was limited to 3 sec. The response was followed by an inter-trial

interval that was jittered between 800-1000 ms. Participants were instructed to keep their eyes

fixated on the center of the screen throughout the experimental blocks. The first two trials in a

block were always updating trials with stimuli from the two categories. Participants were

instructed that accuracy will not be measured in the first two trials in the block. The experiment

comprised of 12 blocks, including 90 trials each. Participants had to reach 80% accuracy on the

practice block before they began the experiment. Participants were allowed to repeat the practice

block up until 4 times.

Electroencephalogram (EEG) Recording and processing

Scalp voltage was measured using 62 Ag/AgCl electrodes referenced to a site

immediately posterior to Cz using a Synamps2 system (bandpass filter 0.5–100 Hz, 500-Hz

sampling rate). Preprocessing was conducted using the EEGLAB toolbox [72]. During pre-

processing, data were low-pass filtered at 30 Hz and high-pass filtered at 0.1 Hz. Epochs were

segmented from -200 to +800 ms surrounding stimulus onset and were baseline corrected from –

200 to 0 ms before the onset of the stimulus. The epoched data were visually inspected and those

containing large artifacts due to facial electromyographic (EMG) activity or other artifacts

(except for eye blinks) were manually removed. Independent components analysis (ICA) was

next conducted using EEGLAB's runica algorithm. Components containing blink, oculomotor

artifacts, or other artifacts that could be clearly distinguished from genuine neural activity

signals, were subtracted from the data.

Data processing for univariate EEG analysis

To extract the neural correlates in the EEG signal of conditions of interest we employed a

mass univariate approach. A multiple regression analysis was conducted for each participant, in

which the EEG amplitude at each electrode site and time point was predicted by the conditions of

interest while controlling for other factors such as RT (such an approach was recently used [52-

53]). For the regression analysis, the EEG signal recorded with 500 Hz sampling rate was down-

sampled by a factor of 4, resulting in 125 time points for the selected window of -200:800 ms

around stimulus onset. The EEG signal was z-scored before it was entered to the robust

multilinear regression analysis to account for remaining noise in the data [53].

Two separate multilinear regressions were run. The first regression assessed the neural

correlates for gate switching. It included 7 regression factors: log of RT (to remove variability

due to slower responses in some conditions; [53]), and 6 contrasts dummy coded as 1 and 0: WM

state (updating vs maintenance), input gating (WM state switch vs repeat), output gating

(category switch vs repeat), response gating (action switch vs repeat), bias (frequent updating vs

rare updating), and finally one interaction between WM state × input gating (to search for a

selective input gating pattern in updating trials).

The other regression assessed the neural prioritization of representations, i.e. to identify

an EEG signal that differentiates between representations at each gating level. The second

regression included 4 factors: log of RT and 3 contrasts dummy coded as 1 and 0: WM state

(updating vs maintenance), category (symbols vs letters) and action (same vs different).

Statistical analysis of GLM weights

Statistics on the regression weights were performed across participants for all electrodes

and time points by testing the significance of each point against 0. To correct for multiple

comparisons, we performed cluster-mass correction by permutation testing [74] with custom

written Matlab scripts. Cluster-based test statistics were calculated by taking the sum of the t-

values within a cluster of significant points with threshold for a t test significance level of P =

0.001. This was repeated 1000 times, generating a distribution of maximum cluster-mass

statistics under the null hypothesis. Only clusters with greater mass than the maximum cluster

mass obtained with 95% chance permutations were considered significant [53]. The results of the

second regression analysis yielded significant univariate patterns for the two representation types

(category and action). Note that a different regression model was also run to assess the neural

correlates of stimulus representations. This regression produced a significant univariate pattern

only for the "O" representation but not for any of the other stimuli. Therefore, we did not

continue with further analyses related to stimulus decodability.

Trial-by-trial decoding

Using the GLM masks we then computed the dot product between individual trials

(voltage maps of electrode * time) and the identified masks (electrode * time maps of t-values of

significant pixels; [53]). This computation produced a trial-level similarity measure (see Fig. 5a)

that presumably reflects how similar the EEG signal of the probed representation in memory on a

given trial to the mask activity of this representation. To visualize the temporal dynamics of the

EEG index (i.e. how the decoded representations evolves in time), the similarity measure

procedure was calculated in sliding time bins of 40 ms across the epoch, and applied only to time

bins in which the original mask was significant. The similarity index was calculated 121 times in

each trial, with a 32ms overlap between time bins. The temporal similarity indexing was

obtained by calculating the mean similarity between trials where one representation was probed

and when the other one was probed.

Note that to test the effect of gate switching on prioritization, we excluded trials from the

temporal dynamic analysis where the same stimulus was repeated from the previous trial. This

exclusion allowed us to control for impact of perceptual switches that could have elicited an

involuntary stimulus-driven enhancement of memory representations that match the probed

category stimulus (e.g., [28,75]). Therefore, we restricted analysis to output repeat trials

involving a perceptual change (e.g., from "X" to "O"), while output switch trials also included a

category change (e.g., from "X" to "%").

Drift diffusion modeling

The DDM is a common sequential sampling model of two-choice RT tasks. The

advantage of this model is that it can translate response time distributions and error rates to the

underlying generative parameters in each task condition, and it has previously been used to

summarize decision dynamics that arise from BG gating [33, 47-49]. The core parameters in the

model are threshold (or boundary separation) a, drift rate v, and non-decision time t. Threshold is

the distance between the response boundaries, where higher threshold indicates that more

evidence needs to be accumulated before committing to a choice, leading to slower but more

accurate responses. Conflict or switching in motor responses leads to elevated decision

thresholds [33, 47-49]. Drift rate is the rate in which evidence is accumulated. Larger drift rates

are usually interpreted to reflect higher quality of evidence that is expressed by faster and more

accurate response times. Finally, non-decision time captures the processes that are not related to

the decision making process such as stimulus encoding and motor execution.

We tested whether the DDM provides a good model of RT distributions of correct and

incorrect choices during the reference-back-2 task in which the decision threshold can be

adjusted as a function of conflict or switches at any gate level (while controlling for any

differences in drift rate). The underlying decision-making process during the reference-back-2

task were estimated from the DDM likelihood functions [33]. We used hierarchical Bayesian

estimation of DDM parameters, where individual's fit is constrained and informed by the group

distribution leading to more accurate estimation of parameters at both the individual and group

level [33].

Parameter estimation in the Hierarchical Bayesian framework used the Markov-chain

Monte-Carlo (MCMC). HDDM is especially beneficial for estimating individual parameters

while optimizing the tradeoff between random and fixed-effects [33]. The first two trials in each

block, omission trials, and trials with very fast RT (<200ms) were excluded from the analysis.

RT was limited to 3sec. There were three thousand samples generated from the posterior using

four chains. The first thousand (burn-in) and every second (thinning) were discarded. Proper

chain convergence was tested between the MCMC chains, using the R^ statistic [76], which

measures the degree of variation between chains relative to the variation within chains. The

maximum R^ value across all parameters in all eight models was 1.03, indicating that all chains

converged successfully [77].

Statistical analysis was performed on the group mean posteriors. The Deviance

Information Criterion (DIC) was used for model comparison [78] which balances model fit

against complexity. We first tested the simplest model where the five conditions (WM state,

input switching, output switching, response switching, and updating frequency) were used as

regression weights without interactions and with group level estimates (DIC: 29339). We

systematically added interactions, and the model with the best fit was one in which drift rate and

threshold exhibited 4-way interactions (DIC 28806). This best fitting model was estimated again

allowing for subject-level estimates in each condition (DIC 27232):

Threshold ~ a_mr + Update_frequency + (WM state × input × output × response) +…

Drift rate ~ v_mr + Update_frequency + (WM state × input × output × response).

A_mr is the intercept for threshold and v_mr is the intercept for drift-rate,

Update_frequency reflects the high or low frequency of updating, and the 4-way interaction

captured all combinations of switch or repeat during updating and maintenance trials (15

combinations in total). Within subject regressions were used such that all gate switch effects are

evaluated relative to the maintenance repeat condition (the intercept), using patsy in HDDM.

Significance was determined if the 95% confidence interval of the posterior mean did not overlap

with 0.

Behavior characterization and model validation

We first plotted the overall RT distributions for each gating condition and interaction,

separately for updating and for maintenance trials (Fig. 6) using Gramm plotting toolbox [79].

This plot showed that the HDDM model captures choice proportions (of correct and incorrect

trials) and the different shape of the RT distributions within each gating condition,

simultaneously. A critical test of a the DDM model is that it can capture the full RT distributions

in each condition. Although we used model fit statistics (DIC) to select the best-fitting model, it

is also important to validate that the best fitting model can capture the observed response

proportions and RT distributions. For this model validation we generated quantile- quantile plots

describing the correspondence between behavior and DDM predictions (Fig. 7) [79]. We

compared the shape of the empirical RT distribution to the shape of the simulated RT

distribution by plotting each data against a theoretical normal distribution. The plot in Fig. 7

exhibits the RTs on the y-axis as a function of the estimated quantiles on the x-axis based on the

inverse of the continuous cumulative distribution function (quantile function) that was estimated

at the group level. RTs of the model were simulated 50 times from the posterior predictive of the

HDDM model and plotted on top of each other to show the uncertainty in the model. As can be

seen, the empirical RT was mostly within the range of the simulated RT with a small over-

estimation at the right tail of the distribution.

References:

1. Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual Review of Neuroscience*, **24**, 167-202.

2. Braver, T. S. (2012). The variable nature of cognitive control: a dual mechanisms framework. *Trends in Cognitive Sciences, 16*, 106-113.

3. Dreisbach, G., & Fröber, K. (2019). On how to be flexible (or not): Modulation of the stability-flexibility balance. *Current Directions in Psychological Science, 28*, 3-9.

4. Goschke, T., & Bolte, A. (2014). Emotional modulation of control dilemmas: The role of positive affect, reward, and dopamine in cognitive stability and flexibility. *Neuropsychologia, 62*, 403-423.

5. Braver, T. S., & Cohen, J. D. (2000). On the control of control: The role of dopamine in regulating prefrontal function and working memory. *Control of cognitive processes: Attention and performance XVIII*, 713-737.

6. Chatham, C. H., Frank, M. J., & Badre, D. (2014). Corticostriatal output gating during selection from working memory. *Neuron, 81*, 930-942.

7. Frank, M. J., Loughry, B., & O'Reilly, R. C. (2001). Interactions between frontal cortex and basal ganglia in working memory: a computational model. *Cognitive Affective Behavior Neuroscience, 1*, 137-60.

8. Frank, M.J. and O'Reilly, R.C. (2006) A mechanistic account of striatal dopamine function in human cognition: psychopharmacological studies with cabergoline and haloperidol. *Behavior Neuroscience, 120 *, 497-517.

9. Hazy, T. E., Frank, M. J., & O'Reilly, R. C. (2006). Banishing the homunculus: making working memory work. *Neuroscience, 139*, 105-118.

10. O'Reilly, R.C. & Frank, M.J. (2006). Making working memory work: A computational

model of learning in the frontal cortex and basal ganglia. *Neural Computation,* **18***,* 283-

328.

11. Frank, M.J. & Badre, D. (2012). Mechanisms of hierarchical reinforcement learning in

corticostriatal circuits 1: Computational analysis. *Cerebral Cortex,* **22**, 509-526.

12. Collins, A.G.E. & Frank, M.J. (2013). Cognitive control over learning: Creating,

clustering and generalizing task-set structure. *Psychological Review*, **120**, 190-229.

13. Cisek, P. (2007). Cortical mechanisms of action selection: the affordance competition

hypothesis. Philosophical Transactions of the Royal Society B: *Biological Sciences*, **362**,

1585-1599.

14. Frank, M. J. (2011). Computational models of motivated action selection in corticostriatal

circuits. *Current Opinion in Neurobiology*, **21**, 381-386.

15. Chatham, C. H., & Badre, D. (2015). Multiple gates on working memory. *Current*

Opinion in Behavioral Sciences, **1***,* 23-31.

16. Cools, R. (2019). Chemistry of the Adaptive Mind: Lessons from Dopamine. *Neuron*,

104, 113-131.

17. Badre, D. (2008). Cognitive control, hierarchy, and the rostro–caudal organization of the

frontal lobes. *Trends in cognitive sciences*, **12**, 193-200.

18. Badre, D., & Frank, M. J. (2012). Mechanisms of hierarchical reinforcement learning in

cortico–striatal circuits 2: Evidence from fMRI. *Cerebral cortex*, **22**, 527-536.

19. Badre, D., Kayser, A. S., & D'Esposito, M. (2010). Frontal cortex and the discovery of

abstract action rules. *Neuron*, **66**, 315-326.

20. Koechlin, E., Ody, C., & Kouneiher, F. (2003). The architecture of cognitive control in

the human prefrontal cortex. *Science,* **302**, 1181-1185.

21. Verstynen, T. D., Badre, D., Jarbo, K., & Schneider, W. (2012). Microstructural

organizational patterns in the human corticostriatal system. *Journal of Neurophysiology,*

107, 2984-2995.

22. Jaeggi, S. M., Buschkuehl, M., Perrig, W. J., & Meier, B. (2010). The concurrent validity

of the N-back task as a working memory measure. *Memory*, **18**, 394-412.

23. Kane, M. J., Conway, A. R., Miura, T. K., & Colflesh, G. J. (2007). Working memory,

attention control, and the N-back task: a question of construct validity. *Journal of*

Experimental Psychology: Learning, Memory, and Cognition, **33**, 615.

24. Chatham, C. H., Herd, S. A., Brant, A. M., Hazy, T. E., Miyake, A., O'Reilly, R., &

Friedman, N. P. (2011). From an executive network to executive control: A

computational model of the n-back task. *Journal of Cognitive Neuroscience,* **23**, 3598-

3619.

25. Rac-Lubashevsky, R., & Kessler, Y. (2016). Dissociating working memory updating and

automatic updating: The reference-back paradigm. *Journal of Experimental Psychology:*

Learning, Memory, and Cognition, **42**, 951.

26. Rac-Lubashevsky, R., & Kessler, Y. (2016). Decomposing the n-back task: An individual

differences study using the reference-back paradigm. *Neuropsychologia*, **90**, 190-199.

27. Rac-Lubashevsky, R., & Kessler, Y. (2018). Oscillatory correlates of control over

working memory gating and updating: An EEG study using the reference-back paradigm.

Journal of Cognitive Neuroscience, **30***,* 1870-1882.

28. Rac-Lubashevsky, R., & Kessler, Y. (2019). Revisiting the relationship between the P3b

and working memory updating. *Biological Psychology,* **148***,* 107769.

29. Rac-Lubashevsky, R., Slagter, H. A., & Kessler, Y. (2017). Tracking real-time changes in

working memory updating and gating with the event-based eye-blink rate. *Scientific*

Reports, **7***,* 1-9.

30. Nir-Cohen, G., Kessler, Y., & Egner, T. (in press). Neural substrates of working memory

updating. *Journal of Cognitive Neuroscience.*

31. Kriete, T., & Noelle, D.C. (2011) Generalization benefits of output gating in a model of

prefrontal cortex. *Connection Science,* **23**, 119-129.

32. Kriete, T., Noelle, D. C., Cohen, J. D., & O'Reilly, R. C. (2013). Indirection and symbol-

like processing in the prefrontal cortex and basal ganglia. *Proceedings of the National*

Academy of Sciences, **110**, 16390-16395.

33. Wiecki, T.V. & Frank, M.J. (2013). A computational model of inhibitory control in

frontal cortex and basal ganglia. *Psychological Review*, **120**, 329-55.

34. Collins, A. G., Cavanagh, J. F., & Frank, M. J. (2014). Human EEG uncovers latent

generalizable rule structure during learning. *Journal of Neuroscience*, **34**, 4677-4685.

35. Myers, N. E., Stokes, M. G., & Nobre, A. C. (2017). Prioritizing information during

working memory: beyond sustained internal attention. *Trends in Cognitive Sciences,* **21**,

449-461.

36. Oberauer, K. (2019). Working memory and attention–A conceptual analysis and review.

Journal of Cognition, **2**, 1-23.

37. Olivers, C. N., Peters, J., Houtkamp, R., & Roelfsema, P. R. (2011). Different states in

visual working memory: When it guides attention and when it does not. *Trends in*

Cognitive Sciences, **15***,* 327-334.

38. D'Esposito, M., & Postle, B. R. (2015). The cognitive neuroscience of working memory.

Annual Review of Psychology, **66***,* 115-142.

39. LaRocque, J. J., Lewis-Peacock, J. A., & Postle, B. R. (2014). Multiple neural states of

representation in short-term memory? It's a matter of attention. *Frontiers in Human*

Neuroscience, **8***,* 1-14.

40. Stokes, M. G. (2015). 'Activity-silent' working memory in prefrontal cortex: a dynamic

coding framework. *Trends in Cognitive Sciences,* **19,** 394-405.

41. Günseli, E., Fahrenfort, J. J., van Moorselaar, D., Daoultzis, K. C., Meeter, M., &

Olivers, C. N. (2019). EEG dynamics reveal a dissociation between storage and selective

attention within working memory. *Scientific Reports,* **9***,* 1-13.

42. LaRocque, J. J., Lewis-Peacock, J. A., Drysdale, A. T., Oberauer, K., & Postle, B. R.

(2013). Decoding attended information in short-term memory: an EEG study. *Journal of*

Cognitive Neuroscience, **25***,* 127-142.

43. LaRocque, J. J., Riggall, A. C., Emrich, S. M., & Postle, B. R. (2017). Within-category

decoding of information in different attentional states in short-term memory. *Cerebral*

Cortex, **27***,* 4881-4890.

44. Lewis-Peacock, J. A., & Postle, B. R. (2012). Decoding the internal focus of attention.

Neuropsychologia, **50***,* 470-478.

45. Olivers, C. N., & Roelfsema, P. R. (2020). Attention for action in visual working

memory. *Cortex,***131**, 179-194.

46. Ratcliff, R., & Frank, M. J. (2012). Reinforcement-based decision making in

corticostriatal circuits: mutual constraints by neurocomputational and diffusion models.

Neural Computation, **24***,* 1186-1229.

47. Cavanagh, J. F., Wiecki, T. V., Cohen, M. X., Figueroa, C. M., Samanta, J., Sherman, S.

J., & Frank, M. J. (2011). Subthalamic nucleus stimulation reverses mediofrontal

influence over decision threshold. *Nature Neuroscience*, **14**, 1462-1467.

48. Frank, M. J., Gagne, C., Nyhus, E., Masters, S., Wiecki, T. V., Cavanagh, J. F., & Badre,

D. (2015). fMRI and EEG predictors of dynamic decision parameters during human

reinforcement learning. *Journal of Neuroscience*, **35**, 485-494.

49. Herz, D. M., Zavala, B. A., Bogacz, R., & Brown, P. (2016). Neural correlates of

decision thresholds in the human subthalamic nucleus. *Current Biology*, **26**, 916-920.

50. Ratcliff, R., & McKoon, G. (2008). The diffusion decision model: theory and data for

two-choice decision tasks. *Neural Computation*, **20**, 873-922.

51. Ranti, C., Chatham, C. H., & Badre, D. (2015). Parallel temporal dynamics in

hierarchical cognitive control. *Cognition,* **142***,* 205-229.

52. Collins, A. G. E., & Frank, M. J. (2016). Neural signature of hierarchically structured

expectations predicts clustering and transfer of rule sets in reinforcement learning.

Cognition, **152**, 160-169.

53. Collins, A. G., & Frank, M. J. (2018). Within-and across-trial dynamics of human EEG

reveal cooperative interplay between reinforcement learning and working memory.

Proceedings of the National Academy of Sciences, **15**, 2502-2507.

54. Kiesel, A., Steinhauser, M., Wendt, M., Falkenstein, M., Jost, K., Philipp, A. M., &

Koch, I. (2010). Control and interference in task switching—A review. *Psychological*

Bulletin, **136**, 849-874.

55. Lewis-Peacock, J. A., Kessler, Y., & Oberauer, K. (2018). The removal of information

from working memory. *Annals of the New York Academy of Sciences*, **1424**, 33-44.

56. van Schouwenburg, M. R., den Ouden, H. E., & Cools, R. (2010). The human basal

ganglia modulate frontal-posterior connectivity during attention shifting. *Journal of*

Neuroscience, **30**, 9910-9918.

57. van Loon, A. M., Olmos-Solis, K., Fahrenfort, J. J., & Olivers, C. N. (2018). Current and

future goals are represented in opposite patterns in object-selective cortex. *ELife,* **7**,

e38677.

58. Yu, Q., Teng, C., & Postle, B. R. (2020). Different states of priority recruit different

neural representations in visual working memory. *PLoS biology*, **18**, e3000769.

59. Kikumoto, A., & Mayr, U. (2020). Conjunctive representations that integrate stimuli,

responses, and rules are critical for action selection. *Proceedings of the National*

Academy of Sciences, **117***,* 10603-10608.

60. Aron, A. R., Durston, S., Eagle, D. M., Logan, G. D., Stinear, C. M., & Stuphorn, V.

(2007). Converging evidence for a fronto-basal-ganglia network for inhibitory control of

action and cognition. *Journal of Neuroscience*, **27**, 11860-11864.

61. Jahfari, S., Ridderinkhof, K. R., Collins, A. G., Knapen, T., Waldorp, L. J., & Frank, M.

J. (2019). Cross-task contributions of frontobasal ganglia circuitry in response inhibition

and conflict-induced slowing. *Cerebral Cortex*, **29**, 1969-1983.

62. Wiecki, T. V., & Frank, M. J. (2010). Neurocomputational models of motor and

cognitive deficits in Parkinson's disease. In *Progress in Brain Research* (Vol. **183**, pp.

275-297). Elsevier.

63. Salmi, J., Ritakallio, L., Fellman, D., Ellfolk, U., Rinne, J. O., & Laine, M. (2020).

Disentangling the role of working memory in Parkinson's disease. *Frontiers in Aging*

Neuroscience, **12**, 1-17.

64. Brown, J. W., Reynolds, J. R., & Braver, T. S. (2007). A computational model of

fractionated conflict-control mechanisms in task-switching. *Cognitive Psychology,* **55**,

37-85.

65. Risse, S., & Oberauer, K. (2010). Selection of objects and tasks in working memory.

Quarterly Journal of Experimental Psychology, **63**, 784-804.

66. Sali, A. W., Jiang, J., & Egner, T. (2020). Neural Mechanisms of Strategic Adaptation in

Attentional Flexibility. *Journal of Cognitive Neuroscience*, **32**, 989-1008.

67. Korb, F. M., Jiang, J., King, J. A., & Egner, T. (2017). Hierarchically organized medial

frontal cortex-basal ganglia loops selectively control task-and response-selection. *Journal*

of Neuroscience, **37**, 7893-7905.

68. Fengler, A., Frank, M., Govindarajan, L., & Chen, T. (2020). Likelihood Approximation

Networks (LANs) for Fast Inference of Simulation Models in Cognitive Neuroscience.

bioRxiv.

69. Turner, B. M., Palestro, J. J., Miletić, S., & Forstmann, B. U. (2019). Advances in

techniques for imposing reciprocity in brain-behavior relations. *Neuroscience &*

Biobehavioral Reviews, **102**, 327-336.

70. Brainard, D. H. (1997). The psychophysics toolbox. *Spatial Vision*, **10**, 433-436.

71. Pelli, D. G. (1997). The Video Toolbox software for visual psychophysics: Transforming

numbers into movies. *Spatial Vision*, **10**, 437-442.

72. Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of

single-trial EEG dynamics including independent component analysis. *Journal of*

Neuroscience Methods, **134**, 9-21.

73. Cooper, P. S., Karayanidis, F., McKewen, M., McLellan-Hall, S., Wong, A. S., Skippen,

P., & Cavanagh, J. F. (2019). Frontal theta predicts specific cognitive control-induced

behavioural changes beyond general reaction time slowing. *Neuroimage*, **189**, 130-140.

74. Nichols, T. E., & Holmes, A. P. (2002). Nonparametric permutation tests for functional

neuroimaging: a primer with examples. *Human brain mapping*, **15**, 1-25.

75. van Ede, F., Board, A. G., & Nobre, A. C. (2020). Goal-directed and stimulus-driven

selection of internal representations. *Proceedings of the National Academy of*

Sciences, **117**, 24590-24598.

76. Gelman, A. (1996). Inference and monitoring convergence. Markov chain Monte Carlo in

practice, 131-143.

77. Gelman, A., & Rubin, D. B. (1992). Inference from iterative simulation using multiple

sequences. *Statistical Science*, **7**, 457-472.

78. Spiegelhalter, D. J., Best, N. G., Carlin, B. P., & Van Der Linde, A. (2002). Bayesian

measures of model complexity and fit. *Journal of the Royal Statistical Society: Series b*

(statistical methodology), **64**, 583-639.

79. Morel, (2018). Gramm: grammar of graphics plotting in Matlab. *Journal of Open Source*

Software, **3**, 568, https://doi.org/10.21105/joss.00568.

Acknowledgements

This research was funded by the National Institutes of Health under award number R01

MH084840-08A1. Work by the first author was partially supported by THE ISAREL SCIENCE

FOUNDATION (grant No. 96/19) and by Fulbright United states - Israel Educational

Foundation.