Self-Supervised Representation Learning of Protein Tertiary Structures (PtsRep): Protein Engineering as A Case Study

Junwen Luo[1]† , Yi Cai[1]†, Jialin Wu[1], Hongmin Cai[2], Xiaofeng Yang[1]* and Zhanglin Lin[1]*

[1]School of Biology and Biological Engineering, [2]School of Computer Science and Engineering, South China University of Technology, University Park, Guangzhou, Guangdong 510006, China.

* To whom correspondence should be addressed:

School of Biology and Biological Engineering, South China University of Technology, 382 East Outer Loop Road, University Park, Guangzhou, Guangdong 510006, China; Tel: +86 (20) 3938-0680; Fax: +86 (20) 3938-0601; Email: zhanglinlin@scut.edu.cn (Z.L.); biyangxf@scut.edu.cn (X.Y.).

† These authors contributed equally to this work.

Abstract

In recent years, deep learning has been increasingly used to decipher the relationships among protein sequence, structure, and function. Thus far deep learning of proteins has mostly utilized protein primary sequence information, while the vast amount of protein tertiary structural information remains unused. In this study, we devised a self-supervised representation learning framework to extract the fundamental features of unlabeled protein tertiary structures (PtsRep), and the embedded representations were transferred to two commonly recognized protein engineering tasks, protein stability and GFP fluorescence prediction. On both tasks, PtsRep significantly outperformed the two benchmark methods (UniRep and TAPE-BERT), which are based on protein primary sequences. Protein clustering analyses demonstrated that PtsRep can capture the structural signals in proteins. PtsRep reveals an avenue for general protein structural representation learning, and for exploring protein structural space for protein engineering and drug design.

Introduction

Self-supervised learning is a successful method for learning general representations from unlabeled samples[1-5]. In natural language processing (NLP), it takes the forms of Word2Vec (continuous skip-grow model, and continuous bag-of-words model)[1], next-token prediction[2], and masked-token prediction[3]. Recently these NLP-based techniques have been applied to representation learning of protein primary sequences[6-10]. Two representative examples are UniRep[10] which is based on next-token prediction, and a BERT[11] model (denoted as TAPE-BERT) which is based on masked-token prediction. Through protein transfer learning, both methods showed good performance for prediction of protein stability landscape, and green fluorescence protein (GFP) activity landscape. In these tasks, two datasets, one from Rocklin *et al*[12], and the other from Sarkisyan *et al*[13] were used. The former includes the sequences and chymotrypsin stability scores of more than 69,000 de novo designed proteins, natural proteins, and their mutants or other derivants. The latter contains more than 50,000 mutants of GFP from *Aequorea victoria*.

Structural biology has made the tertiary structures of many proteins accessible[14], and the advent of recent breakthrough of AlphaFold 2[15] will likely render protein structures more readily available. Thus far, representation learning of proteins has mostly processed protein primary sequence information, whereas the vast amount of protein tertiary structural information available in the PDB[16] database remains unused. How to utilize protein structural information in deep learning remains a fundamentally important question.

In this work, we present a self-supervised learning framework to learn embedded

representations of protein tertiary structures (PtsRep) (Fig. 1). The learned representations

summarized known protein structures into fixed-length vectors (738 dimensions). These were

then transferred to three tasks: (1) protein fold classification, (2) prediction for protein stability,

and (3) prediction for GFP fluorescence (Fig. 1C). We found that PtsRep performed well for fold

reclassification of unlabeled structures, but most importantly, it significantly outperformed the

benchmark methods (UniRep and TAPE-BERT) in the two protein engineering tasks. Thus, this

self-supervised representation learning approach of protein structures provides an avenue to

approximate or capture the fundamental features of protein structures, and has the promise to

advance protein engineering and drug design.

Methods

1. Encoding of protein tertiary structures by *K* nearest residues

To encode the structural information for each residue in a given protein, we adopted a strategy from an algorithm which enables each residue to be represented by its K nearest residues (KNR) in the Euclidean space[17]. Each single residue was represented by its bulkiness[18], hydrophobicity[19], flexibility[20], relative spatial distance, relative sequential residue distance, and spatial position based on spherical coordinate system (Fig. 1A).

2. Bidirectional language model for self-supervised representation learning of protein structures

Given a protein of n residues $(w_1, w_2, …, w_n)$, for each residue, p is the probability[21] of predicted residue corresponding to the actual residue, and the probability for the sequence was calculated by modeling the probability of the residue at position t (w_t), for the given history[22] $(w_1, w_2, …, w_{t-1})$:

$$p(w_1, w_2, …, w_n) = \prod_{t=1}^{n} p(w_t \mid w_1, w_2, …, w_{t-1})$$

At each position t, the forward long short-term memory (LSTM) layer output a context-dependent representation $\overrightarrow{h_t}$, which was used to predict the next residue w_{t+1} with a Softmax layer[21]. We additionally trained the reverse LSTM to provide a bidirectional context for each residue, which produced the representation $\overleftarrow{h_t}$ for w_t, for the given the history $(w_{t+1}, w_{t+2}, …, w_n)$.

$$p(w_1, w_2, \ldots, w_n) = \prod_{t=1}^{n} p(w_t \mid w_{t+1}, w_{t+2}, \ldots, w_n)$$

77   Our formulation maximized the sum of the log likelihoods in both the forward and backward

78   directions as follows:

$$S = \sum_{t=1}^{n} (log\ p(w_t \mid w_1, w_2, \ldots, w_{t-1};\ \boldsymbol{\theta}_w, \boldsymbol{\theta}_{\overrightarrow{LSTM}}, \boldsymbol{\theta}_s) + log\ p(w_t \mid w_{t+1}, w_{t+2}, \ldots, w_n;\ \boldsymbol{\theta}_w, \boldsymbol{\theta}_{\overleftarrow{LSTM}}, \boldsymbol{\theta}_s))$$

Where, we tied the parameters for the residue representation ($\boldsymbol{\theta}_w$), LSTM layer ($\boldsymbol{\theta}_{LSTM}$) and

the Softmax layer ($\boldsymbol{\theta}_s$) in both the forward and backward directions. At each position t, only the

history information was given to avoid leakage of subsequent sequence position information[23].

We used the cross entropy as the loss function[21]. Then we defined $\boldsymbol{d}$ as the distance from the

current position t, and R($\boldsymbol{t}, \boldsymbol{d}$) or the sum of log likelihood in both the forward and backward

directions as follows:

$$R(t, d) = log\ p(w_t \mid w_1, w_2, \ldots, w_{t-d}; \boldsymbol{\theta}_w, \boldsymbol{\theta}_{\overrightarrow{LSTM}}, \boldsymbol{\theta}_s)$$

$$+\ log\ p(w_t \mid w_{t+d}, w_{t+d+1}, \ldots, w_n; \boldsymbol{\theta}_w, \boldsymbol{\theta}_{\overleftarrow{LSTM}}, \boldsymbol{\theta}_s)$$

85   Similarly, we tied the parameters for the residue representation ($\boldsymbol{\theta}_w$), LSTM layer ($\boldsymbol{\theta}_{LSTM}$) and

86   Softmax layer ($\boldsymbol{\theta}_s$) in both the forward and backward directions. Considering that immediately

87   adjacent amino acid residues may be easy to identify with the input structural information, we

88   omitted these two residues in both directions. The final loss was the average of calculated *Loss*

89   for all position of $\boldsymbol{t}$:

$$Loss(n, d) = \frac{1}{4n - 4d - 2} \sum_{t=1}^{n} \sum_{r=d}^{d+1} R(t, r)$$

90 **3. Additional training details**

91   We chose 768 as the dimension of embedding, which followed the Bidirectional Encoder

92   Representation from Transformers (BERT)[3]. Because the length of each protein sequence was

93   different, we used a batch size of 1 with a constant learning rate 2e-3. Swish[24] activation was

94   applied to each layer as follows:

$$Swish(x) = \frac{x}{1 + e^x}$$

Considering that the activations of each layer had a different distribution, a layer

normalization[25] was applied to each layer.

For these stacked networks, the optimizer Adam[26] was selected. The model was trained for

2.5 million weight updates corresponding to ~1 epoch. Convergence was determined as no

improvement in the validation contrastive loss for 5 epochs.

4. Datasets

1) Self-supervised learning dataset.

We used ProteinNet[27] as the training and validation set of the self-supervised model. We first

collected the 90% thinning version of ProteinNet12[27], which had 49,600 protein chains with

tertiary structures. Then we excluded the protein chains (i) which have missing Cα coordinates,

or (ii) which are longer than 700 aa or shorter than 30 aa. The resulting dataset had 35,568

protein chains. We used 95% of the data as the training dataset, and 5% as the validation dataset.

2) Stability landscape prediction dataset

We used the dataset from Rocklin et al[12]. This set includes the sequences and chymotrypsin

stability scores of 69,034 proteins (17,773 de novo designed proteins, 10,674 mutants of these

designed proteins, 1,193 natural proteins, 2,423 mutants of these natural proteins, 24,900

scrambled versions of the proteins, and 12,071 control inactivated sequences where a buried

aspartate residue was inserted) (Supplementary Table 1). Among these proteins or mutants, we

used a total of 16,431 proteins or mutants with structural information (16,159 de novo designed

mini proteins and 272 natural proteins) for training and validation, and 12,851 point mutants of

14 de novo designed proteins and 3 natural proteins with structural information for testing[12]. For

training and validation, we used an 80%/20% splitting strategy.

3) Fluorescence landscape prediction

We used the dataset from Sarkisyan et al[13], which contains more than 50,000 mutants of

green fluorescent protein from *Aequorea victoria*. The number of mutations in the mutants were

from 1 to 15[28]. Following a previous study, we used the mutants with 1~3 mutations for training

and validation, and used the mutants with 4 or more mutations for testing[15]. For training and

validation, we used an 80%/20% splitting strategy (Supplementary Table 1).

4) Benchmark representations

We used UniRep, which is an mLSTM model trained on about 24 million protein sequences,

as a benchmark representation[10]. We downloaded the trained weights and obtained the

representations using the code in https://github.com/churchlab/UniRep. We chose the

1900-dimensional UniRep representation, which was reported to perform best among the

different dimensions[10].

We also used TAPE-BERT trained on about 32 million protein sequences as a second

benchmark representation[3]. We downloaded the trained weights and obtain the representation

using the code in https://github.com/songlab-cal/tape.

Results

1. How PtsRep learned the representations of protein tertiary structures

The framework used in our work consists of three steps as shown in Fig. 1. (A) To feed the protein tertiary structural information, we adopted an algorithm[17] which enables each residue to be represented by the properties of its K nearest residues (KNR) in the Euclidean space[17]. We had varied K, and set it at 15 after optimization (data not shown). A dataset of 35,568 protein chains were selected from PDB, with 95% used for training, 5% for validation. (B) To learned the structural representations, we first used Bi-LSTM to extract embedded features of protein tertiary structures, and then iterated the subnetwork by maximizing the accuracy of predicting the four nearest noncontiguous residues at each amino acid residue of a given protein structure, *i.e.*, positions -3, -2, +2, +3 (the present residue is defined as position 0), after preliminary optimization (data not shown). This yielded an optimal model, which summarized any protein tertiary structures into 768-dimensional vectors of the protein sequence length. (C) Finally, this trained PtsRep was applied to protein engineering tasks through a downstream network, as shown in Fig. 1C. To better align with the benchmark TAPE-BERT[11], we used the same linear regression model.

2. PtsRep performed well for protein fold classification

To examine what PtsRep learned from the PDB dataset, we used t-distributed stochastic neighbor embedding (t-SNE)[29] to test its unsupervised clustering ability of 15,444 semantically related but unlabeled proteins, which have been classified by the Structural Classification of

Proteins (SCOP)[30]. We found that PtsRep separated the five different types of proteins well (Fig.

2, right column). Using the Davies-Bouldin Index[31] (DBI), a general index for evaluating

clustering algorithms, we found that the DBI for PtsRep was only 1.27. In contrast, for the

baseline representation KNR which utilized the same amount of structural information but

without the training of PtsRep, the DBI was 11.62 (Fig. 2, left column). Therefore, the trained

PtsRep model improved the clustering by 9.2 times in this SCOP classification task.

3. PtsRep outperformed benchmarks on protein stability prediction

We then used the downstream tasks as shown in Fig. 1C to further evaluate the protein

structural embeddings learned by PtsRep. As shown in Table 1, we compared Spearman's ρ,

accuracy (ACC), MSE. Protein stability is a key point of protein engineering that has influence

on the production yields[32] and reaction rates[33]. In this study, the dataset from Rocklin et al[12]

consists of the following four protein topological structures: $\alpha\alpha\alpha, \alpha\beta\beta\alpha, \beta\alpha\beta\beta, \beta\beta\alpha\beta\beta$, where

α denotes a helix and β denotes a sheet. It should be noted that the training/validation dataset for

the benchmarks UniRep and TAPE-BERT contains 56,180 proteins (Supplementary Table 1),

among which only 16,431 with structural information were suitable for the PtsRep in this study.

Thus, PtsRep was trained on only 29.3% of the data used for UniRep and TAPE-BERT. However,

all the proteins in the test dataset for the benchmarks have solved structures, thus the same test

dataset was used for both UniRep and TAPE-BERT, and PstRep in this study.

We found that PtsRep significantly outperformed the best benchmark TAPE-BERT

(Spearman's ρ = 0.79 *versus* 0.73), and much more so against the baseline KNR (Spearman's ρ =

0.79 *versus* 0.37). PtsRep also showed generally better performance on accuracy and MSE,

compared with the benchmarks. Interestingly, the benchmark UniRep performed diffidently for

different protein topologies (e.g., *αββα, ααα*), but PtsRep performed more evenly in this aspect,

with one of the smallest standard deviations among all the methods, which was significantly

better compared with the benchmark UniRep (0.11 *versus* 0.25), but was similar to that of BERT

(0.11 *versus* 0.08) (Supplementary Table 2).

4. PtsRep improved the efficiency of green fluorescent protein engineering

Fluorescent proteins are useful in conveniently assessing the protein fitness landscapes in

terms of activity[13]. As described in the previous study[11] using the GFP mutant dataset of

Sarkisyan *et al*[13], we allocated the mutants with 1~3 mutations as the dataset for training and

validation, and the mutants with 4 or more mutations as the dataset for testing. As shown in Table

1, PtsRep outperformed the benchmarks for the test dataset (Spearman's $\rho = 0.70$ *versus* 0.67).

We wanted to explore what these metrics mean for the actual practice of protein engineering.

To this end, we directly probed how much "testing budget" PtsRep would take to arrive at (or

"prioritize") target mutants. We selected the top 0.1% of the GFP mutants in the test dataset in

terms of brightness, or 26 mutants in total (with 4 to 15 mutations), and tested the ability of each

method to prioritize this set of brightest GFP under different test budgets. We trained one-hot,

KNR representations as the baselines. As shown in Fig. 3A, PtsRep performed better than the

benchmarks UniRep and BERT, and significantly better than the baselines. For example, PtsRep

achieved a 70% recall rate for this top 0.1% mutants with about 380 mutants searched, compared

with 559 for BERT, 737 for UniRep, and 1,609 for the baseline KNR (Fig. 3A).

Subsequently, we probed how many trials PtsRep would take to identify the single brightest

GFP protein. As shown in Fig. 3B, we found that the brightest protein was found at the 28^{th} trial

for PtsRep. The next best approach arrived at around the 70^{th} trial, or at a cost of 150% more. It

took 497 trials for the baseline KNR.

We again used t-SNE to test the ability of PtsRep to cluster the GFP mutants. As shown in

Fig. 4, for PtsRep the mutants with bright fluorescence were more clustered with a DBI index of

2.53, compared to KNR with a more scattered distribution with a DBI of 4.62 (Supplementary

Table 3).

Discussion

In this work, we presented a self-supervised learning-based framework to learn general

representations from unlabeled protein tertiary structures in the PDB database (PtsRep), and

transferred the learned model for two presently well recognized protein engineering benchmark

tasks: predictions of protein stability and GFP fluorescence, based on two commonly available

datasets. PtsRep enabled outstanding and partially superior performances on both tasks,

compared with the protein sequences-based benchmark methods UniRep and TAPE-BERT.

As far as protein engineering is concerned, while our study showed that one can extrapolate

results from mutants of 1-3 mutations for mutants of 4-15 mutations, an optimal experimental

search strategy remains to be further defined, for using deep learning to reduce the experimental

burden for a better practice of protein engineering. It is also possible to combine PstRep with

simulated annealing[34] and Bayesian optimization[35], and use PstRep for disease diagnosis, by

estimating the effects of nonsynonymous single-nucleotide polymorphisms[10,36,37].

While what deep learning learns from data is often considered a black box, we strived to

partially dissect what PtsRep has learned from the PDB database. We surmised that PtsRep has at

least understood which protein structures are stable, since unstable protein structures would not

have appeared in the PDB database, since unstable protein structures lead to inactive protein

mutants. We also know from the practice of directed evolution of enzymes that about 30% of

randomly mutated protein variants are inactive[38]. This explains in part the improvement we saw

for the better performance of PtsRep as shown in Fig. 3. This is also consistent with the fact that

PtsRep is able to perform much better than KNR, in terms of protein fold classification, as shown

in Fig. 2.

However, what remains to be understood is how PtsRep is able to better cluster GFP variants

with higher activities (Fig. 4). A similar observation was found for TAPE-BERT, which is based

on protein sequences. It is noteworthy that the KNR format input for PtsRep in this study

contains protein primary sequence information, thus it is likely that the better clustering of GFP

seen for PtsRep was also sequence-based.

Last but not the least, we wish to point out that, comparing to the best benchmark

TAPE-BERT, which used semi-supervised learning with 96 million parameters to train a deep

contextual language model on 32 million sequences, our model was built with only 2.6 % of the

parameters, and trained on only 0.11% of the protein entries (*i.e.*, those with structural

information).

Acknowledgments

This work was supported by the National Key R&D Program of China (2018YFA0901000), and the Guangzhou Science and Technology Program key projects (201904020016). We thank Xing Zhang for technical assistance.

References

1   Mikolov T, Chen K, Corrado G *et al*. Efficient estimation of word representations in vector

space. *arXiv*, 1301.3781 (2013).

2   Peters M E, Neumann M, Iyyer M *et al.* Deep contextualized word representations.

arXiv:1802.05365 (2018).

3   Devlin J, Chang M-W, Lee K *et al.* BERT: Pre-training of deep bidirectional transformers

for language understanding. *arXiv*, 1810.04805 (2019).

4   Gidaris S, Singh P, Komodakis N. Unsupervised representation learning by predicting image

rotations. *arXiv*,1803.07728 (2018).

5   Goyal P, Mahajan D, Gupta A *et al.* Scaling and Benchmarking Self-Supervised Visual

Representation Learning. *International Conference on Computer Vision*, 6400-6409 (2019).

6   Heinzinger M, Elnaggar A, Wang Y *et al.* Modeling aspects of the language of life through

transfer-learning protein sequences. *BMC Bioinformatics* **20**, 723 (2019).

7   Yang K K, Wu Z, Bedbrook C N *et al.* Learned protein embeddings for machine learning.

Bioinformatics **34**, 2642-2648 (2018).

8   Rives A, Meier J, Sercu T *et al.* Biological structure and function emerge from scaling

unsupervised learning to 250 million protein sequences. *bioRxiv*, 622803 (2020).

9   Bepler T, Berger B. Learning protein sequence embeddings using information from structure.

arXiv,1902.08661 (2019).

10 Alley E C, Khimulya G, Biswas S *et al.* Unified rational protein engineering with

sequence-based deep representation learning. *Nature Methods* **16**, 1315-1322 (2019).

11   Rao R S, Bhattacharya N, Thomas N *et al.* Evaluating protein transfer learning with TAPE.

Advances in Neural Information Processing Systems **32**, 9689-9701 (2019).

12   Rocklin G J, Chidyausiku T M, Goreshnik I *et al.* Global analysis of protein folding using

massively parallel design, synthesis, and testing. *Science* **357**, 168-174 (2017).

13   Sarkisyan K S, Bolotin D A, Meer M V *et al.* Local fitness landscape of the green

fluorescent protein. *Nature* **533**, 397-401 (2016).

14   Jin P, Bulkley D, Guo Y *et al.* Electron cryo-microscopy structure of the

mechanotransduction channel NOMPC. *Nature* **547**, 118-122 (2017).

15   Jumper J, Evans R, Pritzel A *et al.* High accuracy protein structure prediction using deep

learning. *Fourteenth Critical Assessment of Techniques for Protein Structure Prediction*

(Abstract Book), 22-24 (2020).

16   Berman H M, Kleywegt G J, Nakamura H *et al.* The protein data bank archive as an open

data resource. *Journal of Computer-aided Molecular Design* **28**, 1009-1014 (2014).

17   Wang J, Cao H, Zhang J Z H *et al.* Computational Protein Design with Deep Learning

Neural Networks. *Scientific Reports* **8**, 6349 (2018).

18   Zimmerman J M, Eliezer N, Simha R. The characterization of amino acid sequences in

proteins by statistical methods. *Journal of Theoretical Biology* **21**, 170-201 (1968).

19   Kyte J, Doolittle R F. A simple method for displaying the hydropathic character of a protein.

Journal of Molecular Biology **157**, 105-132 (1982).

20 Huang F, Nau W M. A conformational flexibility scale for amino acids in peptides.

Angewandte Chemie International Edition **42**, 2269-2272 (2003).

21 Bengio Y, Ducharme R, Vincent P *et al.* A neural probabilistic language model. *Journal of*

Machine Learning Research **3**, 1137-1155 (2003).

22 Jozefowicz R, Vinyals O, Schuster M *et al.* Exploring the limits of language modeling. *arXiv*,

1602.02410 (2016).

23 Peters M E, Ammar W, Bhagavatula C *et al.* Semi-supervised sequence tagging with

bidirectional language models. *Proceedings of the 55th Annual Meeting of the Association*

for Computational Linguistics, 1756-1765 (2017).

24 Ramachandran P, Zoph B, Le Q V. Searching for activation functions. *arXiv*, 1710.05941

(2017).

25 Ba J L, Kiros J R, Hinton G E. Layer normalization. *arXiv*, 1607.06450 (2016).

26 Kingma D P, Ba J L. Adam: A method for stochastic optimization. *arXiv*, 1412.6980 (2015).

27 Mohammed A. ProteinNet: a standardized data set for machine learning of protein structure.

BMC Bioinformatics **20**, 311 (2019).

28 Huang P S, Boyken S E, Baker D. The coming of age of de novo protein design. *Nature* **537**,

320-327 (2016).

29 van der Maaten L, Hinton G. Visualizing Data using t-SNE. *Journal of Machine Learning*

Research **9**, 2579-2605 (2008).

30 Fox N K, Brenner S E, Chandonia J M. SCOPe: Structural Classification of Proteins -

extended, integrating SCOP and ASTRAL data and classification of new structures. *Nucleic*

Acids Research **42**, D304-309 (2014).

31 Davies D L, Bouldin D W. A cluster separation measure. *IEEE Transactions on Pattern*

Analysis and Machine Intelligence **1**, 224-227 (1979).

32 Kwon W S, Da Silva N A, Kellis J T, Jr. Relationship between thermal stability, degradation

rate and expression yield of barnase variants in the periplasm of Escherichia coli. *Protein*

Engineering, Design and Selection **9**, 1197-1202 (1996).

33 Bommarius A S, Paye M F. Stabilizing biocatalysts. *Chemical Society Reviews* **42**,

6534-6565 (2013).

34 Biswas S, Kuznetsov G, Ogden P J *et al.* Toward machine-guided design of proteins. *bioRxiv*,

337154 (2018).

35 Yang K K, Chen Y X, Lee A *et al.* Batched stochastic Bayesian optimization via

combinatorial constraints design. *International Conference on Artificial Intelligence and*

Statistics **89** (2019).

36 Fang J. A critical review of five machine learning-based algorithms for predicting protein

stability changes upon mutation. *Briefings in Bioinformatics* **21**, 1285-1292 (2020).

37 Li M, Kales S C, Ma K *et al.* Balancing protein stability and activity in cancer: a new

approach for identifying driver mutations affecting CBL ubiquitin ligase activation. *Cancer*

research **76**, 561-571 (2016).

38 Romero P A, Arnold F H. Exploring protein fitness landscapes by directed evolution. *Nature*

Reviews Molecular Cell Biology **10**, 866-876 (2009).

Figure 1. Workflow of PtsRep for learning and applying protein tertiary structure representations.

(A) Protein structures from PDB were encoded with the KNR (K nearest residues) algorithm,

with each amino acid represented by the nearest 15 amino acids and their features. (B) PtsRep

was trained to perform contextual noncontiguous residue prediction using a cross-entropy loss

function, and internally represent proteins. (C) A regression neural network was used to transfer

the embedded representations for downstream protein engineering tasks.

Figure 2. t-SNE (t-distributed stochastic neighbor embedding) representations of KNR (left) and

PtsRep (right) for 15,444 proteins classified by the Structural Classification of Proteins (SCOP)[30],

respectively. t-SNE projections from embedded space onto a low dimensional representation are

shown, which represent sequences from SCOP colored by ground-truth structural classes of five

types: alpha, beta, alpha/beta, alpha+beta, and small proteins.

339

340 **Figure 3. (**A) The brightest 0.1% of GFP mutants observed *versus* the testing budget for each

341 representation method. The abscissa uses an exponential scale. (B) The trials taken to identify the

342 brightest GFP mutant for each representation method.

Figure 4. t-SNE visualization of KNR (left) and PtsRep (right) for GFP mutants with 4 to 15

mutations, respectively.

349 **Table 1.** Embedding performances of downstream tasks, using outlined benchmarks or baselines.

Method	Param	Data	Stability			Fluorescence		
			ρ	ACC	MSE	ρ	ACC	MSE
UniRep[10]	182M	24M	0.73*	0.69*	0.15	0.67*	0.96	**0.20***
BERT[11]	92M	32M	0.73*	0.70*	0.12	0.68*	0.96	0.22*
Bepler[9]	19M	0.02M	0.64*	0.67*	-	0.33*	-	2.17*
One-Hot	0	32M	0.19*	0.58*	0.70	0.14*	0.86	2.69*
KNR	0	0.04M	0.37	0.71	0.38	0.67	0.92	0.66
PtsRep	2.5M	0.04M	**0.79**	**0.73**	**0.09**	**0.70**	**0.97**	0.57

350 * taken from ref [11].