Knowledge graph analytics platform with LINCS and IDG for Parkinson's disease target illumination

Jeremy J Yang[1,2,4], Christopher R Gessner[1,3], Joel L Duerksen[2], Daniel Biber[2], Jessica L Binder[4], Murat Ozturk[1,2], Brian Foote[2], Robin McEntire[2], Kyle Stirling[1,2], Ying Ding[1,2,5] and David J Wild[1,2]

[1]*School of Informatics, Computing and Engineering, Indiana University, Bloomington, IN, USA.*
[2]*Data2Discovery, Inc., Bloomington, IN, USA.*
[3]*Chemical Abstracts Service, Columbus, OH, USA.*
[4]*Dept. of Internal Medicine Translational Informatics Division, University of New Mexico, Albuquerque, NM, USA.*
[5]*School of Information, Dell Medical School, University of Texas, Austin, TX, USA.*

Corresponding author: **David Wild**
Email address: djwild@indiana.edu

Abstract

Background

LINCS, "Library of Integrated Network-based Cellular Signatures", and IDG, "Illuminating the Druggable Genome", are both NIH projects and consortia that have generated rich datasets for the study of the molecular basis of human health and disease. LINCS L1000 expression signatures provide unbiased systems/omics experimental evidence. IDG provides compiled and curated knowledge for illumination and prioritization of novel drug target hypotheses. Together, these resources can support a powerful new approach to identifying novel drug targets for complex diseases, such as Parkinson's disease (PD), which continues to inflict severe harm on human health, and resist traditional research approaches.

Results

Integrating LINCS and IDG, we built the Knowledge Graph Analytics Platform (KGAP) to support an important use case: identification and prioritization of drug target hypotheses for associated diseases. The KGAP approach includes strong semantics interpretable by domain scientists and a robust, high performance implementation of a graph database and related analytical methods, using Neo4j. Illustrating the value of our approach, we investigated results from queries relevant to PD. Approved PD drug indications from IDG's resource DrugCentral were used as starting points for evidence paths exploring chemogenomic space via LINCS expression signatures for associated genes, evaluated as target hypotheses by integration with IDG. The KG-analytic scoring function was validated against a gold standard dataset of genes associated with PD as elucidated, published mechanism-of-action drug targets, also from DrugCentral. IDG's resource TIN-X was used to rank and filter KGAP results for novel PD targets, and one, SYNGR3 (Synaptogyrin-3), was manually investigated further as a case study and plausible new drug target for PD.

Conclusions

The synergy of LINCS and IDG, via KG methods, empowers graph analytic methods for the investigation of the molecular basis of complex diseases, and specifically for identification and prioritization of novel drug targets. The KGAP approach enables downstream applications via integration with resources similarly aligned with modern KG methodology. The generality of the approach indicates that KGAP is applicable to many disease areas, in addition to PD, the focus of this paper.

Keywords

Knowledge graph, graph analytics, systems biology, drug discovery, drug target, druggable genome, Parkinson's disease

Background

Integration of heterogeneous datasets is often essential for biomedical knowledge discovery, where relevant evidence may derive from diverse subdomains that include but aren't limited to: foundational biology, chemistry, clinical data, and social sciences of epidemiology and health economics. Furthermore, there is a need for judicious selection of data types and datasets to integrate, driven by scientific use cases, guided by applicability, accessibility, and veracity of datasets. Accordingly, we have integrated LINCS and IDG to identify and prioritize novel drug target hypotheses, via KG methods and tools. LINCS content includes assay results from cultured and primary human cells treated with bioactive compounds (small molecules or biologics) or genetic perturbations. IDG data utilized in this study include drug-disease associations, gene-disease associations and bibliometric scores from literature text mining.

Synergy of LINCS and IDG. LINCS and IDG are NIH Common Fund(1) projects, chosen for integration for specific applicability to drug target discovery. LINCS, Library of Networked Cell-based Signatures, is described as a "System-Level Cataloging of Human Cells Response to Perturbations"(2) and features experimental and computational methodology designed to generate useful biomedical knowledge from a systems/omics framework. As a key example, perturbagens (e.g., small molecules, ligands such as growth factors and cytokines, micro-environments, or CRISPR gene over-expression and knockdowns representing disease phenotypes) are characterized by proteomics, transcriptomics (RNA-seq), or biochemical and imaging readouts. Therefore LINCS provides useful mapping from genome to phenome with direct relevance to biomolecular mechanisms and therapeutic hypotheses. IDG(3), with its Target Central Resource Database (TCRD) and data portal Pharos(4), integrates heterogeneous datasets from IDG experimental centers and diverse external sources with a clear purpose, to illuminate understudied ("dark") protein-coding genes as potential drug targets. IDG is particularly strong in text mining of current biomedical literature and bibliometrics suited for knowledge discovery and evidence evaluation, focused on the sciences of drug discovery research. In addition, another featured resource of IDG is DrugCentral(5). DrugCentral provides information on active ingredients, chemical entities, pharmaceutical products, and their biological targets.

We have combined the complementary strengths of LINCS and IDG to derive new drug discovery insights via these synergies, particularly drug target hypotheses associated with diseases, phenotypes and cell lines. LINCS provides the comprehensive systems/omics view, while IDG focuses on relevant and robust evidence for drug target knowledge and validation. Table 1 summarizes key concepts and the semantic linkage of LINCS and IDG. Previously, LINCS studies have been designed to identify novel drug targets(6), and IDG has included LINCS as a source for selected data(7). However, our approach provides a new KG method and platform to integrate and add value from these sources for an urgent and unmet scientific use case.

Table 1: Key concepts from LINCS and IDG

LINCS key concepts	IDG key concepts

L1000: Broad Institute microarray platform and LINCS project involving landmark genes. **Landmark Gene**: approximately 1000 genes representing the full human genome, from which a maximum set of gene responses can be inferred. **Cell Lines**: Primary cells and human patient induced pluripotent stem cells (iPSCs) representing diverse tissues and disease states (including 'healthy' controls). **Perturbagen**: A perturbagen may be chemical (drug-like), biologics, or genetic. **Signatures**: Various assays (transcriptomics, proteomics, or image analysis) are integrated together to identify patterns of common networks and cellular responses leading to predictive mechanistic interpretations.	**Target**: Drug targets normally defined as human proteins or equivalently protein coding genes. **Mechanism of action**: Known, published, biochemical mechanism of pharmacological effect. **Disease**: Working definition is anything which could be the clinical indication for a drug. **Ligand**: Small molecule with known or hypothesized relationship with one or more targets. **Target Development Level (TDL)**: Simple measure of illumination: Tdark, Tbio, Tchem and Tclin. **Target Importance and Novelty:** Bibliometric measures from TIN-X for target prioritization.
LINCS-IDG semantic linkage	
LINCS centers utilize in-depth gene and protein expression assays to generate signatures directly mappable to IDG protein targets. Disease and phenotype ontology mapping is a community challenge with useful, working solutions such as OMOP and UMLS. LINCS perturbagens include rigorously defined chemical entities and small molecule drugs included in IDG resource DrugCentral. Therefore, LINCS's vast number of human cell lines and experimental chemical perturbation datasets, combined with IDG's protein targets (gene and protein IDs) and DrugCentral active pharmaceutical ingredients (drug compounds) databases, provide a tightly integrated combination resource for drug target discovery.	

Figure 1: Schematic of overall logic, that strong knowledge of approved drugs and cell lines associate diseases via LINCS expression signatures to differentially expressed genes, for IDG filtering and druggability evaluation.

Results

Graph analytics for evidence aggregation

We used the list of PD drugs as starting points for evidence paths in KGAP to identify likely and
novel PD targets. KGs in general and Neo4j in particular provide an intuitive and powerful way
to aggregate instances of evidence paths, yielding a score measuring the aggregated evidence.
As illustrated schematically in Figure 1, each evidence path connects a drug with expression
signature and gene. The magnitude of the expression perturbation is represented by a z-score
which can be used for thresholding and/or weighting. The search resulted in 641 genes, ranked
by KGAP score produced by the Cypher query Listing 1 in Methods.

Validation versus known mechanism-of-action targets

There is a necessity to solve the ongoing fundamental challenges of molecular biomedicine.
Specifically, there are no gold standard validation datasets of causal or druggable genes for
complex diseases, including cancers, neurodegenerative, metabolic, and cardiovascular
diseases. Therefore it is pertinent to elucidate and modulate the genomic basis of diseases, and
to a significant degree, fundamental uncertainties and difficulties concerning the definitions and
diagnostic criteria for complex diseases such as PD. Mindful of these difficulties, we validated
against a dataset of known drug targets, for the same PD drugs described above, all based on
peer-reviewed references, and with elucidated mechanism-of-action (MoA), as manually curated
in the DrugCentral database. Given the scientific and regulatory standards for efficacy met by
approved drugs, and the standards of evidence for peer-reviewed, manually curated MoA
targets, we consider this approach the most useful and informative dataset validation available.

LINCS is experimental based, thus derived independently from the curation of MoA targets from
DrugCentral, or in machine learning terms, there is strict separation of training and test data.
115

Figures 2a-d: ROC curves with AUC for degree-only and z-score weighted evidence path
graph analytics, validated against DrugCentral PD targets and known-with-MoA targets.

116
Figures 2a-d show validation receiver operating characteristic curve (ROC) plots for two
variations of our method, and two validation sets. The "D-weighted" variation connotes
weighting of evidence paths by the sum of degree at the LINCS expression signatures
associating drugs and genes. The "Z-weighted" variation combines degree with the z-score
expression level attribute associating signatures and genes. The two validation sets are (1)
DrugCentral PD targets, and (2) DrugCentral PD targets with known MoA, as described above.
The ROC AUC (area under the curve) values range between 0.64 and 0.74, providing
consistent, independent validation of the proposed method for disease to gene association
discovery. The validation method, for PD or other disease queries, is reproducible using the
source code repository referenced in the Availability of Data and Materials section. Note, the
validation presented does not validate KGAP as a classification method. Evaluated as such,
given the sparsity of known genes, the specificity is very poor. However, classification is not the

goal. Rather, our task is to aggregate and assess experimental evidence from LINCS which is
applicable to PD as proof of concept. The validation presented simply measures
overrepresentation, or enrichment, of known PD genes in relation to KGAP scores, indicating
agreement and independent confirmation between two very different sources of knowledge, one
purely experimental, the other expertly curated and peer-reviewed publication based.

134 Genes associated with PD, prioritized via IDG

Gene hitlists generated by KGAP were mapped to druggability data from IDG. Target
Development Level (TDL) provides a high-level classification into four groups — Tclin, Tchem,
Tbio and Tdark — with respect to the depth of investigation from a clinical, chemical and
biological standpoint. Further evaluation was explored via Target Importance and Novelty
Explorer (TIN-X)(8), an IDG project and bibliometric algorithm for evaluating disease-target
associations from scientific literature. Moreover, TIN-X defines **novelty** as a bibliometric
measure of occurrence rarity in the full PubMed corpus of titles and abstracts, and **importance**
as a bibliometric measure of co-occurrence associating a specific disease and gene. The
premise and motivation for IDG is that many understudied targets could offer new opportunities
for medicines of novel therapeutic benefit. Hence TIN-X ranks and presents targets based on
the principle of non-dominated solutions optimizing novelty and importance. nds_rank=1 is
assigned to all genes relative to which none are superior in both dimensions. nds_rank=2 is this
corresponding set with the first set removed, etc. In practice, typical users browse targets
beginning at the outer boundary, using TDL color code as an additional guide.
149

Figures 3a-c: TIN-X scatterplot of genes for Parkinson's disease, DOID:14330, showing pop-up details for SYNGR3, Synaptogyrin-3, and publication details view for PD associated gene *SYNGR3*.

Case study: SYNGR3, Synaptogyrin-3

To illustrate a typical use case, the KGAP hitlist was browsed for drug target illumination
potential based on annotations from IDG. The highest ranked gene classified as Tdark is
SYNGR3, Synaptogyrin-3. The exact function of SYNGR3 is unclear. However, recently a group
provides evidence in the murine brain that *SYNGR3* encodes for a synaptic vesicle protein that
interacts with a dopamine transporter(9). One of PD's hallmark characterizations is the loss of
nigrostriatal dopaminergic innervation(10). The high TIN-X rank (nds_rank=6 out of 103)
indicates both novelty and importance (PD-relevance), as shown in figure 3a. Additionally, in
figures 3b and 3c, two reference publications from the same authors, present experimental and
theoretical evidence for connection between statin drugs, therapeutic effectiveness for PD, and
the gene *SYNGR3*(11,12). Figure 4 displays evidence paths connecting *SYNGR3* with
associated expression signatures and drugs, matched by our method.
163

Figure 4: Evidence paths generated from Cypher queries on our Neo4j graph database, for case study *SYNGR3*, showing associated expression signatures and drugs.

164   Discussion

This project builds upon numerous prior efforts and resources, conceptual and technological,
from domain specific data semantics, to graph database advances, conferring interoperability of
depth and breadth(13–19). That is, beyond interoperable digital formats, scientists interacting
effectively and rigorously via computational tools and interfaces. Regarding the now-common
term *knowledge graph (KG)*, there are variations of meaning, but we emphasize: (1) Knowledge
with strong semantics via rigorous data modeling; (2) Graph databases are powerful and
intuitive for many biomedical applications and users(20); (3) Neo4j concretely implements a rich
suite of tools (DBMS, query language, APIs, GUI) as an exemplar among graph database
systems. Hence, we use the term KG unambiguously and with specific commitments.
Advances in KG technologies have empowered progress far beyond previous efforts. A case in
point is Chem2Bio2RDF(14,21), developed in the Wild Lab, enabled by RDF and Sparql but
limited for analytic applications by availability of high-performance triple-store technologies.
Another project which one of us (JY) has co-developed is CARLSBAD(22), a bioactivity
knowledge graph limited in analytics performance and versatility by its implementation as a
relational database. Additional lessons learned relate to (1) Generality versus purposefulness,
and (2) Volume versus veracity. Accordingly, this project has prioritized quality and simplicity to
mitigate the common problems of (1) unfocused, incoherent interfaces, and (2) unreliable or

noisy data. Interpretability also depends on understanding of the tool's purpose, logic, results,
and their provenance and confidence. In many cases, simple and clearly focused tools enhance
comprehensibility and usability. In contrast, a toolkit is multi-purpose. For this research the key
aim is to find gene associations based on a disease or drug query.

Though the Neo4j product is featured prominently in this paper, it is important to note that
alternative capable graph databases exist, such as DGraph(23) and Amazon Neptune(24).
Moreover, Neo4j and other graph databases are built on the shoulders of many diverse
contributors and strands of computer science, thus, Neo4j is featured as an exemplar for these
advances, and a powerful technology for our use case.

Development of this knowledge graph analytics platform (KGAP) with LINCS and IDG was
motivated by use cases from IDG and its core purpose to illuminate understudied genes and
new drug targets. Generally stated: For a given disease, what new drug targets are suggested
by the evidence? LINCS data provides aggregated experimental evidence to establish a cell
and expression signature based systems biology database, supporting rational aggregation of
disease-gene associations, powered by KG analytics well suited both to path-based analytics
and interpretation. Representing PD informatically is another key ingredient, addressed by
clinical indications for approved drugs, knowledge meeting high regulatory standards. The
definitions and nosology of PD and other complex diseases are critical issues and limitations
relevant to this study and many others. Any hypotheses regarding PD presumes a useful
definition, however biologically PD and its complexity are better described by subtypes and
clinical phenotypes. Yet, extant data is generally organized by diseases and clinical diagnoses
as historically developed.

204 Conclusions

A knowledge graph analytic platform (KGAP) was developed, integrating datasets from LINCS
and IDG, for efficient search and aggregation of evidence paths based on a disease query, to
identify, score and rank associated genes as drug target hypotheses. Approved indications for
prescription drugs were used as high confidence entry points into the KG, and published MoA
targets were used as a high confidence validation set. Modern graph database systems such as
Neo4j provide a powerful suite of tools for high performance analytics, rigorously and
reproducibly encoded, on semantically rich KGs, with interactivity and visualization enhancing
human understanding. This study has demonstrated how KGAP can generate novel and
plausible drug targets for Parkinson's disease. It includes a case study of the understudied
"Tdark" *SYNGR3* gene, scored highly by KGAP and supported independently by publications
identified via the IDG application TIN-X. The KGAP approach and method as implemented is
generalizable and applicable to drug target illumination in many other disease areas.
Accordingly, in future work we intend to apply KGAP more broadly.
218

Methods

Graph database

Graph databases are one category of NoSQL (non-SQL or non-relational) databases which are designed to outperform relational databases for some specialized datasets and analyses, and are well suited for representing and exploring complex biological systems(25–27). Just as graph diagrams provide an intuitive way to represent and explore relationships between entities, graph databases leverage this intuition to provide both a physical storage method, and approach for combining diverse datasets for exploration and analysis. Neo4j was chosen as an exemplary leader among graph databases with a rich set of graph based capabilities (e.g. Graph Data Science library, and libraries for accessing, flat files, databases, existing open standards such as SPARQL, and open standard in development GQL(28)). In addition, Neo4j offers a free, open source community edition(29), powerful and user-friendly desktop client, APIs, ample documentation, and a vibrant and supportive user community.

Data Sources

As shown in Figure 1 an understanding of entities and the relationships between them can be quickly represented in a representative graph diagram, this establishes high level concepts and methods for discovering new insights, but also provides a clear design for the required extract transform and load (ETL) steps for building the capability. The datasets listed here were used to construct a graph database instantiation of this design. From LINCS we used the L1000 Phase I and II Level 5 differential gene expression data(30). Level 5 connotes the highest level of processing, normalization, evidence aggregation, and therefore confidence, interpretability, and interoperability. LINCS was processed using the same pipeline used by colleagues for the DrugCentral LINCS drug profiling tool, whereby differential gene expression data across 81 cell-lines were mapped to 1613 unique drug active pharmaceutical ingredients(5). Data and metadata files available from the LINCS Data Portal and NCBI GEO were ETL-ed via 1.5TB PostgreSQL db. DrugCentral(5) (June 2020 version) was used for indications, ATC codes, chemical structures and other properties. IDG's TCRD, Target Central Resource Database(31), (v6.7.0) provides gene properties including target development level (TDL: Tclin, Tchem, Tbio, Tdark) and gene family information.

Data modeling, representing the knowledge

Graphs in Neo4j are composed of nodes and relationships, which correspond with vertices and edges in graph theory terms, respectively. Graph queries can be thought of as patterns for matching paths through the graph, which consist of specified relationship types, each between two nodes, a semantic triple, subject-predicate-object. Neo4j is considered a schema-less database, meaning that data is loaded without constraints. But a strict schema with strong semantics informed by domain knowledge can be implemented, and is essential for accurate knowledge representation and interpretability. The meta-model for a graph can be reported by

256 introspective Cypher query (`CALL apoc.meta.graph`). The meta-model for this graph is
257 shown in Figure 5.
258

Figure 5: Neo4j meta graph. Both nodes and relationships have properties which can be used in query filtering and analysis.

259
260 Our graph is constructed of the following.
261
262 **Relationships.** INDICATION is constructed from DrugCentral indications involving a Drug
263 which is also a LINCS perturbagen. CELL_SIGNATURE indicates the Cell type for the LINCS
264 Signature. SIGNATURE_GENE provides the differential expression z-score for the Gene.
265 DRUG_SIGNATURE associates the Drug involved for a given Signature.
266
267 **Nodes.** Concept consists of disease terms from DrugCentral with unique OMOP identifiers, and
268 retaining other disease identifiers as properties for interoperability and extensibility. Drug nodes
269 are derived by filtering for LINCS perturbagens which are in DrugCentral and have one or more
270 indications. Genes are from LINCS, with additional properties added from TCRD (e.g.,
271 development/druggability level). Cell and Signature nodes are from LINCS without filtering.
272
273 Table 2 shows the complete list of relationships present in the graph and count, and Table 3 the
274 list of nodes with counts.
275
276
277 **Table 2:** Type of relationship, source, and total counts

Vertex type	Edge type	Vertex type	Source	Count
Signature	SIGNATURE_GENE	Gene	L1000	45623637
Cell	CELL_SIGNATURE	Signature	L1000	591676

| Drug | DRUG_SIGNATURE | Signature | L1000 | 85814 |
| Drug | INDICATION | Concept | DrugCentral, L1000 | 7164 |

Table 3: Type of node, primary source/ source of additional properties, and total counts

Vertex type	Source	Count
Signature	L1000	591676
Gene	L1000, TCRD	12329
Concept	DrugCentral 2021	2241
Drug	L1000, DrugCentral 2021	1613
Cell	L1000	99

We filter the 45.6M signature associations at z-score threshold $|z|>3$, to identify strong evidence and patterns, which results in 10,663,228 (d:Drug)--(s:Signature)--(g:Gene) paths.

Parkinson's disease drug-set

To apply KGAP to PD knowledge discovery, the set of drugs indicated by PD and related conditions were identified using DrugCentral, which derives drug indication from FDA DailyMed (provides trustworthy information about marketed drugs in the United States), and maps SNOMED to OMOP terms(32) for interoperability. A simple substring search for "Parkinson" matches five terms: "Parkinsonism", "Parkinson's disease", "Arteriosclerotic Parkinsonism", "Dementia associated with Parkinson's Disease", and "Neuroleptic-induced Parkinsonism." Requiring Anatomical and Therapeutic Classification (ATC) "nervous system" is intended to focus on the neurological etiology of PD rather than symptoms. This query returns 25 drugs, shown in Table 4 with their PubChem CID, of which 22 / 25 are present in LINCS. This drug-set represents PD knowledge as in drug-set enrichment analysis (DSEA)(33), analogous to gene-set enrichment analysis (GSEA).

Table 4: Drug-set representing Parkinson's disease

Name	Struct_ID	PubChem_CID	In_LINCS
amantadine	144	2130	*TRUE*
apomorphine	228	6005	*TRUE*
benzatropine	333	1201549	*TRUE*
biperiden	374	2381	*TRUE*
bromocriptine	403	31101	*TRUE*

dexetimide	831	30843	*FALSE*
entacapone	1018	5281081	***TRUE***
levodopa	1567	6047	***TRUE***
melevodopa	1673	23497	*FALSE*
metixene	1780	4167	***TRUE***
opicapone	5143	135565903	*FALSE*
orphenadrine	1999	4601	***TRUE***
pergolide	2105	47811	***TRUE***
pimavanserin	5142	10071196	***TRUE***
piribedil	2202	4850	***TRUE***
pramipexole	2233	119570	***TRUE***
procyclidine	2276	4919	***TRUE***
rasagiline	3521	3052776	***TRUE***
rivastigmine	2392	77991	***TRUE***
ropinirole	2402	5095	***TRUE***
rotigotine	2407	59227	***TRUE***
safinamide	4921	131682	***TRUE***
selegiline	2429	26757	***TRUE***
tolcapone	2697	4659569	***TRUE***
trihexyphenidyl	2745	5572	***TRUE***

Graph analytics for evidence aggregation

KGAP consists of the graph database described plus code and tools used to query the
database for target associations from the input drug-set representing the disease of interest. In
the current version of the platform, the queries were implemented via the Neo4j Python
Driver(34) and our prototype Python3 command-line applications and notebooks. As in the data
modeling in the construction of the database, the Cypher graph queries must be crafted to
accurately express the biomedical question, and justify useful interpretation of results. However,
since the database was designed precisely for target association and ranking, the Cypher
queries involved can be relatively terse. The query used to generate PD target associations is
shown in Listing 1. The scoring function is responsible for aggregating evidence from signature
counts and z-scores, to reflect that confidence increases with additional confirmatory data, and
is an implementation of Stouffer's function for z-score meta-analysis, based on Fisher's function

using p-values(35). Though not used in KGAP for hypothesis testing, the reference indicates the
function is well behaved and combines z-scores as intended.

Listing 1: Cypher query used for PD target association.

```
MATCH p=(d:Drug)-[]-(s:Signature)-[r]-(g:Gene), p1=(s)-[]-
(c:Cell)
WHERE (d.pubchem_cid in [2130, 2130, 2130, 2130, 2381, 2381,
2381, 2381, 4167, 4601, 4850, 4919, 4919, 4919, 4919, 5095,
5572, 5572, 5572, 5572, 6005, 6047, 6047, 6047, 23497, 26757,
30843, 31101, 31101, 47811, 59227, 77991, 119570, 131682,
1201549, 1201549, 1201549, 1201549, 3052776, 4659569, 5281081,
10071196, 135565903])
WITH g, sum(r.zscore)/sqrt(count(r)) AS score
RETURN g.id, g.name, score
ORDER BY score DESC
```

Exploring and visualizing the KG

315 Human interaction with the KG through an effective GUI can greatly facilitate understanding and
316 insights. In this project we used (1) Neo4j Desktop, (2) Neo4j Browser web client, used to
317 produce Figure 5, and (3) Cytoscape (v3.8.1) with the Neo4j plugin, which was used to produce
318 Figure 4.

List of abbreviations

IDG	Illuminating the druggable genome (NIH Common Fund)
KG	Knowledge graph
KGAP	Knowledge graph analytics platform
LINCS	Library of integrated network-based cellular signatures (NIH Common Fund)
MoA	Mechanism of action, describing biomolecular details of drug effect
PD	Parkinson's disease
ROC AUC	Receiver operator characteristic area under curve
TCRD	Target central resource database (IDG)
TDL	Target development level (IDG)

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

Source code for processing and analysis is available publicly under Creative Commons Zero v1.0 Universal license at https://github.com/IUIDSL/kgap_lincs-idg. A Knime workflow is employed to extract, transform and load the graph database from sources, and generate TSV files of nodes and relationships. The database is queried, and results reported and visualized using Python and Cypher. A full dump of the KGAP_LINCS-IDG dataset is available at http://cheminfov.informatics.indiana.edu/projects/kgap/data/dclneodb.dump. Source datasets used to build Neo4j database are: (1) DrugCentral-LINCS database dump: http://cheminfov.informatics.indiana.edu/projects/kgap/data/drugcentral_lincs.pgdump; (2) TCRD targets: http://cheminfov.informatics.indiana.edu/projects/kgap/data/tcrd_targets.tsv.gz. Neo4j Community Edition, Python, Scikit-learn, Cytoscape and other packages used in this work are freely and easily findable and accessible.

Competing interests

JY, JD, BF, DB, KS, YD, and DW are founders, employees or contractors of Data2Discovery, a private company spun off from Indiana University to develop and commercialize knowledge graph technologies.

Funding

None.

Authors' contributions

JY and DW conceived the project. JD designed and built the graph database and ETL workflows. CG and JD developed graph analytic algorithms. JB led the SYNGR3 case study. JY, JD, DB, CG and MO developed client code. JY, JD, CG, DB, and JB co-authored the manuscript. All reviewed and approved the manuscript.

Acknowledgements

We are grateful to the LINCS and IDG projects and investigators responsible for the high value datasets shared with the community and used in this research.

References

1. National Institutes of Health, U.S. Department of Health and Human Services. National Institutes of Health Common Fund [Internet]. NIH Office of Strategic Coordination - The Common Fund. [cited 2020 Dec 21]. Available from: https://commonfund.nih.gov/

2. Keenan AB, Jenkins SL, Jagodnik KM, Koplev S, He E, Torre D, et al. The Library of Integrated Network-Based Cellular Signatures NIH Program: System-Level Cataloging of Human Cells Response to Perturbations. Cell Syst. 2018 Jan 24;6(1):13–24.

3. Oprea TI, Bologa CG, Brunak S, Campbell A, Gan GN, Gaulton A, et al. Unexplored therapeutic opportunities in the human genome. Nat Rev Drug Discov. 2018 May;17(5):377.

4. Sheils T, Mathias SL, Siramshetty VB, Bocci G, Bologa CG, Yang JJ, et al. How to Illuminate the Druggable Genome Using Pharos. Curr Protoc Bioinformatics. 2020 Mar;69(1):e92.

5. Avram S, Bologa CG, Holmes J, Bocci G, Wilson TB, Nguyen D-T, et al. DrugCentral 2021 supports drug discovery and repositioning. Nucleic Acids Res [Internet]. 2020 Nov 5; Available from: http://dx.doi.org/10.1093/nar/gkaa997

6. Chen B, Ma L, Paik H, Sirota M, Wei W, Chua M-S, et al. Reversal of cancer gene expression correlates with drug efficacy and reveals therapeutic targets. Nat Commun. 2017 Jul 12;8:16022.

7. Ursu O, Holmes J, Bologa CG, Yang JJ, Mathias SL, Stathias V, et al. DrugCentral 2018: an update. Nucleic Acids Res [Internet]. 2018 Oct 29; Available from: http://dx.doi.org/10.1093/nar/gky963

8. Cannon DC, Yang JJ, Mathias SL, Ursu O, Mani S, Waller A, et al. TIN-X: target importance and novelty explorer. Bioinformatics. 2017 Aug 15;33(16):2601–3.

9. Egaña LA, Cuevas RA, Baust TB, Parra LA, Leak RK, Hochendoner S, et al. Physical and functional interaction between the dopamine transporter and the synaptic vesicle protein synaptogyrin-3. J Neurosci. 2009 Apr 8;29(14):4592–604.

10. Stoker TB, Greenland JC, editors. Parkinson's Disease: Pathogenesis and Clinical Aspects. Brisbane (AU): Codon Publications; 2019.

11. Schmitt M, Dehay B, Bezard E, Javier Garcia-Ladona F. Harnessing the trophic and modulatory potential of statins in a dopaminergic cell line [Internet]. Vol. 70, Synapse. 2016. p. 71–86. Available from: http://dx.doi.org/10.1002/syn.21881

12. Schmitt M, Dehay B, Bezard E, Garcia-Ladona FJ. U18666A, an activator of sterol

regulatory element binding protein pathway, modulates presynaptic dopaminergic
phenotype of SH-SY5Y neuroblastoma cells. Synapse [Internet]. 2017 Sep;71(9). Available
from: http://dx.doi.org/10.1002/syn.21980

13. Callahan A, Cruz-Toledo J, Ansell P, Dumontier M. Bio2RDF Release 2: Improved
Coverage, Interoperability and Provenance of Life Science Linked Data [Internet]. The
Semantic Web: Semantics and Big Data. 2013. p. 200–12. Available from:
http://dx.doi.org/10.1007/978-3-642-38288-8_14

14. Chen B, Dong X, Jiao D, Wang H, Zhu Q, Ding Y, et al. Chem2Bio2RDF: a semantic
framework for linking and data mining chemogenomic and systems chemical biology data.
BMC Bioinformatics. 2010 May 17;11:255.

15. Digles D, Caracoti A, Jacoby E. Accessing the Open PHACTS Discovery Platform with
Workflow Tools. Methods Mol Biol. 2018;1787:183–93.

16. Szklarczyk D, Gable AL, Lyon D, Junge A, Wyder S, Huerta-Cepas J, et al. STRING v11:
protein-protein association networks with increased coverage, supporting functional
discovery in genome-wide experimental datasets. Nucleic Acids Res. 2019 Jan
8;47(D1):D607–13.

17. Greene CS, Krishnan A, Wong AK, Ricciotti E, Zelaya RA, Himmelstein DS, et al.
Understanding multicellular function and disease with human tissue-specific networks. Nat
Genet. 2015 Jun;47(6):569–76.

18. Koscielny G, An P, Carvalho-Silva D, Cham JA, Fumis L, Gasparyan R, et al. Open
Targets: a platform for therapeutic target identification and validation. Nucleic Acids Res.
2017 Jan 4;45(D1):D985–94.

19. Morton K, Wang P, Bizon C, Cox S, Balhoff J, Kebede Y, et al. ROBOKOP: an abstraction
layer and user interface for knowledge graphs to support question answering.
Bioinformatics. 2019 Dec 15;35(24):5382–4.

20. Lysenko A, Roznovăţ IA, Saqi M, Mazein A, Rawlings CJ, Auffray C. Representing and
querying disease networks using graph databases. BioData Min. 2016 Jul 25;9:23.

21. Chen B, Ding Y, Wild DJ. Assessing Drug Target Association Using Semantic Linked Data
[Internet]. Vol. 8, PLoS Computational Biology. 2012. p. e1002574. Available from:
http://dx.doi.org/10.1371/journal.pcbi.1002574

22. Mathias SL, Hines-Kay J, Yang JJ, Zahoransky-Kohalmi G, Bologa CG, Ursu O, et al. The
CARLSBAD database: a confederated database of chemical bioactivities. Database . 2013
Jun 21;2013:bat044.

23. Dgraph Labs, Inc. Dgraph [Internet]. Dgraph. [cited 2020 Dec 21]. Available from:
https://dgraph.io/

24. Amazon Web Services, Inc. Amazon Neptune [Internet]. Amazon Neptune. [cited 2020 Dec
21]. Available from: https://aws.amazon.com/neptune/

25. Have CT, Jensen LJ. Are graph databases ready for bioinformatics? Bioinformatics. 2013
Dec 15;29(24):3107–8.

26. Himmelstein DS, Baranzini SE. Heterogeneous Network Edge Prediction: A Data
426   Integration Approach to Prioritize Disease-Associated Genes. PLoS Comput Biol. 2015
427   Jul;11(7):e1004259.

428   27. Yoon B-H, Kim S-K, Kim S-Y. Use of Graph Database for the Integration of Heterogeneous
429   Biological Data. Genomics Inform. 2017 Mar;15(1):19–27.

430   28. JCC Consulting, Inc. , acting on behalf of an unincorporated association of ISO Graph
431   Query Language Proponents, and licensed under the Apache License, Version 2. GQL
432   Standard [Internet]. Graph Query Language GQL. [cited 2020 Dec 21]. Available from:
433   https://www.gqlstandards.org/

434   29. Neo4j, Inc. Neo4j Licensing Overview [Internet]. Neo4j. [cited 2020 Dec 21]. Available from:
435   https://neo4j.com/licensing/

436   30. Subramanian A, Narayan R, Corsello SM, Peck DD, Natoli TE, Lu X, et al. A Next
437   Generation Connectivity Map: L1000 Platform and the First 1,000,000 Profiles. Cell. 2017
438   Nov 30;171(6):1437–52.e17.

439   31. IDG-KMC (Illuminating the Druggable Genome Knowledge Management Center). IDG-KMC
440   Target Central Resource Database [Internet]. Target Central Resource Database. [cited
441   2020 Nov 30]. Available from: http://juniper.health.unm.edu/tcrd/

442   32. Hripcsak G, Duke JD, Shah NH, Reich CG, Huser V, Schuemie MJ, et al. Observational
443   Health Data Sciences and Informatics (OHDSI): Opportunities for Observational
444   Researchers. Stud Health Technol Inform. 2015;216:574–8.

445   33. Napolitano F, Sirci F, Carrella D, di Bernardo D. Drug-set enrichment analysis: a novel tool
446   to investigate drug mode of action. Bioinformatics. 2016 Jan 15;32(2):235–41.

447   34. Neo4j, Inc. Neo4j Python Driver [Internet]. Neo4j. [cited 2020 Dec 21]. Available from:
448   https://neo4j.com/docs/api/python-driver/current/

449   35. Rosenthal R. Combining results of independent studies [Internet]. Vol. 85, Psychological
450   Bulletin. 1978. p. 185–93. Available from: http://dx.doi.org/10.1037/0033-2909.85.1.185