Towards Similarity-based Differential Diagnostics For Common Diseases

Luke T Slater[1,2,8*], Andreas Karwath[1,2,8], John A Williams[1,2,8], Sophie Russell[2,8], Silver Makepeace[2,8], Alexander Carberry[2,8], Robert Hoehndorf[7], Georgios V Gkoutos[1,2,3,4,5,6,8],

1 College of Medical and Dental Sciences, Institute of Cancer and Genomic Sciences, University of Birmingham
2 Institute of Translational Medicine, University Hospitals Birmingham, NHS Foundation Trust
3 NIHR Experimental Cancer Medicine Centre
4 NIHR Surgical Reconstruction and Microbiology Research Centre
5 NIHR Biomedical Research Centre
6 MRC Health Data Research UK (HDR UK) Midlands
7 Computer, Electrical and Mathematical Sciences & Engineering Division, Computational Bioscience Research Center, King Abdullah University of Science and Technology
8 University Hospitals Birmingham NHS Foundation Trust, Edgbaston, Birmingham, UK.

* l.slater.1@bham.ac.uk

Keywords: semantic web, ontology, differential diagnosis, mimic-iii, semantic similarity

Abstract

Ontology-based phenotype profiles have been utilised for the purpose of differential diagnosis of rare genetic diseases, and for decision support in specific disease domains. Particularly, semantic similarity facilitates diagnostic hypothesis generation through comparison with disease phenotype profiles. However, the approach has not been applied for differential diagnosis of common diseases, or generalised clinical diagnostics from uncurated text-derived phenotypes. In this work, we describe the development of an approach for deriving patient phenotype profiles from clinical narrative text, and apply this to text associated with MIMIC-III patient visits. We then explore the use of semantic similarity with those text-derived phenotypes to classify primary patient diagnosis, comparing the use of patient-patient similarity and patient-disease similarity using phenotype-disease profiles previously mined from literature. The results reveal a potentially powerful approach that can be applied to a variety of clinical tasks, such as differential diagnosis, cohort discovery, document and text classification, and outcome prediction.

Introduction

While a great effort has been invested in the digitisation of healthcare information and data, natural language remains the primary mode of communication and record in the domain. As such, electronic health records (EHRs) contain a wealth of natural language text that comprises an important and fruitful resource for secondary uses, leading to important insights and improved outcomes for patients [1,2].

Biomedical ontologies encode knowledge in the healthcare domain, including phenotypes and diseases. For example, the Human Phenotype Ontology (HPO) describes disease phenotypes observed in humans, and is used to encode phenotype profiles for real-world entities in healthcare, including patients and diseases [3]. Phenotype ontologies can then be employed to describe phenotype profiles for biomedical entities by associating sets of ontology classes with those entities. Biomedical ontologies have semantic features, including a taxonomic classification, which can can be envisioned as a directed acyclic graph, in which directed edges encode specification of concepts by transitive subsumption relationships.

These resources have been widely explored for the purposes of differential diagnostics and identification for rare diseases. In particular, measurements of semantic similarity between phenotype profiles have been used to generate hypotheses and predict diagnoses [4]. Semantic similarity is a measure of how similar two classes are, derived from analysis of the taxonomic structure of an ontology [5]. Measures of similarity can also be determined for groups of classes, including phenotype profiles. The intuition is that a patient phenotype profile will be more similar to the phenotype profile describing the disease they actually have, than to those they do not. This expectation can be leveraged to produce diagnostic hypotheses.

The Online Mendelian Inheritance in Man (OMIM) and OrphaNet databases contain phenotype profiles for many rare genetic diseases [6, 7], manually curated from literature. Semantic similarity has been used to successfully classify rare disease patients by comparing their phenotype profiles, produced either by clinical experts or patients themselves, with those in OMIM and Orphanet [8]. These approaches form the basis of a useful differential diagnostic and clinical decision support methodology [4].

Phenotype-based methods have been extended to involve data derived from clinical text narratives [9]. Doc2HPO [10] explored the creation of patient phenotypes using HPO from clinical narratives, using text mining to aid experts in curating phenotype profiles which could then be used directly in various differential diagnosis and gene prioritisation tools. Another work developed an approach for deep phenotyping patients from clinical narratives, producing HPO phenotype profiles, particularly for the purpose of disease gene variant prioritisation [11]. Other work has focused on expanding and enriching the phenotype profiles described by OMIM and OrphaNet using EHRs [12]. Finally, literature mining of relationships between DO and HP has been employed to identify relationships between diseases and phenotypes [13], again for variant prioritisation.

Semantic similarity has also been used to support diagnosis and clinical decisions within particular disease domains, such as in skeletal dysplasia [14] and breast pathology [15]. These approaches rely on the use of extensive and specific application ontologies, rather than general phenotype ontologies.

Aside from similarity-based methods, machine learning with quantitative features, as well as features derived from text directly or in the form of word embeddings, have been employed for rare disease diagnosis over EHRs [9, 16]. Differential diagnosis of diseases by converting clinical pathway definitions to sets of rules mapped to ontologies has also been previously been explored, but did not involve clinical narratives or semantic similarity [17].

While semantic similarity has proven a successful approach for classification of rare diseases through comparison with banks of phenotype profiles, it has not been applied to common diseases or generalised diagnostics in a clinical setting. Part of the reason for this is a lack of definitional phenotype profiles in for those common diseases.

We developed an approach for generalised common disease diagnosis, exploring solutions to the problem of limited availability of disease–phenotype associations. First, we create phenotype profiles for patient visits using concept recognition over text associated with patient visits from MIMIC-III. We then evaluate and contrast two methods of predicting diagnosis: comparison to other patients in the cohort, and secondary use of definitional phenotype profiles previously mined from literature.

Methods

Data Preparation and Information Extraction

MIMIC is a freely available healthcare dataset, describing nearly 60,000 critical care visits across three hospitals with a combination of structured and unstructured data, including textual notes [18]. Within MIMIC, diagnoses are provided in the form a canonical ICD-9 code, produced in the original care setting by clinical coding experts. We sampled 1,000 patient visits from the MIMIC-III dataset, collecting their associated texts together into one file per patient visit. We limited our patient visit sample to those with a primary ICD-9 diagnosis that mapped to a class in the Disease Ontology (DO) [19], since the definitional disease phenotypes we are generating are associated with DO classes. Mappings were obtained from DO, using its in-built annotation properties that define database cross-references.

We then used the Komenti semantic text mining framework [20] to create a vocabulary from all non-obsolete terms in HPO. Subsequently, we used Komenti to annotate the texts associated with each sampled patient visit, producing, in effect, a list of HPO terms associated with each patient visit, or a phenotype profile for each patient visit.

Figure 1. Comparison between the two methods of creating a ranking for each patient, in which each box signifies a phenotype profile comparison, in an example where there are five patients and four disease profiles. On the left side, the patient is compared with each other patient in the set, and the ranking is produced from the semantic similarity score between the patient and every other patient. On the right side, the patient is compared with every disease phenotype profile, and the ranking is produced by ordering the semantic similarity score between the patient and every disease profile.

Semantic Similarity and Evaluation

We then produced, for each patient visit, two sets of similarity scores, demonstrated in Figure 1. The first set of similarity scores is formed of pairwise similarity with each other patient visit phenotype profile in the sample. The second was formed based on pairwise similarity scores with a set of definitional disease phenotypes. For generating the definitional disease phenotypes, we re-used a dataset from a previous experiment which derived phenotypes for DO diseases by text-mining literature abstracts for class co-occurrence [13]. We pre-processed this dataset to remove all non-HP phenotypes from the definitions, and collapsed multiple definitions into single definitions with all unique HP classes.

To calculate semantic similarity scores, we used the Semantic Measures Library [21]. We used the Resnik measure of pairwise similarity [22], with Best Match Average for groupwise similarity [23], with information content calculated from annotation frequency. In the case of the patient-patient similarity calculations, information content was calculated using a corpus of all HPO codes associated with sampled patient visits. For the purpose of patient visit-disease phenotype similarity calculations, information content was calculated using all HPO codes associated with sampled patient visits, and all HPO codes associated with all disease phenotypes.

We then measured the ability of ranked similarity scores to be predictive of primary diagnosis. We evaluated the results using Area Under the receiver operating characteristic Curve (AUC), Mean Reciprocal Rank (MRR), and Top Ten Accuracy (the percentage of patients for whom the correct diagnosis was in the top ten most similar entities). The software for the experiment is freely available at `https://github.com/reality/miesim`.

Results and Discussion

We created phenotype profiles for 1,000 patient visits sampled from MIMIC-III by associating them with HPO terms identified in their associated text narrative. We then explored two different methods of classifying primary patient diagnosis: comparison with other patients, and comparison with literature-derived disease phenotype profiles (described in Figure 1). Table 1 summarises the results for use of semantic similarity to predict primary diagnosis, using patient-patient comparisons and patient-disease profile comparisons, while Figure 2 compares the ROC curves. The AUC metric shows that comparison of patient phenotype profiles with diseases produces a better overall classifier. While the patient-patient comparison dataset overall yielded an inferior overall classifier, the MRR and Top Ten Accuracy metrics show that the correct disease appeared at higher ranks much more frequently than in the disease definition comparison dataset. This slightly unintuitive contrast derives from two factors.

Table 1. Performance for matching first diagnosis of MIMIC patients under different settings. Top ten accuracy is the percentage of patients for whom a correct diagnosis appeared in the ten most similar entities.

Setting	AUC	MRR	Top Ten Accuracy
Patient Comparison	0.7 (0.6952-0.7046)	0.177	0.353
Disease Comparison	0.869 (0.8564-0.8818)	0.016	0.029

The first factor consists in a difference between the number of comparisons the two models make. The patient-patient classifier compares each patient with 999 patient phenotype profiles, the disease profile classifier compares each patient with 6,247 phenotype profiles – this provides much greater negative predictive power. That is, while the ranks of matches are higher in absolute terms for the patient-patient classifier, they are lower in relation to how many comparisons appear below it. This is compounded by the fact that patients are likely to have multiple matching patients (patients with a shared diagnosis), while there will be at most one matching disease profile.

The second influence is that while the patient-patient model seems to be much better at producing highly ranked matches in absolute terms, the AUC is calculated from overall normalised

Figure 2. Comparative ROC curves for the two models, with patient-disease comparisons showing much better overall performance. However, the literature disease classifier did not find all true positives, even with a false positive rate of 1, due to confidence levels of zero for certain patient-disease comparisons.

semantic similarity score (becoming an overall score-derived ranking), rather than per-patient rankings (which MRR and Top Ten Accuracy are derived from). Therefore, the metric indicates that in terms of global score the patient-patient classifier is producing high scores for patient pairs that do not share a primary diagnosis. This is implied also by the difference in mean similarity score: 2.869 for the disease profile classifier, and 4.759 for the patient-patient classifier. Figure 3 also shows a comparison between the ranges of scores for the two classifiers, showing that on average the patient-patient scores are both more closely clustered and greater than the patient-disease scores. This is likely due to the text annotations, and therefore the patient profiles, recording features that are irrelevant to the particular disease, but are likely to be shared across entities in the dataset. For example, given MIMIC-III is a critical care setting, many patients are suffering from or are being evaluated for pain. Across the 1,000 patient visits annotated, there are 2,380 instances of `pain` (`HP:0012531`). While this would partially be controlled by the annotation frequency derived information content measure, patients who share nothing in common other than pain would nevertheless be rated more similar on that basis than those who had no annotations in common. This does not affect the disease phenotype classifier, as disease profiles have been derived from a large number of literature texts, with the final disease phenotype profiles retaining only phenotypes that appeared to be significantly associated to that disease in particular.

The patient–patient classifier was also negatively impacted by patients who did not have another patient with a matching disease. For 107 patients, there was no true positive to be found within the ranking due to no other patient visit sharing the primary diagnosis. This situation could be improved by using a hybrid model which enhances disease phenotypes with information from patient profiles. Alternatively, a greater number of patients could be sampled, reducing the chance of an unmatched patient. To an extent, this limitation is handled within the context of the algorithm,

Figure 3. Box plot showing the different range of semantic similarity scores over the two experiments. This shows that patient-patient comparisons were on average more similar than patient-disease comparisons. Outliers are not shown.

with lower scores being assigned to patients with no matching diagnosis.

Figure 2 also shows that the literature disease setting did not find all true positives. That setting, even at the highest false positive rate, was unable to recover all true positives. This is due to a proportion of patient–disease pairs being assigned with zero confidence. This happened for a matching disease profile 14 times, and in every case the disease was 'rheumatic congestive heart failure' (DOID:14172). All of the phenotypes associated with this disease, except for sudden death HP:0001699, were very general and therefore uninformative (with respect to the SS calculation), such as clinical modifier (HP:0012823) and All (HP:0000001). Interestingly, this did not occur for other heart failure-related diseases, which implies that sufficiently specific and informative classes were associated with those diseases, though they did not make it to this one. This could be a potential artefact or bug in the method used to generate the literature disease phenotypes in the previous work, and could potentially be fixed by post-processing to ensure proper propagation of phenotypes across the class hierarchy.

We can conclude from these results that both models exhibit benefits and disadvantages, leaving open for future investigation the prospect that a superior classifier may be obtained through some synthesis of both approaches. In addition, in previous work on similarity-based differential diagnosis for rare genetic diseases, p-values were associated with similarity scores, providing a clearer way of interpreting results [8]. It is also possible that front-end user-facing software, such as Phenomizer [8], could be re-used for this purpose, extending it with a larger set of phenotypes and disease profiles.

One limitation of this evaluation is that phenotype profiles are built from the entirety of the text

record associated with the patient visit which, in most cases, will include the actual diagnosis. In that sense, it is not actually longitudinally predictive. Furthermore, while an HPO annotation refers to a phenotype, rather than a disease, there is significant cross-over between these domains, and it's possible that the disease itself appears as a "phenotype" in the text, positively biasing the similarity task. For example, 'hypertension' is both the name of a phenotype and a disease, depending on the context. However, this limitation would also apply to rare diseases. Additional assessment could explore tasks in which the text record is split at the point a diagnosis was made. For example, we could identify patients who were investigated for a rare cardiac condition, splitting the text record at the point a final diagnosis was made. We could then test whether the phenotype derived from text associated with the patient prior to the final diagnosis was predictive of the true outcome. To introduce a longitudinal aspect to the classification in MIMIC-III itself, and to test the efficacy of the method in prediction of non-diagnostic outcomes, we could explore its use in prognostication. For example, we could test the hypothesis that upon presentation, patients who later go on to experience more severe outcomes during a critical care visit, may be more phenotypically similar than those who do not.

In terms of improving performance, we could explore different methods of calculating similarity or information content. For example, the current measure of information content is weighted by the frequency the concept appears in the corpus, however these can also be calculated topologically, on the basis of how general or specific the classes are [24]. Our previous work has also demonstrated that expansion of vocabulary [25] and ontology extension [26] can improve performance of a similar tasks. Recent work has also explored alternative methods for employing ontology axioms and taxonomy for classification and ranking problems, such as the conversion of ontology axioms to vectors [27], an approach which has been demonstrated to improve performance when compared semantic similarity approaches [28].

Conclusions

We explored methods for automated similarity-based classification of patient diagnosis using text-derived phenotypes. Overall, comparing phenotype profiles with profiles derived from literature produced a better classifier, though comparing patients with other patients was more likely to produce highly ranked matches. In future, we plan to explore methods for synthesising these two methods, to produce a better model. We believe this is a promising development, and could lead to a potentially powerful semantic similarity derived solutions for differential diagnosis of common diseases or outcomes, as well as text classification and cohort discovery tasks in a clinical context.

Ethical approval

This work makes use of the MIMIC-III dataset, which was approved for construction, de-identification, and sharing by the BIDMC and MIT institutional review boards (IRBs). Further details on MIMIC-III ethics are available from its original publication (DOI:10.1038/sdata.2016.35). Work was undertaken in accordance with the MIMIC-III guidelines.

Availability of data and material

Komenti is an open source text mining framework, and is available under an open source licence from `https://github.com/reality/komenti`. The code used to sample MIMIC, and run similarity experiments is available from `https://github.com/reality/miesim/`. The annotated MIMIC dataset is not made publicly available, because researchers are required to meet ethical conditions to access MIMIC-derived datasets. To access this dataset, please contact the corresponding author directly.

Competing interests

The authors declare that they have no competing interests.

Acknowledgements

GVG and LTS acknowledge support from support from the NIHR Birmingham ECMC, NIHR Birmingham SRMRC, Nanocommons H2020-EU (731032) and the NIHR Birmingham Biomedical Research Centre and the MRC HDR UK (HDRUK/CFC/01), an initiative funded by UK Research and Innovation, Department of Health and Social Care (England) and the devolved administrations, and leading medical research charities. The views expressed in this publication are those of the authors and not necessarily those of the NHS, the National Institute for Health Research, the Medical Research Council or the Department of Health. RH and GVG were supported by funding from King Abdullah University of Science and Technology (KAUST) Office of Sponsored Research (OSR) under Award No. URF/1/3790-01-01. AK was supported by by the Medical Research Council (MR/S003991/1) and the MRC HDR UK (HDRUK/CFC/01).

References

1. Pereira, L., Rijo, R., Silva, C., Martinho, R.: Text Mining Applied to Electronic Medical Records: A Literature Review. International Journal of E-Health and Medical Communications (IJEHMC) **6**, 1–18 (2015). doi:10.4018/IJEHMC.2015070101

2. Dalianis, H.: Clinical Text Mining: Secondary Use of Electronic Patient Records. Springer International Publishing, ??? (2018). doi:10.1007/978-3-319-78503-5

3. Köhler, S., Doelken, S.C., Mungall, C.J., Bauer, S., Firth, H.V., Bailleul-Forestier, I., Black, G.C.M., Brown, D.L., Brudno, M., Campbell, J., FitzPatrick, D.R., Eppig, J.T., Jackson, A.P., Freson, K., Girdea, M., Helbig, I., Hurst, J.A., Jähn, J., Jackson, L.G., Kelly, A.M., Ledbetter, D.H., Mansour, S., Martin, C.L., Moss, C., Mumford, A., Ouwehand, W.H., Park, S.-M., Riggs, E.R., Scott, R.H., Sisodiya, S., Vooren, S.V., Wapner, R.J., Wilkie, A.O.M., Wright, C.F., Vulto-van Silfhout, A.T., de Leeuw, N., de Vries, B.B.A., Washingthon, N.L., Smith, C.L., Westerfield, M., Schofield, P., Ruef, B.J., Gkoutos, G.V., Haendel, M., Smedley, D., Lewis, S.E., Robinson, P.N.: The Human Phenotype Ontology project: Linking molecular biology and disease through phenotype data. Nucleic Acids Research **42**(Database issue), 966–974 (2014). doi:10.1093/nar/gkt1026

4. Köhler, S., Øien, N.C., Buske, O.J., Groza, T., Jacobsen, J.O.B., McNamara, C., Vasilevsky, N., Carmody, L.C., Gourdine, J.P., Gargano, M., McMurry, J.A., Danis, D., Mungall, C.J., Smedley, D., Haendel, M., Robinson, P.N.: Encoding Clinical Data with the Human Phenotype Ontology for Computational Differential Diagnostics. Current Protocols in Human Genetics **103**(1), 92 (2019). doi:10.1002/cphg.92

5. From Ontology to Semantic Similarity: Calculation of Ontology-Based Semantic Similarity. https://www.hindawi.com/journals/tswj/2013/793091/

6. Hamosh, A., Scott, A.F., Amberger, J.S., Bocchini, C.A., McKusick, V.A.: Online Mendelian Inheritance in Man (OMIM), a knowledgebase of human genes and genetic disorders. Nucleic Acids Research **33**(Database Issue), 514–517 (2005). doi:10.1093/nar/gki033

7. Pavan, S., Rommel, K., Marquina, M.E.M., Höhn, S., Lanneau, V., Rath, A.: Clinical Practice Guidelines for Rare Diseases: The Orphanet Database. PLOS ONE **12**(1), 0170365 (2017). doi:10.1371/journal.pone.0170365

8. Köhler, S., Schulz, M.H., Krawitz, P., Bauer, S., Dölken, S., Ott, C.E., Mundlos, C., Horn, D., Mundlos, S., Robinson, P.N.: Clinical Diagnostics in Human Genetics with Semantic Similarity Searches in Ontologies. The American Journal of Human Genetics **85**(4), 457–464 (2009). doi:10.1016/j.ajhg.2009.09.003

9. Garcelon, N., Burgun, A., Salomon, R., Neuraz, A.: Electronic health records for the diagnosis of rare diseases. Kidney International **97**(4), 676–686 (2020). doi:10.1016/j.kint.2019.11.037

10. Liu, C., Peres Kury, F.S., Li, Z., Ta, C., Wang, K., Weng, C.: Doc2Hpo: A web application for efficient and accurate HPO concept curation. Nucleic Acids Research **47**(W1), 566–570 (2019). doi:10.1093/nar/gkz386

11. Son, J.H., Xie, G., Yuan, C., Ena, L., Li, Z., Goldstein, A., Huang, L., Wang, L., Shen, F., Liu, H., Mehl, K., Groopman, E.E., Marasa, M., Kiryluk, K., Gharavi, A.G., Chung, W.K., Hripcsak, G., Friedman, C., Weng, C., Wang, K.: Deep Phenotyping on Electronic Health Records Facilitates Genetic Diagnosis by Clinical Exomes. The American Journal of Human Genetics **103**(1), 58–73 (2018). doi:10.1016/j.ajhg.2018.05.010

12. Shen, F., Zhao, Y., Wang, L., Mojarad, M.R., Wang, Y., Liu, S., Liu, H.: Rare disease knowledge enrichment through a data-driven approach. BMC Medical Informatics and Decision Making **19**(1), 32 (2019). doi:10.1186/s12911-019-0752-9

13. Hoehndorf, R., Schofield, P.N., Gkoutos, G.V.: Analysis of the human diseasome using phenotype similarity between common, genetic and infectious diseases. Scientific Reports **5**(1), 10888 (2015). doi:10.1038/srep10888

14. Paul, R., Groza, T., Zankl, A., Hunter, J.: Semantic Similarity-Driven Decision Support in the Skeletal Dysplasia Domain. In: Cudré-Mauroux, P., Heflin, J., Sirin, E., Tudorache, T., Euzenat, J., Hauswirth, M., Parreira, J.X., Hendler, J., Schreiber, G., Bernstein, A., Blomqvist, E. (eds.) The Semantic Web – ISWC 2012. Lecture Notes in Computer Science, pp. 164–179. Springer, Berlin, Heidelberg (2012). doi:10.1007/978-3-642-35173-0$_1$1

15. Steichen, O., Bozec, C.D.-L., Thieu, M., Zapletal, E., Jaulent, M.-C.: Computation of semantic similarity within an ontology of breast pathology to assist inter-observer consensus. Computers in Biology and Medicine **36**(7), 768–788 (2006). doi:10.1016/j.compbiomed.2005.04.014

16. Cohen, A.M., Chamberlin, S., Deloughery, T., Nguyen, M., Bedrick, S., Meninger, S., Ko, J.J., Amin, J.J., Wei, A.J., Hersh, W.: Detecting rare diseases in electronic health records using machine learning and knowledge engineering: Case study of acute hepatic porphyria. PLOS ONE **15**(7), 0235574 (2020). doi:10.1371/journal.pone.0235574

17. Mohammed, O., Benlamri, R.: Developing a Semantic Web Model for Medical Differential Diagnosis Recommendation. Journal of Medical Systems **38**(10), 79 (2014). doi:10.1007/s10916-014-0079-0

18. Johnson, A.E.W., Pollard, T.J., Shen, L., Lehman, L.-w.H., Feng, M., Ghassemi, M., Moody, B., Szolovits, P., Celi, L.A., Mark, R.G.: MIMIC-III, a freely accessible critical care database. Scientific Data **3**(1), 1–9 (2016). doi:10.1038/sdata.2016.35

19. Schriml, L.M., Arze, C., Nadendla, S., Chang, Y.-W.W., Mazaitis, M., Felix, V., Feng, G., Kibbe, W.A.: Disease Ontology: A backbone for disease semantic integration. Nucleic Acids Research **40**(D1), 940–946 (2012). doi:10.1093/nar/gkr972

20. Slater, L.T., Bradlow, W., Hoehndorf, R., Motti, D.F., Ball, S., Gkoutos, G.V.: Komenti: A semantic text mining framework. bioRxiv, 2020–0804233049 (2020). Chap. New Results. doi:10.1101/2020.08.04.233049

21. Harispe, S., Ranwez, S., Janaqi, S., Montmain, J.: The semantic measures library and toolkit: Fast computation of semantic similarity and relatedness using biomedical ontologies. Bioinformatics **30**(5), 740–742 (2014). doi:10.1093/bioinformatics/btt581

22. Resnik, P.: Using Information Content to Evaluate Semantic Similarity in a Taxonomy. arXiv:cmp-lg/9511007 (1995). cmp-lg/9511007

23. Wang, J.Z., Du, Z., Payattakool, R., Yu, P.S., Chen, C.-F.: A new method to measure the semantic similarity of GO terms. Bioinformatics **23**(10), 1274–1281 (2007). doi:10.1093/bioinformatics/btm087

24. Zhou, Z., Wang, Y., Gu, J.: A new model of information content for semantic similarity in WordNet. In: 2008 Second International Conference on Future Generation Communication and Networking Symposia, vol. 3, pp. 85–89. IEEE, ??? (2008)

25. Slater, L.T., Bradlow, W., Ball, S., Hoehndorf, R., Gkoutos, G.V.: Improved characterisation of clinical text through ontology-based vocabulary expansion. bioRxiv, 2020–0710197541 (2020). Chap. New Results. doi:10.1101/2020.07.10.197541

26. Slater, L.T., Hoehndorf, R., Karwath, A., Gkoutos, G.V.: Exploring Binary Relations for Ontology Extension and Improved Adaptation to Clinical Text. bioRxiv, 2020–1204411751 (2020). Chap. New Results. doi:10.1101/2020.12.04.411751

27. Smaili, F.Z., Gao, X., Hoehndorf, R.: OPA2Vec: Combining formal and informal content of biomedical ontologies to improve similarity-based prediction. arXiv:1804.10922 [cs] (2018). 1804.10922

28. Kulmanov, M., Smaili, F.Z., Gao, X., Hoehndorf, R.: Machine learning with biomedical ontologies. bioRxiv, 2020–0507082164 (2020). Chap. New Results. doi:10.1101/2020.05.07.082164