High-order areas and auditory cortex both represent the high-level event structure of music

Jamal A. Williams[1], Elizabeth H. Margulis[1,2], Samuel A. Nastase[1], Janice Chen[4], Uri Hasson[1], Kenneth A. Norman[1], Christopher Baldassano[3]

[1]Princeton Neuroscience Institute and Department of Psychology, Princeton University, Princeton, NJ 08544, USA

[2]Department of Music, Princeton University, Princeton, NJ 08544, USA

[3]Department of Psychology, Columbia University, New York, NY 10027, USA

[4]Department of Psychological and Brain Sciences, Johns Hopkins University, Baltimore, MD 21218, USA

Abstract

Recent fMRI studies of event segmentation have found that default mode regions represent high-level event structure during movie watching. In these regions, neural patterns are relatively stable during events and shift at event boundaries. Music, like narratives, contains hierarchical event structure (e.g., sections are composed of phrases). Here, we tested the hypothesis that brain activity patterns in default mode regions reflect the high-level event structure of music. We used fMRI to record brain activity from 25 participants (male and female) as they listened to a continuous playlist of 16 musical excerpts, and additionally collected annotations for these excerpts by asking a separate group of participants to mark when meaningful changes occurred in

each one. We then identified temporal boundaries between stable patterns of brain

activity using a hidden Markov model and compared the location of the model

boundaries to the location of the human annotations. We identified multiple brain

regions with significant matches to the observer-identified boundaries, including auditory

cortex, mPFC, parietal cortex, and angular gyrus. From these results, we conclude that

both higher-order and sensory areas contain information relating to the high-level event

structure of music. Moreover, the higher-order areas in this study overlap with areas

found in previous studies of event perception in movies and audio narratives, including

regions in the default mode network.

Significance Statement

Listening to music requires the brain to track dynamics at multiple hierarchical

timescales. In our study, we had fMRI participants listen to real-world music (classical

and jazz pieces) and then used an unsupervised learning algorithm (a hidden Markov

model) to model the high-level event structure of music within participants' brain data.

This approach revealed that default mode brain regions involved in representing the

high-level event structure of narratives are also involved in representing the high-level

event structure of music. These findings provide converging support for the hypothesis

that these regions play a domain-general role in processing stimuli with long-timescale

dependencies.

Introduction

Recent work has demonstrated that the brain processes information using a hierarchy of temporal receptive windows, such that sensory regions represent relatively short events (e.g., milliseconds to seconds) and higher-order regions represent longer events (e.g., minutes) while inheriting some of the lower-level structure from sensory regions (Hasson et al., 2015; Chen et al., 2016; Baldassano et al., 2017). For example, Baldassano and colleagues (2017) used a hidden Markov model (HMM) to find transitions between stable patterns of neural activity in BOLD data acquired from participants that watched an episode of the TV series Sherlock. The HMM temporally divides data into "events" with stable patterns of activity, punctuated by "event boundaries" where activity patterns rapidly shift to a new stable pattern. They found that, in sensory regions such as early visual cortex, the data were best-fit by a model with short-lasting chunks, presumably corresponding to low-level perceptual changes in the episode; by contrast, when they applied the model to data from a higher-order area such as posterior medial cortex, the best-fitting model segmented the data into longer-lasting chunks corresponding to more semantically meaningful scene changes. Critically, human annotations of important scene changes most closely resembled the model-identified boundary structure found in frontal and posterior medial cortex, which are key hubs in the brain's default mode network (DMN) (Shulman et al., 1997; Raichle et al., 2001). Studies have also found that the same event-specific neural patterns are activated in default-mode regions by audiovisual movies and by verbal narratives describing these events (Zadbood et al., 2017; Baldassano et al., 2017, 2018),

providing further evidence that these regions represent the underlying meanings of the

events and not low-level sensory features.

Jackendoff and Lerdahl (2006) suggest that music and language are structured into

meaningful events that help people comprehend moments of tension and relaxation

between distant events. If music resembles language in this way, then the

representation of hierarchical event structure in music (e.g., at the level of phrases,

sections, and entire songs) and in verbal and audiovisual narratives may be supported

by similar neural substrates. Indeed, some evidence already exists for shared neural

resources for processing music and language (Tallal and Gaab, 2006; Patel, 2011;

Koelsch, 2011; Peretz et al., 2015; Lee et al., 2019). In the current work, we test the

hypothesis that posterior medial cortex (PMC) and other default mode network (DMN)

regions that represent high-level event structure in narratives also play a role in

representing high-level event structure in music.

In our paradigm, we presented fMRI participants with examples of complex real-world

music belonging to genres familiar to our participant population: jazz and classical. A

separate group of behavioral participants were asked to annotate meaningful events

within each of the excerpts. We applied hidden Markov models using both a whole-brain

searchlight and cortical parcellation to measure event structure represented in cortical

response patterns throughout the brain. We then used the events provided by the

annotators to guide the event segmentation of the brain data. The goal of this analysis

was to identify brain regions that chunk the stimuli in a way that matched the human

annotations. By fitting the model at each ROI and then comparing the observed

boundary structure to that of the annotators, we show that – in a group of passive

listeners – regions in the default mode network and also sensory areas are involved in

representing the high-level event structure in music (i.e., these regions show neural

pattern shifts that line up with human annotations of event boundaries). We also show

that these event representations become more coarse as they propagate up the cortical

processing hierarchy.

99
Materials and Methods
100

101
Participants
102

103 We collected fMRI data from a total of 25 participants (12 female, ages 21–33). We also

104 recruited 7 human annotators for a separate behavioral task (described below). 13 of

105 the fMRI participants were native English speakers. The experimental protocol was

106 approved by the Institutional Review Board of Princeton University, and all participants

107 gave their written informed consent.

109
Stimuli

16 musical excerpts were selected based on the criteria that changes between sub-

sections would likely be recognized by people without formal music training (e.g.,

change from piano solo to drum solo). Excerpts also had to be instrumental (i.e. lack

vocals). Excerpts were drawn from two different genres (8 classical and 8 jazz).

Excerpts were then randomly selected to be truncated (with the introduction kept intact)

to one of four different durations: 90 s, 135 s, 180 s, and 225 s, such that there were

four excerpts of each length. Furthermore, two excerpts of each duration were sampled

from each genre. For example, only two classical excerpts had a duration of 90 seconds

and only two jazz excerpts had a duration of 90 seconds. The total duration of the

playlist was approximately 45 minutes and there were no breaks between excerpts.

Figure 1. Top: Example 45 minute scanning run with classical excerpts depicted in pink and jazz excerpts

in blue. Each block in the timeline represents an excerpt and block lengths reflect excerpt durations.

Bottom: Overview of experiment. Participants heard the playlist four times (once on each of the two days

prior to scanning and twice on the third day while being scanned). The excerpts were presented in a

different order each of the four times that a given participant heard the playlist, but – within a given phase

of the experiment (e.g., Run 1 on Day 3) – the order of excerpts was kept the same across participants.

Experimental design and statistical analysis

The experiment took place over three consecutive days (Figure 1): On the first two

days participants heard a playlist of sixteen musical excerpts (once for each day) and

on the third day they heard the same playlist for two separate runs while we recorded

changes in their BOLD activity using fMRI. Altogether, each participant heard the

playlist four times. Each time that a given participant heard the playlist, the excerpts

were presented in a different order. However, within a given phase of the experiment

(e.g., the first scanner run on day 3), the order of excerpts was kept the same across

participants; this way, all participants listened to the same stimuli in the same order in

the scanner, which was necessary for the Shared Response Model analyses described

below. To promote stable representations of the music, participants listened to the

playlist on each of the two days prior to scanning. During these listening sessions, we

collected ratings from participants about their enjoyment, engagement, and familiarity

with each piece (only familiarity ratings are discussed in this manuscript); these ratings

were collected immediately after hearing each piece. Answers for each rating category

were given on a 5-point Likert scale where a 5 corresponded to very familiar. We found

an increase in average familiarity from day 1 to day 2 (t(22)= 9.04, p < 0.0001)

indicating that participants remembered the music played in the first pre-scan session.

Two participants were excluded from this analysis because their day 2 ratings were lost.

After each of these listening sessions, participants took a short recognition test where

they heard 32 randomly drawn 3-second clips of a piece that were either from the actual

listening session or a lure (i.e. different piece by the same artist) and made a response

using a 5-point Likert scale indicating whether they recognized the excerpt as having

been presented previously. In addition to the familiarity ratings across the two pre-scan

days, this measure helped us determine if participants had learned the music after each

behavioral listening session. Participants showed above-chance discrimination (i.e.,

higher recognition scores for presented excerpts vs. lures) on both days (Day 1: t(24) =

12.2, p < 0.0001; Day 2: t(24) = 15.1, p < 0.0001; Figure 2).

Figure 2. Recognition test scores for both prescan days. Plot shows that presented excerpts were given

higher recognition scores than lures. The y-axis represents a 5-point Likert scale where one means not

studied and five means studied. Error bars represent standard error of the mean.

On the third day, participants returned for the scanning session in which they listened to

the playlist twice (with excerpts played in a different order for the two scanning runs; as

noted above, the order of excerpts within a run was the same across participants).

During each run, participants were asked to perform a white noise detection task.

Specifically, during each excerpt, a brief (1 sec) white noise pulse was played at a

randomly chosen time point within the middle 60% of each excerpt. The onset of each

noise pulse was also randomized across participants. Participants were told to make a

button response to indicate that they heard the noise. This manipulation served to keep

participants attentive throughout each excerpt. Following both scanning runs,

participants took a final recognition test and then completed a brief demographic survey.

Event annotations by human observers

In a separate behavioral experiment, we asked seven different raters (only one rater

reported having extensive musical training) to listen to our stimuli one at a time with the

task of pressing a button when a "meaningful" transition occurred within each piece

(similar to the method used by Sridharan et al., 2007). The number of event boundaries

identified by the observers varied across excerpts ranging from 3 to 17 boundaries (with

a mean of 7.06 and standard deviation of 0.91 across excerpts). It is worth noting that

excerpt durations also varied, with a range of 90 sec to 225 sec (durations were either

90, 135, 190, or 225 sec) and an average duration of 157.5 sec and standard deviation

of 50.3 sec across excerpts. A timepoint was considered to be an event boundary when

at least five annotators marked a boundary within three seconds before or after the

given timepoint (method used from Baldassano et al., 2017). The mean number of

consensus boundaries across excerpts acquired using this method roughly matched the

mean number of boundaries assigned by individual participants across all of the

excerpts (with a mean of 7.98 and standard deviation of 2.98 across excerpts).

Scanning parameters and preprocessing

Imaging data were acquired on a 3T full-body scanner (Siemens Prisma) with a 64-

channel head coil. Data were collected using a multi-band accelerated T2-weighted

echo-planar imaging (EPI) sequence (release R015) provided by a C2P agreement with

University of Minnesota (Moeller et al., 2010; Setsompop et al., 2012; Xu et al., 2013;

Auerbach et al., 2013; Sotiropoulos et al., 2013; Cauley et al., 2014): 72 interleaved

transverse slices; in-plane resolution = 2.0 mm; slice thickness = 2.0 mm with no inter-

slice gap; field of view (FOV) = 208 mm; base resolution = 104; repetition time (TR) =

1000 ms; echo time (TE) = 37 ms; flip angle (FA) = 60 deg; phase-encoding (PE)

direction = anterior to posterior; multi-band acceleration factor = 8. Three spin-echo

volume pairs were acquired matching the BOLD EPI slice prescription and resolution in

opposing PE directions (anterior to posterior and posterior to anterior) for susceptibility

distortion correction: TR/TE = 8000/66.60 ms; FA/refocus FA = 90/180 deg; TA = 32s

(Andersson et al., 2003).

Additionally, a whole-brain T1-weighted volume was collected: 3D magnetization-

prepared rapid gradient echo (MPRAGE) sequence; 176 sagittal slices; 1.0 mm^3

resolution; FOV = 256 mm; base resolution = 256; TR/TE = 2300/2.88 ms; inversion

time (TI) = 900 ms; FA = 9 deg.; PE dir = anterior to posterior; IPAT mode = GRAPPA

2X; TA= 5 min 20 sec.

The EPI volumes were realigned using a 6 parameter rigid-body registration (MCFLIRT;

Jenkinson et al., 2002). Given the short effective TR, slice time correction was not

performed. Susceptibility-induced distortions were modeled in the opposing spin-echo

volume pairs using the FSL 'topup' tool, and the resulting off-resonance field output was

provided as input to distortion correct the time series of fMRI data using the FSL

'applywarp' tool (Andersson et al., 2003). The susceptibility distortion correction and

realignment were applied in a single interpolation step to minimize blurring. Remaining

pre-processing and co-registration steps were performed using FEAT (Woolrich et al.,

2001, 2004). This included linear detrending, high-pass filtering (330 s cutoff), and

spatial normalization to the MNI152 template released with FSL.

221 Whole-brain parcellation and searchlights

We conducted our primary analysis across the whole brain by defining ROIs in two

parallel ways. In the parcellation approach, we used 300 non-overlapping parcels tiling

the whole cortex in MNI space (Schaefer et al., 2018). In the whole-brain searchlight

approach, we divided the MNI volume into overlapping spherical searchlights with a

radius of 10 voxels and a stride of 5 voxels. This resulted in 2,483 searchlights that

spanned the whole cortex in MNI space. Only searchlights containing at least 30 voxels

were included in the analysis (matching the number of shared features specified in the

shared response model described in the following section) and the mean number of

voxels per searchlight was 381.76 voxels with a standard deviation of 168.09 voxels.

We assigned the output value for a given searchlight to all voxels within a 5-voxel radius

to account for the stride and then averaged the values for voxels where overlap

occurred. All analyses below were run separately within each ROI (parcel or

searchlight).

Shared response model

Within each ROI, we first reduced the dimensionality of our BOLD data to a set of

shared features (30 features) using the shared response model (SRM; Chen et al.,

2015), which aligns functional response patterns across participants and provides a low-

dimensional representation of the shared variance in the BOLD data (Figure 3B). Since

the only information shared across participants is the musical stimulus, shared variance

is necessarily *music-related* variance. The SRM procedure thus has the effect of

highlighting (shared) music-related variance (see Figure 3 for diagram of analysis

pipeline). The "optimal" number of shared features will tend to vary across both stimuli

and brain areas (e.g., as determined by cross-validation); here, for the sake of

simplicity, we fixed the number of shared features at 30 as a reasonable middle ground

based on values used in prior work (Chen et al., 2015; Chen et al., 2017; Nastase et al.,

2020). We applied an SRM with parameters estimated from run 1 to transform the run 2

data, and applied an SRM with parameters estimated from run 2 to transform the run 1

data. Next, for each participant's transformed data, song-specific onset and offset times

were used to extract time points corresponding to a particular excerpt; for each of the 32

excerpts (16 songs in each of the two runs), we then averaged (across participants) all

of the participant-specific timeseries for that excerpt, resulting in 32 average timeseries.

These average timeseries were then analyzed using the hidden Markov model as

described in the next section.

Event segmentation analysis

After fitting the SRM to a given ROI, we fit a hidden Markov model (HMM; Baldassano et al., 2017) to the response time series in shared space for each excerpt, setting the number of states in the HMM equal to the number of segments specified by our human annotators for each excerpt. We used a specialized HMM variant developed by Baldassano et al. (2017) that is optimized for event segmentation (i.e., identifying jumps in neural patterns). This HMM variant seeks to model the shared feature timecourse as a set of successive transitions between stable states (i.e., patterns of fMRI activity in shared space), where – in our variant of the HMM – the model is not permitted to return to a state once it leaves that state. Once fit to the data, the model tells us what the stable best-fitting patterns are and when the transitions occurred between these patterns; this HMM variant was implemented using the EventSegment function in BrainIAK (Kumar et al., 2020a, 2020b).

For our primary analysis, we were interested in finding brain regions (parcels or searchlights) whose transition structure most closely resembled the event boundary structure given by our annotators (Figure 3C). After acquiring boundary estimates from the HMM, we evaluated how closely in time the boundaries found by the model matched the boundaries supplied by our annotators. To quantify the degree of match, we counted the number of human-annotated boundaries for which there was a HMM boundary within three TRs of that human-annotated boundary. Note that all human boundaries were shifted forward 5 TRs (5 seconds) to account for the hemodynamic lag. We created a null model by randomly selecting timepoints as boundaries (keeping

the number of events the same, as in Baldassano et al., 2017) and computed the

number of matches for these null boundaries, repeating this process 1000 times to

produce a null distribution. We computed a z-value of the real result versus the null

distribution by subtracting the average of the permuted match scores from the true

match score and dividing this difference by the standard deviation of the permuted

scores. This procedure was repeated at every ROI. By acquiring z-values at each ROI

for all 32 excerpts (16 distinct excerpts x 2 runs), we obtained 32 separate spatial maps

of z-values. Next, we averaged the two z-maps corresponding to each distinct excerpt

(one from each run), resulting in 16 total z-maps. To summarize across the z-values for

the 16 distinct excerpts, we ran a one sample t-test against zero to see which voxels

had the most reliable matches across all excerpts. The resulting t-values were

converted to p-values and then adjusted for multiple tests to control the false discovery

rate (FDR) at a value q (Benjamini & Hochberg, 1995).

To visualize the results, each spatial map of t-values (one corresponding the voxel-wise

searchlight procedure and the other corresponding to the parcellation procedure) was

displayed on the cortical surface (masked to include only vertices that exhibited a

significant effect). Since each analysis was performed in volumetric space, volume data

were projected to the cortical surface using the automatic volume to surface rendering

algorithm within Surf Ice (https://www.nitrc.org/projects/surfice/).

Figure 3. Diagram of analysis pipeline. (From left to right) **Panel A.** For each participant (N=25), voxels

from an ROI were selected using pre-defined parcellations or the searchlight method; we then extracted

song-specific timecourses (Voxels x TRs) from the selected voxels (black circle). Inflated brain image was

created using PySurfer (https://github.com/nipy/PySurfer/). **Panel B.** Selected data were reduced to a set

of shared features using the shared response model (SRM), which highlights shared variance (*music-*

related variance) across participants. The SRM was applied to the full time series concatenated across all

16 excerpts in a single run, then the full time series was split back into separate excerpts. **Panel C.** HMM

boundaries (white dotted lines) and human annotations (black lines) were considered to match (black

downward arrows) when HMM boundaries fell within 3 TRs of a human annotation. Then, true match

scores were compared to a null distribution constructed by comparing shuffled HMM boundaries to

human annotations, resulting in a z-value for each ROI.

Controlling for low-level music features

To further determine whether brain areas of the DMN represent high-level musical event

structure, as opposed to low-level sensory information, we repeated the searchlight

analysis, this time regressing out musical features extracted from each auditory stimulus

prior to fitting the HMM. These features consisted of mel-frequency cepstral coefficients

(MFCCs; i.e. timbre information), chromagrams (harmonic information), and

tempograms (rhythmic information). For MFCCs, the top 12 channels were extracted

since these lower order coefficients contain most of the information about the overall

spectral shape of the source-filter transfer function (Poorjam, 2018). Chromagrams

consisted of 12 features, each corresponding to a distinct key in the chromatic scale.

Tempograms initially consisted of 383 features, each representing the prevalence of

certain tempi (in beats per minute; BPM) at each moment in time. Since most of the

tempo-related variance was explained by a much smaller set of features, we reduced

the 383 features to 12 features using PCA in order to match the number of features

used for MFCCs and chromagrams. Feature extraction on music stimuli was performed

using Librosa (McFee et al., 2015), a Python package developed for audio and music

analysis.

Identifying preferred event timescales

After identifying brain regions with neural event boundaries that match human

annotations (using the procedures described in *Event segmentation analysis*, above),

we ran a follow-up analysis to further probe the properties of three such regions (right

auditory cortex, left angular gyrus, and left precuneus). Specifically, the goal of this

follow-up analysis was to assess the preferred timescale of these regions. In contrast to

our primary event segmentation analysis (which used a fixed number of events for each

excerpt, matching the number of human-annotated events for that excerpt), here we

tried models with different numbers of events and assessed how well model fit varied as

a function of the number of events. The measure of model fit we used was the average

pattern similarity between pairs of timepoint-specific multivoxel patterns falling *within* the

same event, minus the average pattern similarity between patterns falling *across* events

(Baldassano et al., 2017). We call this measure the *WvA score* (short for "Within versus

Across"); higher WvA scores indicate a better fit of the event boundaries to the data.

The ROIs for this analysis (right auditory cortex, left angular gyrus, and left precuneus)

were defined by selecting voxels within the parcellation corresponding to right auditory

cortex, left angular gyrus, and left precuneus, and then (for extra precision) intersecting

these parcels with voxels that were also significant in our primary searchlight analysis

looking for neural boundaries that matched human-annotated boundaries ($q < 0.01$). For

each ROI, we fit HMMs to each song with differing numbers of events ranging from 3 to

45. For each HMM fit, we measured the maximum event duration, and then identified all

pairs of timepoints whose temporal distance was less than this duration. The constraint

of using timepoints whose distance was less than the maximum event duration was

used so that the number of within- and across-event pairs would be roughly equal

(regardless of the number of events). The WvA score was computed as the average

spatial pattern correlation for pairs of timepoints falling in the same (HMM-derived)

event minus the average correlation for pairs of timepoints falling in different events. We

then averaged the results across excerpts. Note that, since the excerpts are different

lengths, a given number of events might correspond to different average event lengths

for different excerpts (e.g., a 3-event model applied to a 180 second excerpt has an

average event length of 60 seconds, but a 3-event model applied to a 90 second

excerpt would have an average event length of 30 seconds). Because our goal was to

find each area's preferred event length, we converted our WvA results for each excerpt

to be a function of the average event length (in seconds) rather than the number of

events, and averaged these results across excerpts. Finally, we computed a preferred

event length for each ROI, operationalized as the weighted average of all possible event

lengths (2 seconds to 75 seconds), with the averaged WvA scores as the weights; put

another way, preferred event length was computed as the center-of-mass of the plot of

WvA as a function of event length.

To test whether the preferred event length in auditory cortex was shorter than that of

angular gyrus and precuneus, we performed a bootstrap analysis, repeating the above

analysis (including re-running SRM) 1000 times for different bootstrap resamples of the

original dataset. At each iteration of the bootstrap, we applied the analysis to a sample

of participants drawn randomly with replacement from the original data. We computed

p-values by finding the proportion of bootstraps where the preferred length for auditory

cortex was greater than the preferred length for angular gyrus or precuneus.

385
Results

Neural boundary match to behavioral annotations

We wanted to test the hypothesis that behaviorally-defined event boundaries could be

identified in higher-order cortical regions, especially those overlapping with the DMN.

For this analysis, we compared the HMM boundaries to the specific timepoints labeled

as boundaries by the annotators. According to both parcellation and searchlight results,

we found that the highest number of matches between model boundaries and human

annotations were in auditory cortex, left angular gyrus, left precuneus, bilateral medial

prefrontal cortex, and motor cortex (Figure 4).

Figure 4. Panel A. Parcellation Results. For each of 300 parcels, we tested whether the average match between HMM-defined neural boundaries and human annotations across all songs was significantly greater than zero. Significant parcels included auditory cortex as well as several regions in the default mode network (DMN): angular gyrus (AG), posterior medial cortex (PMC), and medial prefrontal cortex (mPFC). Parcels in left motor, premotor, and supplementary motor cortex were also significant. Results are thresholded via FDR, q < 0.05. **Panel B. Searchlight Results.** For 2,483 searchlights across the whole cortex, we again tested whether the average match between neural and annotated boundaries across all songs was significantly greater than zero. Significant voxels overlapped with those from the parcellation results, and additionally showed effects in right inferior frontal gyrus and hippocampal regions. Results are thresholded via FDR, q < 0.01.

Influence of low-level music features

To determine whether the neural event boundaries were driven by low-level acoustic features, we also performed a version of the searchlight analysis in which we controlled for timbral, harmonic, and rhythmic features. Overall, this reduced the number of searchlights passing the significance threshold (Figure 5) compared to the original searchlight analysis. However, some higher-order areas overlapping with the DMN (precuneus and mPFC) did pass the significance threshold (q < 0.01), which suggests

416   that event boundaries found in these regions do not directly correspond to low-level

417   music features and may instead be related to more abstract representations of the

418   event structure. Notably, some significant searchlights in auditory cortex were also

419   observed, indicating that – even in sensory areas – the event boundaries were being

420   driven (at least in part) by high-level music features.

Searchlight Regression Results

Figure 5. Searchlight results accounting for low-level music features. We recomputed the match

between HMM-derived neural boundaries and human annotations after regressing out low-level acoustic

features from each participant's BOLD data prior to fitting the HMM. Significant effects were still observed

in higher-order areas overlapping with the DMN as well as several auditory areas, suggesting that

boundaries detected in these areas do not necessarily depend on low-level musical features. Results are

thresholded via FDR ($q < 0.01$).

Preferred event lengths across ROIs

How do we reconcile the role of auditory cortex in high-level event representation (as shown in the above analyses) with its well-known role in representing low-level auditory features? Importantly, these claims are not mutually exclusive. Our analyses, which set the number of event states in the model to equal the number of human-annotated boundaries, show that auditory cortex has some (statistically-reliable) sensitivity to high-level events, but this does not mean that this is the *only* event information coded in auditory cortex or that it is the *preferred* level of event representation. Figure 6 shows timepoint-by-timepoint similarity matrices for three ROIs, in which spatial pattern correlations were computed for each pair of timepoints in an excerpt (Kamasi Washington's *Change of the Guard*). Blocks of high correlation around the diagonal indicate periods of time in which patterns stayed relatively constant. This block structure in default-mode regions (angular gyrus and precuneus) is at a similar scale as the human annotations (black squares), while the smaller blocks in auditory cortex suggest that it represents finer event structure than is present in human annotations.

Figure 6. Timepoint-by-timepoint spatial pattern similarity matrices for Kamasi Washington's *Change of the Guard* in right auditory cortex (left), left angular gyrus (middle), and left precuneus (right). Black squares overlaid on the similarity matrices represent events defined behaviorally by our human annotators.

We defined the preferred timescale of each region by running HMMs with different numbers of event states, and finding the average event length (in seconds) that produced the best model fits across songs (Figure 7). Using a bootstrap analysis, we found that auditory cortex's preferred event length (average center of mass across bootstraps was 16.67 seconds) was significantly shorter than the preferred event lengths of both angular gyrus (p=0.012; average center of mass was 17.57 seconds) and precuneus (p=0.036; average center of mass was 17.34 seconds).

463 **Figure 7.** To test the hypothesis that higher-order areas (precuneus and AG) exhibit event-structured

464 activity for longer periods than auditory cortex, we computed a measure of model fit (within-event vs.

465 across-event pattern correlations; WvA score) for HMMs with the number of events ranging from 3 to 45.

466 We found that auditory cortex's preferred length (purple vertical line) was shorter on average than the

467 preferred lengths of angular gyrus and precuneus (pink and green vertical lines, respectively).

Discussion

In this study, we sought to demonstrate that brain areas that have been implicated in

representing high-level event structure for narrative-based stimuli are also involved in

representing the high-level event structure of music in a group of passive listeners. We

provide evidence that regions in the default mode network (DMN) are involved in

representing the event structure of music as characterized by human annotators. The

durations of these human-annotated events lasted on the order of a few seconds up to

over a minute.

Our results indicate that high-level structure is represented in both high-level DMN

regions but also in auditory cortex. Auditory cortex, however, may not explicitly

represent high-level events at the level of human annotators; that is, the behaviorally-

identified event boundaries are likely a subset of the finer-grained event boundaries

encoded in auditory cortex. When we force the HMM to match the number of human-

annotated boundaries, the HMM finds them, demonstrating that coding in auditory

cortex is modulated by high-level event structure. However, when we remove this

constraint and allow the number of events to vary, auditory cortex prefers shorter events

on average relative to higher-order brain areas (Figure 7). Additionally, we showed

that—when we regress out low-level music features relating to timbre, harmony, and

rhythm and re-run the analysis—higher-order areas (several overlapping with DMN), as

well as auditory cortex, still significantly match with the annotations. These results

provide additional evidence that event boundaries in DMN, as well as auditory areas,

are not purely driven by low-level acoustic changes in the music, but are also tracking

more abstract event structure in musical pieces. It is possible that boundaries marking

the shift between large-scale segments within DMN and auditory regions could be

driven by a complex shift in a combination of the acoustic properties or possibly

emotional changes within the excerpts (Daly et al., 2015). Notably, our findings of high-

level coding in auditory cortex converge with other recent work demonstrating that

hierarchical neural representations of music are distributed across primary and non-

primary auditory cortex (Landemard et al., 2020) and that higher-order representations

of music in these areas support human performance on a genre recognition task (Kell et

al., 2018).

Our findings that left precuneus, bilateral mPFC, and angular gyrus were involved in

representing event structure at the level of phrases and sections contrast with those in

Farbood et al. (2015), who found that these regions responded reliably to stories but did

not respond reliably to music. Furthermore, in their study, there was minimal overlap

between voxels in posterior medial cortex that responded to stories and voxels that

responded to music. In our study, we show that, at a regional level, these "verbal

narrative" areas are indeed involved in representing the high-level event structure in

music. One major way in which our studies differed was our use of an HMM to detect

evidence of musical event structure in higher-order areas. The HMM is optimized to

detect periods of relative stability punctuated by shifts in response patterns, which one

would expect for an area encoding high-level event structure (i.e., there should be

stability within events and changes across events). Temporal ISC (inter-subject

correlation analysis; the analysis method used in the study by Farbood) is designed to

pick up on *any* kind of reliable temporal structure and is not specifically designed to

detect the "stability punctuated by shifts" structure that we associate with event

cognition, making it less sensitive to this kind of structure when it is present. This

highlights one of the advantages of using HMMs for detecting meaningful brain activity

related to the temporal dynamics of naturalistic stimuli, such as music.

In our study, we showed the involvement of frontal brain areas (specifically vmPFC and

rIFG) in representing high-level musical event structure. The recruitment of vmPFC

during music processing has been found in a previous study (Blood and Zatorre, 2001).

Specifically, Blood and Zatorre showed that activity in vmPFC was correlated with

pleasure response ratings to music. This effect was also found in supplementary motor

areas (SMA) as well as anterior cingulate cortex (ACC). Interestingly, these same areas

appear to represent the high-level event structure for music in our study, suggesting that

regions that represent long-timescale structure also play a role in affective responses to

music. This makes sense given that pleasure in response to music is likely derived from

the accumulation of information, leading to the buildup of expectations that are

eventually resolved over time (Margulis, 2005; Lehne et al., 2013; Gingras et al., 2016).

We also showed that rIFG was significantly involved in representing the high-level event

structure of real-world music, particularly in the searchlight analysis. Several studies

have reported the role of rIFG in the processing of musical syntax (Koelsch et al., 2002;

Tillman et al., 2003; Minati et al., 2008) but it was unclear from these studies whether

hierarchical processing was occurring in this region. In a recent fMRI study, however,

Cheung et al. (2018) found that rIFG increased in activity when violations to non-local

dependencies in nested musical sequences occurred, suggesting that rIFG is involved

in the hierarchical processing of event structure in music, consistent with the findings

reported here.

Both searchlight and parcellation analyses revealed the involvement of motor areas in

high-level event representation. Specifically, we see the recruitment of bilateral primary

motor cortex (M1), bilateral premotor cortex (PMC), bilateral supplementary motor areas

(SMA), and primary somatosensory cortex. These findings are not surprising given the

large number of studies that find motor areas to be active during passive music listening

(Gordon et al., 2018). Research suggests that the motor system is involved in a wide

range of music-related processes such as sequencing, timing, and spatial organization

(Zatorre et al., 2007). Furthermore, predictive coding accounts of passive musical

listening such as the ASAP (Action Simulation for Auditory Prediction) hypothesis (Patel

and Iversen, 2014) suggest that the motor cortex sends signals to auditory cortex that

help the auditory system make predictions about upcoming beats. In our study,

consensus boundaries were often found in locations that were on a beat within a

developed beat pattern. In other words, meaningful changes tended to occur on an

expected beat. Importantly, the fMRI participants in our study never performed a manual

event segmentation task (the annotations were made by a separate group of

participants) and were not explicitly told to notice these changes, but motor areas

nonetheless appear to be involved in representing them.

Conclusion

In this study, we sought to determine whether certain regions in the default mode

network, which have been shown to be involved in representing the high-level event

structure in narratives, were also involved in representing the high-level event structure

in real-world music. Recent fMRI work, not using music, has shown that hidden Markov

models (HMMs) can help us understand how the brain represents large-scale event

structure (e.g., Baldassano et al., 2017; Baldassano et al., 2018; Antony et al., 2020).

By using HMMs to segment fMRI response patterns over time according to the event

structure provided by a separate group of human annotators, we found that areas of the

DMN were indeed involved in representing the high-level event structure (e.g., phrases,

sections) in music in a group of passive listeners. We also showed that our event

segmentation model was capable of detecting high-level event structure in auditory

cortex when the model was constrained by the number of human annotations. However,

when we allowed the number of events to vary, we found that the auditory cortex data

was best fit by a model with shorter events, compared to data from precuneus and

angular gyrus. Results in a subset of regions, including higher-order regions and some

auditory regions, remained significant even after controlling for low-level musical

features, suggesting that sensitivity to high-level event structure in higher-order brain

areas may reflect contributions from memory or the perception of more abstract musical

structure.

References

Alexander, S., Ru, K., Gordon, E.M., Laumann, T.O., Zuo, X., Holmes, A.J., Eickhoff, S.B.,

& Yeo, B.T.T. (2018) Local-global parcellation of the human cerebral cortex from intrinsic

functional connectivity MRI. *Cerebral Cortex*, *28*(9), 3095–3114,

https://doi.org/10.1093/cercor/bhx179

Andersson, J.L., Skare, S., & Ashburner, J. (2003) How to correct susceptibility

distortions in spin-echo echo-planar images: application to diffusion tensor imaging.

NeuroImage. 20(2), 870-88.

Antony, J.W., Hartshorne, T.H., Pomeroy, K., Hasson, H., McDougle, S.D., & Norman,

K.A. (2020) Behavioral, physiological, and neural signatures of surprise during

naturalistic sports viewing. *Neuron. 109*(2), 377-390.

https://doi.org/10.1016/j.neuron.2020.10.029

Auerbach, E.J., Xu, J., Yacoub, E., Moeller, S., & Uğurbil, K. (2013) Multiband

accelerated spin-echo echo planar imaging with reduced peak RF power using time-

shifted RF pulses. *Magnetic Resonance in Medicine. 69*, 1261-1267.

Baldassano, C., Chen, J., Zadbood, A., Pillow, J.W., Hasson, U., & Norman, K.A. (2017)

Discovering event structure in continuous narrative perception and memory. *Neuron*,

95(3), 709-721.

Baldassano, C., Hasson, U., & Norman, K.A. (2018) Representation of real-world event

schemas during narrative perception. *Journal of Neuroscience, 38*(45), 9689-9699. doi:

10.1523/JNEUROSCI.0251-18.2018

Blood, A.J. & Zatorre, R.J. (2001) Intensely pleasurable responses to music correlate

with activity in brain regions implicated in reward and emotion. *PNAS*, *98*(20), 11818-

11823. doi: 10.1073/pnas.191355898

Cauley, S.F., Polimeni, J.R., Bhat, H., Wald, L.L., & Setsompop, K. (2014) Interslice

leakage artifact reduction technique for simultaneous multislice acquisitions. *Magnetic*

Resonance in Medicine, *72*(1), 93-102.

Cheung, V.K.M., Meyer, L., Friederici, A.D., & Koelsch, S. (2018) The right inferior

frontal gyrus processes nested non-local dependencies in music. *Scientific Reports*, *8*,

3822. https://doi.org/10.1038/s41598-018-22144-9

Chen, J., Leong, Y.C., Honey, C.J., Yong, C.H., Norman, K.A., & Hasson, U. (2017)

Shared memories reveal shared structure in neural activity across individuals. *Nature*

Neuroscience, *20*, 115-125.

Chen, P., Chen, J., Yeshurun, Y., Hasson, U., Haxby, J.V., & Ramadge, P.J. (2015) A

reduced-dimension fMRI shared response model. *Advances in Neural Information*

Processing Systems (NIPS).

Daly, I., Williams, D., Hallowell, J., Hwang, F., Kirke, A., Malik, A., Weaver, J., Miranda,

E., & Nasuto, S.J. (2015) Music-induced emotions can be predicted from a combination

of brain activity and acoustic features. *Brain and Cognition*, *101*, 1-11.

https://doi.org/10.1016/j.bandc.2015.08.003

Farbood, M. M., Heeger, D. J., Marcus, G., Hasson, U., & Lerner, Y. (2015) The neural

processing of hierarchical structure in music and speech at different timescales.

Frontiers in Neuroscience, *9*, 157. doi: 10.3389/fnins.2015.00157

Gingras, B., Pearce, M.T., Goodchild, M., Dean, R.T., Wiggins, G., & McAdams, S.

(2016) Linking melodic expectation to expressive performance timing and perceived

musical tension. *Journal of Experimental Psychology: Human Perception and*

Performance, *42*(4), 594-609.

Gordon, C.L. (2018) Recruitment of the motor system during music listening: An ALE

meta-analysis of fMRI data. *PLoS One, 13*(11).

https://doi.org/10.1371/journal.pone.0207213

Hasson, U., Chen, J., & Honey, C.J. (2015). Hierarchical process memory: memory as

an integral component of information processing. *Trends in Cognitive Science*, *19*, 304-

313.

Jackendoff, R. & Lerdahl, F. (2006) The capacity for music: what is it and what's special

about it? *Cognition*, *100*, 33–72.

Jenkinson, M., Bannister, P.R., Brady, J.M., & Smith, S.M. (2002) Improved optimisation

for the robust and accurate linear registration and motion correction of brain images.

NeuroImage, *17*(2), 825-841.

Kell, A.J.E., Yamins, D.L.K., Shook, E.N., Norman-Haignere, S.V., McDermott, J.H.

(2018) A task-optimized neural network replicates human auditory behavior, predicts

brain responses, and reveals a cortical processing hierarchy. *Neuron*, *98*(3), 630-644.

https://doi.org/10.1016/j.neuron.2018.03.044.

Koelsch, S., Gunter, T.C., Cramon, D., Zysset, S., Lohmann, G., Friederici, A.D. (2002).

Bach speaks: A cortical 'language-network' serves the processing of music.

NeuroImage, *17*, 956–966.

Koelsch, S. (2011) Toward a neural basis of music perception - a review and updated

model. *Frontiers in Psychology*, *2*, 110.

Kumar, M., Ellis, C.T., Lu, Q., Zhang, H., Capota, M., Willke, T.L., Ramadge, P.J., Turk-

Browne, N.B., Norman, K.A. (2020a) BrainIAK tutorials: User-friendly learning materials

for advanced fMRI analysis. *PLOS Computational Biology*, *16*(1).

https://doi.org/10.1371/journal.pcbi.1007549

Kumar, M., Anderson, M.J., Antony, J.W., Baldassano, C., Brooks, P.P., Cai, M.B.,

Chen, P.H.C., Ellis, C.T., Henselman-Petrusek, G., Huberdeau, D., Hutchinson, J.B., Li,

P.Y., Lu, Q., Manning, J.R., Mennen, A.C., Nastase, S.A., Hugo, R., Schapiro, A.C.,

Schuck, N.W., Shvartsman, M., Sundaram, N., Suo, D., Turek, J.S., Vo, V.A., Wallace,

G., Wang, Y., Zhang, H., Zhu, X., Capota, M., Cohen, J.D., Hasson, U., Li, K.,

Ramadge, P.J., Turk-Browne, N.B., Willke, T.L. & Norman, K.A. (2020b). BrainIAK: The

Brain Imaging Analysis Kit. *OSF Preprints*.

Landemard, A., Bimbard, C., Demene, C., Shamma, S., Norman-Haignere, S.,

Boubenec, Y. (2020). Distinct higher-order representations of natural sounds in human

and ferret auditory cortex. *bioRxiv.*

Lee, D.J., Jung, H., & Loui, P. (2019). Attention modulates electrophysiological

responses to simultaneous music and language syntax processing. *Brain Sciences*,

9(11), 305. https://doi.org/10.3390/brainsci9110305

Lehne, M., Rohrmeier, M., & Koelsch, S. (2013). Tension-related activity in the

orbitofrontal cortex and amygdala: an fMRI study with music. *Social Cognitive and*

Affective Neuroscience, *9*(10), 1515-1523. doi: 10.1093/scan/nst141

Lerner, Y., Honey, C. J., Silbert, L. J., and Hasson, U. (2011). Topographic mapping of

a hierarchy of temporal receptive windows using a narrated story. *Journal of*

Neuroscience, 31, 2906–2915. doi: 10.1523/JNEUROSCI.3684-10.2011

Margulis, E.M. (2005). A model of melodic expectation. *Music Perception*, *22*(4), 663-

714.

McFee, B., Colin R., Dawen, L., Daniel, E.P.W., Matt, M., Eric, B., and Oriol, N. (2015)

"librosa: Audio and music signal analysis in python." *Proceedings of the 14th Python in*

Science Conference, 18-25.

Minati, L., Rosazza, C., D'Incerti, L., Pietrocini, E., Valentini, L., Scaioli, V., Loveday, C.,

& Bruzzone, M.G. (2008). fMRI/ERP of musical syntax: comparison of melodies and

unstructured note sequences. *Neuroreport*, *19*, 1381–1385.

Moeller, S., Yacoub, E., Olman, C.A., Auerbach, E., Strupp, J., Harel, N., & Uğurbil, K.

(2010) Multiband multislice GE-EPI at 7 tesla, with 16-fold acceleration using partial

parallel imaging with application to high spatial and temporal whole-brain fMRI.

Magnetic Resonance in Medicine, *63*(5), 1144-1153.

Nastase, S.A., Liu, Y., Hillman, H., Norman, K.A., & Hasson, U. (2020). Leveraging

shared connectivity to aggregate heterogeneous datasets into a common response

space. *NeuroImage*, *217*. https://doi.org/10.1016/j.neuroimage.2020.116865.

Patel, A.D. (2011) Why would musical training benefit the neural encoding of speech?

The OPERA hypothesis. *Frontiers in Psychology*, *2*, 142. doi:10.3389/fpsyg.2011.00142

Patel, A.D. & Iversen, J.R. (2014) The evolutionary neuroscience of musical beat

perception: the Action Simulation for Auditory Prediction (ASAP) hypothesis. *Frontiers in*

Systems Neuroscience, *8*, 57.

Peretz, I., Vuvan, D., Lagrois, M., & Armony, J. L. Neural overlap in processing music

and speech. *Philosophical Transactions of the Royal Society B*, *370*.

http://doi.org/10.1098/rstb.2014.0090.

Raichle, M.E., MacLeod, A.M., Snyder, A.Z., Powers, W.J., Gusnard, D.A., & Shulman,

G.L. (2001) A default mode of brain function. *PNAS*, *98*(2), 676-682.

Poorjam, A. H. (2018). Re: Why we take only 12-13 MFCC coefficients in feature

extraction?. Retrieved from: https://www.researchgate.net/post/Why_we_take_only_12-

13_MFCC_coefficients_in_feature_extraction/5b0fd2b7cbdfd4b7b60e9431/citation/dow

nload.

Setsompop, K., Gagoski, B.A., Polimeni, J.R., Witzel, T., Wedeen, V.J., & Wald, L.L.

(2012) Blipped-controlled aliasing in parallel imaging for simultaneous multislice echo

planar imaging with reduced *g*-factor penalty. *Magnetic Resonance in Medicine*. *67*(5),

1210-1224.

Shulman, G. L., Fiez, J. A., Corbetta, M., Buckner, R. L., Miezin, F. M., Raichle, M. E. &

Petersen, S. E. (1997) Common blood flow changes across visual tasks: II. Decreases

in cerebral cortex. *Journal of Cognitive Neuroscience*, 9, 648–663.

Sotiropoulos, S.N., Moeller, S., Jbabdi, S., Xu, J., Andersson, J.L., Auerbach, E.J.,

Yacoub, E., Feinberg, D., Setsompop, K., Wald, L.L., Behrens, T.E.J, Uğurbil, K., &

Lenglet, C. (2013) Effects of image reconstruction on fiber orientation mapping from

multichannel diffusion MRI: Reducing the noise floor using SENSE. *Magnetic*

Resonance in Medicine, *70*(6),1682-1689.

Sridharan, D., Levitin, D.J., Chafe, C.H., Berger, J., & Menon, V. (2007) Neural

dynamics of event segmentation in music: converging evidence for dissociable ventral

and dorsal networks. *Neuron*, *55*(3), 521-532.

Tallal, P. & Gaab, N. (2006) Dynamic auditory processing, musical experience and

language development. *Trends in Neuroscience*, *29*(7), 382-390.

Tillmann, B., Koelsch, S., Escoffier, N., Bigand, E., Lalitte, P., Friederici, A.D., &

Cramon, D.Y. (2006) Cognitive priming in sung and instrumental music: Activation of

inferior frontal cortex. *NeuroImage*, 31, 1771–1782.

Woolrich, M. W., Ripley, B. D., Brady, M., & Smith, S. M. (2001). Temporal

autocorrelation in univariate linear modeling of fMRI data. *NeuroImage*, *14*(6), 1370–

1386. http://doi.org/10.1006/nimg.2001.0931

Woolrich, M. W., Behrens, T. E. J., Beckmann, C. F., Jenkinson, M., & Smith, S. M.

(2004). Multilevel linear modelling for fMRI group analysis using Bayesian inference.

NeuroImage, *21*(4), 1732–1747. http://doi.org/10.1016/j.neuroimage.2003.12.023

Xu, J., Moeller, S., Auerbach, E.J., Strupp, J., Smith, S.M., Feinberg, D.A., Yacoub, E.,

& Uğurbil, K. (2013) Evaluation of slice accelerations using multiband echo planar

imaging at 3 T. *NeuroImage*, *83*(0), 991-1001.

Zadbood, A., Chen, J., Leong, Y.C., Norman, K.A., & Hasson, U. (2017) How we

transmit memories to other brains: constructing shared neural representations via

communication. *Cerebral Cortex*, *27*(10), 4988-5000. 10.1093/cercor/bhx202

Zacks, J. M., & Swallow, K. M. (2007). Event segmentation. *Current Directions in*

Psychological Science, *16*(2), 80–84. http://doi.org/10.1111/j.1467-8721.2007.00480.x

Zatorre, R.J., Belin, P., & Penhune, V.B. (2002) Structure and function of auditory

cortex: music and speech. *Trends in Cognitive Sciences*, *6*(1), 37-46.

Zatorre, R., Chen, J. & Penhune, V. (2007) When the brain plays music: auditory–motor

interactions in music perception and production. *Nature Reviews Neuroscience*, *8*, 547–

558. https://doi.org/10.1038/nrn2152.

<u>Acknowledgments</u>

We thank Mark A. Pinsk for contributing to the *Scanning parameters and preprocessing*

section of the manuscript, Benson Deverett for helping with the stimulus presentation

script in python, Elizabeth McDevitt for suggestions on the figures, Sara Chuang for

helping with stimulus selection, and the members of the Hasson, Pillow, and Norman

labs for their comments and support. This work was supported by NIMH R01

MH112357-01 to UH and KAN and NINDS D-SPAN award F99 NS118740-01 to JW.