Speed-related but not detrended gait variability increases with more sensitive self-paced treadmill controllers at multiple slopes

Cesar R. Castano[1]*, Helen J. Huang[1,2]

[1]Department of Mechanical and Aerospace Engineering, University of Central Florida, Orlando, FL, United States

[2]Disability, Aging, and Technology Cluster, University of Central Florida, Orlando, FL, United States

* Corresponding author

Email: Castanocesar@knights.ucf.edu (CRC)

Abstract

Self-paced treadmills are being used more frequently to study humans walking

with their self-selected gaits on a range of slopes. There are multiple options to purchase

a treadmill with a built-in controller, or implement a custom written self-paced controller,

which raises questions about how self-paced controller affect treadmill speed and gait

biomechanics on multiple slopes. This study investigated how different self-paced

treadmill controller sensitivities affected gait parameters and variability on decline, level,

and incline slopes. We hypothesized that increasing self-paced controller sensitivity

would increase gait variability on each slope. We also hypothesized that detrended

variability could help mitigate differences in variability that arise from differences in speed

fluctuations created by the self-paced controllers. Ten young adults walked on a self-

paced treadmill using three controller sensitivities (low, medium, and high) and fixed

speeds at three slopes (decline, -10°; level, 0°; incline, +10°). Within each slope, average

walking speeds and spatiotemporal gait parameters were similar regardless of self-paced

controller sensitivity. With higher controller sensitivities on each slope, speed fluctuations,

speed variance, and step length variance increased whereas step frequency variance

and step width variance were unaffected. Detrended variance was not affected by

controller sensitivity suggesting that detrending variability helps mitigate differences

associated with treadmill speed fluctuations. Speed-trend step length variances,

however, increased with more sensitive controllers. Further, detrended step length

variances were similar for self-paced and fixed speed walking, whereas self-paced

walking included substantial speed-trend step length variance not present in fixed speed

walking. In addition, regardless of the self-paced controller, subjects walked fastest on

the level slope with the longest steps, narrowest steps, and least variance. Overall, our

findings suggest that separating gait variability into speed-trend and detrended variability

could be beneficial for interpreting gait variability among multiple self-paced treadmill

studies and when comparing self-paced walking with fixed speed walking.

Introduction

Self-paced treadmills (also known as user-driven, active, or adaptive speed treadmills) are typically motorized treadmills that modulate belt speeds to match the subject's walking speed and are becoming more prevalent in gait laboratories. Self-paced control algorithms can use ground reaction forces, marker locations, and gait parameters, among other real-time measures, to determine when and how much to speed up or slow down the treadmill belts. Often, the intent for using self-paced treadmills is to match overground walking speeds and allow for less constrained gait [1–3]. As such, subjects can walk at their self-selected walking speed for several minutes and hundreds of strides while preserving natural gait fluctuations on self-paced treadmills [4–6]. Self-paced treadmills can also be set at incline and decline slopes to study self-selected uphill and downhill gaits [7], overcoming limitations of overground sloped walking studies that are often constrained to short (10-20 meter) ramps or available outdoor terrains [8–11].

Several studies have investigated differences between self-paced and fixed speed walking on a level treadmill. Unlike self-paced walking where the treadmill adjusts to the subject's gait, the subject adjusts their gait to match the constant treadmill speed during fixed speed walking. Studies showed that stride variabilities, muscle activities, and walking speed during self-paced treadmill walking were more similar to overground walking than fixed speed treadmill walking [2,6,12]. Peak anterior ground reaction forces also increased on a user-driven treadmill compared to a fixed speed treadmill [2]. On an active (self-paced) treadmill, the sensorimotor cortex was more engaged compared to passively walking on the (fixed speed) treadmill [13]. Additionally, self-paced treadmills

have helped demonstrate that exoskeletons, visual feedback, and mechanical

perturbations can shift a subject's preferred walking speed [14–16].

As more groups incorporate self-paced walking into their studies, more customized

self-paced controllers are being offered as a built-in mode (ex. Motek Medical's M-Gait,

used in this study) or developed and implemented on treadmills already in a laboratory or

on new treadmills that lack a self-paced mode option [1,2,17–21]. A previous study

evaluated step kinematics and step variability for three control algorithms when walking

on a self-paced treadmill at a level slope resulted in a range of speed fluctuations that

resulted in similar step kinematics but a wide range of significantly different step length

standard deviations (0.037-0.062 m) [6]. These differences in step length variability may

make comparing and interpreting findings across multiple self-paced walking studies

difficult. Identifying spatiotemporal gait metrics that can account for differences in speed

fluctuations and treadmill responsiveness of self-paced treadmill controllers may improve

our understanding of self-paced walking.

Gait parameters, particularly those with a strong relationship with speed such as

step length [22], are likely to be sensitive to differences in self-selected gaits and speed

fluctuations. Gait parameters have both long-range correlations over hundreds of steps

[23] and short-range dependencies on preceding strides [24], which may modulate

walking speed over short distances [25]. By removing the speed relationship from step

length during overground walking, step length variability can be separated into speed-

related (speed-trend) and speed-independent (detrended) components. These

components may represent long-term and short-term active balance control [26]. A few

other overground gait studies also removed speed-related trends to analyze detrended

gait variability to avoid speed-related effects [27,28]. If self-paced treadmill walking is

similar to overground walking, then detrended gait variability may be beneficial for

analyzing self-paced treadmill gait. Recently, two studies reported conflicting results

regarding the reliability of spatiotemporal variability during self-paced walking using two

different self-paced treadmill systems. One study showed that spatiotemporal gait

variability on a self-paced treadmill is reliable for within-session and between sessions

[29], whereas another study found significant differences in spatiotemporal variability

between sessions [30]. One potential factor that could affect reliability is differences in

speed dynamics due to the self-paced treadmill systems.

The primary purpose of this study was to investigate how self-paced treadmill

controller sensitivity affects spatiotemporal gait parameters on different slopes (decline,

level, and incline) and to determine whether detrended gait variability may mitigate

differences in treadmill speed fluctuations of self-paced controllers. We hypothesized that

increasing self-paced controller sensitivity would increase speed fluctuations and gait

variability within each slope. We also hypothesized that detrended gait variability could

help mitigate the expected differences in speed fluctuations and would be similar across

sensitivities within a slope. Because studies often use a single sensitivity (or set of

controller parameters) for all conditions, a secondary purpose was to investigate the effect

of slopes on spatiotemporal gait parameters with each self-paced controller sensitivity.

We hypothesized that regardless of sensitivity, self-paced walking speed would be fastest

and gait variability would be smallest on the level slope compared to decline and incline

slopes for each sensitivity.

Materials and Methods

Ten healthy young adults (22.6±3.5 years; 4 females) with no musculoskeletal or neurological conditions participated in this study and provided informed written consent. The University of Central Florida Institutional Review Board approved the protocol and consent form.

Subjects walked on a self-paced instrumented treadmill (M-Gait System and D-Flow software version 3.28, Motek Medical B.V., Amsterdam, Netherlands) as motion capture data using the 16-marker OptiTrack "Conventional Lower Body" marker set was recorded (22 cameras, Prime 13 and 13W, OptiTrack NaturalPoint Inc., Corvallis, Oregon). The self-paced controller was designed by the manufacturer and allows users to adjust 4 parameters in the D-flow graphical user interface. These parameters set 1) whether to set the baseline position to be the center of the treadmill or the person's initial position when the controller is engaged, 2) whether to use the "new algorithm," 3) whether to stop the self-pace controller when the person stops taking steps, and 4) the gain or sensitivity of the controller. We used the center of the treadmill as the baseline position, which also coincides with the origin of lab's coordinate system, the new algorithm, the option to stop the self-paced controller when the person stops, and different sensitivities (0.5, low; 1.0, medium; 1.5, high). The new algorithm was released in D-flow (v. 3.10) to compensate better for large accelerations or decelerations and is less sensitive to the natural pelvic movements during walking. To visualize the differences between the new algorithm used in this study and the old algorithm reported in Sloot et al. and used in several studies [4,7], we provide plots of the belt speed, center of mass position, and

center of mass velocity in the appendix. Conceptually, the algorithm uses the relative

position of the subject's approximate center-of-mass (average of 4 pelvis markers'

positions) with respect to the center of the treadmill to make a "correction" that adjusts

the treadmill belt speeds (Fig. 1). The sensitivity parameter controls how rapidly the

controller corrects the treadmill belt speeds to adjust the subject's position on the

treadmill. The equation for the correction used in the old algorithm was reported in Sloot

et al., but the specific equation of the "new algorithm" is not disclosed.

Figure 1: Schematic illustrating the self-paced controller concept. When the

subject moves in front of the center point of the treadmill, the treadmill belts speed up

(green correction arrow). When the subject moves behind the center point, the treadmill

belts slow down (red correction arrow). When the subject remains near the center point,

the treadmill belts do not change speed.

Experimental Protocol

Subjects first walked on the treadmill with a range of fixed speeds and self-paced

controller sensitivities during a brief familiarization period. They also completed a 10-

meter walk test to identify their level overground walking speed. Subjects then completed

nine 5-minute self-paced treadmill walking conditions, which were the combinations of

controller sensitivities (low, medium, high) and slopes (decline, -10°; level, 0°; incline,

+10°) in a randomized order with brief 1-2 minute rest periods between conditions.

Subjects then completed 3 subject-specific fixed speed conditions, one for each slope.

The subject-specific fixed speeds were calculated as the average walking speed (using

from the last 2.5 minutes of a condition) of the 3 controller sensitivities on a slope for each

subject. While all subjects performed the fixed speed conditions, a file naming error

resulted in just five subjects having complete fixed speed data sets.

Spatiotemporal Gait Parameters

Using custom MATLAB (Mathworks, Inc., Natick, Massachusetts) scripts, we first

resampled the treadmill belt speed data from 333 Hz to 240Hz to match the motion

capture system. We applied a low-pass filter (zero-lag fourth-order Butterworth filter at 6

Hz) to these data. We identified heel strikes as the most anterior position of the calcaneus

markers and toe-offs as the most posterior position of the second metatarsal head

markers for each foot [31].

We excluded the first 45 seconds for all analyses and used the last 215 seconds,

which we considered to be at "steady-state" speeds [4]. Walking speed was the sum of

the treadmill belt speed and speed (0.5 Hz low-pass filtered derivative) of the approximate

center-of-mass. To characterize speed fluctuations, we computed the power spectral

density of the walking speeds between 0.01-0.2 Hz frequencies. Step length was

calculated as the anterior-posterior distance between heel markers divided by the cosine

of the treadmill angle to account for the different slopes. Step width was the mediolateral

distance between heel markers for each step (heel strike to contralateral heel strike), and

step frequency was the number of steps per second.

Variability and Detrended Analysis

We computed the variances for speed, step frequency, step length, and step width. We also separated the step length and step width variances into speed-dependent (speed-trend) and speed-independent (detrended) components [26]. For each self-paced condition, we fitted the speed data with Eq. 2, to calculate the speed-trend step length based on Grieve & Gear, 1966.

$$step\ length = \alpha \cdot v^{\beta} \qquad \text{Eq. 2}$$

where v is walking speed and α and β are constants, and fitted the speed data with Eq. 3, to calculate the speed-trend step width based on Collins and Kuo, 2013.

$$step\ width = (\gamma \cdot v) + \delta \qquad \text{Eq. 3}$$

where v is walking speed and γ and δ are constants. No speed-related trend has been reported or is expected for step width, whereas step length has a well-established relationship with speed and is expected. For each fixed speed condition, we combined data from the three self-paced sensitivities for a slope before performing the fits to identify a single set of parameters (α, β and γ, δ). We calculated the speed-trended step lengths and speed-trended step widths using the fits (Eq. 2, Eq. 3) and subtracted them from the actual step lengths and step widths, respectively, to obtain the detrended component [26]. Then, the variance of the speed-trended and detrended components were calculated. The sum of the variance of both components should approximate to the total variance of the actual step length and step width because the speed-trended and detrended values are uncorrelated.

Statistics

To test our main hypothesis and determine if controller sensitivity was a main effect within a given slope, we applied general linear models with repeated-measures independently for each spatiotemporal gait parameter. The assumptions of a repeated measures ANOVA (normality, homoscedasticity, and sphericity) were validated using a Shapiro-Wilk Test, Bartlett's test, and Mauchly's test. Outliers based on the default methods (Hi leverage, Cook's distance, and DFITS) used in Minitab (version 19.2020.1, Minitab, LLC, State College, Pennsylvania) were excluded. Because gait experiments typically use a single sensitivity, we applied the same statistical approach with each sensitivity to determine if slope (decline, level, and incline) was a main effect for a given sensitivity. Whenever sensitivity or slope was a main effect, we used post-hoc pair-wise Tukey's Honest Significant Difference (HSD) tests adjusted for multiple comparisons (Dunn-Bonferroni correction) to identify which sensitivities were significantly different within a given slope and which slopes were significantly different for a given sensitivity. We set the significance level to 0.05 and only report Tukey HSD p-values when either sensitivity or slope was a main effect for their respective statistical models. Additionally, we used a Wilcoxon signed-rank test to compare the fixed-speed modality and the low, medium, and high sensitivity controllers. We used SPSS (version 25, IBM Corporation, Armonk, NY, USA) for Mauchly's sphericity test and Wilcoxon signed-rank test, and Minitab for all other statistical analyses.

Results

Speed Fluctuations

In all slopes, self-paced walking sensitivities had evident speed fluctuations over time, unlike fixed speed walking (Fig. 2A). Speed fluctuations were distributed across more frequencies and had greater power at higher frequencies as self-paced controller sensitivities increased within each slope (Fig. 2B). The spectral powers for the fixed speed walking (not plotted in Fig. 2B) were 2 orders of magnitude less than self-paced walking.

Figure 2: Walking speed fluctuations for a representative subject and group-average power spectral densities of walking speed. **A)** Walking speed time courses for self-paced walking with the low (green), medium (red), and high (purple) sensitivity controllers and for fixed-speed walking (black) at each slope for a representative subject. Fixed speed walking had nearly no evident fluctuations compared to self-paced walking. **B)** The group (n = 10) averaged power spectral density of walking speed was distributed across more frequencies for self-paced walking with higher sensitivities.

Average Spatiotemporal Gait Parameters

For the level slope, the walking speeds (mean±standard deviation) were 1.24±0.28

m/s, 1.23±0.26 m/s, and 1.22±0.28 m/s for low, medium, and high sensitivities,

respectively, which were similar to the 10-meter walk speeds, 1.27±0.11 m/s. Within each

slope, increasing self-paced controller sensitivity did not affect average speed, step

frequency, step length, or step width (Fig. 3).

Figure 3: Group averaged walking speed, step frequency, step length, and step

width (top row) and corresponding variances (bottom row) for each controller sensitivity

for each slope. For all gait parameters, n=10 except for speed variance and step length

variance where n=9, due to statistical outliers. Single sided error bars are shown and

indicate standard deviations. Square brackets with black asterisks indicate significant

differences between sensitivities within a slope (Tukey HSD, p<0.05). The brackets in

these plots show that controller sensitivity only resulted in significant increases for speed

variance and step length variance. Curly braces indicate significant differences between

slopes within a single sensitivity indicated by the color-coded asterisks (Tukey HSD,

$p < 0.05$). The curly braces in these plots show that **A)** walking speed was fastest and

speed variance was lowest on the level slope; **B)** step frequency was slowest on the

incline while step frequency variance was highest on the decline; **C)** step lengths were

longest and had the least variance on the level slope; and **D)** step width was smallest on

the level slope while step width variances were not significantly different among slopes.

Each sensitivity showed that subjects walked the fastest with the longest step

lengths and narrowest step widths on the level slope compared to the decline and incline

slopes (Fig. 3, colored asterisks, p's<0.05). Additionally, the slowest step frequencies

were on the incline compared to level and decline slopes (p's<0.05). With the low or

medium sensitivity, subjects walked faster on the decline compared to the incline

(p's<0.05).

Variability of Spatiotemporal Gait Parameters

Within each slope, increasing self-paced controller sensitivity did not affect step

frequency variance and step width variance (Fig. 3). Only speed variance and step length

variance showed significant increases with higher sensitivities within each slope (Fig. 3,

black asterisks, p's<0.05).

Each sensitivity showed that step length variance was smallest on the level slope

compared to the incline and decline slopes (Fig. 3, colored asterisks, p's<0.05), and there

were no significant differences in step width variance among slopes (Fig. 3). Each

sensitivity also showed that speed variance on the decline was larger than level

(p's<0.05). Speed variance on the incline was larger than level with just the low sensitivity.

With the low or high sensitivity, step frequency variance on the decline slope was larger

than level and incline slopes (p's<0.05).

Detrended Analysis

In a representative subject, greater fluctuations in speed and step lengths were

evident as self-paced controller sensitivity increased (Fig. 4A), and as expected, there

were strong relationships between step length and speed during self-paced walking for

all sensitivities (Fig. 4B). For fixed speed walking, there was not a relationship between

step length and speed, as speed was nearly constant and step lengths were concentrated

in narrow range (Fig. 4A & 4B). Thus, the speed-trend step length variance for fixed speed

walking was negligible (Fig. 4C). For this subject, the speed-trend step length variance

was smallest for the low sensitivity controller while the medium and high sensitivities had

larger but similar speed-trend step length variances (Fig. 4C). Detrended step lengths,

which equaled the speed-trend step length minus the actual step length, had similar

variances across the self-paced and fixed speed conditions (Fig. 4D).

A) Actual step lengths and speeds for all steps in a trial

B) Step length vs. speed fits

C) Speed-trend step length derived from the fit equations vs. actual step lengths

D) Detrended step lengths

Figure 4: Progression of detrending speed from step length to obtain detrended

and speed-trend variabilities for walking with low (green), medium (red), and high (purple)

self-paced controller sensitivities and at a fixed speed (black), for a representative

subject. **A)** Actual step lengths and speeds for all steps in a trial. Time courses of actual

step lengths (gray lines) and walking speed (dark blue lines) paralleled each other. **B)**

Step length vs. speed fits. Fit lines of the expected step length and speed relationship

(Eq. 2) during self-paced walking (blue line) plotted with the actual step lengths (gray

circles). The equation and line shown for the fixed speed data is from the average of the

equation constants of the low, medium, and high sensitivity fit equations. **C)** Speed-trend

step length derived from the fit equations vs. actual step lengths. The speed-trend step

lengths (open circles) calculated from the fit equations and the actual step lengths (gray

circles)   are   plotted   for   all   steps.   The   variance, σ^2,

of the speed-trend step lengths was nearly zero for fixed speed walking (5.2×10^{-9} m^2)

and ranged between 0.00018 m^2 - 0.00034 m^2 for the self-paced controllers. **D)**

Detrended step lengths. The detrended step lengths (shaded circles) are equal to the

speed-trend step lengths (open circles) minus the actual step lengths (gray circles). The

variance, σ^2, of the detrended step lengths ranged between 0.00022 m^2 0.00036 m^2 for

self-paced and fixed speed walking conditions.

299   Detrended and Speed-trend Step Length Variances

Speed-trend step length variances accounted for 34%, 47%, and 52% of the total

variances for low, medium, and high sensitivities, respectively, on the decline, and similar

percentages were observed on level (35%, 57%, 50%) and incline (41%, 46%, 58%) (Fig.

5A). Within each slope, detrended step length variances were not significantly different

among sensitivities, while speed-trend step length variances were largest with the high

sensitivity compared to the low sensitivity (Fig. 5B, black asterisks, p's<0.05). Speed-

trend step length variances were also larger with the medium sensitivity than the low

sensitivity on the level slope (p<0.05).

Figure 5: Step length variances on decline, level, and incline slopes for low, medium, and high controller sensitivities (n=9, due to statistical outliers). Error bars are standard deviations. Solid colored bars are the total variance. Stacked bars show the summation of the detrended (faded colored bar) and speed-trend (open bar) components. Percentage values above the stacked bars report the percentage of the speed-trend component. **A)** As controller sensitivity increased, the speed-trend component in total step length variance also increased within each slope. **B)** Controller sensitivity did not affect detrended step length variances within a given slope, but as controller sensitivity increased, speed-trend step length variance also increased within a given slope, as indicated with square brackets and black asterisks (Tukey HSD, p<0.05). When comparing across slopes within a given sensitivity, detrended and speed-trend step length variances were smallest on level compared to incline and decline, as indicated by the curly braces with color-coded asterisks of the specific sensitivities (green = low; red = medium; purple = high) (Tukey HSD, p<0.05).

Each sensitivity revealed that detrended step length variance was lowest on the level slope compared to decline and incline (Fig. 5B, colored asterisks, p's<0.05) and that detrended step length variance was not significantly different between decline and incline (Fig. 5B). Each sensitivity also showed that speed-trend step length variance was larger

on the incline than level (p's<0.05). Speed-trend step length variance was larger on the

decline compared to level only with the high sensitivity (p<0.05).

For the five subjects with fixed speed data, on average, fixed speed walking had

smaller step length variances compared to self-paced walking (Fig. 6). Detrended step

length variances for fixed speed walking were within the range of the self-paced

sensitivities, while speed-trend step length variances for fixed speed walking were

negligible $< 1 \times 10^{-7}$ m^2 (Fig. 6). On all slopes, there were significantly greater speed-trend

step length variances with the self-paced conditions compared to the fixed speed

condition (p's<0.05). However, for the detrended step length variances, there were no

significant differences among the self-paced and fixed speed conditions. The total step

length variances were only significantly greater with the high sensitivity controller

compared to the fixed speed (p's<0.05). However, the low sensitivity (p's<0.10) and

medium sensitivity (p's<0.10) controllers were trending towards significantly greater total

step length variance for all slopes compared to the fixed-speed condition.

Figure 6: Total (solid circles), detrended (faded circles), and speed-trend (open circles) step length variances for fixed speed walking (black x's) and self-paced walking with low (green), medium (red), and high (purple) sensitivity self-paced controllers for 5 subjects (multi-colored shaded rectangles). The box-whisker plots of the group data (n = 5) with significant differences represented by brackets (Wilcoxon signed rank test p's<0.05). Total step length variances were significantly lower for fixed speed walking compared to the high sensitivity controller for all slopes (top row) as a result of the near zero speed-trend step length variances for fixed speeds compared to the large speed-trend step length variances with the high sensitivity controller (bottom row). Detrended step length variances were similar among fixed speed and three self-paced controller sensitivities for each slope (middle row).

Detrended and Speed-trend Step Width Variances

Unlike speed-trend step length variances, speed-trend step width variances only accounted for 0.04%, 0.02%, and 0.05% of the total variances for low, medium, and high sensitivities, respectively, on the decline (Fig. 7A). On level and incline, speed-trend step width variances were negligible (<0.01%) in all sensitivities. Within each slope, detrended and step-trend step width variances were not significantly different among sensitivities (main effect p's>0.05, Fig. 7B). Within each sensitivity, there were also no significant differences in detrended and speed-trend step width variances among slopes (main effect p's>0.05, Fig. 7B).

Figure 7: Step width variances on decline, level, and incline slopes for low, medium, and high controller sensitivities (n=9, due to statistical outliers). Error bars are standard deviations. Solid colored bars are the total variance. Stacked bars show the summation of the detrended (faded colored bar) and speed-trend (open bar) components. Percentage values above the stacked bars report the percentage of the speed-trend component. **A)** Step width variances had minimal, near zero speed-trend components within each slope. **B)** Detrended and speed-trend step width variances were not different across sensitivities within a given slope nor across slopes within a sensitivity.

Discussion

We sought to determine how self-paced treadmill controller sensitivity affects

spatiotemporal gait parameters on different slopes and to determine whether detrended

variability could mitigate differences in speed fluctuations that the different sensitivities

would likely impose. Within each slope, increasing self-paced controller sensitivity did not

affect average walking speeds or spatiotemporal gait parameters. However, more

sensitive self-paced controllers resulted in greater speed variance and step length

variance but had no significant effects on step frequency variance or step width variance.

Altogether, these results partially supported our main hypothesis that increasing controller

sensitivity would increase speed fluctuations, step length variability, and step width

variability. Importantly, as hypothesized, detrended variance was not affected by

controller sensitivity suggesting that detrending variability helps to mitigate differences

associated with treadmill speed fluctuations, whereas the speed-trend step length

variance increased with more sensitive controllers. By detrending step length variability,

the increase in total step length variance with more sensitive controllers was clearly

attributed to the predominant speed-trended step length variance component. If these

speed-trended contributions are not accounted for, changes in variability and potentially

kinetics and energetics when walking on a self-paced treadmill may be misinterpreted.

Additionally, we compared speed and gait parameters among slopes with a single

sensitivity as a typical study would do. As hypothesized, walking speed was fastest and

gait parameter variances were smallest on the level slope compared to decline and incline

slopes with each sensitivity. Overall, our study highlights that the choice of self-paced

treadmill controller parameters can alter the speed-related components of step length

variability and potentially other gait parameters with strong relationships with speed. Our

results suggest that detrending speed from step length variability and spatiotemporal gait

parameters is one approach for accounting for the differences in speed dynamics of

different self-paced treadmills.

An important finding was that self-paced treadmill walking had speed-related step

length variability components that increased with more sensitive self-paced controllers for

all slopes and were negligible during fixed speed treadmill walking. Differences in gait

variability were not due to differences in walking speed because speed was not

significantly different among the self-paced conditions in a slope and the fixed speeds

matched the average self-paced walking speeds on the level slope. Multiple studies have

reported that speed length variability for fixed speed walking was less than self-paced

walking [5,6,12]. Our results suggest that the smaller step length variability for fixed speed

walking compared to self-paced walking can be explained by the nearly non-existent

speed-trend step length variance during fixed speed treadmill walking (Fig. 6).

Additionally, speed-trend step length variance component and its percentage of the total

step length variance increased with more sensitive self-paced controllers. Differences in

gait variability would then be exacerbated with more sensitive self-paced controllers.

Detrended step length variances were similar, with no systematic trends, regardless of

the self-paced sensitivity or fixed speed conditions. This suggests that detrended step

length variances may reveal aspects of walking control rather than being a byproduct of

speed fluctuations.

Being able to interpret gait variability is beneficial for understanding walking and

balance control and is one reason for striving to identify a measure that is indifferent to

differences in speed fluctuations of self-paced controllers. Several self-paced treadmill

studies report step variability using standard deviation, variance, or coefficients of

variation but also report differing walking speeds and walking speed variabilities

[4,5,7,12,21,30]. Using these measurements, step length variability was greater in self-

paced walking compared to fixed speed walking, suggesting reduced balance control

while potentially incurring an increased energetic cost during self-paced walking [5,12,30].

Increased variability is indeed often interpreted as being less stable [32–35] or involving

greater active control [20]. Separating variability into detrended and speed-trend

components, however, could additionally be interpreted as the variability attributed to

steady-state walking and to changes in walking speed, respectively. Based on total step

length variance or speed-trend step length variance, walking on a self-paced treadmill

with higher sensitivities reduced stability and increased active control. However, based

on detrended step length variance, there were no apparent differences in stability or

active control between fixed speed and self-paced treadmill walking, for any sensitivity.

Our results suggest that speed-trend step length variability may reflect active control

needed to manage the speed fluctuations [36] and maintain the person's position on the

treadmill during self-paced treadmill walking. Detrended step length variability may reflect

intrinsic active control for maintaining balance and postural control during steady-state

walking, which would likely be the same regardless of treadmill features. The negligible

contributions of speed-trend step width variance was expected, as lateral foot placement

has little relation to speed [26]. Comparisons of step width variability across fixed speed

and self-paced treadmills are likely to be less affected by any potential differences across

controller sensitivities. Thus, increases in total or detrended step width variability for

different treatment groups or external destabilization/stabilization manipulations on any

self-paced treadmills would represent differences in mediolateral stability [35].

Our results suggest that self-paced walking on a decline was the most balance

demanding while walking on level was most efficient. When walking conditions are less

stable, subjects walk slowly with short and wide steps [7,37–39], which we observed on

the decline and incline compared to level. The increased detrended step length variance

on the decline and incline also suggests gaits were less stable compared to level because

increased step length variance corresponds with greater gait instability [33,40].

Comparing between decline and incline slopes, subjects walked faster by taking more

steps (i.e. increased step frequency) of similar step lengths on the decline compared to

the incline. However, step frequency variance on the decline was significantly larger than

incline, suggesting that decline walking was more unstable than incline walking [40–43].

Finally, self-paced treadmill walking on the level slope had the fastest speeds, longest

steps, narrowest steps, and lowest variances compared to decline and incline. This could

be partly due to level walking being more stable and energetically favorable compared to

walking on $\pm 10°$ slopes [42,44].

Similar to other studies, we found that the self-paced walking speeds matched

overground walking speed [2,4]. The average difference between a subject's self-paced

treadmill speed and overground speed was ~0.04 m/s, regardless of controller sensitivity.

Our average self-paced walking speed was ~1.23 m/s on the level treadmill, which is at

the lower end of the range of speeds (1.23-1.61 m/s) of other studies [2,4–7,21].

Differences in speed among self-paced treadmill studies are likely due to other self-paced

controller parameters instead of sensitivity, since we showed that average walking speed

was indifferent to controller sensitivity on all slopes, expanding on the previous study on

a level slope [6]. Differences in speeds could be related to the sample of subjects or

experiment set up such as using visual optic flow. Self-paced walking speeds with optic

flow was faster than without optic flow [4].

Another important consideration regarding gait variabilities across different self-

paced controller algorithms is that the controller structure likely induces different speed

fluctuations. Several self-paced treadmill algorithms have an overall goal of minimizing

the deviations of the person's position from an initial baseline position, which is often the

center of the treadmill [1,6,18,21,36]. However, there is no standard equation for

determining the treadmill belt speed corrections, and the equations vary depending on

the signals related to the treadmill system that can be used in a custom written real-time

controller. Published self-paced algorithms use ground reaction forces [2,21], echo

location [1], or motion capture [4,6,7] to calculate the changes in a subject's position on

the treadmill. Several self-paced treadmills controllers use proportional-derivative control

[6,21,36], while other controllers use proportional-integral-derivative control [18] or

proportional control [45]. The frequency of the treadmill belt speed corrections varies

among controllers spanning from updates at each footstep [21], at 30 Hz (for Motek's old

algorithm) [4,6], and at 120 Hz [19]. Additionally, the self-paced controller structures likely

affect the magnitudes of the belt speed fluctuations and walking speed fluctuations.

Several studies report the standard deviation of the self-paced walking speeds, which

quantifies the spread of walking speeds, providing an indicator of the magnitude of the

walking speed fluctuations. In our study, the range of walking speed standard deviations

for the low, medium, and high controller sensitivities for the level condition spanned

487 between 0.04 m/s to 0.06 m/s. In another Motek self-paced treadmill study for level

488 conditions, walking speed standard deviations were between 0.05 m/s to 0.07 m/s [6]

489 whereas in other studies that reported walking speed variability with custom designed

490 self-paced treadmill controllers, the walking speed standard deviations were 0.06 m/s to

491 0.1 m/s [5,30] (Fig. 8).

Figure 8. Standard deviations of walking speed (red) and treadmill belt speed

(black) on decline, level, and incline slopes for our fixed speed conditions (n=5), our self-

paced conditions (low, medium, and high sensitivities) (n=5), and for other studies that

used a self-paced treadmill. The fixed speed conditions had treadmill belt speed standard

deviations that were near zero, as expected, while walking speed standard deviations for

fixed speed conditions were within the range of walking speed standard deviations for the

self-paced conditions. The treadmill belt speed and walking speed fluctuations were

generally similar for the self-paced conditions. Previous self-paced treadmill studies

report a wide range of walking speed standard deviations. The Sloot et al. study used the

old algorithm for the Motek treadmill and reported values for three self-paced controllers,

V, P, and 2P, which correspond to the abbreviations in their paper [6]. The Wiens et al.

study reported values for two sessions collected on separate days with the same self-

paced controller, shown here as S1 and S2 [30]. Studies using the Motek treadmill are

bolded.

Limitations of this study include potential learning effects of walking on a self-paced

treadmill and testing a small subset of sensitivities and slopes. Participants with no

experience walking on a self-paced treadmill or sloped treadmill could experience a

learning effect over the nine self-paced walking conditions. Another limitation is that we

only used the maximum slope angle possible, $\pm 10°$ and did not test shallower slopes.

Similarly, we did not test sensitivities that spanned the full range, which could have

revealed additional significant effects of sensitivity. Lastly, detrended spatiotemporal gait

parameters were only analyzed with linear variability measures. The applicability of

detrending for nonlinear variability measures, such as detrended fluctuation analysis,

would require further investigation.

In summary, self-paced treadmill walking included speed-dependent gait variability

components that increased with higher sensitivity self-paced controllers. Self-paced

controller sensitivity had non-significant effects on average spatiotemporal gait

parameters (speed, step length, step width, and step frequency) on decline, level, and

incline slopes. Detrended variability seems to mitigate potential effects of different

treadmill speed dynamics of self-paced controllers on gait variability, which may be

beneficial when comparing gait variability among multiple self-paced treadmill studies or

with fixed speed conditions.

Acknowledgements

We would like to thank members of the Biomechanics, Rehabilitation, and

Interdisciplinary Neuroscience (BRaIN) Lab for help with data collections and discussions.

References

1.   Minetti AE, Boldrini L, Brusamolin L, Zamparo P, McKee T. A feedback-controlled
treadmill (treadmill-on-demand) and the spontaneous speed of walking and running
in humans. J Appl Physiol. 2003;95: 838–843. doi:10.1152/japplphysiol.00128.2003

2.   Ray NT, Knarr BA, Higginson JS. Walking speed changes in response to novel user-
driven treadmill control. J Biomech. 2018;78: 143–149.
doi:10.1016/j.jbiomech.2018.07.035

3.   Souman JL, Giordano PR, Schwaiger M, Frissen I, Thümmel T, Ulbrich H, et al.
CyberWalk: Enabling unconstrained omnidirectional walking through virtual
environments. ACM Trans Appl Percept. 2011;8: 25. doi:10.1145/2043603.2043607

4.   Plotnik M, Azrad T, Bondi M, Bahat Y, Gimmon Y, Zeilig G, et al. Self-selected gait
speed--over ground versus self-paced treadmill walking, a solution for a paradox. J
Neuroeng Rehabil. 2015;12: 20. doi:10.1186/s12984-015-0002-z

5.   Choi J-S, Kang D-W, Seo J-W, Tack G-R. Fractal fluctuations in spatiotemporal
variables when walking on a self-paced treadmill. J Biomech. 2017;65: 154–160.
doi:10.1016/j.jbiomech.2017.10.015

6.   Sloot LH, van der Krogt MM, Harlaar J. Self-paced versus fixed speed treadmill
walking. Gait Posture. 2014;39: 478–484. doi:10.1016/j.gaitpost.2013.08.022

7.   Kimel-Naor S, Gottlieb A, Plotnik M. The effect of uphill and downhill walking on gait
parameters: A self-paced treadmill study. J Biomech. 2017;60: 142–149.
doi:10.1016/j.jbiomech.2017.06.030

8.   Silverman AK, Wilken JM, Sinitski EH, Neptune RR. Whole-body angular momentum
in incline and decline walking. J Biomech. 2012;45: 965–971.
doi:10.1016/j.jbiomech.2012.01.012

9.   McIntosh AS, Beatty KT, Dwan LN, Vickers DR. Gait dynamics on an inclined
walkway. J Biomech. 2006;39: 2491–2502. doi:10.1016/j.jbiomech.2005.07.025

10.   Prentice SD, Hasler EN, Groves JJ, Frank JS. Locomotor adaptations for changes in
the slope of the walking surface. Gait Posture. 2004;20: 255–265.
doi:10.1016/j.gaitpost.2003.09.006

11. Sun J, Walters M, Svensson N, Lloyd D. The influence of surface slope on human
gait characteristics: a study of urban pedestrians walking on an inclined surface.
Ergonomics. 1996;39: 677–692. doi:10.1080/00140139608964489

12. Ibala E, Coupaud S, Kerr A. Comparison of The Muscle Pattern Variability During
Treadmill Walking (Fixed and Self-Pace) And Overground Walking of Able-Bodied
Adults. J Ann Bioeng. 2019;1.

13. Bulea TC, Jonghyun Kim, Damiano DL, Stanley CJ, Hyung-Soon Park. User-driven
control increases cortical activity during treadmill walking: an EEG study. Conf Proc
IEEE Eng Med Biol Soc. 2014;2014: 2111–2114. doi:10.1109/EMBC.2014.6944033

14. O'Connor SM, Donelan JM. Fast visual prediction and slow optimization of preferred
walking speed. J Neurophysiol. 2012;107: 2549–2559. doi:10.1152/jn.00866.2011

15. Farrens AJ, Lilley M, Sergi F. Training Propulsion via Acceleration of the Trailing
Limb. IEEE Trans Neural Syst Rehabil Eng. 2020;28: 2816–2825.
doi:10.1109/TNSRE.2020.3032094

16. Song S, Collins SH. Optimizing exoskeleton assistance for faster self-selected
walking. IEEE Trans Neural Syst Rehabil Eng. 2021;PP.
doi:10.1109/TNSRE.2021.3074154

17. Feasel J, Whitton MC, Kassler L, Brooks FP, Lewek MD. The integrated virtual
environment rehabilitation treadmill system. IEEE Trans Neural Syst Rehabil Eng.
2011;19: 290–297. doi:10.1109/TNSRE.2011.2120623

18. Kim J, Stanley CJ, Curatalo LA, Park H. A user-driven treadmill control scheme for
simulating overground locomotion. 2012 Annual International Conference of the
IEEE Engineering in Medicine and Biology Society. 2012. pp. 3061–3064.
doi:10.1109/EMBC.2012.6346610

19. Yoon J, Park H-S, Damiano DL. A novel walking speed estimation scheme and its
application to treadmill control for gait rehabilitation. J Neuroeng Rehabil. 2012;9: 62.
doi:10.1186/1743-0003-9-62

20. O'Connor SM, Kuo AD. Direction-dependent control of balance during walking and
standing. J Neurophysiol. 2009;102: 1411–1419. doi:10.1152/jn.00131.2009

21. Song S, Choi H, Collins SH. Using force data to self-pace an instrumented treadmill
and measure self-selected walking speed. J Neuroeng Rehabil. 2020;17: 68.
doi:10.1186/s12984-020-00683-5

22. Grieve DW, Gear RJ. The relationships between length of stride, step frequency,
time of swing and speed of walking for children and adults. Ergonomics. 1966;9: 379–
399. doi:10.1080/00140136608964399

23. Terrier P, Turner V, Schutz Y. GPS analysis of human locomotion: further evidence
for long-range correlations in stride-to-stride fluctuations of gait parameters. Hum
Mov Sci. 2005;24: 97–115. doi:10.1016/j.humov.2005.03.002

24. Hausdorff JM, Peng CK, Ladin Z, Wei JY, Goldberger AL. Is walking a random walk?
Evidence for long-range correlations in stride interval of human gait. J Appl Physiol.
1995;78: 349–358. doi:10.1152/jappl.1995.78.1.349

25. Riley PO, Paolini G, Della Croce U, Paylo KW, Kerrigan DC. A kinematic and kinetic
comparison of overground and treadmill walking in healthy subjects. Gait Posture.
2007;26: 17–24. doi:10.1016/j.gaitpost.2006.07.003

26. Collins SH, Kuo AD. Two independent contributions to step variability during over-
ground   human   walking.   PLoS   One.   2013;8:   e73597.
doi:10.1371/journal.pone.0073597

27. Dingwell JB, Bohnsack-McLagan NK, Cusumano JP. Humans control stride-to-stride
stepping movements differently for walking and running, independent of speed. J
Biomech. 2018;76: 144–151. doi:10.1016/j.jbiomech.2018.05.034

28. Ojeda LV, Rebula JR, Kuo AD, Adamczyk PG. Influence of contextual task
constraints on preferred stride parameters and their variabilities during human
walking. Med Eng Phys. 2015;37: 929–936. doi:10.1016/j.medengphy.2015.06.010

29. Choi J-S, Kang D-W, Seo J-W, Tack G-R. Reliability of the walking speed and gait
dynamics variables while walking on a feedback-controlled treadmill. J Biomech.
2015;48: 1336–1339. doi:10.1016/j.jbiomech.2015.02.047

30. Wiens C, Denton W, Schieber MN, Hartley R, Marmelat V, Myers SA, et al. Walking
speed and spatiotemporal step mean measures are reliable during feedback-
controlled treadmill walking; however, spatiotemporal step variability is not reliable.
J Biomech. 2019;83: 221–226. doi:10.1016/j.jbiomech.2018.11.051

31. Zeni JA Jr, Richards JG, Higginson JS. Two simple methods for determining gait
events during treadmill and overground walking using kinematic data. Gait Posture.
2008;27: 710–714. doi:10.1016/j.gaitpost.2007.07.007

32. Dingwell JB, Cusumano JP, Cavanagh PR, Sternad D. Local Dynamic Stability
Versus Kinematic Variability of Continuous Overground and Treadmill Walking. J
Biomech Eng. 2001;123: 27–32. doi:10.1115/1.1336798

33. Dingwell JB, John J, Cusumano JP. Do humans optimally exploit redundancy to
control step variability in walking? PLoS Comput Biol. 2010;6: e1000856.
doi:10.1371/journal.pcbi.1000856

34. Hausdorff JM, Edelberg HK, Mitchell SL, Goldberger AL, Wei JY. Increased gait
unsteadiness in community-dwelling elderly fallers. Arch Phys Med Rehabil.
1997;78: 278–283. Available: https://www.ncbi.nlm.nih.gov/pubmed/9084350

35. O'Connor SM, Xu HZ, Kuo AD. Energetic cost of walking with increased step
variability. Gait Posture. 2012;36: 102–107. doi:10.1016/j.gaitpost.2012.01.014

36. Qian Y, Yang K, Zhu Y, Wang W, Wan C. Local Dynamic Stability of Self-paced
Treadmill Walking Versus Fixed-speed Treadmill Walking. J Biomech Eng. 2019.
doi:10.1115/1.4045595

37. Menant JC, Steele JR, Menz HB, Munro BJ, Lord SR. Effects of walking surfaces
and footwear on temporo-spatial gait parameters in young and older people. Gait
Posture. 2009;29: 392–397. doi:10.1016/j.gaitpost.2008.10.057

38. Huijben B, van Schooten KS, van Dieën JH, Pijnappels M. The effect of walking
speed on quality of gait in older adults. Gait Posture. 2018;65: 112–116.
doi:10.1016/j.gaitpost.2018.07.004

39. Mak TCT, Young WR, Chan DCL, Wong TWL. Gait Stability in Older Adults During
Level-Ground Walking: The Attentional Focus Approach. J Gerontol B Psychol Sci
Soc Sci. 2020;75: 274–281. doi:10.1093/geronb/gby115

40. Hausdorff JM. Gait dynamics, fractals and falls: finding meaning in the stride-to-stride
fluctuations   of   human   walking.   Hum   Mov   Sci.   2007;26:   555–589.
doi:10.1016/j.humov.2007.05.003

41. Bohnsack-McLagan NK, Cusumano JP, Dingwell JB. Adaptability of stride-to-stride
control of stepping movements in human walking. J Biomech. 2016;49: 229–237.
doi:10.1016/j.jbiomech.2015.12.010

42. Hunter LC, Hendrix EC, Dean JC. The cost of walking downhill: is the preferred gait
energetically   optimal?   J   Biomech.   2010;43:   1910–1915.
doi:10.1016/j.jbiomech.2010.03.030

43. Beauchet O, Annweiler C, Lecordroch Y, Allali G, Dubost V, Herrmann FR, et al.
Walking speed-related changes in stride time variability: effects of decreased speed.
J Neuroeng Rehabil. 2009;6: 32. doi:10.1186/1743-0003-6-32

44. Jeffers JR, Auyang AG, Grabowski AM. The correlation between metabolic and
individual leg mechanical power during walking at different slopes and velocities. J
Biomech. 2015;48: 2919–2924. doi:10.1016/j.jbiomech.2015.04.023

45. Wiens C, Denton W, Schieber M, Hartley R, Marmelat V, Myers S, et al. Reliability
of a Feedback-Controlled Treadmill Algorithm Dependent on the User's Behavior.
IEEE   Int   Conf   Electro   Inf   Technol.   2017;2017:   545–550.
doi:10.1109/EIT.2017.8053423

Supplement Caption

S1 Figure: The center of mass (COM) position in the anterior-posterior direction,

treadmill belt velocity, and COM velocity in the anterior-posterior direction for a single step

and walking for 60 seconds using Motek's "new algorithm" with the low, medium, and high

sensitivity values used in our study and using Motek's old algorithm (reported in Sloot et

al. 2014) with the default/medium sensitivity value of 1 (gray rectangle). For the single

step condition, the subject took a single forward step and then stood still on the treadmill

belt. For the single step condition, after an initial correction in response to the change in

the person's relative position with the treadmill, the "new algorithm" produced treadmill

belt velocity oscillations that resulted in COM position oscillations with a slow decay rate

towards the steady state position whereas the "old algorithm" rapidly reached the steady

state COM position. The COM oscillations increased in frequency for increasing

sensitivities with the "new algorithm." For the walking condition, the "old algorithm" had

more frequent changes in the COM, treadmill belt velocity, and COM velocity compared

to the "new algorithm."

679