Speed-related but not detrended gait variability increases with more sensitive self-paced treadmill controllers at multiple slopes

Cesar R. Castano[1]*, Helen J. Huang[1,2]

[1]Department of Mechanical and Aerospace Engineering, University of Central Florida, Orlando, FL, United States

[2]Disability, Aging, and Technology Cluster, University of Central Florida, Orlando, FL, United States

* Corresponding author

Email: Castanocesar@knights.ucf.edu (CRC)

Abstract

Self-paced treadmills are being used more and more to study humans walking with their self-selected gaits on a range of slopes. There are multiple options to purchase a treadmill with or implement a custom written self-paced controller, which raises questions about how self-paced controller affect treadmill speed and gait biomechanics on multiple slopes. This study investigated how different self-paced treadmill controller sensitivities affected gait parameters and variability on a decline, level, and incline slopes. We hypothesized that increasing self-paced controller sensitivity would increase gait variability on each slope. We also hypothesized that detrended variability could help mitigate differences in variability that arise from differences in speed fluctuations created by the self-paced controllers. Ten young adults walked on a self-paced treadmill using three self-paced controller sensitivities (low, medium, and high) and fixed speeds at three slopes (decline, -10°; level, 0°; incline, +10°). Within each slope, average walking speeds and spatiotemporal gait parameters were similar regardless of self-paced controller sensitivity. With higher controller sensitivities on each slope, speed fluctuations, speed variance, and step length variance increased whereas step frequency variance and step width variance were unaffected. Detrended variance was not affected by controller sensitivity suggesting that detrending variability helps mitigate differences associated with treadmill speed fluctuations. Speed-trend step length variances, however, increased with more sensitive controllers. Further, detrended step length variances were similar for self-paced and fixed speed walking, whereas self-paced walking included substantial speed-trend step length variance not present in fixed speed walking. In addition, regardless of the self-

paced controller, subjects walked fastest on the level slope with the longest steps,

widest steps, and least variance. Overall, our findings suggest that separating gait

variability into speed-trend and detrended variability could be beneficial for interpreting

gait variability among multiple self-paced treadmill studies and when comparing self-

paced walking with fixed speed walking.

Introduction

Self-paced treadmills (also known as user-driven, active, or adaptive speed

treadmills) are typically motorized treadmills that modulate belt speeds to match the

subject's walking speed and are becoming more prevalent in gait laboratories. Self-

paced control algorithms can use ground reaction forces, marker locations, and gait

parameters, among other real-time measures, to determine when and how much to

speed up or slow down the treadmill belts. Often, the intent for using self-paced

treadmills is to match overground walking speeds and allow for less constrained gait [1–

3]. As such, subjects can walk at their self-selected walking speed for several minutes

and hundreds of strides while preserving natural gait fluctuations on self-paced

treadmills [4–6]. Self-paced treadmills can also be set at incline and decline slopes to

study self-selected uphill and downhill gaits [7], overcoming limitations of overground

sloped walking studies that are often constrained to short (10-20 meter) ramps or

available outdoor terrains [8–11].

Several studies have investigated differences between self-paced and fixed

speed walking on a level treadmill. Unlike self-paced walking where the treadmill adjusts

to the subject's gait, the subject adjusts their gait to match the constant treadmill speed

during fixed speed walking. Studies showed that stride variabilities, muscle activities,

and walking speed during self-paced treadmill walking were more similar to overground

walking than fixed speed treadmill walking [2,6,12]. Peak anterior ground reaction forces

also increased on a user-driven treadmill compared to a fixed speed treadmill [2]. On an

active (self-paced) treadmill, the sensorimotor cortex was more engaged compared to

passively walking on the (fixed speed) treadmill [13]. Additionally, self-paced treadmills

have helped demonstrate that exoskeletons, visual feedback, and mechanical

perturbations can shift a subject's preferred walking speed [14–16].

As more groups incorporate self-paced walking into their studies, more

customized self-paced controllers are being offered as a built-in mode (ex. Motek

Medical's M-Gait, used in this study) or developed and implemented on treadmills

already in a laboratory or on new treadmills that lack a self-paced mode option

[1,2,14,17–20]. A previous study evaluated step kinematics and step variability for three

control algorithms when walking on a self-paced treadmill at a level slope resulted in a

range of speed fluctuations that resulted in similar step kinematics but a wide range of

significantly different step length standard deviations (0.037-0.062 m) [6]. These

differences in step length variability may make comparing and interpreting findings

across multiple self-paced walking studies difficult. Identifying spatiotemporal gait

metrics that can account for differences in speed fluctuations and treadmill

responsiveness of self-paced treadmill controllers may improve our understanding of

self-paced walking.

Gait parameters, particularly those with a strong relationship with speed such as

step length [21], are likely to be sensitive to differences in self-selected gaits and speed

fluctuations. Gait parameters have both long-range correlations over hundreds of steps

[22] and short-range dependencies on preceding strides [23], which may modulate

walking speed over short distances [24]. By removing the speed relationship from step

length during overground walking, step length variability can be separated into speed-

related (speed-trend) and speed-independent (detrended) components. These

components may represent long-term and short-term active balance control [25]. A few

other overground gait studies also removed speed-related trends to analyze detrended

gait variability to avoid speed-related effects [26,27]. If self-paced treadmill walking is

similar to overground walking, then detrended gait variability may be beneficial for

analyzing self-paced treadmill gait. Recently, two studies reported conflicting results

regarding the reliability of spatiotemporal variability during self-paced walking using two

different self-paced treadmill systems. One study showed that spatiotemporal gait

variability on a self-paced treadmill is reliable for within-session and between sessions

[28], whereas another study found significant differences in spatiotemporal variability

between sessions [29]. One potential factor that could affect reliability is differences in

speed dynamics due to the self-paced treadmill systems.

The primary purpose of this study was to investigate how self-paced treadmill

controller sensitivity affects spatiotemporal gait parameters on different slopes (decline,

level, and incline) and to determine whether detrended gait variability may mitigate

differences in treadmill speed fluctuations of self-paced controllers. We hypothesized

that increasing self-paced controller sensitivity would increase speed fluctuations and

gait variability within each slope. We also hypothesized that detrended gait variability

could help mitigate the expected differences in speed fluctuations and would be similar

across sensitivities within a slope. Because studies often use a single sensitivity (or set

of controller parameters) for all conditions, a secondary purpose was to investigate the

effect of slopes on spatiotemporal gait parameters with each self-paced controller

sensitivity. We hypothesized that regardless of sensitivity, self-paced walking speed

would be fastest and gait variability would be smallest on the level slope compared to

decline and incline slopes for each sensitivity.

Materials and Methods

Ten healthy young adults (22.6±3.5 years; 4 females) with no musculoskeletal or

neurological conditions participated in this study and provided informed written consent.

The University of Central Florida Institutional Review Board approved the protocol and

consent form.

Subjects walked on a self-paced instrumented treadmill (M-Gait System and D-

Flow software version 3.28, Motekforce Link, Amsterdam, Netherlands) as motion

capture data using the 16-marker OptiTrack "Conventional Lower Body" marker set was

recorded (22 cameras, Prime 13 and 13W, OptiTrack NaturalPoint Inc., Corvallis,

Oregon). The self-paced controller uses a proportional-derivative controller to adjust belt

speed, $\ddot{x}_b$ based on the subject's speed, $\dot{x}$ and relative position of their approximate

center-of-mass (average of the pelvis markers' positions) on the treadmill relative to the

middle set point, Δx [6](Eq. 1, Fig. 1).

$$\ddot{x}_b = \text{g}(\text{P}\Delta\text{x} - \Delta\text{x}\text{D}\dot{x})$$ Eq. 1

The controller parameters are the sensitivity gain, g, proportional constant, P, and

derivative constant, D. The low, medium, and high sensitivity controllers corresponded

to gains of 0.5, 1.0, and 1.5, respectively.

Figure 1: Schematic illustrating the self-paced controller concept and equation.

The equation parameters are described in Eq. 1, and gains of 0.5, 1.0, and 1.5 yield the

low (green), medium (red), and high (purple) controller sensitivities. When the subject

moves in front of the set point, the treadmill belts speed up. When the subject moves

behind the set point, the treadmill belts slow down. When the subject remains near the

set point, the belt speed does not change.

Experimental Protocol

Subjects first walked on the treadmill with a range of fixed speeds and self-paced

controller sensitivities during a brief familiarization period. They also completed a 10-

meter walk test to identify their level overground walking speed. Subjects then

completed nine 5-minute self-paced treadmill walking conditions, which were the

combinations of controller sensitivities (low, medium, high) and slopes (decline, -10°;

level, 0°; incline, +10°) in a randomized order with brief 1-2 minute rest periods between

conditions. Subjects then completed 3 subject-specific fixed speed conditions, one for

each slope. The subject-specific fixed speeds were calculated as the average walking

speed (using from the last 2.5 minutes of a condition) of the 3 controller sensitivities on

a slope for each subject. While all subjects performed the fixed speed conditions, a file

naming error resulted in just five subjects having complete fixed speed data sets.

Spatiotemporal Gait Parameters

Using custom MATLAB (Mathworks, Inc., Natick, Massachusetts) scripts, we first

resampled the treadmill belt speed data from 333 Hz to 240Hz to match the motion

capture system. We applied a low-pass filter (zero-lag fourth-order Butterworth filter at 6

Hz) to these data. We identified heel strikes as the most anterior position of the

calcaneus markers and toe-offs as the most posterior position of the second metatarsal

head markers for each foot [30].

We excluded the first 45 seconds for all analyses and used the last 215 seconds,

which we considered to be at "steady-state" speeds [4]. Walking speed was the sum of

the treadmill belt speed and speed (0.5 Hz low-pass filtered derivative) of the

approximate center-of-mass. To characterize speed fluctuations, we computed the

power spectral density of the walking speeds between 0.01-0.2 Hz frequencies. Step

length was calculated as the anterior-posterior distance between heel markers divided

by the cosine of the treadmill angle to account for the different slopes. Step width was

the mediolateral distance between heel markers for each step (heel strike to

contralateral heel strike), and step frequency was the number of steps per second.

Variability and Detrended Analysis

163 We computed the variances for speed, step frequency, step length, and step

165 width. We also separated the step length and step width variances into speed-

166 dependent (speed-trend) and speed-independent (detrended) components [25]. For

167 each self-paced condition, we fitted the speed data with Eq. 2, to calculate the speed-

168 trend step length based on Grieve & Gear, 1966.

$$step\ length = \alpha \cdot v^{\beta} \qquad \text{Eq. 2}$$

170 where v is walking speed and α and β are constants, and fitted the speed data with Eq.

171 3, to calculate the speed-trend step width based on Collins and Kuo, 2013.

$$step\ width = (\gamma \cdot v) + \delta \qquad \text{Eq. 3}$$

where v is walking speed and γ and δ are constants. No speed-related trend has been

reported or is expected for step width, whereas step length has a well-established

relationship with speed and is expected. For each fixed speed condition, we combined

data from the three self-paced sensitivities for a slope before performing the fits to

identify a single set of parameters (α, β and γ, δ). We calculated the speed-trended step

lengths and speed-trended step widths using the fits (Eq. 2, Eq. 3) and subtracted them

from the actual step lengths and step widths, respectively, to obtain the detrended

component [25]. Then, the variance of the speed-trended and detrended components

were calculated. The sum of the variance of both components should approximate to

the total variance of the actual step length and step width because the speed-trended

and detrended values are uncorrelated.

Statistics

To test our main hypothesis and determine if controller sensitivity was a main effect within a given slope, we applied general linear models with repeated-measures independently for each spatiotemporal gait parameter. The assumptions of a repeated measures ANOVA (normality, homoscedasticity, and sphericity) were validated using a Shapiro-Wilk Test, Bartlett's test, and Mauchly's test. Outliers based on the default methods (Hi leverage, Cook's distance, and DFITS) used in Minitab (version 19.2020.1, Minitab, LLC, State College, Pennsylvania) were excluded. Because gait experiments typically use a single sensitivity, we applied the same statistical approach with each sensitivity to determine if slope (decline, level, and incline) was a main effect for a given sensitivity. Whenever sensitivity or slope was a main effect, we used post-hoc pair-wise Tukey's Honest Significant Difference (HSD) tests adjusted for multiple comparisons (Dunn-Bonferroni correction) to identify which sensitivities were significantly different within a given slope and which slopes were significantly different for a given sensitivity. We set the significance level to 0.05 and only report Tukey HSD p-values when either sensitivity or slope was a main effect for their respective statistical models. We used SPSS (version 25, IBM Corporation, Armonk, NY, USA) for Mauchly's sphericity test and Minitab for all other statistical analyses.

Results

Speed Fluctuations

In all slopes, self-paced walking sensitivities had evident speed fluctuations over time, unlike fixed speed walking (Fig. 2A). Speed fluctuations were distributed across more frequencies and had greater power at higher frequencies as self-paced controller sensitivities increased within each slope (Fig. 2B). The spectral powers for the fixed speed walking (not plotted in Fig. 2B) were 2 orders of magnitude less than self-paced walking.

Figure 2: Walking speed fluctuations for a representative subject and group-average power spectral densities of walking speed. **A)** Walking speed time courses for self-paced walking with the low (green), medium (red), and high (purple) sensitivity controllers and for fixed-speed walking (black) at each slope for a representative subject. Fixed speed walking had nearly no evident fluctuations compared to self-paced walking. **B)** The group (n = 10) averaged power spectral density of walking speed was distributed across more frequencies for self-paced walking with higher sensitivities.

Average Spatiotemporal Gait Parameters

For the level slope, the walking speeds (mean±standard deviation) were 1.24±0.28 m/s, 1.23±0.26 m/s, and 1.22±0.28 m/s for low, medium, and high sensitivities, respectively, which were similar to the 10-meter walk speeds, 1.27±0.11 m/s. Within each slope, increasing self-paced controller sensitivity did not affect average speed, step frequency, step length, or step width (Fig. 3).

Figure 3: Group averaged walking speed, step frequency, step length, and step width (top row) and corresponding variances (bottom row) for each controller sensitivity for each slope. For all gait parameters, n=10 except for speed variance and step length variance where n=9, due to statistical outliers. Single sided error bars are shown and indicate standard deviations. Square brackets with black asterisks indicate significant differences between sensitivities within a slope (Tukey HSD, $p < 0.05$). The brackets in

these plots show that controller sensitivity only resulted in significant increases for

speed variance and step length variance. Curly braces indicate significant differences

between slopes within a single sensitivity indicated by the color-coded asterisks (Tukey

HSD, p<0.05). The curly braces in these plots show that **A)** walking speed was fastest

and speed variance was lowest on the level slope; **B)** step frequency was slowest on

the incline while step frequency variance was highest on the decline; **C)** step lengths

were longest and had the least variance on the level slope; and **D)** step width was

smallest on the level slope while step width variances were not significantly different

among slopes.

Each sensitivity showed that subjects walked the fastest with the longest step

lengths and narrowest step widths on the level slope compared to the decline and

incline slopes (Fig. 3, colored asterisks, p's<0.05). Additionally, the slowest step

frequencies were on the incline compared to level and decline slopes (p's<0.05). With

the low or medium sensitivity, subjects walked faster on the decline compared to the

incline (p's<0.05).

Variability of Spatiotemporal Gait Parameters

Within each slope, increasing self-paced controller sensitivity did not affect step

frequency variance and step width variance (Fig. 3). Only speed variance and step

length variance showed significant increases with higher sensitivities within each slope

(Fig. 3, black asterisks, p's<0.05).

Each sensitivity showed that step length variance was smallest on the level slope

compared to the incline and decline slopes (Fig. 3, colored asterisks, p's<0.05), and

there were no significant differences in step width variance among slopes (Fig. 3). Each

sensitivity also showed that speed variance on the decline was larger than level

(p's<0.05). Speed variance on the incline was larger than level with just the low

sensitivity. With the low or high sensitivity, step frequency variance on the decline slope

was larger than level and incline slopes (p's<0.05).

Detrended Analysis

In a representative subject, greater fluctuations in speed and step lengths were

evident as self-paced controller sensitivity increased (Fig. 4A), and as expected, there

were strong relationships between step length and speed during self-paced walking for

all sensitivities (Fig. 4B). For fixed speed walking, there was not a relationship between

step length and speed, as speed was nearly constant and step lengths were

concentrated in narrow range (Fig. 4A & 4B). Thus, the speed-trend step length

variance for fixed speed walking was negligible (Fig. 4C). For this subject, the speed-

trend step length variance was smallest for the low sensitivity controller while the

medium and high sensitivities had larger but similar speed-trend step length variances

(Fig. 4C). Detrended step lengths, which equaled the speed-trend step length minus the

actual step length, had similar variances across the self-paced and fixed speed

conditions (Fig. 4D).

Figure 4: Progression of detrending speed from step length to obtain detrended and speed-trend variabilities for walking with low (green), medium (red), and high (purple) self-paced controller sensitivities and at a fixed speed (black), for a representative subject. **A)** Time courses of actual step lengths and walking speed paralleled each other. **B)** Fit lines of the expected step length and speed relationship (Eq. 2) during self-paced walking (blue line). The equation and line shown for the fixed speed data is from the average of the equation constants of the low, medium, and high sensitivity fit equations. **C)** The speed-trend step lengths (open circles) calculated from the fit equations and the actual step lengths (gray circles) are plotted for all steps. The variance of the speed-trend step lengths was nearly zero for fixed speed walking (5.2×10^{-9} m^2) and ranged between 0.00018 m^2 -0.00034 m^2 for the self-paced controllers. **D)** The detrended step lengths (shaded circles) are equal to the speed-trend

287 step lengths (open circles) minus the actual step lengths (gray circles). The variance of

288 the detrended step lengths ranged between 0.00022 m^2 0.00036 m^2 for self-paced and

289 fixed speed walking conditions.

Detrended and Speed-trend Step Length Variances

Speed-trend step length variances accounted for 34%, 47%, and 52% of the total

variances for low, medium, and high sensitivities, respectively, on the decline, and

similar percentages were observed on level (35%, 57%, 50%) and incline (41%, 46%,

58%) (Fig. 5A). Within each slope, detrended step length variances were not

significantly different among sensitivities, while speed-trend step length variances were

largest with the high sensitivity compared to the low sensitivity (Fig. 5B, black asterisks,

p's<0.05). Speed-trend step length variances were also larger with the medium

sensitivity than the low sensitivity on the level slope (p<0.05).

Figure 5: Step length variances on decline, level, and incline slopes for low,

medium, and high controller sensitivities (n=9, due to statistical outliers). Error bars are

standard deviations. Solid colored bars are the total variance. Stacked bars show the

summation of the detrended (faded colored bar) and speed-trend (open bar)

components. Percentage values above the stacked bars report the percentage of the

speed-trend component. **A)** As controller sensitivity increased, the speed-trend

component in total step length variance also increased within each slope. **B)** Controller

sensitivity did not affect detrended step length variances within a given slope, but as

controller sensitivity increased, speed-trend step length variance also increased within a

given slope, as indicated with square brackets and black asterisks (Tukey HSD,

p<0.05). When comparing across slopes within a given sensitivity, detrended and

speed-trend step length variances were smallest on level compared to incline and

decline, as indicated by the curly braces with color-coded asterisks of the specific

sensitivities (green = low; red = medium; purple = high) (Tukey HSD, p<0.05).

Each sensitivity revealed that detrended step length variance was lowest on the

level slope compared to decline and incline (Fig. 5B, colored asterisks, p's<0.05) and

that detrended step length variance was not significantly different between decline and

incline (Fig. 5B). Each sensitivity also showed that speed-trend step length variance

was larger on the incline than level (p's<0.05). Speed-trend step length variance was

larger on the decline compared to level only with the high sensitivity (p<0.05).

For the five individual subjects with fixed speed data, fixed speed walking had the

smallest step length variances compared to self-paced walking (Fig. 6). Detrended step

length variances for fixed speed walking were within the range of the self-paced

sensitivities, while speed-trend step length variances for fixed speed walking were

negligible $< 1 \times 10^{-7}$ m^2 (Fig. 6).

Figure 6: Total (solid circles), detrended (faded circles), and speed-trend (open circles) step length variances for fixed speed walking (black x's) and self-paced walking with low (green), medium (red), and high (purple) sensitivity self-paced controllers for 5 subjects (multi-colored shaded rectangles). Detrended step length variances were similar among fixed speed and three self-paced controller sensitivities for each slope (middle row). Speed-trend step length variances were near zero for fixed speed walking (bottom row). Total step length variances were lowest for fixed speed walking compared to the self-paced walking conditions (top row) as a result of the near zero speed-trend step length variances for fixed speeds (bottom row).

Detrended and Speed-trend Step Width Variances

Unlike speed-trend step length variances, speed-trend step width variances only accounted for 0.04%, 0.02%, and 0.05% of the total variances for low, medium, and high sensitivities, respectively, on the decline (Fig. 7A). On level and incline, speed-trend step width variances were negligible (<0.01%) in all sensitivities. Within each slope, detrended and step-trend step width variances were not significantly different among sensitivities (main effect p's>0.05, Fig. 7B). Within each sensitivity, there were also no significant differences in detrended and speed-trend step width variances among slopes (main effect p's>0.05, Fig. 7B).

Figure 7: Step width variances on decline, level, and incline slopes for low, medium, and high controller sensitivities (n=9, due to statistical outliers). Error bars are standard deviations. Solid colored bars are the total variance. Stacked bars show the summation of the detrended (faded colored bar) and speed-trend (open bar) components. Percentage values above the stacked bars report the percentage of the speed-trend component. **A)** Step width variances had minimal, near zero speed-trend components within each slope. **B)** Detrended and speed-trend step width variances

357 were not different across sensitivities within a given slope nor across slopes within a

358 sensitivity.

Discussion

We sought to determine how self-paced treadmill controller sensitivity affects

spatiotemporal gait parameters on different slopes and to determine whether detrended

variability could mitigate differences in speed fluctuations that the different sensitivities

would likely impose. Within each slope, increasing self-paced controller sensitivity did

not affect average walking speeds or spatiotemporal gait parameters. However, more

sensitive self-paced controllers resulted in greater speed variance and step length

variance but had no significant effects on step frequency variance or step width

variance. Altogether, these results partially supported our main hypothesis that

increasing controller sensitivity would increase speed fluctuations, step length

variability, and step width variability. Importantly, as hypothesized, detrended variance

was not affected by controller sensitivity suggesting that detrending variability helps to

mitigate differences associated with treadmill speed fluctuations, whereas the speed-

trend step length variance increased with more sensitive controllers. By detrending step

length variability, the increase in total step length variance with more sensitive

controllers was clearly attributed to the predominant speed-trended step length variance

component. If these speed-trended contributions are not accounted for, changes in

variability and potentially kinetics and energetics when walking on a self-paced treadmill

may be misinterpreted. Additionally, we compared speed and gait parameters among

slopes with a single sensitivity as a typical study would do. As hypothesized, walking

speed was fastest and gait parameter variances were smallest on the level slope

compared to decline and incline slopes with each sensitivity. Overall, our study

highlights that the choice of self-paced treadmill controller parameters can alter the

speed-related components of step length variability and potentially other gait

parameters with strong relationships with speed. Our results suggest that detrending

speed from step length variability and spatiotemporal gait parameters is one approach

for accounting for the differences in speed dynamics of different self-paced treadmills.

An important finding was that self-paced treadmill walking had speed-related step

length variability components that increased with more sensitive self-paced controllers

for all slopes and were negligible during fixed speed treadmill walking. Differences in

gait variability were not due to differences in walking speed because speed was not

significantly different among the self-paced conditions in a slope and the fixed speeds

matched the average self-paced walking speeds on the level slope. Multiple studies

have reported that speed length variability for fixed speed walking was less than self-

paced walking [5,6,12]. Our results suggest that the smaller step length variability for

fixed speed walking compared to self-paced walking can be explained by the nearly

non-existent speed-trend step length variance during fixed speed treadmill walking (Fig.

6). Additionally, speed-trend step length variance component and its percentage of the

total step length variance increased with more sensitive self-paced controllers.

Differences in gait variability would then be exacerbated with more sensitive self-paced

controllers. Detrended step length variances were similar, with no systematic trends,

regardless of the self-paced sensitivity or fixed speed conditions. This suggests that

detrended step length variances may reveal aspects of walking control rather than being

a byproduct of speed fluctuations.

Being able to interpret gait variability is beneficial for understanding walking and

balance control and is one reason for striving to identify a measure that is indifferent to

differences in speed fluctuations of self-paced controllers. Several self-paced treadmill

studies report variability using standard deviation, variance, or coefficients of variation

[4,5,7,12,14,29]. Using these measurements, step length variability was greater in self-

paced walking compared to fixed speed walking, suggesting reduced balance control

while potentially incurring an increased energetic cost during self-paced walking

[5,12,29]. Increased variability is indeed often interpreted as being less stable [31–34] or

involving greater active control [20]. Separating variability into detrended and speed-

trend components, however, could additionally be interpreted as the variability attributed

to steady-state walking and to changes in walking speed, respectively. Based on total

step length variance or speed-trend step length variance, walking on a self-paced

treadmill with higher sensitivities reduced stability and increased active control.

However, based on detrended step length variance, there were no apparent differences

in stability or active control between fixed speed and self-paced treadmill walking, for

any sensitivity. Our results suggest that speed-trend step length variability may just

reflect active control needed to manage speed fluctuations and unstable dynamics of

self-paced treadmill walking [35], while detrended step length variability may reflect

active control intrinsic for steady-state walking, which would likely be the same

regardless of treadmill features. The negligible contributions of speed-trend step width

variance was expected, as lateral foot placement has little relation to speed [25].

Comparisons of step width variability across fixed speed and self-paced treadmills are

likely to be less affected by any potential differences across controller sensitivities.

Thus, increases in total or detrended step width variability for different treatment groups

or external destabilization/stabilization manipulations on any self-paced treadmills would

represent differences in mediolateral stability [34].

Our results suggest that self-paced walking on a decline was the most balance

demanding while walking on level was most efficient. When walking conditions are less

stable, subjects walk slowly with short and wide steps [7,36–38], which we observed on

the decline and incline compared to level. The increased detrended step length variance

on the decline and incline also suggests gaits were less stable compared to level

because increased step length variance corresponds with greater gait instability [32,39].

Comparing between decline and incline slopes, subjects walked faster by taking more

steps (i.e. increased step frequency) of similar step lengths on the decline compared to

the incline. However, step frequency variance on the decline was significantly larger

than incline, suggesting that decline walking was more unstable than incline walking

[39–42]. Finally, self-paced treadmill walking on the level slope had the fastest speeds,

longest steps, narrowest steps, and lowest variances compared to decline and incline.

This could be partly due to level walking being more stable and energetically favorable

compared to walking on $\pm10°$ slopes [41,43].

Similar to other studies, we found that the self-paced walking speeds matched

overground walking speed [2,4]. The average difference between a subject's self-paced

treadmill speed and overground speed was ~0.04 m/s, regardless of controller

sensitivity. Our average self-paced walking speed was ~1.23 m/s on the level treadmill,

which is at the lower end of the range of speeds (1.23-1.61 m/s) of other studies [2,4–

7,14]. Differences in speed among self-paced treadmill studies are likely due to other

self-paced controller parameters instead of sensitivity, since we showed that average

walking speed was indifferent to controller sensitivity on all slopes, expanding on the

previous study on a level slope [6]. Differences in speeds could be related to the

sample of subjects or experiment set up such as using visual optic flow. Self-paced

walking speeds with optic flow was faster than without optic flow [4].

Limitations of this study include potential learning effects of walking on a self-

paced treadmill and testing a small subset of sensitivities and slopes. Participants with

no experience walking on a self-paced treadmill or sloped treadmill could experience a

learning effect over the nine self-paced walking conditions. Another limitation is that we

only used the maximum slope angle possible, $\pm10°$ and did not test shallower slopes.

Similarly, we did not test sensitivities that spanned the full range, which could have

revealed additional significant effects of sensitivity.

In summary, self-paced controller sensitivity had non-significant effects on

average spatiotemporal gait parameters (speed, step length, step width, and step

frequency) on decline, level, and incline slopes. Self-paced treadmill walking included

speed-dependent gait variability components that increased with higher sensitivity self-

paced controllers. Detrended variability seems to mitigate potential effects of different

treadmill speed dynamics of self-paced controllers on gait variability, which may be

beneficial when comparing gait variability among multiple self-paced treadmill studies or

with fixed speed conditions.

Acknowledgements

We would like to thank members of the Biomechanics, Rehabilitation, and Interdisciplinary Neuroscience (BRaIN) Lab for help with data collections and discussions.

References

1. Minetti AE, Boldrini L, Brusamolin L, Zamparo P, McKee T. A feedback-controlled treadmill (treadmill-on-demand) and the spontaneous speed of walking and running in humans. J Appl Physiol. 2003;95: 838–843. doi:10.1152/japplphysiol.00128.2003

2. Ray NT, Knarr BA, Higginson JS. Walking speed changes in response to novel user-driven treadmill control. J Biomech. 2018;78: 143–149. doi:10.1016/j.jbiomech.2018.07.035

3. Souman JL, Giordano PR, Schwaiger M, Frissen I, Thümmel T, Ulbrich H, et al. CyberWalk: Enabling unconstrained omnidirectional walking through virtual environments. ACM Trans Appl Percept. 2011;8: 25. doi:10.1145/2043603.2043607

4. Plotnik M, Azrad T, Bondi M, Bahat Y, Gimmon Y, Zeilig G, et al. Self-selected gait speed--over ground versus self-paced treadmill walking, a solution for a paradox. J Neuroeng Rehabil. 2015;12: 20. doi:10.1186/s12984-015-0002-z

5. Choi J-S, Kang D-W, Seo J-W, Tack G-R. Fractal fluctuations in spatiotemporal variables when walking on a self-paced treadmill. J Biomech. 2017;65: 154–160. doi:10.1016/j.jbiomech.2017.10.015

6. Sloot LH, van der Krogt MM, Harlaar J. Self-paced versus fixed speed treadmill walking. Gait Posture. 2014;39: 478–484. doi:10.1016/j.gaitpost.2013.08.022

7. Kimel-Naor S, Gottlieb A, Plotnik M. The effect of uphill and downhill walking on gait parameters: A self-paced treadmill study. J Biomech. 2017;60: 142–149. doi:10.1016/j.jbiomech.2017.06.030

8. Silverman AK, Wilken JM, Sinitski EH, Neptune RR. Whole-body angular momentum in incline and decline walking. J Biomech. 2012;45: 965–971. doi:10.1016/j.jbiomech.2012.01.012

9.   McIntosh AS, Beatty KT, Dwan LN, Vickers DR. Gait dynamics on an inclined
walkway. J Biomech. 2006;39: 2491–2502. doi:10.1016/j.jbiomech.2005.07.025

10. Prentice SD, Hasler EN, Groves JJ, Frank JS. Locomotor adaptations for changes
in the slope of the walking surface. Gait Posture. 2004;20: 255–265.
doi:10.1016/j.gaitpost.2003.09.006

11. Sun J, Walters M, Svensson N, Lloyd D. The influence of surface slope on human
gait characteristics: a study of urban pedestrians walking on an inclined surface.
Ergonomics. 1996;39: 677–692. doi:10.1080/00140139608964489

12. Ibala E, Coupaud S, Kerr A. Comparison of The Muscle Pattern Variability During
Treadmill Walking (Fixed and Self-Pace) And Overground Walking of Able-Bodied
Adults. J Ann Bioeng. 2019;1.

13. Bulea TC, Jonghyun Kim, Damiano DL, Stanley CJ, Hyung-Soon Park. User-driven
control increases cortical activity during treadmill walking: an EEG study. Conf Proc
IEEE Eng Med Biol Soc. 2014;2014: 2111–2114. doi:10.1109/EMBC.2014.6944033

14. Song S, Choi H, Collins SH. Using force data to self-pace an instrumented treadmill
and measure self-selected walking speed. bioRxiv. 2019. p. 2019.12.18.870592.
doi:10.1101/2019.12.18.870592

15. O'Connor SM, Donelan JM. Fast visual prediction and slow optimization of
preferred walking speed. J Neurophysiol. 2012;107: 2549–2559.
doi:10.1152/jn.00866.2011

16. Farrens AJ, Lilley M, Sergi F. A Controlled Slip: Training Propulsion via
Acceleration of the Trailing Limb. bioRxiv. 2020. p. 2020.03.27.012591.
doi:10.1101/2020.03.27.012591

17. Feasel J, Whitton MC, Kassler L, Brooks FP, Lewek MD. The integrated virtual
environment rehabilitation treadmill system. IEEE Trans Neural Syst Rehabil Eng.
2011;19: 290–297. doi:10.1109/TNSRE.2011.2120623

18. Kim J, Stanley CJ, Curatalo LA, Park H. A user-driven treadmill control scheme for
simulating overground locomotion. 2012 Annual International Conference of the
IEEE Engineering in Medicine and Biology Society. 2012. pp. 3061–3064.
doi:10.1109/EMBC.2012.6346610

19. Yoon J, Park H-S, Damiano DL. A novel walking speed estimation scheme and its
application to treadmill control for gait rehabilitation. J Neuroeng Rehabil. 2012;9:
62. doi:10.1186/1743-0003-9-62

20. O'Connor SM, Kuo AD. Direction-dependent control of balance during walking and
standing. J Neurophysiol. 2009;102: 1411–1419. doi:10.1152/jn.00131.2009

21. Grieve DW, Gear RJ. The relationships between length of stride, step frequency,
time of swing and speed of walking for children and adults. Ergonomics. 1966;9:
379–399. doi:10.1080/00140136608964399

22. Terrier P, Turner V, Schutz Y. GPS analysis of human locomotion: further evidence
for long-range correlations in stride-to-stride fluctuations of gait parameters. Hum
Mov Sci. 2005;24: 97–115. doi:10.1016/j.humov.2005.03.002

23. Hausdorff JM, Peng CK, Ladin Z, Wei JY, Goldberger AL. Is walking a random
walk? Evidence for long-range correlations in stride interval of human gait. J Appl
Physiol. 1995;78: 349–358. doi:10.1152/jappl.1995.78.1.349

24. Riley PO, Paolini G, Della Croce U, Paylo KW, Kerrigan DC. A kinematic and
kinetic comparison of overground and treadmill walking in healthy subjects. Gait
Posture. 2007;26: 17–24. doi:10.1016/j.gaitpost.2006.07.003

25. Collins SH, Kuo AD. Two independent contributions to step variability during over-
ground human walking. PLoS One. 2013;8: e73597.
doi:10.1371/journal.pone.0073597

26. Dingwell JB, Bohnsack-McLagan NK, Cusumano JP. Humans control stride-to-
stride stepping movements differently for walking and running, independent of
speed. J Biomech. 2018;76: 144–151. doi:10.1016/j.jbiomech.2018.05.034

27. Ojeda LV, Rebula JR, Kuo AD, Adamczyk PG. Influence of contextual task
constraints on preferred stride parameters and their variabilities during human
walking. Med Eng Phys. 2015;37: 929–936. doi:10.1016/j.medengphy.2015.06.010

28. Choi J-S, Kang D-W, Seo J-W, Tack G-R. Reliability of the walking speed and gait
dynamics variables while walking on a feedback-controlled treadmill. J Biomech.
2015;48: 1336–1339. doi:10.1016/j.jbiomech.2015.02.047

29. Wiens C, Denton W, Schieber MN, Hartley R, Marmelat V, Myers SA, et al. Walking
speed and spatiotemporal step mean measures are reliable during feedback-
controlled treadmill walking; however, spatiotemporal step variability is not reliable.
J Biomech. 2019;83: 221–226. doi:10.1016/j.jbiomech.2018.11.051

30. Zeni JA Jr, Richards JG, Higginson JS. Two simple methods for determining gait
events during treadmill and overground walking using kinematic data. Gait Posture.
2008;27: 710–714. doi:10.1016/j.gaitpost.2007.07.007

31. Dingwell JB, Cusumano JP, Cavanagh PR, Sternad D. Local Dynamic Stability
Versus Kinematic Variability of Continuous Overground and Treadmill Walking. J
Biomech Eng. 2001;123: 27–32. doi:10.1115/1.1336798

32. Dingwell JB, John J, Cusumano JP. Do humans optimally exploit redundancy to
control step variability in walking? PLoS Comput Biol. 2010;6: e1000856.
doi:10.1371/journal.pcbi.1000856

33. Hausdorff JM, Edelberg HK, Mitchell SL, Goldberger AL, Wei JY. Increased gait
unsteadiness in community-dwelling elderly fallers. Arch Phys Med Rehabil.
1997;78: 278–283. Available: https://www.ncbi.nlm.nih.gov/pubmed/9084350

34. O'Connor SM, Xu HZ, Kuo AD. Energetic cost of walking with increased step
variability. Gait Posture. 2012;36: 102–107. doi:10.1016/j.gaitpost.2012.01.014

35. Qian Y, Yang K, Zhu Y, Wang W, Wan C. Local Dynamic Stability of Self-paced
Treadmill Walking Versus Fixed-speed Treadmill Walking. J Biomech Eng. 2019.
doi:10.1115/1.4045595

36. Menant JC, Steele JR, Menz HB, Munro BJ, Lord SR. Effects of walking surfaces
and footwear on temporo-spatial gait parameters in young and older people. Gait
Posture. 2009;29: 392–397. doi:10.1016/j.gaitpost.2008.10.057

37. Huijben B, van Schooten KS, van Dieën JH, Pijnappels M. The effect of walking
speed on quality of gait in older adults. Gait Posture. 2018;65: 112–116.
doi:10.1016/j.gaitpost.2018.07.004

38. Mak TCT, Young WR, Chan DCL, Wong TWL. Gait Stability in Older Adults During
Level-Ground Walking: The Attentional Focus Approach. J Gerontol B Psychol Sci
Soc Sci. 2020;75: 274–281. doi:10.1093/geronb/gby115

39. Hausdorff JM. Gait dynamics, fractals and falls: finding meaning in the stride-to-
stride fluctuations of human walking. Hum Mov Sci. 2007;26: 555–589.
doi:10.1016/j.humov.2007.05.003

40. Bohnsack-McLagan NK, Cusumano JP, Dingwell JB. Adaptability of stride-to-stride
control of stepping movements in human walking. J Biomech. 2016;49: 229–237.
doi:10.1016/j.jbiomech.2015.12.010

41. Hunter LC, Hendrix EC, Dean JC. The cost of walking downhill: is the preferred gait
energetically optimal? J Biomech. 2010;43: 1910–1915.
doi:10.1016/j.jbiomech.2010.03.030

42. Beauchet O, Annweiler C, Lecordroch Y, Allali G, Dubost V, Herrmann FR, et al.
Walking speed-related changes in stride time variability: effects of decreased
speed. J Neuroeng Rehabil. 2009;6: 32. doi:10.1186/1743-0003-6-32

43. Jeffers JR, Auyang AG, Grabowski AM. The correlation between metabolic and
individual leg mechanical power during walking at different slopes and velocities. J
Biomech. 2015;48: 2919–2924. doi:10.1016/j.jbiomech.2015.04.023

self-pace controller concept

$$\ddot{x} = g(P\Delta x - \Delta x D x)$$

$g = 1.5$ *(high)*
$g = 1.0$ *(medium)*
$g = 0.5$ *(low)*

belts slow down

set point, maintain speed

belts speed up