VeloViz: RNA-velocity informed 2D embeddings for visualizing cellular trajectories

Lyla Atta[1,2,3], Jean Fan[1,2,4*]

[1]Department of Biomedical Engineering, Johns Hopkins University, Baltimore, MD 21218, USA

[2]Center for Computational Biology, Whiting School of Engineering, Johns Hopkins University,

Baltimore, MD 21211, USA

[3]Medical Scientist Training Program, Johns Hopkins University School of Medicine, Baltimore, MD

21205, USA

[4]Department of Computer Science, Johns Hopkins University, Baltimore MD 21218, USA

[*]To whom correspondence should be addressed

Correspondence should be addressed to: Jean Fan (jeanfan@jhu.edu)

Word count: 999

Figure count: 1

Table count: 0

0 Abstract

RNA velocity analysis can predict cell state changes from single cell transcriptomics data. To interpret

these cell state changes as part of underlying cellular trajectories, current approaches rely on visualization

with 2D embeddings derived from principal components, t-distributed stochastic neighbor embedding,

among others. However, these 2D embeddings can yield different representations of the underlying

trajectories, hindering the interpretation of cell state changes. To address this challenge, we developed

VeloViz to create RNA-velocity-informed 2D embeddings. We show that by taking into consideration the

predicted future transcriptional states from RNA velocity analysis, VeloViz can help ensure a more

reliable representation of underlying cellular trajectories. VeloViz is available as an R package at

https://github.com/JEFworks-Lab/veloviz.

1 Introduction

Single cell transcriptomics provide a static snapshot of transcriptional states for individual cells. The

continuum of transcriptional states for cells along dynamic processes can be used to infer how cell states

may change over time (Tritschler *et al.*, 2019; Saelens *et al.*, 2019). Notably, RNA velocity analysis can

be applied to infer dynamics of gene expression and predict the future transcriptional state of a cell from

single cell RNA-sequencing and imaging data (La Manno *et al.*, 2018; Xia *et al.*, 2019).

To interpret cell state changes from RNA velocity analysis, current approaches project the observed

current and predicted future transcriptional states onto 2-dimensional (2D) embeddings to visualize the

putative directed cellular trajectory (La Manno *et al.*, 2018; Zywitza *et al.*, 2018; Bastidas-Ponce *et al.*,

2019; Zhang *et al.*, 2019). Previously used 2D embeddings include those derived from principal

components (PC), t-distributed Stochastic Neighbor Embeddings (t-SNE), Uniform Manifold

Approximation and Projection (UMAP), or diffusion maps (Coifman *et al.*, 2005; Maaten and Hinton,

2008; McInnes *et al.*, 2018). However, these approaches can yield different representations of the

underlying trajectory. Furthermore, when intermediate cell states are not well represented, current 2D

embeddings may not capture global relationships between cell subpopulations, thereby further hindering

the interpretation of cell state changes (Kester and Oudenaarden, 2018; Weinreb *et al.*, 2018).

Here, we developed VeloViz to visualize cellular trajectories by incorporating information from RNA

velocity analysis. By taking into consideration cells' predicted future transcriptional states inferred from

RNA velocity analysis, VeloViz can help ensure that relationships between cell states are reflected in the

2D embedding, allowing for more reliable representation of underlying cellular trajectories.

<u>2 Method</u>

In order to create an RNA-velocity-informed 2D embedding, VeloViz uses each cell's current observed

and predicted future transcriptional states inferred from RNA velocity analysis to build a nearest neighbor

graph between cells in the population (Figure 1A). Briefly, VeloViz computes a cell-cell composite

distance between all cell pairs in the population (Fig 1A, Supplementary Information 1ii) and assigns

graph edges to the k neighboring cells with the smallest composite distances. Edges are then pruned based

on similarity thresholds (Supplementary Information 1iii). The resulting graph can be visualized as a 2D

embedding using force-directed layout algorithms (Fruchterman and Reingold, 1991).

<u>3 Results</u>

3.1 Comparing VeloViz to other embeddings

To evaluate the performance of VeloViz, we first assessed VeloViz's ability to capture trajectories of simulated data representing cycling or branching trajectories (Supplementary Information 2i) and compared to PC, t-SNE, UMAP, and diffusion map embeddings. We calculated a trajectory consistency (TC) score (Supplementary Information 2ii., (Boggust et al., 2019)) where TC scores closer to 1 indicate more accurate representations of the ground truth trajectory. Among evaluated trajectories, VeloViz embeddings had consistently high TC scores (Supplementary Figure 1). Next, we used VeloViz to visualize pancreatic endocrinogenesis single-cell RNA-sequencing (scRNA-seq) data, where cycling ductal cells give rise to endocrine progenitor-precursor (EP) cells, which then differentiate into hormone producing endocrine cell types (Alpha, Beta, Delta, and Epsilon cells) (Bastidas-Ponce *et al.*, 2019). We observed that while all evaluated embeddings captured the trajectory of endocrine progenitors, VeloViz was better able to capture the cycling structure of ductal cells (Supplementary Figure 2). VeloViz, UMAP, and tSNE also captured the terminal branching differentiation into the different endocrine cell types, which is not clear in PC or diffusion map. Overall, VeloViz is able to capture trajectories of diverse topologies.

3.2 Performance with incomplete trajectories

To evaluate the performance of VeloViz in visualizing trajectories with missing intermediate cell states, we used simulated and real scRNA-seq data where some intermediate cells were removed, creating a trajectory gap. Because t-SNE and UMAP preferentially preserve local cell-cell relationships, we expected that these embeddings would result in two distinct clusters of cells before and after the simulated gap (Kobak and Berens, 2019; Heiser and Lau, 2020). Therefore, in addition to TC scores, we calculated a gap distance (Supplementary Information 2iii), which measures the distance in the 2D embedding space between cells before and after the simulated gap in the trajectory. Embeddings that preserve the underlying trajectory despite this simulated gap will have a smaller gap distance. Indeed, for the cycling trajectory

where cells corresponding to a segment of the cycle were removed, VeloViz was the only embedding able

to preserve the cycling structure. Likewise, for branching trajectories with missing intermediates, only

VeloViz and PCA were able to preserve the underlying topology while tSNE and UMAP split cells before

and after the simulated gap into distinct clusters as expected (Supplementary Figure 3). TC scores were

consistently higher and the gap distance smaller for VeloViz than with t-SNE, UMAP, and diffusion map.

Likewise, for the pancreatic endocrinogenesis scRNA-seq data, we removed pre-endocrine cells and used

cell latent time (Bergen et al., 2020) to identify cells before and after pre-endocrine cells in the

developmental trajectory and to calculate gap distances (Supplementary Information 2iii). Notably, the

transition from endocrine progenitors into terminal endocrine cell types was best captured by VeloViz. As

expected, t-SNE and UMAP split ductal and endocrine progenitor cells from terminal endocrine cell types,

which is reflected in the gap distances (Figure 1B-F). Overall, VeloViz is able to visualize a more reliable

presentation of underlying trajectories even when intermediate cell states are missing.

Funding: This work was supported by the National Institutes of Health [T32GM136577 to L.A.]

Conflict of Interest: none declared.

References

Bastidas-Ponce,A. *et al.* (2019) Comprehensive single cell mRNA profiling reveals a detailed roadmap for pancreatic endocrinogenesis. *Development*, **146**.

Bergen,V. *et al.* (2020) Generalizing RNA velocity to transient cell states through dynamical modeling. *Nat. Biotechnol.*, 1–7.

Coifman,R.R. *et al.* (2005) Geometric diffusions as a tool for harmonic analysis and structure definition of data: Diffusion maps. *Proc. Natl. Acad. Sci.*, **102**, 7426–7431.

Fruchterman,T.M.J. and Reingold,E.M. (1991) Graph drawing by force-directed placement. *Softw. Pract. Exp.*, **21**, 1129–1164.

Kester,L. and Oudenaarden,A. van (2018) Single-Cell Transcriptomics Meets Lineage Tracing. *Cell Stem Cell*, **23**, 166–179.

La Manno,G. *et al.* (2018) RNA velocity of single cells. *Nature*, **560**, 494–498.

Maaten,L. van der and Hinton,G. (2008) Visualizing Data using t-SNE. *J. Mach. Learn. Res.*, **9**, 2579–2605.

McInnes,L. *et al.* (2018) UMAP: Uniform Manifold Approximation and Projection. *J. Open Source Softw.*, **3**, 861.

Saelens,W. *et al.* (2019) A comparison of single-cell trajectory inference methods. *Nat. Biotechnol.*, **37**, 547–554.

Tritschler,S. *et al.* (2019) Concepts and limitations for learning developmental trajectories from single cell genomics. *Development*, **146**.

Weinreb,C. *et al.* (2018) Fundamental limits on dynamic inference from single-cell snapshots. *Proc. Natl. Acad. Sci.*, **115**, E2467–E2476.

Xia,C. *et al.* (2019) Spatial transcriptome profiling by MERFISH reveals subcellular RNA compartmentalization and cell cycle-dependent gene expression. *Proc. Natl. Acad. Sci.*, **116**, 19490–19499.

Zhang,Q. *et al.* (2019) Landscape and Dynamics of Single Immune Cells in Hepatocellular Carcinoma. *Cell*, **179**, 829-845.e20.

Zywitza,V. *et al.* (2018) Single-Cell Transcriptomics Characterizes Cell Types in the Subventricular Zone and Uncovers Molecular Defects Impairing Adult Neurogenesis. *Cell Rep.*, **25**, 2457-2469.e8.

Figures

Figure 1. VeloViz constructs RNA-velocity-informed 2D embeddings. **A)** Workflow to create a VeloViz 2D embedding: 1) Observed current (X_c) and predicted future (X_p) transcriptional cell states inferred from RNA velocity are reduced into a common PC space; 2) composite distances (D) between all cell pairs are computed. Composite distance from Cell A to Cell X ($D_{A \to X}$) takes into account the similarity in transcriptional profiles (d_{AX}) between Cell X's observed current (X_c) and Cell A's predicted future transcriptional state (A_p), and the cosine correlation between Cell A's RNA-velocity (v_A) and the change vector (t_{AX}) representing a transition from Cell A's current state (A_c) to Cell X's current state (X_c). A distance weight (ω) is used to adjust the relative importance of transcriptional similarity and cosine

correlation in the composite distance; 3) for each cell, graph edges are assigned to the k cells with the

minimum composite distances to create a graph. Edge weights are computed based on composite distances

as *weight$_{AB}$ = max(D) – D$_{AB}$*; 4) edges assigned in 3. are removed (in grey, dashed) if they are above the

similarity and/or distance thresholds. Edge shade corresponds to edge weight computed based on

composite distance, with darker arrows representing edges with larger weights; 5) the resulting graph is

visualized as a 2D embedding using a force-directed graph layout. **B)** VeloViz 2D embedding visualizing

pancreatic endocrinogenesis with pre-endocrine intermediates removed creating a gap in the

developmental trajectory. Inset shows the VeloViz embedding of the full dataset. Cells are colored by cell

state annotations provided in (Bergen *et al.*, 2020). Arrows show the projection of velocities derived from

dynamical velocity modelling onto the VeloViz embeddings. Gap distances measure the median distance

in the 2D embedding between the 300 cells before and after pre-endocrine cells in the developmental

trajectory (Supplementary Information 2iii). White circle and square indicate the median coordinates of

cells before and after pre-endocrine cells in the developmental trajectory, respectively. **C-F)** 2D

embeddings visualizing pancreatic endocrinogenesis with removed pre-endocrine intermediates using

PCA, t-SNE, UMAP, and diffusion mapping, respectively with arrows showing the projection of velocities

derived from dynamical velocity modelling.